

INDEX

- a posteriori, 257, 277–8, 297, 379
- a priori, 75, 120, 253, 257, 277, 297, 379
- acceleration, 19–20
 - gravitational, 20, 28, 30, 33, 61, 231, 344, 348–9, 372
 - sensed, 20, 28, 325
- accelerometer, 20, 320
 - calibration, 25, 339
 - electromagnetic, 325–6
 - gyroscopic, 322–324
 - MEMS, 331
 - pendulous, 325
 - proof mass, 320–2
- accumulated delta range, 203
- A/D, xxi, 338
- adaptive Kalman filter, 288
- ADC, xxi, 114, 134
 - SNR, xxvii, 114, 143
- ADR, xxi, 203
- ADS, xxi, 16
- AGC, xxi, 114
- Age of data word, ephemeris, 60
- AHRS, xxi, 25
- AIC, xxi, 148
- Air Traffic Control, 16
- AIRS, xxi, 26
- Akaike information-theoretic criterion, 148
- ALF, xxi, 333–4
- alignment, 22–3, 50, 55, 59–62
 - code, 74–84
 - gimbal, 29, 346
 - gyrocompass, 31–2, 345–6
 - INS, 344–7
 - optical, 344
 - sensor, 344
 - time, 133
 - transfer, 345
- ALS, xxi, 383
- altBOC, xxi, 6–7
- altimeter, 29, 33, 129, 343, 378
- altitude
 - damping, 377
 - instability, 29, 33, 369, 372
 - Schuler time constant, 372
 - sensors, 343
 - stabilization, 377
- angle random walk, 328, 330
 - anomaly, 62
- Anschutz-Kaempfe, H., 317
- antenna
 - adaptive, 139–41
 - beamforming, 140
 - calibration, 142
 - design, 135
 - gain, 73
 - location, 21, 385

- anti-spoofing, 197
 - AODE, xxi, 60
 - AOR-E, xxi, 10, 15
 - AOR-W, xxi, 10, 15
 - argmax, 258–265
 - ARMA, xxi, 147
 - A-S, xxi, 197
 - ascending node, 35, 60–1
 - ASD, xxi, 283
 - ASIC, xxi, 331
 - ASQF, xxi, 204
 - ATC, xxi, 16
 - atmospheric loss factor, 333–4
 - atomic clock, 2
 - cesium, 213, 244
 - errors, 186
 - rubidium, 186
 - steering, 213, 223
 - attitude and heading reference system, 25
 - augmentation
 - ground-based, 7, 12, 205
 - differential, 2, 7, 199
 - JPALS, 205
 - LAAS, 205
 - LADGPS, 7, 199
 - LORAN-C, 206
 - space-based, 8
 - CWAAS, 12
 - EGNOS, 10
 - GAGAN, 12
 - MSAS, 11
 - SNAS, 15
 - WAAS, 9
 - state vector, 283
 - autocorrelation, 66, 312
 - Selective Availability, 281
 - autocovariance, 66, 279, 312
 - Automatic Dependent Surveillance, 16
 - automatic gain control, 114
 - Autonomous Landing System, 335–383
 - Autonetics, 25, 333
 - autoregressive moving average, 147
 - bias
 - clock
 - receiver, 39, 187, 202, 226, 244
 - satellite, 216
 - intercard, 244, 250
 - L1/L2, 156, 162, 220, 242, 244–5, 248, 250
 - L1/L5, 223
 - multipath, 185
 - sensor, 335, 337, 420
 - binary offset carrier, 7, 102
 - alternate, 6–7
 - binary phase shift keying, 3
 - Black, H., 323
 - BOC, xxi, 7, 102
 - Bortz, J. E., 360
 - Bortz rate vector, 361, 422, 428
 - BPSK, xxi, 3
 - Brown, R., 268
 - C/A code, xxii, 3, 65
 - C/Nav, 6–7
 - C&V, xxii, 201–2
 - calibration, 339
 - accelerometer, 25, 335
 - antenna, 142
 - gyroscope, 27, 335
 - frequency, 129
 - ISA, 25, 338
 - models, 335
 - parameters, 340
 - instability, 341
 - uncertainty, 340–342
 - processing, 339
 - self-, 25–6
 - carouseling, 26, 428
 - angle, 375
 - gimbaled, 26, 375, 380
 - strapdown, 27, 375
 - carrier frequency, 2, 152
 - adjustments, 208
 - code coherence, 211
 - command, 202, 216
 - control, 207, 222, 227
 - stability, 212
 - translation errors, 218
- carrier phase, 91
- CDM, xxii, 65, 70
- CDMA, xxii, 65
- celestial navigation, 1, 18
- CEP, xxii, 33
- error model, 410–1
- rate, 33, 409–11
- circular error probable, xxii, 33
- clear code, 3
- clock bias
 - receiver, 39, 187, 202, 226, 244
 - satellite, 216
- clock steering, 202, 213, 223
 - algorithm
 - backup, 215, 229
 - new, 223
 - primary, 214, 228
 - control law, 227
 - GUS, 213, 223
- CMD, xxii, 202

- CNMP, xxii, 250
- coarse acquisition code, 3
- code
 - clear, 3
 - coarse acquisition, 3
 - control, 222
 - code-carrier coherence, 207–11
 - control, 212, 220
- code division multiplexing, 65, 70
- code division multiple access, 65
- Commercial Service, xxii, 5–6
- computer requirements, 363–4
- COMSAT, 14
- coning motion, 358–360
 - correction, 357, 360–362
- Continuously Operating Reference Station, 194
- CONUS, xxii
- coordinates, App. C (on CD)
 - geodetic, 347
 - inertial, 14, 347
 - locally level, xxv, 14, 347
 - LTP, 347
 - navigation, 14, 347
- Coriolis, G. G. de, 326
- Coriolis effect, 28–9, 326
 - coupling, 372
 - gyroscopes
 - rotating, 326
 - vibrating, xxvii, 329
- correlation
 - code, 76
 - cross, 66, 82, 95, 102, 106, 133, 166
 - losses, 134
 - number, 280
 - spatial, 164, 366
 - time, 280–4
- CORS, xxii, 194
- COSPAS-SARSAT, xxii, 6
- Costas loop, 84–8
- covariance analysis, 230, 296, 311
- CRC, xxi, 106
- cruise applications (INS), 25
- CS, xxii, 5
- CWAAS, xxii, 12
- cyclic redundancy check, 106

- dead reckoning, 1
- dead zone, 329, 338
- DFT, xviii, 107
- DGNSS, xxii, 1
- DGPS, xxii, 7, 121, 188, 199
- differential GNSS, 1
- differential GPS, 7, 121, 188, 199
- dilution of information, 389
- dilution of precision, 39, 43
 - geometric, 42–4
 - horizontal, 41–4, 294
 - time, 41–4, 294
 - vertical, 41–4
- discrete Fourier transform, 149
- distribution matrix
 - dynamic noise, 269, 275, 283
 - sensor noise, 264
- DME, xxii, 256
- DOD, xxii, 144
- DOP, xxii, 39, 43
- DOT, 9
- dynamic disturbance noise, 269
 - correlated, 283
 - covariance, 156, 276–7
 - distribution matrix, 269, 275, 283

- E2-L1-E1 band, 7
- E5a, E5b bands, 6
- E6 band, 7
- EC, 5, 10, 15
- eccentric anomaly, 62
- ECEF coordinates, xxii, App. C
- ECI coordinates, xxii, App. C
- EGNOS, xxii, 10, 203
 - Wide Area Network, 11, 204
- Einstein, A., 317
- EIRP, xxii, 72
- electromagnetic accelerometer, 325
- electromagnetic interference, 363
- EMA, xxii, 325
- EMI, 363
- EMRBE, 233
- ENU coordinates, xxiii, 346, 348, App. C
- error budget, 408
- ESA, xxiii, 5, 10, 15
- ESG, xxiii, 318–9
- ESGN, xxiii, 25, 318
- EU, xxiii, 5
- European Commission, 5, 10, 15
- European Space Agency, xxiii, 5, 10, 15
- EWAN, xxiii, 11, 204
- exponentially correlated noise, 280
- extended Kalman filter, 287

- F/Nav, 6
- FAA, xxiii, 8–9, 101, 161, 334
- Fault Free Case, 240, 247–52
- Faulted Case, 240, 247–52
- FEC, xxiii, 106, 206
- feedback control, 323
 - of gimbals, 323
 - negative, 323

- fiberoptic gyroscope, 329
- FIG8 tracking model, 399
- filter
 - Kalman, 255–313
 - adaptive, 288
 - extended, 287
 - linearized, 286
 - Kalman-Bucy, 290
 - shaping, 282
 - SK (Schmidt-Kalman), 302
 - square root, 305
 - tracking, 388ff
 - Wiener, 290
- FIR, 11
- FLL, xxiii, 87, 116–7
- FM, xxiii, 17
- F/Nav, 6
- FOG, xxiii, 329
- force
 - coriolis, 326
 - specific, 20, 28, 325
- Forward Error Correction, 106, 206
- Foucault, J. B. L., 317
- Fourier transform, 312
 - discrete, 149
 - fast, 141
 - inverse, 402
- FPE, xxiii, 48
- free inertial navigation, 32, 367
- free space loss factor, 72
- Frequency Lock Loop, 87, 116–7
- FSLF, xxiii, 72
- FVS, 201

- g (gravity), 323
- GAGAN, xxiii, 8–9, 12, 205
- Galileo, 5
 - C/Nav, 7
 - Commercial Service, 5–7
 - E2-L1-E1 band, 6
 - E5a, E5b bands, 6–7
 - E6 band, 5
 - F/Nav, 6
 - G/Nav, 7
 - I/Nav, 7
 - Navigation Services, 5–7
 - Open Service, 5, 7
 - Public Regulated Service, 6
 - Safety of Life Service, 5
 - satellite signals, 5–6
 - Search and Rescue, 6
 - Signal Task Force, 5
- gaussian
 - distribution, 259
 - likelihood, 260
 - maximum likelihood, 265
 - noise, 273
- GBAS, xxiii, 12, 205, 236, 254
 - JPALS, 12, 205
 - LAAS, 12, 205
- GBI, 16
- GCCS, xxiii, 217
- GDOP, xxiii, 42–44
- geometric dilution of precision, 42–44
- GEO, xxiii, 12, 206, 217, 228, 243
- GEO Uplink Subsystem, 206
- GES, xxiii, 208–9
- GIC, xxiii, 254
- gimbal, 24
 - carouseling, 26
 - feedback control, 28–9, 324, 356
 - flipping, 27
 - indexing, 27
 - lock, 24
- GIPSY, xxiii, 157, 161, 195
- GIS, xxiii, 16, 155, 194
- GIVE, xxiii, 202, 229, 247
- GLONASS, xxiii, 4, 238
 - orbits, 4
 - satellite signals, 4
- GNSS
 - antenna location, 15, 385
 - differential, 199
 - error models, 404
 - host vehicle, 21, 387
 - dynamic models, 383
 - INS integration, 1, 334, 382
 - jamming, 120, 139–41
 - models, 404–7
 - receiver, 382
 - tracking, 390
 - GNSS/INS integration, 1, 334, 382–423
 - loosely coupled, 365, 384–6
 - models
 - GNSS, 404–7
 - INS, 408–10
 - tightly coupled, 365, 384–6, 413–23
 - ultimately tightly coupled, 385
- GOA, xxiii, 150, 195
- Goddard, R. H., 324
- GPS, xxiii, 2, 135
 - antenna location, 21
 - augmented, 7
 - differential, 188
 - indoor, 129
 - modernization, 98
 - orbits, 2
 - Precise Positioning Service, 4

- Signals, 54, 104
- Standard Positioning Service, 4
- time, 44
- GPS/INS integration, 1, 334, 382–423
- GPS/INS Toolbox, xxiii, 370, 425
- gravitational
 - acceleration, 20, 28, 30, 33, 61, 231, 344, 348–9, 372
 - field, 20
 - model, 30–1, 335, 348, 366
 - pendulum, 320, 368–9
 - potential, 349
- grid ionosphere vertical error, 202, 229, 247
- Ground Based Augmentation System, 12, 205, 236, 254
- guidance, 21
- GUS, xxiii, 206
 - clock steering, 213, 223
- GUST, xxiii, 220
- gyrocompass, 317
 - alignment, 31–32, 345, 391–393
- near poles, 32
- gyroscope, 20
 - calibration, 339
 - coriolis
 - rotational, 326–8, 331
 - vibratory, 329, 331
 - displacement, 20
 - dry-tuned, 318
 - electrostatic, 318–9
 - fiberoptic, 329
 - Foucault, 317
 - gas bearing, 318
 - hemispherical resonator, 330
 - input axis, 20
 - MEMS, 331
 - momentum wheel, 316
 - rate, 20
 - ring laser, 328
 - torque feedback, 324
 - tuning fork, 330
 - whole-angle, 20
 - wine glass, 330
 - zero lock, 329
- gyroscopic accelerometer, 322–3

- Handover Word, 56, 100
- Hazardously Misleading Information, 238, 247
- HDOP, xxiii, 41–44, 294
 - heading errors (INS), 366
 - hemispherical resonator gyroscope, 330
- history, 317
- HMI, xxiii, 238, 247
- horizontal dilution of precision, 41–44, 294

- host vehicle, 21
 - dynamics, 387–403
 - tracking filters, 388–403
 - trajectories, 383
- HOW, xxiii, 56, 100
- HRG, xxiv, 330

- I/Nav, 7
- ICAO, xxiv, 11, 239
- ICC, xxiv, 155, 202
- IDV, 202–3
- IF, xxiv, 85, 112
- IFOG, xxiv, 329
- IGP, xxiv, 159, 201
- ILS, xxiv, 9, 12–3
- IMU, xxiv, 20
- in-orbit test, 208–9, 212
- indexing, 27, 380
- inertia, 19
- inertial measurement unit, 20
- inertial navigation, 1, 19
- inertial navigation system, 20–1, 316
- inertial platform, 22
- inertial reference frame, 19
- inertial reference unit, 20
- inertial sensor, 20
 - accelerometer, 20
 - gyroscope, 20
 - input axis, 20
 - multi-axis, 20
- inertial sensor assembly, 20–6
- information matrix, 260
- Inmarsat, xxiv, 14
 - satellite overlay, 14
- input axis, 20
- INS, xxiv, 20–1, 316
 - accuracy
 - high, 33
 - low, 34
 - medium, 34
 - alignment, 29
 - heading, 366
 - leveling errors, 28–9, 365
 - tilt, 366
- altitude instability, 29, 33, 369, 372
 - Schuler period, 372
 - stabilization, 377
- carouseled, 26, 428
 - floated, 26
 - gimballed, 24
 - strapdown, 22, 375
- CEP rate, 33, 409–11
- coriolis coupling, 372–3
- cruise applications, 25

- INS (*contd.*)
- floate d, 22–3, 26
 - advantages, 26
 - disadvantages, 26
 - free inertial operation, 32, 367
 - gimbale d, 22, 24
 - advantages, 25
 - disadvantages, 26
 - gimbal flipping, 27
 - gimbal lock, 24
 - heading errors, 366
 - host vehicle, 21
 - indexing, 27, 380
 - performance, 33–4
 - standalone, 33
 - self-calibration, 25–6
 - signal processing, 28–9
 - strapdown, 27
 - advantages, 27
 - carouseling, 27
 - disadvantages, 27
 - tilt errors, 366–71
 - user interface, 20
 - vertical channel, 29, 33, 369, 372
 - Schuler period, 372
 - vestibular system, 21
 - vibration isolators, 22
- instrument cluster, 20
- integration
 - GNSS/INS, 1, 382
 - sensor, 382
- integrity threats, 247
- intercard bias, 244
- interfrequency bias, 155, 162
- International Terrestrial Reference Frame, 195
- IODC, xxiv, 58
- IODE, xxiv, 59, 60
- ionospheric correction, 155, 202
- ionospheric delay, 71, 156
 - calculation using L1 L2, 156, 221
- IOT, xxiv, 208–9, 212
- IRU, xxiv, 20
- ISA, xxiv, 20–6
 - alignment, 31
 - antenna offset, 21, 385
 - calibration, 338
- Issue Of Data
 - clock, 58
 - ephemeris, 59, 60
- ITRF, xxiv, 195
- jamming, 6, 65, 70, 100, 120, 137–41
- JPALS, xxiv, 12–3, 205
- JTIDS, xxiv, 19
- Kalman filter, 1, 255, 313
 - adaptive, 288
 - correction step, 257
 - equations, 277
 - extended, 287
 - linearized, 286
 - measurement update, 257
 - observational update, 257
 - prediction step, 268, 276
 - temporal update, 257
- Kalman gain, 257–268
- Kepler problem, 62
- Kepler’s equation, 63
- LAAS, xxiv, 12–3, 144, 205
- LADGPS, xxiv, 199
- Langevin, P., 268, 394
- Laplace distribution, 259
- LD, xxiv, 18
- leap second, 44–45
- Leibnitz, G., 268
- LEM, xxv, 333
- leveling errors (INS), 367
- LHCP, xxv, 137, 139
- likelihood function, 260
 - gaussian, 259–60
- linearized Kalman filter, 286
- Local Area Augmentation System, 12–3, 144, 205
- Local Area Differential GPS, 199
- locally level coordinates, 31, 347–8
- lockin, 329, 338
- LORAN, xxv, 12, 14, 18, 129, 206
- LOS, xxv, 226
- LPV, xxv, 239
- LSB, xxv, 324, 338
- LTP coordinates, xxv, 347
- matrix, App. B
- maximum likelihood, 95, 133, 260
- maximum likelihood estimation, 171, 255, 265
 - gaussian, 265
 - multipath, 173
- MCC, xxv, 11, 203
- mean anomaly, 62
- measurement noise, 264
- measurement update, 257, 277
 - serial, 305
- MEDLL, xxv, 171
- MEMS, xxv, 331
 - accelerometer, 331
- Minimum Mean Squared Estimator, 132
- mitigation
 - integrity threats, 241, 247

- Precision Approach, 200
- precision landing, 9, 12
- PRN, xxvi, 3, 59, 64, 154
- process noise, 269
- proof mass, 320–2
- propagation delay, 3, 92, 151–64
 - ionospheric, 151–63
 - tropospheric, 163–4
- PRS, xxvi, 6
- PSD, xxvi, 405–6
- pseudorandom noise, 117, 190
- pseudorange, 150–1, 211–2
- Public Regulated Service, 6
- pure inertial navigation, 33, 369

- quasirigid (IMU mounting), 22

- radio navigation, 1
- RAG, xxvi, 73
- rail integrity, 239
- RAIM, xxvi, 236
- random walk, 187, 336
- Raytheon, 225
- real-time operating system, 364
- RF, xxvi, 59, 113
- Riccati, J. F., 290
- Riccati equation, 278–9, 290
 - instability, 279
- right ascension, 35
- RIMS, xxvi, 10–1, 203
- RINEX, xxvi, 195
- ring laser gyroscope, 328–9
- RLG, xxvi, 328
- RMA, xxvi, 253
- RMS, xxvi
- rotation rate vector, 28, 326
 - noncommutative, 361
- Rotational Vibratory Coriolis Gyroscope, xxvi, 331
- RPY coordinates, xxvi, 348, App. C
- RTCA, xxvi
- RTCM, xxvi, 123
- RTOS, xxvi, 364
- rubidium clock, 2, 185–6
- RVCG, xxvi, 331

- SA, xxvi, 3, 144, 366
- Safety of Life Service, 5
- Sagnac effect, 328
- SAR, xxvi, 6
- SARP, xxvi, 11
- SARSAT, xxvi, 6
- satellite signals
 - Galileo, 6
 - GLONASS, 4
 - GPS, 2–4
- SAW, xxvii, 112, 326
- SBAS, xxvii, 8, 200, 238, 254
 - CWAAS, 12
 - EGNOS, 10, 203
 - GAGAN, 8, 12, 205
 - MSAS, 204–5, 234–5
 - SNAS, 12, 205
 - WAAS, 200–35
 - worldwide coverage, 147
- SBIRLEO, xxvii, 16
- Schmidt, S. F., 287, 302
- Schmidt-Kalman filter, 302
- Schuler, M., 317
- Schuler
 - pendulum, 317, 367–370
 - period, 317, 369
 - altitude instability, 372
 - frequency, 367, 369
 - oscillation, 367–370
 - tuning, 317
- SCOUT, xxvii, 196
- SCP, xxvii, 202
- Search and Rescue, 6
- Selective Availability, xxvi, 3, 100, 120–1, 144–51, 280, 366
- self-calibration of INS, 25–6
- sensor fusion, 382
- sensor integration, 333, 382, 415
 - sensor noise, 263–4
 - common-mode, 264
 - correlated, 284
 - distribution matrix, 264
- serial measurement update, 305
- servo, 323
- servomechanism, 323
- shaping filter, 282
- shock isolators, 22
- Signal In Space, 200, 209
- Signal Task Force, 5
- simulation
 - GPS performance, 294, 300, 303
 - vehicle dynamics, 402–3
- SIS, xxvii, 200, 209
- SK (Schmidt-Kalman) filter, 302–4
- SM, xxvii, 159–60
- SNAS, xxvii, 12, 205
- SNR, xxvii, 114, 143
- SOL, xxvii, 5, 202
- Space Based Augmentation System, 8, 200, 238, 254
- Space Shuttle, 16
- specific force, 20, 28

- Sperry, E., 317
SPS, xxvii, 4, 144
square root filtering, 307–8, 311, 427
stable element, 20
stable platform, 20
Standard Navigator, 318
Standard Positioning Service, 4, 144
state transition matrix, 274–5
STF, xxvii, 5
stochastic, 268
 calculus, 268
 differential equation, 268–269
 systems, 268
SV, xxvii
 time, 58, 90, 185
SVN, xxvii
- TCS, xxvii, 201
TDOP, xxvii, 41–44, 294
TEC, xxvii, 151, 162
TECU, xxvii, 155, 162
temporal update, 257
tilt errors (INS), 366–71
time dilution of precision, 41–44, 294
Time Of Week, 57–8
time synchronization, 135
Time To First Fix, xxvii, 73, 130, 334
TLM, xxvii, 56–7
TOA, xxvii, 81
total electron count, 151, 162
 units, 155, 162
TOW, xxvii, 57–8
tracking filter, 388–403
transducer, 323
Tripartite Group, 15
true anomaly, 62
TTA, xxvii, 246, 252
TTFF, xxvii, 73, 130
- UDRE, xxvii, 229–30, 233–4, 247
UERE, xxvii, 188–9
Universal Time, Coordinated, 44, 59, 260
URE, xxvii, 59
USAF, xxvii, 318
 Standard Navigator, 318
- User-Equivalent Range Error, xxvii, 188–9
USN, xxvii, 25, 318
UTC, xxvii, 44, 59, 260
UTM, xxvii, 196
- VAL, xxvii, 229
VCG, xxvii, 329
VDOP, xxvii, 41–44
vehicle tracking filters, 388–403
vertical channel (altitude), 33, 343
 instability (INS), 29, 33, 369, 372
 Schuler period, 372
 stabilization, 377–379
vertical dilution of precision, 41–44
vestibular system, 21
VHF, xxviii, 12
vibration isolators, 22
vibratory coriolis gyroscope, xxvi, xxviii,
 329
VOR, xxviii, 256
VRW, xxviii, 378
- WAAS, xxviii, 8–9, 15, 200–35
 network time, 200, 213
WADGPS, xxviii, 3, 200
WGS, xxviii
WGS-84 model, 349–54
Week Number (GPS), 45, 57
white noise, 187, 268
Wide Area Augmentation System, xxviii, 8–9,
 15, 200–25
 network time, 200, 213
Wide Area Differential GPS, 3, 200
Wiener filter, 290
Wiener process, 280
wine glass gyroscope, 330
WMS, xxviii, 9, 201–3
WN, xxviii, 45, 57
WNT, xxviii, 200, 213
WRE, xxviii, 202, 245, 250
WRS, xxviii, 9, 155–61, 203
- Zero Lock Gyroscope, xxviii, 329
ZLG, xxviii, 329