

Subject Index

a

- absolute pressure sensors 300, 309 ff
- absorber layers 488
- absorption 335 ff, 352 f
- AC modulation 530
- accelerometers 140 ff, 160–184
- accuracy
 - analog frontends 526
 - digital-to-analog converters (DACs) 550
 - filters 541
 - fingerprint images 425
 - operational transconductance amplifiers (OTAs) 569
- acetic acid etching 18, 302
- acidity sensors 364
- acoustic devices 193–224
- action potentials 463
- add-on layers 43 ff
- adsorption 335 ff
- Agilent 0.5 μm process 218
- aging 150
- air damping 170
- air discharge 412 ff
- alkaline phosphatase 455
- Allen variance 570
- ALP2LV/MV 72
- aluminum
 - bulk material 97 ff
 - Seebeck coefficients 485
 - thin films 83
- aluminum bridge 233
- aluminum capacitors 247
- aluminum metallization 3 ff, 14 ff, 32 f, 43, 182
 - elastic properties 126
- aluminum-silicon alloy layers 464
- ammonium hydroxide compound etching 20
- amorphous silicon 492
- amperometric sensors 359 ff, 449
- amplifiers 196, 217 f, 227
 - chemical sensors 347, 359
 - pressure sensors 259
 - system integration 513 ff
- analog capacitors 519
- analog devices (ADI) SOI MEMS 146, 183
- analog filters 513 ff, 535 ff
- analog frontend 513, 521 ff
- analog resistors 519
- analog-to-digital converters (ADCs) 513 ff, 523, 544 ff
- analysis quality 451
- anemometers 502 f
- anisotropic etching 8 f, 18 ff, 241
- anisotropy factor 287
- annealing 34, 43
- anodically bonded glass encapsulation 309 ff
- anti-aliasing filters 542
- anti-fraud techniques 440
- antiresonant reflecting optical waveguide (ARROW) 355
- application-oriented tests 563
- architectures *see*: block diagrams
- array
 - four-cantilever 377 ff
 - phased 221
- artificial fingerprints 441
- ASIC technology 517
- Atmel's AT77C103A FingerChip 403
- atmospheric pressure vapor deposition (APCVD) 5
- atomic force microscopy (AFM) 345
- Austria Micro System (AMS) process 215 f
- authentication 397
- auto-zero techniques 522, 534
- automatic fingerprint identification system (AFIS) 395 f, 417 f

- automatic generation of test pattern 563
- Avogadro's number 75
- axisymmetric diaphragms 301
- axisymmetric plates 274

- b**
- back annotation 565
- back-end metallization 10
- bandgap voltages 555 ff
- bandpass filters 535 ff
- bandwidth
 - analog frontends 523
 - filters 541
 - inertial sensors 179
 - operational transconductance amplifiers (OTAs) 569
 - switched capacitor amplifier 513, 535
- base emitter voltage 555 ff
- basicity sensors 364
- batch fabrication, biochemical sensors 449 f
- beam test structures 115 ff
- bending stresses, thin plates 274, 277
- benzocyclobutene (BCB) switch 233
- BEOL accelerometer 169 ff
- Bessel filter 153
- bias stability 144
- BiCMOS technology 2 ff, 72, 234
 - interface circuitry 518, 521
- bifurcation 416, 422
- BioAPI 436
- biochemical sensing systems 378 ff, 447–478
- biocompatible materials 14, 464
- biological entities 338
- biometric capacitive fingerprint sensor systems 391–446
- biometric engine level error rate 426
- biosensor arrays 454 ff
- biquad filters 540 ff
- blank reticle 27
- blister test 114 f
- block diagrams
 - ADI XL150 gyroscope 158
 - ADI XL50 148
 - ADI XL76 152
 - calorimetric sensor 503 f, 570
 - chopper amplifier 535
 - constant current generator 558
 - DEP chip 461
 - dielectrophoretic cell 460
 - digital-to-analog converters 549
 - DMOS transistor 519
 - DNA hybridization 455
 - double check structure 493
 - dual slope ACD 545
 - earphone 210
 - fingerprint sensor 405
 - gas detection system 567
 - gas flow meter 505
 - hotplates 369
 - interdigitated capacitive sensor 373
 - i-Stat system 450
 - microelectrode pixel 467
 - microphone 199
 - neural probe 471
 - operational transconductance amplifiers (OTAs) 569
 - oscillator feedback circuitry 347
 - pixel recording 468
 - pressure sensors 304, 312, 316
 - RF switch 225 ff, 232
 - Sallen-Key filter 540
 - Siemens accelerometer 168
 - Sigma-Delta modulator 373, 547
 - switched capacitor amplifier 531
 - thermal RMS converter 500
 - thermocouple 484
 - transceiver 229
 - Wheatstone bridge 529
- blood gas analysis 454
- Boltzmann constant 91, 143, 198, 486
- boron etch-stop 303 ff
- borophosphosilicate glass (BPSG) 38
- boundary elements simulation (BEM) 28
- breakage test 415
- breakdown, dielectric 453
- bridge bending 100, 122 f
- brittle layers 119
- Brownian noise 143 ff, 152 ff, 170 f, 197 f
- Bubnov–Galerkin variation 273, 276
- buckling 107, 111, 115
 - acoustic devices 202 ff
- buffered oxide etching (BOE) 8
- building blocks 522, 539 ff, 559
- bulge test 100 f
- bulk material properties 83 ff, 267
- bulk micromachining 18 ff, 29, 42
 - pressure sensors 257, 300, 305 ff
- bulk silicon 368
 - accelerometer 181
 - inertial sensors 180 ff
- bus-enabled interfaces 572

- c**
- CAE (1.3 μm) 72
- cage compounds 338

- calibration
 - analog frontends 522
 - building blocks 554 ff
 - interface circuitry 521
 - pressure sensors 257, 259
- calixarenes 338
- calorimetric sensors 353, 502 f
 - gas detection system 570 f
 - switched capacitor amplifier 535
- CAN bus 554
- cantilever based sensors
- cantilevers 13, 19, 56, 90 f
 - biochemical sensors 472 ff
 - chemical sensors 345 ff, 377 ff
 - gas detection system 570 f
- capacitive acoustic devices 196
- capacitive bridges 143, 161, 171
- capacitive chemical sensors 15, 359, 568 f
- capacitive detection mode 151
- capacitive fingerprint sensor
 - systems 391–446
- capacitive forces 73 f
- capacitive MEMS ultrasonic transducers (cMUTs) 217
- capacitive microphones 195
- capacitive pressure sensors 257, 301–314
- capacitive read-out 513
- capacitive sensors 527 f
- capacitive transducers 401 f
- capacitor inductor combination 210
- capacitor layers 80
- capacitors 142, 229 ff, 235
 - chemical sensors 372
 - interface circuitry 519
 - tunable 227
- capture conditions, fingerprint
 - images 424
- carbon black-loaded polymers 367
- Carnegie Mellon series 169 ff, 186 f
- cartridges 450
- catalytic thermal sensors 349 ff
- cavities 300
- CBT (2 μm) 72
- cell-based assays 457 ff
- cell–electrolyte electrode interfaces 463
- cell handling 458 f, 464
- cell level ACD 545
- cell trapping, dielectrophoretic 458
- cellular activity 463
- charge carrier transport 74 f
- charge-sensitive amplifier (CSA) 538
- charge transfer 317, 340 ff
- chemical mechanical polishing (CMP) 11
- chemical mechanical rubbing test 414
- chemical reactions 340 ff
- chemical robustness 416 f
- chemical sensors 335–390, 568 f
- chemical vapor deposition (CVD) 3, 44, 202, 210, 220
- chemiluminescence 353, 457
- chemisorption 337
- chemocapacitors 372 ff, 568
- chemoresistors 365
- chemotransistors 361 ff
- chopper amplifier 522, 534 f
- circuit integration 27 ff, 513–577
- circular diaphragms 293 f, 301
- circular plates 277 ff
- clamped beams 115
- Clark cell 361
- Clausius–Mossotti factor 459
- clock period
 - filters 542
 - pressure sensors 319
 - switched capacitor amplifier 533
- closed couplers, acoustics 194
- closed/open loop architectures 150
- coatings 336, 401
- comb fingers 157 f, 162, 170, 237
- common biometric exchange file format (CBEFF) 437
- common mode feed back (CMFB) 317
- comparator 570
- compliance
 - acoustic devices 198
 - coefficients 73 f, 76
 - inertial sensors 147 ff
 - pressure sensors 265 ff
 - sensors 261, 266
- component-based integration 437 ff
- compressibility 262, 267
- computer-aided engineering (CAE) 6
- condensation heat 352
- condenser microphones 195
- conducting polymers 367
- conducting thermocouple materials 85
- conducting thin films 69
- conductivity
 - electrical 82 f
 - thermal 69, 73, 86 ff, 96 ff, 323
- conductometric sensors 358, 365 ff
- constant-current sources 558
- constant-flow modes 502
- contact opening reticle 27
- contact area shifts 424
- contact electrode 454

- contact oxides 12, 96
 - contact resistance 80
 - contamination 453
 - continuous-time detection 530
 - control layer, fingerprint sensors 435
 - controllers, gas detection system 572 f
 - conversion radio architectures 227
 - converters
 - analog-to-digital (ADCs) 315
 - digital-to-analog 513 ff, 523, 549 ff
 - thermal 480, 499 ff
 - cooled photon detectors 482
 - coplanar waveguides (CWG) 231
 - copper
 - bulk material 97 ff
 - metallization 71, 126
 - Seebeck coefficients 485
 - spiral inductor 242
 - thin films 83, 87
 - core-cladding interface 355
 - Coriolis acceleration 144 ff, 156 ff, 164 f
 - correlated double sampling (CDS) 317, 531 f
 - Cottrell equation 359
 - Cr–Al–Cr spacer 180
 - cracking 114
 - critical pressure 107
 - cross sensitivity 525
 - crosstalk 570
 - crowding effects 240
 - crown ethers 338
 - cryptosmartcards 441
 - current mode 151
 - current references 554 ff, 558 ff
 - cut-frame structures 119
 - cyclodextrins 338
 - CYE (0.8 μm) 72
 - cytometers 458
- d**
- Daimler-Benz accelerometer 181
 - damascene copper process 234
 - damping 170, 182
 - acoustic devices 198
 - coefficients 140, 143
 - DARPA 165, 183
 - data interfaces 554 ff
 - databases, fingerprint sensors 429 f, 435
 - decimation filter 513, 552
 - deep reactive ion etching (DRIE) 21, 35, 53, 201 f
 - defects 24
 - defence evaluation 167
 - deflection 103 ff
 - acoustic devices 211
 - diaphragms 257, 301 ff
 - deformation functions 105
 - delay time 570
 - Delta–Sigma converters 313, 319, 321 ff, 513
 - demagnifying projection 399 f
 - demodulation 225, 520
 - demultiplexer 379
 - deployment 438 ff
 - deposition techniques 4 ff, 25, 301
 - design guidelines
 - accelerometers 141 ff
 - biochemical sensors 464 ff
 - gas detection system 566 f
 - system integration 561 f
 - design-rule-check (DRC) 26 ff, 564, 567 ff
 - desorption 352
 - device-under-test (DUT) 205, 527, 562
 - Dialog Semiconductor accelerometer 181
 - diamond shape structures 115
 - diaphragms 106 f
 - acoustic devices 195
 - pressure sensors 257
 - dielectric constant 73 f
 - chemical sensors 374
 - transducers 401
 - dielectric layers 5, 53, 126 f, 368
 - biochemical sensors 452
 - fingerprint sensors 407
 - dielectric thin films 69
 - dielectrometers 372 f
 - dielectrophoresis (DEP) 458 ff
 - differential circuit design 526
 - differential difference amplifier (DDA) 347, 528, 570
 - differential nonlinearity (DNL) 523
 - differential switched capacitor Sigma–Delta modulator 548
 - diffraction effects 197
 - diffusion barrier metallization 71
 - diffusion coefficients 359
 - diffusion effects 370
 - diffusion layers 80, 283 ff
 - diffusivity 73 f
 - digital circuitry 517
 - digital controllers, gas detection system 573 f
 - digital filters 551 ff
 - digital light processing (DLP) 46
 - digital micromirror device (DMD) 22, 46
 - digital output 521

- digital serial protocol controller 452
digital signal processor (DSP) 50
digital sound reconstruction (DSR) 193,
214 ff
digital-to-analog converters (DACs) 513 ff,
523, 549 ff
dilatation 268
diode array pixels 497
diodes, varactor 249
dirt problems, fingerprint sensors 440
discrete time system 542
distance transducers 401
distortions
– analog frontends 524
– filters 551
– fingerprint images 424
DNA analysis 14
doping 4, 24 f
– piezoresistivity 281 ff
– pressure sensors 303
double polysilicon–double metal
(DPDM) 184
drain/source implantation 12, 17, 40
drift 526
dry etching 18 ff
dual-band transceiver 229, 248
dual-slope analog-to-digital converters 544
duality principle 353
Dulong–Petit law 75
dynamic mode
– chemical sensors 345
– digital-to-analog converters (DACs) 549
dynamic properties, analog frontend 523 f
dynamic range, filters 551
dynamic signature verification (DSV) 396
- e**
earphone construction 208 ff
ECPD10 process 72
elastic moduli 69 ff, 73 f, 126 f
– silicon 266
elastic solids 261
elastic stiffness 73 ff, 76
elastoresistivity tensor 280
electret microphones 195
electrical conductivity 82 f
electrical–electrical transduction 74 ff
electrical material data 80 ff
electrical resistivity 69, 73 ff, 80, 485
electrical–thermal transduction 74 ff
electrically programmable read-only memory
(EPROM) 378 f
electrochemical reactions 340 ff
electrochemical read-out 454 f
electrochemical sensors 342, 358 ff
electrode fabrication 454, 464, 470 ff
electrogenic cells 463 ff
electromagnetic resonators 243 ff
electromagnetic waves 353
electromechanical drives 244
electromechanical interfaces 407 f
electron–hole pairs 353, 481
electronic design automation (EDA) 27
electronic noise 551
electrophysiological assays 463
electroplated gold lines 490
electroplating 5 ff, 42, 47
electrostatic deflection 100
electrostatic/thermal actuation 117 f, 235
electrothermomechanical material
data 73 ff
encoding 394 f, 403 ff
endothermic reactions 348
energy minimization method 113
engine level error rate 426
enrichment factor 339
enzyme label 455
epipolysilicon 128, 160 f
equal error rate 427
equivalent input noise 197
error rates
– analog frontends 526 f
– filters 551
– fingerprint sensors 426 ff, 432
– piezoresistivity 284
ESD air discharge 412 ff
etch-stop techniques 20, 42, 50
– electrochemical (ECE) 20, 51, 304 ff
– gate polysilicon 167 f
– microbolometers 495
– pressure sensors 259, 300 ff
etching 4, 18 ff, 38 ff, 241
– chemical sensors 346, 372
– interface circuitry 516
ethylcellulose (EC) 380
ethylenediamine-pyrocatechol (EDP)
etching 20, 53, 84, 241
– chemical sensors 350 ff
– pressure sensors 303
Euler buckling 115
evanescent waves 354
excitation signal 570
exothermic reactions 348
expansion coefficients 273
see also: thermal expansion coefficient
externally polarized microphones 195

f

fabrication 1–68
 – biochemical sensors 452, 464 ff
 – infrared detectors 481
 – interface circuitry 515 ff
 – microphones 197 f, 201 f
 – SOI diode microbolometer 498
 – speakers 209
 – system integration 515 ff
 – ultrasonic sensors 218 f
 Fabry–Perot devices 354 ff
 face recognition 395
 failure statistics 562
 failure-to-capture (FTC) rate 428
 failure-to-enrol (FTE) rate 428
 false acceptance rate (FAR) 397, 426
 false rejection rate (FRR) 397, 426
 faradaic currents 359
 Faraday constant 340
 feature extraction 416 ff, 424
 feedback
 – chemical sensors 345
 – fingerprint sensors 418, 439
 Fermi–Dirac integrals 281 f
 Fermi levels 282, 485
 ferromagnetic films 16
 field-effect transistors (FETs) 122, 230, 361, 463
 field-oxide layers 12, 96
 field tests, fingerprint sensors 411
 figures-of-merit, thermocouples 486
 film bulk acoustic resonator (FBAR) 246
 filters 244 ff
 – building blocks 539 ff
 – digital 551 ff
 – fingerprint sensors 421
 – interface circuitry 520 ff
 – system integration 513 ff
 fingerprint sensor systems 16, 391–446
 finite element modeling (FEM) 27
 – ANSYS 567
 – gas detection system 567
 – material properties 79 f
 finite impulse response (FIR) 313, 552
 flexural plate wave devices (FPWs) 343
 flexural rigidity 103, 271
 flicker noise 163
 flow cytometric analysis 454, 458
 flow diagram, IC fabrication 4
 flow sensors, thermal 480 ff
 fluorescence 353
 fluorescence-activated cell sorting (FACS) 458

focal plane arrays (FPA) 481 ff
 folded cascode operational transconductance amplifiers (OTAs) 568
 force balance equation 140
 force feedback 147, 150 f
 fork-type rate sensors 157 f, 164
 four-terminal transverse voltage strain gauge (X-ducer) 260, 297
 fractional resistances 294 ff
 fracture mechanical properties, silicon 123
 fracture strength/toughness 69 ff, 73 f, 76, 120
 frame-stabilized structures 119
 fraud, fingerprint sensors 440
 frequency conversion 225
 frequency response 212, 216
 frequency shift 336, 343
 frequency sweep 570
 Fresnel lenses 489
 friction 73
 front-side processing, wafers 301
 fully differential analog frontend 526 f
 fused silica 452

g

Gabor filter 421
 gain stability 144
 gallium arsenide 9
 – chemical sensors 353
 – RF CMOS MEMS 226
 Galvanielectrics 463
 gas detection system 379 ff, 566 ff
 gas flow meters 505
 gate capacitance 144
 gates 3, 10
 – layers 80
 – materials 6 f, 167
 – metal electrode 362
 – polysilicon 86, 167
 gauge factors
 – capacitive 300
 – polysilicon films 284 f
 gauge sections 119
 Gaussian distribution
 – piezoresistivity 283
 – system integration 559
 Gaussian plane wave filters 421
 geometric effects 109, 353
 geometric rule violations 564
 geometry–material property relations 79 f
 germanium 45, 187
 glass encapsulation 309 ff

- glucose 449
 - oxidase 454
 - GmC filters 537, 543 ff
 - see also*: transconductance
 - gold
 - black 488
 - electrodes 465
 - electroplating 181
 - layers 6
 - Seebeck coefficients 485
 - gold–tin solder frame 307
 - graph matching 425
 - gravimetric mass detection 217
 - Gray counter 379
 - gray scale dynamics 408, 425
 - Greek cross device 81 ff, 92 ff
 - Gummel number 555
 - gyroscopes 144 ff
- h**
- half-bridge topology 170
 - Hall plates 15, 37
 - hardware description language (HDL) 27
 - harmonic distortion 524
 - heat capacity 69, 73, 95 ff
 - heat loss 85, 502
 - heat transfer 75 ff
 - heating elements 502
 - Hermann–Schönflies notation 265
 - high-g prototype 183
 - high-impedance amplifiers 196
 - high-temperature capacitive pressure sensors 323 ff
 - high-temperature chemoresistors 367
 - high-temperature polysilicon 167
 - high-voltage devices 519
 - Hooke's law 261–269
 - hot junctions 350
 - hotplates 368
 - see also*: microhotplates
 - housing, acoustic devices 211
 - human serum albumin (HSA) 355
 - hybrid systems 454, 515
 - hydrazine water etching 49
 - hydrocarbons 337, 344, 352
 - hydrofluoric acid (HF) etching 8, 18 f
 - pressure sensors 260, 302
 - hydrogen monoxide 337
 - hydrogen peroxide 360
- i**
- I2C bus interface 571
 - identification 391, 416 ff, 439 ff
 - identifier on card (IoC) 441
 - IEEE1451.1–4 interfaces 554
 - image capture, fingerprint sensors 408–419
 - imaging arrays, thermopiles 489
 - immobilization 464
 - impedance, acoustic devices 203
 - impedance spectroscopy 461
 - implantation techniques 12
 - impurity concentration, piezoresistors 298
 - in vivo* electrophysical measurements 470 ff
 - indentation 121 f
 - indium phosphide 353
 - indium tin oxide (ITO) 460, 465
 - indiumantimonide 481
 - inductors 229 ff, 238 ff, 250
 - inertial sensors 137–192, 204
 - infinite impulse response (IIR) 313
 - information check, fingerprint sensors 420
 - infrared detectors, uncooled 480, 483 ff
 - inkjet printing 455
 - input common mode feedback (ICMFB) amplifier 163
 - input noise 197 f
 - input signal domain 73
 - insertion loss 225
 - instrumentation amplifier 513 ff, 536
 - integral nonlinearity (INL) 523
 - integrated circuits (ICs) 4, 79 ff, 341
 - integrated electronics 450 ff
 - integrated inertial sensors 137–192
 - integrated optics 354 ff
 - interconnects 3, 38, 452
 - interface circuitry
 - gas detection system 567 ff
 - system integration 513 ff
 - interfaces
 - electrogenic cells 463 ff
 - electronics 566
 - fingerprint sensors 407 ff, 435
 - interfacial cracking 114
 - interferences, analog frontends 527
 - interferometers 354
 - intermediate CMOS integration 257
 - intermetal insulators 71
 - intermetal oxides 12, 96
 - intermodulation filters 551
 - internal reflection transducer 400
 - intra CMOS micromachining 29, 37 ff
 - interface circuitry 515 f
 - pressure sensors 314 ff
 - inversion layers 78, 129
 - ion implantation 5

ion-selective field-effect transistor (ISFET) 362, 378, 464
 ionic compounds 338
 iris recognition 394 f
 irradiation 353
 islands, silicon layers 368
 isolated transistors 519
 isopropyl alcohol (IPA) 303
 isotropic etching 8 f, 18 f, 21, 302
 isotropic materials, Hooke's law 269 ff
 i-Stat Portable Clinical Analyzer (PCA) 449
 ITRS road map 517

j

Johnson noise 198 ff, 206 f, 486
 junctions 9 ff, 37 ff, 180 f, 234
 – chemical sensors 350
 – pressure sensors 260, 283, 322

k

K band frequencies 243
 Kanda effect 281, 299
 Kelvin relation 74 f
 kernel layer, fingerprint sensors 435
 Kirchoff condition 102
 KPY60 high pressure sensor 298
 Krautkramer transducer 220

l

Lamé's constants 269
 Langmuir–Blodgett films 338
 Laplacian operator 272, 278
 laser trimming 149
 lateral accelerometers 169 ff
 lattice defects 370
 layers
 – acoustic devices 196 ff
 – add-on 43 ff
 – biochemical sensors 453, 464
 – brittle 119
 – chemical sensors 336 ff, 352
 – dielectric 368
 – fabrication 3 ff, 25
 – fingerprint sensors 407
 – interface circuitry 516, 520
 – inversion 78
 – material characterization 80 ff, 89 ff, 96, 234 f
 – piezoresistivity 129, 283 ff
 – polysilicon 167
 – post CMOS micromachining 43 ff
 – pressure sensors 259 ff, 300, 305
 – system integration 565

– thermocouples 488
see also: passivation-, sacrificial-, oxide-layers
 layout-versus-schematic (LVS) verification 26, 565 ff
 lead zirconate titanate (PZT) transducers 219 f
 least significant bit (LSB) 522, 545
 lift-off technique 7, 15
 LIGA 178 f
 light-emitting diode (LED) 357
 limit-of-detection (LOD) 525
 linearity
 – analog frontends 523
 – pressure sensors 276
 – system integration 513
 lipids 338
 liquid flow 502
 lithographic structuring 27, 464
 living cells 463
 load deflection models 103 ff
 local oxidation of silicon (LOCOS) 9
 long diaphragms 109 f
 long-term stability 72
 – analog frontends 526
 long-wave infrared thermal sensors 481
 Lorentz forces 346
 loudspeaker 205
 low-doped drain (LDD) technology 3, 10
 low-noise amplifiers (LNA) 227, 536
 low-pressure CVD (LPCVD) 5, 25, 38
 – chemical sensors 350, 355
 low-pressure sensors 298
 low-temperature chemoresistors 366
 low-temperature oxide (LTO)–spin on glass–LTO sandwich (LTO–SOG–LTO) 47, 180
 lower explosive limit (LEL) 336, 349

m

M test (mechanical) 118
 Mach–Zehnder interferometers 354
 magnetic actuation 346
 magnetic modes 354
 MAMOS transistors 182
 manifold air pressure (MAP) sensing 260 f
 masking 6, 18, 27
 – interface circuitry 518
 – layers 564
 – materials 18
 mass-sensitive resonant cantilever 570 f
 mass-spring damper system 140
 matcher-on-card (MoC) 441

- matching, fingerprint sensors 394 f, 419 f, 424
 - material characterization 11 ff, 69–136, 338, 452
 - Mauguin notation 265
 - measurement techniques 69 ff, 79
 - mechanical–electrical transduction 77
 - mechanical energy domain 69
 - mechanical material data 123 ff
 - mechanical–mechanical transduction 76
 - mechanical properties 100 ff, 125
 - mechanical sensitivity 140
 - mechanical shock resistance 414 ff
 - mechanical switch 420
 - medium temperature deposition 25
 - membrane-based test structures 89 f
 - membranes 105 f
 - mercury cadmium telluride 481
 - metal bulk materials 97 ff
 - metal dielectric structures 172
 - metal–electrolyte interface 464
 - metal films 296, 492
 - metal inertial sensors 176 ff
 - metal layers 6 ff, 53, 169, 235
 - acoustic devices 196
 - biochemical sensors 453
 - interface circuitry 520
 - system integration 565
 - metal oxide semiconductor field effect transistor (MOSFET) 3, 361
 - metal oxide semiconductor implementation system (MOSIS) 215 f, 218
 - metal oxide–polymer diaphragms 196
 - metal-plated accelerometers 177 ff
 - metal silicon contacts 44
 - metal thin films 83
 - metallic sensor materials 338
 - metallization
 - elastic properties 124 ff
 - fabrication 2–16, 32–40
 - interface circuitry 516
 - material properties 71 ff, 80 ff
 - metrics, inertial sensors 140 f
 - microbolometers 479–512
 - microcontact printing 7, 455
 - microelectrode arrays (MAs) 463
 - microfabrication 1–68
 - micro-g accelerometers 139 f
 - microhotplates 367 ff
 - micromachining
 - cantilevers 345 ff
 - pressure sensors 261 ff
 - switches 229 ff
 - micromechanical structuring 79
 - microphones 193 ff, 201 ff
 - microsensors 335
 - microspectrometers 356 ff
 - microstripline filters 243
 - microtensile test 100, 119 f
 - mid-wave infrared thermal sensors 481
 - miniaturization 195
 - biochemical sensors 448 ff
 - fingerprint sensors 394, 409
 - RF CMOS MEMS 225
 - minutiae encoding 403 f, 417 f, 422
 - mixed-signal processing 315 ff, 245
 - mobility 144
 - data interfaces 555
 - RF CMOS MEMS 225
 - Modelsim 567
 - modular integrated CMOS and microstructures (MICS) 161
 - modular monolithic microelectromechanical systems (M²EMS) 33
 - modulation, RF CMOS MEMS 225
 - see also*: Delta–Sigma
 - moisture, fingerprint sensors 412
 - molding 7
 - molecular crystals 338
 - monolithic integration
 - capacitive sensors 530
 - inertial sensors 137–192
 - pressure sensors 259, 299
 - RF CMOS MEMS 226 ff
 - Monte Carlo simulations 559
 - Moore’s law 517
 - multiband transceivers 228 ff
 - multibit quantizers 547
 - multichip solutions 372
 - multilevel metallization 12
 - multimaster interfaces 572
 - multiparameter biochemical microsensor systems 378 ff
 - multiple component processing 194
 - multiplexers
 - biochemical sensors 451, 466
 - chemical sensors 379
 - system integration 545
 - multisensor systems 376 ff
 - multitransducer gas sensor systems 379 ff
- n**
- n-wells 9, 12, 357
 - nanoindentation 100, 121 f
 - Nasicon 338
 - near the edge (E) sensor 219

- Nernst equation 340, 361
 - neural activity 14
 - neural probe 471
 - neurite guidance 464
 - nickel 338
 - bulk material 97 ff
 - ring gyroscope 47
 - Seebeck coefficients 485
 - structure materials 180
 - thin films 83
 - nitric acid etching 18, 302
 - nitride layers 38
 - noble metals 338
 - coatings 369
 - doping 372
 - electrodes 465
 - layers 6
 - noise
 - acoustic devices 193 ff, 197 ff
 - analog frontends 525 ff
 - filters 551
 - inertial sensors 143 ff, 152 ff, 163 ff, 170
 - power spectrum 207
 - resonant devices 570
 - RF CMOS MEMS 225
 - switched capacitor amplifier 532, 537
see also: signal-to-noise ratio
 - noise-equivalent temperature difference (NETD) 479–512
 - normal stresses 262, 280 f
 - normalization, fingerprint images 422
 - Nyquist frequency 315, 546
- o**
- offset
 - analog frontends 513, 522
 - switched capacitor amplifier 535
 - ohmic conductors 291
 - ohmic switches 231
 - on-chip amplifier 217
 - on-chip multiplexer 451
 - on-chip signal processing 195, 340
 - Onsager thermodynamics 75
 - OpAmp-based interface circuits 519 f, 530 f, 548
 - operating temperatures, chemical sensors 368
 - operation modes, acoustic devices 195
 - operational amplifiers 359
 - operational transconductance amplifiers (OTAs) 310, 543 f, 568
 - optical interrogation 461
 - optical path 399
 - optical read-out 457 f
 - optical sensors 337, 342, 353 ff
 - optical transducer 399 ff
 - orientation dependence, piezoresistivity 288
 - oscillating mechanical surface deformation 343
 - oscillators
 - circuits 164
 - frequencies 228
 - gas detection system 571 f
 - resonant cantilevers 570
 - output, interface circuitry 520
 - output signal domain 73
 - oxide nitride layer sandwich 89
 - oxide semiconductor field effect transistor (OSFET) 463, 466
 - oxygen measurements 360
 - oxygen precipitation 24
 - oxygen vacancies 370
- p**
- p-wells 9, 12
 - packaging 231
 - acoustic devices 197
 - biochemical sensors 453, 473 ff
 - inertial sensors 150
 - interface circuitry 521
 - pressure sensors 300
 - RF CMOS MEMS 226
 - system integration 560
 - palladium 338, 362
see also: noble metals
 - parallel-plate capacitors 142, 162
 - parameter deviation 559
 - parameter sensitivity 513, 559 ff
 - parametric adjustments, inertial sensors 149 f
 - parasitic capacitance 240
 - inertial sensors 144, 152 f, 172
 - interface circuitry 517
 - piezoelectric elements 539
 - system integration 565
 - parasitic resistance 80
 - partition coefficient 337 ff, 343, 348
 - passivation 5, 12 f
 - thermal properties 96, 99
 - passivation layers 25, 44
 - biochemical sensors 453, 464
 - fingerprint sensors 407
 - passive devices 516
 - passive test structures 115 f
 - patterning 6, 25, 455
 - Pauw test structure 80, 92 f

- pellistors 349 ff
- Peltier coefficient 73 f
- pencil-drop test 415
- pendulous accelerometer 140
- performance, biometric system 425 ff
- permittivity factor 459
- person's verification 391, 416 ff, 439 ff
- personal identification number (PIN) 393, 398 f
 - diodes 230 f
- personal rights protection 396
- pH sensors 364, 454
- phantom powered microphones 196
- phased arrays 221 f
- phosphate buffered saline (PBS) 360
- phospholipids 338
- phosphorescence 353
- phosphorus implantation 38
- phosphosilicate glass (PSG) 10, 44
- photolithography 4 ff, 153
- photons 353, 482
- photopatterned silicone gasket 454
- photoresists 39, 167
 - layers 6, 234
 - plating mold 47
- photostructurable layers 7
- phototransistors 357
- phthalocyanines 338
- physical design verification 513, 564
- physical properties 69 ff
- physical vapor deposition (PVD) 5, 44
- physisorption 337, 566
- Pierce oscillator circuits 164
- piezoelectric elements 534 ff, 539
- piezoelectric materials 196
- piezoresistive accelerometers 169, 180 f
- piezoresistive coefficients 69 ff, 73 ff, 102, 122 ff, 129
- piezoresistive pressure sensors 49, 257 ff, 278 ff
- piezoresistors
 - analog frontends 527
 - diaphragms 297 ff
- Pirani pressure gauges 56, 261, 323 f
- pixel arrays, fingerprint sensors 406 f
- pixel-by-pixel compensation 457
- plane stress approximation 270 ff
- plane wave filters 421
- plasma-enhanced CVD (PECVD) 3, 71
- plastic properties 119 ff
- plating mold 47
- platinum 6, 14, 338, 349
 - bulk material 97
 - electrodes 454, 465
 - Seebeck coefficients 485
 - thin films 83
- plug-up process sequences 36
- pn-junctions 180, 234
 - fabrication 11 ff, 37 ff, 50 ff
 - pressure sensors 260, 283, 322
- pnp-transistors 556
- pointer structures 115
- Poisson ratio 69 ff, 73 ff, 101, 110, 119, 126 f
 - pressure sensors 267, 272, 284
- polarization 354
- polyether urethane (PEUT) 375 ff, 380
- polyaniline 367
- polybenzoxazole 456
- polycrystalline silicon *see*: polysilicon
- polydimethylsiloxane (PDMS) 7, 219, 352, 380
- polygermanium 45, 187
- polyimides 196, 465
- polymer coatings 336, 453
- polymer layers 6 f, 566
- polymers 338
 - conducting 367
- polypyrroles 367, 454
- polysilicon 3 ff, 10, 32, 43, 53
 - accelerometer 167
 - acoustic devices 196
 - chemical sensors 349
 - elastic properties 126
 - inertial sensors 146 ff
 - layers 85 ff, 167 ff, 305
 - material properties 83
 - piezoresistors 284 f, 305 ff
 - pressure sensors 259, 305, 312 f
 - refill 37
 - residual stress 124
 - resistors 502
 - Seebeck coefficients 485
 - system integration 559, 565
 - tensile properties 128
 - thermal properties 97
- polysilicon–germanium (polySi-Ge) materials 187, 492
- polysilicon–polysilicon interconnects 44
- polythiophene 367
- polyurethanes 338, 347, 375 ff, 380
- post-CMOS micromachining 43 ff
 - chemical sensors 344, 372
 - interface circuitry 515 f
 - passivation layers 453
 - pressure sensors 257

- potassium hydroxide (KOH) etching 5, 19 ff, 24 f, 41, 50 f
 - chemical sensors 346, 350 ff, 372
 - inductors 241
 - inertial sensors 180
 - pressure sensors 260, 303
 - potentiometric sensors 358, 361 ff
 - power amplifier 228
 - power consumption 151
 - interface circuitry 517
 - RF CMOS MEMS 226
 - system integration 513, 559 ff
 - pre-CMOS micromachining 29, 33 ff
 - pressure sensors 257
 - thermal sensors 515 f
 - preamplifiers
 - biochemical sensors 466
 - interface circuitry 520
 - precipitation defects 24
 - precision, analog frontends 526
 - preprocessing, fingerprint sensors 417 f, 421 f
 - pressure sensors 49, 56, 257–334
 - Privism 394
 - processing 9 ff, 17 ff, 24 ff, 69
 - biochemical sensors 452
 - diaphragms 201
 - inertial sensors 145 f
 - pressure sensors 300–313
 - processor smartcards 441
 - proportional-integral-differential (PID) controller 369
 - proportional-to-the-absolute-temperature (PTAT) 554 ff, 558 ff
 - protocols, interfaces 572
 - pseudo-differential amplifiers 528
 - Pseudomonas fluorescense* 450
 - pyroelectric analog frontend 534 ff
 - pyroelectric elements 539
 - pyroelectric infrared detectors 492
 - PZT transducers 219 f
- q**
- quadrature signals 228
 - quality factor
 - biochemical sensors 451
 - chopper amplifier 536
 - fingerprint sensors 409 ff
 - resonant cantilevers 570
 - RF CMOS MEMS 225
 - spiral inductors 240
 - quantization error 546
 - quantization noise 162 f
 - quantum efficiency 353
 - quantum-well infrared photodetectors 481
 - quartz microbalance (QMB) 343
- r**
- radiation resistance 198, 209
 - radiation sensors 480 ff
 - radio receivers 196
 - raw image enhancement 421
 - Rayleigh–Ritz variation 273
 - Rayleigh surface acoustic waves 343 ff
 - reactive ion etching (RIE) 8, 11, 169
 - chemical sensors 346, 355
 - microbolometers 495
 - receiver–operator curve (ROC) 427
 - receivers 227 ff
 - receptors 338, 348
 - recognition processes 394 ff, 411
 - redox cycling 455
 - reduced Fermi level 282
 - reference electrodes 359, 454
 - reference fingerprints 425
 - reflection optical waveguides 355
 - refractive index 354
 - regeneration transistors 538
 - reliability 72, 397
 - request fingerprints 425
 - residual stress 73 f, 109, 236
 - residual stress/strain 101, 123
 - resistive sensors 526 f
 - resistivity
 - electrical 69, 73 ff, 80
 - fingerprint sensors 412 ff
 - resistors 149, 502
 - resolution
 - analog frontends 513, 522
 - digital-to-analog converters (DACs) 549
 - filters 551
 - fingerprint images 425
 - resonance frequencies 77, 144
 - chemical sensors 336, 343
 - resonant-beam oscillator 571 f
 - resonant cantilever 345, 570 f
 - resonators
 - inertial sensors 156 ff
 - RF CMOS MEMS 229 ff, 243 ff, 343
 - thin film bulk acoustic 246
 - reticles 27
 - reversibility, chemical sensors 338
 - RF CMOS MEMS 225–256
 - RF filtering 206
 - ridges, fingerprint sensors 416, 430
 - rigidity 103, 267, 271

- ring gyroscope 47, 179
- ring plates 277 ff
- Robert Bosch accelerometer 160 f
- robustness 79, 414 ff
- Root Allan deviation 160
- root mean square (RMS) voltage 479, 499 f
- rotated coordinate systems 284 f
- rotating pointer structures 115
- rotation, fingerprint images 424
- round robin test 128
- rub-off test 414

- S**
- Saccharomyces cerevisiae* 461
- sacrificial aluminum etching (SALE) 22, 55
- sacrificial layers 36 ff, 89
 - pressure sensors 259 ff, 300, 305
- sacrificial oxide etching 38
- sacrificial photoresist layer 234
- sacrificial spacer 180
- Sallen–Key filters 540
- sample handling 120, 473 ff
- sample-to-answer-path 450
- sandwich technology 3 ff, 47, 54, 89, 96
- scalability 451
- scaling 283, 451
- scanning area limits 425
- scanning probe techniques 472 ff
- scattering 353
- scenario evaluation, fingerprint sensors 429
- schematics *see*: block diagrams
- scratch resistivity 415
- security, fingerprint sensors 438 ff
- Seebeck coefficients 69 ff, 73, 84 ff, 87 ff
 - thermocouple materials 350 ff, 483 ff
- segmentation, fingerprint sensors 421
- selectivity 338, 375
- selfalignment 305
- selfheating 88, 499
- semiconducting substrates 9
- semiconducting thin films 69
- semiconductor switches 230
- sense nodes 172 f
- sensitivity
 - acoustic devices 193 ff
 - analog frontends 525
 - biochemical sensors 451
 - fingerprint sensors 407
 - inertial sensors 140 ff, 160, 177 f, 183
 - system integration 513, 559 ff
- sensor arrays 12
- sensor device integration 434 ff
- separation-by-implantation-of-oxygen (SIMOX) 40, 128, 322, 372
- serial interfaces 513, 572 f
- serpentine metal-oxide mesh pattern 201 f, 211 f, 218 f
- Severinghaus pH FET 378
- shear mode resonator 343
- shear modulus 76, 267
- shear stress 262, 280 f
- sheet resistance 73, 80, 94, 559
- shock tolerance 140
- short-term stability 570
- sidewall implantation 37
- Siemens gate polysilicon accelerometer 167
- Sigma–Delta converter
 - analog-to-digital 546 ff
 - chemical sensors 351, 373, 380
- Sigma–Delta electrostatic force 161 ff
- Sigma–Delta modulators 544, 568
- signal processing
 - biochemical sensors 452
 - fingerprint sensors 399 ff
 - pressure sensors 259, 315 ff
- signal-to-noise ratio (SNR) 152, 340, 513, 577
- signature recognition 396
- silicides metallization 71
- silicon 3 ff
 - acoustic devices 196
 - bulk material 97 ff
 - chemical sensors 368
 - data interfaces 555
 - diaphragms 257
 - elastic properties 126
 - material properties 74 ff, 287 ff
 - microbolometers 492
 - pressure sensors 259, 304 ff
 - RF CMOS MEMS 226
 - Seebeck coefficients 485
 - wafers 287 ff, 452
- silicon dioxide
 - layers 3 ff
 - material properties 74 ff
 - thermal properties 96 ff
- silicon germanium BiCMOS devices 234
- silicon nitride
 - chemical sensors 355
 - diaphragms 260, 305 ff
 - elastic properties 127
 - layers 3 ff, 38, 52 f, 305
 - material properties 74 ff, 78
 - residual stress 125
 - tensile properties 128

- silicon-on-glass (SOG) 47, 55, 180
 - accelerometers 184
 - coatings 71
- silicon-on-insulator (SOI) 2 ff, 35 f, 88
 - chemical sensors 372
 - inertial sensors 183 f
 - microbolometers 497
 - pressure sensors 322
- silicon oxide
 - elastic properties 127
 - residual stress 124
 - tensile properties 128
- silicon trench etching 37
- simulation results, acoustic devices 212
- sinc filters 552
- single-chip gas detection system 566 ff
- single-chip integration 250 f
- single-chip radios 225
- single-master interfaces 572
- skin effects 240
- small-size design 197 ff
- smart cart integration 440 ff
- software development kit (SDK) 434 ff, 438
- software solutions, fingerprint sensors 416 ff, 419 ff
- sol-gel process 372
- solder-bonded capacitive pressure sensors 307 ff
- sound pressure displacement 200
- sound pressure level (SPL) 205
- sound waves 195
- source drain currents 361
- source drain implantation 12, 17, 40
- space charge region 361
- spacers 180
- speaker recognition 396
- speakers 193 f, 208 ff
- specific heat 69 ff
- specifications
 - interface circuitry 520 ff
 - operational transconductance amplifiers (OTAs) 569
 - switched capacitor amplifier 535
- Spectre Synopsys 567
- spiral inductor 240
- spot noise 160, 455
- spring constant 140, 153
- springs, acoustic devices 202 f
- sputtering 6, 42, 45
 - chemical sensors 344
- square diaphragms 106 f
- squeeze film damping 182, 186, 198 f, 201 ff
- ST's TouchStrip TCS3B capacitive transducer 403
- stability 72
 - analog frontends 526
 - fingerprint sensors 432
 - resonant beam oscillator 570
- standard biometric templates 437
- standard software, fingerprint sensors 435 ff
- static mode, chemical sensors 345
- static properties, analog frontend 522 f
- static random access memory (SRAM) 46
- stepper based lithography 27
- stiction, inertial sensors 147, 149 ff
- stiffness 73 f, 76
 - tensors 261, 265 ff
- storage smartcards 441
- strain gauges
 - diaphragms 304 ff
 - pressure sensors 259
- strain tensors 261
- stress 150
 - diaphragms 257
 - relaxation 85
- stress–strain relationship 102
- SU-8 substrates 7, 465
- substrate materials 5 ff
 - biochemical sensors 452
 - interface circuitry 516 f
- substrate temperatures 88
- super-heterodyne radio architectures 227
- surface acoustic waves (SAW) 343 ff
- surface coating 464
- surface deformation 343
- surface doping 372
- surface energy, fingerprint sensors 412
- surface micromachining 22 ff, 29
 - microbolometers 491
 - pressure sensors 257, 300 ff, 344 ff
 - test structures 89 f
- surface properties 7, 78, 115
 - fingerprint sensors 399
- suspended inductors 238 ff
- suspended rings 115
- suspension 151
 - spring constant 140
- swipe sensors 403 f, 440
- switched capacitor
 - Delta–Sigma modulator 317 ff
 - filters 541 ff
 - pressure sensors 257
 - system integration 513 ff, 531 ff, 568
- switching 229 ff

- fingerprint sensors 420 ff
- symmetry transition 113
- synthetic fingerprints 430
- system integration 513–577
 - fingerprint sensors 433 ff
- system level error rates 428
- system-on-card (SoC) 441
- system-on-chip
 - filters 551
 - interface circuitry 521
- system properties, analog frontend 525 f
- system scalability 451

t

- temperature coefficient of resistance (TCR) 74, 82 ff, 95 ff
 - microbolometers 492
- temperature dependence 150, 350
 - base-emitter voltage 555 ff
 - layers 491
 - piezoresistivity 281 ff
 - pressure sensors 259
 - sensitivity 207
 - transducers 402
- template-on-card (ToC) 441
- templates
 - fingerprint sensors 425, 437
 - interface circuitry 521
- tensile stress 147, 262
- tensile test 119 f
- tensor notation 261 f
- tented arches 418
- termination 416
- test structures 88 ff, 115 ff, 150, 513, 561 ff
- tetramethyl ammoniumhydroxide (TMAH) 20, 24, 53, 303, 495
- thermal accelerometer 175 f
- thermal actuation 345
- thermal conductivity 69, 73, 86 ff
 - chemical sensors 368
 - pressure sensors 323
- thermal–electrical transduction 74 ff
- thermal energy domain 69
- thermal expansion coefficient (TCE) 69, 73 ff, 101, 114 ff, 126 f, 236
- thermal–mechanical transduction 77
- thermal pressure sensors 324 ff
- thermal properties 86 ff
- thermal sensors 337, 342, 348 f, 479–512
- thermal–thermal transduction 77 ff
- thermal transducers 402 ff
- thermal van der Pauw test structure 80, 92 f
- thermally stabilized accelerometers 173
- thermistors 6
- thermochuck test 562
- thermocouples 350, 483 ff
- thermoelastic friction 73
- thermoelectric coolers 498
- thermoelectric analog frontend 534 ff
- thermoelectric material data 80 ff, 86 ff
- thermoelectric sensors 350 ff
- thermomechanical noise 142
 - acoustic devices 193, 197 ff
 - see also*: Brownian noise
- thermopiles 12, 479–512
 - chemical sensors 350
 - imaging arrays 489
- thermopower 69, 82 ff
- thermovoltage 350
- thickness control, diaphragms 302 ff
- thickness-shear-mode resonator 343
- thin diaphragms 300
- thin films 69–136, 149
- thin plate deflection 271 ff
- thinned fingerprint images 423
- Thomson coefficient 73 f, 76
- three-electrode system 359
- threshold limited value (TLV) 336
- time constants
 - filters 541
 - thermal 100
- time etch-stop 303 ff
 - see also*: etch-stop
- time-of-flight flow sensors 502 f
- tin dioxide 337
- tin-lead solder frame 307
- tin oxides 338, 370
- tissue cultures 463
- titanium
 - bulk material 97
 - bolometer structures 41
 - thin films 83
- titanium–gold seed layer 47
- titanium nitride thermocouples 488
- total harmonic distortion (THD) 524
- total internal reflection transducer 400
- TouchStrip TCS3B capacitive transducer 403
- toughness 69 ff, 73 f, 76, 101
- transceivers, multiband 228 ff
- transconductance 144
 - switched capacitor amplifier 537, 543 ff, 548
- transducer electronic data sheet (TEDS) 554
- transducers
 - acoustic 194, 214 ff, 219 ff

- biochemical sensors 451
 - chemical sensors 336 ff, 376 f, 379 ff
 - fingerprint sensors 399 ff
 - gas detection system 567
 - pressure sensors 259 ff
 - system integration 560
 - transduction effects 70 ff, 203 ff
 - transfer functions
 - analog frontends 523
 - biquad filter 540
 - Delta–Sigma modulators 257, 321 ff
 - FIR filter 553
 - switched capacitor amplifier 538
 - transformation tensors 263 ff, 287 ff
 - transients, chemical sensors 352
 - transistors 167, 182, 361
 - interface circuitry 516 f, 556
 - RF CMOS MEMS 226
 - switched capacitor amplifier 537
 - transmission gates 542
 - transmission lines 228, 243
 - transverse modes 354
 - trench isolation 35, 184
 - tri-axial piezoresistive accelerometer 182
 - trimming capability 149
 - triple-well technologies 519
 - tunable capacitors 227
 - tungsten
 - bulk material 97
 - elastic properties 126
 - plug 71
 - thin films 83
 - tuning fork resonant sensors 164
 - tuning voltage 234
 - twin-well technology 3
 - two-beam interferometer 355
- u**
- ultrasonic sensors 193 f, 217 ff
 - uncooled infrared detectors 480, 483 ff
 - user interaction, fingerprint sensors 439 ff
- v**
- vacancies 370
 - vacuum cavity 259
 - vacuum operations 499
 - valleys, fingerprints 416
 - van der Pauw test 80, 92 f
 - vanadium oxide 492
 - vaporization heat 352
 - varactor diodes 248
 - variable gain amplifier (VGA) 227
 - verification
 - fingerprint sensors 391, 416 ff, 439 ff
 - system integration 513, 564 ff
 - vertical axis accelerometer 170
 - vertical axis gyroscope 163
 - vertical parallel-plate capacitors 235
 - vertical pnp transistors 556
 - vibrating metal-ring gyroscope 178 ff
 - vibration rejection 193 ff, 200 f
 - vibratory rate gyroscope 144 ff
 - voice scan 396
 - volatile organic compounds (VOCs) 338, 344, 379, 566
 - voltage-controlled charge source (VCQS) 319
 - voltage-controlled oscillator (VCO) 234, 247
 - voltage modes 151, 554 ff
 - voltammetric sensors 337, 358 ff
 - volume reduction 226
- w**
- wafer bonding 300, 310 ff
 - wafer curvature 114 f
 - wafer materials 9 f
 - wafer technology 46 f, 452, 516 f
 - water acoustics 219 ff
 - wave guides 355
 - weight reduction 226
 - well formation 9, 12
 - wet etching 18 f, 24 f, 50
 - pressure sensors 259, 302
 - wet skin, fingerprint sensors 421, 439
 - Wheatstone bridge 11, 50, 181
 - biochemical sensors 472
 - chemical sensors 365
 - circuit integration 513 ff, 526 ff
 - piezoresistors 261, 295 ff, 300 f
 - resonant beam oscillator 570
 - whorl, fingerprint class 418
 - wire bonding 16
 - wireless communication 225 ff
 - working electrodes 359
 - working scheme
 - biometric system 318 ff
 - fingerprint sensors 431
 - worst case combinations 559
- x**
- X-ducer 260, 297
 - xenon difluoride etching 169, 241
 - xerogels 457
 - XL series inertial sensors 146, 151 ff, 155, 158 f

γ

- yield stress 73 f, 76
- Young's modulus 69 ff, 73 ff, 101 ff, 119, 126 f
 - acoustic devices 199, 204
 - inertial sensors 146 f
 - pressure sensors 267, 272, 284
- yttrium barium copper oxide 492 ff

z

- zeolites 338
- zero-input signal 522
- zero-rates 427
- zinc oxide 343
- zirconium dioxide 337

