

INDEX

- AC Analysis, 191, 48, 53, 55
 Activity-based Analysis, 191, 106,
 107, 119, 120, 121,
- Back-annotation, 191, 196, 116
 Block-Level Power Distribution, 191
 Break Cell, 191, 188, 189,
 By-pass Capacitor, 191
- C4 Package, 191, 2, 4, 20, 34, 44, 45,
 63
 Capacitance, 191, 4, 6, 8, 9, 10, 11, 12
 Capacitance Model, 191, 10, 1, 2, 8,
 Chip, 191, 1, 2, 4, 6, 7, 8, 12
 Characterization, 191, 24, 25, 32, 48
 Circuit Simulation, 191, 37, 51, 104,
 107, 162
 Circuit Timing Analysis, 191
 Contact, 192, 10, 11, 53, 66, 76, 78,
 79, 84
 Core, 192, 117, 136, 140, 150, 158,
 172, 188
 Crossbar Leakage Current, 192
- Decoupling Capacitor, 192, 1, 2, 4, 6,
 7, 16, 19, 23, 44, 46, 52, 53, 54,
 55, 57, 59, 61
 Deep-Submicron Process, 192, 4, 44
 Delay, 192, 20, 27, 34, 58, 100, 103,
 126, 160.
 Delta-I Current, 192, 147
- Design Guidelines, 192, 28, 33, 73,
 162
 Design Methodology, 192, 75, 84
 Design Rule, 193, 7, 10, 84
 Device, 1, 4, 9, 20, 34, 37, 53, 55–56,
 58, 60, 69, 71, 80, 82, 84–85, 88,
 106–107, 116–117, 138–139,
 141–142, 153
 Device-Level Extraction, 193
 Di/Dt , 1, 16, 20, 29, 30–31, 33–35,
 67–70, 150, 155–156, 160, 185,
 190
 Die, 193, 1, 12, 28, 29, 30, 44, 45, 53,
 67, 68
 Die Size, 193, 28, 29, 30, 44, 70, 72,
 139
 Die Micrograph, 193, 139, 140, 148,
 149
 DRC, 193, 46.
 Dynamic Analysis, 193, 91, 94, 95, 99
- ECO (Engineering Change Order),
 193, 104, 133
 Electromigration, 193, 3, 56, 75, 76,
 80, 81, 82, 83, 84, 85
 ESR, 193, 72
 Extracted Parasitic, 193
 Extraction, 196, 7, 10, 66, 99, 173
- Flip-Chip, 193, 43, 61, 65, 104, 139,
 148, 153, 156, 157, 158, 159

206 INDEX

- Floorplanning, 193, 33, 34, 35, 61
 Full Chip Power Distribution, 193, 4
- Gate Capacitance, 193, 20, 29, 30, 166.
 Gate Delay, 193, 100, 103, 127
 GDSII, 193, 99
 Global Power Network, 194, 33
 Ground Bounce, 194, 89, 160, 164, 165, 167
- Hot Spot, 194, 12, 16, 57, 61, 71, 186
- Impedance, 194, 23, 25, 27, 57
 Interconnect RC, 194, 7, 66
 IR Drop, 194, 27, 29, 30–36, 38, 62–66, 87–104
 I/O Library, 194, 188.
- $L*di/dt$ Noise, 194, 1, 20, 29–35, 67
 Leakage Current, 194, 13, 141, 146–147
 Linear Network, 194, 1, 109.
 Loop Inductance, 194, 23, 29, 68, 69, 136, 150
 Low-pass Filter, 194, 1, 44
 LVS, 194, 54
- Mean Time to Fail (MTF), 194, 54, 76, 85
 Metal Capacitance, 194, 29, 174
 Metal Ion, 194, 75
 Metal Structure, 195, 24, 25
 Metal Layer, 4, 9–10, 33–34, 73, 76, 84, 100, 109, 113, 115, 135, 140–141, 147, 153
 Metal Utilization, 195, 167, 172, 177
- Modeling, 195, 1–8, 12–16, 27, 32, 35, 37, 38, 48, 50–51, 57, 59, 63, 72–73, 92, 161.
- Netlist, 8, 90, 92–93, 95–97, 99–134
 Noise, 195, 1–2, 12–13, 16, 20, 30–33, 44, 60–61, 67–69, 71, 72, 88, 136, 141, 142, 146, 147, 150, 155, 156, 157, 159, 161, 175
 Noisy Nodes, 195, 17, 18, 19, 32
- On-chip Inductance, 195, 2, 7, 20, 24, 180
- Package, 2, 4, 16, 20, 33–34, 36, 38, 41, 44–45, 48, 50, 53, 55–56, 60, 63, 65, 67–68, 72–73, 107, 136, 139, 148, 151, 155–158
 Parasitic, 195, 7, 8, 10, 20, 98, 175, 177, 151, 161, 162, 178, 181, 183.
 Parasitic Capacitance, 195, 99, 107, 172, 174, 175
 Peak Current, 195, 58, 59, 65, 77, 81, 101, 108, 110, 116, 117, 118, 125, 127, 129
 Physical Design, 195
 Piecewise Linear, 195, 58, 96, 107
 Place & Route, 195
 Power Bus, 195, 42, 55, 56, 57, 60, 61, 89, 104, 113, 181, 189
 Power Distribution, 195, 1, 2, 4–5, 20, 28–30, 32–35, 42, 44–45, 55–56, 69, 73, 76, 84, 97, 104
 Power Grid, 195, 1, 4, 6–7, 12, 14, 20, 32–33, 35–38, 41–43, 45, 47–50, 62–63.
 Power Grid Analysis, 195, 1, 33, 89, 91–108, 116, 121–129
 Power Network, 196, 1–7, 12, 16–20, 28–32, 33–34, 44, 48, 50–55, 58, 65, 68, 73, 83, 89, 104, 116, 118, 129, 133, 135, 140, 157, 162, 167–168, 172, 175, 180
 Power Strap, 196, 38, 65, 118, 119
 Power Supply Voltage, 196, 1, 53, 56–57, 59–61, 70, 88, 116, 133, 136, 156
 Power Switching Noise, 196, 88
 Pre-layout Netlist, 196
- RC Back-annotation, 196
 RC Extraction, 196, 7, 10, 66, 99, 173
 RC Data, 196, 8,
 RC Netlist, 196, 8
 Reflection Noise, 196, 161
 Regulator, 196, 72, 150–153, 156, 163
 Resonance, 196, 150–151, 163–165, 181, 183
 RLC Segment, 196, 4

- Routing, 33, 36, 38, 39, 42, 46, 48, 57, 70, 88, 113, 130–131, 136, 153, 155, 167–172, 177, 181, 183, 185
- RMS Current, 196, 77, 81, 84, 99, 128
- Scaling, 196, 1–3, 28–32, 62, 76, 88, 103, 107, 110, 118, 119, 173
- Simulation, 197, 3, 6, 12, 19, 20, 38, 40, 42, 45–46, 51–52, 58, 60, 63, 65, 80, 83, 92, 98–99, 104, 106–107, 116, 118–119, 124–125, 127, 162–163, 165–167, 172, 175, 177, 181, 183–184
- Simultaneous Switching Noise (SSN), 195, 143, 157, 159, 161, 162, 164, 190
- Standard Parasitic Format (SPF), 197, 8, 9.
- Standby Mode, 197, 141–143, 146
- Static Analysis, 197, 92–93, 96, 100, 105, 107–108, 110, 116–117, 119, 124, 125, 127–128
- Switching Current, 197, 1, 4, 12, 15, 45, 49, 55, 66–67, 73, 133, 155, 160, 175–176
- Switching Factor, 197, 28, 31–32, 76, 93, 98, 103, 110, 118–119, 173
- Tap Current, 197, 85, 90–91, 94–104, 106, 109–133
- Technology Parameters, 197, 135, 147
- Top Metal Layer, 197, 4, 135
- Transistor, 197, 1–4, 13, 19, 28–30, 45, 67, 73, 83–85, 88–104, 106–133, 135–156
- Transistor-Level Simulation, 197, 63, 83, 98
- Transmission Line, 197, 161
- Unit-length Capacitance, 198, 10, 28, 30
- Unit-length Inductance, 198, 4, 29
- Unit-length Resistance, 198, 4, 28
- Via, 198, 10–11, 32, 34, 55, 72, 76, 78–80, 84–85, 89, 129–130, 186
- Via Resistance, 198, 66
- Vector-Based Analysis, 198
- Voltage Distribution, 198, 1
- Voltage Fluctuation, 198, 12, 16
- Voltage Threshold, 198, 17
- Voltage Regulation, 198, 151
- Weak Spot, 198, 89–90, 92–93, 104–106, 126, 133
- Wire Bonding, 198, 36, 38, 43, 61, 63, 65, 118, 159, 168–169, 171–172, 177

