

Index

Note to the Reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

A

accept-lifetime command, 86
 access command, 126
 access-class command, 146
 access-list command, 143–144, 146–148, 166–168
 access-list deny command, 143–145, 147–148
 access-list deny host command, 144
 access-list deny tcp command, 148–149
 access-list deny tcp any host command, 149–151
 access-list permit command, 146–147
 access-list permit ip any any command, 151
 access lists, 141–142
 IP
 extended, 146–151
 monitoring, 158–160
 standard, 142–146
 for Telnet, 145–146
 wildcards with, 145
 named, 151–153
 switch port, 153–156
 time-based, 156–157
 active state
 EIGRP, 88
 LMI, 239
 AD (administrative distances)
 IP routing, 65–66
 static routing, 62
 ad hoc networking, 182
 Add DHCP Pool dialog box, 257, 257
 addresses
 IP
 IPv6 protocol. *See* IPv6 protocol
 mismatched, 231–232, 232
 NAT. *See* Network Address Translation (NAT)
 IPv6 protocol, 201–202, 201
 learning, 103
 MAC, 106–107
 static, 106–107

switches, 115–116
 wireless network authentication, 184–185
 administrative distances (ADs)
 IP routing, 65–66
 static routing, 62
 Advanced NAT configuration, 170
 AES (Advanced Encryption Standard), 186
 agencies for wireless technologies, 176–177
 aging option, 105
 ANSI format, 239
 any command, 143, 147, 152, 154–155
 applet blocking, 141
 Application layer attacks, 139
 Application-Specific Integrated Circuits (ASICs), 102–103
 areas, OSPF, 92
 Asynchronous Transfer Mode (ATM), 224
 authentication
 EIGRP, 85–86
 peer route, 141
 PPP, 227–230
 RIPv1 vs. RIPv2, 70
 wireless networks, 184–185
 authentication-open command, 187
 authentication proxy, 140
 auto-summarization, 81
 autorouter attacks, 139

B

BackboneFast feature, 109, 111
 backdoor attacks, 139
 Backspace command, 6
 backups
 IOS, 31–32
 router, 35–37
 SDM, 262–266, 263–265
 bandwidth command, 14, 79
 banner command, 9–10
 bars (|) for pipes, 80
 base MAC addresses, 116
 Basic NAT Wizard, 170–172, 171

280 basic service sets (BSSs) – configuration

basic service sets (BSSs), 182, 183
 bit-oriented protocols, 224
 block sizes with wildcards, 145
 blocking applets, 141
 boot command, 29
 booting
 commands, 29
 configuration modes, 4–5
 editing and help features, 6–8
 routers, 2–4, 3, 27
 setup modes, 4
 bootstrap protocols, 22
 BPDUFilter feature, 109–110
 BPDUGuard feature, 109–110
 breaks, 27
 bridges, 108, 118–120
 brute force attacks, 140
 BSSs (basic service sets), 182, 183
 byte-oriented protocols, 224

C

cabling, 223
 Carrier Sense Multiple Access with Collision Detect (CSMA/CD), 180, 180
 Catalyst switches. *See* switches
 CBAC (context-based access control), 140
 CCMP (Counter Mode Cipher Block Chaining-Message Authentication Code (CBC-MAC) Protocol), 186
 CD command, 33
 CDP (Cisco Discovery Protocol), 40
 neighbor information, 41–43
 port and interface information, 43–44
 timers and holdtime information, 40–41
 traffic information, 43
 VLAN telephony, 134–136
 cdp enable command, 40
 cdp holdtime command, 40–41
 cdp timer command, 40–41
 central office (CO), 221
 Challenge Handshake Authentication Protocol (CHAP), 230
 channel-group command, 113
 channel-protocol command, 113
 CHAP (Challenge Handshake Authentication Protocol), 230
 Cisco Discovery Protocol (CDP), 40
 neighbor information, 41–43
 port and interface information, 43–44
 timers and holdtime information, 40–41
 traffic information, 43
 VLAN telephony, 134–136
 Cisco encapsulation, 236, 242
 Cisco format in LMI, 239
 Cisco IOS. *See* IOS (Internetwork Operating System)
 class of service (CoS), 134–136
 classful routing, 63, 68
 clear counters command, 14, 16
 clear line command, 45, 48
 Clear To Send (CTS) signal, 180
 clearing Telnet connections, 48
 CLI (command-line interface), 6–8
 clock command, 7
 clock rate command, 14
 clocking, 14
 closing Telnet sessions, 47–48
 CO (central office), 221
 collisions, 180
 command-line interface (CLI), 6–8
 config-register command, 25, 27–28
 configuration
 backing up
 IOS, 31–32
 router, 35–37
 SDM, 262–266, 263–265
 banners, 9–10
 copying
 to NVRAM, 36–37
 to TFTP server, 37
 EIGRP, 77, 274–275, 274–275
 erasing, 38
 hostnames, 9
 IFS for, 38–39
 IPv6 protocol, 204–205
 layer 2 switching, 104–105
 modes, 4–5
 NAT
 dynamic, 166–167
 overloading, 167–168
 SDM for, 170–173, 171–172
 static, 165
 verifying, 168–170
 OSPF, 91
 areas, 92
 debugging, 98–100

- enabling, 92
 - SDM, 275–277, 276–277
 - verifying, 92–98
 - passwords, 10–14
 - PPP, 226–227
 - PPPoE, 233–234
 - restoring, 37–38, 262–266, 263–265
 - RIP, 272–274, 273
 - router interfaces, 14–18
 - switches. *See* switches
 - verifying. *See* verifying
 - VLANs, 122–123
 - inter-VLAN routing, 130–131
 - switch port assignments, 124–125
 - trunk ports, 126–130
 - verifying, 124
 - voice, 134–136
 - VTP, 131–133
 - wireless networks
 - IOS, 186–190
 - SDM/HTTP, 190–197, 191–197
 - configuration registers
 - boot system commands, 29
 - changing values, 24–26
 - checking values, 24
 - for password recovery, 26–27
 - resetting, 28–29
 - configure terminal command
 - Frame Relay, 241, 247
 - modes, 5
 - PPP, 226–227
 - STM, 250–251
 - WANs, 221–222
 - confreg command, 27
 - congestion, 240
 - connections, Telnet, 46, 48
 - connectivity, 52
 - debugging, 53–55
 - ping command, 52–53
 - processes, 55
 - traceroute command, 53
 - content addressable memory, 115
 - context-based access control (CBAC), 140
 - convergence, OSPF, 91
 - copy command, 31–33
 - copy flash tftp command, 30–32
 - copy running-config command, 17
 - copy running-config startup-config command, 17, 29, 35–36, 187
 - copy running-config tftp command, 37
 - copy start run command, 27
 - copy startup-config running-config command, 28
 - copy tftp flash command, 31–32
 - copy tftp running-config command, 37
 - copy tftp startup-config command, 37
 - CoS (class of service), 134–136
 - Counter Mode Cipher Block Chaining-Message Authentication Code (CBC-MAC) Protocol (CCMP), 186
 - CPE (customer premises equipment), 221
 - Create Connection screen, 192
 - Create NAT Configuration screen, 171, 171
 - crypto key generate rsa command, 12–13
 - crypto pki command, 258
 - CSMA/CD (Carrier Sense Multiple Access with Collision Detect), 180, 180
 - Ctrl+A command, 6
 - Ctrl+Break command, 27
 - Ctrl+D command, 6
 - Ctrl+E command, 6
 - Ctrl+F command, 6
 - Ctrl+N command, 6
 - Ctrl+P command, 6
 - Ctrl+R command, 6
 - Ctrl+Shift+6 command, 45
 - Ctrl+U command, 6
 - Ctrl+W command, 6
 - Ctrl+Z command, 6
 - CTS (Clear To Send) signal, 180
 - customer premises equipment (CPE), 221
-
- D**
- data encapsulation
 - Frame Relay, 236–237
 - PPP, 228–231, 228–229, 231
 - VLANs, 130–131
 - WANs, 221
 - Data Link Connection Identifiers (DLCIs), 237–238, 238
 - debug command, 52–54
 - debug all command, 54
 - debug eigrp packet command, 87–88
 - debug frame lmi command, 243, 246–247
 - debug ip eigrp events command, 89
 - debug ip eigrp notification command, 87, 89
 - debug ip nat command, 168–169
 - debug ip ospf adj command, 100

282 debug ip ospf hello command – enabling

debug ip ospf hello command, 99
 debug ip ospf packet command, 98–99
 debug ip rip command, 55, 71–73
 debug ipv6 ospf hello command, 215, 217
 debug ipv6 ospf packet command, 215, 217
 debug ipv6 rip command, 212, 214
 debug ppp authentication command, 228, 230
 debugging

- connectivity, 53–55
- OSPF, 98–100
- PPP, 230–232, 231–232

 default-router command, 187
 defaults

- administrative distances, 65
- routing, 63–65, 64

 delay command, 79
 delete command, 33
 delete flash command, 33
 deleted state in LMI, 239
 deleting configurations, 38
 demarcs, 221
 denial of service (DoS) attacks

- detection and prevention, 141
- types, 139

 deny command, 143–145, 147–149, 152–155
 deny any any command, 154–155
 deny host command, 144
 deny tcp command, 148–149
 deny tcp any host command, 149–151
 description command, 14
 destination network parameter, 62
 destination URL policy management, 140
 DHCPv6 server configuration, 204–205
 dialer-group command, 234
 dialer pool command, 233–234
 Diffusing Update Algorithm (DUAL), 207
 digital subscriber line (DSL), 223
 Dijkstra algorithm, 90
 dir command, 33
 Direct Sequence Spread Spectrum (DSSS)

- technique, 181

 disable command, 5
 disconnect command, 45, 47
 discontinuous networks

- EIGRP, 81
- RIPv1 vs. RIPv2, 70

 distance command, 66
 distance-vector protocols, 69
 DLCIs (Data Link Connection Identifiers), 237–238, 238

DNS (Domain Name System), 50
 dns-server command, 204–205
 domain-name command, 204–205
 Domain Name System (DNS), 50
 DoS (denial of service) attacks

- detection and prevention, 141
- types, 139

 dot1q command, 128
 DSL (digital subscriber line), 223
 DSSS (Direct Sequence Spread Spectrum)

- technique, 181

 DUAL (Diffusing Update Algorithm), 207
 dual stacking in IPv6 migration, 210–211
 dynamic command, 126–127
 dynamic NAT, 164, 166–167
 dynamic port mapping, 141
 dynamic routing, 58

- IGRP
 - default ADs, 66
 - enhanced. *See* EIGRP (Enhanced IGRP)
- RIP. *See* RIP (Routing Information Protocol)

E

Edit Interface/Connection tab, 191, 191, 256, 256
 editing features in command-line interface, 6–8
 EIA/TIA-232-C standard, 225
 802.11 standards, 178–182, 180–181
 EIGRP (Enhanced IGRP), 76

- configuration, 77, 274–275, 274–275
- default ADs, 66
- discontiguous networks, 81
- load balancing, 81–85
- maximum paths and hop counts, 78–79
- propagations, 77–78
- redistribution, 79–80
- route authentication, 85–86
- verifying, 86–90

 EIGRPv6 protocol, 207–208
 enable command

- layer 2 switching, 104
- for modes, 5
- STM, 250–251

 enable password command, 10
 enable secret command, 10
 enabling

- OSPF, 92
- RIP, 68

encapsulation

- Frame Relay, 236–237, 247
- PPP, 228–231, 228–229, 231
- VLANs, 130–131
- WANs, 221

encapsulation command, 127, 221

encapsulation frame-relay command, 236, 241–242, 247

encapsulation ppp command, 226–227

encryption, password, 11–12

Enhanced IGRP. *See* EIGRP (Enhanced IGRP)

eq command, 147

erase command, 33

erase startup-config command, 17–18, 38

erasing configurations, 38

Esc+B command, 6

Esc+F command, 6

ESSs (extended service sets), 182–184, 183

EtherChannel configuration, 112–114

exec banners, 9–10

EXEC mode, 4–5

exec-timeout command, 12

exit command

- access lists, 153
- modes, 5
- STM, 251–252
- Telnet, 45, 47

exit interface parameter, 62

Express Setup settings, 197, 197

extended access lists, 142, 146–151

extended service sets (ESSs), 182–184, 183

extended VLANs, 123

external EIGRP, 66

F

feasible distances, 85

Federal Communications Commission (FCC), 177–178

filter tables, 102–103

firewalls, 138–141, 139

5GHz wireless, 181–182, 181

flash memory

- managing, 259–262, 259–262
- routers, 23
- verifying, 30–31

format command, 33

forward/filter tables, 103

Frame Relay, 235, 235–236

- congestion control, 240
- description, 222
- DLCIs in, 237–238, 238
- encapsulation, 236–237, 247
- implementing, 241
- LMI in, 238–239
- single interfaces, 241–242
- subinterfaces, 242–243
- troubleshooting, 247–248, 248
- verifying, 243–247

frame-relay interface-dlci command, 237–238, 241

frame-relay lmi-type command, 238–239, 241

frame-relay map command, 237, 248

G

gateways of last resort, 64, 64

global addresses in LMI, 239

global configuration mode, 5

global NAT names, 164

guest-mode command, 187

H

HDLC (High-Level Data Link Control)

- protocol
- description, 223
- operation, 224, 225

help features, 6–8

HFC (hybrid fibre-coaxial), 223

High-Level Data Link Control (HDLC)

- protocol
- description, 223
- operation, 224, 225

history, command, 6

holddown timers, 67

holdtime information, 40–41

hop counts

- EIGRP, 78–79
- RIPv1 vs. RIPv2, 69

host command, 147, 152, 154

host tables, 48–50

hostname command

- access lists, 143, 147, 152
- PPP, 227

284 hostnames – IP access lists

routers, 9
 SSH, 13
 wireless devices, 187
 hostnames
 host tables for, 48–50
 resolving, 48–51
 setting, 9
 hybrid fibre-coaxial (HFC), 223
 HyperTerminal program, 27

I

IARP (Inverse ARP), 237
 IBSSs (infrastructure basic service sets), 182, 183
 ICMP (Internet Control Message Protocol), 140
 IEEE (Institute of Electrical and Electronics Engineers) standards, 176, 178–182, 180–181
 IFS (IOS file system), 38–39
 IGRP (Interior Gateway Routing Protocol)
 default ADs, 66
 enhanced. *See* EIGRP (Enhanced IGRP)
 implicit denies, 141
 inactive state in LMI, 239
 incoming banners, 9–10
 Industrial, Scientific, and Medical (ISM) bands, 177
 infrastructure basic service sets (IBSSs), 182, 183
 infrastructure-ssid command, 187
 inside NAT names, 164
 Institute of Electrical and Electronics Engineers (IEEE) standards, 176, 178–182, 180–181
 Integrated Services Digital Network (ISDN), 222
 inter-VLAN routing, 130–131
 interface command
 EIGRP, 85
 Frame Relay, 236, 241–242
 IPv6, 209
 modes, 5
 PPP, 226
 PPPoE, 233
 routers, 14
 SDM, 250
 WANs, 221
 wireless devices, 187
 interface ethernet command, 14
 interface multipoint command, 242
 interface point-to-point command, 242
 interface port-channel command, 112–114
 interface range command, 109–110, 124–125
 interface serial command, 14
 interface vlan command, 104
 interfaces
 CDP for, 43–44
 router, 14–18
 traffic information for, 43
 Interior Routing Gateway Protocol
 default ADs, 66
 enhanced. *See* EIGRP (Enhanced IGRP)
 internal routers, 22–23, 138, 139
 Internet Control Message Protocol (ICMP), 140
 Internet Engineering Task Force (IETF)
 encapsulation, 236–237, 242
 Internet protocols
 IP addresses
 IPv6 protocol. *See* IPv6 protocol
 mismatched, 231–232, 232
 NAT. *See* Network Address Translation (NAT)
 routing. *See* IP routing
 Version 6. *See* IPv6 protocol
 Internetwork Operating System. *See* IOS (Internetwork Operating System)
 intrusion detection, 140
 Inverse ARP (IARP), 237
 IOS (Internetwork Operating System)
 backing up, 31–32
 command-line interface, 6–8
 flash memory
 managing, 259–262, 259–262
 verifying, 30–31
 restoring, 32
 upgrading, 32
 IOS file system (IFS), 38–39
 IOS firewall, 140–141
 ip access-group command, 143, 147, 151
 ip access-group in command, 151
 ip access-group out command, 151
 ip access-list command, 151–152
 ip access-list standard command, 152
 IP access lists, 141–142
 extended, 146–151
 monitoring, 158–160
 standard, 142–146

- for Telnet, 145–146
 - wildcards with, 145
 - ip address command, 14, 187, 209–210
 - ip address mask command, 241
 - ip address negotiated command, 234
 - IP addresses
 - IPv6 protocol. *See* IPv6 protocol
 - mismatched, 231–232, 232
 - NAT. *See* Network Address Translation (NAT)
 - ip authentication key-chain command, 85
 - ip authentication mode command, 85
 - ip classless command, 63
 - ip default-gateway command, 104–105
 - ip default-network command, 64
 - ip dhcp excluded-address command, 187
 - ip dhcp pool command, 187, 258
 - ip domain-lookup command, 48
 - ip domain-name command, 12–13, 49
 - ip host command, 48–49
 - ip http command, 251–252
 - ip interface command, 15
 - ip name-server command, 49
 - ip nat inside command, 165–167
 - ip nat outside command, 166–167
 - ip nat pool command, 166–167
 - ip nat statistics command, 168, 170
 - ip nat translation command, 168–169
 - ip rip authentication command, 70
 - ip rip mode command, 70
 - ip route command, 61–62
 - IP routing, 58
 - basics, 58–60, 59
 - default, 63–65, 64
 - protocols
 - administrative distances, 65–66
 - RIP, 66–73
 - static, 61–62
 - IP spoofing, 140
 - ip ssh command, 12–13
 - IP Unnumbered option, 268
 - ipv6 address command, 203, 209–211
 - ipv6 dhcp pool command, 204–205
 - ipv6 dhcp server command, 204–205
 - ipv6 eigrp command, 207–208
 - ipv6 ospf command, 208–209
 - IPv6 protocol, 200
 - addresses, 201–202, 201
 - configuration, 204–205
 - EIGRPv6, 207–208
 - migrating to, 209–210
 - 6to4 tunneling, 211–212, 211
 - dual stacking, 210–211
 - need for, 200–201
 - OSPFv3, 208–209
 - RIPng, 206–207
 - shortened expressions, 202
 - verifying
 - OSPFv3, 215–217
 - RIPng, 212–215
 - ipv6 rip command, 206–207
 - ipv6 router eigrp command, 207–208
 - ipv6 router ospf command, 208–209
 - ipv6 router rip command, 206–207
 - ipv6 unicast-routing command, 203, 209–210
 - ISDN (Integrated Services Digital Network), 222
 - ISL command, 128
 - ISM (Industrial, Scientific, and Medical) bands, 177
 - ITU-T format, 239
-
- ## J
- Java applet blocking, 141
-
- ## K
- keepalives, 238
 - key chain command
 - EIGRP, 85
 - RIPv2, 70
 - key command
 - EIGRP, 86
 - RIPv2, 70
 - key-string command
 - EIGRP, 86
 - RIPv2, 70
 - keys, wireless networks, 185–186
-
- ## L
- LANs (Local Area Networks)
 - SDM for, 266–272, 266–272
 - VLANs. *See* VLANs (virtual LANs)

286 LAPB (Link Accessed Procedure, Balanced) – multicasts

- LAPB (Link Accessed Procedure, Balanced), 222
- LAPD (Link Access Procedure, D channel), 222
- layer 2 switching, 102
 - benefits, 102–103
 - configuration, 104–105
 - functions, 103–104
 - security, 105–106
 - static MAC addresses, 106–107
 - STP in. *See* STP (Spanning Tree Protocol)
- LCP (Link Control Protocol), 225–226
- licensing for wireless technologies, 177–178, 177
- line command
 - for modes, 5
 - passwords, 10
- line console command
 - STM, 251–252
 - wireless devices, 187
- line vty command
 - SSH, 13
 - STM, 252
 - wireless devices, 187
- Link Access Procedure, D channel (LAPD), 222
- Link Accessed Procedure, Balanced (LAPB), 222
- Link Control Protocol (LCP), 225–226
- LMI (Local Management Interface), 238–239
- load balancing, 81–85
- load command, 79
- Local Area Networks (LANs)
 - SDM for, 266–272, 266–272
 - VLANs. *See* VLANs (virtual LANs)
- local loops, 221
- Local Management Interface (LMI), 238–239
- local NAT names, 164
- logging synchronous command, 12, 187
- login banners, 9–10
- login command, 10
- login local command, 251–252
- loops
 - avoiding, 103
 - local, 221
- mac access-group command, 154–155
- mac access-list command, 154
- mac-address option, 105
- man-in-the-middle attacks, 140
- management of routers
 - CDP for, 40–44
 - configuration backups and restoration
 - backups, 35–37
 - erasing, 38
 - IFS for, 38–39
 - restoring, 37–38
 - SDM for, 262–266, 263–265
 - hostname resolution, 48–51
 - IOS backups and restoration, 30
 - backups, 31–32
 - flash memory management, 259–262, 259–262
 - flash memory verification, 30–31
 - restoring and upgrading, 32
 - network connectivity, 52–55
 - Telnet for, 44–48
- map command, 237, 243
- mappings
 - dynamic port, 141
 - Frame Relay, 248, 248
- mask parameter, 62
- maximum option, 105
- maximum paths, 78–79
- maximum-paths command, 78
- Maximum Transmission Units (MTUs), 79–80
- Media Access Control (MAC) addresses
 - static, 106–107
 - switches, 115–116
 - wireless network authentication, 184–185
- metric command, 79
- metric maximum-paths command, 78–79
- migrating to IPv6 protocol, 209–210
 - 6to4 tunneling, 211–212, 211
 - dual stacking, 210–211
- mini-OS component, 23
- mismatched encapsulation, 231, 231
- mismatched IP addresses, 231–232, 232
- MKDIR command, 33
- mls qos command, 135–136
- mode command, 109
- more command, 33
- MOTD banners, 9–10
- MPLS (MultiProtocol Label Switching), 224
- MTU command, 79
- MTUs (Maximum Transmission Units), 79–80
- multicasts, 238

M

- MAC (Media Access Control) addresses
 - static, 106–107
 - switches, 115–116
 - wireless network authentication, 184–185

multiple devices, Telnet with, 45–46
 multiplexing, 242
 multipoint subinterfaces, 243
 MultiProtocol Label Switching (MPLS), 224

N

name command, 123
 named access lists, 142, 151–153
 names
 NAT, 164
 resolving, 48–51
 VLANs, 123
 NAT. *See* Network Address Translation (NAT)
 native VLAN modification, 129–130
 NCP (Network Control Protocol), 225–226
 neighbors, CDP, 41–43
 Network Address Translation (NAT), 141, 162
 configuration
 dynamic, 166–167
 overloading, 167–168
 SDM for, 170–173, 171–172
 static, 165
 verifying, 168–170
 names, 164
 types, 163–164
 uses, 162–163, 163
 network command
 EIGRP, 77
 OSPF, 92
 RIP, 68
 RIPv2, 70
 wireless devices, 187
 network connectivity, 52
 debugging, 53–55
 ping command, 52–53
 processes, 55
 traceroute command, 53
 Network Control Protocol (NCP), 225–226
 network reconnaissance attacks, 140
 Network Time Protocol (NTP), 156
 next hop address parameter, 62
 no auto-summary command, 81
 no cdp enable command, 40
 no cdp run command, 40
 no ip domain-lookup command, 51
 no ip host command, 50

no login command, 45
 no service password-encryption command, 12
 no shutdown command
 EIGRP, 207–208
 routers, 14
 STM, 250–251
 wireless devices, 187
 nonegotiate command, 126–127
 NTP (Network Time Protocol), 156
 NVRAM (non-volatile RAM)
 copying configuration to, 36–37
 displaying, 38–39
 for startup-config file, 26

O

OFDM (Orthogonal Frequency Division Multiplexing) technique, 181
 open-access mode, 184
 OSPF (Open Shortest Path First) protocol
 configuration, 91
 areas, 92
 debugging, 98–100
 enabling, 92
 SDM, 275–277, 276–277
 verifying, 92–98
 default ADs, 66
 overview, 90–91
 vs. RIP, 90–91
 OSPFv3 protocol
 overview, 208–209
 verifying, 215–217
 outside NAT names, 164
 overloading NAT, 164, 167–168

P

packet sniffer attacks, 140
 pairwise temporal keys, 186
 passive-interface command
 EIGRP, 77–78
 RIP, 69
 passive interfaces, 273
 passive state in EIGRP, 88
 password attacks, 140
 password command, 10, 187, 227

288 passwords – registers

passwords

- encrypting, 11–12
- recovering, 26–27
- SDM, 253
- Secure Shell, 12–14
- setting, 10–12
- Telnet, 45

PAT (Port Address Translation), 164, 167–168

paths, EIGRP, 78–79

peer route authentication, 141

per-user firewalls, 140

Per-VLAN Spanning-Tree (PVST), 116

perimeters, 138, 139

periodic command, 157

permanent parameter, 62

permit command, 143, 147, 152–155

phone calls in VLANs, 134–136

ping command

- network connectivity, 52–53
- STM, 250–251

ping of death attacks, 139

pipes, 8

Point-to-Point Protocol. *See* PPP (Point-to-Point Protocol)

Point-to-Point Protocol over Ethernet (PPPoE)

- configuration, 233–234
- description, 223

point-to-point subinterfaces, 243

policy-based, multi-interface filtering, 141

POPs (points of presence), 221

Port Address Translation (PAT), 164, 167–168

port redirection attacks, 140

PortFast feature, 109–110

ports and port numbers

- access lists, 153–156
- CDP for, 43–44
- dynamic mapping, 141
- VLANs, 124–130, 134

POST (power-on self test), 23

PPP (Point-to-Point Protocol), 225–226, 226

- authentication, 227–230
- configuration, 226–227
- debugging, 230–232, 231–232
- description, 223
- encapsulation, 228–231, 228–229, 231

ppp authentication command, 227, 234

ppp chap command, 234

PPPoE (Point-to-Point Protocol over Ethernet)

- configuration, 233–234
- description, 223

pppoe-client command, 233–234

pppoe enable command, 233–234

pppoe max-sessions command, 233

Pre-Shared Key (PSK), 185–186

prefix-delegation command, 204–205

priority fields in VLANs, 134

privilege level command, 252

privileged mode

- defined, 4
- entering, 28
- moving between, 5

processes, connectivity, 55

propagations

- EIGRP, 77–78
- RIP, 69

protocol command, 147

protocols. *See specific protocols by name*

PSK (Pre-Shared Key), 185–186

PVST (Per-VLAN Spanning-Tree), 116

PWD command, 33

Q

QoS (Quality of Service), 134

question marks (?) for commands, 7

R

RA (router advertisement) requests, 204

radio frequencies (RF), 176

RAM (random access memory), 23

range command

- STP, 110
- VLANs, 124–125

Rapid Spanning Tree Protocol (RSTP), 112

read-only memory (ROM), 23

recovering passwords, 26–27

redirection attacks, 140

redistribute command, 79–80

redistribution in EIGRP, 79–80

registers, configuration

- boot system commands, 29
- changing values, 24–26
- checking values, 24
- for password recovery, 26–27
- resetting, 28–29

reliability command, 79
 reload command, 18, 26–27
 reloading routers, 28–29
 Request To Send (RTS) signal, 180
 Reset Router option, 266
 resetting configuration registers, 28–29
 resolving host names, 48–51
 restoration
 configuration, 37–38, 262–266, 263–265
 IOS, 32
 RF (radio frequencies), 176
 RIDs (Router IDs), 208
 RIP (Routing Information Protocol), 66–67
 configuration, 272–274, 273
 default ADs, 66
 enabling, 68
 vs. OSPF, 90–91
 propagations, 69
 RIPv2, 69–71
 timers, 67–68
 verifying, 71–73
 RIPng protocol
 overview, 206–207
 verifying, 212–215
 RMDIR command, 33
 ROM (read-only memory), 23
 ROM monitor component, 23
 ROM monitor mode, 27–28
 rommon 1 prompt, 27–28
 root bridges, 108, 118–120
 route authentication, 85–86
 route flush timers, 67
 route invalid timers, 67
 route redistribution, 79–80
 route update timers, 67
 routed protocols, 58
 router advertisement (RA) requests, 204
 router eigrp command, 5, 77–79
 router-id command, 208–209
 Router IDs (RIDs), 208
 router ospf command, 92
 router rip command, 66–70
 router solicitation (RS) requests, 204
 routers
 booting, 2–4, 3, 27
 configuring. *See* configuration
 interfaces for, 14–18
 internal, 22–23, 138, 139
 managing. *See* management of routers
 reloading, 28–29

routing, IP. *See* IP routing
 Routing Information Protocol. *See* RIP
 (Routing Information Protocol)
 routing protocols. *See specific protocols*
 by name
 routing tables, 58
 RS (router solicitation) requests, 204
 RSTP (Rapid Spanning Tree Protocol), 112
 RTS (Request To Send) signal, 180
 running-config file, 17
 for configuration, 36
 for IP access lists, 158, 160
 for PPP, 232
 RXBOOT component, 23

S

SDM (Security Device Manager)
 backups and restores, 262–266, 263–265
 configuration, 250–259, 253–257
 EIGRP, 274–275, 274–275
 NAT, 170–173, 171–172
 OSPF, 275–277, 276–277
 RIP, 272–274, 273
 wireless network, 190–197, 191–197
 flash memory management, 259–262,
 259–262
 LAN and WAN interfaces, 266–272,
 266–272
 Secure Shell (SSH), 12–14
 security, 138
 access lists. *See* access lists
 devices for, 138, 139
 firewalls, 140–141
 layer 2 switching, 105–106
 threats, 139–140
 wireless networks, 184–186
 Security Device Manager. *See* SDM (Security
 Device Manager)
 send-lifetime command, 86
 service password-encryption command, 10,
 227
 Service Set Identifiers (SSIDs), 182–185, 183
 service sets for wireless networks, 182–184,
 183
 sessions, Telnet, 47–48
 setup command, 4
 setup modes, 4
 shared keys, 185–186

290 shortened expressions in IPv6 – static MAC addresses

- shortened expressions in IPv6, 202
- show access-list command, 158–159
- show cdp command, 40–41
- show cdp entry * command, 40, 42
- show cdp interface command, 40, 43
- show cdp neighbors command, 40–41
- show cdp neighbors detail command, 40, 42, 228, 232
- show cdp traffic command, 40, 43
- show controllers command, 19
- show file command, 33–35, 38–39
- show flash command, 25, 30, 34
- show frame command, 243–244
- show frame-relay command, 243
- show frame-relay lmi command, 243–244
- show frame-relay map command, 237, 243, 246, 248
- show frame-relay pvc command, 237, 240, 243, 245
- show history command, 6
- show hosts command, 48–49
- show interface command, 14, 18–19
 - Frame Relay, 243, 245–246
 - PPP, 228–229, 232
 - switches, 114–115
- show interface brief command, 20
- show ip access-list command, 158
- show ip eigrp command, 81–82, 84
- show ip eigrp neighbors command, 86–87
- show ip eigrp topology command, 87–88
- show ip interface command, 15, 19, 72, 158–160
- show ip nat command, 168
- show ip ospf command, 93–95
- show ip ospf database command, 93, 95
- show ip ospf interface command, 93, 95–96
- show ip ospf neighbor command, 93, 96–97
- show ip ospf protocols command, 93
- show ip protocols command, 71–72, 97–98
- show ip route command, 8, 59–60
 - default routes, 65
 - EIGRP, 86
 - OSPF, 93
- show ipv6 interface command, 212, 214
- show ipv6 ospf neighbor command, 215–216
- show ipv6 protocols command, 212–213, 215–216
- show ipv6 rip command, 212–213
- show ipv6 route command, 212–213, 215
- show mac access-group command, 158
- show mac address-table command, 103–104, 115–116
- show processes command, 52, 55
- show protocols command, 19–20
- show running-config command, 8, 17–19
 - configuration, 35–36
 - IP access lists, 158, 160
 - PPP, 232
- show sessions command, 44, 47
- show spanning-tree command, 108, 112, 114, 116–119
- show startup-config command, 17–19, 35–36
- show terminal command, 6
- show users command, 44, 46–48
- show version command, 24–25, 30
- show vlan command, 124, 133
- show vlan privileged command, 135
- show vtp password command, 133
- show vtp status command, 132–133
- shutdown command, 14
- 6to4 tunneling, 211–212, 211
- spanning-tree command, 107–108
- spanning-tree backbonefast command, 111
- spanning-tree bpduguard command, 110
- spanning-tree bpduprotect command, 112
- spanning-tree portfast command, 109–110
- Spanning-Tree Protocol. *See* STP (Spanning Tree Protocol)
- spanning-tree uplinkfast command, 110–111
- spanning-tree vlan priority command, 118, 120
- spanning-tree vlan root priority command, 118, 120
- spanning-tree vlan root secondary command, 118
- specific configuration modes, 5
- spoofing, 140
- SSH (Secure Shell), 12–14
- ssid command, 187
- SSIDs (Service Set Identifiers), 182–185, 183
- Stacheldraht attacks, 139
- standard access lists, 142–146
- startup-config file
 - deleting, 38
 - displaying, 17, 36
 - password recovery, 26
- Stateful IOS Firewall inspection engine, 140
- static command, 106
- static MAC addresses, 106–107

static NAT, 163, 165

static routing, 58, 61–62, 65

status of virtual circuits, 239

STP (Spanning Tree Protocol), 107–108

- EtherChannel, 112–114
- interface range, 110
- operations, 108–109
- PortFast, 109–110
- root bridge selection, 118–120
- switches. *See* switches
- verifying, 114–120

subinterfaces

- Frame Relay, 242–243
- VLANs, 130

subnets and subnetting VLANs, 131

summarization in EIGRP, 81

switch ports

- access lists, 153–156
- VLANs, 124–125

switches

- configuration
 - BackboneFast, 111
 - BPDUFILTER, 110
 - BPDUGuard, 110
 - EtherChannel, 112–114
 - RSTP, 112
 - trunking, 127–128
 - UplinkFast, 110–111
 - verifying, 114–120
- layer 2. *See* layer 2 switching

switchport command, 125

switchport access command, 125–126

switchport mode command, 125–126

switchport nonegotiate command, 114, 126–127

switchport port-security command, 105–106

switchport priority command, 135–136

switchport trunk allowed command, 128

switchport trunk encapsulation command, 127–129

switchport trunk native command, 129

switchport voice vlan command, 134–135

system ID extensions, 117

T

Tab command, 6

TCP SYN flood attacks, 139

telephony, VLANs, 134–136

Telnet protocol, 44–45

- closing sessions, 47–48
- connections, 46, 48
- IP access lists, 145–146
- with multiple devices, 45–46
- passwords, 13–14, 45
- users, 46–47

Teredo, 212

terminal history size command, 6

terminal monitor command, 72

TFN (Tribe Flood Network) attacks, 139

TFTP (Trivial File Transfer Protocol), 31–32, 36–37

threats, security, 139–140

time-based access lists, 141, 156–157

time-range command, 156–157

timers

- CDP for, 40–41
- RIP, 67–68

timers command, 67–68

toll networks, 221

traceroute command, 52–53

traffic information, CDP for, 43

transport input command, 13, 252

Tribe Flood Network (TFN) attacks, 139

Trivial File Transfer Protocol (TFTP), 31–32, 36–37

Trojan horse attacks, 140

troubleshooting

- connectivity, 53–55
- Frame Relay, 247–248, 248
- show ip protocols for, 71–72

trunk command, 126–127

trunk ports, 126–130

trust exploitation attacks, 140

tunnel destination command, 209, 211

tunnel mode command, 209, 211

tunnel source command, 209, 211

tunneling in IPv6 migration, 211–212, 211

2.4GHz wireless, 179–181, 180–181

U

undebug command, 52, 54

unified wireless security solution, 184–186

UNII (Unlicensed National Information Infrastructure), 177, 177, 181, 181

upgrading IOS, 32

UplinkFast feature, 109–111

292 user EXEC mode – WPA (Wi-Fi Protected Access)

user EXEC mode, 4–5
 username command, 227, 251–252
 usernames
 PPP, 227
 SDM, 252–253
 users, Telnet, 46–48

V

V.24 standard, 225
 V.35 standard, 225
 variable-length subnet masks (VLSMs), 70
 variance command, 82, 85
 verifying
 EIGRP, 86–90
 flash memory, 30–31
 Frame Relay, 243–247
 NAT, 168–170
 OSPF, 92–98
 OSPFv3, 215–217
 PPP encapsulation, 228–230, 228–229
 RIP, 71–73
 RIPng, 212–215
 router, 36
 switches, 114–120
 VLANs, 124
 version command, 70
 version 2 command, 70–71
 vertical bars (|) for pipes, 8
 violation option, 105
 virtual LANs. *See* VLANs (virtual LANs)
 vlan command, 122–123
 vlan priority command, 108
 VLAN Trunk Protocol (VTP), 131–133
 VLANs (virtual LANs), 122
 configuration, 122–123
 inter-VLAN routing, 130–131
 switch port assignments, 124–125
 trunk ports, 126–130
 verifying, 124
 voice, 134–136
 VTP for, 131–133
 VLSMs (variable-length subnet masks), 70
 voice configuration, 134–136

voice traversal with firewalls, 140
 VTP (VLAN Trunk Protocol), 131–133
 vtp domain command, 131–133
 vtp mode client command, 133
 vtp mode server command, 131–132
 vtp password command, 132–133
 VTY
 access lists for, 145–146
 passwords for, 45
 vty command, 13

W

WANs (wide area networks), 220–221
 Frame Relay. *See* Frame Relay
 HDLC for, 224, 225
 PPP for, 225–226, 226
 authentication, 227–230
 configuration, 226–227
 debugging, 230–232, 231–232
 encapsulation, 228–231, 228–229, 231
 PPPoE for, 233–234
 SDM for, 266–272, 266–272
 support, 221–224
 terminology, 221
 WEP (Wired Equivalency Protocol), 184–185
 Wi-Fi Alliance, 177
 Wi-Fi Protected Access (WPA), 185–186
 wildcard
 for access lists, 145
 for default routes, 63
 Wired Equivalency Protocol (WEP), 184–185
 Wireless Express Security screen, 193, 193
 Wireless Interfaces screen, 194–195, 194–195
 wireless networks, 175
 802.11 standards, 178–182, 180–181
 configuration
 IOS, 186–190
 SDM/HTTP, 190–197, 191–197
 overview, 176–178, 177
 security, 184–186
 service sets, 182–184, 183
 Wireless Security settings, 196, 196
 WPA (Wi-Fi Protected Access), 185–186