

Index

Note to the Reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

A

- accept-lifetime command, 86
- access command, 126
- access-class command, 146
- access-list command, 143–144, 146–148, 166–168
- access-list deny command, 143–145, 147–148
- access-list deny host command, 144
- access-list deny tcp command, 148–149
- access-list deny tcp any host command, 149–151
- access-list permit command, 146–147
- access-list permit ip any any command, 151
- access lists, 141–142
 - IP
 - extended, 146–151
 - monitoring, 158–160
 - standard, 142–146
 - for Telnet, 145–146
 - wildcards with, 145
 - named, 151–153
 - switch port, 153–156
 - time-based, 156–157
- active state
 - EIGRP, 88
 - LMI, 239
- AD (administrative distances)
 - IP routing, 65–66
 - static routing, 62
- ad hoc networking, 182
- Add DHCP Pool dialog box, 257, 257
- addresses
 - IP
 - IPv6 protocol. *See* IPv6 protocol
 - mismatched, 231–232, 232
 - NAT. *See* Network Address Translation (NAT)
 - IPv6 protocol, 201–202, 201
 - learning, 103
 - MAC, 106–107
 - static, 106–107
 - switches, 115–116
 - wireless network authentication, 184–185
- administrative distances (ADs)
 - IP routing, 65–66
 - static routing, 62
- Advanced NAT configuration, 170
- AES (Advanced Encryption Standard), 186
- agencies for wireless technologies, 176–177
- aging option, 105
- ANSI format, 239
- any command, 143, 147, 152, 154–155
- applet blocking, 141
- Application layer attacks, 139
- Application-Specific Integrated Circuits (ASICs), 102–103
- areas, OSPF, 92
- Asynchronous Transfer Mode (ATM), 224
- authentication
 - EIGRP, 85–86
 - peer route, 141
 - PPP, 227–230
 - RIPv1 vs. RIPv2, 70
 - wireless networks, 184–185
- authentication-open command, 187
- authentication proxy, 140
- auto-summarization, 81
- autorouter attacks, 139

B

- BackboneFast feature, 109, 111
- backdoor attacks, 139
- Backspace command, 6
- backups
 - IOS, 31–32
 - router, 35–37
 - SDM, 262–266, 263–265
- bandwidth command, 14, 79
- banner command, 9–10
- bars (|) for pipes, 80
- base MAC addresses, 116
- Basic NAT Wizard, 170–172, 171

basic service sets (BSSs), 182, 183
bit-oriented protocols, 224
block sizes with wildcards, 145
blocking applets, 141
boot command, 29
booting
 commands, 29
 configuration modes, 4–5
 editing and help features, 6–8
 routers, 2–4, 3, 27
 setup modes, 4
bootstrap protocols, 22
BPDUFilter feature, 109–110
BPDUGuard feature, 109–110
breaks, 27
bridges, 108, 118–120
brute force attacks, 140
BSSs (basic service sets), 182, 183
byte-oriented protocols, 224

C

cabling, 223
Carrier Sense Multiple Access with Collision Detect (CSMA/CD), 180, 180
Catalyst switches. *See* switches
CBAC (context-based access control), 140
CCMP (Counter Mode Cipher Block Chaining-Message Authentication Code (CBC-MAC) Protocol), 186
CD command, 33
CDP (Cisco Discovery Protocol), 40
 neighbor information, 41–43
 port and interface information, 43–44
 timers and holdtime information, 40–41
 traffic information, 43
 VLAN telephony, 134–136
cdp enable command, 40
cdp holdtime command, 40–41
cdp timer command, 40–41
central office (CO), 221
Challenge Handshake Authentication Protocol (CHAP), 230
channel-group command, 113
channel-protocol command, 113
CHAP (Challenge Handshake Authentication Protocol), 230
Cisco Discovery Protocol (CDP), 40
 neighbor information, 41–43
 port and interface information, 43–44
 timers and holdtime information, 40–41
 traffic information, 43
 VLAN telephony, 134–136
Cisco encapsulation, 236, 242
Cisco format in LMI, 239
Cisco IOS. *See* IOS (Internetwork Operating System)
class of service (CoS), 134–136
classful routing, 63, 68
clear counters command, 14, 16
clear line command, 45, 48
Clear To Send (CTS) signal, 180
clearing Telnet connections, 48
CLI (command-line interface), 6–8
clock command, 7
clock rate command, 14
clocking, 14
closing Telnet sessions, 47–48
CO (central office), 221
collisions, 180
command-line interface (CLI), 6–8
config-register command, 25, 27–28
configuration
 backing up
 IOS, 31–32
 router, 35–37
 SDM, 262–266, 263–265
 banners, 9–10
 copying
 to NVRAM, 36–37
 to TFTP server, 37
 EIGRP, 77, 274–275, 274–275
 erasing, 38
 hostnames, 9
 IFS for, 38–39
 IPv6 protocol, 204–205
 layer 2 switching, 104–105
 modes, 4–5
 NAT
 dynamic, 166–167
 overloading, 167–168
 SDM for, 170–173, 171–172
 static, 165
 verifying, 168–170
 OSPF, 91
 areas, 92
 debugging, 98–100

- enabling, 92
 - SDM, 275–277, 276–277
 - verifying, 92–98
 - passwords, 10–14
 - PPP, 226–227
 - PPPoE, 233–234
 - restoring, 37–38, 262–266, 263–265
 - RIP, 272–274, 273
 - router interfaces, 14–18
 - switches. *See* switches
 - verifying. *See* verifying
 - VLANs, 122–123
 - inter-VLAN routing, 130–131
 - switch port assignments, 124–125
 - trunk ports, 126–130
 - verifying, 124
 - voice, 134–136
 - VTP, 131–133
 - wireless networks
 - IOS, 186–190
 - SDM/HTTP, 190–197, 191–197
 - configuration registers
 - boot system commands, 29
 - changing values, 24–26
 - checking values, 24
 - for password recovery, 26–27
 - resetting, 28–29
 - configure terminal command
 - Frame Relay, 241, 247
 - modes, 5
 - PPP, 226–227
 - STM, 250–251
 - WANs, 221–222
 - confreg command, 27
 - congestion, 240
 - connections, Telnet, 46, 48
 - connectivity, 52
 - debugging, 53–55
 - ping command, 52–53
 - processes, 55
 - traceroute command, 53
 - content addressable memory, 115
 - context-based access control (CBAC), 140
 - convergence, OSPF, 91
 - copy command, 31–33
 - copy flash tftp command, 30–32
 - copy running-config command, 17
 - copy running-config startup-config command, 17, 29, 35–36, 187
 - copy running-config tftp command, 37
 - copy start run command, 27
 - copy startup-config running-config command, 28
 - copy tftp flash command, 31–32
 - copy tftp running-config command, 37
 - copy tftp startup-config command, 37
 - CoS (class of service), 134–136
 - Counter Mode Cipher Block Chaining-Message Authentication Code (CBC-MAC) Protocol (CCMP), 186
 - CPE (customer premises equipment), 221
 - Create Connection screen, 192
 - Create NAT Configuration screen, 171, 171
 - crypto key generate rsa command, 12–13
 - crypto pki command, 258
 - CSMA/CD (Carrier Sense Multiple Access with Collision Detect), 180, 180
 - Ctrl+A command, 6
 - Ctrl+Break command, 27
 - Ctrl+D command, 6
 - Ctrl+E command, 6
 - Ctrl+F command, 6
 - Ctrl+N command, 6
 - Ctrl+P command, 6
 - Ctrl+R command, 6
 - Ctrl+Shift+6 command, 45
 - Ctrl+U command, 6
 - Ctrl+W command, 6
 - Ctrl+Z command, 6
 - CTS (Clear To Send) signal, 180
 - customer premises equipment (CPE), 221
-
- ## D
- data encapsulation
 - Frame Relay, 236–237
 - PPP, 228–231, 228–229, 231
 - VLANs, 130–131
 - WANs, 221
 - Data Link Connection Identifiers (DLCIs), 237–238, 238
 - debug command, 52–54
 - debug all command, 54
 - debug eigrp packet command, 87–88
 - debug frame lmi command, 243, 246–247
 - debug ip eigrp events command, 89
 - debug ip eigrp notification command, 87, 89
 - debug ip nat command, 168–169
 - debug ip ospf adj command, 100

- debug ip ospf hello command, 99
 - debug ip ospf packet command, 98–99
 - debug ip rip command, 55, 71–73
 - debug ipv6 ospf hello command, 215, 217
 - debug ipv6 ospf packet command, 215, 217
 - debug ipv6 rip command, 212, 214
 - debug ppp authentication command, 228, 230
 - debugging
 - connectivity, 53–55
 - OSPF, 98–100
 - PPP, 230–232, 231–232
 - default-router command, 187
 - defaults
 - administrative distances, 65
 - routing, 63–65, 64
 - delay command, 79
 - delete command, 33
 - delete flash command, 33
 - deleted state in LMI, 239
 - deleting configurations, 38
 - demarcs, 221
 - denial of service (DoS) attacks
 - detection and prevention, 141
 - types, 139
 - deny command, 143–145, 147–149, 152–155
 - deny any any command, 154–155
 - deny host command, 144
 - deny tcp command, 148–149
 - deny tcp any host command, 149–151
 - description command, 14
 - destination network parameter, 62
 - destination URL policy management, 140
 - DHCPv6 server configuration, 204–205
 - dialer-group command, 234
 - dialer pool command, 233–234
 - Diffusing Update Algorithm (DUAL), 207
 - digital subscriber line (DSL), 223
 - Dijkstra algorithm, 90
 - dir command, 33
 - Direct Sequence Spread Spectrum (DSSS)
 - technique, 181
 - disable command, 5
 - disconnect command, 45, 47
 - discontiguous networks
 - EIGRP, 81
 - RIPv1 vs. RIPv2, 70
 - distance command, 66
 - distance-vector protocols, 69
 - DLCLs (Data Link Connection Identifiers), 237–238, 238
 - DNS (Domain Name System), 50
 - dns-server command, 204–205
 - domain-name command, 204–205
 - Domain Name System (DNS), 50
 - DoS (denial of service) attacks
 - detection and prevention, 141
 - types, 139
 - dot1q command, 128
 - DSL (digital subscriber line), 223
 - DSSS (Direct Sequence Spread Spectrum)
 - technique, 181
 - DUAL (Diffusing Update Algorithm), 207
 - dual stacking in IPv6 migration, 210–211
 - dynamic command, 126–127
 - dynamic NAT, 164, 166–167
 - dynamic port mapping, 141
 - dynamic routing, 58
 - IGRP
 - default ADs, 66
 - enhanced. *See* EIGRP (Enhanced IGRP)
 - RIP. *See* RIP (Routing Information Protocol)
-
- ## E
- Edit Interface/Connection tab, 191, 191, 256, 256
 - editing features in command-line interface, 6–8
 - EIA/TIA-232-C standard, 225
 - 802.11 standards, 178–182, 180–181
 - EIGRP (Enhanced IGRP), 76
 - configuration, 77, 274–275, 274–275
 - default ADs, 66
 - discontiguous networks, 81
 - load balancing, 81–85
 - maximum paths and hop counts, 78–79
 - propagations, 77–78
 - redistribution, 79–80
 - route authentication, 85–86
 - verifying, 86–90
 - EIGRPv6 protocol, 207–208
 - enable command
 - layer 2 switching, 104
 - for modes, 5
 - STM, 250–251
 - enable password command, 10
 - enable secret command, 10
 - enabling
 - OSPF, 92
 - RIP, 68

encapsulation

- Frame Relay, 236–237, 247
- PPP, 228–231, 228–229, 231
- VLANs, 130–131
- WANs, 221

encapsulation command, 127, 221

encapsulation frame-relay command, 236, 241–242, 247

encapsulation ppp command, 226–227

encryption, password, 11–12

Enhanced IGRP. *See* EIGRP (Enhanced IGRP)

eq command, 147

erase command, 33

erase startup-config command, 17–18, 38

erasing configurations, 38

Esc+B command, 6

Esc+F command, 6

ESSs (extended service sets), 182–184, 183

EtherChannel configuration, 112–114

exec banners, 9–10

EXEC mode, 4–5

exec-timeout command, 12

exit command

- access lists, 153
- modes, 5
- STM, 251–252
- Telnet, 45, 47

exit interface parameter, 62

Express Setup settings, 197, 197

extended access lists, 142, 146–151

extended service sets (ESSs), 182–184, 183

extended VLANs, 123

external EIGRP, 66

F

feasible distances, 85

Federal Communications Commission (FCC), 177–178

filter tables, 102–103

firewalls, 138–141, 139

5GHz wireless, 181–182, 181

flash memory

- managing, 259–262, 259–262
- routers, 23
- verifying, 30–31

format command, 33

forward/filter tables, 103

Frame Relay, 235, 235–236

- congestion control, 240
- description, 222
- DLCIs in, 237–238, 238
- encapsulation, 236–237, 247
- implementing, 241
- LMI in, 238–239
- single interfaces, 241–242
- subinterfaces, 242–243
- troubleshooting, 247–248, 248
- verifying, 243–247

frame-relay interface-dlci command, 237–238, 241

frame-relay lmi-type command, 238–239, 241

frame-relay map command, 237, 248

G

gateways of last resort, 64, 64

global addresses in LMI, 239

global configuration mode, 5

global NAT names, 164

guest-mode command, 187

H

HDLC (High-Level Data Link Control)

- protocol
- description, 223
- operation, 224, 225

help features, 6–8

HFC (hybrid fibre-coaxial), 223

High-Level Data Link Control (HDLC)

- protocol
- description, 223
- operation, 224, 225

history, command, 6

holddown timers, 67

holdtime information, 40–41

hop counts

- EIGRP, 78–79
- RIPv1 vs. RIPv2, 69

host command, 147, 152, 154

host tables, 48–50

hostname command

- access lists, 143, 147, 152
- PPP, 227

- routers, 9
 - SSH, 13
 - wireless devices, 187
 - hostnames
 - host tables for, 48–50
 - resolving, 48–51
 - setting, 9
 - hybrid fibre-coaxial (HFC), 223
 - HyperTerminal program, 27
-
- I**
- IARP (Inverse ARP), 237
 - IBSSs (infrastructure basic service sets), 182, 183
 - ICMP (Internet Control Message Protocol), 140
 - IEEE (Institute of Electrical and Electronics Engineers) standards, 176, 178–182, 180–181
 - IFS (IOS file system), 38–39
 - IGRP (Interior Gateway Routing Protocol)
 - default ADs, 66
 - enhanced. *See* EIGRP (Enhanced IGRP)
 - implicit denies, 141
 - inactive state in LMI, 239
 - incoming banners, 9–10
 - Industrial, Scientific, and Medical (ISM) bands, 177
 - infrastructure basic service sets (IBSSs), 182, 183
 - infrastructure-ssid command, 187
 - inside NAT names, 164
 - Institute of Electrical and Electronics Engineers (IEEE) standards, 176, 178–182, 180–181
 - Integrated Services Digital Network (ISDN), 222
 - inter-VLAN routing, 130–131
 - interface command
 - EIGRP, 85
 - Frame Relay, 236, 241–242
 - IPv6, 209
 - modes, 5
 - PPP, 226
 - PPPoE, 233
 - routers, 14
 - SDM, 250
 - WANs, 221
 - wireless devices, 187
 - interface ethernet command, 14
 - interface multipoint command, 242
 - interface point-to-point command, 242
 - interface port-channel command, 112–114
 - interface range command, 109–110, 124–125
 - interface serial command, 14
 - interface vlan command, 104
 - interfaces
 - CDP for, 43–44
 - router, 14–18
 - traffic information for, 43
 - Interior Routing Gateway Protocol
 - default ADs, 66
 - enhanced. *See* EIGRP (Enhanced IGRP)
 - internal routers, 22–23, 138, 139
 - Internet Control Message Protocol (ICMP), 140
 - Internet Engineering Task Force (IETF)
 - encapsulation, 236–237, 242
 - Internet protocols
 - IP addresses
 - IPv6 protocol. *See* IPv6 protocol
 - mismatched, 231–232, 232
 - NAT. *See* Network Address Translation (NAT)
 - routing. *See* IP routing
 - Version 6. *See* IPv6 protocol
 - Internetwork Operating System. *See* IOS (Internetwork Operating System)
 - intrusion detection, 140
 - Inverse ARP (IARP), 237
 - IOS (Internetwork Operating System)
 - backing up, 31–32
 - command-line interface, 6–8
 - flash memory
 - managing, 259–262, 259–262
 - verifying, 30–31
 - restoring, 32
 - upgrading, 32
 - IOS file system (IFS), 38–39
 - IOS firewall, 140–141
 - ip access-group command, 143, 147, 151
 - ip access-group in command, 151
 - ip access-group out command, 151
 - ip access-list command, 151–152
 - ip access-list standard command, 152
 - IP access lists, 141–142
 - extended, 146–151
 - monitoring, 158–160
 - standard, 142–146

- for Telnet, 145–146
 - wildcards with, 145
 - ip address command, 14, 187, 209–210
 - ip address mask command, 241
 - ip address negotiated command, 234
 - IP addresses
 - IPv6 protocol. *See* IPv6 protocol
 - mismatched, 231–232, 232
 - NAT. *See* Network Address Translation (NAT)
 - ip authentication key-chain command, 85
 - ip authentication mode command, 85
 - ip classless command, 63
 - ip default-gateway command, 104–105
 - ip default-network command, 64
 - ip dhcp excluded-address command, 187
 - ip dhcp pool command, 187, 258
 - ip domain-lookup command, 48
 - ip domain-name command, 12–13, 49
 - ip host command, 48–49
 - ip http command, 251–252
 - ip interface command, 15
 - ip name-server command, 49
 - ip nat inside command, 165–167
 - ip nat outside command, 166–167
 - ip nat pool command, 166–167
 - ip nat statistics command, 168, 170
 - ip nat translation command, 168–169
 - ip rip authentication command, 70
 - ip rip mode command, 70
 - ip route command, 61–62
 - IP routing, 58
 - basics, 58–60, 59
 - default, 63–65, 64
 - protocols
 - administrative distances, 65–66
 - RIP, 66–73
 - static, 61–62
 - IP spoofing, 140
 - ip ssh command, 12–13
 - IP Unnumbered option, 268
 - ipv6 address command, 203, 209–211
 - ipv6 dhcp pool command, 204–205
 - ipv6 dhcp server command, 204–205
 - ipv6 eigrp command, 207–208
 - ipv6 ospf command, 208–209
 - IPv6 protocol, 200
 - addresses, 201–202, 201
 - configuration, 204–205
 - EIGRPv6, 207–208
 - migrating to, 209–210
 - 6to4 tunneling, 211–212, 211
 - dual stacking, 210–211
 - need for, 200–201
 - OSPFv3, 208–209
 - RIPng, 206–207
 - shortened expressions, 202
 - verifying
 - OSPFv3, 215–217
 - RIPng, 212–215
 - ipv6 rip command, 206–207
 - ipv6 router eigrp command, 207–208
 - ipv6 router ospf command, 208–209
 - ipv6 router rip command, 206–207
 - ipv6 unicast-routing command, 203, 209–210
 - ISDN (Integrated Services Digital Network), 222
 - ISL command, 128
 - ISM (Industrial, Scientific, and Medical) bands, 177
 - ITU-T format, 239
-
- J**
- Java applet blocking, 141
-
- K**
- keepalives, 238
 - key chain command
 - EIGRP, 85
 - RIPv2, 70
 - key command
 - EIGRP, 86
 - RIPv2, 70
 - key-string command
 - EIGRP, 86
 - RIPv2, 70
 - keys, wireless networks, 185–186
-
- L**
- LANs (Local Area Networks)
 - SDM for, 266–272, 266–272
 - VLANs. *See* VLANs (virtual LANs)

- LAPB (Link Accessed Procedure, Balanced), 222
 - LAPD (Link Access Procedure, D channel), 222
 - layer 2 switching, 102
 - benefits, 102–103
 - configuration, 104–105
 - functions, 103–104
 - security, 105–106
 - static MAC addresses, 106–107
 - STP in. *See* STP (Spanning Tree Protocol)
 - LCP (Link Control Protocol), 225–226
 - licensing for wireless technologies, 177–178, 177
 - line command
 - for modes, 5
 - passwords, 10
 - line console command
 - STM, 251–252
 - wireless devices, 187
 - line vty command
 - SSH, 13
 - STM, 252
 - wireless devices, 187
 - Link Access Procedure, D channel (LAPD), 222
 - Link Accessed Procedure, Balanced (LAPB), 222
 - Link Control Protocol (LCP), 225–226
 - LMI (Local Management Interface), 238–239
 - load balancing, 81–85
 - load command, 79
 - Local Area Networks (LANs)
 - SDM for, 266–272, 266–272
 - VLANs. *See* VLANs (virtual LANs)
 - local loops, 221
 - Local Management Interface (LMI), 238–239
 - local NAT names, 164
 - logging synchronous command, 12, 187
 - login banners, 9–10
 - login command, 10
 - login local command, 251–252
 - loops
 - avoiding, 103
 - local, 221
 - mac access-group command, 154–155
 - mac access-list command, 154
 - mac-address option, 105
 - man-in-the-middle attacks, 140
 - management of routers
 - CDP for, 40–44
 - configuration backups and restoration
 - backups, 35–37
 - erasing, 38
 - IFS for, 38–39
 - restoring, 37–38
 - SDM for, 262–266, 263–265
 - hostname resolution, 48–51
 - IOS backups and restoration, 30
 - backups, 31–32
 - flash memory management, 259–262, 259–262
 - flash memory verification, 30–31
 - restoring and upgrading, 32
 - network connectivity, 52–55
 - Telnet for, 44–48
 - map command, 237, 243
 - mappings
 - dynamic port, 141
 - Frame Relay, 248, 248
 - mask parameter, 62
 - maximum option, 105
 - maximum paths, 78–79
 - maximum-paths command, 78
 - Maximum Transmission Units (MTUs), 79–80
 - Media Access Control (MAC) addresses
 - static, 106–107
 - switches, 115–116
 - wireless network authentication, 184–185
 - metric command, 79
 - metric maximum-paths command, 78–79
 - migrating to IPv6 protocol, 209–210
 - 6to4 tunneling, 211–212, 211
 - dual stacking, 210–211
 - mini-OS component, 23
 - mismatched encapsulation, 231, 231
 - mismatched IP addresses, 231–232, 232
 - MKDIR command, 33
 - mls qos command, 135–136
 - mode command, 109
 - more command, 33
 - MOTD banners, 9–10
 - MPLS (MultiProtocol Label Switching), 224
 - MTU command, 79
 - MTUs (Maximum Transmission Units), 79–80
 - multicasts, 238
-
- M**
- MAC (Media Access Control) addresses
 - static, 106–107
 - switches, 115–116
 - wireless network authentication, 184–185

multiple devices, Telnet with, 45–46
 multiplexing, 242
 multipoint subinterfaces, 243
 MultiProtocol Label Switching (MPLS), 224

N

name command, 123
 named access lists, 142, 151–153
 names
 NAT, 164
 resolving, 48–51
 VLANs, 123
 NAT. *See* Network Address Translation (NAT)
 native VLAN modification, 129–130
 NCP (Network Control Protocol), 225–226
 neighbors, CDP, 41–43
 Network Address Translation (NAT), 141, 162
 configuration
 dynamic, 166–167
 overloading, 167–168
 SDM for, 170–173, 171–172
 static, 165
 verifying, 168–170
 names, 164
 types, 163–164
 uses, 162–163, 163
 network command
 EIGRP, 77
 OSPF, 92
 RIP, 68
 RIPv2, 70
 wireless devices, 187
 network connectivity, 52
 debugging, 53–55
 ping command, 52–53
 processes, 55
 traceroute command, 53
 Network Control Protocol (NCP), 225–226
 network reconnaissance attacks, 140
 Network Time Protocol (NTP), 156
 next hop address parameter, 62
 no auto-summary command, 81
 no cdp enable command, 40
 no cdp run command, 40
 no ip domain-lookup command, 51
 no ip host command, 50

no login command, 45
 no service password-encryption command, 12
 no shutdown command
 EIGRP, 207–208
 routers, 14
 STM, 250–251
 wireless devices, 187
 nonegotiate command, 126–127
 NTP (Network Time Protocol), 156
 NVRAM (non-volatile RAM)
 copying configuration to, 36–37
 displaying, 38–39
 for startup-config file, 26

O

OFDM (Orthogonal Frequency Division
 Multiplexing) technique, 181
 open-access mode, 184
 OSPF (Open Shortest Path First) protocol
 configuration, 91
 areas, 92
 debugging, 98–100
 enabling, 92
 SDM, 275–277, 276–277
 verifying, 92–98
 default ADs, 66
 overview, 90–91
 vs. RIP, 90–91
 OSPFv3 protocol
 overview, 208–209
 verifying, 215–217
 outside NAT names, 164
 overloading NAT, 164, 167–168

P

packet sniffer attacks, 140
 pairwise temporal keys, 186
 passive-interface command
 EIGRP, 77–78
 RIP, 69
 passive interfaces, 273
 passive state in EIGRP, 88
 password attacks, 140
 password command, 10, 187, 227

- passwords
 - encrypting, 11–12
 - recovering, 26–27
 - SDM, 253
 - Secure Shell, 12–14
 - setting, 10–12
 - Telnet, 45
- PAT (Port Address Translation), 164, 167–168
- paths, EIGRP, 78–79
- peer route authentication, 141
- per-user firewalls, 140
- Per-VLAN Spanning-Tree (PVST), 116
- perimeters, 138, 139
- periodic command, 157
- permanent parameter, 62
- permit command, 143, 147, 152–155
- phone calls in VLANs, 134–136
- ping command
 - network connectivity, 52–53
 - STM, 250–251
- ping of death attacks, 139
- pipes, 8
- Point-to-Point Protocol. *See* PPP (Point-to-Point Protocol)
- Point-to-Point Protocol over Ethernet (PPPoE)
 - configuration, 233–234
 - description, 223
- point-to-point subinterfaces, 243
- policy-based, multi-interface filtering, 141
- POPs (points of presence), 221
- Port Address Translation (PAT), 164, 167–168
- port redirection attacks, 140
- PortFast feature, 109–110
- ports and port numbers
 - access lists, 153–156
 - CDP for, 43–44
 - dynamic mapping, 141
 - VLANs, 124–130, 134
- POST (power-on self test), 23
- PPP (Point-to-Point Protocol), 225–226, 226
 - authentication, 227–230
 - configuration, 226–227
 - debugging, 230–232, 231–232
 - description, 223
 - encapsulation, 228–231, 228–229, 231
- ppp authentication command, 227, 234
- ppp chap command, 234
- PPPoE (Point-to-Point Protocol over Ethernet)
 - configuration, 233–234
 - description, 223
 - pppoe-client command, 233–234
 - pppoe enable command, 233–234
 - pppoe max-sessions command, 233
 - Pre-Shared Key (PSK), 185–186
 - prefix-delegation command, 204–205
 - priority fields in VLANs, 134
 - privilege level command, 252
 - privileged mode
 - defined, 4
 - entering, 28
 - moving between, 5
 - processes, connectivity, 55
 - propagations
 - EIGRP, 77–78
 - RIP, 69
 - protocol command, 147
 - protocols. *See specific protocols by name*
 - PSK (Pre-Shared Key), 185–186
 - PVST (Per-VLAN Spanning-Tree), 116
 - PWD command, 33

Q

 - QoS (Quality of Service), 134
 - question marks (?) for commands, 7

R

 - RA (router advertisement) requests, 204
 - radio frequencies (RF), 176
 - RAM (random access memory), 23
 - range command
 - STP, 110
 - VLANs, 124–125
 - Rapid Spanning Tree Protocol (RSTP), 112
 - read-only memory (ROM), 23
 - recovering passwords, 26–27
 - redirection attacks, 140
 - redistribute command, 79–80
 - redistribution in EIGRP, 79–80
 - registers, configuration
 - boot system commands, 29
 - changing values, 24–26
 - checking values, 24
 - for password recovery, 26–27
 - resetting, 28–29

reliability command, 79
 reload command, 18, 26–27
 reloading routers, 28–29
 Request To Send (RTS) signal, 180
 Reset Router option, 266
 resetting configuration registers, 28–29
 resolving host names, 48–51
 restoration

- configuration, 37–38, 262–266, 263–265
- IOS, 32

 RF (radio frequencies), 176
 RIDs (Router IDs), 208
 RIP (Routing Information Protocol), 66–67

- configuration, 272–274, 273
- default ADs, 66
- enabling, 68
- vs. OSPF, 90–91
- propagations, 69
- RIPv2, 69–71
- timers, 67–68
- verifying, 71–73

 RIPng protocol

- overview, 206–207
- verifying, 212–215

 RMDIR command, 33
 ROM (read-only memory), 23
 ROM monitor component, 23
 ROM monitor mode, 27–28
 rommon 1 prompt, 27–28
 root bridges, 108, 118–120
 route authentication, 85–86
 route flush timers, 67
 route invalid timers, 67
 route redistribution, 79–80
 route update timers, 67
 routed protocols, 58
 router advertisement (RA) requests, 204
 router eigrp command, 5, 77–79
 router-id command, 208–209
 Router IDs (RIDs), 208
 router ospf command, 92
 router rip command, 66–70
 router solicitation (RS) requests, 204
 routers

- booting, 2–4, 3, 27
- configuring. *See* configuration
- interfaces for, 14–18
- internal, 22–23, 138, 139
- managing. *See* management of routers
- reloading, 28–29

routing, IP. *See* IP routing
 Routing Information Protocol. *See* RIP
 (Routing Information Protocol)
 routing protocols. *See specific protocols*
by name
 routing tables, 58
 RS (router solicitation) requests, 204
 RSTP (Rapid Spanning Tree Protocol), 112
 RTS (Request To Send) signal, 180
 running-config file, 17

- for configuration, 36
- for IP access lists, 158, 160
- for PPP, 232

 RXBOOT component, 23

S

SDM (Security Device Manager)

- backups and restores, 262–266, 263–265
- configuration, 250–259, 253–257
 - EIGRP, 274–275, 274–275
 - NAT, 170–173, 171–172
 - OSPF, 275–277, 276–277
 - RIP, 272–274, 273
 - wireless network, 190–197, 191–197
- flash memory management, 259–262, 259–262
- LAN and WAN interfaces, 266–272, 266–272

 Secure Shell (SSH), 12–14
 security, 138

- access lists. *See* access lists
- devices for, 138, 139
- firewalls, 140–141
- layer 2 switching, 105–106
- threats, 139–140
- wireless networks, 184–186

 Security Device Manager. *See* SDM (Security Device Manager)
 send-lifetime command, 86
 service password-encryption command, 10, 227
 Service Set Identifiers (SSIDs), 182–185, 183
 service sets for wireless networks, 182–184, 183
 sessions, Telnet, 47–48
 setup command, 4
 setup modes, 4
 shared keys, 185–186

- shortened expressions in IPv6, 202
- show access-list command, 158–159
- show cdp command, 40–41
- show cdp entry * command, 40, 42
- show cdp interface command, 40, 43
- show cdp neighbors command, 40–41
- show cdp neighbors detail command, 40, 42, 228, 232
- show cdp traffic command, 40, 43
- show controllers command, 19
- show file command, 33–35, 38–39
- show flash command, 25, 30, 34
- show frame command, 243–244
- show frame-relay command, 243
- show frame-relay lmi command, 243–244
- show frame-relay map command, 237, 243, 246, 248
- show frame-relay pvc command, 237, 240, 243, 245
- show history command, 6
- show hosts command, 48–49
- show interface command, 14, 18–19
 - Frame Relay, 243, 245–246
 - PPP, 228–229, 232
 - switches, 114–115
- show interface brief command, 20
- show ip access-list command, 158
- show ip eigrp command, 81–82, 84
- show ip eigrp neighbors command, 86–87
- show ip eigrp topology command, 87–88
- show ip interface command, 15, 19, 72, 158–160
- show ip nat command, 168
- show ip ospf command, 93–95
- show ip ospf database command, 93, 95
- show ip ospf interface command, 93, 95–96
- show ip ospf neighbor command, 93, 96–97
- show ip ospf protocols command, 93
- show ip protocols command, 71–72, 97–98
- show ip route command, 8, 59–60
 - default routes, 65
 - EIGRP, 86
 - OSPF, 93
- show ipv6 interface command, 212, 214
- show ipv6 ospf neighbor command, 215–216
- show ipv6 protocols command, 212–213, 215–216
- show ipv6 rip command, 212–213
- show ipv6 route command, 212–213, 215
- show mac access-group command, 158
- show mac address-table command, 103–104, 115–116
- show processes command, 52, 55
- show protocols command, 19–20
- show running-config command, 8, 17–19
 - configuration, 35–36
 - IP access lists, 158, 160
 - PPP, 232
- show sessions command, 44, 47
- show spanning-tree command, 108, 112, 114, 116–119
- show startup-config command, 17–19, 35–36
- show terminal command, 6
- show users command, 44, 46–48
- show version command, 24–25, 30
- show vlan command, 124, 133
- show vlan privileged command, 135
- show vtp password command, 133
- show vtp status command, 132–133
- shutdown command, 14
- 6to4 tunneling, 211–212, 211
- spanning-tree command, 107–108
- spanning-tree backbonefast command, 111
- spanning-tree bpdupfilter command, 110
- spanning-tree bpduguard command, 110
- spanning-tree mode command, 112
- spanning-tree portfast command, 109–110
- Spanning-Tree Protocol. *See* STP (Spanning Tree Protocol)
- spanning-tree uplinkfast command, 110–111
- spanning-tree vlan priority command, 118, 120
- spanning-tree vlan root priority command, 118, 120
- spanning-tree vlan root secondary command, 118
- specific configuration modes, 5
- spoofing, 140
- SSH (Secure Shell), 12–14
- ssid command, 187
- SSIDs (Service Set Identifiers), 182–185, 183
- Stacheldraht attacks, 139
- standard access lists, 142–146
- startup-config file
 - deleting, 38
 - displaying, 17, 36
 - password recovery, 26
- Stateful IOS Firewall inspection engine, 140
- static command, 106
- static MAC addresses, 106–107

static NAT, 163, 165

static routing, 58, 61–62, 65

status of virtual circuits, 239

STP (Spanning Tree Protocol), 107–108

- EtherChannel, 112–114
- interface range, 110
- operations, 108–109
- PortFast, 109–110
- root bridge selection, 118–120
- switches. *See* switches
- verifying, 114–120

subinterfaces

- Frame Relay, 242–243
- VLANs, 130

subnets and subnetting VLANs, 131

summarization in EIGRP, 81

switch ports

- access lists, 153–156
- VLANs, 124–125

switches

- configuration
 - BackboneFast, 111
 - BPDUFILTER, 110
 - BPDUGuard, 110
 - EtherChannel, 112–114
 - RSTP, 112
 - trunking, 127–128
 - UplinkFast, 110–111
 - verifying, 114–120
- layer 2. *See* layer 2 switching

switchport command, 125

switchport access command, 125–126

switchport mode command, 125–126

switchport nonegotiate command, 114, 126–127

switchport port-security command, 105–106

switchport priority command, 135–136

switchport trunk allowed command, 128

switchport trunk encapsulation command, 127–129

switchport trunk native command, 129

switchport voice vlan command, 134–135

system ID extensions, 117

T

Tab command, 6

TCP SYN flood attacks, 139

telephony, VLANs, 134–136

Telnet protocol, 44–45

- closing sessions, 47–48
- connections, 46, 48
- IP access lists, 145–146
- with multiple devices, 45–46
- passwords, 13–14, 45
- users, 46–47

Teredo, 212

terminal history size command, 6

terminal monitor command, 72

TFN (Tribe Flood Network) attacks, 139

TFTP (Trivial File Transfer Protocol), 31–32, 36–37

threats, security, 139–140

time-based access lists, 141, 156–157

time-range command, 156–157

timers

- CDP for, 40–41
- RIP, 67–68

timers command, 67–68

toll networks, 221

traceroute command, 52–53

traffic information, CDP for, 43

transport input command, 13, 252

Tribe Flood Network (TFN) attacks, 139

Trivial File Transfer Protocol (TFTP), 31–32, 36–37

Trojan horse attacks, 140

troubleshooting

- connectivity, 53–55
- Frame Relay, 247–248, 248
- show ip protocols for, 71–72

trunk command, 126–127

trunk ports, 126–130

trust exploitation attacks, 140

tunnel destination command, 209, 211

tunnel mode command, 209, 211

tunnel source command, 209, 211

tunneling in IPv6 migration, 211–212, 211

2.4GHz wireless, 179–181, 180–181

U

undebug command, 52, 54

unified wireless security solution, 184–186

UNII (Unlicensed National Information Infrastructure), 177, 177, 181, 181

upgrading IOS, 32

UplinkFast feature, 109–111

user EXEC mode, 4–5
 username command, 227, 251–252
 usernames
 PPP, 227
 SDM, 252–253
 users, Telnet, 46–48

V

V.24 standard, 225
 V.35 standard, 225
 variable-length subnet masks (VLSMs), 70
 variance command, 82, 85
 verifying
 EIGRP, 86–90
 flash memory, 30–31
 Frame Relay, 243–247
 NAT, 168–170
 OSPF, 92–98
 OSPFv3, 215–217
 PPP encapsulation, 228–230, 228–229
 RIP, 71–73
 RIPng, 212–215
 router, 36
 switches, 114–120
 VLANs, 124
 version command, 70
 version 2 command, 70–71
 vertical bars (|) for pipes, 8
 violation option, 105
 virtual LANs. *See* VLANs (virtual LANs)
 vlan command, 122–123
 vlan priority command, 108
 VLAN Trunk Protocol (VTP), 131–133
 VLANs (virtual LANs), 122
 configuration, 122–123
 inter-VLAN routing, 130–131
 switch port assignments, 124–125
 trunk ports, 126–130
 verifying, 124
 voice, 134–136
 VTP for, 131–133
 VLSMs (variable-length subnet masks), 70
 voice configuration, 134–136

voice traversal with firewalls, 140
 VTP (VLAN Trunk Protocol), 131–133
 vtp domain command, 131–133
 vtp mode client command, 133
 vtp mode server command, 131–132
 vtp password command, 132–133
 VTY
 access lists for, 145–146
 passwords for, 45
 vty command, 13

W

WANs (wide area networks), 220–221
 Frame Relay. *See* Frame Relay
 HDLC for, 224, 225
 PPP for, 225–226, 226
 authentication, 227–230
 configuration, 226–227
 debugging, 230–232, 231–232
 encapsulation, 228–231, 228–229, 231
 PPPoE for, 233–234
 SDM for, 266–272, 266–272
 support, 221–224
 terminology, 221
 WEP (Wired Equivalency Protocol), 184–185
 Wi-Fi Alliance, 177
 Wi-Fi Protected Access (WPA), 185–186
 wildcards
 for access lists, 145
 for default routes, 63
 Wired Equivalency Protocol (WEP), 184–185
 Wireless Express Security screen, 193, 193
 Wireless Interfaces screen, 194–195, 194–195
 wireless networks, 175
 802.11 standards, 178–182, 180–181
 configuration
 IOS, 186–190
 SDM/HTTP, 190–197, 191–197
 overview, 176–178, 177
 security, 184–186
 service sets, 182–184, 183
 Wireless Security settings, 196, 196
 WPA (Wi-Fi Protected Access), 185–186