

Index

- 2G, 2.5G, 3G 13
- 3GPP 118
 - Release 5 (Rel'5) 124
 - Release 6 (Rel'6) 125
 - Release 97/98 (Rel'97/98) 119
 - Release 99 (Rel'99) 120–4
- 3GPP2 129
- 4G 13, 44

- A-bis interface 180
- Access Point Name (APN) 120, 124
- Access system classification 14
- Accessibility 189
- Acknowledgment 58, 61
- Adaptive Multi-Rate (AMR) 94, 281–2
- Admission control 24, 104, 116
- Application performance audit 202
- Attach 20, 198

- Bandwidth Delay Product (BDP) 159–61, 225, 232, 269
- Base Station Transceiver (BTS) 18
- Best Effort 104, 108, 110, 112
- Bluetooth 40
- Broadcast Channel (BCH) 25

- CDMA 5–6
 - channels 29
 - mobility 38
 - voice service 33
- Cell reselection
 - cell reselection times 211
 - Network Assisted Cell Change (NACC) 149
 - Network Controlled Cell Reselection (NCCR) 149
- Coding Scheme 19

- Common Packet Channel (CPCH) 25
- Compression 265, 279–82, 288
 - header compression 284

- Datagram Congestion Control Protocol (DCCP) 277–8
- Dedicated Channel (DCH) 25
- Delay 96, 100, 107
 - delay spike 158–9
- Detach 20, 198
- Differentiated Services (DiffServ) 111–13, 133
 - Per-Hop-Behaviour (PHB) 111
- Dimensioning 173–85
- Downlink Shared Channel (DSCH) 25, 149–50
- Drive testing tools 213

- EDGE 21
- Establishment time 211

- Fast CLPC 24
- Forward Access Channel (FACH) 25, 149–51
- Forward Packet Data Channel (F-PDCH) 29
- Frequency Hopping 16
- FTP 188, 199, 218, 224, 231

- Gaming 98–101
- Gb interface 197
- Gi interface 198
- Gn interface 197
- GPRS 5–6
 - GPRS Bearer Service 119
- Gr interface 198
- GSM
 - enhancement techniques 16, 19, 21
 - GSM/GPRS/EDGE 14–22
 - network architecture 17

- Handover control 24
- Heterogeneous networks 44
- High load test 203
- Home Location Register (HLR) 18
- HSDPA 22, 28
- HS-DSCH 25

- iDEN 235
- Integrated Services (IntServ) 109–11
- Internet Control Message Packets (ICMP) 188
- IP Multimedia Subsystem (IMS) 55
- IS-95/CDMA2000-1x, EV-DV, EV-DO 28–38
- Iu interface 197

- Key Performance Indicator (KPI) 188–9
 - active KPI 199–201
 - core network KPI 191, 197
 - network KPI 190
 - passive KPI 195, 196–9
 - radio access network KPI 191, 194
 - service-based KPI 190, 199
 - signaling KPI 191, 198
- Key Quality Indicator (KQI) 251–2

- Load control 24
- Long Range Dependencies (LRD) 218
- Loose-coupling approach 41

- Mean Opinion Score (MOS) 212
 - PoC MOS 98
- Mobile Services Switching Center (MSC) 18
- Multimedia Messaging Service (MMS) 73–7, 201, 235
- Multiple Input Multiple Output (MIMO) 47
- Multiprotocol Label Switching (MPLS) 113, 133

- Network coverage and radio quality 201
- Network indicators 187
- Network Management System (NMS) 187
- Node-B 23

- Optimization 264–5
 - network optimization 266–8
 - TCP optimization 268–78
- Orthogonal Frequency Division Multiplexing (OFDM) 46–7
- Orthogonal Variable Spreading Factor (OVSF) 26
- OSI
 - Management model 187
 - reference model 56
- Outer Loop Power Control (OLPC) 23

- Packet Channel (PCH) 25
- Packet Control Unit (PCU) 19
- Packet Data Support Node (PDSN) 31
- Packet Data Traffic Channels (PDTCH) 18

- Packet Scheduler (PS) 24, 116
- PDP Context 20, 54–5, 198
- Performance Enhancing Proxies (PEP) 265, 284–8
- Ping 201
- Pipelining 87, 172
- Policy Decision Function (PDF) 56
- Pre-trial field work 206
- Prioritization 238
- Push-to-Talk over Cellular (PoC) 88–98, 200, 235

- Quality 189
- Quality of Service (QoS) 21, 103, 195
 - end-to-end QoS 117–18
 - policy management 131–7
 - QoS attributes 120–1
 - QoS differentiation 104, 238–41

- Radio Access Bearer (RAB) 121, 195
- Radio Link Protocol (RLP) 31
- Radio Network Controller (RNC) 23
- Radio outage time 212
- Random Access Channel (RACH) 25, 149–51
- Reduction factor 147, 176–80
- Resource manager 24
- Resource sharing 35–6, 147, 177
- Retainability 189
- Reverse Packet Data Channel (R-PDCH) 29
- Round-Trip Time (RTT) 59, 161, 211, 222
- Routing Area 267

- Self-similar traffic 218
- Service
 - mobile services 1–3, 50–2
 - Service Management 249
 - service performance 142–3
 - service performance benchmarking 202
 - services architecture 52–6
- Service Level Agreement (SLA) 104, 186, 258–62
- Session Initiation Protocol (SIP) 90–2, 126
- Single service verification 202
- Soft Handover (SHO) 23
- Spatial aggregation 191
- Streaming 171, 228, 235

- TDMA frame 16
- Temporal aggregation 191
- Temporary Block Flow (TBF) 20, 147–58, 195, 267
- Terminal capability 15, 19
- Test case definition 219–21
- Tight-coupling approach 41
- Traffic generation 217
- Transmission Control Protocol (TCP) 57
 - advertised window 59, 62, 64, 161, 269–70
 - Bandwidth Delay Product (BDP) 159–61, 269
 - buffer congestion management 273–5

- Transmission Control Protocol (TCP) (*Continued*)
 establishment delay 210
 limited transmit 271
 Maximum Segment Size (MSS) 59, 272
 Retransmission Timeout (RTO) 59, 164–7, 175
 Selective Acknowledgment (SACK) 272
 slow start 52, 144–6
 TCP performance 156
 Timestamp 273
- Trial methodology 201
- Troubleshooting 202
- TSL capacity 147, 175
- UMTS 22
 Radio Resource Control (RRC) 23–4
 system architecture 22
- User Datagram Protocol (UDP) 58, 67, 170
- User multiplexing 146–7, 153, 177, 180, 230
- User outage time 212
- User throughput 153–5, 174, 210
- Vertical handover 45
- Visitor Location Register (VLR) 18
- WCDMA 5–6, 22–8
 channels 25, 150
- Web service (HTTP) 85–8, 172, 200, 218, 227,
 234, 235
- Weighted Round Robin (WRR) 238
- Wireless Application Protocol (WAP)
 77–85, 201
 Segmentation and Re-assembly (SAR) 82
- WLAN/Wi-Fi 38
 WLAN-3GPP and 3GPP2 architecture 41–4







