

# Index

Note: page numbers in **bold** refer to tables and those in *italic* to figures.

- Activated energy, perovskite type oxides, 224
- Adsorption
- gas adsorption/desorption isotherms, 63–66, 71, 72
  - partial oxidation of methane, 277
  - surface flow, 106–107, 108–109, 111–113
- Agglomerates, spinning suspension particles, 32–34, 35
- Air separation
- design equations, 193–195
  - mixed conducting membranes, 190–206
  - performance analysis, 195–206
- Alkoxides, sol–gel process, 27
- Alumina membranes
- composite TiO<sub>2</sub>/Al<sub>2</sub>O<sub>3</sub>, 48–49, 50, 51
  - effective porosity, **81**
  - pore size distribution, 67, 68, 71, 72
  - porous, 43–48
    - Al<sub>2</sub>O<sub>3</sub> content, 46–48
    - modification, 114–115
  - silica multilayer membranes, 61–62
  - solute rejection measurement, 82
  - surface roughness, 63
- Amorphous membranes, 101–102, 103, 249
- Atomic force microscopy (AFM), 60, 62–63
- Atomic layer chemical vapour deposition (ALCVD), 258
- Axial dispersion, dissolved O<sub>2</sub> elimination, 270
- Bending strength
- porous Al<sub>2</sub>O<sub>3</sub> membranes, **48**
  - three point bend test, 90–91
- Binary gas mixtures
- gas transfer, 167–168
  - perfect mixing, 122–123
- Binders, 29, 30, 35, 39–40, 44–45, 46–47, 48
- Bubble point method, pore size distribution, 72–74
- Bulk density, 30
- Bulk (lattice) diffusion, 181, 183, 229
- Capillaries, gas transport mechanisms, 103–106, 111, 167–168
- Capillary condensation, 66–67, 107–109, 114
- Carbon membranes, 103
- Carman–Kozeny equation, 74, 75
- Catalytic membrane reactors (CMRs), 17–18, 256
- dense ceramic membranes, 249–252, 273–274
  - mixed conducting membranes, 173, 280
  - porous membranes, 246–249, 258–259, 260
- Catalytic oxidative dehydrogenation, 256–257, 258–259
- Caustic soda, electro dialysis, 13, 14
- Ceramic membranes
- configurations, 3, 4, 5, 17–18
  - membrane processes, 5–18
  - preparation, 1, 3, 21–57
  - thickness, 206, 220, 221, 222, 223, 230–231, 235–236
- Characterization, 59–95
- composite membranes, 59
  - dense ceramic membranes, 59, 83–91
  - porous membranes, 59, 63–83, 84

- Chemical reactions  
mass transfer effects, 139, 156–158, 271–273  
*see also* Membrane reactors
- Chemical vapour deposition (CVD), 22, 27–28  
chemical reactions, **28**  
microporous membranes, 257, 258  
silica, 102, 103
- Coatings  
conversion coatings, 28  
dip coating, 22, 27  
gas transport resistance, 116, 120–122
- Cocurrent flow  
design equations, 126–127, 193, 194, 195  
methane coupling reactors, 253  
performance analysis, 198–199, 247  
system design, 123, 124
- Coking, dehydrogenation reactors, 248–249
- Colloids  
DLVO theory, 54  
separation, 10–11  
sol–gel process, 25, 26
- Combustion and reforming reactions (CRR), 276
- Composite membranes  
characterization, 59, 61–62  
composition, 1, 2, 3  
gas transport resistance model, 117–122  
preparation methods, 21, 22  
 $\text{TiO}_2/\text{Al}_2\text{O}_3$  membranes, 48–49, 50, 51
- Condensed gases, surface flow, 113
- Configurational diffusion, 109–110, 115
- Configurations  
membrane reactors, 250, 251, 256, 273–275  
membranes, 3, 4, 5, 17–18
- Conservation equations, dissolved  $\text{O}_2$   
elimination, 262–264
- Consolidation *see* Phase inversion
- Contactors *see* Membrane contactors
- Conversion coatings, 28
- Coordination number, particle packing, 30, **32**
- Countercurrent flow  
design equations, 128, 193, 194–195  
performance analysis, 198, 247  
system design, 123, 124
- Cross flow  
design equations, 125–126  
filtration, 11  
solute rejection measurement, 83, 84  
system design, 123
- Cross sections  
hollow fibre membranes, **44**, 45–46  
morphology, 60–63  
pore size reduction, 257
- Crowdions, oxygen transport, 183–184
- Dead end filtration, 11
- Dead end test cell, 83
- Deflocculation, spinning suspensions, 29, 33
- Degassing, spinning suspensions, 35
- Dehydrogenation reactions  
membrane reactors, 16, 18, 246–248, 251, 275, 281, **283**  
partial oxidation, 256–257, 273  
proton conducting membranes, 237–239, 251
- Dense ceramic membranes  
characterization, 59, 83–91  
dehydrogenation, 275, 281, **283**  
methane coupling, 252–256, 275–276, 284–288  
oxygen permeation, 86–88, 173–181  
preparation, 3, 4  
product separators, 249–256  
reactant distributors, 257, 273–288
- Dense perovskite  
LSCF, 49–51, 84–85, 187–189, 195–197, 200–203  
X-ray diffraction, 51, 52, 90, 91, 286, 288  
SCYb, 51, 53, 89–90, 234–236, 252–256
- Densification, sintering, 40, 42, 53
- Derjaguin–Landau–Verwey–Overbeek theory *see* DLVO theory
- Desalination, 12–13
- Design equations  
air separation, 193–195  
gas absorption, 159–162  
gas separation, 124–128
- Desorption  
gas adsorption/desorption isotherms, 63–66, 71, 72  
olefin/paraffin separation, 138–139
- Dialysis, 11–12, **13**
- Differential scanning calorimetry (DSC), 70–71
- Dimensionless parameters, 263, 264
- Dip coating, 22, 27
- Direct partial oxidation (DPO), 276
- Disc membranes  
gas permeation, 206  
mechanical strength, 90  
membrane reactors, 273–274  
pressing, 24
- Dispersion  
dispersants, 33–35  
DLVO theory, 54  
spinning suspension particles, 32–35
- Dissolved oxygen (DO) elimination, 260–273
- Distillation, 14–15, 29
- DLVO theory, 54

- Doping, mixed conducting materials, 172, 174–177, 181, 184, 218, 219, 224
- Dual phase membranes  
hydrogen permeation, 225–226, 237  
oxygen separation, 182–183
- Effective porosity, 80, **81**
- Electrical double layer model, 54
- Electrochemical potential, 185
- Electrochemical pumping, 251
- Electrodialysis, 12–14
- Electron (hole) conducting materials, 171–177, 181, 228–230  
nonperovskite type oxides, 224–225  
perovskite type oxides, 217–224
- Electron microscopy, 60
- Electrostatic forces, 53–54, 55
- Ethylene production, 251, 253–256, 276, 280
- Extrusion, 22, 24–25, 35
- Fast reactions, mass transfer enhancement, 158
- Feed flow rate, 199
- Fick's first law, 106, 109
- Field emission scanning electron microscopy (FESEM), 60, 61–62
- Filtration processes, 9–11
- Fischer–Tropsch process, 276
- Fluidized bed membrane reactors (FLBMRs), 259, 260
- Fractal structure, porous membranes, 257, 258
- Free proton transport, 227, 228
- Fuel cell configuration, membrane reactors, 250, 251
- Gas absorption  
design equations, 159–162  
hollow fibre contactors, 136–139  
chemical reactions, 156–158  
operating modes, 139–143, 153–156, 193
- Gas adsorption/desorption isotherms, porous membranes, 63–66, 71, 72
- Gas permeability  
capillary condensation, 107–108  
porous  $\text{Al}_2\text{O}_3$  membranes, 46, 47, **48**  
 $\text{TiO}_2/\text{Al}_2\text{O}_3$  membranes, 49, **51**  
zeolite membranes, **122**
- Gas permeation  
dense ceramic membranes, 84–90  
porous membranes, 74, 75, 76–81, 117–122  
with PSD consideration, 78–81  
without PSD consideration, 76–78
- Gas separation, 6–7  
hollow fibre contactors, 135–168  
system design  
design equations, 124–128  
operating schemes, 122–124, 193–195  
*see also* Air separation; Oxygen separation
- Gas separation membranes  
characterization, 59–95  
dense, 97  
materials, 99–103, 170–173  
porous, 97–103  
modification, 114–117  
performance indicators, 98–99
- Gas stripping, 142, 271
- Gas tightness, leakage test, 84–85
- Gas transport  
binary gas mixtures, 167–168  
composite membrane resistance model, 117–122  
mechanisms, 103–113  
simultaneous occurrences, 111–113  
*see also* Oxygen transport
- Gas/vapour treatment, hollow fibre contactors, 135–148
- Graetz solution, mass transfer coefficients, 144–146, 155
- Grain boundaries, **41**, 42
- Grain growth, hollow fibre membranes, 40, **41**, 42
- Hagen–Poiseuille equation, 74, 75, 105–106, 138, 153, 154, 194
- Halsey equation, 65
- Hatta approach, gas transfer rate, 157
- Height of transfer unit (HTU), 161
- Henry's law, 110, 113, 141, 142, 161
- Hollow fibre lumens, mass transfer, 138, 144–146, 153–154, 159–162, 187, 190
- Hollow fibre membranes  
characterization, 59  
contactors for gas/vapour treatment, 15–16, 135–168  
gas tightness, 84–85  
membrane reactors, 252–256, 274, 275, 284–288  
methane coupling, 284–288  
oxygen production, 203–206  
packing density, 3–4, 5, 151–152  
preparation, 4–5, 21, 22, 29–53, 206–207  
carbon, 103  
composite  $\text{TiO}_2/\text{Al}_2\text{O}_3$ , 48–49, 50, 51  
dense perovskite, 49–53  
polymeric, 29, 37–38  
porous  $\text{Al}_2\text{O}_3$ , 43–48

- precursor spinning, 21, 22, 35–38  
sintering, 21, 22, 39–46, 207
- Hopping model, surface flow, 106
- Hydrodynamic model, surface flow, 106, 107
- Hydrogen flow rate, dissolved O<sub>2</sub> elimination, 262, 267–270
- Hydrogen fluxes  
nonperovskite type oxides, 225–226  
perovskite type oxides, 220–223, 233–236
- Hydrogen permeation  
mixed conducting membranes, 86, 88–90, 217–243  
proton conducting membrane, 6–7, 88
- Hydrogen production, 219, 236–237
- Hydrophilicity, 136, 138, 143, 154, 155
- Hydroxyl defects, proton transport, 226–228
- Instantaneous reactions, mass transfer  
enhancement, 156–158
- Integrated gasification combined cycle (IGCC), 192
- Interstitials, oxygen transport, 183–184
- Ion exchange membranes, electro dialysis, 12–14
- Ionic conduction, 169, 170, 171, 172–181  
*see also* Mixed conducting membranes
- Ionic repulsion, 33, 34
- Ions, electrostatic forces, 53–54
- Ion transport membrane (ITM), 192
- Kelvin equation, 64–65, 66–67, 68, 107, 108
- Kinetic theory of gases, 104
- Knudsen flow, 104–105, 111, 114  
hollow fibre contactors, 146–147, 149–150  
microporous membranes, 7  
permeation measurement, 76, 77, 78  
permporometry, 67
- Laplace equation, 68–69, 72–73, 74, 154, 265
- Lattice (bulk) diffusion, 183
- LCFO perovskite membranes, 175–176, **178**
- Leakage test, dense ceramic membranes, 84–85
- Leveque solution, mass transfer coefficients, 144–146
- LGO perovskite membranes, 177, **178–179, 180**
- Liquid absorption, polymeric membranes, 135
- Liquid displacement techniques, porous membranes, 71–74, 75
- Liquid mixtures, pervaporation, 7–8
- Liquid permeation, pore size measurement, 74–75, 76
- Liquid phase transport, zeolite membrane synthesis, 100–101
- Liquid–vapour equilibrium  
membrane contactors, 14, 15, 136, 137–142  
pervaporation, 7–8
- LSCF perovskites  
hollow fibre membranes, 49–51, 84–85, 187–189, 195–197, 200–203  
X-ray diffraction, 51, 52, 90, 91, 286, 288
- Lyophilic/lyophobic dispersions, 54
- Macropore characterization, 74
- Mass transfer  
chemical reaction effects, 139, 156–158  
dissolved O<sub>2</sub> elimination, 262–273  
hollow fibre contactors  
across membranes, 146–151  
coefficient determination, 142–143, 167–168  
hollow fibre lumens, 138, 144–146, 153–154, 159–162, 187, 190  
pore size distribution, 147–151  
shell side of contactor, 144, 151–153, 159–162, 187, 190, 191  
wetting conditions, 136–138, 139–142, 146, 153–156  
membrane contactors, 14–15  
mixed conducting membranes, 183–190, 191  
resistance, 116–122, 136, 137–138, 144  
sintering, 40, **41**
- Mechanical strength  
dense ceramic membranes, 90–91  
porous Al<sub>2</sub>O<sub>3</sub> membranes, 46–48
- Membrane area, 199–200, 201, 274
- Membrane contactors, 14–16  
design equations, 159–162  
hollow fibre membranes, 135–168  
mass transfer, 146–162, 167–168, 187, 190, 191  
operating modes, 139–143, 153–156
- Membrane processes, 5–18
- Membrane reactors, 16–18, 245–298  
configurations, 250, 251, 256, 273–275  
functions, 17  
product separators  
dense ceramic reactors, 249–256  
microporous reactors, 246–249  
reactant distributors  
dense ceramic reactors, 257, 273–288  
porous reactors, 257–273
- Membrane separation factor, 99
- Mercury porosimetry, 67–69
- Methane coupling, 237–239, 245  
dense ceramic membranes, 252–256, 275–276, 284–288

- mixed conducting membranes, 277, 280–281, **282**  
 proton conducting membranes, 249–252  
 Microfiltration, 10–11  
 Microporous membranes  
   dehydrogenation reactors, 246–249, 257  
   gas permeation, 7  
   gas separation, 97, 99–103  
   micropore diffusion, 109–110, 115  
   *see also* Porous ceramic membranes  
 Microstructure  
   sintering, 40, **41**, 42  
   TiO<sub>2</sub>/Al<sub>2</sub>O<sub>3</sub> membranes, 49, 50  
 Mixed conducting membranes  
   air separation, 190–206  
   area, 199–200, 201  
   characterization, 83  
   conduction properties  
     hydrogen permeation, 217–218, 219–220, 224, 225  
     oxygen separation, 172–177, **178–179**, **180**, 182–183  
   developments, 206–207  
   hydrogen permeation, 217–243  
     applications, 236–239  
     doping, 218, 219–220  
     dual phase membranes, 225–226, 237  
     hydrogen fluxes, 220–223, 225–226, 233–236  
     measurement, 86, 88–90  
     nonperovskite type oxides, 224–225  
     perovskite type oxides, 217–224  
     proton transport, 226–236  
   operating principle, 169, 170  
   oxidative coupling of methane, 277, 280–281, **282**  
   oxygen permeation measurement, 86–88  
   oxygen separation, 169–215  
     doping, 172, 174–177, 181, 184  
     dual phase membranes, 182–183  
     material properties, 170–173  
     nonperovskite type oxides, 179–181  
     oxygen transport, 183–190, 191, 280  
     perovskite type oxides, 170–177, **178–179**, **180**, 181, 191, 280–281, **282**  
     substitution effects, 174–177  
   performance, 170  
   proton conducting membranes, 6–7, 88, 218–225, 228–230  
   syngas production, 277, **278–279**  
 Mixing *see* Perfect mixing  
 Mixtures *see* Binary gas mixtures; Gas separation  
 Molecular sieving effects, 26, 100  
 Molecular weight cut off (MWCO), 81–82  
 Mole flux, gas separation, 98–99, 105–106  
 Morphology  
   dense perovskite, 50–51, 52, 53  
   electron microscopy, 60  
   membrane surfaces and cross sections, 60–63  
   mercury porosimetry, 69  
   optical microscopy, 60  
   porous Al<sub>2</sub>O<sub>3</sub>, 43–46  
 Multilayer membranes *see* Composite membranes  
 Nanofiltration (NF), 9–10  
 Nernst–Einstein equation, 185  
 Nernst–Planck equation, 185, 228–229  
 Nitrogen  
   gas adsorption/desorption isotherms, 64–65  
   permeation measurement, 78, 84  
 NonFaradaic electrochemical modification of catalytic activity (NEMCA), 251  
 Nonperovskite type oxides  
   hydrogen permeation, 224–225  
   oxygen permeable membranes, 179–181  
 Nonwetted mode, membrane contactors, 136–137, 139–141, 146, 153–162  
 Nonzeolitic pores, gas transport resistance, 116–117, 119–122  
 Number of transfer unit (NTU), 161  
 Ohm's law, permeation rate, 117  
 Olefin/paraffin separation, 138–139  
 Operating schemes, gas separation, 122–124  
 Optical microscopy, 60  
 Oxidative coupling of methane (OCM), 275–276, 277, 280–281, **282**, 284–288  
 Oxidative dehydrogenation, 256–257, 258–259, 281, **283**  
 Oxygen permeable membranes  
   current status, 173–181, 273  
   materials summary, 181  
   nonperovskite type oxides, 179–181  
   oxygen transport, 183–190, 191  
   perovskite type oxides, 173–177, **178–179**, **180**, 191  
 Oxygen permeation  
   methane coupling, 285, 287  
   mixed conducting membranes, 86–88, 173–177, **178–179**, **180**  
   permporometry, 67, 68  
 Oxygen production, 190, 191–193, 203–206

- Oxygen separation  
dense ceramic membranes, 6–7  
mixed conducting membranes, 169–215, 280  
air separation, 190–206
- Oxygen transport  
dissolved O<sub>2</sub> elimination, 265–267  
mixed conducting membranes, 183–190, 191, 280  
analysis, 187–190, 191  
equations, 185–187  
mechanism, 183–185
- Packed bed membrane reactors (PBMRs), 246, 247, 256, 259, 260
- Packing density  
hollow fibre membranes, 3–4, 6, 151–152  
optimal, 32  
spinning suspension particles, 30–32, 34
- Parallel plug flow  
design equations, 126–128, 194  
system design, 123, 124
- Partially wetted mode, membrane contactors, 137, 138, 153–156
- Partial oxidation of methane (POM), 276–277, 278–279
- Partial oxidative dehydrogenation, 256–257, 273
- Partial pressure *see* Pressure effects
- Particles  
dispersion, 32–35  
packing, 30–32, 34  
spinning suspension preparation, 30–34  
surface charge, 33
- Particle size, porous Al<sub>2</sub>O<sub>3</sub> membranes, 46, 48
- Peclet number, dissolved O<sub>2</sub> elimination, 270–271
- Perfect mixing  
design equations, 124–125  
system design, 122–123
- Performance analysis  
air separation, 195–206  
dehydrogenation reactors, 247, 259  
experimental data, 200–202, 233–236  
feed flow rate, 199  
flow patterns, 197–199  
membrane area, 199–200, 201, 274  
methane coupling reactors, 253–256  
pressure/temperature effects, 195–197
- Performance indicators, gas separation membranes, 98–99
- Permeability *see* Gas permeability; Solvent permeability
- Permeation *see* Gas permeation; Liquid permeation
- Permporometry, porous membranes, 66–67, 68
- Perovskite type oxides  
hollow fibre membrane preparation, 49–53  
mixed conducting ceramics  
hydrogen permeation, 217–224  
hydrogen fluxes, 220–223, 233–236  
oxygen permeable membranes, 173–177, 178–179, 180, 181, 191  
LCFO, 175–176, 178, 180  
LGO, 177, 178–179, 180  
SCFO, 174–175, 178, 180  
structure, 170–172, 288
- Pervaporation, 7–8
- Phase inversion, spinning suspensions, 29, 30, 37–38, 46, 207
- Physisorption isotherms, 64
- Plastic deformation, 41, 42
- Plasticizers, 29, 30, 35
- Poiseuille flow, 76, 77
- Polar molecules, electrostatic forces, 53–54, 55
- Polyethylene glycol (PEG), solute rejection measurement, 82
- Polymeric membranes  
hollow fibre, 29, 37–38, 135, 206  
ion selective, 14  
phase inversion, 37–38
- Polymers, sol–gel process, 26
- Pore changes, sintering, 42–43
- Pore radius  
mass transfer coefficients, 147–150, 167–168  
measurement, 65–81
- Pore size  
Al<sub>2</sub>O<sub>3</sub> membranes, 81  
classification, 103  
measurement, 65–81  
membrane categories, 2  
reduction, 257–259  
sol–gel control, 25, 26
- Pore size distribution (PSD)  
composite membranes, 1, 2, 65, 66  
gas permeation method, 76–81  
liquid displacement techniques, 71–74, 75  
mass transfer coefficients, 147–151, 168  
mercury porosimetry, 67–69  
permporometry, 66–67, 68  
surface flow, 113  
thermoporometry, 69–71, 72
- Porous ceramic membranes  
Al<sub>2</sub>O<sub>3</sub> hollow fibre membranes, 43–48  
characterization, 59, 63–83, 84  
gas transport and separation, 97–134  
modifications, 114–117  
pore size reduction, 257–259

- reactors, 257–273  
 applications, 259–261  
 dissolved O<sub>2</sub> elimination, 261–273  
 microporous, 246–249, 257  
*see also* Microporous membranes
- Powders, spinning suspension preparation, 29, 30–34
- Preparation methods, 1, 3, 21–57  
 composite membranes, 21, 22  
 hollow fibre membranes, 4–5, 21, 22, 29–53  
 composite TiO<sub>2</sub>/Al<sub>2</sub>O<sub>3</sub>, 48–49, 50, 51  
 dense perovskite, 49–53  
 porous Al<sub>2</sub>O<sub>3</sub>, 43–48
- Presintering, hollow fibre membranes, 39
- Pressing, 22, 24
- Pressure effects  
 air separation membranes, 195–197, 199–200  
 capillary condensation, 66–67, 107–109, 114  
 dissolved O<sub>2</sub> elimination, 267–270  
 gas transfer rate, 140–141, 159, 167–168, 184–187  
 hydrogen fluxes, 220–223, 232–233, 234, 235  
 hydrogen production, 236  
 membrane contactor wetting, 138, 140–142, 153–155
- Product separators  
 dense membrane reactors, 249–256  
 microporous membrane reactors, 246–249
- Proton conducting membranes, 218–225, 228–230  
 dehydrogenation reactions, 237–239, 251  
 hydrogen permeation, 6–7, 88  
 hydrogen production, 236–237  
 methane coupling, 249–252
- Proton formation, 226–227
- Proton transport, 218–239  
 analysis, 230–236  
 applications, 236–239  
 equations, 228–230  
 mechanism, 226–228
- Random walk model, surface flow, 106
- Reactant distributors  
 dense membrane reactors, 257, 273–288  
 porous membrane reactors, 257–273
- Reactors *see* Membrane reactors
- Resistance model  
 composite membrane gas transport, 117–122  
*see also* Mass transfer
- Reverse osmosis (RO), 9
- Reynolds number, mass transfer coefficients, 152–153
- Rheology, spinning suspensions, 35, 36–37
- Scanning electron microscopy (SEM), 60, 61–63
- SCFO perovskite membranes, 174–175, 178
- SCYb perovskites  
 hollow fibre membranes, 51, 53, 89–90, 234–236  
 methane coupling, 238, 252–256  
 mixed conducting membranes, 217–218, 230, 233–236
- Selectivity  
 gas separation, 99, 107, 114–117, 118–120, 121  
 membrane reactors, 245, 246, 247, 255–256, 257, 259, 273  
 mixed conducting membranes, 169, 280
- Separation *see* Gas separation
- Separation factor, 99, 114
- Separation index (SI), 99
- Separators *see* Product separators
- Shell side of membrane contactor, mass transfer, 144, 151–153, 159–162, 187, 190, 191
- Sherwood number, mass transfer coefficients, 152–153
- Shrinkage, 41, 42, 43–44, 53
- Silica–alumina multilayer membranes, 61–62
- Silica membranes  
 dehydrogenation reactors, 246–247, 248  
 gas separation, 101–102, 103, 115
- Sintering  
 final stage, 40–42  
 hollow fibre membranes, 21, 22, 39–43, 207  
 morphology, 43–46, 50–51, 52, 53  
 pore change, 42–43  
 presintering, 39  
 temperature, 39, 40, 46, 47, 48  
 thermolysis, 39–40
- Size exclusion, solute rejection measurement, 81
- Size ratio, spinning suspension particles, 31, 32
- Slip casting, 22–23
- Slip flow, 78, 104–105, 111
- Sol–gel process, 22, 25–27, 34  
 microporous silica membranes, 101–102  
 ultrafiltration membranes, 65
- Solid–liquid phase transition, thermoporometry, 69–71
- Solute rejection measurement, porous membranes, 81–83, 84
- Solvent permeability, 9–14
- Specific volume, 32, 171, 181
- Spinning  
 extrusion comparison, 24–25  
 hollow fibre precursors, 21, 22, 35–38  
 spinnability, 36–37

- Spinning suspension preparation, 21, 22, 29–35  
  deflocculation, 29, 33  
  degassing, 35  
  general procedure, 34–35  
  particles, 29, 30–34
- Steric hindrance, 33, 34, 54–55
- Stern layer, 53
- Strength *see* Mechanical strength
- Structure  
  perovskite type materials, 170–172, 288  
  *see also* Microstructure
- Support layers, gas transport resistance,  
  116–117, 118–119
- Surface charge  
  electrostatic forces, 53–54  
  particles, 33
- Surface diffusion, **41**, 42, 109–110, 114–115,  
  181, 190
- Surface flow, 106–107, 109–113  
  capillary condensation, 107–109
- Surface forces, 53–55
- Surface porosity, 76–77, 79–80
- Surface roughness  
  Al<sub>2</sub>O<sub>3</sub> membranes, 63  
  hollow fibre membranes, 48–49
- Surfaces, morphology, 60–63
- Sweep gas, membrane reactors, 246–247, 251
- Syngas production, 276–277, **278–279**
- System design, 122–128, 193–195
- Tape casting, 22, 23–24
- Temperature effects  
  air separation membranes, 195, 197, 201, 202,  
    203–206  
  hydrogen fluxes, 220, 223, 226, 233, 234–235  
  hydrogen production, 236, 237  
  methane coupling, 249, 253–256, 284–287  
  nonperovskite type oxides, 224  
  permeation measurement, 86, 87, 88–89,  
    187–190, 191, 231–232  
  perovskite mixed conduction, 176, 184, 217,  
    218  
  polymeric membranes, 135–136  
  protonic conduction, 218  
  sintering, 39, 40, 46, 47, **48**  
  thermoporometry, 69–71, 72
- Thermolysis, hollow fibre membranes, 39–40
- Thermoporometry, porous membranes, 69–71,  
  72
- Thickness effects, 206, 220, 221, 222, 223,  
  230–231, 235–236
- Titania–alumina membranes, 48–49, 50, 51
- Tolerance factor, lattice deformation, 171, 181,  
  265
- Transmission electron microscopy (TEM), 60,  
  61–62
- Transport *see* Gas transport
- Tubular membranes, 206
- Ultrafiltration, 10–11, 25, 26, 60, 65, 74
- Vacancies  
  oxygen transport, 171, 172, 181, 183, 184,  
    186, 232  
  proton conduction, 217, 218, 232
- Van der Waals forces, 54, 55
- Vapour absorption  
  hollow fibre contactors, 136–139  
  operating modes, 139–143, 153–156
- Vapour separation  
  hollow fibre contactors, 135–168  
  liquid–vapour equilibrium, 7–8  
  *see also* Gas separation
- Vehicle proton transport, 227
- Viscosity  
  dip coating, 27  
  spinning suspensions, 33, 35, 37
- Viscous flow  
  gas separation, 78, 104, 105–106, 111, 112  
  sintering, 39, **41**, 42
- Voids  
  packing density, 30–32  
  sintering, 44–45, 48
- Volatile organic compounds (VOCs), 139
- Wagner theory, 182
- Wetted mode, membrane contactors, 137,  
  141–142, 153–156
- Wetting  
  hollow fibre contactors, 136–138, 139–142,  
    146, 153–156  
  spinning suspension particles, 34
- Wilson plots, 143
- X-ray diffraction (XRD)  
  dense ceramic membranes, 90, 91  
  LSCF membranes, 51, 52, 90, 91, 286, 288  
  TiO<sub>2</sub>/Al<sub>2</sub>O<sub>3</sub> membranes, 49, 51
- Zeolite membranes  
  dehydrogenation reactors, 247, 249  
  gas separation, 8, 100–101, 115–117, 119–122