

# Index

- acceptability, 19–22, 35–36, 102
- accessability, 20
- accommodation, 192
- acoustic leakage, coupling, 89–91, 177, 193–194, 199, 236–237
- advantage of access, 46
- advantage factor (A), 46, 259
- anchor (point), anchoring, 33, 155, 189–190, 194, 268, 271
- articulation, 3–4, 197, 203
  - comprehensibility, 9–11, 25
- artificial
  - ear, 29
  - mouth, 29
- assessment, 16–18, 23–48, 99, 113, 281
- assimilation, 192
- asymmetry, 77, 98
- asynchronous transfer mode (ATM), 55
- attribute scaling, *see* scaling, attribute scaling
- auditory
  - event, 1–3, 86
  - perception, 1, 8, 11, 58, 154
  - test, 1–3, 11, 16–18, 23–39, 43, 49, 75–78, 85, 111–127, 130–140, 147–151, 154–162, 163–168, 172–173, 176–188, 192–204, 225, 234, 241–242, 251–254, 265–275
- bandpass, 85–91, 93, 175–188, 193–204, 226–227
- bandwidth, 5–7, 57–61, 84–91, 99, 100, 103–105, 175–197, 200–203, 208–210, 234–235, 274–275
  - critical, 5–6, 87–88, *see also* Bark, critical-band rate
  - equivalent rectangular bandwidth (ERB), 187–188, 209–210
- Bark, 5–6, 184–188, 208–210
- binaural loudness, 194
- bit-errors, *see* error, bit-error
- Burst Ratio (*BurstR*), 45, 67, 106, 128–129, 132–133, 139, 205–206
- burst(y) (packet) loss, burstiness, 45, 64–67, 70, 77, 104–108, 128–146, 162–171, 205–206, 223, 271–273
- call
  - clarity index (CCI), 43, 47–48
  - set-up, 52–53, 100, 227, 230, 233
- CDMA 2000, 54
- channel coding, 59, 78, 228
- clarity, 93
- code domain multiple access (CDMA), 54, 78
- coder, codec
  - wideband, 59, 61, 189–191, 208–210
- coder, codec, coding, 40–42, 46–47, 57, 58–61, 71–75, 78, 84, 89, 92–96, 100, 103, 105–106, 116–120, 122–123, 124–129, 152–158, 170–172, 189–191, 206–207, 208–210, 226–231, 233–234, 252, 266, 271
- codec impairment, *see* impairment, impairment factor, equipment impairment factor
- color of sound, 60, 93
- coloration, 86–89, 93, 184
- comfort noise, *see* noise, comfort noise
- communication efficiency, 22
- composition
  - desired composition, *see* nature, desired nature
  - perceived composition, *see* nature, perceived nature
- comprehension, 9–11, 13–14,

- context, 1, 4, 8, 9–11, 12–13, 15, 20, 25–27, 30, 39, 51, 87, 91, 99–102, 177, 184, 197–198
- conversation  
 effectiveness, 21–22  
 task, 30–32
- critical bands, 5–6, 83, 87–88, 188
- critical-band rate, 5–6, 188
- cumulative distribution function (CDF), 222
- delay  
 absolute ( $T_a$ ), transmission delay, delay, 10, 13, 22, 30, 32, 44, 46, 53, 55–56, 58, 61–63, 154, 219, 220–223, 227, 231–234, 242, 268–273,  
 mean one-way ( $T$ ), 44, 79, 106, 149, 154, 159, 161, 227  
 roundtrip ( $T_r$ ), 44, 79–80, 226–227, 229, 268, 273,  
 variation, *see* jitter
- device (INMD), *see* INMD
- D-factor ( $D_s$ ,  $D_r$ ), 45, 268, 273
- diagnostic acceptability measure (DAM), 35–36
- dichotic, 241
- digital circuit multiplexing equipment (DCME), 48, 114
- digital subscriber line (DSL), 78–79
- diotic, 193–196, 235–236
- distortion  
 linear distortion, 85–91, 106–108, 175–189, 194  
 non-linear distortion, 58–61, 81, 91–98, 106, 189–190, 208–210  
 time-varying distortion, 103, 111
- distribution, 228, 242–243  
 equilibrium, 218  
 Pareto, 221  
 Weibull, 221, 223
- dummy head, *see* head and torso simulator
- duration  
 call/conversation duration, 30–32, 52, 61, 138, 150, 271–272  
 memory, 8, 12  
 packet loss-related, 72–74, 77, 86, 113, 115, 124, 132, 137–138, 162, 242, 271–272  
 perceived duration, 15, 72, 86  
 phoneme/syllable duration, 4, 74, 79  
 stimulus duration, 28, 123–124, 145, 182  
 talkspurt duration, 62
- ear reference point (ERP), xviii
- ease of communication, 21–22
- echo, 30, 46, 61, 83, 86, 98, 235, 256–257  
 attenuation, 79, 213, 242,  
 canceller (EC), cancellation, xxii, 29–30, 52, 80–82, 106,  
 delay, *see* delay, mean one-way delay  
 echo loss, 44  
 listener echo, 44, 48, 80, 106, 225–228, 256–257  
 talker echo, xxv, 22, 43, 44, 56–57, 79–82, 91, 101, 106, 107, 154–155, 158–162, 166–170, 225–228, 238–241, 256–257, 268–271, 274  
 talker echo loudness rating (TELR), 44, 79–80, 106, 154, 157–162, 166–168, 256–259, 266, 269–274  
 weighted echo path loss (WEPL), 44, 48, 259, 274
- effectiveness  
 conversation effectiveness, 21–22
- efficiency, 149  
 communication efficiency, *see* communication efficiency  
 service efficiency, 22
- E-model, xxiii, xxv, 33, 34, 43–46, 47–48, 56, 58, 60–61, 79, 82–83, 97, 98,  
 additivity property, 45–46, 98, 151–162, 206–208,  
 algorithm, 43–46, 104, 105–108, 113–123, 128–129, 131–135, 138–146, 149, 151–162, 163–172, 175–188, 189–190, 205–210, 224, 226, 252–254, 255–259, 277–280
- emotion, 1, 4, 14, 20, 84, 100
- equipment, 58  
 terminal equipment, *see* user interface
- equivalent-Q method, 92, 178–179, 251–253
- error, 150, 213, 232, 258  
 bit error, 54, 57, 63, 78–79, 94–96, 223–224, 228, 266  
 correction, 59, 61, 70, 223 (*see also* packet, loss, packet loss concealment)  
 forward error correction (FEC), 57, 63, 70, 72–73, 219–223

- root mean squared error (RMSE), 94, 120, 146, 171, 186–187,
- transmission error, 22, 40, 60, 70, 73, 94, 108, 117, 124, 252
- expectation
  - factor (*A*), *see* advantage factor
  - statistical, 65, 137, 218–219
  - user expectation, xxiii–xxv, 8, 15, 51, 90, 91, 102–103, 109, 113, 176, 191–203, 234, 251
- experience, xxii, 15, 22–23, 63, 86–87, 100–101, 110, 190–192, 213, 251
- feature, 281
  - desired feature, xxiii–xxv, 15–19, 38, 49, 99–102, 190–203, *see also* nature, desired nature
  - perceived feature, xxii–xxv, 15–19, 24, 35, 49, 72, 74, 88, 99–100, 113, 191, 213
- FEC, *see* error, forward error correction
- formant, 3–4, 7
- forward error correction (FEC), *see* error, forward error correction
- frame, 58, 59, 70, 73–75, 78,
  - frame erasure, frame loss, xxiv, 54, 70, 73–75, 78, 94, 111, 118, 153, 223
  - size, 75, 230
- frequency
  - center frequency, 6, 184–188, 208–209
  - component, 5, 60, 89–90, 175, 177, 183, 196, 199, 213, 235
  - cut-off frequency, 85, 89, 199, 234
  - fundamental frequency, 3–4, 202–203
  - perception, 3, 5–8, 38, 43–44, 83, 85–91, 92–97, 104–105, 175–189, 193–197, 199–203, 208–210, 226–227, 234–238, 245–250
  - word frequency, 11
- frequency distortion, *see* distortion, linear distortion
- General Packet Radio Services (GPRS), 54, 78–79
- Gilbert model, 67–68
- Gilbert-Elliott model, 67–68
- Global System for Mobile communication (GSM), 52, 54–55, 57, 59, 75, 78, 79, 93–96, 114–115, 119, 125, 210, 223, 226–228, 230, 265–267
- GoB, 258
- handset, 13, 45–46, 55, 57, 79, 84–85, 89, 90–91, 100–101, 107, 113, 126, 175, 177, 182, 188, 192–197, 199, 235–237, 240, 249–250, 259
- hands-free terminal (HFT), 235, 238–241
- head and torso simulator (HATS), 29–30, 195, 234, 250
- headphone, 29, 105, 177, 192–196, 213–214, 228, 235–236, 238–240
- headset, 89, 90–91, 100, 235, 247–248
- Hi-fi phone, 177–196, 199, 235–237
- hybrids, 79
- impairment
  - factor, 45–46, 151–153, 255–259
    - delayed impairment factor (*I<sub>d</sub>*), 45–46, 115, 170, 205, 257
    - effective equipment impairment factor (*I<sub>e,eff</sub>*), 45–46, 117, 125, 128, 151–157, 170, 205–206, 258
    - equipment impairment factor *I<sub>e</sub>*, 46, 60, 105–106, 117–119, 125–126, 132, 141, 153, 189, 206, 209–210, 224, 252, 258–259, 268, 273
    - impairment factor for bandwidth restriction (*I<sub>bw</sub>*), 186, 208
    - impairment factor for speech clipping (*I<sub>cl</sub>*), 115
    - packet loss impairment factor (*I<sub>loss</sub>*), 122
    - simultaneous impairment factor (*I<sub>s</sub>*), 45–46, 122, 256
    - wideband equipment impairment factor *I<sub>e,wb</sub>*, 189–190, 209–210
- in-service non-intrusive measurement device (INMD), 43, 47–48
- instrumental
  - measure, 24, 40–42, 49–50,
  - measurement (methods), 1, 18, 24, 39–48, 58, 62, 103–108, 147, 153, 228, 233–235, 253
- intelligibility, 9–11, 11–13, 25–26, 35–36, 70, 78, 84, 85, 87–89, 93, 120, 143, 162, 165–166, 169, 197–198, 203, 206–207, 282
- intermediate reference system (IRS), 82, 85–88, 90–91, 177, 182–183, 188, 192–196, 226, 235, 237–238
- internet protocol (IP), 48, 52–57, 68, 79, 117, 220–223, 229–233

- interview, 32
- isometric evaluation, 24, 35–36
- jitter, 22, 53, 55–57, 61–63, 72–74, 100, 106–107, 220–223, 231–232  
 buffer, 55–57, 72–74, 76, 107, 220–223  
 distribution, 221, 231–232
- LBR, *see* low bit-rate redundancy
- linear distortion, *see* distortion, linear distortion
- listener sidetone, *see* sidetone
- listening–effort, 3, 26, 35, 85, 203
- Local Area Network (LAN), 53
- Lombard effect, 13, 22, 84
- loudness, 6, 8, 13, 15, 26, 38, 43–44, 76–78, 82–83, 84, 86, 87, 89, 93, 98, 108, 233, 237  
 binaural loudness, 194  
 rating, 43–44, 48, 82–83, 98, 106, 170, 199, 207, 226, 234, 255–257  
 overall loudness rating (OLR), 43–44, 106, 170, 255–256  
 receive loudness rating (RLR), 43–44, 106, 194, 226, 234–235, 255–259  
 send loudness rating (SLR), 43–44, 106, 121, 155–157, 170, 226–227, 234–235, 237, 255–259  
 talker echo loudness rating (TELR), *see* echo, talker echo, talker echo loudness rating
- Loudspeaker-Enclosure-Microphone system (LEM), 80–81
- low bit-rate redundancy (LBR), 57, 70
- magnitude estimation, 33, 87, 93, 187
- Markov model, Markov chain  
 2-state, 64–68, 72, 75, 123–129, 135, 137, 220, 267  
 3-state, 135–137, 138–140, 142–145, 151, 162, 170, 271–274  
 4-state, 68–69, 135, 138, 141, 147–148, 171, 217–219, 232  
 n-state, 68, 232
- masking, 6, 58, 79, 82–84, 122, 156–157, 162, 168–170, 207, 257  
 backward recognition masking, 8
- mean opinion score (MOS), 26–27, 31, 33–34, 251–254, 258  
 MOS-LQO, MOS-LQS, MOS-LQE, 253
- mobile communication, 52–53, 84, 94, 212, 228
- modulated noise reference unit (MNRU), 60, 92, 99, 177, 226, 251–253
- monitoring, 18, 20, 43, 46–48, 72, 103–108, 130–141, 228
- monotic, 89, 193–196, 235–236
- MOS, *see* mean opinion score
- motivation, 15, 21, 100
- mouth reference point (MRP), xviii, 193
- multidimensional  
 assessment, 35–39, 59–60, 91–98, 99, 151–154  
 scaling (MDS), 35–37, 59–60, 91–98, 99, 151–153, 163
- nature  
 desired nature, 15–19, 20, 38, 99–102, 113, 176, 190–203, 215–216, 281, *see also* feature, desired feature  
 perceived nature, 15–19, 20, 196, 215, 281, *see also* feature, perceived feature
- narrowband (NB), 28, 57–59, 61, 82–83, 85–90, 101, 104–105, 176–181, 181–188, 189–190, 192–197, 208–210, 226–231, 245–246
- naturalness  
 perceived, 12, 37, 42, 60–61, 87–92, 95, 121–122, 187  
 of situation, 15, 30–32, 182, 236,
- network  
 access, 101  
 element, component, 16, 18, 29, 40–42, 56–58, 61, 99, 108  
 planning, xxiii, 16, 18, 20–46, 175  
 simulation, 228, 231–232
- noise, 83–85, 155–157, 163–165, 168  
 ambient noise, 84, 91  
 background, 56–57, 84, 104  
 circuit noise, 44, 84, 101, 189  
 comfort noise, 37, 57, 58, 84  
 floor, 44, 228, 255  
 impulsive noise, 48, 84  
 line noise, 44, 46, 83–84, 86, 121, 138, 151, 154–157, 162–165, 168–172, 206–208 *see also* noise floor, circuit noise

- signal–correlated noise, 46, 60, 76, 77, 84, 92
- suppression, 85
- non-linear distortion, 175–203, 208–210
- normalization, 92, 118, 125, 126, 155, 158, 159, 178, 179, 184, 185, 251–254
- OLR, 43–44, 106, 170, 207, 255, 256
- order effects, 150
- packet, 52–53
  - arrival time, 222, 223
  - delay, 57, 221
  - header, 53, 55, 57, 104
  - loss, 63–78, 113–123, 151–172, 205–206, 219–223
    - packet loss concealment (PLC), 56, 70, 112, 117, 206, 230, 268
    - packet loss percentage (*Ppl*), 45, 63, 113, 115, 123, 127, 132, 134, 146, 164, 206, 258
    - packet loss probability (*ppl*), 222
    - distribution, 58, 63–69, 70, 72, 74, 84, 108, 124, 130, 137, 220, 243,
    - robustness factor (*Bpl*), 45, 117, 119, 122, 123
  - network, 57, 59, 63, 65, 72, 220, 222
  - size, 52, 63, 69, 71–75
- packet-based system, 20, 59
- packet-based transmission, xxii, 59, 75–76, 103, 108, 111
- payload, 52, 71
  - size, 71
- perceptual analysis measurement system (PAMS), 41
- perceptual evaluation of speech quality (PESQ), 40, 41, 48, 74, 75, 104, 105, 108, 254
- perceptual speech quality measure (PSQM), 41, 48, 73, 104
- pitch, 5, 7–8, 15, 86
  - fundamental frequency, *see* fundamental frequency
- playout
  - delay, 221, 222
- PLC, 45, 56, 57, 63, 70, 72–75, 94, 106, 108, 112, 113, 115–123, 129, 206, 230, 268, 271
- polarity profile, 35
- PoW, 258
- power law, 87, 187
- prediction model, 40, 43, 48, 82, 152, 214
  - input parameters, 155, 268
- presentation method, 25, 26, 89
- price, 101
- prosody, 4
- psophometer, 234
- psychological factors, 45
- psychometric methods, 25
- public switched telephone network, 51, 225
- Q, 92, 178, 251–252
- quality, 15
  - apparent quality, 213
  - assessment, 16–18, 192, 197, 238
  - elements, 18–19, 20, 21, 51–110, 219–223
  - end-to-end quality, 19
  - event, 17, 28, 77
  - feature, 16–21, 24, 40, 43, 49, 51, 55, 58, 59–61, 62, 71–72, 74–75, 76–78, 79, 80–82, 84–85, 86–90, 91–99, 103, 108–109, 111, 151–173
  - instantaneous quality, 19, 28, 49, 72, 76, 132, 140, 282
  - integral quality, xxiv, 19, 24, 26–28, 33, 37, 40, 42, 54, 59–60, 76–78, 81, 85, 93–96, 99, 112, 129–147, 151–157, 167–170, 182, 206, 215–216, 269, 277–280
  - mouth-to-ear quality, 19, 41, 47, 85
  - overall quality, 19, 38, 109, 152, 153, 175, 194
  - perception, 16, 49, 71, 197–203, 214
  - planning quality, xxii, xxiii, 43–46, 135, 151, 214
  - of experience(QoE), 20, 282
  - of service (QoS), 19–22, 55–56
  - speech quality, 1–22, 23–50, 103–108
  - speech sound quality, 86–90
  - speech transmission quality, 8, 19, 22, 74, 78, 91, 94–95, 119, 152, 153, 192, 282
  - subjective and objective quality, 17–18, 24, 281
  - test, 16–18, 24, 26–30
  - user directed quality, 16, 18, 20–21, 55
  - voice transmission quality, 21, 22

- quantizing distortion, 256–257  
 unit (qdu), xvi, 256–257
- questionnaire, 102–103, 112
- rating  
 absolute category rating (ACR), 26, 28, 88, 96, 194, 265  
 comparison category rating (CCR), 27  
 degradation category rating (DCR), 27  
 paired comparison rating (PC), 26, 27, 28, 37, 40, 87, 181
- real-time transport  
 control protocol (RTCP), 107  
 control protocol extended reports (RTCP XR), 107  
 protocol (RTP), 52, 57, 104, 124
- reference  
 internal, 41, 91  
 signal, 19, 25
- reliability, 25, 105
- RLR, 43, 44, 106, 194, 226–228, 234, 255–257, 259, 268, 273
- robust header compression (ROHC), xix
- root mean squared error (RMSE), 94, 96, 119, 146, 171, 186, xix
- running quality index, 40, 49, 87
- satisfaction, 19, 20, 27
- scale  
 CCR, 27, xvii  
 conversation quality scale, 27  
 CR–10 scale, 33, 34, 126, 138, 154, 155, 181, 265, 269, 272,  
 DCR scale, 27, 28  
 level, 25  
 loudness preference scale, 39  
 psychological scale, 45  
 transmission rating scale, 45–46  
 wideband extension, 178, 179
- scaling, 2, 3, 9, 13, 14, 15, 41–46, 48, 49  
 absolute category scaling, 26–27, 28, 85, 88, 96, 194, 265  
 attribute scaling, 35, 94, 96  
 category–ratio scaling, 33  
 multidimensional scaling, 2, 9, 13–14, 41–43, 45, 46, 48, 49  
 ratio scaling, 45, 86, 98, 155, 181
- schema, 15, 18, 22, 25
- semantic differential, *see* scaling, attribute scaling
- semantically unpredictable sentences (SUS), 23
- semiotic triangle, 2
- service, 102  
 integrity, 52, 216, 225  
 operability, 19–20  
 performance, 19–20  
 security, 19–20  
 serveability, 19–20  
 support, 19–20
- session initiation protocol (SIP), 52
- short message service (SMS), xix, 100
- sidetone, 45, 79, 91, 225, 227, 235, 240, 257,  
 listener sidetone rating (LSTR), xv, 45, 91, 259
- masking rating (STMR), xvi, 45, 91, 257, 259
- sign, 2, 197
- signal-to-correlated-noise-ratio, 76, 77, 252
- signal-to-noise-ratio (SNR), xix, 39, 46, 83, 85, 156–157, 170, 191, 207, 211, 255
- SLR, 43, 44, 156, 170, 226, 227, 235, 259, 268
- SNR, *see* signal-to-noise-ratio (SNR)
- sojourn, 69, 123, 137, 148, 217–219  
 time, 123, 137, 141, 148
- sound  
 event, xvi, 1, 86  
 quality, 86–90, 97, 109, 182, 274–275  
 speech sound quality, *see* quality,  
 speech sound quality
- speaker, 3–4, 81, 87, 115, 127, 150, 202–203, 274  
 alternation rate (SAR), 148, xix
- speech, 1–13  
 clipping, 81, 82, 115, 117  
 coding, codec, xxiv, 55, 58–59, 78, 117, 214  
 form and content, 81–82, 115, 117  
 intelligibility, 10, 84, 85, 88, 169, 211, 212, 216  
 level, 4, 26, 46, 83, 98, 156, 193, 198  
 perception, 3, 4–13  
 production, 3, 58  
 quality, *see* quality, speech quality  
 recognition, 9, 10, 243  
 speech sound quality, *see* quality, speech sound quality  
 synthesis, 25, 119, 122, 197, 198, 243

- spoken dialogue systems, 20, 121, 243  
SUBMOD model, 43, 47, 48, 176
- talker echo loudness rating (TELR), *see*  
echo, talker echo, talker echo loudness  
rating
- technologies, 23, 52, 54, 78–79, 100, 111,  
215, 226, xxi
- telecommunication system, xxii, 18, 30, 39
- Telekom objective speech quality measure  
(TOSQA), 41, 105
- telephone line simulation, 193, 225
- TELR, 44, 79, 154, 158, 159, 160, 167,  
168, 256, 257, 259, 270,
- terminal  
coupling loss (*TCL<sub>w</sub>*), 44, 79, 268  
equipment, 194
- terminal equipment, 194  
hands-free terminal, xviii, 56, 57, 79, 80,  
88, 89, 90–91, 96, 97, 193, 238–241
- test, 16, 25–32, 92, 94, 123–126, 241,  
265–275  
articulation and intelligibility test, 25  
auditory test, xxii, 2, 11, 16, 25, 49, 76,  
85, 265–275  
Cluster Identification test (CLID test), 25  
conditions, 31, 35, 124, 127, 138, 139,  
140, 155, 167, 177, 189, 231, 252,  
265, 268  
conversation test (CT), 3, 26, 29, 30–32,  
99, 101, 113, 114, 115, 119, 135,  
138, 142–146, 148, 154, 165–166,  
227, 268–274  
diagnostic rhyme test (DRT), xvii, 26  
double-talk test, 29–30, 47, 49, 63, 79,  
81, 82, 147, 148, 169  
informal test, 237  
interactive short conversation test (iSCT),  
32, 147–151, 261–263  
interference test, 26  
isopreference test, 26, 28, 92  
Kandinsky test, 31  
laboratory test, 16, 27, 225  
language material, 124  
listening-only test (LOT), xviii, 114,  
115, 119, 177, 178, 194, 267  
modality, 25  
modified rhyme test (MRT), xviii, 26  
scenario, 1, 16, 31–32, 261–263, 269  
short conversation test (SCT), 31–32, 49,  
149–150, 155, 166, 268, xix  
speakers, 127, 262, 263  
subjects, 16, 30, 32, 34, 36, 94, 99,  
101–102, 119, 131, 138, 142, 144,  
147, 154, 157, 161, 164–165, 270,  
272–273  
talking and listening test, 30
- timbre, 86–87, 88–91, 184
- time-varying, 3, 61, 63, 78, 80–82  
delay, 61  
distortion, 14, 19, 22, 28, 31, 53–54, 61,  
71–72, 74–75, 76–78, 81–82, 94,  
96, 101, 103, 111–173, 205–208  
noise, 52, 77, 84  
quality, 8, 19, 28–29, 31, 49, 71–72,  
76–78, 108, 129–147, 162–168,  
205–207
- transmission  
control protocol (TCP), 52, 53, 221, xix  
elements, 107–108  
errors, 14, 22, 40, 44, 60, 252  
parameters, xxiv, 225  
paths, 43, 44, 59, 84, 90, 225  
planning, 175  
rating factor, 46, 132, 155, 157–158,  
161, 167–168, 178, 213
- universal mobile telecommunications  
service (UMTS), 54, xix
- usability, 22
- user, 90–91, 192–197, 234–241, 247–250  
group, 25, 34, 101–102  
interface, 194–196
- user datagram protocol (UDP), 52, 53,  
221
- utility, 22
- validity, 25, 34, 35, 36, 98, 105, 107–108,  
151
- voice, 9, 13, 30, 58, 199  
quality, 8, 108, 200
- voice activity detector/detection (VAD), 57,  
58, 108, 120, 230, 271, xix
- voice over internet protocol (VoIP), 18,  
51–110, 211, 229–233, xix
- W-CDMA, 54
- Weibull distribution, 221, 223
- wideband (WB), 59, 61, 89, 175–203,  
208–210, 234, 235, 246, 248, xix, xxv
- wireless local area network (WLAN), 52,  
63, 78, 111