

Index

Note to the reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

Symbols & Numbers

? (question mark), for command listing, 162–163
 ^ (caret), 164
 8-pin modular connector, 36
 10Base2 standard, 37
 10Base5 standard, 37
 10BaseT standard, 37
 100BaseFX (IEEE 802.3u), 37
 100BaseTX (IEEE 802.3u), 37
 802.3 Committee, 36
 standards, 37
 802.3 Ethernet, frame format, 34
 802.3ab (Gigabit Ethernet on category 5), 36
 802.3ae (10Gbps over fiber and coax), 36
 802.3u (Fast Ethernet), 36, 37
 1000BaseCX (IEEE 802.3z), 37
 1000BaseLX (IEEE 802.3z), 38
 1000BaseSX (IEEE 802.3z), 38
 1000BaseT (IEEE 802.3ab), 38

A

access layer of Cisco model, 48
 Acknowledgment number field, in TCP header, 72
 acknowledgments, 17, 20
 address learning by Layer 2 switches, 295, 296–297
 Address Resolution Protocol (ARP), 45, 85–87
 local broadcast, 87
 administrative_distance, 238, 239, 254–255
 default, 255
 agents in SNMP, 69
 anonymous user for FTP, 67
 answer in [], questions with, 184
 Application layer (OSI), 14–15
 application servers, and OSI model layers, 13
 application-specific integrated circuit (ASIC), 24

ARP (Address Resolution Protocol), 85–87
 local broadcast, 87
 ARP cache, 221
 Arp command, 135
 Asynchronous Transfer Mode (ATM), 382
 Attachment Unit Interface (AUI), 37
 attenuation, 36
 AUI (Attachment Unit Interface), 37
 authentication
 in PPP session, 387
 through TACACS server, 171
 auto-detect mechanism, 32
 autonomous system (AS), 254
 auxiliary password, 170, 172
 auxiliary port, connecting to Cisco router through, 154

B

backbone, collapsed, 290
 backoff algorithm, in CSMA/CD, 30, 31
 backup
 of Cisco IOS, 325–331
 of Cisco router configuration, 331–333
 bandwidth, 190, 383
 wasting, 271
 bandwidth command, 183–184
 banners, 169–170
 baseband, 37
 baseline for SNMP, 69
 binary numbering, 25–26
 conversion to decimal, 26–27
 converting to hex, 28
 for IP address, 89
 binding, 11
 bit, 25, 89
 bit-oriented protocols, 385
 blocked port, 302
 boot process, for router, 155
 boot sequence, interrupting, 323
 boot system command, 324
 bootloader, 317

462 bootstrap – Class B network

bootstrap, 316, 317
 Bootstrap protocol (BootP), 69–70
 bridge ID, 301
 Bridge Protocol Data Unit (BPDU), 301
 bridges, 292
 at Data Link Layer, 24–25
 vs. LAN switching, 295
 bridging, 7
 broadcast address, 4, 89
 for subnet, 113
 broadcast domain
 routers to break up, 5, 6
 size of, 9
 broadcast storm, 299, 299
 buffer, 17
 full, ICMP and, 83
 byte, 25, 89
 and hex character, 28
 byte-oriented protocols, 385

C

cabling
 categories, 36–37
 Ethernet, 38–42
 crossover, 39, 39
 rolled, 39–42, 40
 straight-through, 38, 38–39
 for WAN, 382–384
 serial transmission, 393
 call setup, 16
 caret (^), 164
 Carrier Sense Multiple Access with Collision
 Detection (CSMA/CD), 30, 31
 CDP (Cisco Discovery Protocol), 334–344
 for documenting network topology,
 341–344, 342, 344
 timers and holdtime information, 335
 cdp enable command, 340
 central office (CO), 379
 Challenge Handshake Authentication
 Protocol (CHAP), 388
 channel service unit/data service unit
 (CSU/DSU), 29, 384
 Checksum field
 in TCP header, 72
 in UDP segment, 74
 CIDR (Classless Inter-Domain Routing),
 110–111
 circuit switching, 379, 380
 Cisco
 editing features, 162–166
 troubleshooting recommendations,
 133–135
 Cisco 2500 series routers, changing
 configuration bit value, 323
 Cisco 2501 router, interfaces and
 connections, 154, 154
 Cisco 2600 router
 changing configuration bit value, 323
 interfaces and connections, 154, 154
 Cisco Discovery Protocol (CDP), 334–344
 for documenting network topology,
 341–344, 342, 344
 timers and holdtime information, 335
 Cisco Internetwork Operating System,
 153–156
 backup and restore, 325–331
 Cisco routers
 backup and restore of configuration,
 331–334
 boot sequence, 317–318
 checking utilization, 359
 connecting to, 153–154
 internal components, 316–317
 on internetwork, 316
 passwords for, 170–174
 proprietary 60-pin serial connector, 383
 serial interfaces, 383
 Cisco three-layer hierarchical model,
 46–48, 47
 access layer, 48
 core layer, 47
 distribution layer, 48
 CiscoFusion, 153
 Class A network, 90, 91
 IP addresses, 93–94
 reserved IP address space, 95
 subnetting, 127–129
 in your head, 129
 Class B network, 90, 92
 IP addresses, 94
 reserved IP address space, 95
 subnetting, 120–126
 in your head, 126

- Class C network, 90, 92
 - IP addresses, 94–95
 - reserved IP address space, 95
 - subnetting addresses, 112–119
 - in your head, 119
 - Class D network, 92
 - Class E network, 92
 - classful routing, 108, 130, 130, 258, 260
 - Classless Inter-Domain Routing (CIDR), 110–111
 - classless routing, 108, 130, 131, 258
 - clear counters command, 191
 - clock rate command, 183, 193, 233, 237
 - clocking, 182, 182–183
 - closing Telnet sessions, 348–349
 - Code bits field, in TCP header, 72
 - collapsed backbone, 290
 - collision domains, 10, 292
 - switches to break up, 7
 - collisions, in Ethernet LAN, 30
 - command-line interface (CLI), 157–168
 - editing and help features, 162–166
 - logging into router, 158
 - prompts, 159–162
 - interfaces and connections, 160
 - line commands, 161
 - routing protocol configuration, 161
 - subinterfaces, 160
 - router modes, 158–159
 - commands, ? (question mark) for listing, 162–163
 - communication, connection-oriented, 16–18, 17, 71
 - Compaq, 300
 - composite metric, 269
 - for IGRP, 266
 - config-register command, 321, 325
 - configuration register, 317, 318–325
 - bits, 318–319
 - Boot field, 319
 - changing, 320–322
 - checking current value, 320
 - configurations
 - copying to TFTP server, 333
 - deleting, 186, 334
 - restoring, 333–334
 - verifying, 186–192
 - with show interface command, 186–192
 - with show ip interface command, 192
 - with show protocols command, 193
 - viewing and changing, 324–325
 - viewing, saving, and erasing, 184–195
 - configure memory command, 159
 - configure network command, 159
 - configure terminal command, 158–159
 - connected interface, default administrative distance, 255
 - connection-oriented communication, 16–18, 17, 71
 - connectionless protocol, 74
 - connectivity of network, checking, 354–360
 - connector, setting type, 179
 - console password, 170, 173
 - console port, 153
 - converged routing tables, 257, 258
 - convergence, 303
 - copy flash tftp command, 326, 327, 328
 - copy run start command, 330, 331
 - copy running-config startup-config command, 184, 332
 - copy running-config tftp command, 331, 333
 - copy startup-config running-config command, 333
 - copy startup-config tftp command, 331
 - copy tftp flash command, 328–329
 - core layer of Cisco model, 47
 - crossover cabling, 39, 39
 - CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 30, 31
 - CSU/DSU (channel service unit/data service unit), 29
 - cumulative interface delay, 269
 - customer premises equipment (CPE), 379
 - cut-through (FastForward) switch, 303, 304
-
- ## D
- data communication equipment (DCE), 29, 384
 - data encapsulation, 42–46, 43
 - Data field
 - in IP header, 81
 - in TCP header, 72
 - in UDP segment, 74
 - data frame, 23

464 Data Link layer (OSI) – erase startup-config command

Data Link layer (OSI), 23, 23–28
 data encapsulation, 43
 Ethernet at, 33–36
 switches and bridges, 24–25, 25
 data packets, 21
 data terminal equipment (DTE), 29, 384
 Cisco routers as, 182
 datagrams, 43
 DCE (data communication equipment),
 29, 384
 de-encapsulation, 43
 debug all command, 357–358
 Debug command, 357–358
 debug ip igrp command, 276
 debug ip igrp events command, 276
 debug ip igrp transactions command, 276–277
 debug ip rip command, 274–275
 DEC (Digital Equipment Corporation), 300
 decimal numbering, binary conversion to,
 26–27
 default administrative_distance, 255
 default gateway, ping, 134
 default routing, 242–244
 default subnet mask, 110
 default time-out, for console EXEC
 session, 173
 deleting
 configurations, 186, 334
 startup-config, 334
 delimiting character, for banner, 170
 demarcation point, 379, 384
 Department of Defense (DoD) model
 layers, 65
 vs. OSI model, 65
 and TCP/IP, 64–88, 66
 description command, 177
 descriptions, setting on interface, 177–178
 designated port, 302
 desktop layer, 48
 Destination Address (DA), in Ethernet
 frame, 34
 Destination IP address field, in IP header, 81
 destination MAC address (hardware
 address), 227
 “destination network unreachable”
 message, 222, 225
 ICMP and, 83
 destination port, 77–78

Destination port field
 in TCP header, 72
 in UDP segment, 74
 DHCP (Dynamic Host Configuration
 Protocol), 69–70
 diagnostic address, 133
 Digital Equipment Corporation (DEC), 300
 disable command, 158
 disabled port, 302
 disconnect command, 348
 distance vector routing protocols, 255–256,
 256–257, 257
 distribution layer of Cisco model, 48
 DIX (Digital, Intel and Xerox), 36
 DNS (Domain Name Service), 4, 69
 vs. host table, 354
 IP address of server, 353
 name resolution with, 352–354
 documenting network topology, with CDP,
 341–344, 342, 344
 DoD model. *See* Department of Defense
 (DoD) model
 dotted-decimal addressing, 89
 DTE (data terminal equipment), 29
 Dynamic Host Configuration Protocol
 (DHCP), 69–70
 dynamic routing, 219, 254

E

EEPROM (electronically erasable
 programmable read-only
 memory), 155
 EGPs (exterior gateway protocols), 254
 EIA (Electronic Industries Association), 36
 Electronic Industries Association (EIA), 36
 email, SMTP for, 68
 enable command, 158
 enable password, 170, 171–172
 for Telnet, 346
 enable secret password, 170
 encapsulation, 42–46, 43
 of PPP, 389
 Enhanced IGRP, 270
 default administrative distance, 255
 erase startup-config command, 186

erasing
 configuration, 334
 flash memory, 330

Ethernet, 30–38
 cabling, 38–42
 crossover, 39, 39
 rolled, 39–42, 40
 straight-through, 38, 38–39

at Data Link Layer, 33–36
 addressing, 33, 33
 Ethernet frames, 34, 34–36
 half- and full-duplex, 32–33
 at Physical layer, 36, 36–38

Ethernet II, frame format, 34, 35

Etherpeek analyzer software, TCP session
 capture, 76–77

exec banner, 170

exec process creation banner, 169

EXEC session, 153

exec-timeout 0 0 command, 173

exit command, 348

exit interface, 243

exterior gateway protocols (EGPs), 254

F

Fast Ethernet (802.3u), 36, 37, 292

FastForward (cut-through) switch, 303, 304

File Transfer Protocol (FTP), 67
 when to use, 68

fixed configuration router, 179

Flags field, in IP header, 80

flash memory, 155, 317
 erasing, 330
 loading Cisco IOS from, 318
 verifying, 326–327

flat addressing scheme, advantages, 90

flow control, 16

flush timers, for IGRP, 267

forward/filter decisions, 297–299

forward/filter table, 295
 populating, 297

forwarding port, 302

FQDN (fully qualified domain name), 69

Fragment offset field, in IP header, 81

FragmentFree (modified cut-through)
 switch, 303, 304

Frame Check Sequence (FCS), 35, 222

frame filtering, 297–298

Frame Relay, 381

frames in Ethernet, 34, 34–36
 packet encapsulation in, 43

FTP (File Transfer Protocol), 67
 when to use, 68

full-duplex Ethernet, 32–33

fully qualified domain name (FQDN), 69

G

gateway of last resort, 243

gateways, and OSI model layers, 13

Gigabit Media Independent Interface
 (GMII), 37

global command, 158–159

global configuration mode, 162

H

half-duplex Ethernet, 32–33

hardware address. *See* MAC address
 (hardware address)

hardware addressing, 80
 for Data Link layer, 24
 Ethernet for, 33

HDLC (High-Level Data Link Control)
 protocol, 381, 385
 frame format, 385

Header checksum field, in IP header, 81

Header length field
 in IP header, 80
 in TCP header, 72

hexadecimal numbering, 27–28
 for configuration register address, 318
 converting binary to, 28
 for IP address, 89

hierarchy, 46

High-Level Data Link Control (HDLC)
 protocol, 381, 385
 frame format, 385

history of router commands, 165

holddown timer, 258
 for IGRP, 267

hop count, 22, 255, 262
 limits, ICMP and, 83
 RIP use of, 256, 257

466 host address – Internet Protocol (IP)

host address, 90

host IDs

- for Class A network, 94
- for Class B network, 94
- for Class C network, 95
- per subnet, 108

host table

- vs. DNS server, 354
- for name resolution, 350–352

Host-to-Host layer (DoD), 65

protocols, 70–79

- key concepts, 75–76
- port numbers, 76–79
- Transmission Control Protocol (TCP), 71–73

User Datagram Protocol (UDP), 73–74

hostname command, 168–169, 388

hostnames, 168–169

- DNS (Domain Name Service) for resolving, 69

resolving, 350–354

hub network, 290

hubs, 5, 29, 293

- at Physical layer, 29
- vs. switches, 10, 25

hybrid protocols, 257

HyperTerminal, to create console connection, 40, 40

I

I, in routing table, 269

ICMP (Internet Control Message Protocol), 83–85, 86, 221, 224, 227

error message, 84

Identification field, in IP header, 80

IEEE 802.3ab (1000BaseT), 38

IEEE 802.3u (100BaseFX), 37

IEEE 802.3u (100BaseTX), 37

IEEE 802.3z (1000BaseCX), 37

IEEE 802.3z (1000BaseLX), 38

IEEE 802.3z (1000BaseSX), 38

IEEE Ethernet Data Link layer, sublayers, 24

IGPs (interior gateway protocols), 254

IGRP. *See* Interior Gateway Routing Protocol (IGRP)

“in-band,” 154

incoming banner, 169, 170

int serial command, 178

Integrated Services Digital Network (ISDN), 381

interface command, 160

interface configuration mode, 160

interface ethernet command, 179

interfaces, 178–184

bringing up, 179–180

checking status, 180

configuring IP address on, 180–181

information gathering on traffic, 339

in routing table, 22

setting descriptions on, 177–178

summarizing commands, 181

interior gateway protocols (IGPs), 254

Interior Gateway Routing Protocol (IGRP), 266–272

configuring routing, 267–269

decision to use, 270

default administrative distance, 255

load balancing, 272

vs. RIP, 266

timers, 267

troubleshooting, 270–271

using with RIP, 271, 271–272

verifying routing tables, 269–270

International Organization for Standardization (ISO), 10

Internet, 292

Internet Control Message Protocol (ICMP), 83–85, 86, 221, 224, 227

error message, 84

Internet Explorer (IE), 14

Internet layer (DoD), 65

Address Resolution Protocol (ARP), 45, 85–87

local broadcast, 87

Internet Control Message Protocol (ICMP), 83–85, 86, 221, 224, 227

error message, 84

Proxy Address Resolution Protocol (Proxy ARP), 88, 88

Reverse Address Resolution Protocol (RARP), 87–88, 88

Internet Protocol (IP), 80–82, 221

header, 81

internetworking

- basics, 3, 3–10
 - defining terminology, 7
- exam essentials, 49–50
- models, 10–12. *See also* Cisco three-layer hierarchical model; Open Systems Interconnection (OSI) reference model
- RIP use in, 264
- routers in, 22
- invalid timers, for IGRP, 267
- IOS (Cisco Internet Operating System), 153–156
 - backup and restore, 325–331
- ip address command, 180
- IP addresses, 80, 89–96
 - configuring, 231–232
 - configuring on interface, 180–181
 - determining problems, 135–140
 - for diskless machines, 87
 - of DNS server, 353
 - hierarchical scheme, 89–95
 - private, 95–96
 - reserved, 92–93
 - troubleshooting, 133, 133–140
- ip classless command, 243–244
- ip domain-lookup command, 353
- ip domain-name command, 353
- ip host command, 350
- IP (Internet Protocol), 80–82, 221
 - header, 81
- ip name-server command, 353
- ip route command, to add static route, 238
- IP routing, 218
 - configuring, 230–244
 - process, 220, 220–237
 - testing understanding, 226–230
- IP subnet-zero command, 107
- Ipconfig /all command, 135
- ISDN (Integrated Services Digital Network), 381
- ISO (International Organization for Standardization), 10

J

jam signal, in CSMA/CD, 30

K

keepalives, 190

kernel, 153

L

LAN (local area network)

- first switched, 292
- switch types, 303–304
- traffic congestion, 5

LAN Manager, 291

LAPB (Link Access Procedure, Balanced), 381

LAPD (Link Access Procedure, D-Channel), 381

latency, 24

Layer 2 switching, 290–293, 291

- functions, 295–300
- limitations, 294–295

layer 3 switches, 7

layered architecture, 11

LCP (Link Control Protocol), 386

learning port, 302

leased lines for WAN, 379, 382

Length field

- in Ethernet frame, 35
- in UDP segment, 74

line command, for user-mode password assignment, 171–172

line console 0 command, 161, 173

Line Printer Daemon (LPD), 68

line vty command, 174

Link Access Procedure, Balanced (LAPB), 381

Link Access Procedure, D-Channel (LAPD), 381

Link Control Protocol (LCP), 386

link-state protocols, 257

listening port, 302

load balancing

- by IGRP, 267
- by RIP, 256

local loop, 379

logging synchronous command, 173

logical address, 80

Logical Link Control (LLC) 802.2, 24

logical segmentation, 293

logical topologies, 24

468 login banner – Open Systems Interconnection (OSI) reference model

login banner, 169, 170
 login command, 172
 logout command, 158
 loopback tests, 133
 reserved IP address for, 92
 loops
 avoidance, 296, 299–300
 in layer 2 switched internetwork, 290
 LPD (Line Printer Daemon), 68

M

MAC address (hardware address), 3, 221
 destination, 227
 Ethernet for managing, 33, 33
 MAC frame format, 34
 mainframe network, 291
 mask locations, 242
 maximum transmission units (MTUs), 190
 MD5 hash function, 388
 Media Access Control (MAC) 802.3, 23–24
 Media Independent Interface (MII), 37
 media translation, 25
 media-type command, 179
 message of the day (MOTD) banner, 169–170
 metric, in routing table, 22
 MII (Media Independent Interface), 37
 Mini-IOS, 317
 modem, for router connection, 154
 modified cut-through (FragmentFree)
 switch, 303, 304
 MOTD (message of the day) banner, 169–170
 MTUs (maximum transmission units), 190

N

name resolution
 with DNS, 352–354
 host table for, 350–352
 NAT (Network Address Translation), 95
 NCP (Network Control Protocol), 386, 387
 neighbors, information gathering on,
 336–339
 network
 checking connectivity, 354–360
 documenting topology, with CDP,
 341–344, 342, 344

 segmentation, 4
 traffic, subnetting and, 106
 Network Access layer (DoD), 65
 Network Address Translation (NAT), 95
 network addresses, 89, 90–92
 classes, 91
 in routing table, 21
 network command, 259
 Network Control Protocol (NCP), 386, 387
 Network File System (NFS), 67–68
 network hosts, and OSI model layers, 13
 network IDs, required number, 108
 network interface card (NIC), testing, 134
 Network layer (OSI), 21–22
 data encapsulation, 43
 obtaining neighbor's address, 187
 network management stations (NMSs), and
 OSI model layers, 13
 next-hop_address, 238
 NFS (Network File System), 67–68
 nibble, 25, 37
 and hex character, 28
 NIC (network interface card), testing, 134
 no cdp enable command, 339–340
 no cdp run command, 335
 no debug all command, 275
 no ip domain-lookup command, 352
 no ip host command, 352
 no ip route command, 259
 no login command, 174
 no shutdown command, 179, 180
 node address, 90
 nondesignated port, 302
 nonroot bridge, 301
 “not ready” indicator, 18
 Novell, 291
 number conversion
 binary to decimal, 26–27
 binary to hex, 28
 NVRAM (nonvolatile RAM), 155, 317
 copying current configuration to,
 332–333

O

octet, 89
 Open Systems Interconnection (OSI)
 reference model, 10, 12–29

- Application layer, 14–15
 - Data Link layer, 23, 23–28
 - data encapsulation, 43
 - Ethernet at, 33–36
 - switches and bridges, 24–25, 25
 - vs. DoD model, 65
 - layer functions, 14
 - lower layers, 13
 - Network layer, 21–22
 - data encapsulation, 43
 - obtaining neighbor's address, 187
 - Physical layer, 29
 - encoding by, 43
 - Ethernet at, 36, 36–38
 - Presentation layer, 15
 - Session layer, 15
 - Transport layer, 15–20
 - acknowledgments, 20
 - connection-oriented communication, 16–18, 17
 - flow control, 16
 - reliable delivery, 20
 - windowing, 19, 19–20
 - upper layers, 12, 13
 - Options field
 - in IP header, 81
 - in TCP header, 72
 - organizationally unique identifier (OUI), 33
 - OS/2, 291
 - OSI. *See* Open Systems Interconnection (OSI) reference model
 - OSPF, default administrative distance, 255
 - OUI (organizationally unique identifier), 33
 - “out-of-band,” 154
-
- P**
- packages, dropping on return trip, 224
 - Packet Internet Groper (Ping). *See* Ping (Packet Internet Groper)
 - packet switching, 7, 380, 380
 - packets, 43, 45
 - PAP (Password Authentication Protocol), 387
 - parallel transmission, 383
 - parameters for commands, listing, 163
 - passive-interface command, 264
 - Password Authentication Protocol (PAP), 387
 - password-encryption command, 175–176
 - passwords, 388
 - for Cisco routers, 170–174
 - encrypting, 175–177
 - recovering, 322–325
 - for remote device, 345
 - permanent parameter, for route in routing table, 240
 - Physical layer (OSI), 29
 - encoding by, 43
 - Ethernet at, 36, 36–38
 - hubs at, 29
 - physical network, testing, 134
 - Ping (Packet Internet Groper), 85, 327, 354, 355
 - and ICMP, 83
 - for IP address troubleshooting, 133–135
 - limitations, 186
 - pinhole congestion, 256, 257, 271
 - point of presence, 379
 - point-to-point connection, 379
 - for full-duplex Ethernet, 32
 - Point-to-Point Protocol (PPP), 381, 386–389
 - authentication configuration, 388–389
 - authentication methods, 387–388
 - configuring on Cisco routers, 388
 - protocol stack, 386
 - session establishment, 387
 - verifying encapsulation, 389
 - port cost, 302
 - port numbers, 76–79
 - at Transport layer, 44, 45
 - well-known, 79
 - ports, information gathering on, 339–341
 - positive acknowledgement with
 - retransmission, 20
 - power-on self-test (POST), 155, 316, 317
 - powers of 2, 108–109
 - preamble, in Ethernet frame, 34
 - prefix routing, 258
 - Presentation layer (OSI), 15
 - printers, Line Printer Daemon (LPD) for
 - sharing, 68
 - Priority and Type of Service field, in IP header, 80, 81
 - private IP addresses, 95–96
 - privileged exec mode (privileged mode), 156, 158, 162, 324

470 Process/Application layer (DoD) – Router(config-subif)# prompt

Process/Application layer (DoD), 65, 66–70

- Bootstrap protocol (BootP), 69–70
- Domain Name Service (DNS), 69. *See also* DNS (Domain Name Service)
- Dynamic Host Configuration Protocol (DHCP), 69–70
- File Transfer Protocol (FTP), 67
 - when to use, 68
- Line Printer Daemon (LPD), 68
- Network File System (NFS), 67–68
- Simple Mail Transfer Protocol (SMTP), 68
- Simple Network Management Protocol (SNMP), 69
- Telnet, 66–67, 187, 344–349
 - checking connections, 348
 - checking users, 348
 - closing sessions, 348–349
 - for multiple devices simultaneously, 346–347
- Trivial File Transfer Protocol (TFTP), 67, 325, 333
- X Window, 68

Protocol Data Units (PDUs), 42

Protocol field, in IP header, 81, 82, 82–83

protocols. *See also specific protocols*

- well-known port numbers, 79

Proxy Address Resolution Protocol (Proxy ARP), 88, 88

Q

question mark (?), for command listing, 162–163

questions, with answer in [], 184

R

R, in routing table, 261

random-access memory (RAM), 317, 325

RARP (Reverse Address Resolution Protocol), 87–88, 88

RARP server, 87

read-only memory (ROM), 317

redistribution, 264

redundant links, problems from, 299

reference model, 11. *See also* Cisco three-layer hierarchical model; Open Systems Interconnection (OSI) reference model

- advantages, 11–12

registered jack (RJ) connector, 36

reliability, 190

reliable networking, 16

remote network, calculating best cost, 184

“request timed out” message, 225

Requests for Comments (RFC)

- 768 on UDP, 73
- 791 on Internet Protocol, 80
- 1256 on ICMP, 83
- 3232 on source port numbers, 76

Reserved field, in TCP header, 72

reserved IP addresses, 92–93

resources, for Debug command, 357

restore, of Cisco IOS, 325–331

Reverse Address Resolution Protocol (RARP), 87–88, 88

reverse Telnet, banner for, 170

RIP (Routing Information Protocol), 257–266. *See also* Routing Information Protocol (RIP)

RJ-45 (8-pin modular) connection, for console port, 153

RJ (registered jack) connector, 36

rolled cabling, 39–42, 40

- port settings, 41

ROM monitor, 317

ROM monitor mode, 323

ROM (read-only memory), 317

root bridge in STP, 301

root port, 301

route flush timer, 258

route invalid timer, 258

route update packets, 21

route update timer, 258

routed protocols, 21, 218

router-command history, 165

router igrp command, 268

Router> prompt, 158

router rip command, 259

Router(config-if)# prompt, 160

Router(config-line)# prompt, 161

Router(config-router)# prompt, 161

Router(config-subif)# prompt, 160

- routers, 5–7, 6
 - advantages, 6
 - bringing up, 155–156
 - in internetworking, 22
 - major points, 22
 - setting identity of, 168–169
 - routing
 - basics, 218–220
 - default, 242–244
 - gathering basic information, 167–168
 - information requirements, 219
 - routing by rumor, 256
 - Routing Information Protocol (RIP), 257–266
 - configuring routing, 259–261
 - default administrative distance, 255
 - holding down propagations, 264
 - timers, 258
 - using with IGRP, 271, 271–272
 - verifying routing tables, 261–263
 - version 2 (RIPv2), 264–266
 - routing protocols, 218, 254
 - administrative distances, 254–255
 - displaying configured, 273–274
 - prompt for configuring, 161
 - routing tables, 21, 21–22, 219
 - converged, 257, 258
 - manually adding routes, 237–242
 - verifying
 - configuration, 241–242
 - for IGRP, 269–270
 - for RIP, 261–263
 - viewing on Cisco router, 232
 - running-config, 158–159, 184
 - RXBOOT, 317
-
- S**
- scrolling long lines, 165
 - secondary IP address, 180
 - segments, flow control for transmitting, 18
 - Sequence number field, in TCP header, 72
 - serial interface
 - commands, 182–184
 - for router, 6
 - serial transmission, 383
 - service password-encryption command, 388
 - Session layer (OSI), 15
 - setup command, 156
 - setup mode, 162
 - for router, 156
 - shortest-path-first protocols, 257
 - show cdp command, 335
 - show cdp entry * command, 338
 - show cdp interface command, 339–340
 - show cdp neighbor command, 336–337
 - show cdp neighbor detail command, 337, 341
 - show cdp neighbors command, for
 - documenting network topology, 343
 - show cdp traffic command, 339
 - show controllers command, 193–195, 194, 236
 - show flash command, 326–327
 - show history command, 165
 - show hosts command, 351
 - show interface command, 187–192, 389
 - to view interface description, 177
 - show interface fastethernet 0/0 command, 188–189
 - show interface serial 0/0 command, 190
 - show interfaces command, 179, 190
 - show ip arp command, 135, 223
 - show ip interface brief command, 192–193
 - show ip interface command, 192, 195
 - show ip protocols command, 273–274
 - to display timers, 274
 - show ip route command, 219, 232, 240, 354
 - show mac address-table command, 298
 - show processes command, 359–360
 - show protocols command, 193, 272–273
 - show run command, 388
 - show running-config command, 180, 185, 331–332
 - for documenting network topology, 342
 - and password display, 175
 - to verify IP address, 181
 - to view interface description, 177
 - show sessions command, 348, 349, 352
 - show startup-config command, 185, 332
 - show terminal command, 165, 166
 - show users command, 348
 - show version command, 167, 320
 - shutdown command, 179
 - Simple Mail Transfer Protocol (SMTP), 68
 - Simple Network Management Protocol (SNMP), 69

“smart-serial,” 383
 software address, 80
 Source Address (SA), in Ethernet frame, 35
 Source IP address field, in IP header, 81
 source port, 76–77
 Source port field
 in TCP header, 72
 in UDP segment, 74
 Spanning Tree Protocol (STP), 296, 300–303
 port states, 302
 Start Frame Delimiter (SFD)/Synch, in
 Ethernet frame, 34
 startup-config, 155, 318
 deleting, 186, 334
 state transitions, 29
 static routing, 219, 237–242
 benefits and disadvantages, 238
 default administrative distance, 255
 deleting, 259
 store-and-forward switch type, 303, 304
 STP (Spanning Tree Protocol), 296,
 300–303
 port states, 302
 straight-through cabling, 38, 38–39
 stub networks, 242
 subcommands, 161
 subnet masks, 109–110
 for RIP and IGRP, 260
 subnetting, 106–111
 Class A addresses, 127–129
 in your head, 129
 Class B addresses, 120–126
 in your head, 126
 Class C addresses, 112–119
 in your head, 119
 exam essentials, 140–141
 powers of 2 and, 108–109
 subnetworks, creating, 107–108
 summary routes, 132
 supernetting, 132
 switched network, with switching loops, 301
 switches, 5
 at Data Link Layer, 24–25
 vs. hubs, 10, 25, 290
 in internetworking, 25
 switching services, 293–300
 syn packet acknowledgment, 78–79
 system restarted by bus error message, 167

T

TACACS server, authentication through, 171
 TCP/IP (Transmission Control Protocol/
 Internet Protocol), 64
 and DoD model, 64–88, 66
 TCP (Transmission Control Protocol), 71–73
 key features, 75
 port numbers, 76
 segment format, 71, 71–72
 Telecommunications Industry Alliance
 (TIA), 36
 Telnet, 66–67, 187, 344–349
 checking connections, 348
 checking users, 348
 closing sessions, 348–349
 for multiple devices simultaneously,
 346–347
 telnet (VTY) password, 170, 174
 setting and encrypting, 176
 terminal emulation, 66
 terminal history size command, 165, 166
 terminal monitor command, 274, 346
 TFTP (Trivial File Transfer Protocol), 67
 copying configuration to server, 333
 host, IOS backup on, 325
 thicknet, 37
 thin protocol, 73
 thinnest, 37
 thrashing the MAC table, 300
 three-way handshake, 16, 17, 17
 TIA (Telecommunications Industry
 Alliance), 36
 Time to Live field, in IP header, 81
 timers
 for CDP, 335
 for IGRP, 267
 for RIP, 258
 show ip protocols command to
 display, 274
 toll network, 379
 Total length field, in IP header, 80
 Traceroute, 83, 135, 187
 traceroute command, 354, 356–357
 Tracert, 135
 Transmission Control Protocol/Internet
 Protocol (TCP/IP), 64
 and DoD model, 64–88, 66

Transmission Control Protocol (TCP), 71–73
 key features, 75
 port numbers, 76
 segment format, 71, 71–72
 transparent bridging, 24
 Transport layer (OSI), 15–20, 44
 acknowledgments, 20
 connection-oriented communication,
 16–18, 17
 flow control, 16
 reliable delivery, 20
 windowing, 19, 19–20
 trap in SNMP, 69
 Trivial File Transfer Protocol (TFTP), 67,
 325, 333
 troubleshooting
 Interior Gateway Routing Protocol
 (IGRP), 270–271
 IP addresses, 133, 133–140
 network connectivity, 354–360
 Ping for, 186
 trustworthiness of routing information,
 254–255
 tunneling, 34
 twinax, 37
 Type field, in Ethernet frame, 35

U

UDP (User Datagram Protocol), 73–74
 key features, 75
 port numbers, 76
 segment format, 75
 undebg all command, 275, 276
 update timer, for IGRP, 267
 Urgent field, in TCP header, 72
 User Datagram Protocol (UDP), 73–74
 key features, 75
 port numbers, 76
 segment format, 74, 75
 user EXEC mode, 158, 162
 user-mode password, for Telnet, 174

V

Variable Length Subnet Masks (VLSMs),
 130–132

reason to use, 132
 RPIv2 support for, 265
 variance command, 267
 Version field, in IP header, 80
 virtual circuit, 71
 port numbers for, 76
 virtual LANs (VLANs), 9, 293
 VLSMs (Variable Length Subnet Masks),
 130–132
 reason to use, 132
 RPIv2 support for, 265
 VTY password, 346

W

web servers, and OSI model layers, 13
 well-known port numbers, 79
 wide area networks (WANs), 378–382
 cabling, 382–384
 serial transmission, 393
 connection types, 379–380, 380
 High-Level Data Link Control (HDLC)
 protocol, 385
 frame format, 385
 Point-to-Point Protocol (PPP), 386–389
 authentication configuration, 388–389
 authentication methods, 387–388
 configuring on Cisco routers, 388
 protocol stack, 386
 session establishment, 387
 verifying encapsulation, 389
 subnet mask, 118
 support, 380–382
 terminology, 379
 typical connection, 182
 wildcards, for configuring default route, 242
 Window field, in TCP header, 72
 windowing, 19, 19–20
 Windows Registry, IP address storage, 90
 wireless connection, 382
 workgroup layer, 48

X

X Window, 68