

Index

- Adaptation function:
 - GFP, 151
 - VCAT, 126
 - VCAT, LCAS capable, 142, 149
- Add drop multiplexor, 2
- Add member, 41, 72, 74
- Alarm inhibit signal, 129
- Assembly, 18, 39, 175, 176
- Asymmetric connections, 67
- Asynchronous interface for DVB, 111
- Asynchronous transfer mode, 99

- Bandwidth decrease, 36
- Bandwidth increase, 36

- Capacity, 21, 26
- Channel identification, 107
- Client signal fail, 121
- Concatenation, 9–34
 - Contiguous concatenation (CCAT), 11, 13
 - Virtual concatenation (VCAT), 12, 17
 - Higher order SDH/SONET, 21
 - Lower order SDH/SONET, 25
 - PDH, 28
 - OTN, 34
- Constant bit rate, 4, 5, 99, 165, 166, 168

- Container, 5, 6
 - Contiguous concatenated container, 5
 - Continuous payload container, 5
 - Virtual concatenated container, 5
 - Virtual container, 5
 - Virtual tributary container, 5
- Control field, 37, 40
- Control packet, *see also* VLI, 23, 27, 37, 51, 187
- Conversion, 32
- Customer premises equipment, 4
- Cyclic Redundancy Check (CRC), 37, 43
 - CRC decoding, 44
 - CRC division, 43
 - CRC encoding, 43
 - CRC multiplication, 43
 - CRC superblock, 120

- Delay:
 - Delay compensation, 19, 38
 - Differential delay, 19, 22, 27, 39, 129, 140, 146, 174, 175
 - Fiber delay, 19
 - Propagation delay, 19, 39
 - Transfer delay, 19
- Digital video broadcast, 111

- Distribution, 18, 171, 173
- Diverse routing, 18, 39, 67
- Do not use, 41, 72, 74
- DS1, 1, 6, 29
- DS3, 6, 31

- E1, 1, 6, 29
- E3, 6, 31
- Efficiency, 33, 34
- End of sequence, 41, 72, 74
- Enterprise systems connectivity, 111
- Ethernet, 2, 33, 99, 101, 111, 114, 115, 119, 122, 165, 167, 220
- Ethernet over SDH/SONET, 99
- Exercises, LCAS, 169–229
 - Exercise 1, VCG initiation, 178–189
 - Exercise 2, member addition, 189–200
 - Exercise 3, member removal, 200–210
 - Exercise 4, member failure, 210–215
 - Exercise 5, member recovery, 215–219
 - Exercise 6, degraded network, 220–226
- Extended signal label, 27, 28
- Extension header identifier, 106

- Fibre channel, 111, 114
- Fixed bandwidth, 41
- Frame check sequence, 108
- Frame mapped GFP, 101, 114–118
- Fibre connectivity, 111
- Fixed stuff, 5, 15, 16, 17, 22
- Frame relay, 3
- Functional models, 125–168
 - GFP adaptation functions, 151–164
 - GFP equipment functions, 165–168
 - Interworking function, 125–140
 - LCAS capable VCAT functions, 141–151
 - Virtual concatenation functions, 125–135

- Generic Framing Procedure (GFP), 99–124
 - Basic structure, 102
 - Client data frames, 109
 - Client management frames, 110
 - Control frames, 112
 - 8B/10B client signals, 119
 - Error handling, 118
 - Examples, 122–124
 - Extension header, 107
 - Frame delineation, 112
 - Frame multiplexing, 114
 - Frame mapped, 101, 114–118
 - Functional model, 102
 - Mapping, 121
 - Payload area, 104
 - Payload FCS field, 108
 - Payload header, 105
 - Payload information field, 108
 - Payload scrambling, 109
 - Relation, 101
 - 64B/65B code blocks, 120
 - Transparent mapped, 101, 119–121
 - Type field, 105
- GFP payload:
 - Ethernet MAC, 111, 114
 - Fibre channel, 111, 117
 - IP/PPP, 111, 114
 - MPLS, 111, 117
 - RPR, 111, 115
- Group identification, 37, 41

- Header Error Check (HEC):
 - Core header HEC (cHEC), 103
 - Extension header HEC (eHEC), 107
 - Type header HEC (tHEC), 106
- High-level data link control, 100

- Idle state, 41, 72, 74
- Implementation, 20, 41, 42, 62, 69, 81, 122, 129, 140, 156, 162, 169
- Intermediate network element, 18, 20
- Internet protocol, 2, 101, 114

- Internet service provider, 2
- Interworking function, 51, 135
- Layer, 6
- Line, 6
- Link Access Protocol SDH (LAPS), 99
- Link Capacity Adjustment Scheme (LCAS), 35–65
- LCAS disabled, 226
- Local area network, 2
- Media access control, 101, 114
- Member, 18, 36
- Member signal unavailable, 50, 73, 146
- Member status, 37, 44
- Member status multi-frame, 45
- Metro area network, 2
- Multi-frame, 22
- Multi-frame indicator, 20, 27, 37, 39
- Multi-frame structure, 25, 29–32, 37
- Multiplexes:
 - Multiplex structure, 100
 - PDH, 9
 - SDH, 10, 11
 - SONET, 10, 12
- Multiplex section, 6
- Multi-protocol label switching, 111, 114
- Network element, 18
- Network management system, 18
- Normal operation, 41, 72, 74
- Operations, administration & maintenance, 1
- Optical channel, 3
- Optical channel data unit, 6
- Optical channel payload unit, 6
- Optical Transport Network (OTN), 2
- Order of transmission, 7
 - Least significant bit, 7
 - Most significant bit, 7
- Packet over SDH/SONET, 99
- Path, 6
- Path overhead, 15, 16, 17, 22
 - VCAT path overhead, 23, 24, 28
- Path protection, 18
- Path termination, 18
- Payload container, 5, 9
- Payload distribution, 18, 171, 173
- Payload FCS Identifier, 106
- Payload length indicator, 103
- Payload reconstruction, 18, 39, 175, 176
- Payload type identifier, 105
- Planned member addition 47
- Planned member deletion 48
- Pleisiochronous Digital Hierarchy (PDH), 1
- Point of presence, 2
- Point-to-point protocol, 3
- Protection connection, 3, 16
- Protection path, 18, 20
- Protection switch, 19, 77
- Protocol data unit, 100, 103
- Quality of service, 3
- Re-alignment, 175, 176
- Regenerator section, 6
- Remove member, 72, 74
- Re-sequence acknowledge, 37, 45
- Resilient packet ring, 114
- Section, 6
- Sequence number, 18
- Sequence indicator, 37, 40
- Server signal fail, 129, 131
- Simple data link, 99
- Sink, 37, 74, 78, 100
- Sink engine, 175
- Sink states:
 - IDLE–OK–FAIL, 77
- Source, 37, 77, 78, 100
- Source engine, 172

- Source states:
 - IDLE-NORM-DNU-ADD-REMOVE, 74
- Specification and Description
 - Language (SDL), 67, 70–79
 - Diagrams, 74
 - Events, 71
 - Hold off, 77
 - State machine, source, 74, 78
 - State machine, sink, 77, 78
 - Symbols, 70
 - Wait to restore, 77
- Standards, 4
 - ANSI, 4
 - ETSI, 4
 - IEEE, 114
 - ITU-T, 4
- Storage area network, 3
- Survivability, 36
- Symmetric connections, 68
- Synchronous Digital Hierarchy (SDH), 2
- Synchronous Optical Network (SONET), 2
- Synchronous payload envelop, 5
- Synchronous transport module, 3
- Synchronous transport signal, 5

- Temporary member removal, 49
- Time division multiplex, 4
- Time sequence diagram, 81
- Trail, 6
- Trail selection, 172, 173
- Trail signal degrade, 73, 220
- Trail signal fail, 131, 211, 216
- Trail termination function:
 - VCAT, 126, 129, 131
 - VCAT, LCAS capable, 141, 146, 149
- Trail trace identifier, 41, 42, 135, 137
- Transparent mapped GFP, 101, 119–121
- Transport signals, 9
- Tributaires, virtual, 9

- User payload identifier, 106

- Variable bit rate, 4, 99
- Virtual Concatenation Group (VCG), 18, 36
 - Provisioning, 82
 - Planned bandwidth increase, 83–88
 - Planned member addition, 83–88
 - Planned bandwidth decrease, 88–92
 - Planned member removal, 88–92
 - Size, 69
 - Unplanned decrease, 93–98
 - Unplanned member removal, 93–98
- VCAT + LCAS Information (VLI):
 - Higher order VLI structure, 51
 - Higher order VLI MST multi-frame, 53
 - Higher order VLI example, 54
 - Insertion, 172
 - Lower order VLI structure, 54
 - Lower order VLI MST multi-frame, 57
 - Lower order VLI example, 57
 - OTN VLI structure, 57
 - OTN VLI example, 59
 - PDH VLI, 61, 62, 63
 - PDH VLI example, 63, 65
- Wavelength division multiplex, 4
- Wide area network, 2