

Contents

- Preface** **xiii**

- List of Acronyms** **xv**

- 1 Related Work and Preliminary Considerations** **1**
 - 1.1 Introduction 1
 - 1.2 Related Work 2
 - 1.2.1 A Routing-Based Approach 2
 - 1.2.2 An Information-Theoretic Approach 3
 - 1.2.3 A Dynamic Control Approach 4
 - 1.2.4 A Game-Theoretic Approach 4
 - 1.3 A New Perspective for the Design of Ad Hoc Wireless Networks 5
 - 1.4 Overview of the Underlying Assumptions in the Following Chapters 9
 - 1.5 The Main Philosophy Behind the Book 11

- 2 A Communication-Theoretic Framework for Multi-hop Ad Hoc Wireless Networks: Ideal Scenario** **15**
 - 2.1 Introduction 15
 - 2.2 Preliminaries 16
 - 2.2.1 Topology 16
 - 2.2.2 Route Discovery 17
 - 2.2.3 Average Number of Hops 18
 - 2.3 Communication-Theoretic Basics 18
 - 2.3.1 Bit Error Rate at the End of a Multi-hop Route 18
 - 2.3.2 Link Signal-to-Noise Ratio 20
 - 2.4 BER Performance Analysis 23
 - 2.4.1 Uncoded Transmission 23
 - 2.4.2 Coded Transmission 27
 - 2.5 Network Behavior 29
 - 2.5.1 Minimum Spatial Energy Density and Minimum Transmit Power for Full Connectivity 30
 - 2.5.2 Connectivity: Average Sustainable Number of Hops 34
 - 2.5.3 Lifetime of a Node 40
 - 2.6 Concluding Remarks 41

3	A Communication-Theoretic Framework for Multi-hop Ad Hoc Wireless Networks: Realistic Scenario	43
3.1	Introduction	43
3.2	Preliminaries	44
3.3	Communication-Theoretic Basics	46
3.4	Inter-node Interference	48
3.4.1	Geometric Considerations	48
3.4.2	Traffic Model	49
3.5	RESGO MAC Protocol	50
3.5.1	Scenario with Strong LOS and Interference from Nodes in Tier 1	50
3.5.2	Scenario with Strong LOS and Interference from Nodes in Tiers 1 and 2	57
3.5.3	Scenario with Strong Multipath (Rayleigh Fading)	58
3.5.4	Discussion	63
3.6	RESLIGO MAC Protocol	64
3.6.1	Scenario with Strong LOS	66
3.6.2	Scenario with Strong Multipath (Rayleigh Fading)	69
3.6.3	Discussion	72
3.7	Network Behavior	73
3.7.1	Minimum Spatial Energy Density and Minimum Transmit Power for Full Connectivity	73
3.7.2	Scenario with Strong LOS	73
3.7.3	Scenario with Strong Multipath (Rayleigh Fading)	75
3.7.4	Connectivity: Average Sustainable Number of Hops	78
3.8	Conclusions	83
4	Connectivity in Ad Hoc Wireless Networks: A Physical Layer Perspective	85
4.1	Introduction	85
4.2	Quasi-regular Topology	86
4.2.1	A Formal Definition of Quasi-regular Topology	87
4.2.2	A Communication-Theoretic Approach	88
4.2.3	What Happens if Each Node has Two Spatial Neighbors?	93
4.2.4	What Happens if There is Inter-node Interference?	96
4.3	Random Topology	100
4.3.1	Related Work	100
4.3.2	Connectivity in Ad Hoc Wireless Networks with Random Topology	102
4.3.3	Evaluation of the Likelihood of Broadcast Percolation	104
4.3.4	What Happens if There is Inter-node Interference?	108
4.4	Concluding Remarks and Discussion	109
5	Effective Transport Capacity in Ad Hoc Wireless Networks	111
5.1	Introduction	111
5.2	Model and Assumptions	113
5.3	Preliminaries	115
5.3.1	Route Bit Error Rate	115
5.3.2	Link Signal-to-Noise Ratio	115
5.3.3	Average Sustainable Number of Hops	117
5.4	Single-Route Effective Transport Capacity	117

- 5.5 Aggregate Effective Transport Capacity 120
 - 5.5.1 Ideal (no INI) Case 121
 - 5.5.2 Realistic (INI) Case: RESGO MAC Protocol 123
 - 5.5.3 Realistic (INI) Case: RESLIGO MAC Protocol 128
- 5.6 Comparison of the RESGO and RESLIGO MAC Protocols 131
- 5.7 Spread-RESGO: Improved RESGO MAC Protocol with Per-route Spreading Codes 134
- 5.8 Discussion 138
- 5.9 Concluding Remarks 141

- 6 Impact of Mobility on the Performance of Multi-hop Ad Hoc Wireless Networks 143**
- 6.1 Introduction 143
- 6.2 Preliminaries 144
 - 6.2.1 Ideal (no INI) Case 147
 - 6.2.2 Realistic (INI) Case 147
- 6.3 Switching Models 149
 - 6.3.1 Opportunistic Non-reservation-Based Switching 149
 - 6.3.2 Reservation-Based Switching 150
- 6.4 Mobility Models 150
 - 6.4.1 Direction-Persistent Mobility Model 150
 - 6.4.2 Direction-Non-persistent (DNP) Mobility Model 155
- 6.5 Numerical Results 157
 - 6.5.1 Direction-Persistent Mobility Model 157
 - 6.5.2 Direction-Non-persistent Mobility Model 161
- 6.6 Conclusions 163

- 7 Route Reservation in Ad Hoc Wireless Networks 167**
- 7.1 Introduction 167
- 7.2 Related Work 168
- 7.3 Network Models and Assumptions 169
 - 7.3.1 Network Topology 169
 - 7.3.2 Typical Routes 170
 - 7.3.3 Bit Error Rate at the End of a Multi-hop Route 170
 - 7.3.4 Retransmission Model 172
 - 7.3.5 Mobility 172
- 7.4 The Two Switching Schemes 173
 - 7.4.1 Reservation-Based Switching 173
 - 7.4.2 Non-reservation-Based Switching 175
- 7.5 Analysis of the Two Switching Techniques 176
 - 7.5.1 Reservation-Based Switching 176
 - 7.5.2 Non-reservation-Based Switching 179
- 7.6 Results and Discussion 182
 - 7.6.1 Switching Scheme and Traffic Load 182
 - 7.6.2 Effects of Interference 183
 - 7.6.3 Effects of the Number of Simultaneously Active Disjoint Routes 188
 - 7.6.4 Effects of Node Spatial Density 189

7.6.5	Effects of Mobility	191
7.6.6	Implications on Practical Scenarios	192
7.7	Concluding Remarks	193
8	Optimal Common Transmit Power for Ad Hoc Wireless Networks	195
8.1	Introduction	195
8.2	Model and Assumptions	196
8.2.1	Network Topology	196
8.2.2	Routing	197
8.2.3	Medium Access Control Protocol	199
8.3	Connectivity	199
8.3.1	Square Grid Topology	200
8.3.2	Two-Dimensional Poisson Topology	201
8.4	BER at the End of a Multi-hop Route	202
8.4.1	Square Grid Topology	202
8.4.2	Random Topology	204
8.5	Optimal Common Transmit Power	204
8.5.1	Optimal Common Transmit Power for Networks with Square Grid Topology	204
8.5.2	Optimal Common Transmit Power for Networks with Random Topology	205
8.6	Performance Metrics	205
8.6.1	Node and Network Lifetime	205
8.6.2	Effective Transport Capacity	206
8.7	Results and Discussion	208
8.7.1	Optimal Transmit Power and Data Rate	208
8.7.2	Optimal Transmit Power and Node Spatial Density	210
8.7.3	Effects of Strong Propagation Path Loss	211
8.7.4	Connectivity Robustness to Node Spatial Density Changes	213
8.7.5	Practical Determination of the Optimal Transmit Power	215
8.8	Related Work	216
8.9	Conclusions	217
9	The Routing Problem in Ad Hoc Wireless Networks: A Cross-Layer Perspective	219
9.1	Introduction	219
9.2	Experimental Evidence	220
9.3	Preliminaries: Analytical Models and Assumptions	221
9.3.1	Physical Layer	221
9.3.2	Medium Access Control	225
9.3.3	Basic Networking Assumptions	226
9.4	Route Selection: Simulation Study	227
9.4.1	Network Topology	227
9.4.2	BER-Based Routing versus Shortest-Path Routing	227
9.5	Network Performance Evaluation	235
9.5.1	Average Hop Length Models	235
9.5.2	Retransmission Model	239

9.5.3	Packet Error Rate	239
9.5.4	Delay	240
9.6	Discussion	243
9.6.1	Cross-layer Routing: A Practical Perspective	243
9.6.2	Mobility	246
9.7	Related Work	246
9.8	Conclusions	248
10	Concluding Remarks	249
10.1	Introduction	249
10.2	Extensions of the Theoretical Framework: Open Problems	249
10.2.1	Performance of Ad Hoc Wireless Networks: Random Versus Uniform Topologies	249
10.2.2	Impact of Clustering on the BER Performance in Ad Hoc Wireless Networks	251
10.2.3	Impact of Receiver Sensitivity on the Performance of Ad Hoc Wireless Networks	253
10.2.4	Spectral Efficiency–Connectivity Tradeoff in Ad Hoc Wireless Networks	254
10.2.5	MIMO-OFDM Wireless Communications	256
10.2.6	Smart Antennas and Directional Antennas	256
10.3	Network Architectures	256
10.4	Network Application Architectures	257
10.5	Standards	258
10.6	Applications	263
10.7	Conclusions	264
Appendix A	Analysis of the Inter-node Interference	265
A.1	Introduction	265
A.2	Exact Computation of the Average Link BER in a Scenario with Strong LOS	265
A.2.1	Interference from Nodes in Tier 1	266
A.2.2	Interference from Nodes in Tiers 1 and 2	271
A.2.3	Interference from Nodes in Tier 2	273
A.2.4	Simulation Scenario	274
A.3	Exact Computation of the Average Link BER in a Scenario with Strong Multipath (Rayleigh Fading)	276
A.3.1	Interference from Nodes in Tier 1	277
A.3.2	Interference from Nodes in Tiers 1 and 2	278
A.3.3	Interference from Nodes in Tiers 1, 2 and 3	278
A.4	LOS and Multipath (Rice Fading)	280
A.5	Gaussian Assumption for the Interference Noise	280
A.5.1	Route Bit Error Rate	282
A.5.2	Interference Power	284
Appendix B	Proof of Theorem 1, Chapter 5	287
Appendix C	Route Discovery	293

Appendix D	Validation of Analytical Results	295
D.1	Validation of Network Goodput	295
D.2	Validation of Delay	295
D.3	Validation of Average Number of Simultaneously Active Routes	297
Appendix E	Derivation of Joint CDF of W and Φ	299
References		307
Index		327