

## INDEX

---

- Above the API, 6
- Access tandem (AT)
  - definition, 38
  - switch, 61
- Account Manager interface, 165
- Address Complete Message (ACM), 20
- Advanced Intelligent Network, *see* AIN 5
- Advice of charge, 171
- AIN
  - architecture, 59
  - core features, 64
  - description, 5, 15
  - design choices, 44
  - events, 225
  - example services, 78
  - history, 59
  - introduction, 59
  - limitations, 23
  - principles, 64
  - summary of PSTN evolution, 33
  - triggers, 221
- Answer Message (ANM), 20
- API(s)
  - above and below, 6
  - asymmetric nature, 6
  - choosing a specification language, 48
  - complexity, 237
  - Conference Call Control, 179–181
  - definition, 45
  - description, 1
  - design choices, 44
  - design issues, 35, 207–217
  - example services, 27
  - extensibility, 55
  - factories, 116
  - function in networks, 1
  - future, 242
  - General Call Control, 171
  - implementation, 5, 45
  - issues with exiting, 236
  - JCC/JCAT components, 115
  - listeners, 116
  - methodology, 235
  - Multimedia Call Control, 178–179
  - Multiparty Call Control, 174–178, 196–202
  - network core, 54
  - network edge, 54
  - open, 2
  - overhead, 237
  - PAM, 167
  - Parlay, 160
  - Parlay/OSA, 151
  - programmability, 5
  - protocols, 145
  - specification, 5
  - standard, 2
  - vs. protocols, 6, 24, 26
- Application-centric call processing, 53
- Application server, 19
- Applications
  - definition, 36, 45
  - end-user, 36
  - event-driven, 168
  - Internet Call Waiting, 142–145, 202
- Asymmetric
  - call models, vs. symmetric, 52
  - protocols, 25
- Asynchronous method, 167
- Authentication process, 160, 182–184, 191
- Base call state model (BCSM)
  - Originating BCSM, 64, 67

- Base call state model (BCSM) (*Continued*)
  - Terminating BCSM, 64, 67
  - types, 67
- Base station (BS), 76
- Below the API, 6
- Black phones, 17
- Bootstrapping, 216
- Broker, 157
  
- Call Agents, description, 19
- Call Center package, overview, 97
- Call(s)
  - clearing, 67
  - custom services, 15
  - definition, 112
  - flows, JCC, 128–138
  - gapping, 171
  - leg manipulation, 174
  - logging, 133
  - party handling (CPH), 73
  - restriction, 900 numbers, 80
  - routing, 171
  - screening, 113
  - setup times, 14
  - transfer, 114
- Call control API
  - call model, 45
  - General, 171–173
  - Parlay, 163, 171
- Call control
  - agent function (CCAF), 72
  - core, 112
  - conference, 179–181
  - description, 1
  - first-party, 44
  - function (CCF), 71
  - model, design issues, 35
  - multimedia, 178, 193–196
  - multiparty, 174–178
  - overview, 3, 94
  - synchronous vs. asynchronous, 207
  - third-party, 44
- Call forwarding
  - dynamic, 101
  - provisioned, 99
- Call model(s)
  - description, 45
  - design choices, 44
  - full, 104
  - half, 105
  - half vs. full, 51
  - symmetric vs. asymmetric, 52
- Call processing
  - application-centric, 54
  - network-centric, 53
  - simple model, 39–42
- Callback, 212
- CAMEL, description, 77
- Capability Set 1 (CS 1), 71
- Carriers
  - common, 37
  - definition, 36
- CCITT No. 6, 14
- CCS, 13, 14
- Central offices (COs), 38
- Centralized business model, 23
- Charge plan, 171
- Charging API, 166
- Charging, description, 4
- Circuit-associated signaling, description, 12
- Circuit-switched networks, description, 11
- Class, abstract, 214
- CLASS, 15
- Class hierarchy, 214
- Click-To-Dial (CTD)
  - architecture, 31
  - description, 30, 114
  - in PINT, 222
- Click-To-Fax, 222
- Clients, definition, 37
- Commercial off-the-shelf technology, 23
- Common carriers, definition, 37
- Common-Channel Signaling (CCS), 13, 14
- Communication provider, 157
- Computer-controlled switches, 12
- Computer telephony integration (CTI), 83
- Connectivity Manager, 165
- Converged networks
  - architectures, 17
  - description, 2, 12, 16
  - programmability, 23
  - PSTN services, 23
- CORBA
  - initializing ORB, 182
  - registering interfaces, 198
  - transports, using, 233
- Core package
  - call control, 94–97
  - overview, 92
- Core, description, 55
- COTS technology, use of, 23
- CTI, introduction, 83
- Custom calling services, 15
- Customer-Premises Equipment (CPE), 18
- Customized Applications for Mobile
  - Enhanced Logic (CAMEL), 67

- Data Session Control (DSC), 164
- Design(s)
  - choices, 44
  - patterns, Parlay, 168
- Detection point (DP), 64
- Distributed JTAPI, 103
- Dynamic call forwarding, 101
  
- End offices (EOs)
  - description, 38
  - SSPs, 61
- End users, definition, 37
- End-user applications, 36
- European Computer Manufacturers Association (ECMA), 84
- Event detection point, 64
- Event filters
  - custom, 133
  - standard, 136
- Event(s)
  - blocking, 123
  - dynamic, 213
  - filters, 125
  - handling, 212
  - inheritance, 117
  - listeners, 212
  - notification, 162
  - static, 213
- Examples
  - common, 32
  - ICW, 33, 142–145
  - JCC and JCAT, 138
  - JTAPI, 98
  - toll-free calling, 32, 78, 138–142
- Exchanges, definition, 37
- Extensibility, APIs, 55
  
- Factory
  - definition, 117
  - pattern, 216
- Feature interaction, description, 57
- Filters, events, 125
- Finite state machines, *see* FSMs
- First-party call(s)
  - control, 44
  - description, 131
- FSMs
  - definition, 41
  - inheritance, 208
  - Parlay call control, 172
- Full call model, 51, 104
- Full-duplex sessions, description, 3
  
- General Call Control API, 171
- Generic Messaging Service (GMS), 165
  
- Half-call model(s), 51, 105
- Half-duplex sessions, description, 3
- Hierarchy
  - class, 214
  - even, 213
  - listener, 213
- Home location register, 76
- Horizontal separation, 25
  
- ICW
  - application, 142–145, 202
  - description, 33
  - history, 79
- IDL, description, 47
- IM, description, 33
- Immutable objects, 210
- Implementation, APIs, 5
- IN
  - application part (INAP), 63
  - architecture, 71
  - core aspects, 64
  - CS-1 core elements, 71
  - CS-2, 73
  - history, 77
  - ITU-T aspects, 71
  - principles, 64
  - processing model, 66
  - wireless, 74
- In-band signaling, description, 12
- Inheritance
  - event, 117
  - linear, 214
  - listeners, 117
  - multiple, 214
  - rules of, 208
- Initial Address Message (IAM), 19
- Instant messaging (IM), 33
- Integrity management, 162
- Intelligent Network, *see* IN
- Interexchange signaling, description, 12
- Interface Definition Language (IDL), 47
- Internet Call Waiting, *see* ICW
- IP networks, introduction of, 18
- ISDN User Part (ISUP), 19, 63
- ITU-T, IN aspects, 71
  
- JAIN
  - architecture, 109

- JAIN (*Continued*)
  - background, 107
  - call control, 111
  - JCC design choices, 44
  - standardization areas, 108
- Java APIs for Integrated Networks, *see* JAIN
- Java Call Control extensions, *see* JCAT
- Java Call Control, *see* JCC
- Java Community Process (JCP), 107
- Java Specification Request (JSR), 107
- Java Telephony API, *see* JTAPI
- Java, description, 47
- JCAT
  - advanced call control objects, 116
  - API components, 115
  - design choices, 44
  - Extended Call Control, 112
  - JcatAddress, 127
  - JcatCall, 126
  - JcatConnection, 126
  - JcatProvider, 125
  - JcatTerminalConnection, 127
  - Merge Call Application, 146
  - objects, 125
  - relationship to JTAPI and Parlay, 147
  - service drivers, 114
  - standard examples, 138
- JCC
  - API components, 115
  - application-level features, 110
  - call flows, 128–138
  - Core Call Control, 112
  - event blocking, 123
  - event filters, 125
  - introduction, 107
  - JccAddress, 124
  - JccCall, 119
  - JccConnection, 121–124
  - JccProvider, 118
  - relationship to JTAPI and Parlay, 147
  - service drivers, 113
  - signaling protocols, 110
  - standard examples, 138
- JCP, background, 107
- JSR, description, 107
- JTAPI
  - advantages, 84
  - basics, 85–88
  - Call Center package, 97
  - call scenarios, 88
  - Core package, 92
  - design choices, 44
  - distributed, 103
  - dynamic call forwarding, 101
  - examples, 98
  - history, 85
  - introduction, 83
  - Media package, 98
  - Mobile package, 98
  - Peer, 90
  - Phone package, 98
  - PrivateData package, 98
  - provisioned call forwarding, 99
  - relationship to JCC/JCAT, 147
  - three-party calls, 90
  - two-party call, 88
- JWG process, 154
- Languages, specification, *see* Specification
  - languages
- Listener
  - definition, 116
  - event, 212
  - hierarchy, 116
  - inheritance, 117
- Local office, 38
- Location registration function (LRF), 76
- Mated pair, description, 62
- Media package, JTAPI, 98
- Media stream, 178
- Merge Call application, 146
- Message Transfer Part (MTP), 63
- Mobile application part (MAP), 63
- Mobile package, JTAPI, 98
- Mobile station (MS), 76
- Mobile switching center (MSC), 75
- Mobile terminal access control function (MACF), 76
- Mobility service, 164
- Multiparty call control, 171
- Multiple sessions per object, 211
- Naming conventions, Parlay, 167, 169–171
- Network operators, definition, 36
- Network providers, definition, 36
- Network-centric call processing, 53
- Network(s)
  - circuit-switched, 11
  - converged, 16
  - core APIs, description, 54
  - edge APIs, description, 54
  - intelligence model, 236
  - IP, *see* IP networks
  - management system, 168

- next generation, 17
  - packet-switched, 11
- Next-generation networks (NGNs), 17
- NI3PCC, 233
- 900 number restriction, 80
  
- Object Management Group (OMG), 47
- Object mutability, 210
- O-BSCM, description, 67
- Offices, types, 38
- OSA API, *see* Parlay/OSA API
- Out-of-band signaling, description, 12
  
- packet-switched networks, description, 11
- PAM, 161, 167
- Parlay/OSA API
  - description, 151–206
  - history, 151
  - JWG process, 154
- Parlay
  - API overview, 160
  - applications, 158
  - Account Manager interface, 165
  - architecture, 157
  - Call Control APIs, 163
  - Charging API, 166
  - Connectivity Manager, 165
  - data types, 169–170
  - design choices, 44
  - design patterns, 168
  - designing application, 181–193
  - designing service, 189–189
  - DSC, 164
  - Framework, 160
  - GMS, 165
  - manager class, 193
  - methods, 170
  - mobility service, 164
  - naming conventions, 168, 169–171
  - OSA API, *see* Parlay/OSA API
  - PAM, 167
  - policy management service, 166
  - registering and using, 158, 192
  - relationship to JCC/JCAT, 147
  - services, 158, 186
  - terminal capabilities, 164
  - TINA-C history, 155
  - user interaction service, 163
- Parlay X, 231–234
- PayCircle, 233
- PBX, description, 28
- Peer, 90–91, 216
  
- Phone package, JTAPI, 98
- Phones, black, 17
- PIN override, 900 number, 80
- PINT, 219–227
- Points in call (PIC), 64
- Policy Management service, 161, 166
- Presence and Availability Management (PAM), 161, 167
- Private Branch Exchange (PBX), 28
- PrivateData package, JTAPI, 98
- Programmable gateway architecture, 158
- Programmability
  - APIs, 5, 235
  - basic model, 43
  - converged networks, 23
  - importance in networks, 5
  - protocols, 26
- Protocols
  - APIs, 145
  - Programmability, 26
  - SS7, 63
  - symmetric and asymmetric, 25
  - vs. APIs, 6, 24, 26
- Provider(s)
  - communication, 157
  - description, 87, 115
  - third-party service, 157
- Provisioned call forwarding, 99
- PSTN, 222–223
  - evolution, 11, 33
  - initial building blocks, 14
  - nature of, 5
  - outmoded, 17
  - services offered in converged networks, 23
- Public Switched Telephone Network, *see* PSTN
  
- Radio access control function (RACF), 76
- Radio terminal function (RTF), 76
- RBOCs in the 1980s, 16
- Reference implementation (RI), 107, 237
- Regional Bell Operating Company (RBOC), 16
- Release Complete Message (RCM), 21
- Release Message (RM), 21
- Ringling, description, 12
  
- SCCPs, description, 63
- SCML
  - example, 229
  - overview, 227–231
  - script, 228

- SCPs, 60, 62, 71
- Security, 238
- Service(s)
  - agreement, 187
  - call transfer, 114
  - Control Points (SCPs), 60, 62, 71
  - Creation Markup Language, *see* SCML
  - control function (SCF), 71
  - creation environment, 73
  - custom calling, 15
  - data function (SDF), 71
  - data point (SDP), 72
  - definition, 35
  - discovery, 162
  - drivers, JCAT, 114
  - drivers, JCC, 113
  - examples for APIs, 27
  - features, definition, 36
  - Freephone, 15
  - independent building block (SIB), 74
  - management system (SMS), 73, 76
  - manager, 168
  - providers, definition, 36
  - providing, 19
  - registration, 192
  - resource function (SRF), 72
  - single ended, 73
  - subscription, 162
  - supplementary, 14
  - switch-based, 14
  - switching function (SSF), 71
  - switching points (SSP), 60, 62, 71
  - trusted and untrusted, 109
- Service logic
  - execution environment, 19
  - definition, 36
  - program (SLP), 71
- Session Initiation Protocol (SIP), 21
- Sessions, overview, 3
- SIB, description, 74
- Signaling
  - circuit-associated, 12
  - Common-Channel, 13
  - connection control part (SCCP), 63
  - in-band, 12
  - interexchange, 12
  - ISUP protocol, 19, 63
  - link, 62
  - out-of-band, 12
  - point (SP), 81
  - protocol, JCC, 110
  - simple calls, 19
  - subscriber, 12
  - transfer point (STP), 61, 62
  - types, 12
- Simplex, description, 3
- Single-ended services, 73
- SIP, description, 21
- Sockets, role in networks, 5
- Softswitch, description, 19
- Specialized resource point (SRP), 72
- Specification, APIs, 5, 237
- Specification language(s)
  - choosing, 48–50
  - IDL, 47
  - Java, 47
  - UML, 48
  - WSDL, 48
- SPIRITS, 219–227
- SS6, 14
- SS7
  - elements in AIN, 61
  - hierarchy, 63
  - introduction of, 14
  - ISUP protocol, 19
  - major elements, 61
  - protocols, 63
- Standards bodies, descriptions, 6
- Subscriber(s)
  - signaling, description, 12
  - definition, 37
- Supplementary services, 14
- Switch-based services, 14
- Switches
  - AT, 61
  - classes, 38
  - computer controlled, 12
  - definition, 37
  - switching centers, 37
  - switching exchanges, 37
  - switching facilities, 37
- Switching Service Point (SSP), 16
- Symmetric call models vs. asymmetric, 52
- Symmetric protocols, 25
- Synchronous method, 167–168
- Tandem, definition, 38
- T-BSCM
  - description, 70
  - states, 68–70
- TCAP, 61, 63
- Teardown, 67
- Terminal capabilities, 164
- Terminology
  - call control, 35
  - service and network providers, 36
  - switches, 37

- users and subscribers, 37
- Test complexity kit (TCK), 237
- Third-party call control, 44
- Three-party calls, 90
- TINA
  - Business Model, 156
  - TINA-C history, 155
- Toll centers, 38
- Toll-free calling
  - examples, 32, 78, 138–142
  - introduction of, 15
- Transaction capability application part (TCAP), 61, 63
- Trigger
  - detection point, 64
  - dynamic, 168, 171, 224
  - static, 168, 171, 224
- Trunks, description, 12
- Trusted services, 109, 111
- Two-party calls, 88
  
- Unified Modeling Language (UML), 48
- Untrusted services, 109
- User interaction
  - description, 4
  - service, 163
- Users, definition, 37
  
- VAD, 29, 30
  
- Vertical separation, 25
- Virtual Private Network (VPN), 28, 113
- Visible transitions, 208
- Visitor location register (VLR), 76
- Voice over IP (VoIP), 17
- Voice Recognition Service (VRS), 29
- Voice-activated dialing (VAD), 29, 30
- VoIP, description, 17
- VPN, 28, 113
  
- Web Services Definition Language (WSDL), 48, 232
- Wireless Intelligent Networks (WINs)
  - description, 74
  - architecture, 75
  - functional elements, 75–77
  - history, 74
- WSDL, 48, 232
  
- XML
  - documents, 233
  - programmability, 219–234
  - services, 220
  - PINT, 219–226
  - SPIRITS, 219–226
  - JAIN SCML, 219–220
  - Parlay X, 219–220
- XSL, 231

