

Index

Note to the reader: Throughout this index boldfaced page numbers indicate primary discussions of a topic. Italicized page numbers indicate illustrations. See also the Appendix and Glossary.

Numbers

8-pin modular connector, 32
 10Base2, 32
 10Base5, 32
 10BaseT, 32
 80/20 rule, 392
 100BaseFX, 33
 100BaseTX, 33
 100VG-AnyLAN, 33
 802.ae (10Gbps over fiber and coax), 31
 802.u (Fast Ethernet), 33
 802.2 frame, 29–30, 31
 802.3ab (Gigabit Ethernet on category 5), 31
 802.3u (Fast Ethernet), 31
 1000BaseCX, 33
 1000BaseLX, 33
 1000BaseSX, 33
 1000BaseT, 33

A

access attempts, monitoring, 498
 access-class command, 494
 access layer in Cisco hierarchical model, 45
 access links in switched environment, 391
 access-list statement, options, 497
 access lists
 basics, 484–487
 DDR with, 566–567
 exam essentials, 504
 extended lists, 485, 494–500
 examples, 498–500
 guidelines for creating and implementing, 486–487
 monitoring, 502–503
 named lists, 500–501
 number ranges, 499
 standard lists, 485, 487–494
 deny statement, 488

 example, 490–493
 syntax, 487–488
 VTY (Telnet) access control, 493
 unapplied, 500
 access rate for Frame Relay, 541
 acknowledgment number for TCP, 68
 acknowledgments, 17
 active state route, 305
 address learning in Layer 2 switching, 349, 350–351
 Address Resolution Protocol (ARP), 80–81, 82
 cache, 225
 request, 94
 adjacencies
 in EIGRP, 291
 in OSPF, 308
 timer settings and, 323
 administrative distances (AD), 238, 245–246
 administrative VLAN, 388
 advertising, summary
 address, 141
 agents in SNMP, 65
 "Ambiguous command" message, 175
 anonymous user for FTP, 63
 ANSI LMI signaling format, 545
 any parameter, in access list statement, 488, 491
 AppleTalk, 291
 AppleTalk Session Protocol (ASP), 12
 Application layer (OSI), 10–11
 access list to filter by protocol, 496
 application-specific integrated circuit (ASIC), 21, 347
 Area Border Routers (ABRs), 307
 ARP (Address Resolution Protocol), 80–81, 82
 cache, 225
 request, 94
 ASIC (application-specific integrated circuit), 21

Asynchronous Transfer Mode (ATM), 524
 Attachment Unit Interface (AUI), 32
 attenuation, 32
 authentication
 as LCP option, 529
 login in FTP, 63
 PPP methods, 530
 configuring, 531–532
 debugging, 533–534
 auto-detect mechanism, 26
 Autonomous System Boundary Router (ASBR), 308
 autonomous system
 numbers (ASNs)
 for EIGRP, multiple, 294–295
 for IGRP, 260, 261
 auxiliary port
 password for, 183
 of router, 161

B

B (Bearer) channels in ISDN, 555, 559
 backup designated router (BDR) in OSPF, 309
 Backward Explicit Congestion Notification (BECN), 546
 bandwidth, 525
 for dynamic routing, 245
 and network design, 386
 bandwidth command, 193
 banners, 180–181
 baseline for SNMP, 65
 Basic Management for setup mode, 164
 Basic Rate Interface (BRI), 555–556, 559
 configuring, 566
 binary notation for IP addresses, 87
 conversion to decimal and hexadecimal, 83–86

662 binding – Cisco Internetwork Operating System (IOS)

- binding, 8
 - bits, 83, 87
 - in configuration register, 434–435
 - block sizes, 147
 - starting, 138
 - and wildcard mask, 488–489
 - blocked port in STP, 355, 357, 358
 - boot field bits in configuration register, 435
 - boot sequence of router, 433, 466–467
 - messages, 163
 - boot system command, 439
 - bootstrap, 432
 - Bootstrap Protocol (BootP), 65–66
 - bridge ID in STP, 354
 - Bridge Protocol Data Unit (BPDU) in STP, 354, 356
 - bridges, 4, 5, 346
 - at Data Link Layer, 21–23
 - vs. switches, 349
 - broadband PCS, 38
 - broadcast addresses, 87, 90, 94–95
 - calculating for Class C subnet, 115
 - broadcast control in virtual LANs, 386
 - broadcast domain, 6
 - router breakup, 3
 - VLAN as, 389
 - broadcast (multi-access) networks, 309
 - broadcast storms, 352, 352
 - VLANs and, 387
 - broadcasting routing updates, and loops, 249, 249–250
 - buffer for traffic congestion, 15
 - Buffer Full event, ICMP and, 79
 - bulletin boards, 11
 - byte, 87
-
- C**
- cabling
 - Ethernet, 33–36
 - crossover, 34
 - rolled, 35–36
 - straight-through, 33–34
 - wide area networks (WANs), 524–526
 - data communication equipment (DCE), 525–526, 526
 - fixed and modular interfaces, 526
 - serial transmission, 525
 - call setup, 13
 - Carrier Sense Multiple Access with Collision Detect (CSMA/CD), 24
 - Catalyst 1900 switch
 - configuring, 362–370
 - passwords, 364–366
 - power-on self-test (POST), 363
 - output after power up, 363
 - port configuration for VLAN, 399–400
 - port LED color, 363
 - telnet into, 458
 - trunk port configuration, 401–402
 - and trunking, 403
 - VLAN configuration, 398
 - Catalyst 1912 switch, 362
 - Catalyst 1924 switch, 362
 - Catalyst 2950 switch
 - inter-VLAN routing configuration, 405
 - IP address configuration on, 367–368
 - port configuration for VLAN, 400–401
 - trunk port configuration, 402
 - and trunking, 403
 - VLAN configuration, 398–399
 - Catalyst 3550 switch
 - inter-VLAN routing configuration, 405
 - trunking with, 402–403
 - Catalyst switch configuration, 362–370
 - erasing, 369–370
 - hostname, 366
 - interface descriptions, 368–369
 - IP information settings, 367–368
 - passwords, 364–366
 - port security, 369
 - startup, 363–364
 - CCNA exam
 - Class C 255.255.255.240 mask, 117
 - time restrictions, 113
 - cdp enable command, 454
 - cdp holdtime command, 450
 - cdp timer command, 450
 - central office (CO), 521, 540
 - Challenge Handshake Authentication Protocol (CHAP), 530
 - channel service unit/data service unit (CSU/DSU), 23, 525, 526
 - in Frame Relay network, 540
 - chat rooms, 11
 - Checksum field
 - for TCP, 68
 - for UDP, 70
 - CIDR (Classless Inter-Domain Routing), 110–111
 - circuit-switched WAN
 - connection, 521, 522
 - Cisco Discovery Protocol (CDP), 449–454
 - CDP timers and holdtime information, 450
 - interface traffic information, 453
 - neighbor information, 450–453
 - port and interface information, 453–454
 - Cisco Frame Relay
 - encapsulation, 553
 - Cisco Internetwork Operating System (IOS), 3, 160–161
 - administrative functions, 179–188
 - banners, 180–181
 - hostname, 179–180
 - password encryption, 186–187
 - setting descriptions, 188
 - setting passwords, 181–185
 - backup and restore, 440–446
 - backup, 442–443
 - restoring or upgrading, 443–446
 - verifying flash memory, 441–442
 - command line access, 161

- command-line interface (CLI), 168–179
 - editing and help features, 173–178
 - gathering basic routing information, 178–179
 - logging into router, 169–170
 - negating commands, 178
 - prompts, 171–173
 - reviewing history, 176–177
 - router modes, 170–171
- decompression, 163
- exam essentials, 203–204
- interface configuration, 189–193
 - bringing up, 190–191
 - serial interface commands, 192–193
- viewing and saving configurations, 194–203
- verifying configuration, 196–197
- Cisco routers, 3
 - 2500 series routers
 - configuration register changes, 438–439
 - fixed configuration, 190
 - 2501 router, 162
 - 2509 router, neighbor information, 451
 - 2600 series routers, 162
 - configuration register changes, 438
 - ISL routing support, 396
 - boot sequence, 433
 - configuration management
 - backup and restore, 446–449
 - boot sequence, 433
 - with Cisco Discovery Protocol (CDP), 449–454
 - exam essentials, 468–469
 - hostname resolution, 461–465
 - IOS backup and restore, 440–446
 - network connectivity, 466–467
 - with Telnet, 455–461
- configuration register, 434–440
 - bits, 434–435
 - changing, 436–437
 - checking current value, 436
 - password recovery, 437–440
- fixed and modular interfaces, 526
- internal components, 432–433
- ISDN with, 560–561
- PPP configuration on, 531
- serial connector, 525
- user interface, 160–168
 - bringing up, 162–164
 - connecting, 161–162
 - setup mode, 164–168
- Cisco switches. See Catalyst ...
- Cisco three-layer hierarchical model, 42–45, 43
 - access layer, 45
 - core layer, 44
 - distribution layer, 44–45
- CiscoFusion, 161
- Class A network, 88–90
 - address format, 90–91
 - default subnet masks, 110
 - subnetting addresses, 128–130
 - in your head, 130
- Class B network, 88
 - address format, 91–92
 - address range, 89
 - default subnet masks, 110
 - subnetting addresses, 122–128
 - in your head, 127–128
- Class C network, 88
 - address format, 92
 - address range, 89–90
 - default subnet masks, 110
 - subnetting addresses, 112–130
 - binary method, 112–114
 - fast method, 114–121
 - in your head, 119–120
- Class D network, address range, 90
- Class E network, address range, 90
- classful routing, 108, 131, 131, 252, 253
- Classless Inter-Domain Routing (CIDR), 110–111
- classless routing, 252
 - RIPv2 for, 258
 - subnet information advertising, 131
- clear counters command, 199–200
- client mode in VTP domain, 394–395, 413
- clock rate command, 192–193, 202, 233, 526
- closing Telnet sessions, 459–460
- Code bits field for TCP, 68
- collapsed backbone, 345
- collision domain, 4, 6
 - switches vs. hubs, 22
 - switching to break up, 344
- collision management in Ethernet network, 24–25
- command-line interface (CLI) for Cisco IOS, 168–179
 - editing and help features, 173–178
 - gathering basic routing information, 178–179
 - logging into router, 169–170
 - negating commands, 178
 - prompts, 171–173
 - reviewing history, 176–177
 - router modes, 170–171
- Committed Information Rate (CIR), 537, 541–542
 - and congestion control, 545
- Compaq, 353
- composite metric, 259, 262
- compression, as LCP option, 529
- config-register command, 437, 440
- configuration register, 433
- configure memory command, 171
- configure network command, 171
- configure terminal command, 170–171
- connection-oriented communication, 13–16, 67
 - establishing session, 14
- Connectionless Network Service (CLNS), 291
- connectionless protocol, UDP as, 69
- connectivity to network, 466–467

664 console – Dial-on-demand routing (DDR)

console

- HyperTerminal to create connection, 35–36
- password for, 183, 184
- console port of router, 161
- contention media access, 27
- convergence
 - of routing tables, 248, 249
 - of STP port modes, 358
- copy flash tftp command, 442, 443
- copy run start command, 369, 445, 446
- copy running-config tftp command, 446, 448
- copy startup-config running-config command, 194
- copy startup-config tftp command, 446
- copy tftp flash command, 443–444
- copy tftp running-config command, 448
- copy tftp startup-config command, 448–449
- core layer in Cisco hierarchical model, 44
- cost metric
 - in OSPF, 310
 - in STP for Ethernet networks, 357
- counting to infinity, 250
- CPU processes for dynamic routing, 245
- crossover cable
 - for Ethernet, 34
 - for switches, 363
- crosstalk, 32
- CSMA/CD (Carrier Sense Multiple Access with Collision Detect), 24
- cumulative interface delay, 262
- customer premises equipment, 520
- cut-through switch, 360, 361
- cyclic redundancy check (CRC), 41, 225
 - in store-and-forward switching, 362

D

D (Data) channel in ISDN, 555, 559

data communication equipment (DCE), 23, 525–526, 526

- in Frame Relay network, 540

data encapsulation, 38–42, 39

- Frame Relay, 542
- mismatched WAN, 534, 535
- verifying PPP, 532, 532–533

Data field

- in Ethernet frame, 28
- in IP header, 77
- for TCP, 68
- for UDP, 70

data frame, 20

Data Link Connection Identifiers (DLCI), 543–544, 544

Data Link layer (OSI), 20, 20–23, 225

- Ethernet at, 26–30
 - 802.2 and SNAP, 29–30, 31
 - addressing, 26–27
 - frames, 27–29, 28
 - sublayers, 21
 - switches and bridges, 21–23

data packets, 18

data stream, 13

data terminal equipment (DTE), 23, 525–526, 526

- in Frame Relay network, 540

datagram, 39. See also packets

DCE (data communication equipment), 23, 525–526, 526

- in Frame Relay network, 540

DDR. See Dial-on-demand routing (DDR)

de-encapsulation, 40

debug commands. See also troubleshooting

- receiving output from, 269

debug dialer command, 568

debug frame lmi command, 552

debug ip igrp command, 271–273

debug ip igrp events command, 272

debug ip igrp transactions command, 272–273

debug ip rip command, 269–271

debug isdn q921 command, 568

debug isdn q931 command, 568

debug ppp authentication command, 533

decimal notation for IP addresses, binary

- conversion to hexadecimal and, 83–86

dedicated WAN connection, 521, 522

default gateway, 225, 228

- for Catalyst switches, 367
- testing connection, 143

default routing, 241–244

- misconfigured, 244

default settings for router configuration, 164

delete. See also erase ...

delete nvram command, 369

delimiting character for banner, 181

demarcation (demarc) point, 520–521, 525

- in Frame Relay network, 540

deny statement

- in extended access list, 495
- implied at end of access list, 493
- in standard access lists, 488

description command, 188–189, 368–369

designated port in STP, 355

designated router in OSPF, 309

desktop layer in Cisco hierarchical model, 45

Destination Address field in Ethernet frame, 28

Destination IP address field in IP header, 77

"destination network unreachable" message, 226

destination port

- for TCP session, 68, 73
- for UDP, 70

Destination Unreachable event, ICMP and, 79

"destination unreachable" message, 227

Dial-on-demand routing (DDR), 561–567

- with access lists, 566–567
- configuring, 562–566

- dialer information,
 - 563–565
 - static routes, 562
- optional commands, 566
- troubleshooting, 565–566
- dialer-group command, 563
- dialer idle-timeout command, 566
- dialer-list command, 563
- dialer load-threshold command, 566
- dialer map command, 563–564
- dialer-string command, 563
- Diffusing Update Algorithm (DUAL), 293–294
- Digital Equipment Company, 353
- Digital Network Architecture
 - Session Control Protocol (DNA SCP), 12
- Dijkstra algorithm, 306, 308
- disable command, 170
- disabled port in STP, 357
- Discard Eligibility (DE) bit, 546
- disconnect command, 494
 - for Telnet, 459–460
- discontiguous networks, 295, 295–296
 - configuring, 302
- distance-vector routing
 - protocols, 246–247, 247–248
- distribute list, 484
- distribution layer in Cisco
 - hierarchical model, 44–45
- DIX (Digital, Intel and Xerox), 31
- DLCI (Data Link Connection Identifiers), 543–544, 544
- DoD (Department of Defense)
 - model, 60–83, 62
- Host-to-Host layer
 - protocols, 66–74
 - key concepts, 71
 - port numbers, 71–75
 - Transmission Control Protocol (TCP), 66–69, 71–75
 - User Datagram Protocol (UDP), 69–70, 71, 74
- Internet layer protocols, 75–83
 - Address Resolution Protocol (ARP), 80–81, 82, 94, 225

- Internet Control
 - Message Protocol (ICMP), 78–80, 224, 226, 230
- Internet protocol (IP), 75–78, 224–225
- Proxy Address
 - Resolution Protocol (Proxy ARP), 83
- Reverse Address
 - Resolution Protocol (RARP), 81–82, 82
- Process/Application layer
 - protocols, 62–75
 - Bootstrap Protocol (BootP), 65–66
- Domain Name Service (DNS), 65, 463–465
- Dynamic Host
 - Configuration Protocol (DHCP), 65–66
- File Transfer Protocol (FTP), 63, 64, 67, 67–69
- Line Printer Daemon (LPD), 64
- Network File System (NFS), 12, 64
- Simple Mail Transfer Protocol (SMTP), 64
- Simple Network
 - Management Protocol (SNMP), 65
- Telnet, 63. See also Telnet
- Trivial File Transfer Protocol (TFTP), 63
- X Window, 12, 64
- Domain Name Service (DNS), 65
 - for hostname resolution, 463–465
- dotted-decimal notation for IP
 - addresses, 87
- DTE (data terminal
 - equipment), 23
- Dynamic Host Configuration Protocol (DHCP), 65–66
- Dynamic Inter-Switch Link
 - encapsulation method, 401
- dynamic NAT, 95
- dynamic routing, 223, 245
- dynamic VLANs, 390

E

- e-mail gateways, 11
- editing commands in Cisco
 - command-line interface, 175–176
- EEPROM, 162
- EIA/TIA (Electronic Industries Association and Telecommunications Industry Alliance), 32
- electronic data interchange (EDI), 11
- enable command, 169–170
- enable-mode password, for Telnet access, 457
- enable password command, 364–365
- enable passwords, 165
 - for Catalyst switches, 364–366
- enable secret password, 165, 366
- encapsulation command, 522
- encapsulation of data, 38–42, 39
 - Frame Relay, 542
 - mismatched WAN, 534, 535
 - verifying PPP, 532, 532–533
- encryption of passwords, 186–187
- Enhanced Interior Gateway Routing Protocol (EIGRP), 245, 263, 290–294
 - configuring, 298–302
 - discontinuous
 - networks, 302
 - summary routes, 325–327
- Diffusing Update Algorithm (DUAL), 293–294
- exam essentials, 328
- for large network support, 294–298
 - multiple AS, 294–295
 - route discovery and maintenance, 296–298
 - VLSM support and summarization, 295–296
- metrics, 297–298
- neighbor discovery, 291–293

666 erase startup-config command – help, for router configuration

protocol-dependent modules, 291

Reliable Transport Protocol (RTP), 293

verifying configuration, 303–305

erase startup-config command, 195–196, 369, 370, 449

erasing flash memory contents, 445

error detection, as LCP option, 529

Ethernet, 24–33, 345

- cabling, 33–36
- crossover, 34
- rolled, 35–36
- straight-through, 33–34
- at Data Link Layer, 26–30
 - 802.2 and SNAP, 29–30, 31
 - addressing, 26–27
 - frames, 27–29, 28
- half-duplex and full-duplex, 25–26
- at Physical layer, 31, 31–33

exec banner, 181

EXEC session, 161

exec-timeout 00 command, 184

exit command, 170

- for Telnet, 459–460

exit interface, for default route, 242

exiting console, 170

extended access lists, 485, 494–500

- examples, 498–500

Extended Setup for router, 164–168

exterior gateway protocols (EGPs), 245

external EIGRP routes, 294

F

Far End Crosstalk (FEXT), 32

FastEthernet, 33, 346

- router configuration, 232

FastForward mode for switch, 360, 361

fault tolerance, in core layer of Cisco model, 44

feasible distance, 305

- for EIGRP, 292

feasible successor for EIGRP, 292–293

File Transfer Protocol (FTP), 63

- reasons to use, 64
- segment format, 67, 67–69

filter table, 22

financial transaction services, 11

fixed interfaces, for Cisco routers, 526

Flags field in IP header, 76

flapping, 251, 319

flash memory, 162, 433

- erasing contents, 445
- verifying, 441–442

flat networks

- as broadcast domain, 384, 385
- security for, 386

flexibility, in virtual LANs, 387–389

flow control in Transport layer, 13

- transmitting segments with, 15

flush timer for IGRP, 260

forward delay, 358

Forward Explicit Congestion Notification (FECN) bit, 546

forward/filter decisions in Layer 2 switching, 349, 351–352

forwarding port in STP, 355, 357, 358

Frag offset field in IP header, 76

FragmentFree switch, 360, 361

Frame Check Sequence (FCS) field, 28–29, 225, 393

frame filtering, 352

Frame Relay, 523, 536–554

- committed information rate (CIR), 541–542
- congestion control, 545–547
- Data Link Connection Identifiers (DLCI), 543–544, 544
- encapsulation types, 542
- exam essentials, 569–570
- implementation and monitoring, 547–554
- Local Management Interface (LMI), 544–545

- technology basics, 537–541, 539
- troubleshooting networks, 553–554
- virtual circuits, 542

frame-relay map statement, 553

frame tagging, 392

frames, 39, 41

full duplex mode, 12, 25–26

fully qualified domain name (FQDN), 65

G

Gang-of-Four LMI, 545

gateway of last resort, 243, 243

gateway protocols, interior and exterior, 245

Gigabit Media Independent Interface (GMII), 32

global addressing, 544

global configuration mode, 170–171

global parameters, configuring, 164

Google, 11

Gopher, 11

H

half-duplex mode, 12

- for Ethernet, 25–26

hardware address, 26, 26

- ARP to find for IP address, 80–81

hardware broadcasts, 94

HDLC (High-Level Data Link Control) protocol, 523

header

- from Data Link layer, 20
- IP, 76, 76
- for TCP, 67

Header checksum field in IP header, 77

Header Length field, 68, 76

Hello protocol, 308

help, for router configuration, 173–175

- hexadecimal notation for IP
 - addresses, 85–86, 87
 - binary conversion to decimal
 - and, 83–86
 - hierarchical scheme for IP
 - addresses, 87
 - High-Level Data Link Control (HDLC) protocol, 523, 527, 527
 - holddown timer, 252, 260
 - holddowns, 251
 - holdtime for CDP, 450
 - hop count, 19, 246
 - hops, 246–247
 - ICMP and, 79
 - maximum hop count, 250, 256, 290, 298
 - host address, 88
 - host command, in access list, 488
 - host IDs, valid hosts by network, 91, 92
 - host mask, 320
 - Host-to-Host layer protocols, 61, 66–74
 - key concepts, 71
 - port numbers, 71–75
 - Transmission Control Protocol (TCP), 66–69, 71–75
 - User Datagram Protocol (UDP), 69–70
 - hostname
 - for Catalyst switches, 366
 - configuring for router, 232
 - resolving, 65, 461–465
 - with DNS, 463–465
 - host table creation, 461–463
 - host table vs. DNS, 465
 - hostname command, 179–180, 531
 - hosts per subnet, calculating for Class C network, 115
 - hub network, 344
 - hubs, 4, 5
 - at Physical layer, 23, 24
 - hybrid protocols, 247
 - EIGRP as, 290
 - HyperTerminal, 35–36
 - Ctrl+Break key
 - combination, 437
-
- ICMP (Internet Control Message Protocol), 78–80, 224, 226, 230
 - Identifier field in IP header, 76
 - IEEE specifications
 - 802.1D for STP, 353, 357
 - 802.1Q on frame tagging, 392
 - Data Link layer and, 20
 - IETF (Internet Engineering Task Force), encapsulation, 553
 - "in-band" configuration, 162
 - inbound access lists, 486
 - incoming banner, 181
 - infrared wireless LANs, 38
 - Integrated Services Digital Network (ISDN), 523, 554–561
 - Basic Rate Interface (BRI), 559
 - configuring, 166
 - benefits, 555
 - with Cisco routers, 560–561
 - components, 556–558
 - connections, 555–556
 - decision to use, 561
 - exam essentials, 570
 - and OSPF, 324, 325
 - Primary Rate Interface (PRI), 560
 - protocols, 558
 - reference points, 558
 - switch types, 558–559
 - terminals, 557–558
 - verifying operation, 567–568
- Inter-Switch Link (ISL) protocol, 392, 393
 - router support for, 396
- inter-VLAN routing,
 - configuring, 403–409, 419
- interesting packets for ISDN, 563
- interface command, 171–172
- interface configuration mode, 172
 - for EIGRP, 298
- interfaces
 - description configuration on
 - Catalyst switches, 368–369
 - OSPF information on, 317–318
- for routers
 - bringing up, 190–191
 - configuring, 189–193
 - IP address configuration
 - on, 191–192
 - in routing table, 19
- interior gateway protocols (IGPs), 245
- Interior Gateway Routing Protocol (IGRP), 245, 259–265
 - configuring, 260–262
 - vs. RIP, 259
 - and subnetting, 131
 - timers, 259–260
 - troubleshooting, 264
 - using with RIP, 264, 264–265
 - verifying routing table, 262–263
- Intermediate
 - System-to-Intermediate System (IS-IS), 291
- internal EIGRP routes, 294
- International Organization for Standardization (ISO), 7
- Internet, 346
- Internet Control Message Protocol (ICMP), 78–80, 224, 226, 230
- Internet layer protocols, 61, 75–83
 - Address Resolution Protocol (ARP), 80–81, 82, 94, 225
 - exam essentials, 96–97
 - Internet Control Message Protocol (ICMP), 78–80, 224, 226, 230
 - Internet protocol (IP), 75–78
 - Proxy Address Resolution Protocol (Proxy ARP), 83
 - Reverse Address Resolution Protocol (RARP), 81–82, 82
- Internet navigation utilities, 11
- Internet Protocol (IP), 75–78, 224–225
- internetworking. See also Ethernet; Open Systems Interconnection (OSI) model
 - basics, 2–6
 - data encapsulation, 38–42, 39

668 invalid timers for IGRP – LMI

devices, 5
 exam essentials, 46
 models, 7–8
 Cisco three-layer
 hierarchical model,
 42–45, 43
 layered approach, 7–8
 routers and, 19
 Routing Information Protocol
 (RIP) and, 256–257
 switching services
 configuration example,
 413–420
 wireless networking,
 36–38, 37
 invalid timers for IGRP, 260, 267
 Inverse ARP (IARP), 543
 ip access-list command, 500
 ip address command,
 191–192, 367
 IP addresses, 75, 86–92
 assigning multiple to
 hostname, 461
 determining for assignment
 to host, 145
 hierarchical scheme,
 87–93, 89
 network classes, 88–90
 mismatched WAN,
 535–536, 536
 private, 92–93
 reserved, 90
 troubleshooting, 142–147
 ip classless command, 242–243
 ip default-gateway command, 367
 ip default-network command, 243
 ip domain-lookup command, 464
 ip domain-name command, 464
 IP header, 76, 76
 ip host command, 461
 ip name-server command, 464
 IP options field, in IP header, 77
 ip ospf cost command, 311
 ip route command, 237–238
 IP routing, 222
 basics, 223
 Catalyst switch settings,
 367–368
 exam essentials, 273–274
 on larger network, 230–236
 on network, 236–245
 default routing, 241–244
 dynamic routing, 245
 static routing, 236–241

 process, 224–236
 testing understanding,
 228–230
 verifying configuration,
 265–273
 debug ip igrp
 command, 271
 debug ip igrp events
 command, 272
 debug ip igrp transactions
 command, 272–273
 debug ip rip command,
 269–271
 show ip protocols
 command, 266–268
 show protocols
 command, 266
 IP stack failure, testing for, 142
 ip subnet-zero command,
 107, 136
 for subnetting Class C
 addresses, 112–113
 IPX, 291
 ISDN. See Integrated Services
 Digital Network (ISDN)
 isdn disconnect command, 568
 isdn switch-type command,
 558, 560
 ITU-T (Q.933A) LMI signaling
 format, 545

J

JPEG (Joint Photographic
Experts Group), 12

K

keepalive, 199, 544
kernel, 160–161

L

LAN Manager, 345
 LAN switching, types, 360–362
 LAPB (Link Access Procedure,
 Balanced), 523
 LAPD (Link Access Procedure,
 D-Channel), 523

large files, FTP to transfer, 64
 large networks, EIGRP support
 for, 294–298
 multiple AS, 294–295
 route discovery and
 maintenance, 296–298
 VLSM support and
 summarization,
 295–296
 latency, 21, 360
 Layer 2 broadcasts, 94
 Layer 2 switching, 21, 344.
 See also Catalyst switches;
 Spanning Tree
 Protocol (STP)
 benefits, 348
 vs. bridges, 349
 exam essentials, 370–371
 functions, 349–353
 address learning, 350–351
 forward/filter decisions,
 351–352
 loop avoidance, 352–353
 limitations, 348–349
 network conditions before,
 344–347, 345
 layer 3 switches, routers as, 3–4
 layered architecture, 7
 learning port in STP, 357
 lease lines for WAN, 522
 Length field
 in Ethernet frame, 28
 for UDP, 70
 line command, 172–173
 for user-mode passwords,
 182–183
 Line Printer Daemon (LPD), 64
 Link Access Procedure, Balanced
 (LAPB), 523
 Link Access Procedure,
 D-Channel (LAPD), 523
 Link Control Protocol (LCP), 528
 configuration options, 529
 link in OSPF, 308
 Link State Advertisement
 (LSA), 309
 link-state routing
 protocols, 247
 listening port in STP, 357
 LMI (Local Management
 Interface), 544–545
 checking for traffic, 551
 traffic statistics,
 displaying, 550

load balancing, 246, 265
 with EIGRP, 297–298
 with IGRP, 260
 with Routing Information Protocol, 247

load-threshold command, 565

local loop, 521

Local Management Interface (LMI), 544–545

log command, 498

logging synchronous command, 184

logical addressing, 75

Logical Link Control (LLC) 802.2 sublayer, 21

logical segmentation, 347

login banner, 181

login command, and password, 183

login (user mode) password, for Catalyst switches, 364–366

logout command, 170

loopback address, 142

loopback interfaces, and Open Systems Interconnection (OSI) model, 319–322

loopback tests, IP address for, 90

M

MAC (Media Access Control) address, 26, 26
 802.3 sublayer, 21
 IP address request for, 81–82, 82
 and route bridge selection, 355

MAC forward/filter table, 350, 350, 351
 populating, 351

mainframe network, 345

maximum hop count, 250, 256
 for EIGRP, 290, 298

maximum transmission unit (MTU), 297

MD5 (one-way hash function), 530

Media Independent Interface (MII), 32

media translation, 23

message of the day (MOTD) banner, 180–181

metrics
 for EIGRP, 297–298
 in routing table, 19

Microsoft Callback Control Protocol (CBCP), 529

MIDI (Musical Instrument Digital Interface), 12

mini-IOS, 432

modems
 connecting to router, 161–162
 setup mode to configure, 166

modified cut-through switch, 360, 361

modular interfaces, for Cisco routers, 526

MPEG (Moving Pictures Experts Group), 12

Multicast, 94, 95

multicast traffic in EIGRP, 293

multicasting, 544

multilink, as LCP option, 529

multiplexing, 548

multipoint subinterface, 548

N

named access lists, 485, 500–501

narrowband PCS, 37

narrowband wireless LANs, 37

NAT (Network Address Translation), 92–93, 95–96

native VLAN, 391

Near End Crosstalk (NEXT), 32

neighbor discovery in EIGRP, 291–293

neighbor table for EIGRP, 292, 297

neighbors in OSPF, 308
 information on, 318

Neighborhood database in OSPF, 308

NetWare servers, 345

Network Access layer (DoD), 61

Network Address Translation (NAT), 92–93, 95–96

network addresses, 87, 88–90, 89
 in routing table, 18

network analyzer, data from ICMP echo request, 79–80

network command, 253
 for OSPF areas, 312, 313

network connectivity, 466–467

Network Control Protocol (NCP), 528, 530

Network File System (NFS), 12, 64

network interface cards (NICs)
 MAC address, 26, 26
 testing, 142–143

Network layer (OSI), 17–20
 packets at, 18, 41

Network layer-to-DLCI mappings, 552

network loops
 Layer 2 switching for
 avoiding, 349, 352–353
 stopping, 344

network segmentation, 3

network termination equipment in ISDN, 557–558

networking. See internetworking

next-hop router, for default route, 242

nibble, 32, 83

no auto-summary command, 302, 326

no cdp enable command, 453–454

no cdp run command, 450, 453–454

no debug all command, 270

no ip domain-lookup command, 464

no ip route command, 252–253

no login command, 456

no shutdown command, 190–191, 231

node address, 88

non-broadcast multi-access networks, 309

nondesignated port in STP, 355

nonroot bridge in STP, 354

nonvolatile RAM. See NVRAM (nonvolatile RAM)

Novell, 345

number ranges for access lists, 487

numbers, binary to decimal and hexadecimal conversion, 83–86

NVRAM (nonvolatile RAM), 162, 433
 changing configuration, 171
 copying current configuration to, 447–448

670 octet – port numbers

O

- octet, 87
 - Open Shortest Path First (OSPF), 245
 - Open Systems Interconnection (OSI) model, 7, 8–23, 305–311
 - advantages of, 8
 - Application layer, 10–11
 - configuring, 311–314
 - areas for OSPF, 312–314
 - enabling, 311
 - summary routes, 325–327
 - Data Link layer, 20, 20–23
 - design example, 307
 - vs. DoD model, 61
 - exam essentials, 328
 - layer functions, 10
 - and loopback interfaces, 319–322
 - configuring, 319–320
 - verifying, 321–322
 - lower layers, 9
 - Network layer, 17–20
 - Physical layer, 23
 - Presentation layer, 11–12
 - vs. RIP, 306–307
 - SPF tree calculation, 310–311
 - terminology, 308–310
 - Transport layer, 13–17
 - reliable delivery, 18
 - troubleshooting, 322–324
 - upper layers, 8
 - verifying configuration, 314–319
 - show ip ospf command, 315–316
 - show ip ospf database command, 316
 - show ip ospf interface command, 317–318
 - show ip ospf neighbor command, 318
 - show ip protocols command, 318–319
 - Options field for TCP, 68
 - organizationally unique identifier (OUI), 27
 - OS/2 server, 345
 - OSPF areas, 309
 - configuring, 312–314
 - OSPF Process ID, 311
 - OUI (organizationally unique identifier), 27
 - "out-of-band" configuration, 162
 - outbound access lists, 486
 - overloading NAT
 - configuration, 96
 - oversubscription, 538
-
- P**
 - packet filtering, access lists
 - for, 484
 - packet switching, 4
 - WAN connection, 521, 522
 - packets, 39
 - interesting, for ISDN, 563
 - at Network layer, 18
 - parallel transmission, 525
 - parameters for commands, help
 - with, 175
 - passive-interface command, 256–257, 299
 - passive state route, 305
 - Password Authentication Protocol (PAP), 530
 - passwords
 - for auxiliary port, 183
 - for Catalyst switches, 364–366
 - for console, 184
 - enable, 165, 182–183
 - encrypting, 186–187
 - for router, recovering, 437–440
 - setting, 181–185
 - for switches to VTP domain, 394
 - for Telnet, 165, 183, 185
 - user-mode, 182–183
 - VTY, for telnet access to router, 455–456
 - PCs, early network connections, 345–346
 - PCS (Personal Communication Services), 37
 - Permanent Virtual Circuits (PVCs), 542
 - permit any command, in access list, 486
 - permit ip any any statement, 500
 - Personal Communication Services (PCS), 37
 - Physical layer (OSI), 23
 - Ethernet at, 31, 31–33
 - PICT file format, 12
 - Ping (Packet Internet Groper), 80, 466
 - ICMP and, 79
 - for ISDN verification, 567
 - to test TFTP server
 - connection, 442
 - for troubleshooting IP addresses, 142–143
 - to verify IOS
 - configuration, 196
 - to verify routing table
 - configuration, 240–241
 - pinhole congestion, 247, 248, 265
 - Plain Old Telephone Service (POTS), 561
 - point of presence (POP), in
 - Frame Relay network, 540
 - point-to-multipoint network topology, 310
 - point-to-point network topology, 310
 - for WAN, 522
 - Point-to-Point Protocol (PPP), 523, 528–536
 - authentication methods, 530
 - callback, as LCP option, 529
 - configuring authentication, 531–532
 - configuring on Cisco routers, 531
 - Link Control Protocol (LCP) configuration
 - options, 529
 - mismatched IP addresses, 535–536, 536
 - session establishment, 529–530, 530
 - stack, 528
 - use with ISDN, 555
 - verifying encapsulation, 532–533
 - point-to-point subinterfaces, 548
 - poison reverse, 250
 - polling, 27
 - port address translation (PAT), 96
 - port cost in STP, 355
 - port numbers, 71–75, 72
 - destination port for TCP, 73

source port for TCP, 72–73
in Transport layer, 41, 42

ports
 assigning to VLANs, 399–401
 security on Catalyst switch, 369

positive acknowledgment with retransmission, 17

POTS (Plain Old Telephone Service), 561

power-on self-test (POST), 162, 432, 433

Power Sum NEXT (PSNEXT), 32

powers of 2, 108–109

PPP. See Point-to-Point Protocol (PPP)

preamble field, in Ethernet frame, 27

prefix routing, 252

Presentation layer (OSI), 11–12

Primary Rate Interface (PRI), 555, 560

printer sharing, with Line Printer Daemon, 64

priority, for switches in STP, 356

private IP addresses, 92–93

privileged exec mode, 169

privileged mode for router, 164
 entering, 439

Process/Application layer protocols, 61, 62–75

 Bootstrap Protocol (BootP), 65–66

 Domain Name Service (DNS), 65, 463–465

 Dynamic Host Configuration Protocol (DHCP), 65–66

 File Transfer Protocol (FTP), 63, 64, 67, 67–69

 Line Printer Daemon (LPD), 64

 Network File System (NFS), 12, 64

 Simple Mail Transfer Protocol (SMTP), 64

 Simple Network Management Protocol (SNMP), 65

 Telnet, 63

 Trivial File Transfer Protocol (TFTP), 63

 X Window, 12, 64

prompts in Cisco command-line interface, 171–173

 for interfaces, 171–172

 line commands, 172–173

 for routing protocol configuration, 173

 for subinterfaces, 172

Protocol Data Units (PDUs), 39
 and layer addressing, 40

protocol-dependent modules, in EIGRP, 291

Protocol field in IP header, 77, 78, 78

protocols. See also subentries
 under DoD (Department of Defense) model
 displaying information on, 318–319
 possibilities in IP header, 78

Proxy Address Resolution Protocol (Proxy ARP), 83

pruning in VTP, 396

Q

Q.921 protocol, 558

Q.931 protocol, 558

question mark (?), for router configuration help, 173–175

QuickTime, 12

R

R reference point in ISDN, 558

RAM (random access memory), 433

redundancy, in links between switches, 352

reference model, 7. See also DoD (Department of Defense) model; Open Systems Interconnection (OSI) model

reference points in ISDN, 558

registered jack (RJ) connector, 32

Registry, default gateway, 225

reliability, and UDP, 69

reliable multicast, 293

reliable networking, 13

Reliable Transport Protocol (RTP), 293

Remote Procedure Call (RPC), 12

reported distance, for EIGRP, 292

Request for Comments (RFCs)
 768 on UDP, 69
 792 on ICMP, 79
 1256 on ICMP, 78
 2338, for cost metric definition, 310
 3232 on well-known port numbers, 71–72

"request timed out" message, 227

Reserved field for TCP, 68

reserved IP addresses, 90

Reverse Address Resolution Protocol (RARP), 81–82, 82

rolled cable, for Ethernet, 35–36

ROM (read-only memory), 433

ROM monitor, 432

route bridge in STP, 354, 355
 example, 359
 selecting, 355–356

root ports in STP, 354–355
 example, 359
 selecting, 356–357

route aggregation (summarization), 134, 141–142

route flush timer, 252

route invalid timer, 252

route poisoning, 250

route redistribution, 305

route table for EIGRP, 297

route update packets, 18

route update timer, 252

routed protocols, 18
 displaying, 266
 vs. routing protocols, 222

router configuration mode for EIGRP, 298

router eigrp command, 298, 300

Router ID in OSPF, 308

router igrp command, 261

router ospf command, 311

Router> prompt, 169

Router# prompt, 170

router rip command, 253

routers. See also Cisco Internetwork Operating System (IOS)
 advantages of, 3
 configuring

672 routing – show users command

- for FastEthernet, 232
 - for serial interface, 233–234
 - in Network layer, 17–20
 - password recovery, 437–440
 - traffic reduction with, 107
 - routing
 - basics, 222–224
 - information
 - requirements, 223
 - by rumor, 247
 - Routing Information Protocol (RIP), 245, 251–258
 - configuring routing, 252–254
 - holding down propagations, 256–257
 - vs. Interior Gateway Routing Protocol (IGRP), 259
 - redistribution, 257
 - and subnetting, 131
 - timers, 252
 - use with IGRP, 264, 264–265
 - verifying routing table, 255–256
 - version 2, 257–258
 - routing loops, 249, 249–250
 - routing protocols. See also specific names of protocols
 - administrative distances (AD), 245–246
 - classes, 246–247
 - displaying, 266–268
 - vs. routed protocols, 222
 - routing table
 - adding static route, 237–238, 239
 - EIGRP advertising of, 292
 - information in, 18–19, 19
 - verifying configuration, 240–241
 - for IGRP, 262–263
 - for RIP, 255–256
 - viewing, 233
 - RTF (Rich Text Format), 12
 - running-config file, 194
 - changing, 170–171
 - RXBOOT, 432
-
- S**
- S reference point in ISDN, 558
 - S/T interface, 555
 - satellite services, 38
 - saving Cisco IOS configurations, 194–203
 - scalability, in virtual LANs, 387–389
 - secondary IP address, 191–192
 - secret password, 182
 - security
 - in layer 2 switched internetwork, 385
 - for port on Catalyst switch, 369
 - for router, 494
 - in virtual LANs, 386–387
 - sequence number for TCP, 68
 - serial interface
 - commands, 192–193
 - router configuration, 233–234
 - serial transmission for WANs, 525
 - server mode in VTP domain, 394
 - service password-encryption
 - command, 186–187, 531
 - service profile identifiers (SPIDs), 559
 - setup command, 164
 - setup mode for router, 164–168
 - shortest-path-first (SPF)
 - protocols, 247, 310
 - tree calculation, 310–311
 - show access-list 110
 - command, 502
 - show access-list command, 502
 - show cdp command, 450
 - show cdp entry * command, 452–453
 - show cdp interface command, 453–454
 - show cdp neighbor command, 450–451
 - output for 2509 router, 451
 - show cdp neighbor detail
 - command, 451–452, 455, 536
 - show cdp traffic command, 453
 - show controllers command, 202
 - show dialer command, 567
 - show flash command, 441–442
 - show frame command, 549
 - show frame map command, 552
 - show frame pvc command, 550–551
 - show frame-relay command, 550
 - show frame-relay lmi
 - command, 550
 - show frame-relay pvc
 - command, 546
 - show history command, 177
 - show hosts command, 462
 - show interface command, 197–201, 532, 536, 551
 - for description display, 188
 - show interface fastethernet
 - command, 198–199
 - show interface serial
 - command, 199
 - show interface trunk
 - command, 416
 - show ip access-list command, 502
 - show ip eigrp neighbors
 - command, 303, 304–305
 - show ip eigrp topology
 - command, 292, 303, 305
 - show ip interface brief
 - command, 201–202, 268
 - show ip interface command, 201, 502, 503
 - show ip ospf command, 315–316, 319
 - show ip ospf database
 - command, 316, 321
 - show ip ospf interface
 - command, 317–318, 321
 - for troubleshooting, 322–323
 - show ip ospf neighbor
 - command, 318
 - show ip protocols command, 266–268, 318–319
 - show ip route command, 233, 303, 568
 - show ip route eigrp
 - command, 303
 - show isdn active command, 567
 - show isdn status command, 567
 - show protocols command, 202, 266
 - show running-config command, 191, 194, 502, 536
 - for description display, 188
 - for password display, 186
 - show sessions command, 459, 460, 463
 - show startup-config command, 194–195, 447
 - show terminal command, 177
 - show users command, 459, 494

- show version command, 178, 436, 437
 - show vlan brief command, 417
 - show vlan command, 398
 - show vtp command, 410
 - shutdown command, 190
 - Simple Mail Transfer Protocol (SMTP), 64
 - Simple Network Management Protocol (SNMP), 65
 - simplex mode, 12
 - slash notation, subnet masks of, 110–111, 120–121
 - SNAP (Subnetwork Access Protocol), frames, 30, 31
 - software address, 75
 - Source Address field, in Ethernet frame, 28
 - Source IP address field, in IP header, 77
 - Source Port field
 - for TCP, 67, 72–73
 - for UDP, 70
 - spanning-tree algorithm (STA), 353
 - Spanning Tree Protocol (STP), 344, 349, 353–354
 - example, 358–360, 359
 - operations, 355–358
 - root bridge selection, 355–356
 - root port selection, 356–357
 - port states, 357–358
 - terminology, 354–355
 - uses for, 358
 - SPF (shortest-path-first) protocols, 247, 310
 - tree calculation, 310–311
 - split horizon, 250, 269
 - spread spectrum wireless LANs, 38
 - standard access lists, 485, 487–494
 - deny statement, 488
 - example, 490–493
 - syntax, 487–488
 - VTY (Telnet) access control, 493
 - Start Frame Delimiter/Synch field, in Ethernet frame, 27
 - startup-config file, 171, 194
 - state transitions, 23
 - static NAT, 95
 - static routing, 223, 236–241
 - adding to routing table, 237–238
 - for DDR, 562
 - and RIP, 254
 - static VLANs, 389–390
 - store-and-forward switching, 361, 362
 - straight-through cable, for Ethernet, 33–34
 - Structured Query Language (SQL), 12
 - stub networks, default routing on, 241–244
 - subinterfaces, 172
 - in Frame Relay network, 547–549
 - for VLANs, 403
 - subnet masks, 109–110. See also Variable Length Subnet Masking (VLSM)
 - for RIP and IGRP, 253
 - of slash notation, 110–111, 120–121
 - for two hosts, 118
 - subnetting
 - basics, 106–111
 - benefits, 107
 - Classless Inter-Domain Routing (CIDR), 110–111
 - ip subnet-zero command, 107
 - subnetwork creation, 108
 - Class A IP addresses, 128–130
 - in your head, 130
 - Class B IP addresses, 122–128
 - in your head, 127–128
 - Class C IP addresses, 112–130
 - binary method, 112–114
 - fast method, 114–121
 - in your head, 119–120
 - exam essentials, 148
 - Subnetwork Access Protocol (SNAP), 29–30, 31
 - successor route for EIGRP, 293
 - summarization, 134, 141–142
 - switch fabric, 392
 - Switched Virtual Circuits (SVCs), 542
 - switches, 4, 6
 - at Data Link Layer, 21–23, 22
 - real world scenario, 6
 - and routing, 229
 - switching services, 347–353. See also Layer 2 switching
 - configuring on sample internetwork, 413–420
 - switchport command, 402
 - switchport mode access command, 402
 - syn packet acknowledgment for TCP, 74–75
-
- ## T
- T reference point in ISDN, 558
 - TACACS server, router
 - authentication through, 182
 - TCP/IP (Transmission Control Protocol/Internet Protocol), 60
 - and DoD model, 62
 - Telnet, 63, 197, 455–464
 - checking connections, 459
 - checking users, 459
 - closing sessions, 459–460
 - for connecting to Cisco router, 162
 - for ISDN verification, 567
 - for multiple devices simultaneously, 457–458
 - and password encryption, 187
 - password for, 165, 183, 185
 - standard access list to control, 493
 - terminal adapter in ISDN, 558, 560
 - terminal emulation, 63
 - terminal equipment in ISDN, 557–558, 560
 - terminal history size command, 177
 - terminal monitor command, 269, 457
 - TFTP server
 - for Cisco IOS backup, 440, 442–443
 - copying configuration to, 448
 - thrashing MAC table, 353
 - three-way handshake, 13–14, 14
 - TIFF (Tagged Image File Format), 12
 - timers
 - and adjacencies, 323

674 token passing – VTY passwords

- for CDP, 450
- for IGRP, 259
- for routing protocol, 267
- token passing, 27
- Token Ring LAN, 345
- toll network, 521
- topology database in OSPF, 308
- topology table for EIGRP, 292, 297
- ToS with IP Precedence Bits field in IP header, 76
- Total length field in IP header, 76
- traceroute command, 196, 467
 - ICMP and, 79
- tracert command, 467
- traffic congestion
 - buffer for, 15
 - causes, 3
- translation services, in Presentation layer, 11
- Transmission Control Protocol (TCP), 66–69
 - destination port, 72–73
 - key features, 71
 - protocols using, 74
 - source port, 72–73
 - syn packet acknowledgment, 74–75
- transparent bridging, 22
- transparent mode for VTP, 394, 396
- Transport layer (OSI), 13–17
 - port numbers, 41, 42
 - reliable delivery, 18
- traps in SNMP, 65
- Trivial File Transfer Protocol (TFTP), 63
- troubleshooting
 - Enhanced Interior Gateway Routing Protocol (EIGRP), 303
 - Frame Relay networks, 553–554
 - Interior Gateway Routing Protocol (IGRP), 264
 - IP addresses, 142–147
 - ISDN DDR, 565–566
 - Open Systems Interconnection (OSI) model, 322–324
 - PPP authentication, 533–534
 - using Frame Relay congestion control, 546–547

- VLAN Trunking protocol (VTP), 411–413
- trunk command, 401
- trunk links, 391, 391
- trunk ports, configuring for VLAN, 401–403
- TTL field in IP header, 77
- tunneling, 27
- Type field in Ethernet frame, 28

U

- U interface, 555
- U reference point in ISDN, 556, 558
- undebg all command, 270
- Unicast, 94
- unshielded twisted-pair (UTP) cabling, 32
- update timers for IGRP, 259
- Urgent field for TCP, 68
- U.S. Department of Defense (DoD), 60. See also DoD (Department of Defense) model
- User Datagram Protocol (UDP), 69–70
 - key features, 71
 - protocols using, 74
 - segment format, 70, 70
- user exec mode, 169
- user-mode passwords, line command for, 182–183
- users, checking Telnet, 459
- UTP (unshielded twisted-pair) cabling, 32

V

- Variable Length Subnet Masking (VLSM), 130–140
 - advantages of, 133
 - block sizes, 134
 - design, 132, 132–134, 133
 - EIGRP support for, 295–296
 - implementing networks, 134–140
 - RIPv2 support for, 258
 - table, 135, 137

- variance command, 260
- Version field in IP header, 76
- virtual circuits, 67
 - in Frame Relay network, 542, 547
 - status of, 544
- virtual LANs (VLANs), 5, 347, 384
 - basics, 384–389
 - broadcast control, 386
 - flexibility and scalability, 387–389
 - security, 386–387
 - configuring, 397–409
 - inter-VLAN routing, 403–409
 - switch port assignment, 399–401
 - trunk ports, 401–403
 - trunking with Catalyst 3550 switch, 402–403
 - exam essentials, 420–421
 - identifying, 390–393
 - frame tagging, 392
 - Inter-Switch Link (ISL) protocol, 393
 - methods, 392–393
 - memberships, 389–390
 - network management, 385–386
 - routing between, 396, 397
- vlan command, 398
- VLAN ID, 392
- vlan-membership command, 399
- VLAN Trunking protocol (VTP), 393–396
 - benefits, 394
 - configuring, 409–413
 - troubleshooting, 411–413
 - modes of operation, 394–396, 395
 - need for, 395
 - pruning, 396
- VLSM. See Variable Length Subnet Masking (VLSM)
- Voice over IP (VoIP), 69
- vtp command, 410
- VTP transparent mode, 394, 396
- VTY passwords, 455–456

W

- WAIS, 11
- well-known port numbers, 71–72
- Wi-Fi (Wireless Fidelity), 38
- wide area networks (WANs)
 - basics, 520–524
 - terminology, 520–521
 - cabling, 524–526
 - data communication equipment (DCE), 525–526, 526
 - fixed and modular interfaces, 526
 - serial transmission, 525
 - Cisco support, 522–524
 - connection types, 521, 521–522
 - Dial-on-demand routing (DDR), 561–567
 - with access lists, 566–567
 - configuring, 562–566
 - optional commands, 566
 - troubleshooting, 565–566
 - Frame Relay, 536–554
 - committed information rate (CIR), 541–542
 - congestion control, 545–547
 - Data Link Connection Identifiers (DLCI), 543–544, 544
 - encapsulation types, 542
 - implementation and monitoring, 547–554
 - Local Management Interface (LMI), 544–545
 - technology basics, 537–541, 539
 - troubleshooting networks, 553–554
 - virtual circuits, 542
- High-Level Data Link Control (HDLC) protocol, 527, 527
- Integrated Services Digital Network (ISDN), 554–561
 - Basic Rate Interface (BRI), 559
 - with Cisco routers, 560–561
 - components, 556–558
 - connections, 555–556
 - Primary Rate Interface (PRI), 560
 - protocols, 558
 - reference points, 558
 - switch types, 558–559
 - terminals, 557–558
 - verifying operation, 567–568
- Point-to-Point Protocol (PPP), 528–536
 - authentication methods, 530
 - configuring authentication, 531–532
 - configuring on Cisco routers, 531
 - Link Control Protocol (LCP) configuration options, 529
 - mismatched IP addresses, 535–536, 536
 - session establishment, 529–530, 530
 - stack, 528
 - verifying encapsulation, 532–533
- wildcard mask, 312, 313
 - in access list, 488–490
 - for default route, 241
 - troubleshooting, 322
- Window field for TCP, 68
- windowing, 16, 17
- wireless networking, 36–38, 37, 524
- workgroup layer in Cisco hierarchical model, 44
- World Wide Web (WWW), 11

X

- X Window, 12, 64
- X.25 technology, 536

Y

- Yahoo!, 11