

Index


Note to the Reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

Symbols & Numbers

#PRE switch in LMHOSTS file, 209
 2^N - 2, 169, 294
 6BONE, 268, 294

A

A record, 232, 294
 dynamic update, 240, 242–243
 acknowledgments, 58, 294
 and delivery guarantee, 60
 DHCP acknowledgment packet, 125, 295
 negative, 253, 298
 acronyms, 304–305
 Active Directory, 247
 Address Resolution Protocol (ARP), 42,
 43–46. *See* ARP (Address Resolution
 Protocol)
 addressing scheme, 12, 18. *See also* IP
 addressing
 Advanced Research Projects Agency
 (ARPA), 4
 Advanced TCP/IP Settings dialog box,
 DNS tab, 245, 245–246
 alias, 201, 294
 anonymous FTP user, 71, 294
 Anycast, 275, 294
 API (Application Programming Interface),
 194, 294
 APIPA (Automatic Private IP Addressing), 128
 AppleTalk protocol suite, 19
 Application layer (DoD), 29, **68–75**, 294
 FTP (File Transfer Protocol), **71–73**
 HTTP (Hypertext Transfer Protocol),
 74–75
 ports and sockets, **67–70**
 well-known ports, **70**
 Application layer (OSI), 25, 28
 Application Programming Interface (API),
 194, 294
 ARP (Address Resolution Protocol), 42,
 43–46, 294
 ARP cache, 43, 43, 294
 ARP packets, **46**
 ARP reply, 45, 46, 46, 294
 ping to examine, 48
 ARP request broadcast, 43, 46, 46, 294
 ping to examine, 48
 to resolve hardware address, **44–45**
 ARPA (Advanced Research Projects
 Agency), 4
 ARPAnet, **4–5**, 294
 cessation, 7
 requirements, 5
 ASCII text file, 294
 HOSTS file as, 200
 audio streaming with IGMP, 50–51
 Automatic Private IP Addressing
 (APIPA), 128



bandwidth—custom subnet masks


B

bandwidth, 256, 294, 298
 name resolution broadcast and, 207
 Berkley Internet Name Domain (BIND), 228
 binary file format, 71, 294
 binary numbering system, 36,
 80–82, 294
 converting decimal to, **84–89**
 with bit value method, 84–85
 with calculator, 88, 88–89
 with division method, 86–87
 converting to decimal, **83**
 counting in, 138
 BIND (Berkley Internet Name
 Domain), 228
 bit, 83
 bit value method, for decimal to binary
 conversion, 84–85
 broadcast, 294
 of NetBIOS name query, 254–255, 256
 broadcast packets, 37, 294
 subnetting rules and, 151

C

cache, 224, 294
 NetBIOS name cache, **203–204**
 caching-only server, 231, 294
 calculator, for decimal to binary
 conversion, 88, 88–89
 Cerf, Vint, “A Protocol for Packet Network
 Interconnection,” 7
 checksum, in UDP header, 61
 CIDR (Classless Inter-Domain Routing),
 96, **186–187**, 295
 circuit-switched network, 9, 9, 295
 classes of IP addresses, **92–96**
 class A, **92–93**
 subnet masks, 171
 subnetting, 161–162

 class B, **94**
 problems from, **181–182**
 subnet masks, 172
 subnetting, 163–164
 class C, **95**
 subnet masks, 173
 valid hosts, 165–167
 class D, **96**
 class E, **96**
 custom subnet masks, 143
 limitations, 180
 standard subnet masks, **142–143**
 classful addressing system, 180, 295
 classless addressing system, 186
 client. *See also* Microsoft TCP/IP client
 for FTP, 71
 Windows configuration for dynamic
 DNS, 244–247
 CNAME (Canonical Name) record,
 232, 295
 .com domain, 221
 command prompt, to run HOSTNAME
 utility, 199
 communication, host-to-host, 7
 connection-oriented communication, 56,
 58, 295
 connectionless communication, 57, 295
 UDP (User Datagram Protocol) for,
 61–63
 contiguous bits, 295
 in subnet mask, 155
 Control Panel (Windows XP), 103, 103, 104
 Crocker, Steve, 6
 custom subnet masks, **148–170**, 295
 creating additional networks, 150
 creation, **151–170**
 calculating number of networks and
 hosts, 169–170
 determining maximum number of
 hosts on networks, 153
 determining number of subnets
 needed, 152–153



custom subnet masks—dotted decimal notation

- range of valid host IP addresses, 158–160
- subnet mask determination, 153–156
- valid network addresses, 157–158
- subnetting rules, 150–151

CuteFTP, 73, 295

D

Data-Link layer (OSI), 27, 28. *See also* Network Interface layer (DoD)

data transfer, protocols and, 18

database for DNS, **228**

- A record, 232, 294
 - dynamic update, 240, 242–243
- CNAME (Canonical Name) record, 232, 295
- MX (Mail eXchanger) record, 233, 297
- NS record, 232, 298
- PTR (pointer) record, 233, 299
 - dynamic update, 240, 242–243
- Start of Authority (SOA) record, 232, 300

decimal numbering system, 36, 80–82, 295

- converting binary to, **83**
- converting to binary, **84–89**
 - with bit value method, 84–85
 - with calculator, 88, 88–89
 - with division method, 86–87

default gateway, 40, 42, 295

- in Windows NT, 113

DHCP (Dynamic Host Configuration Protocol), **116–117**, 238

- leases, 121, **126–128**
 - IP address renewal, **127–128**
 - setting duration, **130**
- obtaining address from server, **118–125**
 - DHCP acknowledgment packet, 124–125, 125, 295
 - DHCP discover packet, 118–119, 119, 295
 - DHCP offer packet, 119–121, 121, 295
 - DHCP request packet, 121–123, 123, 295
 - reserving DHCP IP addresses, **129**
 - setting scopes and options, **131**
 - setup in Windows NT, 111

DHCP server, 116, 295

- in Dynamic DNS, 239
- UDP to search for, 62–63
- Windows 2000 configuration for dynamic update, **241–247**, 242

diagnostics. *See* troubleshooting

division method, for decimal to binary conversion, 86–87

DNS (Domain Name System), **202**, **219–233**, 295. *See also* Dynamic DNS

- completing resolution, **226**
- database
 - automatic updates, 239
 - maintenance, **228**
 - record types, **231–233**
- on the Internet, **221**
- querying name servers, **224–225**
- what it is, **220**

DNS server

- maintaining, **229–233**
 - caching-only server, 231
 - primary name server, 229
 - secondary name server, 229
- querying, **223**
 - Windows XP settings to indicate, 106

DNS zone transfer, **230**, 230

DoD (Department of Defense), 4, 295


- reference model, **29**

domain, 221, 295

domain controller, 247

domain name space, 221, 295

dotted decimal notation, 90, 139–140, 296



double-colon notation—HOSTS file

double-colon notation, 271,
272–273, 296
 Dynamic DNS, **237–247**, 296
 benefits, 247
 on Internet, 247
 Windows 2000 server configuration,
 241–247

E

.edu domain, 221
 electrical appliances, IP addresses
 for, 270
 encapsulation, 20, 296
 Ethernet address, 36
 exclusions, 296
 from DHCP scope, 131

F


failure recovery, as TCP design goal, 8
 fault tolerance, 296
 secondary name server for, 229
 firewall, 48, 296
 flexibility, of TCP/IP, 3
 FTP (File Transfer Protocol), **71–73**,
 72, 296
 port for, 70
 FTP command interpreter, 71, 73, 296
 FTP command line utility, 71, 296
 FTP server, 296
 FTP/TCP/IP packet, 72, 296
 FTP Voyager, 73

G

gateway. *See* default gateway
 global option, for DHCP scope, 131, 296

H

handshake, three-way, **58–59**, 300
 hardware address, 35, **36–37**
 ARP request broadcast to resolve,
 44–45
 determining, **42**
 resolution of IP address to, 43
 target, 37
 hardware, independence as TCP design
 goal, 8
 headers for packets, 20, 296
 IP (Internet Protocol), 39
 from Network Interface Layer, 35
 TCP (Transmission Control Protocol), 63
 sequence numbers, 60
 UDP (User Datagram Protocol), 61, 63
 hexadecimal numbering system, 36,
 81, 296
 for IPv6 addresses, 271
 host, 3, 296
 interaction with Network Interface
 layer, 34
 host name resolution, **193**, **196–212**, 296
 broadcast, **206–207**
 cycle, 212, 212
 DNS (Domain Name System), **202**
 HOSTS file, **200–201**
 LMHOSTS file, **208–209**
 local host process, **198–199**
 NetBIOS name cache, **203–204**
 NetBIOS name resolution vs., **195**
 WINS (Windows Internet Naming
 Service), **205**
 host-to-host communication, 7
 Host-to-Host layer. *See* Transport layer
 HOSTNAME utility, **198–199**, 296
 hosts, 18
 number on network, 153
 HOSTS file, **200–201**, 296



hosts.txt file—IP addressing

- hosts.txt file, 220, 296
- HTML (Hypertext Markup Language), 74, 297
- HTTP (Hypertext Transfer Protocol), **74–75**, 297
 - port 80 for requests, 69
- HTTP/TCP/IP packet, 74, 296
- hyperlinks, 74, 296
- |
- IANA (Internet Assigned Number Authority), 70, 181, 297
- ICMP (Internet Control Message Protocol), **47–48**
 - ping to examine packet, 48
- IETF (Internet Engineering Task Force), 6, 297
- IGMP (Internet Group Management Protocol), **49–51**
- IN-ADDR.ARPA zone, 233, 297
- installing IP addressing, **102–117**
 - manual configuration, **102**
 - on Windows 95/98, **114–116**
 - on Windows 2000, **106–110**
 - on Windows NT, **110–114**
 - on Windows XP, **103–106**
- Internet, 2
 - growth, 180
 - origins, **4–5**
- Internet Assigned Number Authority (IANA), 70, 181, 297
- Internet Control Message Protocol (ICMP), **47–48**
 - ping to examine packet, 48
- Internet Engineering Task Force (IETF), 6, 297
- Internet Group Management Protocol (IGMP), **49–51**
- Internet layer (DoD), 29, **38–51**, 297
 - IP (Internet Protocol), **39–42**
 - Internet Protocol, Next Generation (IPng), 297. *See also* IP (Internet Protocol) version 6
 - Internet Protocol (TCP/IP) Properties dialog box, 105–106, 106
 - for manual IP address assignment, 109, 109
 - Internet routing tables, 181–182, 297
 - supernetting and, **183–185**
 - internetwork, 12, 13, 297
 - InterNIC, reserved IP addresses, 93
 - interoperability of TCP/IP, 3
 - IP (Internet Protocol), **39–42**, 297
 - hardware address determination, **42**
 - local or remote destination, **40–41**
 - IP (Internet Protocol) version 6, **267–277**, 297
 - addressing scheme, **269–274**
 - future possibilities, 270
 - converting IPv4 addresses to, 273
 - documentation, **274**
 - improvements of, **275**
 - special addresses, **274**
 - transition plan, **276–277**
 - Web documents about, 309
 - IP addressing, 38, **80–97**, 297. *See also* DHCP (Dynamic Host Configuration Protocol); name resolution allocation, **180–182**
 - CIDR (Classless Inter-Domain Routing), 96
 - classes, **92–96**
 - custom subnet masks, 143
 - standard subnet masks, **142–143**
 - summary, **97**
 - converting IPv4 to IPv6, 273
 - dotted decimal notation, 90
 - installation and assignment, **102–117**
 - manual configuration, **102**
 - on Windows 95/98, **114–116**
 - on Windows 2000, **106–110**

IP addressing—name resolution

- on Windows NT, **110–114**
- on Windows XP, **103–106**
- numbering systems, **80–89**
- reserved, 49
- resolution to hardware address, 43
- IP broadcast address, 93
- IPng (Internet Protocol, Next Generation), 268, 297
- IPv5, 268
- IPX/SPX protocol suite, 19
- ISO (International Organization for Standardization), 23, 297. *See also* OSI reference model
- iterative query, 226–227, 297

K

Kahn, Bob, “A Protocol for Packet Network Interconnection”, 7

L

- LAN Manager, 209, 297
- layers in OSI model, 23, **24**, 297
 - mnemonics for remembering, 27
 - responsibilities, **25–27**
- leading zeros, in binary number conversion, 89
- leases in DHCP, 121, **126–128**
 - discarding forward lookups after expiration, 243
 - setting duration, **130**
- LLC (Logical Link Control) sublayer, 27
- LMHOSTS file, **208–209**, 297
- load balancing, 297
 - secondary name server for, 229
- Local Area Connection Properties page (Windows 2000), 107
- Local Area Connection Properties page (Windows XP), 105
- local host, 297

- local host process, in name resolution, **198–199**
- local network, 297
 - identifying, **139–141**
 - as packet destination, 136
- logical address, 39, 297
- Logical Link Control (LLC) sublayer, 27
- loopback address, 93, 274, 297

M

- MAC (Media Access Control) address, 36
- MAC (Media Access Control) sublayer, 27
- Mail eXchanger (MX) record, 233, 297
- master DNS database, 229, 297
- memory, ARP cache in, 43, 43
- Microsoft TCP/IP client, 298
 - host name, 196
 - name resolution steps, 195
 - NetBIOS name cache, **203–204**
- Microsoft TCP/IP Properties dialog box (Windows NT), IP Address tab, 113, 113
- Microsoft TCP/IP Properties dialog box, WINS Address tab, 204
- multicast address, 49, 96, 275, 298
- multicast packet, 298
- multimedia streaming, 51
- MX (Mail eXchanger) record, 233, 297

N

- name release request, to WINS server, 261
- name resolution, **191–215**, 298
 - basics, **192–193**
 - broadcast, **206–207**
 - DNS (Domain Name System), **202, 222–228**
 - host name resolution, **193**
 - cycle, 212, 212
 - HOSTS file, **200–201**

name resolution—overhead, minimization as TCP/IP goal

- LMHOSTS file, **208–209**
 - local host process, **198–199**
 - NetBIOS name cache, **203–204**
 - NetBIOS name resolution, **194, 213–215**
 - vs. host name resolution, **195**
 - WINS (Windows Internet Naming Service), **205**
 - name servers, 229, 298
 - querying, **224–225**
 - NAT (Network Address Translation), 93, 298
 - nbtstat command, 209–211, *210*, 298
 - NCP (Network Control Protocol), 4, 298
 - limitations, 7
 - negative acknowledgment, 253, 298
 - negative name query response, 260
 - net view command, 213, 215
 - NetBIOS, 298
 - NetBIOS applications, **252–263**
 - NetBIOS name resolution with WINS, **257–261**
 - name registration, 257
 - NetBIOS name resolution without WINS, **252–256**
 - name registration, 253
 - WINS Manager, **262–263**
 - NetBIOS name cache, **203–204**, 254, 298
 - pre-loading entries, 209
 - viewing contents, 209–211, *210*
 - NetBIOS name query, 254, 298
 - NetBIOS name resolution, **194, 213–215**, 298
 - cycle, 214–215, *215*
 - vs. host name resolution, **195**
 - NetBIOS name server, 257, 298
 - NetBIOS names, 298
 - in LMHOSTS file, 208
 - NetBIOS scope ID, 204
 - NetWare, HOSTS file, 201
 - network
 - 6BONE, 268, 294
 - circuit-switched, **9, 9**, 295
 - packet-switched, **10, 10**, 299
 - functioning of, 11
 - Network Address Translation (NAT), 93, 298
 - network administrator, 2, 298
 - Network and Dial-Up Connections window (Windows 2000), 106
 - network bandwidth, 256, 294, 298
 - Network Control Protocol (NCP), 4, 298
 - limitations, 7
 - Network dialog box (Windows 95/98), Configuration tab, *114*
 - Network dialog box (Windows NT)
 - Identification tab, *110, 112*
 - Protocols tab, *112*
 - network interface cards (NIC), 36
 - Network Interface layer (DoD), 29, **34–37**, 298
 - Network layer (OSI), 26
 - Network Neighborhood, 252
 - network topology, 34, 298
 - NIC (network interface card), 36, 298
 - Novell, 19
 - Novell Netware server, configuration for dynamic DNS, 243–244, *244*
 - NS record, 232, 298
 - numbering systems, 36, **80–89**
- ## O
- octal numbering system, 81
 - octets, 90, 298
 - open standard, TCP/IP as, 12
 - operating systems, support for TCP/IP, 2
 - OSI (Open Standards Interconnection) reference model, **23–28**, 298
 - vs. DoD model, 29
 - layers, 23, **24**
 - mnemonics for remembering, 27
 - responsibilities, **25–27**
 - use, **28**
 - overhead, minimization as TCP/IP goal, 8

Packet InterNet Groper—RFCs (Requests for Comments)

P

Packet InterNet Groper. *See* Ping (Packet InterNet Groper)

packet-switched network, **10**, 10, 299
functioning of, 11

packets, 10, **20–21**, 21, 298

DHCP

- acknowledgment packet, 124–125, 295
- discover packet, 118–119
- offer packet, 119–121
- request packet, 121–123

DHCP acknowledgment packet, 125

- for DNS query, 226
- for IPv6, 275
- TCP portion, 57, 57
- UDP portion, 57, 57

parsing, 201, 299

PC DOS, 180, 299

peer-layer communication, 28, 299

physical address, 36

Physical layer (OSI), 27, 28

Ping (Packet InterNet Groper), 47, 196–197, 299

- packets, **48**

ports and sockets, **67–70**, 299

- for HTTP, 74
- for UDP, 61
- well-known ports, **70**, 301

#PRE switch in LMHOSTS file, 209

Presentation layer (OSI), 26, 28

primary name server, 229, 299

printers, reserved IP addresses for, 129

protocol stack, 1, 2, 19, 299

protocol suite, 1, 2, 299

- examples, 19

protocols, 1, 2, 299

- need for, **22**
- packet movement by, **20–21**, 21
- questions answered by, 19

- what they are, **18–21**

- proxy server, 93, 299

PTR (pointer) record, 233, 299

- dynamic update, 240, 242–243

Q

querying

- DNS server, **223**

- iterative or recursive, 226–227

- name servers, **224–225**

R

RAM, ARP cache in, 43, 43

RAND Corporation, 4

read-only, 299

- DNS database as, 230

read/write, 299

- DNS database as, 229

real-time, 275, 299

records, 299

- DNS types, **231–233**

recursive query, 226–227, 299

redundancy, as ARPAnet requirement, 5

reliability, 56

remote network, 40, 299

- identifying, **139–141**

- as packet destination, 136

remote resolution, secondary name

- server for, 229

reserved IP addresses, 49, 93, 299

- class E as, 96

resolve, 299

resolver, 222, 299

RFCs (Requests for Comments), **6**, 299

- 761 for TCP, 63

- 768 for UDP, 63

- 801 for NCP to TCP transition, 7

- 849 for hosts.txt file, 220

- 959 for FTP, 71

RFCs (Requests for Comments)—subnet mask

- 1034 for DNS, 220, 238
 - 1035 for DNS, 220, 238
 - 1060 for well-known ports, 70
 - 1700 for well-known ports, 70
 - 1752 for IPng, 268
 - 1878 for subnet addressing, 151
 - 1884 on IPv6 addressing, 271
 - 1924 on IPv6 addressing, 271
 - 1933 for transition to IPv6, 276
 - 1946 on IPv5, 268
 - 2136 for Dynamic DNS, 239
 - 2137 for Dynamic DNS security, 239, 246
 - for IPv6, 274
 - Web site links, 308
 - root name servers, 223, 299
 - routability
 - on-the-fly, 5
 - of TCP/IP, 3, 8, 12
 - routers, 40, 147, 299. *See also* default gateway
 - name resolution broadcast and, 206
 - and reserved IP addresses, 93, 129
 - routing, 299
 - Internet layer for, 38
 - routing table, 41, 299
- S**
- scope for DHCP, 117, 300
 - setting, **131**
 - scope ID, NetBIOS, 204
 - scope option, 300
 - secondary name server, 229, 300
 - secured dynamic updates of DNS, 246
 - Select Network Component Type dialog box (Windows 2000), 107
 - Select Network Protocol dialog box (Windows 95/98), 115
 - Select Network Protocol dialog box (Windows 2000), 108
 - Select Network Protocol dialog box (Windows NT), 111
 - sequence numbers, 300
 - in TCP header, 60
 - server service, 252, 300
 - servers
 - for FTP, 71
 - reserved IP addresses for, 129
 - Session layer (OSI), 26
 - shares, 213, 300
 - shutdown, and DHCP lease, 128
 - SIT (Simple IPv6 Transition), 276, 300
 - SMTP (Simple Mail Transfer Protocol), 75
 - SNMP (Simple Network Management Protocol), 75
 - port for, 70
 - SOA (Start of Authority) record, 232, 300
 - sockets, 69, 300
 - software, independence as TCP design goal, 8
 - source-quench packet, 47, 300
 - SRI-NIC (Stanford Research Institute Network), 220, 300
 - standard subnet masks, 142–143, 300
 - standards, need for, **22**
 - Stanford Research Institute, 5
 - Start of Authority (SOA) record, 232, 300
 - static entry in WINS database, 262–263, 300
 - statically-assigned IP addresses, and dynamic update, 243
 - stream of data, 300
 - sending audio and video with IGMP, 50–51
 - sending to multiple hosts, 49
 - subnet, 148, 300
 - subnet bits, 150, 300
 - subnet calculator, 151, 300, 309
 - subnet goggles, 300
 - subnet mask, 300

subnet masks—URL (Uniform Resource Locator)

subnet masks, 39. *See also* custom subnet masks

- class A, 171
- class B, 172
- class C, 173
- local or remote network identification, **139–141**
- network and host, **138–139**
- standard for classes, **142–143**
- supernetted, 185
- what it is, **136–141**
- in Windows NT, 113

supernetted subnet mask, 300

supernetting, **183–185**

switches, 300

- in LMHOSTS file, 209

T

TCP (Transmission Control Protocol), 56, **58–60**, 300

- data organization and delivery guarantee, 60
- ports, 69

TCP/IP (Transmission Control Protocol/Internet Protocol), 1, 301

- advantages, **12–13**
- birth, **7**
- companion Web site, **308–309**
- design goals, **8**
- and DoD model, **29**
- features, 3
- installing on Windows 95/98, **114–116**
 - manual assignment of IP address, **115–116**
- installing on Windows 2000, **106–108**
- installing on Windows NT, **110–114**
 - manual assignment of IP address, **112–114**
- installing on Windows XP, **103–106**
 - manual assignment of IP address, 103–106

Microsoft client, 298

- host name, 196
- name resolution steps, 195
- NetBIOS name cache, **203–204**
- need for new version, **268**
- what it is, **2–3**

testing. *See also* troubleshooting

- 127. IP address for, 93

text file format, 71

TFTP (Trivial File Transfer Protocol), 75

- port 69 for, 69, 70

three-way handshake, **58–59**, 300

Transport layer (DoD), 29, **56–57**

- TCP (Transmission Control Protocol), **58–60**
- UDP (User Datagram Protocol), **61–63**

Transport layer (OSI), 26

troubleshooting

- 127. IP address for, 93
- HOSTNAME utility for, 199
- ICMP to perform, 47
- loopback address for, 93, 274

TTL (time to live), 300

- for DHCP lease, 126
- setting duration, 130

U

UDP (User Datagram Protocol), 56, 57, **61–63**, 301

- ports, 69

Unicast, 275, 301

United States Department of Defense (DoD), 4, 295

- reference model, **29**

University of California at Los Angeles, 5

University of California at Santa Barbara, 5

University of Utah, 5

Unix, HOSTS file, 201

unspecified address (IPv6), 274

URL (Uniform Resource Locator), 74, 301

vendors, support for TCP/IP—zone transfer

V

vendors, support for TCP/IP, 3
video streaming with IGMP, 50–51

W

WAN connection, 301
 subnet address for, 153
Web browser, 301
 HTTP for, 74
Web browser application, 74
Web server, 74, 301
Web sites
 connection process, 74–75
 for *TCP/IP JumpStart*, **308–309**
well-known ports, **70**, 301
WellKnown Service (WKS) record, 233
WildPackets, IP Subnet Calculator, 149, 149
Windows 95/98
 DHCP on, 108
 HOSTS file, 201
 IP addressing installation, **114–116**
 manual assignment of IP address,
 115–116
Windows 2000
 client configuration for dynamic DNS,
 244–247
 DHCP server configuration for
 dynamic update, **241–247**
 HOSTS file, 201
 IP addressing installation, **106–110**
 manual assignment, **109–110**

Windows (Microsoft), calculator, 88,
88–89
Windows NT
 HOSTS file, 201
 IP addressing installation, **110–114**
 manual assignment, **112–114**
Windows XP
 client configuration for dynamic DNS,
 244–247
 HOSTS file, 201
 IP addressing installation, **103–106**
WINS (Windows Internet Naming
Service), 49, **205**, 301
 IP addressing installation, 49
 NetBIOS name resolution with,
 257–261
 name registration, 257–259
 NetBIOS name resolution without,
 252–256
 name registration, 253
 static entry in database, 262–263
WINS Manager, **262–263**
WINS server, limits on clients, 261
WKS (WellKnown Service) record, 233
workstation service, 252, 301

Z

zeros, leading, in binary number
conversion, 89
zone file, for DNS server database, 228
zone transfer, 230, 230, 301