

Index

- 8-PSK, 10, 23, 162, 163, 164, 167
- (IP) Servers, 277, 294, 331–335, 341, 347–348, 350–351, 353–354, 378–384, 397–403, 427–430
- 2 Mbps Channel, 355
- 2 Mbps Planning, 286
- 3dB compression point, 166
- 3GPP, 10, 328, 329, 331, 332, 333, 335, 337, 339, 341, 342, 343, 352, 467, 472, 473
- 4 bit cyclic redundancy check (CRC4), 113
- 4G, 417, 418, 419, 420, 421, 422, 423, 425, 426, 428, 429, 430, 431, 435, 436, 437
- 8-PSK, 10, 23, 162, 163, 164, 167
- 8-PSK power envelope, 168
- 8-PSK Vector Diagram (Phase-State Transition), 10, 163–168, 173
- A_{bis} Interface, 110, 135
- A Interface Trace, 110
- AAL (ATM Adaptation Layer), 11, 223–224, 228–231, 273–274, 309–311, 340–341, 349
- AAL2 Signalling, 274, 340
- Abis, 25, 35, 110–111, 130, 135, 140, 268–271, 286–288, 300
- ABR (Available Bit Rate), 231, 233
- Absorption, 256
- Access Link Control Application Part (ALCAP), 274
- Access Point Node (APN), 174, 381, 383, 395, 402, 413
- Accessibility, 131, 299, 303–307, 408, 414–415
- Accessibility, Retainability, Quality (ARQ), 162
- Adaptive Mean Rate (AMR), 12, 60–61, 144, 342
- Adjacency, 121, 125, 147, 150–151
- Adjacency control, 85, 110, 158
- Adjacency Definition, 93, 121, 147, 150, 154–155
- Adjacency management, 122–123, 125
- Adjacency optimization, 151
- Adjacency parameters, 150
- Adjacency planning, 18, 20, 122, 125
- Adjacent Channel, 282, 305
- Administrative automation, 122–123
- Admission Control (AC), 103–106, 307–308, 441
- Advection, 263
- AGCH, 61, 80–87
- A-GPS (Assisted-GPS), 246, 289
- AICH, 90, 94–95, 102
- Air-Interface, 3, 9–11, 26–27, 87, 133, 135–137, 140, 173, 419, 498–500, 506
- Alarm Management, 291
- Alarm monitoring, 104, 110, 369
- Algorithms, 8, 20, 24, 26, 101, 109, 126, 144–145, 156, 305, 388, 390, 471, 473
- ALL-IP Networks, 427–428
- Amplifier, 31, 53
- AMR Codec, 342–343
- ANSI, 273, 295, 452
- Antenna directivity, 238
- Antenna Filter, 283
- Antenna gain, 31–33, 36, 39–40, 49, 53, 56, 234, 238, 249, 252
- Antenna Height, 53, 115, 242, 244, 252, 420
- Antenna system maintenance, 160, 251
- Application Manager (AM), 27, 455
- Architecture, 129, 135, 324, 328, 330, 335–341, 346, 361, 399–401, 417, 428–429, 432–434
- ARIB, 10
- Asynchronous Transfer Mode (ATM), 11, 201, 217, 219–234, 273, 276, 294–295, 311–314, 329–331, 345, 350, 353, 355, 395, 401

- ATM Adaptation Layer (AAL), 224, 228
- ATM Adaptation Layer 1 (AAL 1), 230
- ATM Adaptation Layer 2 (AAL 2), 11, 273, 274, 309–311, 340, 345, 377
- ATM Adaptation Layer 3 and 4 (AAL 3/4), 230–231
- ATM Adaptation Layer 5 (AAL 5), 11, 231, 273, 350, 353, 355
- ATM cell, 224–228, 230–231, 313
- ATM Cross-Connect (AXC), 293
- ATM Layer, 223–226, 228, 230–231, 312
- ATM Performance, 231, 312
- ATM Terminations, 293
- Atmospheric Fading, 239
- Attenuation, 27, 40, 235–236, 240–241, 249, 256, 424
- Authentication Centre (AC), 5
- Authentication Centre (AUC), 5
- Automatic Repeat Request (ARQ), 162, 469
- Automation tools, 122
- Availability, 33, 64, 98, 113, 132, 147, 188, 247, 281–282, 285, 300–302, 347, 368, 440, 447
- Availability Bit Rate (ABR), 231, 233
- Average Antenna Height, 246
- Average Power Decrease (APD), 163–165
- Averaging, 74, 144, 371

- Background Class, 11
- Backoff, 36, 163–164, 166–167
- Base band hopping, 75, 116
- Base Station (BS), 4, 8, 11, 32, 49, 54–55, 70, 80, 294, 420, 430
- Base Station Controller (BSC), 4, 106–107, 120–121, 128, 132–133, 152, 155, 160, 175, 269, 281, 284–285, 289–292, 338–339, 448
- Base Station Identity Code (BSIC), 76, 121, 150, 154–155
- Base Station Subsystem (BSS), 4, 74, 85–86, 110, 130, 140, 155, 270, 392, 407
- Base Station Subsystem GPRS Protocol (BSSGP), 85, 391
- Base Transceiver Station (BTS), 4, 18, 30–33, 36, 44, 46, 51–53, 74, 77, 126, 134, 145, 146, 155, 159–161, 268–269, 278–280, 285–287, 289–291, 444, 478
- BCCH, 7, 61, 74–77, 79–80, 82–83, 88, 93–94, 116, 150, 155, 164–165, 171
- BCCH strategy, 116
- BCCH TRX, 74, 160, 164
- Bit Error Rate (BER), 53, 109, 141, 172
- Bit-Error Probability (BEP), 171, 342

- Block error Rate (BLER), 54, 102
- Blocking, 6, 33, 37, 58–59, 62–65, 71, 133, 174–175, 179–180, 271, 276–278, 412
- Body Loss, 31, 36, 38, 56
- Boosting power, 142
- Border Gateway (BG), 377, 395–396
- BPSK, 470
- Broadcast Channel (BCCH), 7, 61, 74–77, 82–83, 88, 93–96, 116, 150, 155, 164, 171
- BSC and transcoder hardware maintenance, 160
- BSC Load, 120–121, 160
- BSC Location, 160
- BSC rehosting plan, 120
- BSS parameters classification, 155
- BSS Protocol, 4, 8, 25, 74, 85–86, 130, 155, 391, 429
- BTS Antenna Gain, 36
- BTS hardware maintenance, 159
- BTS power back-off, 35
- BTS Sensitivity, 30
- Buffering, 173, 232, 276, 340
- Burst Period, 25, 164
- Burst Structure, 164
- BVC flow control, 35

- C/I Ratio, 282
- Cable Losses, 31
- Call management (CM), 136
- Call performance, 185
- Call phase signaling charts, 110, 130, 133, 137
- Call phases, 130, 137, 139
- Call Quality, 131, 149
- Call setup failure (CSF), 107
- Call Set-Up Success Rate, 17–18, 132, 181, 188
- Call Set-Up Time, 368, 371, 493
- Call success rate (CSR), 132, 344
- Call-Admission Control (CAC), 275
- Camping, 92, 148, 155
- Capacity, 2, 3, 10–13, 17–26, 29, 33–34, 46, 61–63, 65, 67, 69, 74, 79, 82–84, 86–87, 98, 103, 109, 121, 123, 126, 141–143, 5, 160, 179, 201, 205–206, 208, 215, 217, 222, 242, 261, 269, 272, 280–281, 299, 301, 312, 331, 336, 347, 375–376, 396–397, 426, 462
- Capacity Analysis, 24
- Capacity enhancement, 61, 141–142, 144
- Capacity Estimations, 275
- Capacity Planning, 20, 57–71, 503, 505
- CBR (Constant Bit Rate), 231
- CCPCH, 89, 96

- CDMA Radio Networks, 34, 89
- CDV (peak-to-peak Cell Delay Variation, 231–233
- CDVT, 233
- Cell Coverage, 29–30, 51–52, 73
- Cell Delay Variance (CDV), 231–232
- Cell Error Ratio (CER), 232
- Cell Loss Priority (CLP), 312–313
- Cell Loss Ration (CLR), 231–232, 312
- Cell Mis-Insertion Ratio (CMR), 232
- Cell Overlay, 485
- Cell Range, 29, 35–36, 42, 47–48, 57, 504
- Cell re-selection, 80, 93–94
- Cell search, 91–92
- Cell Service Area, 4, 48
- Cell Structure, 227
- Cell Transfer Delay (CTD), 232
- Cellular troubleshooting, 126
- Chain Topology, 281
- Channel Allocation, 142, 200, 493
- Channel Configurations, 86
- Channel to Interference (C/I) Ratio, 282
- Channelisation Codes, 98
- Charging Gateways (CG), 385, 396
- Chip Rate, 26–28, 69, 105
- Chips, 26, 89–90
- Circuit Group, 323–324, 357–359, 369–370, 375, 378, 399, 499
- Circuit Switched (CS), 315, 335, 341, 349, 352–355, 361, 368–377
- Class A Mobiles, 342, 385, 392
- Class B Mobiles, 342, 386
- Class C Mobiles, 342, 386
- CLR (Cell Loss Ratio), 231–232, 306
- Cluster, 181–182, 187, 195, 429–430
- Co-Channel Interference, 20, 71–72, 76
- Code Division Multiple Access (CDMA), 3, 10–11, 26, 421
- Code Planning, 183
- Coding Schemes, 23, 54–55, 66, 163, 367, 369
- Configuration Management, 291
- Conformance, 494
- Congestion, 21, 133, 174, 228, 304, 311, 373, 401, 474
- Connection Admission Control (CAC), 103–104
- Connection establishment, 138, 274, 311, 361
- Connectivity, 278, 329, 399, 403, 406, 487
- Connector Losses, 31, 36, 241
- Constant Bit Rate (CBR), 231
- Control Channels (CCH), 60, 88, 133, 275
- Control Unit (RRM), 26, 29, 66, 286
- Convergence (CL), 272, 309, 486
- Conversational Class, 11
- Core Network (CN), 11, 333, 421–422, 429
- Core Network Optimisation, 368–377, 404–410
- Core Network Optimisation Plan, 373, 373–377, 378–402, 404–413, 414
- Core Network Planning, 315–415
- Counters, 128–131, 141, 189, 309, 370, 407, 465
- Coverage, 17, 20, 34, 46–47, 51, 54–55, 57, 141, 144, 337, 487
- Coverage and capacity enhancement methods, 17, 34, 53, 141
- Coverage Enhancements, 53, 141–142
- Coverage Planning, 20, 45–47, 50–55, 57
- Coverage Plans, 20, 52
- Coverage Threshold, 21, 48–49, 52
- CPICH, 89, 91–92, 94, 105
- CS Territory, 63
- CS-1, 23, 36, 54–56
- CS-2, 23, 36, 55–56, 66–67, 350
- CS-3, 23, 36, 55, 57, 67, 271
- CS-4, 23, 36, 54–55, 67
- CSW, 66, 168
- DAT Tapes, 463
- Data Collection and Analysis, 370
- Data Collection: Signalling, 128, 140, 369
- DCR, 107, 131–133, 191
- Delay, 232, 242
- Demodulation, 236
- Destination, 7, 378
- Detailed Network Planning, 323, 325, 352, 353, 355, 357
- Diffraction, 40, 44, 254–255
- Diffraction Fading, 254
- Dimensioning, 19, 29, 33–34, 37, 51, 57–59, 62, 64, 68–69, 84, 128, 272, 275, 278, 315, 317, 319–320, 335–336, 339, 341, 345, 347, 377, 390–398, 412, 476–480
- Direct Sequencing, 26
- Directed retry, 23
- Direct-Sequence WCDMA Frequency-Division Duplex (DS-WCDMA-FDD), 97
- Direct-Sequence WCDMA Time-Division Duplex (DS-WCDMA-TDD), 11, 97
- Discontinuous transmission, 74, 91, 143, 342
- Diversity Effects, 31
- Domain Name Server (DNS), 331, 395, 402
- Double frame mode (DBLF), 113
- Downlink Modulation, 70,
- Downlink Power Budget, 70, 143, 146

- Downlink Shared Channel (DSCH), 468–477
- Downlink Spreading, 27
- Drive Test, 20–21, 45, 106–108, 114, 121, 127, 140, 154, 181–182, 185, 187, 465
- Drive testing (EGPRS), 23–25, 34–36, 54, 62, 66, 68, 69, 78, 79, 82, 162, 163, 164, 165, 169–171, 172–175, 179–181, 269, 271
- DRNC (Drifting RNC), 100
- Drop Call Rate (DCR), 107
- DSCH, 469, 474
- Dual band, 23, 143
- Dual-Tone Multi-Frequency (DTMF), 349
- Ducting, 351, 361–362
- Dynamic Abis, 269–270, 300
- Dynamic Abis Pool (DAP), 300

- E1, 35, 314, 384
- Eb/N₀*, 94
- Effective Radius, 245
- EGPRS, 23–25, 34–36, 54, 62, 67–69, 78–80, 83, 162–165, 169–172, 174, 175, 279
- EGPRS Abis transmission, 35
- EGPRS Coverage Planning, 54–57
- EGPRS Dimensioning, 46
- EGPRS Throughput per Timeslot vs C/I, 169
- EGPRS Throughput, Latency, Link Adaptation, 171–172
- EIR, 5–6
- Emergency Numbers, 323
- Enablability, 149, 156–157
- End-to-End QoS, 434, 436, 437
- Enhanced Data Rates In GSM Environment (EDGE), 10, 271–272, 287, 293
- Equipment Enhancements, 483, 484
- Equipment Identity Registers (EIR), 352
- Equipment Location, 5, 7–8, 16, 18–21, 45–46, 51, 53, 58, 74–75, 77, 86, 92–93, 96, 100, 103, 106, 115, 125, 160, 161, 182, 246, 250, 256, 280, 281, 287, 291–292, 303, 314, 316–317, 320, 336–337, 339, 347, 350–352, 378–381, 383, 384, 436
- Erlang B, 58–59, 62, 71, 278
- Erlang C, 58, 506
- Error Performance, 251–252, 300–301
- Error Rate, 102, 113, 141
- Error Seconds (ES), 301
- Estimated Traffic, 33, 37
- ET Port, 323
- ET Port Allocation Plans, 323
- ETSI, 23, 30, 48, 342, 493–494

- Exchange Terminals, 160, 294
- Extended cell smart radio concept, 142
- External Interference, 182, 187

- FACH, 88–89, 103
- Fade Margin, 247, 250, 266–267
- Fading, 31, 34, 38, 41, 47–49, 142, 162, 169, 171–172, 174, 234–236, 239, 251, 254, 256, 261, 264–265, 281, 421, 423–424, 441, 465
- Failure Analysis, 106, 107, 121, 128, 130, 132, 137, 141, 152, 154–155, 160, 172, 174, 177–179, 183, 187, 189, 191, 195, 205, 250, 284, 291, 301, 307, 310–311, 314, 318, 321, 324, 354, 373, 375, 377, 401, 403, 408–409, 421, 439, 449, 453, 456–460
- Fast Associated Control Channel (FACCH), 61, 133, 135, 136
- Fast moving threshold, 151
- Fault analysis and improvement, 128
- FDD, 94, 97
- Feeder loss, 240–241, 252
- Filter, 31, 33, 36, 110, 114, 140, 283, 435
- Final Acknowledge Indicator (FAI), 180, 181
- Firewall (FW), 396
- Firewall Servers, 403, 410
- First-Generation, 1, 2, 3
- Flat Fading, 252
- Forward Error Correction (FEC) – codec rate, 162, 171–173, 236, 491
- Fourth-Generation Networks, 417–436
- Frame Error Rate (FER), 106, 109, 110, 141
- Frame-Relay, 220, 231, 286, 403
- Free-Space Loss (FSL), 249, 252
- Frequency Allocation, 115, 143, 283
- Frequency Band, 2–4, 11, 18, 33, 40, 59, 71, 115–116, 125, 143, 187, 234–236, 241, 282, 419–420, 435, 488
- Frequency Band Division, 59
- Frequency Bands in WCDMA-FDD, 97
- Frequency Correction Channel (FCCH), 61, 82–83
- Frequency Diversity, 3, 265, 267
- Frequency Hopping, 54–55, 61, 74–75, 116, 120, 125, 143
- Frequency Plan, 20, 24, 76, 78, 108, 115, 126, 154, 283–284, 503
- Frequency planning, 18, 20, 22, 26, 71–78, 115–116, 124–126, 282–284, 302, 503
- Frequency Re-use, 71–72, 74, 144, 145
- Frequency Usage, 26, 112, 183, 419–420, 500

- Frequency-Division Multiple Access (FDMA), 2, 59, 500
- Frequency-Selective Fading, 261, 265, 423
- Fresnel zone, 245–246, 255, 264
- Frontal System, 263
- Front-to-Back ratio, 239
- FTP, 166, 180–181, 183
- Full-Rate (FR), 54, 60, 144, 399, 494

- Gain of the Antenna, 4, 29, 31–33, 36, 39, 40, 49, 234, 238–239, 249, 252, 504
- Gate Tunnelling Protocol (GTP), 35, 273, 277, 382, 384, 390–391, 401
- Gateway (GW), 348, 429
- Gateway GPRS Support Node (GGSN), 11, 273, 328–329, 332, 377–385, 391, 394–395, 399–400, 403, 413–414
- Gateway Mobile Switching Centre (GMSC), 5, 7, 330
- Gaussian Minimum Phase-Shift Keying (GMSK), 10, 163–168, 171–173, 175, 179
- G_b Interface, 377–378, 384, 391–392, 407
- G_b Link, 25, 35
- G_b NSVC CIR, 35
- G_d Interface, 407
- General Packet Radio Services (GPRS), 9, 10, 11, 22–23, 54–55, 57, 62–69, 78–80, 82–86, 174, 285–286, 327–331, 377–384, 390–392, 407
- Generic Flow Control (GFC), 227
- G_f Interface, 407
- G_i Interface, 381, 396, 402–403, 411
- G-Interfaces, 401–403
- Global System for Mobile Communication, 3
- GMSK Modulation, 164, 166
- G_n, 273, 381, 390, 394, 401–402
- G_n Interface, 381–382, 390, 401–402
- G_p Interface, 390–391
- GPRS and EGPRS Quality of Service, 67–69
- GPRS and EGPRS Rate Reduction, 67–68
- GPRS Attach Request, 78–80
- GPRS Coding Scheme Coverage, 23–24, 54–56, 68–69, 173, 174
- GPRS Detach Request, 78, 80, 82, 400
- GPRS Territory, 64–67, 79
- GPRS Throughput per Timeslot vs C/I, 66–67
- GPRS Tunnelling Protocol (GTP), 35, 273, 277, 382, 396
- GPRS/EGPRS Cell re-selection, 90–91
- G_r Interface, 381, 407
- G_s Interface, 371, 381
- GSN, 381, 382, 384, 390–391, 395
- GTP Signalling, 277
- GTPU, 273, 376, 390, 391, 401
- Guard Band, 250

- Half rate, 60, 143–144, 500
- Handover, 145–152, 154–159, 186, 274–275, 277–279, 303, 308, 418, 430, 433–434, 436, 470, 482, 485–487
- Handover algorithm, 147, 149
- Handover and adjacency difference, 168–169
- Handover causes, 147, 154
- Handover control, 20, 97, 133, 156, 157, 183, 430
- Handover distribution, 107, 133
- Handover failures, 154, 155
- Handover features, 149
- Handover parameters, 126, 149–150
- Handover performance, 145, 154
- Handover phases, 160
- Handover success rate, 22, 121, 132, 154, 368
- Hard handover, 97, 99–100
- Hardware configuration, 339
- Hardware monitoring, 160
- Header Error Control (HEC), 225, 228, 313
- High-Speed Circuit-Switched Data (HSCSD), 377
- Home Location Register (HLR), 5, 76, 318, 328–330, 333–335, 348, 352, 368, 371, 375, 377–378, 378–382, 395, 400, 403, 413
- HSN planning, 118
- Hyperframe, 60

- IDLE, 84, 85, 103, 166, 383
- Idle State, 84–85, 383
- IMEI, 5–6, 136, 376–377
- IMSI, 5–7, 85, 98, 106, 136, 322, 382–383, 400
- IMSI Analysis, 85, 96, 136, 327, 376, 383, 400
- IMSI Numbers, 318, 326–327
- IMT, 10–11, 417
- In Application Protocol (INAP), 330, 352–354, 397
- Incremental Redundancy (IR), 469, 471–472, 480
- Indoor coverage, 29, 48–49, 52, 108, 142, 479, 486
- Indoor Coverage, 142
- Information Theory, 28
- Intelligent Network, 317
- Interactive Class, 11, 12
- Interface Unit (IFU), 401
- Interfaces and Signalling in GSM, 22–23, 56, 59–60, 79, 133–135, 175, 327–328, 341
- Interference, 22, 31, 38, 69–76, 104, 113, 143, 147–148, 154, 187, 282–283

- Interference Degradation, 31–32, 48
- Interference Diversity, 116
- Interference Margin, 38–39, 69
- Interference Plans, 282–283
- Inter-Hop Interference, 282
- Inter-Mode Handover, 8
- International Telecommunication Union (ITU), 10, 11, 204
- Internet Protocol (IP), 367, 377–392, 394–403, 407, 412, 422, 427–433, 436, 445, 448, 465
- Inter-Switch Traffic, 318, 321, 324, 338, 367
- Intra-System Interference, 97, 101, 183
- IP Addressing, 295, 385–388, 399, 401, 411
- IP Routers, 395
- IP Routing, 331, 335, 351, 384, 388–389
- IP-BTS, 465
- ISDN (Integrated Services Digital Network), 6–8, 110, 134, 201, 205–206, 211, 217–220, 223, 224, 226, 233, 322, 326–329, 332, 335, 348, 356, 358, 429
- I_{ur} , 189, 267, 272–273, 275–277, 279–280
- IU (Indoor Unit), 236–237
- I_{ub} , 267, 272–276, 278–279, 295
- I_{u-cs} , 272–274, 276–280
- I_{u-ps} , 272–273, 276–278, 280, 295
- I_{ur} , 99–100, 272, 274, 276–277, 278, 280, 295
- IVR, 318

- Key Performance Indicators (KPIs), 20–21, 106, 127, 128, 131, 175, 309, 368, 405, 408, 439, 465
- Key Performance Indicators in WCDMA Network, 439
- k-factor*, 11, 243–244, 248, 253–254, 264
- k-Fading*, 253–254, 264
- Knife-Edge Diffraction, 254–255

- LAN, 378, 397, 401–402, 417–418, 425, 428–429, 433, 465, 485–486, 488, 492
- LAPD, 86, 134, 135, 140, 286
- Layer 1: Physical Layer, 88–89, 133–134, 135, 205, 217, 223–226, 272–273, 275, 293, 307, 309, 313–314, 345, 481, 487, 498
- Layer 2: Data Link Layer, 134, 217, 223–224, 491
- Layer 3 messages, 110, 170, 179
- Layer 3: Network Layer, 135–136, 319, 384, 427–428, 110, 170, 179
- Layer 4: Transport Layer, 136, 275, 293, 331, 335, 341, 351, 361, 432
- Layer 7: Application Layer, 169, 173, 293
- LCB, 289
- Legal Interception Gateway (LIG), 378
- Level, 18–21, 23, 29, 36, 40, 47, 53–54, 57–58, 63–66, 71, 73–77, 84–86, 91, 94, 101, 106, 108, 125, 128, 131–134, 140–154, 156–160, 163–164, 171–174, 200–202, 251–253, 283, 355, 397, 409–410, 418, 425–430, 432–433, 451–452, 461
- Line of Sight Survey, 246
- Linear Power Amplifier (PA), 166
- Line-of-Sight (LOS), 43, 246, 441
- Link (or Power) Budget, 32, 49, 504
- Link Adaptation, 171–175, 179, 471, 476, 480
- Link Budget, 162–163, 247, 253, 261, 254, 282–283, 302, 441, 472, 477, 504
- Link Budget Calculation, 29, 31, 34, 46, 54, 57, 247, 261, 264, 282–283, 302
- Link Performance, 70, 133, 163, 171, 266, 301
- Linking layer, 134–135
- LLC packet routing, 171
- LLC/GTP buffers, 35
- LMDS, 421
- Load Balancing, 399
- Load control, 29, 93, 103–104
- Load sharing, 143, 320, 366, 375, 395–397
- Loading Effect, 67
- Loading Factor, 396
- Location area planning, 121, 122, 126
- Location Probability, 17, 37, 47–50
- Location update, 7–8, 76–77, 103, 106, 121, 127, 133–134, 136–137, 140, 322, 371, 376–378
- Location-Based Services (LBS), 12
- Logical channels, 60, 80, 87–88, 133
- Logical Link Control (LLC), 35, 86, 169–173, 273
- Loop protection, 284
- Loop Topology, 281
- LOS (Line-of-Sight), 40, 41, 43, 44, 197, 246, 251, 430, 441
- Low-Noise Amplifiers (LNA), 237, 435

- Macro-Cells, 4, 23, 29, 43, 51, 61, 80, 150
- MAIO planning, 118
- Maximum Burst Size (MBS), 231, 233
- Maximum CTD (Maximum Cell Transfer Delay), 231, 233
- MCB, 289

- MC-CDMA, 421
- MCR (Minimum Cell Rate), 231
- MCS, 23, 25, 35, 36, 54, 68, 162, 163, 171–176, 269, 270, 271, 302
- Mean CTD (Mean Cell Transfer Delay), 231, 232, 233
- Mean Opinion Score (MOS), 106, 109, 144, 145
- Measurement Triggering, 98, 100, 101
- Media Gateway (MGW), 329–332
- Medium Access Control (MAC), 25, 87, 88, 173, 273, 401, 469–478, 474
- Microwave link, 234–237, 246, 249, 250, 253, 272, 300–302
- Microwave Link Performance, 301
- Microwave Link Planning, 234
- MIMO, 13, 420, 425, 426, 427, 467–475
- Minimum Cell Rate (MCR), 231
- Mixed Networks, 288
- MMS, 381, 408, 409
- Mobile allocation list (MAList), 106, 116–119
- Mobile Station (MS), 4, 6, 381, 496
- Mobile Switching Centre (MSC), 4, 5, 7, 33, 113, 126, 136, 138, 149, 152, 289, 328, 329, 330, 335, 348, 350, 352, 359, 367, 378, 397
- Mobile Terminal, 277, 413, 420, 429, 431, 433, 436, 484, 485, 486, 504
- Mobility, 23, 77, 80, 84, 85, 136, 145, 150, 154, 155, 274, 307, 329, 330, 335, 347, 349, 381, 392, 400, 405, 408, 412, 417, 428, 429, 430, 436, 437, 485, 486
- Mobility Management (MM), 84, 136, 400
- Modulation, 3, 10, 23, 24, 35, 54, 66, 171, 172, 173, 175, 199, 236, 282, 420, 423, 425, 468–477, 484, 485, 488, 489, 500
- Modulation and Coding Scheme, 23, 24, 163, 471
- Modulation Coding Scheme (MCS) distribution, 35, 54, 66, 171, 172
- Modulation Coding Scheme allocation, 35
- Modulation Types, 282
- MS Antenna Gain, 31, 33
- MS Sensitivity, 30
- Multi-BCF, 121, 155, 156, 269, 287, 292, 293
- Multi-Carrier Code-Division Duplex (MC-CDMA), 421
- Multiframe, 23, 25, 54, 60, 82, 83, 84, 109, 113, 163, 166, 169
- Multimode device, 421
- Multipath, 29, 40, 41, 44, 142, 234, 235, 239, 256, 261, 263, 265, 266, 268, 420, 424, 425, 426, 427, 477
- Multipath Propagation, 41, 44, 420, 425, 427, 477
- Multiple-Access Techniques, 11, 423
- Multiplexing, 134, 135, 199, 200–204, 206, 207, 213, 215, 216, 217, 218, 220, 223, 225, 230, 236, 309, 328, 423, 480, 490
- Multivendor interoperability, 161
- NBAP, 274, 275, 294, 304
- Neighbour Cells, 89, 93, 94, 155
- Neighbour list, 94, 98, 182, 183, 185
- NETACT Planner, 50
- Network Analysis, 375, 376, 378
- Network assessment, 128, 315, 316, 318, 319, 320, 323, 336, 339, 397
- Network Assisted Cell Change (NACC), 167, 169
- Network care activity, 159
- Network Coverage, 17, 50, 141, 403, 414, 419
- Network dimensioning, 19, 33, 48, 58, 64, 128, 315, 316, 317, 319, 322, 323, 336, 390, 391, 447
- Network elements restructuring, 121
- Network Interface Unit, 407, 410, 495
- Network layer, 135, 136, 319, 384, 427, 430, 432
- Network Management, 11, 221, 228
- Network Management Planning, 197
- Network Management System (NMS), 78, 106, 124, 128, 159, 291, 300, 301
- Network Optimisation, 20, 106
- Network Performance Monitoring, 377
- Network Switching Subsystem (NSS), 106, 113, 140, 155, 161
- Network Topology, 116, 205, 373, 406, 503
- Network-to-Network Interface (NNI), 227, 350, 401
- NMS maintenance, 161
- Node B Application Protocol (NBAC), 274, 275, 296, 304
- Nominal Planning, 19
- Non-Real-Time Variable Bit Rate (NRT-VBR), 231
- Nordic Mobile Telephone (NMT), 1, 2
- NRT, 37, 467
- nrt-VBR (Non-Real-Time Variable Bit Rate), 231
- NSS faults, 161
- NSS performance, 106, 113
- Octagonal Phase-Shift Keying (8-PSK), 10, 23, 35, 163, 167, 173, 179
- OFDM, 420, 423, 424
- Offline Observation, 110
- Okumara-Hata Model, 57

- OMC (operation & maintenance center), 5, 127, 140, 160
- One-phase access, 35, 174
- Optimisation, 17, 19, 20, 21, 106, 107, 110, 114, 115, 122, 125
- Orthogonal Signals, 423
- Orthogonal Variable Spreading Factor (OVSF), 27, 469
- OSI Reference Model, 223, 224
- Othogonality, 27, 420, 423
- Othogonality Factor, 38, 70, 105
- OU (Outdoor Unit), 237, 443
- Outage, 233, 260, 267, 406, 463
- Outer-Loop Power Control, 97, 102, 106
- Overheads, 212, 276, 277, 390, 391
- Overlay Network, 421
- Packet Access Grant Channel (PAGCH), 80
- Packet Associated Control Channel (PACCH), 163, 166
- Packet BCCH (PBCCH), 171
- Packet Call Quality, 179
- Packet Common Control Channel (PCCCCH), 80
- Packet Control Unit (PCU), 25, 286
- Packet Data Channel (PDCH), 23
- Packet data connection, 102
- Packet Data Scheduling, 26
- Packet Downlink/Uplink Ack/Nack (PDAN, PUAN), 180
- Packet Paging Channel (PPCH), 80
- Packet Random Access Channel (PRACH), 90, 94, 95
- Packet Scheduling Optimisation, 295, 471, 279
- Packet Switched (PS), 11, 96, 270, 276, 331, 377, 421
- Paging, 85, 88, 126
- Paging and Access Grant Channel (PAGCH), 80
- Paging procedure, 85, 96
- Parameter extraction, 159
- Parameter implementation, 140, 159
- Parameter management, 155
- Parameter Planning, 19, 20, 78
- Parameter Setting, 17, 20, 77, 78, 301
- Parameter Tuning, 146, 151
- Parameters, 6, 17–24, 29
- Path balance, 133, 141
- Path Loss, 30, 33, 40, 43, 44
- Path loss improvement, 141
- Payload Type (PT), 228, 231, 343
- PBGT, 147, 148
- PCH, 61, 84, 89, 96, 103
- PCM, 113, 200, 285, 299, 355
- PDCH Multiframe Structure, 163, 166
- PDCCP, 272, 273
- PDH (Plesiochronous Digital Hierarchy), 201–207, 217, 272, 288
- PDH Interface, 288, 293
- PDP Context, 85, 378, 382, 383, 384, 400, 407, 413
- Peak Cell Rate (PCR), 231, 232
- Peak-Hour Multiplier, 69, 405
- Peak-to-average, 166, 167
- Performance and Fault Management, 127, 160, 184, 457
- Performance Enhancing Proxy (PEP), 174
- Performance indicators, 20, 127, 128, 175, 187, 188, 368, 369
- Periodic Routing Area Update (PRAU), 175
- Periodicity, 149, 157
- Physical Channels, 60, 89, 96, 102, 470
- Physical Layer, 88, 133, 134, 223, 224, 225, 272, 309, 430
- Physical Medium (PM), 89, 224
- PICH, 89, 92, 96
- Pico-Cells, 29, 51
- Pilots Bits, 89, 91, 92
- PLMN selection, 91, 94
- Point-to-Point Topology, 280, 281
- Polarisation, 235, 236, 239, 282, 283
- Power Amplifier, 163
- Power Boosters, 31, 53, 142
- Power Budget, 28, 32, 148, 149, 504
- Power budget margin, 151
- Power control, 11, 38, 73, 90, 98, 101, 102, 146, 156
- Power Control Headroom, 38
- Power Control Parameter, 23, 156
- Primary Reference Clock (PRC), 289
- Priority and load, 158
- Probe, 410, 414
- Processing Gain, 28
- Propagation, 17, 20, 22, 29, 41, 43–48, 115, 304, 420, 425
- Propagation Model, 20, 22, 40, 41, 45, 48
- Propagation Over Vegetation, 253, 255
- Propagation Over Water, 262
- Protection, 23, 54, 144, 264, 342, 445
- Protocol analysers, 136, 140, 410
- Protocol Layer, 349, 393, 404
- Protocol Overhead, 276, 390, 391
- Protocol Stacks, 272, 341, 390
- Protocol trace, 136, 140

- PSK, 10, 23, 163, 166, 167, 470
- PSTN, 8, 330, 338, 360
- Public Land Mobile Network (PLMN), 5, 91, 376, 377, 381, 383, 403
- Puncturing, 472
- PVCs, 377

- QoS Class, 11
- QoSB, 431, 434
- Quadrature Phase-Shift Keying (QPSK), 468, 475
- Quality, 4, 12, 19–22
- Quality of Service (QoS), 11, 68, 104, 220, 412, 421, 428
- Quality Optimisation, 34
- Queuing, 50, 143, 222, 413

- RACH, 35, 61, 80, 83, 88, 90, 170, 182
- Radiation Night, 263
- Radio Access Network (RAN), 11, 275, 412, 462
- Radio channel allocation technics, 164
- Radio Link Control (RLC), 23, 163, 169, 174
- Radio Link Management (RLM), 110
- Radio Network Controller (RNC), 11, 37, 97, 98–101, 191, 275, 429
- Radio Network Optimisation, 106
- Radio Network Planning Process, 18, 504
- Radio Parameter, 115, 183
- Radio performance increase, 144
- Radio Refractivity, 243, 253
- Radio Resource Control (RRC), 11, 189, 429
- Radio Resource Management (RRM), 26, 29
- Radius of the Fresnel Zone, 245
- Rain Attenuation, 256
- RAKE Receivers, 29
- RANAP, 275, 349, 356, 361, 401
- Random Access Channel (RACH), 61, 80
- Random access procedure, 94, 95
- Rate Matching, 472
- Rayleigh Fading, 41, 172
- Real-Time Variable Bit Rate (RT-VBR), 231
- Receive Block Bitmap (RBB), 180
- Received Power, 38, 40, 249, 250
- Receiver Diversity, 426, 427
- Redundancy, 24, 162, 376, 396, 397
- Reflections, 41, 44, 45, 53, 297, 484
- Refractivity, 242, 243, 244, 253, 263
- Reliability, 123, 191, 221, 456
- Reports generation, 128
- Retainability, 178, 307, 308, 409
- Re-Transmissions, 173, 174, 308, 471, 472
- RLC Block Transmission, 25

- RNSAP, 275
- Round Trip Time (RTT), 468
- Routers, 386–387, 395, 403
- Routing, 4, 7, 80, 84, 86, 292, 320, 323, 358, 366, 376, 384, 390
- rt-VBR (Real-Time Variable Bit Rate), 231
- Rural, 2, 31, 48, 117

- SACCH Frame, 151
- Scattering, 40
- Scope of Radio Network Planning, 15, 18, 21, 107, 439, 503, 504
- SCR (Sustainable Cell Rate), 209, 231, 342
- Scrambling Codes, 27, 92, 186, 187
- SDCCH, 57, 59, 61, 110, 133, 138
- SDCCH drop, 107, 130, 133
- SDH (Synchronous Digital Hierarchy), 201, 203, 204, 224
- SDH Equipment Clock (SEC), 289
- SDH Interface, 205, 226
- SDH Network, 205–207, 288
- SECBR, 232
- Second-Generation, 2, 3, 5, 7, 9, 10
- Second-Generation System, 3, 10
- Security, 2, 3, 5, 8, 291, 410–411, 433, 436, 493, 494
- Security Management, 5, 291
- Segmentation and Reassembly (SAR), 173, 228–230, 345
- Servers, 334, 369, 410, 428
- Serving GPRS Support Node (SGSN), 11, 81, 84, 85, 328, 377, 378, 391–395, 400–408
- Serving RNC, 97, 100, 275, 276, 475
- Setup success, 18, 132, 175, 181, 188
- Severe Error Seconds (SES), 301
- Severely Errored Cell Block Ratio (SECBR), 232
- Shadowing, 41
- SHO process, 99
- Short Message Service Centre (SMSC), 326, 352
- Signaling Payload, 174
- Signalling Links (SL), 296, 304, 307, 353–356, 399, 407
- Signalling Network Dimensioning, 347
- Signalling Overhead, 173
- Signalling Plans, 399
- Signalling Point Codes (SPC), 295, 318, 323, 378
- Signalling Points (SP), 324, 346, 354, 355, 356, 378
- Signalling Transfer Point (STP), 331, 335, 376
- Signal-to-Interference Ratio (SIR), 90, 101, 102, 106

- SIM Card, 26, 136
- Site follow-up, 122
- Site re-engineering, 114, 115, 126, 160
- Site Selection, 440
- Site survey, 18
- Slave Clock – Synchronisation Supply Unit (SSU), 289
- Slow Associated Control Channels (SAACH), 34, 61, 133
- Slow Fading, 41, 47–49, 256
- Smart antenna, 143, 508
- Smart Radio Concept, 142
- Smooth-Sphere Diffraction, 254, 255
- SMS, 3, 4, 77, 82, 352, 408
- SMS establishment phases, 138
- Soft Capacity, 70
- Soft Handover (SHO), 97–102, 479
- Softer handover, 98
- Spatial Multiplexing, 426, 427
- Spectrum Efficiency, 73, 74, 494
- Spreading, 26–28, 95, 435
- Spreading and De-spreading, 27, 435
- SRNC, 100, 276, 475
- SS7, 134, 285, 321, 347, 352, 355, 356, 401
- STANDBY, 85, 385, 395
- Statistics, 106, 107, 121, 124, 127, 128, 154, 371
- Statistics' extraction, 127, 128
- STM (Synchronous Transport Module), 207, 216
- Streaming Class, 11, 12
- Sub-Destination, 316, 366, 375, 378
- Subscriber Identity Module (SIM), 5, 6
- Subsidence, 263
- Suburban, 29, 30, 48, 57, 405
- Superframe, 60
- Sustainable Cell Rate (SCR), 231
- Switches, 319–321, 401
- Switching, 2, 4, 7, 11, 22, 219, 222, 320, 377, 397
- Switching and Multiplexing, 217
- Symbols, 29, 90, 165, 425, 489
- Synchronisation, 5, 61, 89, 91, 92, 162, 201, 225, 288, 289, 370, 375
- Synchronisation Channel (SCH), 61
- Synchronisation Planning, 288, 289, 323, 324, 370
- Synthesised frequency hopping, 116, 120, 125
- System information, 61, 86–88, 92–94, 171
- System Information Messages, 170, 171, 180
- T1, 35, 201, 393, 394
- Target cell evaluation, 148
- TBF, 35, 66, 172–175, 177–181
- TBF Blocking, 174, 175, 179, 180
- TBF Performance, 157, 180
- TBF Release Delay, 35, 174, 179
- TCH and SDCCH availability, 132
- TCH strategy, 117
- TDD, 11, 97
- Technical automation, 122, 124
- Temporary Block Flow (TBF), 35, 66, 173, 175, 177, 178, 179, 181
- TETRA, 493–506
- The A Interface, 328, 329, 349, 384
- The I_u Interface, 273, 276, 328, 329, 333
- The I_{ub} Interface, 273, 274, 276, 279, 471, 474
- The I_{ur} Interface, 100, 274, 277
- Third-Generation, 10, 11, 13, 485
- Third-Generation Networks, 1
- Thresholds, 21, 35, 48, 104, 157
- Time Slots (TS), 9, 23, 24, 35, 60, 63, 65–67, 78, 79, 163, 269–271, 355, 384, 500
- Time-Division Multiple Access (TDMA), 3, 10, 25, 54, 59, 60, 73, 74, 115, 134
- Timeslot allocation, 286
- Time-Slot Allocation Planning, 286
- Timing advance, 77, 107, 114, 133
- Topology, 22, 116, 152, 155, 280, 281, 340, 351, 364, 373, 402, 406, 503
- Tracing, 44, 43, 106, 110, 407, 409
- Traffic, 4, 5, 9, 11, 26, 33, 34, 37, 58, 59, 60, 62–67, 69, 70, 107, 113, 121, 126, 133, 149, 227, 231, 269, 276, 278, 317–321, 337–341, 346, 369, 370, 375, 391–401, 406–415, 422, 499
- Traffic Calculation, 33
- Traffic Channels (TCH), 54, 60, 61, 74, 76, 116, 134, 137, 269
- Traffic Distribution, 114, 319, 321, 476
- Traffic Estimates, 58, 402
- Traffic Management, 23, 143, 397
- Traffic Mix, 306, 413, 476
- Traffic Parameters, 227, 233
- Traffic Routing Tool, 323, 338, 370, 375, 398
- Transceiver (TRX), 19, 20, 33, 59, 74–76, 107, 113, 116, 118, 133, 142, 163
- Transceiver Signalling (TRXSIG), 287
- Transcoder Sub-Multiplexers (TSCM), 269
- Transit Layer, 321 324, 330, 340
- Transit Switch, 320
- Transmission, 1–3, 11, 19, 25, 26, 29, 31, 35, 53, 54, 62, 66, 67, 73, 74, 77, 88–91, 94, 96–98, 101, 102, 104, 113, 161, 199, 204, 219, 224–226, 296

- Transmission Convergence (TC), 224
- Transmission Network, 19, 113, 161, 189, 195, 307, 308
- Transmission network auditing, 106, 113
- Transmission Network Optimisation, 296, 299
- Transmission Network Planning Process, 197, 198
- Transmission Unit (TRU), 293
- Transport channels, 88, 89, 102, 471
- Transport Control Protocol (TCP), 351, 353, 295, 471, 474
- TRAU, 286
- Triggering, 98–101, 130, 131
- Troubleshooting follow-up, 122, 124
- TRX quality, 107, 133

- UBR (Unspecified Bit Rate), 231
- Umbrella, 4, 116, 147, 148, 149, 157
- Umbrella level, 151
- Unspecified Bit Rate (UBR), 231, 294
- Uplink and downlink power control, 143, 156
- Urban, 2, 17, 21, 39, 31, 40, 41, 42, 44, 46, 48, 50, 107, 115, 116, 117, 143, 274, 275, 405, 441, 443
- User Data Protocol (UDP), 272, 273, 277, 343, 344, 345, 351, 390, 391
- User Equipment (UE), 11, 37, 39, 88, 89, 91, 92, 93, 96, 97, 100, 186, 400, 403, 471, 472, 473, 475, 476, 480, 481
- User-to-Network Interface (UNI), 227
- USIM, 11, 494
- Utilisation, 270, 271, 368, 371, 389, 422, 478
- UTRAN, 11, 93, 96, 276, 329, 333, 349

- Value Added Services (VAS), 317, 398
- VC (Virtual Container), 205, 207, 212, 213
- VCC (Virtual Channel Connection), 220, 221, 222, 226, 228, 231
- VCI, 221, 226, 227, 228, 294, 295, 355
- Video Call Quality, 16
- Virtual Channel (VCI), 220, 221, 226, 227, 228, 294, 295, 355
- Virtual Channel link, 226
- Virtual Path (VPI), 226, 227, 228, 294, 295, 355
- Virtual Path link, 226
- Visitor Location Register (VLR), 5, 11, 76, 328
- Voice Activity Factor (VAF), 278, 279
- Voice Call Quality, 62, 132, 355, 346, 399, 478
- Voice Mail System (VMS), 318
- Voice-Activity Detection, 74, 399
- VP, 220, 226, 227, 294
- VPC (Virtual Path Connection), 220, 221, 222, 226
- VPI (Virtual Path Identifier), 226, 227, 228, 294, 295, 355

- Walfish-Ikegami Model, 40, 43, 44, 57
- WAN, 205, 399, 402, 427
- WAP, 381
- Wave Propagation, 29, 40–45, 247, 253–267
- WCDMA, 12, 26, 28–29, 34, 38–39, 57, 69–70, 72, 89, 92–93, 97, 101, 181, 183, 184, 272, 273, 274, 329, 332, 467
- WCDMA carrier, 26
- WCDMA Technology, 57
- Wideband CDMA Mobile Switching Centre (WMSC), 350
- Wireless Local-Area Network (WLAN), 333, 417, 418, 425, 485, 486, 492