

Index

- Absorber
 - SAW accelerometer, 89, 334
 - X-ray lithography, 277
 - Vibration, 13, 82, 243
- Accelerometer
 - Absorbers, 89, 334
 - Applications of, 14, 15
 - integrated with CMOS, 308
 - with movable gate FET, 54
 - with SAW IDT
 - combined with gyroscope, 372
 - design, 88
 - fabrication, 333
- Acoustic
 - admittance, 98
 - aperture, 338
 - emission sensor, 371
 - impedance, 86, 332
 - comparison of properties, 86
 - PVDF, 60
 - sensor, 57, 86
 - wave, 57, 97
 - Lamb wave, 326
 - Love wave, 57
 - sensor, 371
- Active control, 212
 - Composite Beam, 248
- Active damping, 11
- Actuation law, 114, 187
- actuator dynamics
 - Cantilever beam, 251
- Actuator (*see also* Transducers)
 - applications of, 14, 15
 - collocated with sensors, delamination, 356
 - Comparison of schemes, 83
 - Control strategies, 247
 - definition of, 6
 - in microfluidic systems, 100
 - in smart systems, 7
 - magnetostrictive
 - cantilever with, modeling of, 211
 - noise control in helicopter, 386
 - spectral element model of beam with, 213
 - piezoelectric
 - modeling of, 188, 189
 - vibration control with, 378
 - piezofiber composite
 - modeling of, 212
 - spectral element model of beam with, 213
 - polymers for, 27
 - PZT mounted beam, modeling of, 203
- Adaptive
 - control, 387
 - filter, 248
 - structures, 216
 - definition, 4
- Adhesion
 - of sputtered thin films, 21
 - comparison of curing schemes, 33
 - properties of polymers, 282
- AMANDA process, 302
- Amorphous thin film, 49
- Amplifier
 - charge preamplifier, in piezoelectric sensor, 86
 - differential, in resonant sensor, 53
 - high isolation, in wireless telemetry, 368
 - MOSFET, in PVDF hydrophone, 87
 - power amplifier, in structural health monitoring, 351
- Analogies, 64
- Anisotropic composite beam, wave equation for, 135
- Anisotropic
 - etchants, 260, 269
 - etching, 261, 271, 317
 - nature
 - composites, 118
 - piezoelectric substrate, 58, 73
- Annealing
 - after direct bonding, 262
 - for ion implantation, 271
 - interfacial stress, 314, 322

- Annealing (*continued*)
 - rapid thermal, for stress relief, 308, 337
 - solgel deposited films, 25
 - sputtered films, 25
- Anodic bonding, 262
 - comparison with other schemes, 321
 - piezoresistive sensors, 50
- Anodization, pulse potential, 270
- APCVD (atmospheric pressure chemical vapor deposition), 266
- Area coordinates, 161
- Array
 - of reflectors in SAW, 89, 334–336
 - ball-grid, 316
 - micro-mirror, 317
 - of perturbation mass, 372
 - of reaction chamber, 243
 - of electrodes, 216
 - of optical fibers, 286
- Assay buffer, 344
- Axisymmetric model, 213

- ball-grid array, 316
- bar element, Quadratic, 169, 170
- Beam
 - element, FEM, 160
 - exact solution, 160
 - piezofiber composite Actuator, spectral element model, 213
 - spectral element model piezofiber composite Actuator, 213
 - as flexural waveguide, 134
 - bending modes, 203, 378
 - composite, 135, 140, 195
 - active control of, 248
 - PFC, 252
 - piezoelectric bimorph, 195
 - smart, 195, 196, 350
 - Spectral element modeling, 215
 - Terfenol-D, 210
 - Euler–Bernoulli model, 215, 222
 - isotropic, wave propagation in, 139
 - laminated composite, wave equations for, 135
 - modeling of, PZT Actuator, 203
 - dispersion relation, 142
 - spectrum relation, 142
- Bending
 - mode wave, 144, 383
 - moment, 215
 - rigidity, 152
 - stiffness, 128
 - bimorph beam, 195
 - modes in a beam, 203, 378
- bimorph beam, 195
 - Bending, 195
 - electrothermal, 80
 - magnetostrictive, 211
 - piezoelectric composite, 195, 378
 - PVDF, 196, 202
 - bimorph plate, 188
- Biomimetic materials, 5
- Bonding layer, 217
- Bonding, flip chip, 315
 - hermetic, 317
- Boundary conditions, 91, 118, 149, 152
 - in beams, 153, 252
 - in coupled analysis, 210
 - in FEM, 193, 199
 - in spectral element modeling, 215
- Bragg grating, 52

- Cantilever beam, 202, 211
 - distributed actuator, dynamics, 251
 - dynamics, 244
- Cantilever rod, 181
- Cantilever, carbon nanotube, 228
- Capacitance
 - analytical model of sensor, 216
 - deflected diaphragm, 46
 - gate, 55
 - in electromechanical analogies, 64
 - PZT, 218
- carbon nanotube
 - composites, 35, 60
 - Electrical Conductivity, 38
- Carrier mobility, 55, 88
- Carrier signal, 370
- ceramic, Composites, 23
- Ceramics, Deposition, 22, 268
- Channel, current density, 54
- Charge preamplifier, in piezoelectric sensor, 86
- Charge
 - electromechanical analogy, 64
 - generated in electrostrictive, 76
 - generated in piezoelectric, 48, 73, 85, 97, 360
 - stored in electrostatic actuator, 65
 - in polymerization, 29, 30
- Classical finite difference technique, 150
- closed loop control, 10, 232, 384
- CNT sensor, CV diagrams, 341
- CNT, UV curable polymer composite, 39
- comparison
 - bonding schemes, 321
 - actuation schemes, 83
- Compliance, 63, 64
- Composite Beam, 135, 140, 195
 - active control of, 248
 - active control, 248
 - laminated, 135, 140, 353
- composite
 - smart beam, 195, 196, 350
 - laminated, 120
 - metal/polymer, 300
 - piezoelectric, 191

- piezofiber, 212
- sensors, modeling, 212
- smart structure, 188, 192, 205
- anisotropic nature, 118
- carbon nanotube, 35, 60
- ceramic, 23
- structural health monitoring, 349
- Conductivity, Electrical, 18
 - Electrical, of carbon nanotube, 38
- Conductivity, in liquid sensing, 99
- Conductivity, thermal, 18
- Control of cracks, open loop, 364
- Control strategies, actuator, 247
 - vibration control, 247
- Control variable, 231
- Control
 - Vibration with Piezoelectric actuator, 378
 - closed loop, 10, 232, 384
 - open loop, 9, 194, 232, 384
 - open loop, cracks, 364
 - active, 212
 - Adaptive, 387
- Controllability, 238, 247
- Coriolis force, in SAW sensor, 373
- coupled analysis, Boundary conditions, 210
- Crack detection, 216, 273, 326, 349, 370
- Crack formation, in packages, 315
- Crack formation, in structures, 321, 362
- Crystal cut, piezoelectric, 57, 85, 367
- Crystal growth, silicon, 19, 260
- Crystal orientation, 20, 260, 271
- Crystal structure, 18, 81
- Current density, effect on electrodeposition, 296
- Current
 - CV diagrams of CNT sensor, 341
 - drain current in FET, 55, 87
 - electromechanical analogy, 64
 - in electromagnetic actuator, 69
 - in electrostatic actuator, 67
 - in electrostrictive actuator, 76
- CVD, 21, 39, 264, 332
 - of dielectrics, 266
- Damping
 - force, 157, 163, 231, 377
 - matrix, 159, 164, 168, 171, 234, 242
- Data acquisition system, 327
- Data fusion, 374
- Delamination, actuator, collocated with sensors, 356
- Demolding, 297
- Deposition, 21
 - of ceramics, 22, 268
 - of metal, 20, 264
 - of polymer thin films, 35, 59
 - of Silicon, 263
 - Electrochemical, 299
 - Polysilicon, 268, 273
 - Pulse laser, 35
 - Silicon dioxide, 272, 273
 - Silicon nitride, 331
 - Sol-gel, 22, 25
 - Thick film, 23
 - Thin film, 22, 25, 263
- Diaphragm, 26, 46, 80, 101, 317
 - capacitance, 46
 - micro valve, 100
- Dielectric polarization, 74
- Dielectrics, CVD, 266
- Differential Amplifier, in resonant sensor, 53
- Dipole moment, 48, 59, 73
- Direct bonding, Annealing in, 262
- Direct electromechanical analogies, 64
- Dispersion angle, 327
- Dispersion relation, 129, 135, 182, 326, 369
 - For beams, 142
- Divergence theorem, 113, 155
- Dopant selective etching, 260
- Double cantilever beam, 361
- Drain current in FET, 55, 87
- DRIE (deep reactive ion etching), 260
- Dry etching, 260
- Effective
 - mass, 77
 - stress, 217
- Eigen structure, 240, 381, 383
- Elastic
 - constant, 48, 58, 75, 115, 124
 - waves, 57
- Electrical conductivity, 18
- Electrochemical deposition, 299
- Electrochemical
 - etching, 269
 - fabrication, 296
 - polymerization, 27, 282, 340
- Electrodeposition, 296
- Electrodynamical transducer, 70
- Electromagnetic transducer, 68
- Electromechanical analogies, 64
- Electromechanical coupling coefficient, 99, 338
- Electroplating, 21
- Electrostatic transducer, 64
- Electrostrictive transducer, 74
- Electrothermal actuator, 80
- Emission sensor, acoustic, 371
- Epitaxial deposition, 20
- Etch stop, 19, 260, 269, 270
 - Electrochemical, 269
 - Polycrystalline, 269
- Etchant, 260, 269
 - anisotropic, 260, 269
 - Anisotropic, properties, 269

- Etching, 254, 263
 - Anisotropic, 260, 261
- Eulerian
 - coordinates, 106
 - strain tensor, 108
- Eutectic bonding, 317, 318
- Evaporation, 21, 264
 - Metal, 21, 264, 289, 335
- Exact solution, 151, 160, 183
- Excimer laser, 290, 294

- Feedback
 - control, 232, 239, 248, 365, 380
 - gain, 251, 388
 - sensor, 250, 391
 - System, Block Diagram, 248, 327, 343, 378
- FEM, 115, 128, 145–185, 234
 - Superconvergent formulation, 147, 178, 380
- fiber optic gyro
 - Open loop configuration, 93
- Field Strength, 74, 78
- Finite Difference Method, 2
- Flexural Plate Waves, 57, 97
- Flexural waveguide with beam, 134
- Flip chip, bonding, 315
- Force balance, 65
- Force method, 145
- Force –Piezoelectric, 9
- Fourier Transform, 129, 182, 233, 243
- Friction, 36, 171, 371

- Gas damping, 53
- Gate capacitance, 55
- Hamilton principle, 135, 156, 192
- Helicopter noise control. Magnetostrictive actuator, 386
- Hermetic bonding, 317, 320
- Hermetic package, 312
- High aspect ratio
 - micro-fabrications, 288
 - micromachining, 301
 - microstructures, 8, 26, 257, 284, 290
- high isolation amplifier, in wireless telemetry, 368
- Hookean elastic solid, 114
- Hooke's law, 114
- Hot embossing, 289
- Hybrid processing, 8
- Hybrid technology, 366
- hydrophone, MOSFET Amplifier in, 87

- IDT accelerometer, 332, 372
- IDT accelerometer, 372
- Impact damage, 366, 370
- induced Strain, 12, 96, 195, 352
- Inductor, moving coil, 68
- Inertial
 - constants, 136, 202
 - coupling, 136
 - force, 55, 148, 242
 - frame of reference, 92
 - loading, 371
 - navigation system, 366, 372
 - sensors, 46, 321
 - space, 92
- injection molding, Polycarbonate (PC), 291
- Interconnect, 308
- Interdigital transducers, 51, 326, 365
- interfacial stress, effect of annealing, 314, 322
- Inverse Transform, 131
- Ion implantation, Annealing for, 271
- Isoparametric elements, 167
- Isotropic
 - plasma etching, 26
 - solids, 118, 119
 - waveguide, 136
 - wet etching, 260

- Jacobian, 107, 165, 166, 170, 193
 - matrix, 167
 - transformation, 193
- J-integral, 360

- Lagrange equation, 158
- Lagrangian
 - coordinates, 109
 - strain tensor, 108
 - variable, 106
- Lamb wave, 326
- laminated, Composite beam, 135, 140, 353
- Lamination, Classical theory, 126
- Laser ablation, 25, 268, 290, 309, 317
- Laser and electrochemical etching, 26
- Laser, excimer, 290, 294
- Laser-Doppler effect, 51
- Lift off technique, 259
- LIGA, process, 8, 257, 269, 274
- linear time-invariant System, 240
- Liquid crystal display, 288
- liquid sensing, by Conductivity, 99
- Lithography, 257
 - masks in, 258
- Love wave, 57
 - sensor, 371
- Low pressure chemical vapor deposition (LPCVD), 266, 272, 321
- Lumped-element model
 - accelerometer, 88
 - for pressure sensor, 46

- Magneto-optic effect, 51
- Magnetostrictive actuator, 49, 78, 349
 - modeling of, 204
 - Structural health monitoring with, 349

- Metal
 - Deposition, 20, 264
 - evaporation of, 21, 264, 289, 335
 - sputtering of, 21
- metal/polymer composite, 300
- Metallo organic chemical vapor deposition (MOCVD), 21, 265
- Micro-channel, 344
- Microfabrication, electroplating, 21
- Microfluidic system, 342
 - Actuation, 100
- Micromachining
 - demolding in, 297
 - Micromolding, 289
 - in capillaries (MIMIC), 292
- micro-mirror array, 317
- Micro-nozzles, 29
- Micro-transfer molding, 291
- Minority carrier lifetime, 19
- Mobility analogies, 64
- MOCVD, 265
- model, axisymmetric, 213
- Modeling of
 - carbon nanotubes, 35, 219, 340
 - magnetostrictive actuator, 204
 - piezofiber composite Actuator, 212
 - PZT mounted beam actuator, 203
 - piezoelectric actuator, 188, 189
 - cantilever with Magnetostrictive actuator, 211
 - Composite, sensors, 212
- Molding, Micro-transfer, 291
- Molecular beam epitaxy (MBE), 20
- Monolayers, self assembled, 223
- MOSFET Amplifier, in PVDF hydrophone, 87
- Movable gate FET, Accelerometer, 54
- Multichip modules (MCMs), 311
- multilayer packages, 315

- Nanocomposite, 39, 221
- n-channel MOSFET 55, 86, 328
- Negative resists, 258
- Nickel electroplating, 296

- Open loop, fiber optic gyro, 93
- open loop Control, 9, 194, 232, 384
- Operational amplifier, 54, 86
- optical fiber array, 286
- Optical, glucose sensors, 340
- Optimum damping, 82, 233
- Organic materials
 - deposition methods for, 59, 266
 - nonstandard, 21, 264
 - patterning of, 31, 257, 259, 297, 330, 335
 - Organic thin films, 35, 59
- Oxidation, 265
 - processes, 266

- Packaging, 307–322
- Passivation, 50, 321, 332
 - electrochemical, 269
 - PCR, 240
 - PDMS, 37, 289, 292
- Passive valve, 100
- PDMS (polydimethylsiloxane) process
 - critical dimensions in, 260
 - line width in, 258, 287, 295
 - profiles in, 37
 - reactors for, 343
 - Passivation, 37, 289, 292
- Permalloy
 - electroplating of, 21, 282, 290, 296–298, 300
 - Permanent magnets, 22
- perturbation mass, 372
- PFC Beam, 252
- Phase modulation, 93
- Phospho silicate, 274, 307, 318
- Phosphosilicate glass thin films, 274, 307
- Photo electrochemical (PEC) etching, 8
- Photoforming process, 9, 293
- Photolithography, 14, 287, 289
- Photoresist, 258
 - as masking layer for implant, 272
 - deposition of, 31, 290, 335
 - spin casting of, 332
 - SU-8, 263, 332, 342
 - electron-beam, 258
 - negative, 258
 - patterning, 31
 - positive, 258, 331
 - removal of, 297
- Physical vapor deposition, 21, 264
- PID control, 239, 240
- Piezoelectric actuator, 364
 - modeling of, 188, 189
 - vibration control with, 378
 - bimorph, 195
 - bimorph, composite, Beam, 195
- Piezoelectric coefficient, 85, 187
- Piezoelectric composite, 191
- Piezoelectric effect, 12, 333
- Piezoelectric material, 4, 11, 48, 57, 77, 89, 187, 249, 338
- Piezoelectric
 - sensor, charge preamplifier, in, 86
 - substrate, anisotropic nature, 58, 73
 - transducer, 73
 - Crystal cut, 57, 85, 367
- Piezoelectricity, 12, 48, 59, 195
- Piezofiber composite Actuator
 - modeling of, 212
 - spectral element model of beam with, 213
- Piezoresistive pressure sensor, 94, 267
- Piezoresistive sensors, anodic bonding, 50
- Planarization, 298, 308

- Plane stress, 120, 127, 136, 189, 359
- Plasma enhanced chemical vapor deposition (PECVD), 272, 332, 336
- Plasma etching, 26, 260, 269, 272
- Plasma
 - in dry etching processes, 260
 - reactors for, 265, 272, 274
 - as etchants, 26, 260, 269, 272, 289, 321
 - etch rates, 260, 269
 - in deposition techniques, 263, 266, 332
 - ionization of, 260
- Plastics
 - PMMA (poly(methylmethacrylate)), 18, 277, 343
 - Polycarbonate (PC), in injection molding, 291
 - PDMS process in x-ray lithography, 275
 - Polyethylene (PE), in injection molding, 289, 291
- PMMA (poly(methylmethacrylate)), 18, 277, 343
- Point load, 178, 179, 192
- Poisson equation, 118
- Polarization, dielectric, 74
- Polycarbonate (PC), in injection molding, 291
- Polycrystalline silicon, 8, 273
 - as etch mask for KOH, 260
 - as etch stop, 269
 - as masking layer for implant, 317
 - CVD of, 273
 - etch rate in KOH, 269
 - mechanical properties of, 19
- PDMS process in x-ray lithography, 275
- Polyimide, 60
- polymer thin films, Deposition, 35, 59
- polymerization, Electrochemical, 27, 282, 340
- Polymers
 - actuator for, 27
 - Polyoxymethylene (paM) resist, 291
 - properties, 282
- Polysilicon, 50, 54, 62, 80, 89, 263, 266, 268, 272, 273, 274
 - deposition, 268, 273
- Polystyrene, 36
- Polyvinylidene, 86, 102
- Positive Photoresist, 258, 331
- power amplifier, in structural health monitoring, 351
- Principle of Potential energy, 154
- Principle of Virtual Work, 115, 147, 254
- Projection operator, 244
- Projection, 8, 112, 284, 285
- Proof mass, 53, 54
- properties of polymers, 282
- Proportional damping, 159
- Proportional, 296, 336
- Protein synthesis, 343, 344
- Proximity printing, 275
- Pulse laser deposition, 35
- pulse potential anodization, 270
- PVC, 2, 36, 340
- PVD, 21, 264, 302
- Pyrex, 50
- PZT mounted beam actuator, modeling of, 203
- PZT, Capacitance, 218
- Q_matrix, 126
- Quadratic bar element, 169, 170
- Quadratic functional, 152
- Quadratic rod element, 165
- Quadrature, 166, 179
- Quantum-well spectrum, 51
- Quartzite, 19
- Radial-flow, 266
- Radiation, 24, 29
- Radical-generating photoinitiator, 33
- Rain monitors, 14
- Rapid thermal annealing (RTA), 307
- Rare earth elements, 5
- Rate of formation, 33
- Reaction chamber, 243
- Rectangular element, FEM, 160
- Rectangular grid, 106
- Refractive index, 92
- Refractory material, 21
- Residual stress, 51, 91, 273, 360
- Resistance change, 50, 95
- Resistive heating, 82
- Resonant frequency, 100, 233, 320
- resonant sensor, differential amplifier in, 53
- Resonator, 14, 53, 68, 323, 367
- Rod element, FEM, 160
- rod, cantilever, 181
- Root locus, 237, 238, 239, 248, 391
- Rotation rate, 14, 15, 52, 92
- Rotational Inertia, 140, 215
- Sacrificial layer, 26, 271–277
- Sagnac effect, 51, 92
- SAW accelerometer, 332, 372
 - combined with gyroscope, 372
 - design, 88
 - fabrication, 333
- SCREAM, 26, 269, 271
- Screen printing, 314
- Second-order system, 135, 161, 232, 237
- Self assembled monolayer, 223
- Sensitivity analysis, 369
- Shape memory alloy (SMA), 3, 5, 22, 81
- Shape memory alloy (SMA), in thermal actuators, 81
- Shape memory, applications of, 14
- Shape memory, effect, 81
- Shape memory, phase transformation, 3, 81
- Shape memory, stress-induced martensite, 81
- Shell
 - CNT, 38, 221
 - finite element, 203

- thermal, 313
- Shipley, 331, 335
- Silica, 27, 52
- Silicon dioxide, 260, 271, 313, 334, 373
 - deposition, 272, 273
- Silicon
 - growth, 19–20
 - hardness, 19
 - in micromachining, 110–111
 - nitride deposition, 331
 - [100] orientation, 19, 261, 269
 - [110] orientation, 261, 269
 - crystalline, 8, 19, 26, 257, 269
 - deep reactive ion etching, 260
 - deposition and etching of, 263
 - lattice planes in, 296
 - mechanical properties of, 17, 19, 21, 33
 - orientation of, 19, 261, 269
 - oxidation of, 265
 - physical/chemical etching, 260, 269, 271
 - piezoresistivity, 50
 - residual stress, 51, 91, 273
 - resists in, 258
 - Single crystal silicon, 268, 271
 - Wet etching, 260
 - silicon-on-insulator, 262, 318
- Single crystal silicon, 268, 271
- slotted-quartz, 256, 266
- SMA, Crystal structure, 81
- Smart composite beam, 195, 196, 350
- smart structure, Composite, 188, 192, 205
- Smart systems, Actuator, 7
- sol-gel deposited films, Annealing, 25
- Sol-gel deposition, 22, 25
- Space-charge density, 87
- Sparse matrix, 173
- Spectral element model of beam
 - with piezofiber composite Actuator, 213
 - with magnetostrictive actuator, 213
 - Boundary conditions, 215
 - composite beam, 215
- Spectrum relation, 129, 135, 139
- spin casting, 332
- Spring-mass-damper system, 233, 236
- sputtered films, Annealing, 25
- sputtered thin films, Adhesion of, 21
- Sputtering, Metal, 21
- Stability analysis, 239
- State equations, 234, 236
- State variables, 65, 71, 76, 81, 234
- Stiction, 313
- Stiffness coefficients, 124, 137, 183, 199, 252
- stiffness, bending, 128
- Strain energy, 135, 147, 162, 197
- Stress gradient, 164
- stress relief, by rapid thermal annealing, 308, 337
- Stress
 - normal, 112
 - principal, 111
 - residual, 51, 91, 273
- Stress-induced martensite, 81
- Structural health monitoring
 - with Magnetostrictive transducer, 349
 - power amplifier in, 351
- Structure, modeling of, for control, 189, 248
- SU-8
 - resist, 263, 332, 342
 - Spin casting, 332
- Surface micromachining, 8, 26, 271–275
- Surface tension, 273, 335
- Synchrotron radiation, 275
- System architecture, 8
- System, linear time-invariant, 240
- System, linear, 232, 237
- Terfenol-D, composite, 210
- Thermal annealing, 262, 314
- Thermal
 - Conductivity, 18
 - evaporation, 318
- Thermal expansion coefficient, 51, 80, 82, 314, 316
- Thermal stress, 314
- Thick film deposition, 23
- Thick films, 23
- Thin film deposition, 22, 25, 263
- Thin film multilayer packages, 315
- Thin film sensors, 216
- thin films, sputtering, adhesion of, 21
- Transconductance, 87, 328
- Transducer
 - comb type electrostatic, 68
 - Electrodynamic, 70
 - Electromagnetic, 68
 - electrostatic, 64
 - Electrostrictive, 74
 - Electrothermal, 80
 - Magnetostrictive, 74
 - Structural health monitoring with, 349
 - piezoelectric, 73
- Transduction factor, 67, 72, 76, 80
- transition temperatures, 77, 291
- Triangular element, FEM, 160, 161
- Tuned system, 286
- Tungsten, 21, 264, 273, 307
- Ultrasonic actuators, 15
- Ultrasonic energy, 312
- Ultrasonic NDT techniques, 325, 348
- Ultrasonic probe, 39
- Ultrasonic transducer, 7, 73, 325, 326
- Ultrasonic wire bonding, 313
- Ultrasonicated, 340, 341

- Ultraviolet irradiation, 27, 282
- Ultraviolet light, 31
- Undercut etching of channels, 274
- Undercut of the mask, 272
- Unit feed back, 239
- Unit gate area, 55
- Unmanned carriage system, 13
- Unstable system, 237, 239
- UV curable polymers, 8, 27, 263, 281
- UV curable polymers, with CNT, 39
- UV, 258, 291

- Vacuum Pressure reservoir, 21, 24, 50, 264
- Valence band, 18, 38
- Vapor phase etching, 310
- Variational methods, 145
- Velocity feedback, 251, 394
- Velocity of sound, 57, 67, 89
- Very low pressure chemical vapor deposition (VLPCVD), 265
- Vibration absorber, 13, 82, 243

- Virtual work, 114, 154
- Viscoelasticity, 105

- Wafer bonding, 261, 317–320, 335
- wave equation for
 - anisotropic composite beam, 135
 - laminated composite beam, 135
- wave propagation in
 - composite beam, 143
 - isotropic beam, 139
- Wet bench, 3, 35
- Wet chemical etchant, 271
- Wet etching, 50, 260, 269, 310, 317
- Wet oxidation, 329
- Wetting action, 316
- Wheatstone bridge, 45, 50, 95
- Wire bonding, 310
- Work, virtual, 114, 154

- x-ray lithography, 275