

---

# INDEX

---

- A-scan, 482  
Acoustic emission, 483  
Aelotropic material, 175  
Anisotropic material, 175  
Anisotropy, 3  
    controlled, 10, 11  
    of thermal expansion, 111  
Aramid fibers, *see* Kevlar  
Autoclave, 46, 47, 48  
Average fiber stress, 139–140  
Average stress criterion, 349  
Axes of symmetry, 63, 160
- B-scan, 482  
Bag molding, 46–48  
    pressure, 46, 47  
    processes, 46–48  
    vacuum, 46, 47  
Bagging, 46  
Balanced orthotropic lamina, 172  
Bending  
    of beams, 315  
    of general laminates, 294  
    of plates, 288  
Biocomposites, 499–503  
Bio fibers, 499–501  
Bio product, 499  
Bonded-fastened joints, 361  
Bonding mechanisms, 355–356  
Boron fibers, 27–28  
    by CVD, 27  
    properties of, 28  
Boundary-layer phenomenon, 328  
Buckling, 296  
    load, 296  
    critical, 298  
    mode, 296  
    of plates, 295  
    of square plate, 300  
Burn off method, 441
- C-scan, 483  
Carbon black, 6  
Carbon-carbon composites, 498–499
- Carbon fibers, 23–26 *also see* graphite fibers  
    carbon yield, 24  
    form of, 26  
    PAN, 24  
    precursor, 24  
    process of making, 24, 35  
    properties of, 25, 26  
    roving of, 26  
    yarn of, 26  
Cermets, 6  
    oxide-based, 6  
    carbide-based, 6  
Ceramic fibers, 28–29  
    Alumina, 28, 29  
    Fibers FP, 28, 29  
    properties of, 29  
    silicon carbide, 28, 29  
Charpy tests, 475  
Classical lamination theory, 214  
CLT, *see* classical lamination theory  
COD, *see* crack-opening displacement  
Code, laminate orientation, 544–548  
Coefficient of thermal expansion, 111  
Cold solders, 6  
Combustion method, 441  
Compliance curve, 467  
Compliance matching procedure, 467  
Compliance matrix, 184  
    invariant form of, 194  
    transformation of, 189  
Compliance tensor, 184  
Composite materials:  
    applications of, 10–14  
    bridge, 12–14  
    characteristics of, 2–3  
    classification of, 3–5  
    consumption of, 12  
    continuous fiber, 9  
    cross-ply, 3  
    definition of, 1–2  
    degradation of, 426–429
- density of, 65–66, 440  
    discontinuous fiber, 7, 9  
    fabrication of, 41–60  
    fiber-reinforced, 5, 7–10  
    fibrous composite, 7–11  
    growth of, 11  
    hybrid, 9, 407–411  
    multilayered, 7, 8  
    particulate, 1, 5–7  
    particle-reinforced, 5  
    properties of, 2, 123–124, 550–554  
    quasi-isotropic, 147  
    ribbon reinforced, 152–155  
    short-fiber, 132–155  
    single layer, 7, 8, 9  
    tape reinforced, *see* ribbon reinforced  
    unidirectional, 3, 9, 62–131  
    use in U.S. industries, 12  
Compounding, 57  
Compression molding, 56  
Computer:  
    laminate analysis through, 272  
    programs, 550  
    software, commercial, 556  
Concentration, 2  
Constant-stress model, 80  
Constitutive equations, 192  
    for laminates, 221, 224–225  
Contact lay-up, 43  
Continuous fiber reinforced composite, 9  
Coupling agents, 16, 19  
Coupling coefficients, *see* Cross-coefficients  
Crack-driving force, 466  
Crack extension, 342  
Crack-extension force, 466  
Crack-extension force curve, 466  
Crack-growth resistance, 466  
Crack-growth resistance curve, 466, 467  
Crack-length-estimation curve, 467, 469

- Crack-opening displacement, 467
- Crack opening mode, 342
- Creel, 49
- Critical buckling load, 298
- Critical fiber length, 136
- Critical volume fraction, 75, 76, 146
- Cross-coefficients, 168–170
- Cross-linking, 42
- Cumulative weakening, 78
- Curing agent, 35
- Curing stresses, 268
- Damage:
  - due to low velocity impact, 411–416
  - fatigue, 368
  - identification, 481–488
  - initiation, 96
- DCB *see* double-cantilever-beam
- Debonding, 96, 370
  - of fibers, 399
- Degradation of composites, at elevated temperatures, 426–429
- Delamination, 96
- Delamination crack, 370, 373, 396, 401
- DEN, *see* double edge notched
- Density, 57–58, 440
- Diffusion, mass, 106
- Diffusivity, 120
  - longitudinal, 120, 121
  - measurement of, 443
  - transverse, 120, 121
- Discontinuous fiber reinforced composites, *see* Short-fiber composites
- Double-cantilever-beam, 472, 473
- Double edge notched specimen, 465
- Drop-weight impact test, 476
- Ductility index, 409
- Edge delamination
  - suppression, 335
- Edge effects, 324–335
- Effect of temperature and moisture on composite properties, 422–426
- Effective modulus, 252
- Elastic constants, 175, *see also* Engineering constants
  - number of, 182
  - relations with compliance matrix, 185
  - relations with stiffness matrix, 185–187
  - restrictions on, 187–189
  - symmetry of, 175
  - variation of, 170–172
- Elasticity methods, 83
- Electrical conductivity, 115, 116, 118
- End effects, 78
- End tabs, 445, 446
- Energy absorbing mechanisms, 396
  - fiber breakage, 397
  - fiber debonding, 399
  - matrix cracking, 398
  - matrix deformation, 398
- Energy curves, 471
- Engineering constants, 160
  - determination of, *see* Testing of composites
  - extremum value of, 170
  - for orthotropic lamina, 160, 161
  - restrictions on, 187–189
  - relations with compliance matrix, 185
  - relations with stiffness matrix, 185–187
  - transformation of, 166–172
  - variation of, 170–172
  - variations with fiber orientation, 169–172
- Environmental interaction effects, 416–431
- Epoxy, 36–38
  - properties of, 37
- Epoxy resin, 36
- Equations of motion, 302
- Experimental characterization, 431–495
  - See also* Testing of composites
- Fabrication of composites, 41–60
  - by bag molding, 46–48
  - by contact lay-up, 43
  - by hand lay-up, 43–45
  - by resin transfer molding, 49
  - by stamping, 57
  - by thermoforming, 57, 58
  - ceramic matrix, 59–60
  - filament winding, 49–51
  - metal matrix, 58–59
  - molding compounds, 53
  - prepregs, 55
  - pultrusion, 51–53
  - thermoplastic resin matrix, 55–58
  - thermosetting resin matrix, 42–55
- Failure:
  - envelop, 204–205, 206
  - initiation, 88, 96
    - microscopic, 335
  - internal, 96
  - load, 97
  - models, 78–79
  - modes of, 96–108
  - shear, 107, 109
- Failure criteria, *see also* Failure theories
  - for biaxial stress field, 197–205
  - for notched composites, 349
  - maximum distortion energy, 91
  - Whitney-Nuismer, 349–355
- Failure theories:
  - maximum strain, 200–203
  - maximum stress, 197–200
  - maximum work, 203–205
  - Tsai-Hill, 203
- Fatigue, 368–395
  - characterization of, 374–375
  - crack arrest in, 370
  - crack branching in, 370
  - cross-ply cracks in, 371, 372
  - damage, 370
  - damage initiation, 370
  - delamination crack, 370
  - empirical relations for, 385–386
  - factors influencing behavior, 378
  - Goodman-Boller relationship, 384
  - influence of mean stress, 383
  - influence on properties, 375–377
  - of high modulus fiber composites, 386–390
  - of short fiber composites, 390–395
  - schematic representation of, 373–374
  - shear, 382–383
  - S-N curve, 375
- Fibers:
  - advanced, 16–30
  - aramid, 7, 26
  - average stress on, 139
  - boron, 27–28

- breaking of, 96, 100–101, 397
- buckling of, 102, 103
- carbon, 23–26
- ceramic, 28
- chopped, 10
- critical length of, 136
- crushing of, 107
- debonding of, 399
- end effects, 133
- Fiber FP, 28
- glass, 7, 16–23
  - cake, 17
  - composition, 18
  - end, *see* strand
  - production of, 17, 18
  - properties, 18, 19
  - roving, 21
  - sizes, 17
  - staple, 17, 18
  - strand, 17
  - surface treatment of, 18–20
  - yield, 21
- graphite, 7, 33–26
  - see also* Carbon-fibers
- ineffective length of, 136
- Kevlar, 26–27
- load transfer length of, 136
- man-made, 7
- microbuckling of, 102
- polyethylene, 28–30
- properties of, 7, 8
- pullout, 100–101
- silicon carbide, 28
- Spectra, 29
- Fiber aspect ratio, 140
- Fiber composites,
  - applications of, 10–14
  - properties of, 10
- Fiber packing, 124
- Fiber pullout, 396, 399–401
- Fiber splitting, 106, 107
- Fiber volume fraction
  - minimum, 75, 146
  - critical, 75, 146
- Fiberglass, *see* glass fibers
- Fiber-reinforced composites, 7–10
- Filament winding, 49–51
  - patterns, 50, 51
- Fillers, 39
  - inorganic, 6
- Finite element analysis codes, 555, 556
- Finish, 18
- Flakes, 6
  - mica, 6
- Fracture mechanics, 335–355
  - Fracture mechanics concepts, 338–346
  - Fracture process in composites, 336–338
  - Fracture process in impact, 395–396
  - Fracture process zone, 397
  - Fracture surface work, 341
  - Fracture toughness
    - measures of, 338
    - of composite laminates, 346–349
  - Fundamental frequency, 303
- Gel coat, 43
- Generalized Hooke's law, 175
- Generally orthotropic lamina, 164
- Glass fibers, 7, 16–23
  - cake, 17
  - composition, 18
  - chopped-strand mat, 22
  - continuous-strand mat, 22
  - coupling agent, 18
  - E-, 19
  - end, 17
  - fabric, 23
  - finish, 18
  - forms of, 21–23
  - mat, 22
  - milled, 23
  - production of, 17–18
  - properties of, 8, 18, 19
  - roving, 21
  - S-, 19
  - sizes, 17
    - compatible, 18, 19
    - temporary, 18
  - staple, 17–18
  - strand, 17
  - surface treatment of, 15
  - surfacing mat, 22
  - veil, 22
  - woven roving, 22
  - yarn, 23
- Goodman-Boller relationship, 383, 384
- Graphite fibers, 23
  - from PAN, 24
  - precursor, 24
  - tows, 26
- Gel coating, 43
  - for short-fiber composites, 141–144
  - for transverse modulus, 85
  - for transverse transport properties, 115
- Hand lay-up technique, 43
- Hole size effect, 349
- Homogeneity, 3
- Hooke's law, 174
  - for generally isotropic material, 174–177
  - for generally orthotropic material, 174–177
  - for isotropic material, 181–182
  - for specially orthotropic material, 177–180
  - for transversely isotropic material, 180–181
  - generalized, 175
  - in contracted notation, 179–180
- Hybrid, *see* hybrid composites
- Hybrid composites, 9, 397, 407–411
- Hybrid laminates, 3, 5
- Hybridization, 407
- Hygrothermal forces, 268
- Hygrothermal moments, 268
- Hygrothermal stresses, 263–273
  - Calculations, 264–273
- IITRI test fixture, 450
- Impact:
  - energy absorbed, 396
  - energy absorbing
    - mechanisms, 396–401
  - failure modes, 396–401
  - initiation energy, 408
  - low velocity, damage due to, 411–416
  - propagation energy, 408
  - hybrid composites, 407–411
  - strength of short-fiber composites, 152
  - Charpy, 475
  - drop weight, 476
  - instrumented Charpy, 477
  - Izod, 475–476
- Impact energy values for materials, 408
- Impact properties,
  - effect of materials variables on, 401–407
  - effect of testing variables on, 401–407
- Haplin-Tsai equations
  - for ribbon reinforced composites, 154
  - for shear modulus, 93

- Impact properties (*Continued*)  
of unidirectional fiber-epoxy composites, 410
- Ineffective length, 136
- Interfacial bond, 79
- Interfacial area, 1
- Interfacial conditions, 79
- Initiation energy, 405, 408
- Intelligent structures, 503
- Interlaminar fracture toughness, determination of, 471–475
- Interlaminar shear strength, determination of, 324–335, 471
- Interlaminar stresses, 471, 472  
approximate solutions for, 330–334  
concepts of, 324–326  
determination of, 326–328  
effect of stacking sequence on, 328–330
- Invariant forms of compliance matrix, 194–196  
stiffness matrix, 194–195
- Isotropic composite, 132
- Isotropy, 3, 159
- Izod tests, 475
- J-curve, 471
- J-integral, 345–346  
critical, 470  
determination of, 470–471  
energy interpretation, 470
- Joints  
adhesively bonded, 355–360  
advantages of, 359  
configuration, 356–357  
design of, 355  
failure modes, 357  
stresses in, 358  
bonded-mechanically fastened, 361–362  
for composite structures, 355  
mechanically fastened, 360–361  
advantages of, 361  
disadvantages of, 361  
failure modes of, 36
- K-calibration factor, 465
- $K_I$ -curve, *see* crack extension force curve
- Kevlar fibers, 26–27  
chemistry of, 26
- properties of, 27
- Knee of stress-strain curve, 250
- Lamina, 63, 158, *see also* Orthotropic lamina
- Laminate:  
analysis after initial failure, 247–262  
analysis of, 213–281  
analysis through computers, 272–277  
angle-ply, 228–229  
constitutive equations for, 221, 224–225  
cross-ply, 228–229  
curing stresses, 268  
definition of, 158  
description system, 225–226, *see also* laminate orientation code  
effective modulus, 251  
fracture mechanics of, 335–355  
hygrothermal forces in, 268  
hygrothermal moments in, 268  
hygrothermal stresses in, 263–272  
interlaminar stresses in, 324–335, 471  
load carrying capacity of, 255  
mechanical strains in, 266  
netting analysis, 280  
orientation code, 544–549  
primary modulus, 250  
quasi-isotropic, 229–230  
residual stresses, 268  
resultant force, 218  
resultant moment, 218  
secondary modulus, 250  
specially orthotropic, 228  
stacking sequence, 219, 328, 544–549  
stiffness matrices, 221  
strains in, 238  
strength analysis, 274–276  
stress analysis, 273–274  
stresses and strains in, determination of, 238–247  
stresses in, 238  
symmetric, 227–228  
thermal strain, 263  
thermal stresses, *see* Laminate, hygrothermal stresses
- unidirectional, 228–229
- Laminated beams  
bending of, 315–318  
buckling of, 318–319  
free vibrations of, 319–320  
governing equations for, 314
- Laminated plates  
bending of, 288  
buckling of, 295  
equilibrium equations for, 283–286  
free vibrations of, 301  
governing equations for, 283  
in terms of displacements, 286–288
- Laminates, 8, 158  
bidirectional, 10
- Laser shearography, 488
- Law of mixtures, *see* Rule of mixtures
- Load coefficients, 290
- Load sharing, 71–73
- Load transfer length, 136
- Longitudinal direction, 63
- Longitudinal stiffness:  
factors influencing, 76–80  
prediction of, 68–69
- Longitudinal strength:  
factors influencing, 76–80  
prediction of, 75–76
- Low velocity impact, 411–416  
damage due to, 411–416
- Mass diffusion, 117–123
- Major Poisson's ratio, 95
- Mandrel, 50
- MAPLE, 555, 556
- Mat, 10, 22  
chopped-strand, 22–23  
continuous-strand, 22–23  
surfacing, 22–23
- Material axes, 63
- Mathcad, 520, 555, 556
- MATLAB, 520, 555, 556
- Matrix material, 2, 7, 30–41  
Bismaleimides, 38  
effect of temperature and moisture on, 422–426  
elevated temperature, degradation at, 426–429  
epoxy, 36–38  
metals, 39, 41  
microcracking, 96  
phenolics, 38

- plastics, 30–40
- polyester, 34–35
- polyimides, 38
- polymers, 30–40
- vinyl esters, 38
- Matrix (mathematical):
  - addition, 514
  - column, 510
  - definitions, 509
  - determinant, 513
  - diagonal, 511
  - elements of, 509
  - identity, 511
  - inverse, 517
  - multiplication, 516
  - operations, 514–520
  - orthogonal, 519
  - principal diagonal of, 511
  - row, 510
  - skew symmetric, 511
  - square, 510
  - subtraction, 514
  - symmetric, 511
  - transformation of, 519
  - transpose of, 510
  - unit, 511
- Matrix digestion method, 441
- Matrix dissolution method, 441
- Matrix ductility, 150
- Maximum strain theory, 200–203
- Maximum stress theory, 197–200
- Maximum work theory, 203–205
- Measure of fiber orientation, 148
- Measurement of
  - critical crack growth resistance, 464
  - critical J-integral, 470
  - critical strain-energy release rate, 463
  - critical stress-intensity factor, 464
  - density, 440
  - diffusivity, 444–445
  - flexure properties, 459
  - impact properties, 475
  - in-plane shear properties, 452
  - interlaminar fracture toughness, 471
  - interlaminar shear strength, 471
  - measures of fracture toughness, 463
  - mechanical properties, 445–481
  - moisture absorption, 444–445
  - moisture expansion coefficients, 444–445
  - physical properties, 440–445
  - properties in compression, 449
  - properties in tension, 445
  - stiffness and strength, *see* testing of composites
  - thermal expansion coefficients, 442
  - void volume fraction, 442
  - volume fraction, 441
  - weight fractions, 441
- Microbuckling of fibers, 102, 103
  - in extension mode, 102
  - in shear mode, 102, 103
- Micromechanics of transverse failure, 88
- Microscopic failure initiation, 335
- Milled fibers, 23
- Minimum volume fraction:
  - of short fiber composite, 146
  - of unidirectional composite, 76
- Minor Poisson's ratio, 95
- Modulus:
  - effective, 252
  - longitudinal, 68, 160
  - primary, 250, 375
  - residual, 375
  - secondary, 250, 375
  - shear, 91–95, 160
  - of short-fiber composites, 141–145
  - transverse, 80–91, 141, 160
- Moisture absorption, 114
- Moisture expansion coefficients, 114
- longitudinal, 114
- transverse, 114
- Mold release, 43
- Molding compounds, 10, 53–55
  - BMC, 42, 53
  - bulk, 42, 53
  - DMC, 53
  - dough, 53
  - prepregs, 42, 55
  - sheet, 42, 53, 54
  - SMC, 42, 53, 54
- Nanocomposites, 7, 496–498
  - Clay-reinforced, 7
  - Nanotube-reinforced, 7
- Nanotubes, 7, 496
  - Single walled, 497
  - Multi-walled, 497
- Natural fibers, 499
  - properties of, 500
- Navier's approach
- NDE, *see* nondestructive evaluation
- Neutral axis, 460
- Nodal lines, 304
- Nondestructive evaluation, 481–488
- Nondestructive evaluation techniques:
  - acoustic emission, 483
  - laser shearography, 488, 489
  - thermography, 486
  - ultrasonics, 481
  - X-radiography, 485
- Notch sensitivity, 346
- Notched-bend tests, 464–465
- Notched plate, 465
- Notched-plate test, 472, 473
- Orthotropic lamina, 161
  - analysis of, 158
  - balanced, 172
  - engineering constants of, 160, 166
  - generally, 161
  - shear strength, importance of sign, 205–209
  - specially, 161
  - strength of, 196–209
  - strength under biaxial stresses, 196–209
  - stress-strain relations in arbitrary direction, 164–166
  - transformation of engineering constants, 166–174
  - variation of elastic constants, 170–172
- Orthotropic materials, 158–160, *see also* Orthotropic lamina
  - definition of, 158–160
  - deformation behavior of, 159
  - Hooke's law for, 160–174
- PAN, 24
- Particulate composites, 1, 5–7
- Plasma spraying, 9

- Plastics, *see* polymers
- Platelets, 2, 496
- Ply, 63
- Point of instability, 466
- Point-stress criterion, 349
- Poisson's ratio:
- major, 95, 161
  - minor, 95, 161
  - prediction of, 95
  - restriction on, 188, 189
- Polyester, 34–36
- properties of, 35, 36
- Polyethylene fibers, 28–30
- Dyneema, 29
  - properties of, 29
  - Spectra, 29
- Polymerization, 42
- Polymers, 30–40
- crystalline melt
    - temperatures of, 32
  - epoxy, 36–38
    - properties of, 37
  - glass transition temperatures
    - of, 32, 33
  - melting point of, 32
  - network, 31
  - polyester, 34–35
    - properties of, 35, 36
  - properties of, 31–34
    - epoxy resin, 37
    - phenolics, 38
    - polyester resin, 34
    - polyimide, 38
    - thermoplastic resins, 40
  - thermoplastic, 31, 38–39
    - high temperature, 39
    - properties of, 39, 40
  - thermosets, 31
    - temperature for
      - processing of, 32
  - thermosetting, 31
- Preform, 10
- Preimpregnated fibers, *see* prepregs
- Prepregs, 42
- Prepregs, 9, 42, 55
- Primary modulus, 375
- Propagation energy, 405, 408
- Properties of fiber composites, 550–554
- Properties of unidirectional composites, 123–124
- Pultruded shapes, 51, 52
- Quasi-isotropic laminate, 229–230
- R-curve, *see* crack-growth resistance curve
- Rail shear test, 458
- Reinforcements, 2
- geometry of, 3
  - orientation of, 3
- Reinforcing material, 2
- Residual strength, 376
- Residual stresses, 79–80, 268
- Resin transfer molding (RTM), 49
- vacuum assisted (VARTM), 49
- Resultant forces, 218
- Resultant moments, 218
- Ribbon-reinforced composites, 152–155
- Halpin-Tsai equations for, 154
  - in-plane transverse modulus of, 154
- Rule of mixtures, 69
- for density, 65
  - for longitudinal diffusivity, 120
  - for longitudinal modulus, 69
  - for Poisson's ratio, 96
  - for stress, 68
  - for transport properties, 114
- Sandwich cross-beam, 459
- Secondary cracks, 398
- Secondary modulus, 250, 375
- Self-consistent models, 84, 85
- Self-similar crack growth, 337
- SEN, *see* single edge notched
- Series solution, 290
- Shear coupling, 164
- Shear deformation theory
- first-order, 306–311
  - higher-order, 311–314
- Shear failure, 107, 109
- Shear-lag analysis, 134
- Shear modulus, 91–95, 160
- Shear strain:
- engineering, 180, 534–535
  - tensorial, 180, 535
- Shear strength, 197
- Shearography, laser, 488
- Short beam shear test, 472
- Short-fiber composites, 132–157
- critical fiber length, 136
  - critical fiber volume fraction of, 146, 147
  - effect of matrix ductility on properties of, 150–152
  - examples of, 133
  - failure initiation of, 146
  - fatigue of, 390–395
  - impact strength of, 152
  - ineffective fiber length, 136
  - load transfer length, 136
  - matrix ductility, effect of, 150–152
  - minimum fiber volume fraction of, 146, 147
  - modulus of, 140
    - prediction of, 141
    - randomly oriented, 143
  - randomly oriented, 143, 147
  - ribbon reinforced, 152–155
  - strength of, 140, 145–149
    - prediction of, 145
  - strength of random fiber composite, 147, 148
  - stress distribution in, 137–139
  - theories of stress transfer for, 133–140
- Single edge notched specimen, 465
- Sizes, 17, 18–20
- compatible, 18, 19
  - temporary, 18
- Smart structures, 503
- S-N curve, 378
- Software packages, commercially available, 556
- Sound deadener, 6
- Specially orthotropic lamina, 161
- stress-strain relations for, 161–164
  - under plane stress, 182
    - constitutive equation for, 192
    - stiffness coefficients for, 183
- Specially orthotropic material, 177
- Specific stiffness, 7–8, 11
- Specific strength, 7–8, 11
- Speckle effect, 488
- Spray-up, 44, 45
- Stamping, 57
- Staple fibers, 18
- Static fatigue, 417
- Static fatigue of fibers, 417
- Static-rupture of fibers, 417
- Stiffness:
- factors influencing, 76–80
  - methods of predicting
    - longitudinal, 68–69
    - residual, 376
    - transverse, 84–87

- Stiffness matrix, 183  
 bending, 221  
 coupling, 221  
 engineering constants,  
 relations with, 185–187  
 extensional, 221  
 for orthotropic materials,  
 183  
 invariant form of, 194  
 inversion of, 238  
 of fractured plies, 248  
 synthesis of, 218–221  
 transformation of, 189
- Strain:  
 analysis of, 532–535  
 compatibility conditions,  
 535  
 determination of, 238  
 engineering, 180, 535  
 mechanical, 266  
 tensorial, 180, 535  
 transformation equation,  
 534
- Strain-displacement relations,  
 533
- Strain-energy release rate,  
 339–341  
 critical, 341
- Strain magnification factor, 90
- Strain-stress relations, *see*  
 Stress-strain relations
- Strength:  
 factors influencing, 76–80  
 longitudinal compressive,  
 103–106, 197  
 longitudinal tensile, 75–76,  
 197  
 notched, 351–355  
 of orthotropic lamina, 196  
 of quasi-isotropic laminate,  
 257  
 residual, 376  
 of short-fiber composite,  
 145–149  
 transverse, 87–91, 197  
 theories of, 197–205
- Strength reduction factor, 90
- Strengthening mechanisms, 3,  
 5
- Stress:  
 analysis of, 536–540  
 boundary conditions, 537,  
 539  
 curing, 268  
 determination of, 238–247  
 equilibrium equations, 539  
 hygrothermal, 263–272  
 interlaminar, 324–335  
 residual, 79–80, 268  
 sign convention for, 205,  
 537  
 symmetry of, 538  
 thermal, *see*, hygrothermal  
 transformation, 539–540
- Stress concentration factor, 88,  
 90
- Stress corrosion, 419  
 features of, 416  
 of glass fibers, 419–422  
 of GRP, 419–422
- Stress-intensity factor, 339,  
 341–344  
 critical, 464  
 determination of, 464–470  
 relation with strain energy  
 release rate, 342
- Stress-rupture characteristics,  
 429–431
- Stress-rupture of fibers, 418
- Stress-strain relations, 160  
 for anisotropic materials,  
 175–176  
 for generally orthotropic  
 lamina, 164–166  
 for isotropic materials, 540  
 for specially orthotropic  
 lamina, 161–164  
 generalized, 175  
 in terms of engineering  
 constants, 163
- Surface energy, 341
- Surfacing mat, 44
- Symmetric laminates, 227
- Tensors:  
 definition of, 527  
 laws of transformation, 527
- Tests,  
 bend, four point, 459, 460  
 bend, three point, 459, 460  
 compression, 449  
 coupon, [ $\pm 45$ ]<sub>s</sub>, 455  
 coupon, off-axis, 456  
 double cantilever beam, 472  
 flexural, 459  
 fracture toughness, 463  
 impact, 475  
 drop weight, 476  
 Charpy, 476  
 Izod, 476  
 in-plane shear, 452  
 Iosipescu shear, 453  
 notched plate, 472  
 picture frame, 458  
 rail shear, 458  
 sandwich cross beam, 459  
 sandwich beam, 448  
 short beam shear, 472  
 tension, 445  
 torsion tube, 452
- Testing of composites:  
 bending, 459  
 Charpy, 475–481  
 compression, 449  
 drop weight, 476  
 flexural, 459  
 four-point bending, 459  
 fracture toughness, 463–475  
 in-plane shear, 452–459  
 Iosipescu, 453  
 [ $\pm 45$ ]<sub>s</sub> coupon, 455  
 off-axis coupon, 456  
 torsion tube, 452  
 instrumented Charpy, 475–  
 481  
 Izod, 475–481  
 notched bend, 465  
 notched plate, 463  
 off-axis shear, 457  
 off-axis tension, 447  
 picture frame, 458  
 rail shear, 458  
 sandwich crossbeam, 459  
 short beam shear, 472  
 tension, 445–449  
 three point bending, 459
- Thermal stresses  
 concepts of, 263–264
- Thermography, 486–488  
 pulse-echo, 487  
 through transmission, 487
- Thickness shear, 472
- Transverse shear  
 deformations due to, 306–  
 311  
 effects of, 306
- Transverse splitting, 102
- Transversely isotropic, 63, 160
- Theories of failure, *see* failure  
 theories
- Theories of stress transfer,  
 133–140
- Thermal conductivity, 115–  
 117
- Thermal expansion  
 coefficients, 108–114  
 longitudinal, 111  
 transverse, 111
- Thermal strains, 264
- Thermal stress, *see*  
 Hygrothermal stress
- Thermofforming, 57
- Thermoplastic polymers, 31  
 properties of, 40
- Total impact energy, 405
- Transformation:  
 matrix, 190

Transformation (*Continued*)

- of strain, 534
- of stress, 539
- relations, 190

## Transport properties, 114

## Transverse:

- isotropy, 63
- splitting, 102–106
- stiffness, 80–87
- strength, 87–91

## Transverse direction, 63

## Tsai-Hill theory, 203

## Ultrasonics, 481–483

- pitch-catch method of, 481, 482
- pulse-echo method of, 481, 482
- through transmission method of, 482, 483

## Unidirectional composites:

- anisotropy of thermal expansion, 112
- coefficient of thermal expansion, 108–114
- critical volume fraction, 75–76
- expansion coefficients, 108–114

## failure initiation, 74

- failure mechanism of, 74
- failure modes, 96–108
- longitudinal behavior of, 67
- longitudinal stiffness, 68–71
- longitudinal strength, 75–76
  - factors influencing, 76
  - statistical models for, 77
- mass diffusion in, 117–123
- model for, 68
- moisture in, 114
- minimum volume fraction, 75
- Poisson's ratio, 95
  - major, 95
  - minor, 95
  - prediction of, 95–96
- properties of, typical, 113, 123, 124
- shear modulus of, 91–95
  - prediction of, 91
  - Haplin-Tsai equations for, 93
- thermal conductivities, 115–117
- thermal expansion, 108–114
- transport properties, 114
- transverse stiffness, 80–87
- transverse strength, 87–91
  - prediction of, 90

- empirical approach for, 91

transversely isotropic, 63  
Unstable crack growth, 466

Variation of stresses in a laminate, 216–217

Veil, 23, 44

Voids, 67

volume fraction, 67

Void content, 67

Volume fraction, 64, 65

- critical, 76, 146
- definition of, 65–66
- minimum, 75, 146

Weight fractions, 2, 64, 65

Whitney-Nuismer failure

criteria, 349–355

for notched composites, 349–355

Winding angle, optimal, 280

Wood-plastic composite, 501–502

X-radiography, 485–486  
penetrant-enhanced, 486