

INDEX

A

- ABS, *see* Antilock braking systems
Absolute pressure sensors, 44
Acceleration, scaling of, 231, 233
Accelerators, 290
Accelerometers, micro-, *see*
 Microaccelerometers
Accuracy, 16
Acoustic streaming, 204
Acoustic wave sensors, 36–37
Active substrate materials, 247, 352
Actuation, micro-, *see* Microactuation
Actuation energy, 36
Actuation method, 3
Actuators:
 in automobiles, 21
 defined, 53
 in microfluidics, 72
 principles used in, 53
Adhesion, 336, 337
Adhesives, 430–431
Advection, 388
A-elements, 375, 376
Aerospace industry, 28–29
AFM, *see* Atomic force microscope
AFM-guided nanomachining (AGN) system, 470
Agriculture, 503
Air, viscosity of, 138
Airbag deployment systems, 3–6, 22, 67, 68
Alcohol, 138
Alignment tolerances, 415, 416
Alkaline etchants, 326
Alumina, 445
Aluminum:
 atomic/ionic radii of, 306
 diffusion coefficient of, 95
 as dopant, 291
 electrical resistivity of, 246
 electron mobility of, 266
 mechanical/thermophysical properties of, 257
 sputtering of, 400
 thermal diffusivity of, 258
 wet etching on, 401
 as wire material, 437
Aluminum-to-nitride bonding, 442
Ammeters, 447
Amperometric electrochemical detectors, 388
Analytes, 39
Analytical modeling, 501–502
Analytical systems, 39–40
Analytic systems, 12
Angioplasty pressure sensors, 28
Animation, 397
Anisotropic etching, 11, 316, 325–326
Annealing, 437
Anode, 101–102
Anodic bonding, 432–434, 442, 443
Antilock braking systems (ABS), 22, 66
Antimony, 291
APCVC, *see* Atmospheric pressure CVD
A/P ratio, *see* Aspect ratio
AP&T, *see* Assembly, packaging, and testing

- Arc discharge method, 474
 Argon, 304, 306
 Arsenic:
 atomic/ionic radii of, 306
 diffusion coefficient of, 95
 diffusivity of, 294
 as dopant, 91, 98–99, 291
 ion implantation of, 291
 solid solubility of, 94
 Aspect (A/P) ratio, 17, 330, 331, 354, 355
 Assembly:
 of loose atoms/molecules, 470
 micro-, *see* Microassembly
 nano-, 500
 reliability testing during, 457
 Assembly, packaging, and testing (AP&T),
 407–458
 costs of, 407–409
 microassembly, *see* Microassembly
 packaging, *see* Microsystems packaging
 in production process flowchart, 408
 standardization timeline for, 408
 testing, 456–458
 Atmospheric pressure CVD (APCVD), 310,
 311
 Atoms:
 assembly of loose, 470
 elastic bonding of, 480–481
 intermolecular forces for charge-carrying, 89
 isolation of, 468–470
 rebonding of free, 470, 471
 Atomic cohesive forces, 87
 Atomic force microscope (AFM), 468–469,
 496–497
 Atomic number, 85
 Atomic structure of matter, 83–86
 Attitude determination and control systems, 28
 Attraction, 88
 Attrition, 472
 Automobiles, miniature, 19–20
 Automotive industry, 21–27
 acoustic wave sensors in, 36
 comfort/convenience in, 24
 durability requirements in, 23
 engine/power trains in, 24, 25
 future applications in, 26–27
 motivation for MEMs in, 21
 safety in, 22
 sensors in, 21–23
 vehicle diagnostics/health monitoring in, 24,
 26
 Avogadro's number, 305
 Avogadro's theory, 305
- B**
- Back-side pressurization, 44, 45
 Baking, 280
 Band broadening, 392, 394
 Bandpass filters, 36
 Bardeen, J., 11
 Barium titanate, 270
 Base plate, 340
 Batteries, 476
 BEA (boundary element analysis), 395
 Beam-attached-mass, 125, 126
 Beam-mass, 125, 126
 Beams:
 deflection of, 129
 as MEMS components, 362
 thermal stresses in, 159–165
 Beam springs, 362
 Bearings, 66
 Bell, Alexander Graham, 61
 Bending, of thin plates, 110–119
 circular plates with edge fixed, 112–114
 rectangular plates with all edges fixed,
 114–115
 square plates with edges fixed, 116–119
 Bending moments, 111, 367
 Bending stresses, 111, 368
 Bernoulli's equation, 194
 Bilayers:
 fracture mechanics in, 169–171
 temperature stress in, 153–157
 Bimetallic strips, 53–54
 Binnig, Gerd, 468, 469
 Bio-barcode, 475
 Biological markers, 475
 Biological systems, 466
 Biomedical interfaces, 427
 Biomedical products, 32
 Biomedical sensors, 2, 37–40
 Biomedicine, 475
 BioMEMs, 37–38, 482
 Biosensors, 2, 12, 39
 Biotesting and analytical systems, 39–40
 Bitumen extraction, 477
 Boeing Company, 416
 Bonding:
 molecular, 87–88
 part, 411
 surface, *see* Surface bonding

- Bonding-and-etchback technique, 436
- Boron:
- atomic/ionic radii of, 306
 - diffusion coefficient of, 95
 - diffusivity of, 294
 - as dopant, 91, 98–99, 291
 - ion extraction from, 87
 - ion implantation of, 291
 - solid solubility of, 94
- Boronphosphosilicate (BPSG), 336
- Boss stiffeners, 380
- Bottom-up approach, 467
- Boundary conditions, 210–215
- convective, 212–215
 - prescribed heat flux at boundary, 210–212
 - prescribed surface temperature, 210
- Boundary element analysis (BEA), 395
- Boundary layer, 209
- BPSG (boronphosphosilicate), 336
- Brattain, W. H., 11
- Buckyballs, 471, 474
- Buckytubes, 473
- Bulk micromachining:
- design/selection of, 354–355
 - micro-cantilever beams produced by, 334
 - simulation of, 376–377
- Bulk micromanufacturing, 324–333, 343
- dry etching, 329–333
 - etching, generally, 324
 - etch stop, 328–329
 - isotropic/anisotropic etching, 325–326
 - wet etchants, 326–328
 - wet vs. dry etching, 333
- Burn-in, 457
- C**
- CAD, *see* Computer-aided design
- Cantilever beam, 338
- Capacitance:
- and geometric tolerance, 415
 - and signal transduction, 46–49, 357
- Capacitance measurements, 450, 451
- Capacitive pressure sensors, 24, 25
- Capacitors, 447
- Capillaries, 382–383
- Capillary effect, 200–203, 238
- Capillary electrophoresis (CE), 386–394
- in curved channels, 392–394
 - design issues for, 394
 - electrohydrodynamic pumping in, 102
- Capillary electrophoresis network systems, 386–392
- in biotesting/analytical systems, 39–40
 - design case, 389–392
 - mathematical modeling of, 388–389
- Capillary electrophoresis on-a-chip, 382
- Carbon, 276
- Carbon C₆₀, 472
- Carbon nanotubes (CNTs), 473, 474, 476, 478
- Carrier gas, 301
- Cartesian robots, 412
- Casings, 445
- Catalyzed chemical vapor deposition, 474
- Cathode, 101–102
- CE, *see* Capillary electrophoresis
- CE analysis, 387–388
- Cesium, 44
- CFD, *see* Computational fluid dynamics
- CFD-ACE⁺ code, 389, 391
- CFD Research, 389
- Channels, 362
- Charge-carrying atoms, 89
- Charge density analysis, 402
- Chemical engineering, 15
- Chemical etching, 316–318. *See also* Wet etching
- Chemical sensors, 2, 40–42
- Chemical vapor deposition (CVD), 301–311
- and CAD, 400
 - chemical reactions in, 302–303
 - diffusion in, 92
 - enhanced, 310–311
 - etch rates for, 336
 - rate of deposition, 303–310
 - sealing by localized, 443
 - working principle of, 301–302
- Chemicapacitor sensors, 41
- Chemimechanical sensors, 41
- Chemiresistor sensors, 40–41
- Chlorinated phenols, 477
- Chou, Stephen Y., 498
- Circular conduits, 195–197
- Circular frequency, 120
- Circular plates, 112–114
- Circular tubes, 383, 386
- Class 10 clean room, 286
- Cleaning, substrate, 400
- Clean rooms, 286
- CMOS (complementary metal oxidation of semiconductors) epitaxy, 313
- CNTs, *see* Carbon nanotubes

- Coating(s):
 with controllable optical properties, 277
 nanoparticles in, 477
 selection of polymer, 500
 with silicone gel, 453
- Coefficient of surface tension, 200
- Coefficient of thermal expansion (CTE), 152
- Color:
 of nanoparticles, 472
 oxide thickness by, 300–301
- Comb drive, 60–62, 414–416
- Comfort, automobile, 24
- Command and control systems, 28
- Communications systems, 29
- Compact tension (CT), 167, 168
- Complementary metal oxidation of
 semiconductors (CMOS) epitaxy, 313
- Complementary solution (CS), 127
- Compressible fluids, 138, 187
- Compressive stress, 153
- Computational fluid dynamics (CFD), 198–199
- Computer-aided design (CAD), 177, 395–402
 design case using, 398–402
 for microsystems, 395–398
 rationale for using, 395
 selection of, 398
- Conduction, heat, *see* Heat conduction
- Conductive fibers, insertion of, 276
- Conductive polymers, 275–276
- Conductivity:
 electrical, *see* Electrical conductivity
 thermal, *see* Thermal conductivity
- Conductors:
 and atomic structure, 84
 electrical resistivities of, 90, 246
 resistivity of, 246
- Conduits:
 incompressible fluid flow in micro-, 199–204
 laminar fluid flow in circular, 195–197
- Constraint base, 379
- Contact problems in microassembly tools,
 416–419
 electrostatic force, 417–418
 surface tension, 419
 van der Waals force, 418–419
- Continuity equation, 187–189
- Continuum fluid dynamics, 187–195
 continuity equation, 187–189
 equation of motion, 192–195
 momentum equation, 190–192
- Contraction, thermal, 152
- Control surfaces, 187
- Control volumes, 187
- Convection, heat, 243–244
- Convective boundary condition, 212–215
- Convenience, automobile, 24
- Conversion of units, 525–526
- Cooling law, Newton's, 208–209
- Copper:
 atomic/ionic radii of, 306
 electrical conductivity of, 276
 electrical resistivity of, 90, 246
 electron mobility of, 266
 mechanical/thermophysical properties of, 257
 thermal diffusivity of, 258
 as wire material, 437
- Cordless phones, 19
- Coriolis effect, 70, 71
- Coriolis force, 70, 71
- Costs:
 of AP&T, 407, 408
 as design constraint, 352
 of microassembly, 410–411
- Coulomb, Charles Augustin, 56
- Coulomb's law, 56, 88
- Covalent bonds, 250
- Creep deformation, 150–152
- Critical damping, 122, 123
- Critical load, 167
- Crystal(s):
 growing single, 248–250
 piezoelectric, 268–274
 structure of silicon, 250–253
- CS (complementary solution), 127
- CT, *see* Compact tension
- CTE (coefficient of thermal expansion), 152
- Curie, Paul-Jacque, 55, 268
- Curie, Pierre, 55, 268
- Curl, Robert, 471
- Curved channels, 392–394
- Customer demands, 351
- CVD, *see* Chemical vapor deposition
- CVD silicon dioxide, 336
- Czochralski (CZ) method, 248, 249

D

- Damping coefficients, 134–144
 in shear, 137–144
 in squeeze film, 134–137
- Damping effect, 121

- Damping parameter, 122
- Darcy friction factor, 195
- Darcy–Weisbach equation, 195
- Dashpot, 66, 67, 121, 125
- Deceleration, 142
- Deep reactive ion etching (DRIE), 331–333, 415
- Deformation:
- and acoustic wave sensors, 36
 - creep, 150–152
- Delivery, of parts/materials, 421
- Denso Corporation, 19
- Deposition:
- chemical vapor, *see* Chemical vapor deposition
 - by epitaxy, 313–315
 - in thin-film fabrication, 361
- Derivation of element equations, 372–373
- Descumming, 289
- Design:
- constraints on, 351–352
 - for microassembly, 422
 - of microsystems, *see* Microsystems design
 - of packaging, 424
- Design case on microsystems packaging, 451–455
- device-level packaging, 455
 - die-level packaging, 452–455
 - die/substrate preparations, 452
 - system-level packaging, 455
- Design database, 395, 396
- Deterioration, 456
- Device-level packaging, 425–426, 455
- Device performance, range of acceptable, 457
- Diamond lattice, 251, 252
- Diamonds, 90, 246
- Diaphragms, 110, 362. *See also* Thin plates
- Diazoquinone ester (DQ), 287
- Die(s):
- of micropressure sensor, 378–382
 - packaging materials for, 445
 - preparation of, 429, 452
 - protection of, 409
- Die bonding, 445
- Die design, 378–382
- and applications, 378
 - and constraint base, 379
 - geometry/size, 379–380
 - for operating pressures, 381
 - with operating temperature, 382
 - for overpressures, 382
 - strength, 380
 - and working medium, 378
- Die down, 453
- Die isolation, 452–453
- Dielectric materials, 47, 84, 295
- Die-level packaging, 424–426
- die down, 453
 - die protection, 453–455
 - material properties for, 445
 - preparations, 452
 - primary considerations, 452–453
- Die passivation, 378
- Diffusion:
- in capillary electrophoresis, 388, 392
 - in microfabrication, 292–295
 - and nanoparticles, 475
 - process of, 92–99
 - in thin-film fabrication, 361
- Diffusivity, 93
- Dimensional stability, 247
- Dimensional tolerances, 414, 415
- Dipole–dipole interaction, 89
- Discharge method, 474
- Discrete ions, 86
- Discretization, 174, 370–372
- Dispersion, 392
- Disposable blood pressure transducer (DPT), 27
- Dissociation, 99
- Distribution channels, 72–73
- Donor atom, 90
- Dopants, 90, 290–292
- Dopant-controlled etch stop, 328, 329
- Doping, 89–99
- by diffusion, 92–99, 292–295
 - and electrical resistivities, 246–247
 - of polymers, 276
- DPT (disposable blood pressure transducer), 27
- DQ (diazoquinone ester), 287
- DRIE, *see* Deep reactive ion etching
- Dry etching, 318, 329–333. *See also* Plasma etching
- deep-reactive-ion, 331–333
 - plasma, 329–330
 - rates of, 330
 - wet vs., 333
- Dual-axial motion sensors, 69
- Dynamic analysis, 364–369
- Dynamic deflection operation mode, 448
- Dynamic forces, scaling in, 230–231

Dynamic force equilibrium, Newton's law of, 127
 Dynamic viscosity, 185

E

Eckert, J. Presper, 16
 Edge beads, 288
 Edge-sliding mode, 166
 EDP etchant, *see* Ethylene-diamine and pyrocatechol etchant
 EHD, *see* Electrohydrodynamics
 Einstein, Albert, 479
 Elastic bonding, of atoms, 480–481
 Electrical conductivity:
 of materials, 276
 of nanowires, 472, 478
 of semiconductors, 89–92
 Electrical engineering, 15
 Electrical resistivity, 246
 Electrical signals in microsystems, 447
 Electric breakdown voltage, 233
 Electric field energy, 238
 Electricity, scaling in, 237–238
 Electric resistance, 237
 Electrobreakdown, 100
 Electrochemical etch stop, 328
 Electrochemical sensors, 38
 Electrochemistry, 13, 100–105
 electrohydrodynamics, 102–105
 electrolysis, 101–102
 Electrodes, 101
 Electrohydrodynamics (EHD), 13, 102–105
 in biotesting/analytical systems, 39
 electro-osmotic pumping, 103–105
 electrophoretic pumping, 104, 105
 Electrohydrodynamic pumping, 100–105
 Electrokinetic focusing, 392
 Electrolysis, 86, 101–102
 Electrolytes, 101
 Electrolytic cells, 101
 Electromagnetic forces, scaling of, 235–237
 Electromechanical analysis, 401
 Electromechanical failure, 456
 Electromechanical interfaces, 428
 Electromechanical means, isolation of atoms by, 469, 470
 Electromechanical system design, 358
 Electromigration, 388
 Electromotive force (emf), 50, 236

Electrons:
 in atomic structure, 83–86
 heat transmission of, 486–489
 and ionization, 86–87
 Electron beams, 86–87
 Electronics, molecular, 476
 Electron mobility, 266
 Electro-osmosis, 39, 382
 Electro-osmotic pumping, 103–105
 Electrophoresis, 39, 100, 382
 Electrophoretic pumping, 104, 105
 Electroplating:
 in LIGA process, 341–342
 of polymer molds, 100
 in thin-film fabrication, 360, 361
 Electroresistant heating, 357
 Electro-resistant heating alloys, 447
 Electrostatic actuation, 3, 4
 Electrostatic bonding, 432
 Electrostatic forces:
 actuation using, 55–59, 363
 Coulomb's law, 56
 and microassembly tools, 417–418
 in parallel plates, 56–59
 scaling in, 233–235
 Elements, finite, 173
 Element equations, 371–375
 Element numbers, 85
 Emerging MST products, 31, 32
 emf, *see* Electromotive force
 Encapsulation, 411
 integrated, 440–441
 and sealing, 439–443
 Energy:
 and electron orbits, 84
 and ionization, 86–87
 nanoproducts in, 476–477
 nanoscale engineering in, 502
 oscillations formula for radiating, 478
 Energy carriers, 479
 Engines, sensors in automobile, 24, 25
 Engineering:
 nanoscale, *see* Nanoscale engineering
 thermofluid, *see* Thermofluid engineering
 Engineering mechanics, 109–178
 finite element stress analysis, 173–178
 fracture mechanics, 165–171
 mechanical vibration, 119–149
 static bending of thin plates, 110–119
 thermomechanics, 150–165

- thin-film mechanics, 172–173
units used in, 110
- Engineering science, 83–105
atomic structure of matter, 83–86
diffusion process, 92–99
doping of semiconductors, 89–92
electrochemistry, 100–105
ions/ionization, 86–87
molecular theory of matter/intermolecular forces, 87–89
plasma physics, 99–100
- Enhanced chemical vapor deposition, 310–311
- ENIAC (Electronic Numerical Integrator and Calculator), 16–18
- Environment, nanoproducts and, 477
- Environmental conditions, as design constraint, 351–352
- Environmental effects, failure due to, 456
- Epitaxial casting, 474
- Epitaxial deposition, 313–315, 317, 361
- Epoxy, 445
- Epoxy resin, 446
- Epoxy resin bonds, 430, 439
- Equation of motion, 192–195
- Error function, 96
- Etchants, 316
plasma-gas, 330
selectivity ratios of, 327
wet, 326–328
- Etching, 10, 11, 315–318, 324–333
chemical, 316–317
deep reactive ion, 331–333
dry, 329–333
ideal/undercutting/under-, 327
isotropic/anisotropic, 325–326
overview of, 324
plasma, 317, 329–330
of polysilicon by RIE, 401
stopping techniques for, 328–329
wet, 326–328
wet vs. dry, 333
- Etch rates, 326, 336
- Etch stop, 89, 328–329
- Ethanol, 76
- Ethylene-diamine and pyrocatecol (EDP)
etchant, 326, 327
- Euler's equation, 193
- European Community, 30
- Eutectic alloy, 431, 432
- Eutectic bonding, 431–432
- Eutectic solders, 431
- Eutectic temperature, 431
- Examples, presentation of, xxiv–xxv
- Excitation, 100
- Excitation force, frequency of, 123
- Expansion, thermal, 152
- F**
- Fabrication:
of masks, 359
micro-, *see* Microfabrication
- Fabrication database, 395–397
- Fabrication facility, 352
- Face-centered cubic (FCC), 251
- Failure:
AP&T as source of, 407
in MEMS/microsystems, 456
thermomechanical, 423
- Fairchild Semiconductors, 11
- Faraday's law, 236
- Fastening, 411
- FCC (face-centered cubic), 251
- FEA, *see* Finite element analysis
- Feeding, part, 411
- FEM, *see* Finite element method
- FE (finite element) mesh, 375
- Ferroelectric polymer thin films, 277
- Ferromagnets, 501
- Feynman, Richard, 465–466, 478
- Fibers, insertion of conductive, 276
- Fick's law, 92, 293
- Field-assisted thermal bonding, 432
- Final testing, 457
- "Fingers," 36, 415, 416
- Finite element analysis (FEA), 173–178
and CAD, 395, 402
considerations for, 176–178
engineering applications of, 175
formulation of finite element, 370–375
graphical output from, 176
input information to, 175
for mechanical design, 369–377
output from, 175–176
principle of, 173–174
simulation of microfabrication process, 375–377
- Finite element (FE) mesh, 375
- Finite element method (FEM), 369–375
considerations for using, 176–178
derivation of element equations, 372–373

- Finite element method (FEM), (*Continued*)
 discretization, 370–372
 Galerkin method, 373–374
 principle of, 173
 Rayleigh–Ritz method, 374–375
 rules of, 174
- Fixtures, microassembly, 416
- Flowchart, CAD, 396, 397
- Flow patterns, 187
- Fluids, interaction of solids and, 209–210
- Fluid dynamics, 184
 computational, 198–199
 continuum, 187–195
 finite element method applied to, 175
- Fluid flow, 12
 incompressible, 199–204
 Knudsen/Mach numbers, 482–483
 in microconduits, 199–204
 modeling of, 483–485
 rarefaction, 482
 in submicrometer-/nanoscales, 482–485
- Fluid mechanics, 110, 184–187
 control volumes/control surfaces, 187
 flow patterns/Reynolds number, 187
 at macro-/mesoscales, 184–187
 scaling in, 238–242
 streamlines/stream tubes, 186
 viscosity of fluids, 184–186
- Fluid resistance, 383–386
- Fluid statics, 184
- Fluorescence detectors, 388
- Fluoropolymers, 332, 333
- Flux:
 heat, 205–206, 210–212, 242
 ion, 94
- Fo (Fourier number), 243
- Force-balanced microaccelerometers:
 basic structure of, 131–132
 damping of, 139
- Force scaling vector, 231
- Fourier law of heat conduction, 205–206
- Fourier number (Fo), 243
- Fracture analysis, interfacial, 369
- Fracture mechanics, 165–171
 interfacial, 169–171
 stress intensity factors, 166–167
 toughness, fracture, 167–169
- Fracture toughness, 167–169
- Free atoms or molecules, 470, 471
- Free vibrating beam, 146
- Frequency:
 of excitation force, 123
 of vibrating mass, 120
- Front-side pressurization, 44, 45
- Fuel cells, 476, 477
- Fuller, Richard Buckminster, 471
- G**
- GaAs, *see* Gallium arsenide
- Gage pressure sensors, 44
- Galerkin method, 373–374
- Gallium:
 atomic/ionic radii of, 306
 diffusion coefficient of, 95
 as dopant, 291
- Gallium arsenide (GaAs), 11, 266–267
 as active substrate material, 247, 353
 electrical resistivity of, 90, 246
 electron mobility of, 266
 mechanical/thermophysical properties of, 257
 and microsystems design, 353
 plasma gas etchants for, 330
 quantum efficiency of, 44
 silicon vs., 267
- Gallium nitride, 474, 478
- Gallium phosphide, 90, 246
- Gases:
 physical behaviors of molecular, 89
 rarefied, 482
- Gas flow:
 modeling of micro-/nanoscale, 483–485
 spectrum of regimes for, 483
- Gears, 7, 8, 12
- Gear train, 410
- Geodesic dome, 471
- Geometric tolerances, 414–416
- Geometry:
 of MEMS components, 362
 scaling in, 228–230
 and size of die, 379–380
- Geometry shaping, 362
- Gerber, Christoph, 468
- Germanium:
 as active substrate material, 247
 atomic/ionic radii of, 306
 electrical conductivity of, 276
 electrical resistivity of, 90, 246
 mechanical/thermophysical properties of, 257
- Glass, 11, 90, 246, 276
- Glucose sensors, 38

Gold, 339, 340, 432, 437
 Grashoff number (Gr), 207, 208
 Grasping, part, 411
 Gravitational acceleration, 110
 Grippers:
 micro-, 3, 4, 59–62, 417–419
 photolithography of, 401
 separation of substrate and, 401
 Gripping force, 418
 Gyroscopes, micro-, 70–72

H

Hanke, Wilhelm, 55
 Headers, packaging materials for, 445
 Head loss, 195, 197
 Health care industry, 27–28, 502, 503
 Heat capacity, 228
 Heat carriers, 488
 Heat conduction, 486–491
 and boundary conditions, 210–215
 equation for, 207, 490–491
 Fourier law of, 205–206
 general principle of, 204–205
 in multilayered thin films, 215–220
 at nanoscale, 220–221, 486–489
 and Newton's cooling law, 208–209
 scaling in, 242–243
 and solid–fluid interaction, 209–210
 in solids, 204–215, 220–221
 in thin films, 489–491
 Heat conduction analysis, 175
 Heat conduction equation, 207, 490–491
 Heat convection, 243–244
 Heat flux, 205–206, 210–212, 242
 Heat pipes, micro-, 75–77
 Heat sink, 76
 Heat transfer coefficient, 207
 Heat transfer scaling, 242–244
 Helium, 87, 138, 306
 Hermetic seals, 439
 HF (hydrofluoric) solution, 316
 High-aspect-ratio microstructures, 17, 18
 High-aspect-ratio processes, 355
 High-precision transfer tool, 421
 HNA etchant, 326, 328
 Hoffmann, Ronald, 466
 Homologous melting point, 150
 Hoop stress, 112
 Horizontal epitaxy deposition reactor, 314
 Hot embossing lithography, 498

Hydration process, 434, 435
 Hydrazine etchant, 326, 327
 Hydrofluoric (HF) solution, 316
 Hydrogen:
 atomic/ionic radii of, 306
 atomic structure of, 83–85
 in epitaxial deposition, 313–315
 viscosity of, 304
 Hydrogen bonding, 338
 Hydrogen chloride, 313, 315
 Hydrogen gas, 87
 Hydrophilic process, 434

I

IBM, 468, 469
 IBM-Watson Research Center, 278
 IC chips, *see* Integrated circuit chips
 Ideal gas law, 305
 IDT (interdigital transducer), 37
 Imaging unit stereomicroscopes, 420
 Imperial Museum of Arts (Taipei, Taiwan), 324
 Incompressible fluid flow, 199–204
 capillary effect, 201–203
 laminar, 187
 micropumping, 203–204
 surface tension, 199–201
 Indirect pressure transmission, 453–456
 Indium, 291
 Industrial engineering, 15
 Industrial materials, polymers as, 274–275
 Industrial products, 29
 Inertia:
 mass moment of, 230
 mechanical, 66–72
 thermal, 228
 Inertia forces, 364
 Inertial guidance systems, 28
 Inertia sensors, 3–6, 66, 68
 Infrared (IR) sensors, 411
 Infusion pump pressure sensors, 28
 Injection channels, 386–387
 Injection cycle, 391
 Inkjet printer head, 53
 In-packaged microaligner, 416
 Insitu bitumen extraction, 477
 Instructors, suggestions to, xxiii–xxv
 Insulated boundary condition, 215
 Insulators:
 and atomic structure, 84
 bonding silicon onto, 435–437

Insulators: (*Continued*)

- electrical resistivities of, 90, 246
- packaging materials for, 445
- resistivity of, 246
- Integrated circuit (IC) chips:
 - accelerometers on, 4
 - fabrication technology for, 11
- Integrated encapsulation, 440–441
- Integrated micropositioner, 420
- IntelliCad, 395
- Intelligent end effectors, 421
- Intelligent microsystems, 5
- IntelliSense Corporation, 395
- IntelliSuite, 395, 398–400
- Interconnect pins, 445
- Interdigital transducer (IDT), 37
- Interfaces:
 - in microsystems packaging, 427–428
 - problems with, 426
- Interfacial fracture analysis, 369
- Interfacial fracture mechanics, 169–171
- Interfacial stresses, 336, 337
- Intermolecular forces, 87–89, 479
- International System (SI), 110
- Interpolation function, 371
- Intrauterine pressure sensors (IUPs), 27
- Intrinsic stresses, 172–173, 364, 456
- Ion–dipole interaction, 89
- Ion etching, deep reactive, 331–333
- Ion flux, 94
- Ion implantation, 289–292, 361
- Ion-implanted silicon dioxide, 336
- Ion-induced dipole interaction, 89
- Ion–ion interaction, 89
- Ionization, 86–87, 99
- Ionization energy, 87
- Ion mobility, 387
- Ions, 86–87
- I/O ports, 12
- Iron, 306
- IR (infrared) sensors, 411
- Isolation, of atoms and molecules, 468–470
- Isotropic etching, 11, 316, 325
- IT peripherals, 30–32
- IUPs (intrauterine pressure sensors), 27

K

- Karlsruhe Nuclear Research Center, 339
- Kerosene, 138
- kg (kilogram), 110

- Kilby, Jack, 11
- Kilogram (kg), 110
- Kinematic viscosity, 185
- Kinetic energy, 88–89
- Kinetics of thermal oxidation, 297
- Knudsen number (Kn), 482–483
- Kodak, 287
- KOH etchant, *see* Potassium hydroxide etchant
- Kroto, Harry, 471
- KTFR, 287

L

- Lab-on-the-chip concept, 6, 15, 444
- Lag time, 490
- Laminar fluid flow, 187, 195–197
- Langmuir–Blodgett (LB) film, 277–278
- Lao-Tze, vi
- Laptop computers, 17, 18
- Laser ablation, 474
- Lattices, 87, 251
- LB film, *see* Langmuir–Blodgett film
- Lead zirconate titanate, 270
- LEFM, *see* Linear elastic fracture mechanics
- Lenses, 7, 10
- LIGA process, *see* Lithographie Galvanoformung Abformung process
- Light, 12, 288–289
- Linear elastic fracture mechanics (LEFM), 165–167
- Linear rate constant, 298, 299
- Liquids, physical behaviors of molecular, 89
- Lithium, 44, 84, 85
- Lithiumion batteries, 476
- Lithographie Galvanoformung Abformung (LIGA) process, 11, 338–343
 - advantages of, 339
 - description, 339–340
 - design/selection of, 355
 - electroplating step in, 341–342
 - high-aspect-ratio microstructures manufactured by, 17, 18
 - microgears produced using, 7, 8
 - photoresist materials for, 341
 - sacrificial, 342–343
 - simulation of, 375–376
 - substrate materials for, 340–341
- Lithography:
 - photo-, *see* Photolithography
 - x-ray, 339–341
- Localized CVD sealing, 443

- Loose atoms or molecules, 470
 Low-pressure CVD (LPCVD), 260, 310, 311, 400
 Lucas NovaSensor, 454
- M**
- Mach number (Ma), 483
 Magnets, nano-, 501
 Magnetic induction, 19
 Magnification, 417
 Manifold absolute pressure (MAP), 21, 24, 48
 Manufacturing:
 design/selection of process for, 354–355
 of ICs/microelectronics, 13
 micro-, *see* Micromanufacturing
 Manufacturing process sensors, 29
 MAP, *see* Manifold absolute pressure
 Mapping, signal, *see* Signal mapping
 Market(s):
 for microsystems, 30–32
 time-to-, 351, 395
Mark's Standard Handbook for Mechanical Engineers (Avalone and Baumeister), 137
 Mask(s):
 design of, 359, 360
 in diffusion, 94
 in microfabrication, 318
 in surface micromachining, 336
 in wet etching, 324, 327
 for x-ray, 339, 340
 Masking, 316
 Mass, 66, 119
 Massachusetts Institute of Technology (MIT), 395
 Mass flow rate, 188
 Mass matrix, 145
 Mass moment of inertia, 230
 Mass–spring, 119
 Mass–spring–dashpot, 119
 Material(s), 11, 245–281
 active substrate, 247
 and CAD, 398
 deterioration of, 456
 gallium arsenide, 266–267
 for nanoelectromechanical systems, 500–501
 packaging, 280–281
 piezoelectric crystals, 268–274
 polymers, 274–280
 quartz, 267–268
 selection of, 352–354
 silicon, 247–258
 silicon compounds, 258–261
 silicon piezoresistors, 261–266
 for substrates/wafers, 245–247
 thermal effects on mechanical strength of, 150
 Material science, 421–422
 Materials database, 395–397
 Materials engineering, 15
 MATHCAD, 219
 Mathematical modeling, 388–389
 Matter:
 atomic structure of, 83–86
 molecular theory of, 87–89
 Mauchly, John, 16
 MBE (molecular beam epitaxy), 313
 MCMs (multichip modules), 443
 Mean free path (MFP), 137, 482, 487
 Mean free time (MFT), 487
 Mechanics:
 defined, 109
 fracture, *see* Fracture mechanics
 thermo-, *see* Thermomechanics
 thin-film, 172–173
 Mechanical design, 362–379
 dynamic analysis, 364–369
 finite element method for, 369–377
 geometry of MEMS components, 362
 interfacial fracture analysis, 369
 thermomechanical loading, 362–363
 thermomechanical stress analysis, 363–364
 Mechanical engineering principles, 14–15
 Mechanical failure, 456
 Mechanical inertia, 66–72
 Mechanical interfaces, 428
 Mechanical properties, 256–258
 Mechanical strength, 150
 Mechanical vibration, 119–149
 damping coefficients, 134–144
 design theory of accelerometers, 126–134
 general formulation, 119–123
 microaccelerometers, 125–126
 resonant microsensors, 144–149
 resonant vibration, 123–125
 MEMS, *see* Microelectrical mechanical systems
 MEMS with microactuators, 59–66
 microgripper, 59–62
 micromotor, 64–66
 microphone, 61, 63–64
 MEMCAD, 395
 MEMSCaP, 395

- MEMSPro, 395
MEMS products, market growth for, 31
Mercury, 477
Mercury vapor lamp, 288
Mesoscales, 3
Metals, 11
Metal films, 295
Metallic materials, 11
Metal organic CVD (MOCVD), 313
Metal oxide gas sensors, 41–42
Meter, 110
Meters per square second (m/s^2), 110
Methanol, 76
MFP, *see* Mean free path
MFT (mean free time), 487
Microaccelerometers, 3–5, 66–69
 design theory of, 126–134
 die-level packaging of, 426
 mechanical vibration in, 125–126
Microactuation, 53–59
 electrostatic-force, 55–59
 piezoelectric-effect, 54, 55
 shape-memory-alloy, 54
 thermal-force, 53–54
Microactuators, 3, 59–66
 with mechanical inertia, 66–72
 microaccelerometer, 66–69
 microgripper, 59–62
 microgyroscope, 70–72
 micromotor, 64–66
 microphone, 61, 63–64
Microassembly, 409–422
 contact problems in tools for, 416–419
 costs of, 410–411
 issues in, 421–422
 overview of, 409
 problems in, 413–419
 processes of, 411–413
 tolerances in, 414–416
 tools/fixtures for, 416
 volume of, 409
 work cells in, 419–421
Microassembly processes, 411–413
 encapsulation/passivation, 411
 lack of established, 410
 part bonding/fastening, 411
 part feeding, 411
 part grasping, 411
 part mating, 411
 sensing/verification, 411–413
Microassembly work cells, 419–421
Micro-biomedical sensors, 2
Micro-cantilever beams, 334–336
Microcars, 19–20
Microchannels:
 fluid resistance in, 383–386
 in microfluidics, 72–73
Micro Chem Corporation, 278
Microconduits, incompressible fluid flow in,
 199–204
Microcosm Technologies, 395
Microdamping in shear, 137–144
Microelectrical mechanical systems (MEMS):
 components of, 1–3
 demand for, xix
 failure mechanisms in, 456
 geometry of components in, 362
 with microactuators, *see* MEMS with
 microactuators
 packaging reliability in, 455–456
 polymers for, 275
Microelectronics, microsystems vs., 11–13
Microfabrication, 285–318
 chemical vapor deposition, 301–311
 diffusion, 292–295
 epitaxy, deposition by, 313–315
 etching, 315–317
 evolution of, 10–11
 ion implantation, 289–292
 oxidation, 295–301
 photolithography, 285–289
 physical vapor deposition/sputtering,
 312–313
 simulation of, 375–377
Microfluids, 102, 105
Microfluidic network systems, 382–394
 capillary electrophoresis, 386–392
 capillary electrophoresis in curved channels,
 392–394
 design case, 389–392
 and fluid resistance in microchannels,
 383–386
 issues in design of CE processes, 394
 mathematical modeling of, 388–389
Microfluidic systems, 72–77
 advantages of, 72
 components of, 72–73
 interfaces in, 428
 micro-heat pipe, 75–77
 micropump, 75, 76

- microvalve, 74–75
- Microgears, 7, 8
- Microgrippers, 3, 4, 59–62, 365–369, 417–419
- Microgyroscopes, 70–72
- Micro-heat pipes, 75–77
- Micro-inertia sensors, 3–6
- Microlithography, *see* Photolithography
- Micromachining, 10–11, 323
 - bulk, *see* Bulk micromachining
 - of silicon, 325–326
 - silicon-based, 338–339
 - surface, *see* Surface micromachining
- Micromanipulators, 420–421
- Micromanufacturing, 323–343
 - bulk, 324–333, 343
 - defined, 323
 - LIGA process, 338–343
 - surface micromachining, 333–338, 343
- Micromechatronics systems, 15
- Micromirrors, 229–230
- Micromotors, 7, 9, 64–66
- Micro-optical components, 7, 10
- Micro-optical systems, 12
- Micro-O-rings, 440
- Microphones, miniature, 61, 63–64
- Micropositioner, 420
- Micro-pressure sensors, 44–50
 - assembly of, 46
 - bridge for capacitance measurements in, 48
 - capacitance signal transduction in, 47
 - costs of, 407
 - cross sections of, 45
 - manifold absolute pressure sensor with capacitor transducer, 48
 - nonlinear output of, 49
 - silicon die of, 378–382
 - with vibrating beam signal transducer, 50
- Micro-pressure sensor packages, 2
- Microprocessor control components, 26
- Micropropulsion systems, 29
- Micropumps, 75, 76
- Micropumping, 203–204
- Microrotary motors, 65–66
- Microscale technologies, 467–468
- Microscopes, 413–414, 417, 420
- Microscope optics, 420
- Microsculptures, 324
- Microsensor(s), 1–3, 35–53
 - acoustic wave, 36–37
 - advantages of, 1
 - biomedical/bio-, 37–40
 - chemical, 40–42
 - defined, 35
 - LB-film in, 277
 - in microfluidics, 72
 - optical, 42–44
 - pressure, 44–50
 - resonant, 144–149
 - thermal, 50–53
 - and transduction units, 3
 - types of, 1, 2
- Microshells, 441
- Microsystems, failure mechanisms in, 456
- Microsystems design, 349–402
 - computer-aided, 395–402
 - considerations in, 350–358
 - constraints on, 351–352
 - of electromechanical system, 358
 - and manufacturing-process selection, 354–355
 - and material selection, 352–354
 - of mechanicals, 362–377
 - of microfluidic network systems, 382–394
 - and packaging, 358
 - of process, 358–362
 - and signal-transduction selection, 355–357
 - of silicon die of micropressure sensor, 378–382
- Microsystems packaging, 422–456
 - considerations in, 424, 452–453
 - design case on, 451–455
 - device-level, 425–426
 - die-level, 424–426
 - die preparation for, 429
 - interfaces in, 427–428
 - levels of, 424, 425
 - material selection for, 444–446
 - need for, 408, 409
 - overview of, 422–423
 - reliability in, 455–456
 - sealing/encapsulation in, 439–443
 - and signal mapping/transduction, 447–451
 - surface bonding in, 429–437
 - system-level, 427
 - technologies for, 428–443
 - three-dimensional, 443–444
 - wire bonding in, 437–439
- Microsystem technology (MST), 1–32
 - aerospace applications of, 28–29
 - assembly of, *see* Microassembly

- Microsystem technology (MST), (*Continued*)
 automotive applications of, 21–27
 components of, 3, 4
 consumer products applications of, 29
 defined, 3
 design/manufacture of, 13–15
 health-care applications of, 27–28
 industrial products applications of, 29
 intelligent, 5
 lab-on-the-chip concept of, 6
 markets for, 30–32
 microelectronics vs., 11–13
 and microfabrication, 10–11
 microgear, 7, 8
 micromotor, 7, 9
 micro-optical component, 7, 10
 microturbine, 7, 9
 and miniaturization, 15–20
 nanotechnology vs., 467–468
 packaging of, *see* Microsystems packaging
 polymers for, 275
 revenue in, xix
 scale of, 3
 telecommunications applications of, 30
- Microthermopiles, 51–53
 Microtribology, 66
 Microturbines, 7, 9
 Microtweezers, 417
 Microvalves, 12, 74–75
 Miller indices, 253–256
 Miniature microphones, 61, 63–64
 Miniaturization, 15–20
 need for, 15
 scaling laws in, 227–244
 "Miniaturized" ENIAC, 17, 18
 MIT (Massachusetts Institute of Technology), 395
 Mobile phones, 19
 Mobile telecommunications equipment, 18–19
 MOCVD (metal organic CVD), 313
 Modal analysis, 124
 Modes, of vibration, 124
 Modeling:
 mathematical, 388–389
 of micro-/nanoscale gas flow, 483–485
 nanoscale analytical, 501–502
 process, 422
 Mode number, of vibration, 149
 Molar mass, 305
 Molecular beam epitaxy (MBE), 313
 Molecular biology, 13
 Molecular dynamics, 479–481
 Molecular electronics, 476
 Molecular physics, 14
 Molecular theory of matter, 87–89
 Molecule(s):
 assembly of loose, 470
 defined, 87
 fluid, 184
 isolation of, 468–470
 physical behaviors of, 89
 rebonding of free, 470, 471
 Momentum equation, 190–192
 Monolithic circuit, 11
 Motion:
 defined, 109
 equation of, 192–195
 Motors:
 micro, 7, 9
 micro-, 64–66
 Moving parts, 12
 m/s² (meters per square second), 110
 MST, *see* Microsystem technology
 Multichip modules (MCMs), 443
 Multilayers:
 fracture analysis in, 369
 fracture mechanics in, 169–171
 heat conduction in, 215–220
 temperature stress in, 153–157
- N**
- N (newton), 110
 Nanoassembly, 500
 Nanoelectromechanical devices, 477
 Nanoelectromechanical systems (NEMS), 468, 500–501
 Nanofabrication:
 nanopatterning in, 498–500
 principle of, 468–471
 Nanoimprint lithography (NIL), 498–499
 Nanomagnets, 501
 Nanometer (nm), 15
 Nanoparticles, 472, 477
 Nanopatterning, 498–500
 Nanoproducts, 471–474
 applications of, 474–478
 in biomedicine, 475
 buckyballs, 471
 in energy, 476–477
 in environment, 477

- in molecular electronics, 476
 - nanoparticles, 472
 - in nanostructures, 478
 - nanotubes, 472–474
 - nanowires, 472
 - in optoelectronics/electromechanical devices, 477
 - properties of, 475
 - in surface coatings, 477
 - Nanoscale engineering, 465–503
 - and analytical modeling, 501–502
 - challenges in, 497–502
 - and fluid flow, 482–485
 - and heat conduction, 486–491
 - and materials, 500–501
 - and micro- vs. nanoscale technologies, 467–468
 - and molecular dynamics, 479–481
 - and nanoassembly, 500
 - and nanopatterning, 498–500
 - and nanoproducts, 471–474
 - principle of, 468–471
 - and quantum physics, 478–479
 - social impacts of, 502–503
 - and testing, 502
 - Nanotechnology (NT):
 - defined, 465
 - microsystem technology vs., 467–468
 - revenues generated by, 466
 - Nanotubes, 472–474, 478
 - Nanowires, 472
 - National Science Foundation, 466
 - Natural frequency, 120, 121, 124, 131, 145, 364
 - Navier–Stokes equations, 198, 483
 - Navigation systems, 22
 - N*-crystalline silicon, 42, 44
 - Negative resists, 286, 287, 289
 - NEMS, *see* Nanoelectromechanical systems
 - Neomicrosculpt, 324
 - Network of Excellence in Multifunctional Microsystems, 30
 - Network systems:
 - capillary electrophoresis, *see* Capillary electrophoresis network systems
 - microfluidic, *see* Microfluidic network systems
 - Neutrons, 83–85
 - Newton (N), 110
 - Newtonian fluids, 185, 186
 - Newton's cooling law, 208–209
 - Newton's law of dynamic force equilibrium, 127
 - Newton's second law, 119
 - NEXUS, 30
 - Nickel, 90, 246, 306
 - NIL, *see* Nanoimprint lithography
 - Nitrogen, 138, 304, 306
 - nm (nanometer), 15
 - Nodes, 173
 - Noncompressible fluids, 138
 - Non-slip boundary condition, 184–185
 - Normal thermal force, 159
 - Noyce, Robert, 11
 - NT, *see* Nanotechnology
 - N*-type semiconductors, 90–92
 - Nu (Nusselt number), 207
 - Nucleus, 83–85
 - Numerical solution, of temperature distribution, 163–165
 - Nusselt number (Nu), 207
 - Nylon, 276
- O**
- Object avoidance systems, 22
 - Obround tubes, 383
 - Oil-filled stainless diaphragm, 454–455
 - Opening mode, 166
 - Operating pressures, 381
 - Operating temperature, 382
 - Optical interfaces, 427–428
 - Optical microgyroscopes, 70
 - Optical sensors, 42–44
 - Optical switches, 7, 10
 - Optoelectronics, 477
 - Orbits, electron, 83–86
 - Organic alloys, 275
 - Oscillations, 478–480
 - Outward normal line, 209
 - Overdamping, 122
 - Overlay accuracy, 499
 - Overpressures, 382
 - Oxidation, 295–301
 - color, oxide thickness by, 300–301
 - rates of thermal, 296–300
 - residual stress/strain during/after, 337
 - and silicon dioxide, 296
 - thermal, 295–301
 - in thin-film fabrication, 361

- Oxides:
 color as indicators of thickness of, 300–301
 electrical resistivity of, 90, 246
- Oxygen, 304, 306
- P**
- Pa (pascal), 110
- Packaging:
 design factors of, 358
 failure due to, 456
 of ICs/microelectronics, 13
 microsystems, *see* Microsystems packaging
- Packaging materials, 11
 for MEMS/microsystems, 280–281
 properties of, 445
 selection of, 354, 444–446
 temperature-dependent properties of, 446
- Packaging technologies, 428–443
 die preparation, 429
 sealing/encapsulation, 439–443
 surface bonding, 429–437
 wire bonding, 437–439
- Paints, 477
- Palladium, 437
- Parabolic rate constant, 298, 299
- Parallel microassembly, 412–413
- Parallel plates, 56–59, 233–235
- Parametric testing, 457
- Parasite stresses, 452
- Part bonding, 411
- Part feeding, 411
- Part grasping, 411
- Particular solution (PS), 127
- Part insertion, 421
- Part mating, 411
- Parylene, 453
- PAS (polyalkensulfone), 341
- Pascal (Pa), 110
- Paschen effect, 233, 234
- Passivation, 378, 411
- Passive substrate materials, 352
- Pattern design, 359, 360
- Patterning, nano-, 498–500
- P*-crystalline silicon, 42, 44
- PDA's (personal digital assistants), 19
- PECVD, *see* Plasma-enhanced CVD
- Peeling stress, 437
- Periodic table, 85
- Personal digital assistants (PDAs), 19
- Phenolic novolak resin, 287
- Phonons, 221, 479, 486–489
- Phonon scattering, 487
- Phosphorus, 91, 92
 atomic/ionic radii of, 306
 diffusion coefficient of, 95
 diffusivity of, 294
 as dopant, 96–98, 291
 ion implantation of, 291
 solid solubility of, 94
- Phosphosilicate glass (PSG), 335, 336
- Photolithography, 285–289, 498–499
 of grippers, 401
 light sources, 288–289
 photoresist development, 289
 photoresist removal/postbaking, 289
 photoresists, 286–288
 process design of, 359–360
 by UV exposure, 400
- Photons, 479
- Photoresist(s), 286–288
 application of, 400
 deposition of, 401
 development of, 289
 in DRIE process, 332
 in LIGA process, 341
 light sources for, 288–289
 materials for, 318, 332, 341
 positive/negative, 287
 postbaking of, 289
 removal of, 289, 400, 401
 SU-8, 278–280
- Photovoltaic (PV) cells, 476–477
- Phthalocyanine, 40
- Physical deposition, 317–318
- Physical size, 352
- Physical vapor deposition (PVD), 301, 312–313
- Piezoelectric coefficients, 270
- Piezoelectric crystals, 268–274, 500–501
- Piezoelectric effect, 54, 55, 268–269
- Piezoelectric force, 363
- Piezoelectricity, 55, 363
- Piezoelectric materials, 357, 447
- Piezoelectric pumping, 203–204, 241–242
- Piezopumps, 75
- Piezoresistance, 261
- Piezoresistive coefficient matrix, 262
- Piezoresistive coefficients, 263, 264
- Piezoresistive transducer (PRT) pressure sensors, 24

- Piezoresistors:
 drawback of, 265
 and microsystems design, 356
 for signal mapping/transduction, 448–451
 silicon, 261–266
 as transducers, 356, 447
- Pinched loading technique, 392
- Pipes, micro-heat, 75–77
- Planar packaging, 444
- Planck, Maxwell, 478, 479
- Planck's constant, 478
- Plasma, 99
- Plasma-enhanced CVD (PECVD), 260, 310–311
- Plasma etching, 317, 318, 329–330
- Plasma physics, 13, 99–100
- Plastic passivation, 407
- Plastics, 11
- Plates, 362
- Plate springs, 362
- Platinum, 90, 246
- PLG (polylactide-co-glycolide), 341
- PMI (polymethacrylimide), 341
- PMMA, *see* Polymethyl methacrylate
- P-n* junctions, 89
- Poisson's ratio, 261
- Polyalkensulfone (PAS), 341
- Polychlorinated biphenols, 477
- Polycrystalline silicon:
 in chemical vapor deposition, 303
 CVD in, 303
 and microsystems design, 354
 properties of, 260–261
 as substrate material, 354
 in thermal oxidation, 295
- Polyethylene, 276
- Polylactide-co-glycolide (PLG), 341
- Polymers, 11, 274–280
 conductive, 275–276
 in DRIE process, 332
 as industrial materials, 274–275
 Langmuir–Blodgett polymer film, 277–278
 for MEMS/microsystems, 275
 and microsystems design, 353
 SU-8 photoresist, 278–280
 as substrate material, 353
- Polymer coating, selection of, 500
- Polymethacrylimide (PMI), 341
- Polymethyl methacrylate (PMMA), 7
 as LIGA photoresist, 341
 as positive photoresist, 287
 as x-ray photoresist, 339–340
- Polyoxymethylene (POM), 341
- Polysilicon:
 LPCVD deposition of, 400
 mechanical properties of, 261
 plasma gas etchants for, 330
 RIE etching of, 401
- Polyvinylidene fluoride (PVDF), 270, 277
- POM (polyoxymethylene), 341
- Positioner, micro-, 420
- Positive resists, 286, 287, 289
- Postbaking, 289
- Potassium, 44
- Potassium hydroxide (KOH) etchant, 316, 326, 327
- Potential energy, 374
- Power density scaling, 232
- Power systems, aerospace, 29
- Power trains, automobile, 24
- Prandtl number (Pr), 207, 208
- Prescribed heat flux at boundary, 210–212
- Prescribed surface temperature, 210, 211
- Pressure, operating, 381
- Pressure drop, 241
- Pressure sensors, 1, 44–50
 in automobiles, 21, 23
 packaging of, 451–455
 signal mapping/transduction in, 448–451
- Primary creep, 151
- Primary flats, 255–256
- Primary unknown quantities, 371, 372
- Process design, 358–362
 of geometry shaping, 362
 of photolithography, 359–360
 of thin-film fabrications, 360–361
- Process flow table, 397
- Process modeling, 422
- Process pressure transmitters, 29
- Proof mass, 68, 69, 125, 126, 137
- Propulsion systems, 29
- Protons, 83–86
- PRT (piezoresistive transducer) pressure sensors, 24
- PS (particular solution), 127
- Pseudoelements, 375
- PSG, *see* Phosphosilicate glass
- P*-type semiconductors, 90, 91
- Pumps, 12, 75, 76

- Pumping:
 electrohydrodynamic, 100–105
 electro-osmotic, 103–105
 electrophoretic, 105
 micro-, 203–204
 piezoelectric, 203–204, 241–242
 surface, 228
- PV cells, *see* Photovoltaic cells
 PVD, *see* Physical vapor deposition
 PVDF, *see* Polyvinylidene fluoride
 Pyrex glass, 44, 432, 433, 452
 Pyrolysis, 276, 303, 313, 472
 PZT piezoelectric material, 357, 500
- Q**
- Quantum dots, 472
 Quantum efficiency, 44
 Quantum physics, 14, 478–479
 Quartz, 11, 267–268
 and acoustic wave sensors, 36
 as active substrate material, 247, 353
 electrical resistivity of, 90, 246
 mechanical/thermophysical properties of, 257
 and microsystems design, 353
 piezoelectric coefficient of, 270
 properties of, 268
 Quate, Calvin, 468
- R**
- Radar systems, 29
 Radial stress, 112
 Range of acceptable device performance, 457
 Rapid thermal processing (RTP) bonding, 442, 443
 Rarefaction, 482
 Rarefaction coefficient, 485
 Rayleigh–Ritz method, 374–375
 RCA, 11
 Re, *see* Reynolds number
 Reactants, 317
 Reactive neutrals, 329
 Reactive sealing, 441
 Real-time computer, 421
 Rebonding, 470–471
 Recombination, 100
 Rectangular channels, 383, 386
 Rectangular plates:
 deflection with lateral bending of, 110–111
 static bending of, 114–115
 Relative permittivity, 46–47
- Relaxation time, 491
 Reliability:
 of delivery, 421
 in MEMS packaging, 455–456
 of microsystems packaging, 422
 Reliability testing, 456–458
 during assembly, 457
 burn-in and final, 457
 parametric testing, 457
 range of acceptable device performance, 457
 self-testing, 457–458
 during use, 458
 Replication, 500
 Repulsion, 88
 Residual stresses, 172, 173, 337
 Resist, selection of polymer, 500
 Resistance, 383–386
 Resistance measurements, 45, 447, 448
 Resistive power loss, 237
 Resistivity, electrical, 90, 246, 263
 Resonant microsensors, 144–149
 Resonant vibration, 123–125, 357, 364
 Reversed sputtering, 330
 Reynolds number (Re), 187, 207
 RF plasma, 310
 Rhombus tubes, 383
 RIE, 401
 Rigid-body dynamics, 230–233
 Rochelle salt, 270
 Rohrer, Heinrich, 469
 Room temperature vulcanizing (RTV) silicone rubber, 281, 430, 445
 Rotary motors, 65–66
 Rotational microgyroscopes, 70
 Rotor poles, 66
 Rotors, 7
 RTP bonding, *see* Rapid thermal processing bonding
 RTV silicone rubber, *see* Room temperature vulcanizing silicone rubber
 Rubidium, 44
- S**
- Sacrificial components, 335, 336
 Sacrificial layers, 334, 401
 Sacrificial LIGA (SLIGA) process, 342–343, 355
 Sample loading, 392
 Sample plug, 387
 Sample separation, 392

- Sandia National Laboratory, 411, 412, 419
 SAW, *see* Surface acoustic wave
 Scaling, 227–244
 in electricity, 237–238
 of electromagnetic forces, 235–237
 in electrostatic forces, 233–235
 in fluid mechanics, 238–242
 in geometry, 228–230
 in heat transfer, 242–244
 in rigid-body dynamics, 230–233
 Scaling laws, 14, 227–244
 Scanning atomic force microscope, 469, 496–497
 Scanning thermal microscopy method, 496–497
 Scanning tunneling microscope (STM), 469, 470
 SCAP sensors, *see* Silicon capacitive absolute pressure sensors
 Scattering, phonon, 487
 Schockley, W., 11
 Schrödinger equation, 481
 Sculpture, 324
 Sealing:
 and encapsulation, 439–443
 by localized CVD process, 443
 by microshells, 441
 reactive, 441
 by RTP bonding, 442, 443
 vacuum, 442–443
 by wafer bonding, 441–442
 Secondary flats, 255–256
 Seebeck, T. J., 50
 Seebeck coefficient, 50, 51
 Seebeck effect, 50
 Segway Human Transporters, 70
 Seismic mass, 125, 126
 Selectivity ratios of etchants, 327
 S-elements, 376, 377
 Self-assembly, 412, 500
 Self-orienting fluidic transport (SOFT), 412
 Self-testing, 457–458
 Semiconductors:
 doping of, 89–92
 electrical resistivities of, 90, 246
 heat conductivity measurement in, 492–493
 resistivity of, 246
 Sensing, 411–413, 421
 Sensors:
 in automobiles, 21–23, 27
 in industrial products, 29
 micro-, *see* Microsensor(s)
 Separation channels, 386–387
 Separation cycle, 391
 Sequential microassembly, 412, 413
 SFB (silicon fusion bonding), 434, 435
 Shape memory alloys (SMAs), 54, 357, 447
 Shear, microdamping in, 137–144
 Shear deformation, of fluids, 184
 Shear force, 185
 Shear modulus of elasticity, 256
 Shear resistance, 134
 Shear stress, 138, 185, 238
 Shielding elements, 13
 Si, *see* Silicon
 SI (International System), 110
 Sidewall protection materials, for DRIE, 332
 Signals, in microsystems, 423
 Signal mapping, 355, 447–451
 and capacitance measurements, 450, 451
 and electrical signals in microsystems, 447
 in pressure sensors, 448–451
 and resistance measurements, 447, 448
 Signal transducers, 68
 Signal transduction, 447–451
 design/selection of, 355–357
 in micro-pressure sensors, 46–50
 in pressure sensors, 448–451
 Silanol bond, 434
 Silicon (Si), 11, 247–258
 as active substrate material, 247, 353
 atomic/ionic radii of, 306
 atomic structure of, 84, 85
 crystal structure of, 250–253
 doping of, 90–92
 electrical conductivity of, 276
 electrical resistivity of, 90, 91, 246
 electron mobility of, 266
 etch rates for, 326
 gallium arsenide vs., 267
 as ideal substrate for MEMS, 247–248
 mechanical/thermophysical properties of, 256–258
 micromachining of, 325–326
 and microsystems design, 352
 Miller indices of, 253–256
 and molecular theory, 87
 oxidation in, 299
 plasma gas etchants for, 330
 single-crystal, 248–250
 temperature-dependent thermophysical properties of, 151

- Silicon (Si), (*Continued*)
 thermal diffusivity of, 258
 Young's modulus of, 501
- Silicon-based IC, 11
- Silicon-based micromachining, 338–339
- Silicon-based microsensors, 30
- Silicon capacitive absolute pressure (SCAP)
 sensors, 24, 25
- Silicon carbide:
 advantages of, 259
 mechanical/thermophysical properties of, 257
 and microsystems design, 354
 as substrate material, 354
- Silicon compounds, 258–261
 etch rates for, 326
 polycrystalline silicon, 260–261
 silicon carbide, 259
 silicon dioxide, 258–259
 silicon nitride, 259–260
- Silicon dichloride, 313
- Silicon dioxide, 258–259
 in chemical vapor deposition, 302
 CVD creation of, 400
 CVD in, 302
 in DRIE process, 332
 electrical conductivity of, 276
 for etching mask, 316
 etch rates for, 326
 mechanical/thermophysical properties of, 257
 and microsystems design, 353
 and oxidation, 296
 plasma gas etchants for, 330
 properties of, 258
 as sacrificial component, 335, 401
 selectivity ratios of etchants to, 327
 as substrate material, 353
 thermal diffusivity of, 258
- Silicon dopants, ion implantation of, 291
- Silicone gel coating, 453
- Silicone oil, 138
- Silicone rubber:
 for die-level packaging, 445
 RTV, 281, 430, 445
- Silicon fusion bonding (SFB), 434, 435
- Silicon nitride, 259–260
 advantages of, 259
 in chemical vapor deposition, 303
 CVD in, 303
 electron mobility of, 266
 etch rates for, 326
 mechanical/thermophysical properties of, 257
 and microsystems design, 354
 plasma gas etchants for, 330
 properties of, 260
 selectivity ratios of etchants to, 327
 as substrate material, 354
 as x-ray mask, 340
- Silicon-on-insulator (SOI) bonding, 435–437
- Silicon oxidation rate constant, 300
- Silicon oxide, 266
- Silicon piezoresistors, 261–266
- Silicon solar photovoltaic cells, 476–477
- Silicon strain gages, 263
- Siloxanes, 453
- Silver, 90, 246, 437
- Simulation:
 of bulk micromachining, 376–377
 of microfabrication process, 375–377
 process, 422
 of surface micromachining/LIGA process,
 375–376
- Single-crystal form, of silicon/wafers, 248–250
- Singularity parameter, 170
- SLIGA process, *see* Sacrificial LIGA process
- Smalley, Richard, 471
- Smart cars, 21
- Smart materials, 502
- Smart sensors, 36
- SMAs, *see* Shape memory alloys
- Smith, Charles, 261
- Social impacts, of nanoscale engineering,
 502–503
- Sodium, 44
- SOFT (self-orienting fluidic transport), 412
- SOI bonding, *see* Silicon-on-insulator bonding
- Solar energy, 477
- Solar photovoltaic cells, 44, 476–477
- Solder, 445
- Solder alloy, 446
- Solids:
 heat capacity of, 228
 heat conduction in, 204–215, 220–221
 at meso-/microscales, 243
 physical behaviors of molecular, 89
 scaling in effect of heat conduction in, 243
 at submicrometer scale, 220–221
- Solid–fluid interaction, 209–210
- Solid mechanics, 110
- Solid solubility, 94
- Space environment sensors, 29

- Speed, 16
- Spinning, 279, 288
- Spintronics, 476
- Springs, 66–68
- Spring constant, 130
- Spring–mass, 125
- Spring–mass–dashpot, 125
- Sputtering:
- aluminum, 400
 - as physical vapor deposition process, 312–313, 317–318
 - reversed, 330
 - in thin-film fabrication, 361
- Square plates with edges fixed, 116–119
- Squeeze-film damping, 134–137
- Stainless steel, 257
- Standardization, 407, 408, 410
- Stanford University, 468
- Static balanced mode, 447, 448
- Static bending, of thin plates, 110–119
- circular plates with edge fixed, 112–114
 - rectangular plates with all edges fixed, 114–115
 - square plates with edges fixed, 116–119
- Static pressure, 203
- Stator poles, 66
- Stators, 7
- Steady-state creep, 151
- Stereomicroscopes, 420
- Stiffness constant, 124
- Stiffness matrix, 145
- STM, *see* Scanning tunneling microscope
- Stoppers, 382
- Stormer, Horst, 466
- Strain analysis, 175
- Streamlines, 186
- Stream tubes, 186
- Strength of materials, thermal effects on mechanical, 150
- Stress(es):
- and acoustic wave sensors, 36
 - bending, 111, 368
 - compressive, 153
 - hoop, 112
 - interfacial, 336, 337
 - intrinsic, 172–173, 364, 456
 - parasite, 452
 - peeling, 437
 - residual, 172, 173, 337
 - shear, 138, 185, 238
 - stress, 112
 - thermal, *see* Thermal stresses
 - von Mises, 176
- Stress analysis:
- finite element, 173–178
 - thermomechanical, 363–364
- Stress intensity factors, 166–167
- Stress singularity, 167
- Striction, 87, 337, 338
- SU-8 photoresists, 278–280
- Submicrometer scale:
- fluid flow in, 482–485
 - heat conduction in solids at, 220–221
- Substrates, 11
- cleaning of, 400
 - purpose of, 245–246
 - separation of grippers and, 401
- Substrate materials, 245–247
- active, 247
 - for LIGA process, 340–341
 - preparations, 452
 - selection of, 352–354, 399–400
 - silicon as ideal, 247–248
- Surface acoustic wave (SAW), 36–37
- Surface bonding, 429–437
- adhesives, 430–431
 - anodic, 432–434
 - eutectic, 431–432
 - overview of, 434–435
 - silicon fusion, 434
 - silicon-on-insulator, 435–437
- Surface coatings, 477
- Surface forces, 363
- Surface micromachining, 88, 333–338, 343
- and adhesion of layers, 336, 337
 - description, 333–334
 - design/selection of, 355
 - and interfacial stresses, 336, 337
 - mechanical problems with, 336–338
 - micro-cantilever beams produced by, 334
 - and microsystems design, 355
 - process of, 335–336
 - simulation of, 375–376
 - and striction, 337, 338
- Surface properties, 228
- Surface pumping, 228
- Surface reaction rate constant, 300
- Surface temperature, prescribed, 210, 211
- Surface tension, 199–201, 419
- Surface-to-volume ratios, 228–229

Suspension systems, 22
 System-level packaging, 427, 455
 Systems engineering, 422
 Systems integration, 73

T

TCP (temperature coefficient of piezoresistor), 450
 TCR (temperature coefficient of resistance), 450
 Tearing mode, 166
 Telecommunications, 30, 36
 Telecommunications equipment, 18–19
 Temperature:
 operating, 382
 prescribed surface, 210
 and silicon piezoresistors, 265–266
 Temperature coefficient of piezoresistor (TCP), 450
 Temperature coefficient of resistance (TCR), 450
 Temperature variation:
 through depth, 159–165
 through thickness, 158–159
 Templates, 500
 Tensile force, 146, 199
 Tension, surface, 199–201, 419
 Tertiary creep, 151
 Testing:
 method for, 422
 nanoscale, 502
 for reliability, 456–458
 Tetramethyl ammonium hydroxide (TMAH)
 etchant, 326, 327
 Texas Instruments, 11
 Thermal coefficient, 261
 Thermal conductivity:
 measurement of, 491–497
 of nanotubes, 476
 scanning thermal microscopy method of
 measuring, 496–497
 of solids, 205
 of thin films, 489–490
 3-omega method of measuring, 493–496
 Thermal control systems, 29
 Thermal diffusivity, 207
 Thermal distortion, 16
 Thermal effects, on mechanical strength of
 materials, 150
 Thermal forces, 16, 53–54
 Thermal inertia, 228
 Thermal moment, 159
 Thermal oxidation, 295–297
 Thermal oxidation rates, 296–300
 Thermal sensors, 50–53
 Thermal stresses, 152–165
 in beams due to temperature variation
 through depth, 159–165
 in bilayer strips, 153–157
 in thin plates with temperature variation
 through thickness, 158–159
 Thermal wave propagation, 491
 Thermocompression wire bonding, 438
 Thermocouples, 51–53
 Thermofluid engineering, 183–221
 computational fluid dynamics, 198–199
 continuum fluid dynamics, 187–195
 fluid mechanics, 184–187
 heat conduction in solids, 204–215
 incompressible fluid flow in microconduits,
 199–204
 laminar fluid flow in circular conduits,
 195–197
 Thermomechanics, 150–165
 creep deformation, 150–152
 mechanical strength of materials, thermal
 effects on, 150
 thermal stresses, 152–165
 Thermomechanical loading, 362–363
 Thermomechanical stress analysis, 363–364
 Thermophysical properties, 257
 Thermophysical quantities, units for, 523
 Thermopiles, 51, 52
 Thermoplastics, 274
 Thermoplastic nanoimprint lithography (T-Nil),
 498–499
 Thermosets, 274
 Thermosonic bonding, 439
 Thin film(s):
 heat conduction equation for, 490–491
 heat conduction in multilayered, 215–220
 heat conductivity measurement in, 491–497
 mechanics of, 172–173
 for nanoelectromechanical systems, 501
 process design fabrication of, 360–361
 thermal conductivity of, 489–490
 Thin-film deposition, 10
 Thin plates:
 static bending of, 110–119
 thermal stresses in, 158–159

3-omega method, 493–496
 Three-dimensional packaging, 443–444
 Three-dimensional structures, 13
 Three-point bending, 168
 Time:
 lag, 490
 mean-free, 487
 relaxation, 491
 scaling of, 231, 233
 Time-to-market (TTM), 351, 395
 TMAH etchant, *see* Tetramethyl ammonium hydroxide etchant
 T-Nil, *see* Thermoplastic nanoimprint lithography
 Tolerances, in microassembly, 414–416
 alignment, 415, 416
 dimensional, 414, 415
 geometric, 414–416
 Tongue-and-groove contacting surfaces, 440
 Tools:
 for design verification, 422
 for microassemblies, 410
 microassembly, 416
 Top-down approach, 467
 Torque transmission gears, 7
 Toughness, fracture, 167–169
 Transducers, 447
 Transduction, signal, *see* Signal transduction
 Transduction units, 1–3
 Transfer tool, high-precision, 421
 Transistors, 11, 16
 Trapezoidal channels, 383
 Trimmer force scaling vector, 231–233
 TTM, *see* Time-to-market
 Tubes, 362
 Tuning-fork-type microgyroscopes, 70–71
 Tunnel, 469
 Turbines, 7, 9
 Tweezers, 417

U

Ultra-large-system integration (ULSI), 11, 16
 Ultrasonic wire bonding, 437–439
 Ultraviolet (UV) light, 287, 288, 400, 477
 Underdamping, 122, 123
 "Under Heaven" (Lao-Tze), vi
 U.S. Army, 16
 Units:
 conversion of, 525–526
 for solid mechanics, 110

for thermophysical quantities, 523
 University of Pennsylvania, 16
 Use, testing during, 458
 UV light, *see* Ultraviolet light
 UV-nanoimprint lithography (UV-Nil), 499

V

Vacuum chuck, 288
 Vacuum sealing and encapsulation, 442–443
 Valence electrons, 84, 250
 Valves, micro-, 74–75
 Van der Spiegel, J., 17
 Van der Waals force, 87, 363, 418–419, 478
 Vapor-deposited organic, 453
 Vapor-liquid-solid (VLS) synthesis, 472
 Vapor-phase epitaxy (VPE), 313
 Variable capacitance, 48
 Vehicle diagnostics, 24, 26
 Vent hole, 443
 Verification, 411–413
 Vertical epitaxy deposition reactor, 315
 V-groove channels, 383–386
 Vibrating microgyroscopes, 70

Vibration, 16
 excessive, 364
 of lattices in substance, 486
 mechanical, *see* Mechanical vibration
 and molecular forces, 88–89
 resonant, 123–125
 Viscoelasticity, 36
 Viscosity:
 of fluids, 138, 184–186, 238–239
 of gases in CVD processes, 304
 Vision It software, 421
 VLS (vapor-liquid-solid) synthesis, 472
 Voltage, 51
 Voltmeters, 447
 Volume, scaling and, 228
 Volumetric fluid flow, 239–241
 Von Mises stress, 176
 VPE (vapor-phase epitaxy), 313
 Vulcanizing silicone rubber, 430

W

Wafers:
 materials for, 245–247
 single-crystal, 248–250
 in solar photovoltaic cells, 477

Wafer bonding, 441–442
Wafer dicing, 429, 452
Water, viscosity of, 138
Water column height, 202
Wedge–wedge ultrasonic bonding,
438–439
Weighted residuals method, 373
Weight limitations, 352
Wet etching, 316–318, 324–329
on aluminum, 401
dry vs., 333
isotropic/anisotropic, 325–326
photoresist removal by, 400, 401
rates of, 326
selectivity rates for, 327
stop techniques for, 328–329
Wet perimeter, 197

Wheatstone bridge, 447–451
Wicking materials, 75–76
Wire bonding, 425, 437–439
Wire bonds, 445
Work cells, 412, 419–421

X

X-ray, 289
X-ray lithography, 339–341
Xylene, 287

Y

Young's modulus, 247, 256, 261, 501

Z

Zinc oxide, 473, 474
Zinc oxide film, 477