

Index

Addressing, 11, 19

- active matrix, 20, 22–23, 28–9, 56–7, 74–7,
94, 113, 123, 135–7, 169, 215, 246–7, 281,
290, 291, 292, 294, 295, 297, 298
- alternate frame scan, 139, 145
- analog, 23, 25, 36, 41, 43, 47, 48, 66, 73, 80,
138, 144
- bit depth, 9, 63–4, 67, 71–2, 250, 329, 332
- bit splitting, 63, 69, 72, 250, 331
- cadmium selenide, 137
- CCD method, 14
- charge-transfer plate, 231
- crosstalk, 137, 138, 139, 145
- dc balance, 53–6, 62, 73, 135, 137, 141,
169–70, 213
- digital, 7, 25, 43, 48, 60–73, 246–50, 296
- digital fringe field, 63
- digital mean-square voltage, 60–1
- direct, 19
- DRAM, 35, 39, 40, 52, 55, 56–9, 100, 108,
113–14, 116–17
- electron beam, 10, 12, 13, 231, 232
- frame inversion, 53–5, 138, 139, 145, 147
- gate voltage feedthrough, 52–3, 58, 137,
139
- hybrid frame rate, 322
- hysteresis, 256
- interface ASIC, 41–5, 138, 140, 226
- line inversion, 53–5, 138, 139, 144, 145

- look-up-table (LUT), 44–5, 63–4, 70, 140,
322, 334
- matrix, 10, 19–20
- multiple line (active), 22
- passive matrix, 20–22, 64, 256–7, 259
- phased array addressing, 72, 242, 250
- photoaddress, 14, 82–3
- pixel storage, 113–14
- polysilicon leakage, 136, 138, 139, 141
- polysilicon matrix addressing, 136, 137,
138–41, 145
- pulse code/width modulation, 7, 24, 26,
64–80, 77–78, 236, 242, 250, 259, 322,
323, 331, 332
- thin film transistors (TFT), 11, 22, 28, 41, 54,
89, 123, 136–7, 149–50
- transistor body effect, 35, 38, 58
- voltage-holding ratio, 58–9, 141, 157, 169
- Aperture ratio (pixel fill factor), 29, 59, 96–7, 140–2,
236, 238, 242, 243, 244, 246, 254, 256, 257

Arc lamp

- arc fluctuations, 312
- metal halide, 311, 313
- synchronizing, 331–2
- UHP, 308, 311, 312–3, 322, 328
- xenon, 311, 313

Assembly

- cell gap spacers, 102, 211, 216–17, 219–20,
221

Assembly (*continued*)

- cell gap uniformity, 103, 118–21, 182, 192, 207, 211, 214–15, 216, 219–20, 221, 223, 224–5, 226
- liquid crystal filling, 220–1
- liquid crystal seal, 217–18, 219–22
- pressure, 220–1
- wafer singulation, 91, 100, 213, 214, 218, 219, 220, 225, 226
- wafer-scale, 211, 214, 219, 220

Back-end processing, 212–13

Backplane, 90, 123–4, 126

Circuits and Systems

- analog voltage addressing, 44, 46, 139
- column data driver, 47
- data path, 50
- data rate, 51
- gated transmission, 38, 57
- interface ASIC, 42, 44, 139
- inverter, 39
- LCOS NTE, 42
- LCOS parallel color projection, 44
- LCOS transmission with column inversion, 46
- OLED CMOS digital, 79
- OLED CMOS analogue, 81
- OLED CMOS sub threshold, 81
- OLED current programmed, 76
- OLED optical feedback, 77
- OLED TFT addressing, 75
- OLED voltage threshold compensation, 76
- pixel frame buffer, 42, 59, 60, 62
- pulse modulation, 65, 66
- row scan driver, 48, 51

CMOS, 29–30, 32–7, 90–1

- back-end, 91, 118
- cost, 102, 121, 126–30
- Damascene polishing, 111–13
- DMD, 239–41, 246–7, 249, 252
- DRAM, 100, 108, 113–14, 116–17
- dummy structures, 102, 110
- etch back, 99, 104–5, 110, 112
- fabrication, 91, 93–4, 102, 121, 123
- feature size, 90, 91, 93, 125, 126
- flatness, 95, 102
- footprint, 91, 92–3, 100, 114, 121, 125, 130
- high voltage, 99–100, 125, 130
- interconnection, 92, 93–4, 98–99, 112, 115, 117, 125, 130
- light leakage, 95, 97–117

metal layers, 91, 93, 94, 98, 99, 115, 116, 125, 130

microdisplays, 2, 89, 90, 94–5, 101, 112, 212, 292, 295–6

Moore's law, 91

MOS capacitor, 37

MOSFET, 32–7, 90, 92

OLED, 113, 124–5, 130, 292, 295–6

pixel gap fill, 118–19

pixel reflectivity, 97, 99, 117–18, 213

planar technology, 90

planarize, 94, 98, 99, 102–13, 118, 121–2

process node, 91, 92, 94, 126

roadmap, 91, 125–6

SIFT process, 118–19

spin-on glass, 99, 104–5

SRAM, 39–40, 62, 68–9, 246, 247, 252

structure, 91, 93–5, 100, 102, 110, 121

trench capacitor, 89, 93, 114, 130

wafer cost, 102, 121, 126–30

wafer size, 126

yield, 95, 99, 102, 103, 120, 127–9

Color

- breakup, 4, 10, 69, 322, 342, 342, 343, 345
 - combining cube (dichroic), 326, 327, 328
 - contour (posterizing), 7, 71–2
 - convergence, 324, 325, 326
 - dispersion, 183, 187, 189, 196, 197
 - field parallel, 28, 321, 326–9
 - field sequential, 15, 26–7, 146, 147, 236, 250, 253, 259, 309, 310, 322–5, 330, 332, 334, 342, 343, 344, 345, 346, 347, 351, 353, 359
 - color fusion, 10, 321, 322
 - color recapture, 324
 - color wheel, 26, 322–3, 324, 332
 - color drum, 325
 - spiral color wheel, 324
 - spiral lens wheel, 325
 - holographic filter, 325–6
 - management, 321–2
 - perception, 4
 - saturation, 4, 6, 8, 9, 15, 288, 308, 309, 322–3
 - scrolling, 27, 323–5
 - subpixels, 25–6, 150, 264, 269, 325, 343, 345, 351
 - temperature, 4, 7, 310, 311, 322, 332
 - uniformity, 5, 14, 211, 214, 216, 334
- Contact potential, 118, 135, 170, 213, 323
- Contrast, 2, 4, 5, 8

Contrast ratio, 2, 4, 6, 9, 151–3, 155, 161, 167,
175, 176–9, 181, 183–4, 187–190, 192–3,
196–201, 203, 207, 236, 242–6, 253, 256,
258–9, 343, 344, 349, 351, 355

Contrast ratio ANSI, 9, 333

Contrast sensitivity, 4, 5, 6

Dark adaptation, 6

Digital mirror device (DMD), 235–53

addressing, 242, 246–50, 252

bias potential, 247–50, 251

burn-in, 240, 241

CMOS, 239–41, 246–7, 249, 252

crossover state, 249

damping, 247–50

dark metal, 246

diffraction integral, 244–5

digital mirror device, 13, 72–3, 113, 118, 124,
235–52, 314, 322–3, 329, 330, 331, 332,
334, 344

electrostatic deflection, 231, 233–5, 252, 253,
256, 259

fabrication, 239–41

fast track pixel design, 251–2

hermetic sealing, 239, 241, 250

hinge, 236, 237, 238, 239, 240, 247, 250, 251, 252

on-time efficiency, 242, 246

optical damage, 251

passivation surfactant, 239, 240, 241, 253

permanent set, 250

phased array addressing, 72, 242, 250

spring tips, 237, 238, 239, 247, 249, 252

stay state, 249, 251

switching tolerance, 249, 251

switching transient, 248–249, 250

tilt angle, 237, 241, 242, 244, 247, 249

yoke, 236, 237, 238, 240, 247, 251

Display, 10–13

cathode ray tube, 10

Eidophor, 231

field emission, 11

liquid crystal, 12, 14

OLED, 12, 16

plasma, 11

projection, 3

Ruticon, 231

Electroluminescent microdisplays, 12, 297, 298

Emissive displays, 337, 342, 359

Etendue, 231, 256, 308–9, 310–11, 312, 313, 314,
320–1, 323, 324, 325, 327, 330

Eyesight

foveal vision, 5

vernier acuity, 5, 8

vision hyperacuity, 5, 8

visual acuity, 5, 8, 341

Fabrication

black matrix, 142, 145

chemical mechanical polishing, 94, 99, 104–9,
141, 220, 239, 253

dielectric mirror, 82, 181, 213–14, 215

glass substrate, 213, 215, 216, 218, 220, 222, 225

ITO transparent electrode, 211, 213, 215, 216,

217, 218, 220, 225, 228, 266, 278, 279

light block, 63, 82, 135, 141

pixel capacitor stacking, 140, 141

recessed substrate, 140, 141

sacrificial layer, 239–240, 254

surface metrology, 102

Ferroelectric liquid crystal (FLC), 12, 14, 58,

64–71, 205–8, 343, 345, 346, 359, 323, 331

antiferroelectric liquid crystal (AFLC), 207

distorted helix, 207

electroclinic response, 208

surface stabilized (SSFLC), 206–7

V-shaped response, 207–8

Flicker, 5–6, 9–10, 54, 139, 145, 331–2

critical flicker frequency (CFF), 6, 53

Gamma, 7, 43, 65, 69, 72, 322

Grayscale, 7, 9, 23–5

analog, 234–5, 253, 256, 257

backlight modulation, 332

contouring, 7, 9, 71–2, 250

dithering, 24, 72, 250, 257, 259, 332

quantization, 7

Heat sink, 310, 311, 327

Holographic optical element, 351, 352

Holographic storage, 16

Image, 3–10

moving picture quality, 64

quality, 181–2, 332, 333, 334, 345

sticking (ghost), 10, 167–9, 138, 139, 286

Infrared scene generator, 16

Jones matrix, 153, 185

Laser, 309–10, 330–1

laser infrared, 309

power, 309–10

Laser (*continued*)

scanning, 330–1
speckle, 309, 310, 331

LCOS, 14, 26, 29–32, 40–60, 100, 121–3, 173–4, 205, 211, 212, 223, 311, 323, 325, 326–7, 332

electronic architecture, 40–60
floor plan, 43–7
microdisplay, 2, 212
projector, 3, 174–76, 205, 323, 327
silicon-on-insulator, 124, 130, 145–7
transferred silicon, 94, 123, 130, 145–7
transmission, 89, 123–4

Light emitting diode (LED), 21, 152, 207, 309, 310–11, 337, 342, 343, 344, 345, 348, 349, 351

GaN microdisplay, 298
photonic lattice structure, 311
projector illumination, 15, 152, 310–11

Liquid crystal alignment, 151, 156–9, 214, 217, 219, 220–1

rubbed, 156–9, 214, 217
inorganic, 156–7, 214, 219
oblique evaporation, 157
pretilt angle, 155, 157–9, 161–2, 165
surfactant, 157
e-beam, 159

Liquid crystal cell

bisector effect, 176, 194, 195–6
chiral dopant, 155, 191, 200
chiral pitch, 191, 205, 206, 207
diffraction device, 203, 205
finger-on-plane, 201, 203
Gooch-Tarry condition, 154
ion space charge, 168–70
ion transit time, 168–9
ionic conduction, 166–8
fringe field, 54–5, 63, 139, 140, 144, 145, 147, 165–7, 179–81, 184, 187, 190, 193, 199, 200, 281, 324, 334
cell gap, 103, 114, 118–21
Maugin limit, 153, 154
mixed mode twisted nematic (MTN), 184–185
MTN 45 deg normally black, 199–201
MTN 45 deg normally white, 196–9
MTN 60 deg normally white, 194–6
MTN 63.6 deg normally black, 190–4
MTN 63.6 deg normally white, 189–90
MTN 90 deg, 186–9
normally black mode, 153, 166, 176

normally white mode, 152, 153, 154, 155, 176
parallel aligned (homogeneous) nematic, 182–3

phase modulation, 203, 205, 330
polymer dispersed liquid crystal (NCAP, PDLC), 203–5, 314, 330
reflectance maximum, 186, 187, 200
reflective TN cells, 184–5
twisted nematic cell 90 deg, 152–6, 166–7
twisted nematic general, 153–4
vertical aligned nematic (VAN), 151, 155–7, 159–64, 165–6, 176–81
voltage response VAN, 159, 161, 176–7

Liquid crystal material, 218, 219**Lumen**, 3**Lumen output**, 308, 332**Lumens ANSI**, 332–3**Luminance**, 8–9, 339, 342, 344, 349, 350, 351, 355, 357, 358–9**Microdisplay**, 1–2, 13–14**Microdisplay specification**, 224, 226–7**Mobile phone**, 337, 353, 355, 361, 362**Micro-optical-electromechanical systems**

(**MOEMS**), 13, 14, 231, 234, 259–60, 124, 259–60

diffraction efficiency, 236, 242–6, 254–8
grating blazed, 243, 244, 258
grating light valve (GLV), 254–8, 330–1
Interference color pixels, 258–9
interference modulation (IMoD), 258–9
lifetime, 231, 232, 239, 241, 249, 250–1, 254, 258, 259
mechanical resonance, 249, 258
mirror matrix tube, 232–3
piezoelectric micromirror (TMA), 252–4
stiction, 247, 249, 252, 257

Near-to-eye, 15, 282, 288, 290, 298, 301, 337, 355

augmented reality, 347, 351, 357
beam-splitting optics, 338, 340, 342, 344, 348–9, 350, 351, 353, 359
binocular vision, 347, 348, 349, 354, 359
diffractive pupil expansion, 357
eye box (output pupil), 338–9, 340, 341, 342, 344, 348, 349, 355, 359, 361
eye relief, 338–9, 341–2, 345, 347, 349, 351, 353, 355, 359, 361
eye tracking, 360
eyestrain, 5, 377, 341, 361

- eyewear-mounted, 353–4
- face-mounted, 347, 349
- head mounted, 2, 7, 337, 340, 341, 346–7, 362
- head tracking, 351, 358, 360
- light pipe system, 353–4
- light-guide pupil expansion, 355, 357
- magnification, 337–40, 344–5
- mangin lens, 348–9
- motion sickness, 361
- optical field curvature, 344, 349, 351, 359
- partial emersion, 7, 347
- screen, 340, 358–9
- see-through image, 346, 347, 349, 351, 354
- simulator sickness, 7, 347, 361
- total emersion, 7, 347, 360–1
- viewfinder, 345–6
- virtual image, 337–8, 340, 344, 354, 359
- virtual reality, 7, 346–7, 358
- web browser, 361
- Nematic liquid crystal**, 218–9, 321, 323, 326, 327
 - optical dispersion, 160, 162
 - order parameter, 160
 - pretilt, 174, 178, 180, 182, 183, 184, 214
 - response time, 22, 24, 60, 63–4, 164–5, 166, 170
 - temperature response, 1, 59–60, 164–5, 168, 170, 176, 177, 184, 192, 207, 208
- Optical**
 - damage, 156–7, 214, 251
 - f*/number, 155, 156, 162, 166, 175–6, 178–9, 203, 235, 241, 253, 308, 321, 327, 330, 332, 333, 339, 342, 343, 344, 359
 - field of view, 16, 155–6, 162, 166, 176, 178–9, 183, 187, 190, 192–3, 196, 197–8, 200, 341–2, 354, 355, 358–9
 - index matching, 215, 216, 218, 327
 - modulation transfer function, 8, 181–2, 319, 334, 344–5, 349, 351, 353
 - multireflections, 216
 - PBS compound angle effect, 315–6, 317, 327
 - scattering, 314, 330, 333
- Optical systems and components**
 - catadioptric, 340–1, 348–9, 359
 - color-quad system, 327, 328–9
 - dichroic mirror, 322, 326, 327, 330
 - filter birefringent, 328–9
 - Fresnel lens, 359–60
 - kinoforn, 349
 - microlens array, 136, 140, 141, 142–3, 325, 326–7
 - molded plastic optics, 350
 - optical compensation, 155, 156, 162, 178–9, 183, 184, 189, 190, 197, 315, 321, 326, 333, 343
 - polarization conversion, 309, 311, 319–21, 327
 - polarizer absorbing (dichroic), 314, 319, 326, 327, 328
 - polarizing beamsplitter (PBS), 174, 314–17, 320, 327, 328
 - polarizing beamsplitter Cartesian, 316–7
 - prism anamorphic, 349, 350–1, 361
 - prism magnifiers, 348–53, 361
 - quarter-wave retarder, 315, 317, 321, 327
 - relay optics, 340, 351, 353, 354, 358–9
 - Schlieren filter, 330
 - surface structure (microlens array), 282
 - wire grid polarizer, 317–20, 328
- circular polarized readout, 166–7
- optical correlation, 16
- optical switching, 17
- Packaging**, 211, 212, 221, 223–4, 225, 226, 279, 280
- Performance ANSI**, 331
- Pixel array format**, 8
- Pixel diffraction loss**, 97, 118, 125
- Projection**
 - screen gain, 8, 9, 307–8
 - front, 9
 - performance, 331–3
 - rear, 3
 - scanning, 257, 258
 - Schlieren, 231, 253, 256, 258, 330–1
 - sequential contrast ratio, 332–3
 - system contrast ratio, 333
 - transmission, 151–2, 326–7
- Reflectivity**, 141, 213, 242, 246, 254, 255, 258
- Resolution**, 340, 341, 344, 345, 346, 351, 353, 354, 355, 358–9, 360, 361–2
- Response speed**, 343, 344
- Organic electroluminescence**
 - aging, 264, 285–6, 288
 - anode, 265, 266, 268, 278, 279, 281, 291, 292
 - bottom emitting, 268, 278, 279, 280, 290
 - carrier diffusion length, 266
 - carrier injection, 266, 268, 273, 277, 278, 280, 282, 292

Organic electroluminescence (*continued*)

carrier mobility, 264, 265, 266
 cathode, 266, 268, 278, 279, 281, 288, 294
 charge balance efficiency, 282
 color converters, 288–9, 292
 conduction band, 265–7
 dc characteristic, 282–3
 dendrimers, 269, 273, 275
 electromotive properties, 266
 electron affinity, 265
 electron blocking layer (EBL), 279
 electron transporting layer (ETL), 266, 268, 270, 273, 278, 280, 292
 electron-hole exciton, 266–7, 269, 273, 278, 279, 281, 282
 electron-hole recombination, 266–8, 273
 emission color, 264, 267, 271, 273, 285, 286, 288, 289, 298
 emission double region, (2-PIN-OLED), 280
 emissive aperture ratio (EAR), 281, 300
 encapsulation, 268, 278, 280, 282
 fabrication, 269, 273, 277, 292–3
 fluorescence, 267, 269
 ghost image, 286
 glass transition temperature, 269, 273
 heterojunction, 263, 266, 267, 291
 highest occupied molecular orbital (HOMO), 265, 266, 267
 hole blocking layer (HBL), 274, 279
 hole transporting layer (HTL), 266, 271, 274, 279, 280, 293
 host materials, 267, 271, 273, 274, 278, 279
 inkjet printing, 268, 269, 272, 277
 interface layers, 268, 277, 278, 279, 280
 intrinsic emitting layer (PIN-OLED), 271, 276, 279–80
 lifetime, 268, 273, 276, 277, 278, 279, 280, 285–6, 288, 289, 292
 lowest unoccupied molecular orbital (LUMO), 265–7
 microdisplays, 290–7
 n-type conductivity, 265–7, 278, 279, 298
 optical cavity, 268
 organic light emitting diode, 41, 73–4, 263–4, 267–8, 343–4, 346, 351, 359, 360
 out-coupling efficiency, 268, 281–2
 performance, 263, 268, 269, 273–77, 280, 281, 285, 292
 phosphorescence, 263, 267, 269, 273, 274, 280, 281, 297, 302

phosphorescent dye doping (PHOLED), 267, 269, 273, 274, 276, 279
 polymer (P-OLED), 268, 271
 P-OLED microdisplays, 294–7
 polymer cross linking, 273
 polymer materials, 272
 p-type conductivity, 265–7, 279
 quantum efficiency, 267, 269, 273, 281
 radiative decay, 267, 269, 281
 recombination zone, 266, 267
 response time, 264, 284–5, 291
 shadow masking, 268, 277
 singlet exciton state, 267, 269, 273, 281
 small molecule (SMOLED), 263, 264, 268, 269, 270, 271, 273, 276, 277, 278, 284, 291–3
 SMOLED materials, 269–71, 276
 SMOLED microdisplays, 291–3
 solution processing, 268, 269, 272, 273
 space charge limited current (SCLC), 266, 268
 spin coating, 268, 272
 stacked colors, 286, 288, 289
 tiled displays, 292, 294
 triplet exciton state, 267, 269, 273
 vacuum deposition, 268, 269, 277
 valence band, 265
 white emitter, 276, 282, 284, 286–9, 291, 293, 294–6, 297
 work function, 265–6, 278, 293

Silicon

amorphous, 11, 28–29, 137–8, 149–51
 continuous grain, 28
 crystalline, 28–9
 nitride, 141, 246, 253, 254, 255, 258, 260
 polysilicon, 11, 28–9, 32, 53, 55, 89, 90, 91, 92, 93, 97, 114, 136, 137–8, 140, 141, 143, 145, 146, 150–1
 porous, 298–301
 transferred, 145–7
 wafer, 211, 213, 215, 221, 225
 on-insulator, 89, 124, 130
 on-sapphire, 146–7
 Spatial light modulator, 13

Test, 211, 213, 215–16, 225–6
 circuits, 48, 50
 electrical, 213, 220, 225, 227
 flatness, 102, 216
 Linnik interferogram, 98, 109

- optical inspection, 213, 216, 227
- performance, 227
- stress, 225, 227, 228
- surface quality, 213, 215, 216, 225
- Throughput efficiency, 231, 235, 236, 241–6, 249, 250, 253, 256, 257, 258, 310, 322, 323, 324, 326, 329, 332
- Tiled microdisplays, 359–61
- Transmission LCD, 149–51
- Transmission microdisplay, 211, 214, 215, 216, 224, 314, 326, 332, 342, 343, 345, 351, 353
- Ultraviolet imaging, 16

