
Index

- Accumulation, 19, 216, 221
- Active region, 9
- Admittance
- gate-to-bulk, 68, 274
 - gate-to-source, 68, 270, 274
 - gate-to-drain, 68, 270, 274
 - bulk-to-drain, 68, 270
 - bulk-to-source, 68, 270
 - substrate, 255
 - correlation, 263, 261, 265
- Band gap, 112
- extrapolated, 113
 - widening, 156, 133, 157, 158, 160, 161
- Bode theorem, 106–107, 92, 274*n*
- Boltzmann constant, 10, 87
- Capacitance
- gate oxide, 17, 214
 - silicon, 18, 19, 224
 - gate, 13, 18, 19, 30, 73, 233
 - depletion, 19, 30
 - intrinsic, 70, 72, 73, 75, 233
 - overlap, 214, 220, 221, 222, 223, 232, 233
 - junction, 54, 214, 224–226, 232, 244, 249, 288
 - fringing-field, 220, 221, 222, 233,
 - bottom-wall, 220, 226
 - side-wall, 226
- Capacitor
- overlap, 10, 66, 77
- Carrier
- fluctuations, 96, 100
 - heating, 167, 205–209, 211, 285
- Cascode configuration, 226
- Channel
- buried, 143, 144, 145
 - homogeneous, 47–49
 - length, 46, 53, 54, 60, 164–167, 176, 186–188, 198, 208, 232, 285
 - length modulation, 33, 48, 50, 52–54, 167, 186–188, 208
 - narrow, 50
 - residual current, 45
 - voltage, 34, 38, 43, 49, 52, 78, 83, 116
 - width, 34, 46, 60, 164, 218
 - gradual, 13, 14, 16, 167, 187, 189
 - conductance, 86, 89, 90, 199, 201
 - region, 14, 51, 81, 198, 218, 219, 222, 223, 231
- Channel length modulation, 48, 50, 52–54, 167, 186–188, 208
- Charge
- elementary, 10, 189, 227
 - fixed, 10, 11, 15–17, 150, 151, 155, 187
 - inversion, 4, 10, 11, 20, 21, 24, 30, 65, 87, 96, 143, 146, 171–176, 206, 211
 - total, 11, 13, 17, 21, 27, 144
 - concentration, 13, 14, 33, 187
 - depletion, 11, 12, 15, 17, 21, 23, 26, 30, 47, 49, 97, 134, 138, 157, 224
 - specific, 13, 24, 32, 117, 133, 154, 161
- Charge density, 11
- depletion, 11, 12, 15, 17, 19, 21, 26, 30, 47, 97, 134, 138, 157, 224
 - in silicon, 23, 27, 189
 - inversion, 20, 21, 25, 30, 65, 87, 96, 143, 148, 172–176, 192, 211
 - specific, 13, 24, 32, 117, 133, 154, 159, 161
 - fixed, 11, 17, 150, 151, 155, 187

300 INDEX

- Charge sheet approximation, 13, 20, 21, 23, 33, 158
- Charge-potential linearization, 23–32
- Common-source amplifier, 233, 261, 282, 286–288
- Concentration
 - hole, 14
 - intrinsic carrier, 14, 112, 113
 - electron, 14, 20, 158, 187
 - doping, 14, 47, 51, 60, 114, 138, 142, 147, 149, 159, 160, 223
- Concentric transistor, 54
- Conductance
 - drain-to-source, 60, 89
 - specific, 57, 119, 154, 219
- Critical field, 91, 167–169, 171, 180
- Current
 - drain, 10, 33, 168, 171–174, 179, 182, 184, 191, 194, 203, 217, 225, 274, 282
 - forward, 35, 48, 56, 63, 133, 163, 164
 - gate leakage, 106, 133, 161–166, 223
 - reverse, 35, 37, 39, 42, 56, 58, 62, 133, 135–137, 224
 - specific, 37, 40, 52, 65, 118, 154, 161
 - drift, 10, 33, 34
 - diffusion, 10, 33, 34, 49, 54, 89, 166, 171, 172, 213, 215, 223, 246
 - tunneling, 220, 227
 - generation, 223, 224
 - gain, 83, 232, 233, 234, 237
- Debye length, 15
- Depletion
 - thickness, 19, 189
 - capacitance, 17, 19, 30
- Dielectric constant of silicon, 14
- Differential pair, 122, 129
- Diffusivity, 202
- Doping
 - concentration, 7, 9, 13, 14, 16, 47, 51, 60, 114, 118, 138, 142–147, 159, 223
 - ratio, 141, 143, 145–148
- Drain, 3, 4, 7, 9, 10
 - induced barrier lowering (DIBL), 167, 189–197
 - voltage, 3, 7, 10, 207, 208, 210
- Drain current, 10, 11, 25, 33, 40–46, 55, 60, 65, 83, 85, 88, 100–104, 127, 133, 154, 171
 - alternative models of, 36, 43, 45, 194
 - general expression, 37, 42, 46, 55, 59
 - in strong inversion, 13, 18, 19, 31, 41, 52, 58, 63, 75, 95, 102
 - in weak inversion, 17, 26, 36, 43, 52, 64, 74, 89, 105, 118
- Ebers-Moll model, 3, 46
- Einstein relation, 202
- Electric field
 - longitudinal, 33, 205
 - effective, 134, 156, 171, 186
 - vertical, 15, 134, 135
- Energy band gap of silicon, 112
- Equilibrium, 10
- Extrinsic
 - part, 9, 131, 213, 222, 231, 257
 - noise sources, 227, 228
- Fast surface state, 11
- Figure of merit, 64, 90, 105, 232, 236–238
- Flat-band condition, 17, 114, 150, 221
- Flicker noise, 81, 86, 96–106, 226, 227
 - corner frequency, 96
- Fluctuations
 - mobility, 96, 101, 104–106
 - carrier, 96
 - resistance, 103
 - of width, 126
 - of length, 126
- Gate
 - capacitance, 13, 18–20
 - doping, 114, 115
 - leakage current, 133, 161, 163, 223
 - modulation factor, 149
 - oxide capacitance, 17
 - overhead voltage, 41
- Gate-drain noise correlation factor, 278
- Gauss' law, 16, 17, 134, 186, 189
- Geometrical effects, 53, 54
- Grading coefficient, 225
- Gradual channel approximation, 14, 16, 17, 167, 187, 189
- Harmonic distortion, 216
- High injection, 223
- Hooge
 - model, 101, 102
 - parameter, 101, 105
- Impedance field method, 83
- Induced gate noise, 83, 262, 273, 281, 282

- Induced substrate noise, 271
- Intrinsic
 - part, 9, 10, 66, 77, 81, 213
 - capacitances, 73–74, 249, 275
 - channel time constant, 65, 275
 - nodes, 216
- Inversion charge density
 - in weak inversion, 26
 - in strong inversion, 26
 - at the drain, 38, 78
 - at the source, 38
- Inversion coefficient (or factor), 40–44, 53
- Langevin, 83
 - method, 82, 83
 - noise source, 83
- Lateral bipolar transistor, 12
- Linear mode, 36, 40, 42, 52, 59
- Low-noise amplifiers, 218, 257
- Matching, 120–129
- Maximum available gain, 236
- Maximum frequency of oscillation, 236
- Microscopic noise source, 84
- Minimum noise figure, 231, 238, 239, 261, 266, 287
- Mismatch, 111, 120, 122, 123, 129
 - of drain current, 122, 127
 - of gate voltage, 122, 124
 - systematic, 124
 - random, 125–128
- Mobility, 33
 - effective, 168–171
 - fluctuations, 101, 106
 - nonuniform, 138
 - reduction due to the vertical field, 133, 205, 209
 - temperature variation, 113–115
 - low field, 133
 - field dependent, 133, 172, 203
 - differential, 168, 200, 202
 - cord, 168, 203–206
- Mode of operation
 - linear, 36, 42
 - triode, 36
 - nonsaturation, 36
 - weak inversion, 36
 - strong inversion, 36
 - subthreshold, 37, 43
 - blocked, 37
 - bipolar, 37
- Moderate inversion, 37, 41, 64, 102, 105
- Noise
 - factor, 238, 265
 - figure, 238
 - matching, 238, 267, 285
 - parameters, 91, 261, 285, 286, 290
- Nonquasi-static
 - small-signal circuit, 67, 82, 93, 94, 229, 249
 - operation, 65, 249, 257
 - large-signal operation, 77–79, 249
- Normalization
 - frequency, 68, 70, 72
 - bias, 70, 72
- Normalized
 - drain current, 37, 88, 154, 194
 - inversion charge density, 24, 38, 65
 - inversion charge density at the drain, 38, 57, 173
 - inversion charge density at the source, 38, 57, 173
 - voltages, 24, 41
 - pinch-off voltage, 24, 43, 67, 73, 135, 156
 - forward current, 37, 63
 - reverse current, 37, 135–137
 - intrinsic capacitances, 73, 74
 - transconductances, 57, 181, 182
 - transcapacitances, 75, 76
- Nyquist theorem, 106–107, 274
- Operating point, 56, 68, 81, 90, 168
- Optimum source admittance, 261, 267
- Overlap region, 216, 221, 223
- Oxide
 - charge in, 11
 - field, 11
 - thickness, 9, 10
 - gate, 9
- Physical parameters, 111, 112, 115, 120
 - spatial fluctuations of, 120
 - statistical fluctuations, 125
- Pinch-off
 - potential, 22, 25, 145, 147, 159
 - voltage, 25, 209–211
- Poisson
 - distribution, 128
 - equation, 14, 51
- Potential
 - barrier, 51, 89, 190, 194
 - electrostatic, 11, 49, 50
 - surface, 11, 14, 17, 52, 97
 - extraction, 11, 114, 115

302 INDEX

- Potential (*Cont.*)
 - Fermi, 14, 34, 113, 114
 - pinch-off, 22, 25, 145, 147, 159
- Power spectral density (PSD), 81
 - of drain current, 87
- Pseudo-resistor, 33, 49, 165
- Quad configurations, 125
- Quasi-Fermi potential, 10, 14, 34
- Quasi-static
 - frequency, 65, 66, 275
 - time constant, 65, 75, 92, 275
 - small-signal circuit, 76, 92, 249
- Random fluctuations
 - of carrier velocity, 81, 83
 - of carrier density, 81
- Resistance
 - access, 213, 215, 216–219, 247
 - gate, 14, 213, 217, 247, 252
 - source, 213, 215, 287
 - drain, 102, 213, 215, 217, 226
 - substrate, 214, 226, 243–246
 - salicide, 215
 - via, 215, 218
 - contact, 215
- Sample-and-hold, 92
- Saturation
 - forward, 36, 40, 42, 54, 60, 70
 - reverse, 36, 53, 60, 70, 71
- Saturation mode, 36, 40
 - forward, 36, 40, 42, 54, 60, 70
 - reverse, 36, 53, 60, 70, 71
- Saturation voltage, 36, 42, 66, 173
- Scattering
 - mechanisms, 96, 115, 134
 - due to acoustic phonon, 115
 - due to ionized impurities, 115
- Short-channel effects, 48, 131, 167–212
- Silicon dioxide, 9, 161
- Slope factor, 21, 23, 25, 162
 - charge, 153, 162
 - evaluation of, 29–31
 - voltage, 152
- Source-drain extension, 215
- Space charge regions, 51
- Spacer, 216, 220
- Spatial correlation, 109, 125
- Specific conductance, 57, 119, 154, 219
- Step profile, 141–144, 148, 225
- Strong inversion, 17, 232–234, 239, 252
 - charge approximation, 20, 21, 27, 155
 - current approximation, 41, 194
- Substrate modulation factor, 21, 116, 140, 159
- Substrate network, 214, 242–247, 249
- Subthreshold mode, 37
- Surface
 - electric field, 11, 47, 49, 144
 - potential, 11, 17, 21, 23, 38, 52, 189
- Symmetry, 46, 68
 - source and drain, 9, 56
- Temperature
 - absolute, 10, 87, 112
 - effects on transistor, 111–120
 - noise, 202
 - carrier, 202
 - lattice, 203, 205
- Temperature coefficient of
 - Fermi voltage, 114
 - extraction voltage, 115
 - threshold voltage, 117
 - inversion charge, 117, 120
 - specific current, 118
 - transconductances, 119
- Thermal noise
 - conductance at the drain, 87, 203
 - excess factor, 89, 90–91, 93–95, 206–212
 - parameter, 81, 89, 90–92, 206–212
 - voltage variance, 95
 - short-channel, 197–212
- Threshold
 - function, 13, 21, 22, 27, 29, 116, 138, 140, 142, 150
 - voltage (at equilibrium), 28
- Threshold function, 21
- Transadmittance
 - drain, 66–68
 - source, 66–68
 - gate, 66–68
- Transcapacitances
 - gate, 75
 - drain, 74
 - source, 74
- Transconductance
 - bulk, 288
 - drain, 56–60, 62, 136, 154
 - gate, 56, 197, 234, 288
 - source, 56, 60, 154, 183, 201, 234
 - effective, 216
 - intrinsic, 216

- Transconductance-to-current ratio, 62, 183
- Transducer gain, 237
- Transfer parameter, 34, 40, 118, 121
- Transistor
 - bipolar, 12, 37, 45, 229
 - extrinsic part, 9, 131, 213, 214, 227, 231
 - intrinsic part, 9, 61, 66, 213, 214
 - schematic cross section, 10
 - symbols, 12
- Transit frequency, 55, 66, 232, 233, 234, 235, 239, 268, 287
 - peak, 234
- Transit time, 239, 240
 - total, 239
 - of intrinsic part, 239
 - of extrinsic part, 239
- Trapping, 96, 98, 100
- Tunneling, 98

- Unilateral power gain, 236, 237
- Unity gain transit frequency, 233

- Velocity
 - Saturation, 86, 167, 168, 171, 177, 232, 235
 - saturation region, 186, 187
 - drift, 167, 168, 173

- Velocity-field models, 169–171
- Voltage
 - channel length modulation, 60
 - drain, 10, 33, 35, 36, 38, 42, 56, 60, 170, 171
 - gain, 61, 64, 167, 197, 198
 - gate, 10, 17, 18, 23, 25, 27, 32, 35, 40, 50, 143, 150, 153
 - pinch-off, 3, 25, 32, 35, 36, 43, 135, 180, 211
 - intrinsic, 216
 - saturation, 37, 44
 - source, 10
 - thermodynamic, 10, 83
 - channel, 9, 14, 19, 23, 25, 26, 77, 83, 116
 - flat-band, 17, 49, 50, 52, 114, 221
 - band gap, 112
 - extrapolated band gap, 113
 - avalanche breakdown, 224

- Weak inversion, 17, 18, 20, 26, 30, 36, 39
 - current approximation, 43–45
- Well
 - perimeter, 226
 - area, 226

- Y-parameters, 234, 237, 243, 249, 251, 252, 253, 255, 261, 263, 265, 273

