
Contents

Foreword	xiii
Preface	xv
List of Symbols	xvii
1 Introduction	1
1.1 The Importance of Device Modeling for IC Design	1
1.2 A Short History of the EKV MOS Transistor Model	2
1.3 The Book Structure	5
Part I The Basic Long-Channel Intrinsic Charge-Based Model	7
2 Definitions	9
2.1 The N-channel Transistor Structure	9
2.2 Definition of Charges, Current, Potential, and Electric Fields	10
2.3 Transistor Symbol and P-channel Transistor	11
3 The Basic Charge Model	13
3.1 Poisson's Equation and Gradual Channel Approximation	13
3.2 Surface Potential as a Function of Gate Voltage	17
3.3 Gate Capacitance	18
3.4 Charge Sheet Approximation	20
3.5 Density of Mobile Inverted Charge	21
3.5.1 Mobile Charge as a Function of Gate Voltage and Surface Potential	21
3.5.2 Mobile Charge as a Function of Channel Voltage and Surface Potential	23
3.6 Charge-Potential Linearization	23
3.6.1 Linearization of $Q_i(\psi_s)$	23
3.6.2 Linearized Bulk Depletion Charge Q_b	26
3.6.3 Strong Inversion Approximation	27
3.6.4 Evaluation of the Slope Factor	29
3.6.5 Compact Model Parameters	32

viii CONTENTS

4	Static Drain Current	33
4.1	Drain Current Expression	33
4.2	Forward and Reverse Current Components	35
4.3	Modes of Operation	36
4.4	Model of Drain Current Based on Charge Linearization	37
4.4.1	Expression Valid for All Levels of Inversion	37
4.4.2	Compact Model Parameters	39
4.4.3	Inversion Coefficient	40
4.4.4	Approximation of the Drain Current in Strong Inversion	41
4.4.5	Approximation of the Drain Current in Weak Inversion	43
4.4.6	Alternative Continuous Models	45
4.5	Fundamental Property: Validity and Application	46
4.5.1	Generalization of Drain Current Expression	46
4.5.2	Domain of Validity	46
4.5.3	Causes of Degradation	48
4.5.4	Concept of Pseudo-Resistor	49
4.6	Channel Length Modulation	50
4.6.1	Effective Channel Length	50
4.6.2	Weak Inversion	52
4.6.3	Strong Inversion	52
4.6.4	Geometrical Effects	53
5	The Small-Signal Model	55
5.1	The Static Small-Signal Model	55
5.1.1	Transconductances	55
5.1.2	Residual Output Conductance in Saturation	60
5.1.3	Equivalent Circuit	61
5.1.4	The Normalized Transconductance to Drain Current Ratio	62
5.2	A General NQS Small-Signal Model	65
5.3	The QS Dynamic Small-Signal Model	72
5.3.1	Intrinsic Capacitances	72
5.3.2	Transcapacitances	74
5.3.3	Complete QS Circuit	75
5.3.4	Domains of Validity of the Different Models	77
6	The Noise Model	81
6.1	Noise Calculation Methods	81
6.1.1	General Expression	81
6.1.2	Long-Channel Simplification	86
6.2	Low-Frequency Channel Thermal Noise	87
6.2.1	Drain Current Thermal Noise PSD	87
6.2.2	Thermal Noise Excess Factor Definitions	89
6.2.3	Circuit Examples	91
6.3	Flicker Noise	96
6.3.1	Carrier Number Fluctuations (Mc Worther Model)	96
6.3.2	Mobility Fluctuations (Hooge Model)	101
6.3.3	Additional Contributions Due to the Source and Drain Access Resistances	103

6.3.4	Total $1/f$ Noise at the Drain	104
6.3.5	Scaling Properties	105
6.4	Appendices	106
	Appendix: The Nyquist and Bode Theorems	106
	Appendix: General Noise Expression	108
7	Temperature Effects and Matching	111
7.1	Introduction	111
7.2	Temperature Effects	112
7.2.1	Variation of Basic Physical Parameters	112
7.2.2	Variation of the Voltage–Charge Characteristics	116
7.2.3	Variation of the Voltage–Current Characteristics	118
7.2.4	Variation of the Current–Charge Characteristics	120
7.3	Matching	120
7.3.1	Introduction	120
7.3.2	Deterministic Mismatch	121
7.3.3	Random Mismatch	125
Part II	The Extended Charge-Based Model	131
8	Nonideal Effects Related to the Vertical Dimension	133
8.1	Introduction	133
8.2	Mobility Reduction Due to the Vertical Field	133
8.3	Nonuniform Vertical Doping	138
8.3.1	Introduction and General Case	138
8.3.2	Constant Gradient Doping Profile	139
8.3.3	Step Profile	141
8.3.4	Effect on the Basic Model	147
8.4	Polysilicon Depletion	148
8.4.1	Definition of the Effect	148
8.4.2	Effect on the Mobile Inverted Charge	149
8.4.3	Slope Factors and Pinch-Off Surface Potential	150
8.4.4	Voltage Slope Factor n_v	152
8.4.5	Charge Slope Factor n_q	153
8.4.6	Effect on $Q_i(V)$, Currents, and Transconductances	154
8.4.7	Strong Inversion Approximation	155
8.5	Band Gap Widening	156
8.5.1	Introduction	156
8.5.2	Extension of the General Charge–Voltage Expression	158
8.5.3	Extension of the General Current–Voltage Expression	160
8.6	Gate Leakage Current	161
9	Short-Channel Effects	167
9.1	Velocity Saturation	167
9.1.1	Velocity-Field Models	169
9.1.2	Effect of VS on the Drain Current	171
9.1.3	Effect of VS on the Transconductances	181

x CONTENTS

9.2	Channel Length Modulation	186
9.3	Drain Induced Barrier Lowering	189
9.3.1	Introduction	189
9.3.2	Evaluation of the Surface Potential	189
9.3.3	Effect on the Drain Current	194
9.3.4	Effect on Small-Signal Parameters in Weak Inversion	196
9.4	Short-Channel Thermal Noise Model	197
9.4.1	Thermal Noise Drain Conductance	198
9.4.2	Effect of VS and Carrier Heating on Thermal Noise	205
9.4.3	Effects of Vertical Field Mobility Reduction and Channel Length Modulation	209
9.4.4	Summary	211
10	The Extrinsic Model	213
10.1	Extrinsic Part of the Device	213
10.2	Access Resistances	215
10.2.1	Source and Drain Resistances	215
10.2.2	The Gate Resistance	217
10.3	Overlap Regions	220
10.3.1	Overlap Capacitances	220
10.3.2	Overlap Gate Leakage Current	223
10.4	Source and Drain Junctions	223
10.4.1	Source and Drain Diodes Large-Signal Model	223
10.4.2	Source and Drain Junction Capacitances	224
10.4.3	Source and Drain Junction Conductances	226
10.5	Extrinsic Noise Sources	226
Part III	The High-Frequency Model	229
11	Equivalent Circuit at RF	231
11.1	RF MOS Transistor Structure and Layout	231
11.2	What Changes at RF?	231
11.3	Transistor Figures of Merit	232
11.3.1	Transit Frequency	232
11.3.2	Maximum Frequency of Oscillation f_{\max}	236
11.3.3	Minimum Noise Figure	238
11.3.4	Moderate and Weak Inversion for RF Circuits	239
11.4	Equivalent Circuit at RF	240
11.4.1	Equivalent Circuit at RF	240
11.4.2	Intradevice Substrate Coupling and Substrate Resistive Networks	242
11.4.3	Practical Implementation Issues	247
12	The Small-Signal Model at RF	249
12.1	The Equivalent Small-Signal Circuit at RF	249
12.2	Y-Parameters Analysis	251
12.3	The Large-Signal Model at RF	257

CONTENTS xi

13 The Noise Model at RF	261
13.1 The HF Noise Parameters	261
13.1.1 The Noisy Two-Port	261
13.1.2 The Correlation Admittance	263
13.1.3 The Noise Factor	265
13.1.4 Minimum Noise Factor	266
13.2 The High-Frequency Thermal Noise Model	267
13.2.1 Generalized High-Frequency Noise Model	268
13.2.2 The Two-Transistor Approach at High Frequency	269
13.2.3 Generic PSDs Derivation	272
13.2.4 First-Order Approximation	273
13.2.5 Higher Order Effects	279
13.3 HF Noise Parameters of a Common-Source Amplifier	282
13.3.1 Simple Equivalent Circuit Including Induced Gate Noise and Drain Noise	282
13.3.2 Equivalent Circuit Including Induced Gate Noise, Drain Noise, Gate and Substrate Resistances Noise	288
References	291
Index	299

