

Index

- 3GPP (3rd Generation Partnership Project) 4–5, 8, 10, 12–13, 20, 30–5, 37, 39, 40, 48, 50, 51–6, 59, 61, 72, 78, 80, 82, 86, 89, 90, 108, 163, 182, 207, 216, 218, 219–20, 222, 225, 226, 240–1
- Abstract Service Primitive (ASP) 233–5
- Abstract Syntax Notation One (ASN.1) 156, 220, 231–2, 239
- Abstract Test Suite (ATS) 224, 239–40
- Acceptable Cell 153, 198–9
- Acceptance 6, 7, 20, 49, 53, 54, 59, 64–5, 67–9, 171, 197
- Access Point Name (APN) 173, 193
- Access Service Class (ASC) 125, 126, 131–2
- ASCII 47, 231
- Access Stratum (AS) 40, 41, 47, 217
- Acknowledged Mode (AM) RLC 132, 135, 137–41, 144, 186, 208
- Acquisition Indicator Channel (AICH) 83, 85, 98, 131, 132, 185
- Activate PDP context 193–4
- Activate secondary PDP context 174
- Active set 161–2, 166, 195–6, 204–6
- Adaptive Modulation and Coding (AMC) 207
- Adaptive modulation 82, 89, 92, 105–8, 112, 119, 149, 207–8, 222
- Adaptive Multi-Rate Wideband (AMR-WB) 35, 52
- Adaptive Multi-Rate (AMR) speech codec 35, 52, 189
- Additive White Gaussian Noise (AWGN) 116
- Adjacent Channel Leakage Power Ratio (ACLR) 73, 102, 103, 104, 212
- Adjacent Channel Selectivity 110–1
- Adversarial testing 26
- ALOHA 130–1
- AM-RLC, *see* Acknowledged Mode (AM) RLC
- AS, *see* Access Stratum (AS)
- Assisted Global Positioning System (A-GPS) 35, 41, 42, 50, 51, 56, 59
- Association of Radio Industries and Business (ARIB) 11, 12, 52, 59
- AT commands 27, 189
- Attach 170–1, 174, 188–9, 191–3, 239
- Authentication Centre (AuC) 147, 148, 169
- Authentication 41, 95, 109, 151, 169–70, 188, 190–4
- Authentication vector 169, 191
- Automatic Repeat Request (ARQ) 135–6
- Automation 27, 221
- Barred or Reserved Cell 67, 198, 201
- Base constraint 230
- Base Station Controller (BSC) 149
- Base Transceiver Station (BTS) 149
- Baseband 24, 37, 44, 93, 105, 116, 118–19, 183, 222
- Birth-death 116
- Bit Error Rate (BER) 106, 117
- Block Error Rate/Block Error Ratio (BLER) 45, 59, 116–17, 157, 166, 203, 205
- Blocking characteristics 111–12
- Broadcast Channel (BCH) 122, 123, 124, 125, 150, 155, 185, 186, 197
- see also* Broadcast Control Channel (BCCH)
- Broadcast Control Channel (BCCH) 83, 122–6, 128, 133, 185–6
- Broadcast Control Functional Entity (BCFE) 150
- Broadcast/Multicast Control (BMC) 48, 123, 146, 177

- C/C++ language 51, 179–80
- C/T Field 129–30
- Call Control (CC) 49, 56, 149, 171, 182, 218
- Cell Broadcast (CBS) 146, 177
- Cell identity 155
- Cell Radio Network Temporary Identifier (C-RNTI) 130, 154, 160, 161, 194, 195
- Cell reselection 26, 47, 48, 66, 151, 153–5, 198–205
- Cell selection 47, 151, 153, 155, 188, 192, 198–205
- Cell update 48, 153, 159–61, 194–5
- Cell update procedure 48, 153, 161
- CELL_DCH 26, 152, 153, 156, 159, 161, 186, 188, 189, 190, 192, 193, 205
see also RRC States
- CELL_FACH 26, 113, 114, 152–3, 156, 159, 160–1, 186, 194–5, 205
see also RRC States
- CELL_PCH 152–4, 156, 160
see also RRC States
- Certification 5, 7–8, 16–17, 20–1, 29–30, 41, 51, 53, 55–61, 65, 66
- Change request 54–5
- Channel Coding 80–2, 91, 149, 207
- Channelization code 80–2, 111, 122, 161, 162, 186, 208–10
tree 81
- Chase Combining 210
- China Communication Standards Association (CCSA) 12, 52
- Ciphering 37, 41, 127, 134, 136, 137, 151, 157, 169–70, 181, 187–9, 191–3
- Circuit Switched (CS) 49, 132, 148–9, 169, 170, 182, 189, 216, 217, 229–30
- Closed loop power control 39, 72, 77, 82, 84, 85, 94–9, 101, 106, 115, 132, 205, 207, 212
- Code Division Multiple Access (CDMA) 4, 9–11, 61, 102
CDMA-2000 10
- Code domain error 73, 106–7
- Code tree, *see* Channelization code tree
- Codec 13, 24, 35, 51–2, 59, 149, 183, 189, 218, 220
- Common channel 82, 84, 97, 110, 121, 122, 124, 125, 136, 151, 153, 155, 159, 185, 186, 195, 208
- Common Control Channel (CCCH) 123, 186
- Common Pilot Channel (CPICH) 83–4, 97–8, 106, 111, 164–5, 186, 200, 205, 206, 233
- Common Traffic Channel (CTCH) 123, 125, 128, 134, 146
- Communication point 233
- Compressed mode 39, 114–15
- Compression 144–6
- Compression method 144
- Concatenation 132, 134, 135, 137, 146
- Connection management 151, 156, 169, 170–3
- Connection mobility 48, 151
- Constraint 15, 27, 89, 212, 228–32, 235–40
- Continuous packet connectivity 222
- Control PDU 135, 137, 138, 140
- Control plane 125, 141
- Control super field 138–42
- Convolutional coder 80–2
- Convolutional Coding 91
- Core Network (CN) 4, 13, 34, 121, 144, 147–8, 154–6, 158, 170, 217, 221
- CRC 91, 116, 166
- CRNC 127, 153, 154, 156, 157, 160–2, 211, 217, 222
- CW Signal 108–9
- D/C field 137
- DECT 10–11
- Dedicated Channel (DCH) 41, 85, 122
- Dedicated Control Channel (DCCH) 83, 90–1, 123, 125–9, 130, 133–4, 137, 156, 187–8, 190, 192–3
- Dedicated Control Functional Entity (DCFE) 150
- Dedicated Physical Channel (DPCH) 89, 153, 186
- Dedicated Physical Control Channel (DPCCCH) 84, 85
- Dedicated Physical Data Channel (DPDCH) 84, 85
- Dedicated Traffic Channel (DTCH) 90, 123
- Default behaviour 237, 240
- Deregulation 17, 29, 30, 53
- Direct
sequence 10–11
spread 10–11
transfer 151, 157, 226
- Discontinuous Reception (DRX) 146
- Discontinuous Transmission (DTX) 209
- Domain Name Service (DNS) 173, 218
- Drift RNC (DRNC) 144
- Dual-mode 13, 114
- Dual Transfer Mode (DTM) 162
- Dynamic behaviour 227–9, 235–9
- Dynamic rate control 86
- EDGE compact
IS-136 HS 11
- EDGE 4, 11, 13, 161, 222
- EGPRS 4, 10
- Electro Magnetic Radiation Compliance (EMC) 29, 35, 50, 57, 59
- Encryption 234
- Enhanced Dedicated Channel (E-DCH) 46, 154, 208–9, 212
- Enhanced Dedicated Physical Control Channel (E-DPCCH) 209–10
- Enhanced Dedicated Physical Data Channel (E-DPDCH) 209
- Enhanced Uplink (E-UL) 56, 89, 207, 208–209, 210, 211, 222

- Equivalent PLMN (EPLMN) 198
- Error Vector Magnitude (EVM) 106
- ESP 144
- ETR 141
 - TTCN style guide 229
- European Telecommunications Standards Institute (ETSI) 4, 10–12, 30–1, 37, 51–5, 216, 219, 229, 230, 241
- Fading 36, 97, 116–17
- Fading Simulator 116–17
- Field Programmable Gate Array (FPGA) 24
- Fixed Reference Channel (FRC) 212
- Forward Access Channel (FACH) 114, 122–3, 125–6, 128–30, 146, 152, 153, 156, 159, 160–1, 185–6, 194
- Frequency control 101
- Frequency Division Duplex (FDD) 5, 50–1
- Frequency Division Multiple Access (FDMA) 9, 222
- Gateway GPRS Support Node (GGSN) 173
- Gateway MSC (GMSC) 147, 148
- Gaussian filter 102
- Gaussian Minimum Shift Keying (GMSK) 111
- General Packet Radio System (GPRS) 4, 31, 144, 149, 162, 170, 171, 173, 182, 188, 189, 191
- Global Certification Forum (GCF) 8, 30, 53, 55–61, 66, 217
- Global Positioning System (GPS)
 - Assisted Global Positioning System (AGPS) 41, 50, 51
- GPRS Mobility Management (GMM) 13, 148–9, 168, 170–1, 174–6, 182, 191–3, 218
- GPRS Radio Resources (GRR) 182, 218
- Graphical scripting 181, 221
- Graphical tool 220, 221
- Group System Mobile (GSM) 4, 6, 10, 12–14, 30–1, 34, 39, 42–4, 46–9, 53, 55, 57, 86, 114, 121, 147–9, 155, 158, 162–3, 166, 182–3, 205
- GSM Carrier RSSI 166
- GSM/EDGE Radio Access Network (GERAN) 4, 13
- Hard Handover (HHO) 26, 48, 154, 162, 203, 203
- Header Extension (HE) field 137
- Hierarchical cell selection 200
- High Speed Downlink Packet Access (HSDPA) 32–3, 46, 56, 66, 121, 154, 207–9, 212, 222
- High Speed Downlink Physical Control Channel (HS-DPCCH) 208, 209, 212
- High Speed Packet Access (HSPA) 14, 207–12
- High Speed Shared Control Channel (HS-SCCH) 208
- High Speed Uplink Packet Access (HSUPA) 208
 - see also* E-UL
- Higher layer scheduling 114
- Home Location Register (HLR) 156
- Home PLMN (HPLMN) 197–8
- Human Operator
 - test operator 69, 146, 189
- Hybrid ARQ (HARQ) 207–11
- Idle Mode 47–8, 151–6, 160, 169, 177, 197, 199, 203
- Implementation Conformance Statement (ICS) 47
 - see also* PICS
- Implementation Under Test (IUT) 223–5
- IMT-2000 4, 9–11, 13, 14, 61
- In-band blocking 111–12
- Incremental redundancy 210
- Indentation
 - level 227–8, 235–6, 238–9
- Infrastructure 6, 14, 17, 20, 26, 38, 52, 63–5, 67, 69, 90
- Inner loop power control 72, 94, 96, 97, 106
- Integrated Multimedia Subsystem (IMS) 56
- Integrity 41, 151, 157, 169, 170, 187, 189, 191–3
 - protection 151, 187
- Inter-frequency measurements 73, 164, 165, 205
- Inter-RAT handover 26, 162–3, 205
- Inter-RAT reselection 26, 162–3, 166, 205
- Interference signal 107, 112–13
- Interleaving 81, 82, 86, 87, 91
- Intermodulation 107–8, 112–13
 - characteristics 112–13
- International Mobile Subscriber Identity (IMSI) 154, 170–1, 188, 191
- International Telecommunications Union (ITU) 4
- Internet Engineering Task Force (IETF) 144
- Internet Protocol (IP) 15, 144, 216
- I_{oc} 117
- I_{or} 98, 100, 101, 108, 110, 113, 117, 203
- IPSec 144, 218
- ISO/IEC 9646 223–4
- Length indicator 134–5, 138, 142
- Link failure 26, 161, 203
- List and relative list 140
- Local oscillator 101, 106, 115
- Location Area (LA) 154
- Location Area Code (LAC) 201
- Location Based services (LCS) 49
- Location registration 153
- Location update 26, 170, 186, 188, 191, 198, 199, 201
- Logical channel 25, 82, 83, 87, 90, 121–3, 127–9, 132, 133, 139, 146, 157, 160, 186
- Long-Term Evolution (LTE) 31, 220, 222
- Loss of synchronization 99, 101, 161, 162, 186, 197, 234
- Lossless SRNS Relocation 145

- MAC PDU 127–9
- Macrocell 200
- Macrodiversity 161
- Master Information Block (MIB) 155, 185, 201
- Maximum power 95–6, 106, 108, 110
- Measurement accuracy 103, 200, 204
- Measurement events 165, 167
- Measurement object 164, 166
- Measurement quantity 166, 205, 206
- Measurement timing 204
- Measurement uncertainty 103
- Measurement validity 164–5
- Medium Access Control (MAC) 13, 122, 124–132, 158, 211
- Mobile broadband 222
- Mobile originated call 171–2
- Mobile originated 26, 66, 171, 189
- Mobile Switching Centre (MSC) 149
- Mobile terminated call 172, 195
- Mobile terminated 26, 27, 66, 172, 195
- Mobility Management (MM) 48, 149, 169, 170, 182
- Mobility 12, 30, 48, 148–51, 159, 161, 163, 169–70, 182, 194–5, 200
- Modulation quality 106
- Modulation 73, 82, 89, 92, 105–8, 112, 113, 117, 119, 149, 206–8, 222
- Monitored Set 161
- Move Receiving Window 140
- Multicast 41, 48, 56, 146
- Multicode 107, 212
- Multimedia Messaging Service (MMS) 60, 66, 150, 169
- Multipath 116–17
- Multipath profiles 116
- Multiple Input Multiple Output (MIMO) 222

- Narrow band blocking 35, 111, 113
- Network emulation 181
- Network Operating Mode 169, 174, 188
- Network operator 6–7, 17, 18, 20, 30, 39, 41, 53, 64, 67, 69, 86, 173, 177, 220
 - Operator 4–7, 11, 13, 17, 18, 20–1, 27, 30, 38–41, 44, 53, 57, 59, 61, 64, 65, 67, 68, 69, 86, 112, 114, 146, 171, 173, 177, 189, 197–9, 216, 220, 232
- Node B 25, 85, 89, 94–5, 97, 100–1, 105, 108, 114, 124, 130, 148–9, 160, 161, 207–9, 211, 222
- Non Access Stratum (NAS) 13, 41–2, 47–8, 95, 150–1, 153, 157, 158, 168, 182, 187–8, 190, 192–3, 197, 218, 226, 228, 234
- Nonlinearity 72, 89, 103, 105, 106, 107
- Notification 150, 151, 176, 177
- NSAPI 173, 193, 194
- Numerically controlled oscillator 101

- Occupied bandwidth 73, 102
- Open Loop Power Control 72, 97, 132, 205
- Orthogonal Channel Noise Simulation (OCNS) 110
- Orthogonal codes 10, 79, 80, 131
- Orthogonal Frequency Division Multiple Access (OFDMA) 222
- Out-of-band blocking 111, 112
- Out-of-band power 89
- Orthogonal Variable Spreading Factor (OVSF) 38
- Outer-loop power control 94

- P-TMSI 154, 171, 191
- Packet Control Unit (PCU) 147–8
- Packet Data Convergence Protocol (PDCP) 13, 24, 48, 143–6, 148–9, 157, 158, 182, 183, 218
- Packet Data Protocol (PDP) 26, 27, 150, 168, 173–5, 191, 193–4
- Packet-switched (PS) 15, 49 66, 88, 132, 143, 148–50, 154, 169, 173, 182, 209, 216
- Paging Channel (PCH) 122, 186
- Paging Control Channel (PCCH) 122
- Paging Indicator Channel (PICH) 85, 186
- Paging Notification Functional Entity (PNFE) 150
- Paging 85, 122, 150–1, 156, 157, 160, 169–72, 186, 194–5, 199
- Parasitic coupling 92, 103
- Pcompensation 200
- PCS Type Certification Review Board (PTCRB) 53, 57
- PDP context
 - activation 26, 27, 174, 175, 191, 193
 - deactivation 174–5
 - modification 174–5
- Peak-to-average Power Ratio (PAR) 105, 107, 212
- Phase discontinuity 106, 212
- Physical channel 38, 48, 72, 73, 82, 84, 88–9, 97, 122, 153, 158–62, 164, 186, 207–9, 233
 - reconfiguration 48, 159–62
- Physical Layer (PHY) 5, 11, 23–5, 33, 77–119, 124, 132, 149, 158, 159, 161, 162, 208, 233–4
- Physical Random Access Channel (PRACH) 82, 85, 97–9, 107, 131, 132, 155, 160, 161, 185, 186
- Piggy-backed status 136, 139, 142
- Pilot 21, 84, 97, 132, 186
- PLMN reselection 26
- PLMN selection 47, 152, 153, 188, 192, 197–201
- Plug-fest 218
- PN sequence 78, 80, 109
- Point of Control and Observation (PCO) 233–4
- Polling request 137
- Power Class 96, 113
- Power command 95, 97, 115
- Power control 39, 72, 77, 82, 84, 85, 94–9, 101, 106, 115, 132, 205, 207, 212

- Power mask 99, 100
- Power spectral density 100
- Power Step 95, 96, 98, 115
- Preamble 98–9
- Primary Common Control Physical Channel (P-CCPCH) 84, 111, 185–6, 205
- Primary Common Pilot Channel (P-CPICH) 97
- Primary Synchronization Channel (P-SCH) 85, 185, 186
- Processing gain 82, 89
- Protocol conformance test system 29, 35, 36, 38, 39, 44, 46, 54, 117–18, 203, 206
- Protocol Data Unit (PDU) 90, 127–9, 133–46, 176, 212, 229, 234
- Protocol Implementation Conformance Statement (PICS) 219
- Protocol Implementation eXtra Information for Testing (PIXIT) 219
- PS domain 150, 170, 171, 192, 216
- Pseudorandom number sequence 78, 80, 109
- Public Land Mobile Network (PLMN) 155, 171, 188, 195, 202, 217
- Puncturing 81, 210

- QhystX 200
- QoffsetX 200
- Qqualmin 114, 200
- Qrxlevmin 114, 200
- Quadrature Amplitude Modulation (QAM) 82, 89, 208, 212, 222
- Quadrature Phase Shift Keying (QPSK) 82, 89, 105, 208
- Quality of Service (QoS) 18, 94, 108, 121, 157, 162, 173, 174, 193, 205, 207, 222

- RACH Procedure 130–2, 160, 189, 203
- Radio & Telecommunication Terminal Equipment (R&TTE) 57–8
- Radio Access Bearer (RAB) 141, 144, 158, 189, 190, 193–4
- Radio Access Network (RAN) 4, 13, 121–45, 147
- Radio Access Technology (RAT) 26, 162–4, 166, 199, 205
- Radio Bearer Establishment 159
- Radio Bearer Management 150, 151, 159, 162
- Radio Bearer Reconfiguration 159
- Radio Bearer Release 159, 191, 194
- Radio Bearer (RB) 26, 39–41, 48–50, 90, 96, 109, 119, 129, 132, 133, 144, 151, 157–63, 173, 189, 191, 193, 194, 204, 232
- Radio Communication Analyser (RCA) 93
- Radio frame 83, 91
- Radio Link Control (RLC) 13, 182
- Radio Network Controller (RNC) 94, 114, 124, 127, 129, 144, 148–51, 153, 154, 156, 157, 160, 161, 162, 211, 217, 222
- Radio Network Temporary Identity (RNTI) 130, 154, 160–1, 194–5
- Radio Resource Control (RRC) 13, 48, 182
- Radio Resource Management (RRM) 45, 182
- Radio Resource (RR) 13, 45, 48, 162, 182
- Radio spectrum allocations 9
- Random Access Channel (RACH) 83, 85, 97–9, 122, 123, 125, 126, 128–32, 153, 156, 160, 185, 186, 189, 200, 203
- Random access procedure 203
- Rate Matching (RM) 91
- Real-time Transport Protocol (RTP) 144
- Reassembly 132–4, 137, 141–2, 156
- Receive constraint 230–1, 237
- Received Signal Code Power (RSCP) 97, 98, 164, 165, 200, 205
- Received Signal Strength Indicator (RSSI) 166, 205
- Receiver characteristic test 212
- Receiver sensitivity 108–9
- Reference Measurement Channel (RMC) 90, 91, 92, 96, 100, 101, 102, 109, 116–17, 212
- Reference Sensitivity 73, 108–9, 110, 112–13
- Reference Sensitivity Level 108, 110, 113
- Registration 26, 153–4, 160, 169, 170, 171, 188, 190, 192–3, 195, 201, 202
- Release 4 32, 33, 34, 56, 144
- Release 5 32, 33, 46, 56, 82, 110, 149, 207, 212, 216
- Release 6 56, 105, 155, 207, 208, 212
- Release 7 41, 82, 89, 220, 222
- Release 99 30, 32, 40, 41, 44, 50, 54, 55, 56, 66, 82, 110, 144, 212
- Reporting Criteria 164, 165, 167
- Request for Comments (RFC)
 - RFC 2507 144
 - RFC 3095 144
- Reselection 26, 47, 48, 66, 151, 153–5, 159, 198–205
- RF conformance test system 38, 39, 117, 118, 203, 206
- Robust Header Compression (ROHC)
 - RFC 3095 144
- Root raised cosine
 - filter 95, 102, 103, 105, 108
- Routing Area (RA) 129, 154, 155, 171, 202
 - code 201
- Routing Functional Entity (RFE) 150
- RRC connection establishment 156
- RRC connection management 156–7
- RRC connection 20, 41, 48, 95, 97, 109, 114, 136, 150–3, 156–9, 170, 172, 186, 188–93, 200, 201–3
- RRC connection release 157, 188, 190, 192

- RRC re-establishment delay 203
- RRC States
- CELL_DCH 26, 152, 153, 156, 159, 161, 186, 188, 189, 190, 192, 193, 205
 - CELL_FACH 26, 113, 114, 152–3, 156, 159, 160–1, 186, 194–5, 205
 - CELL_PCH 152–4, 156, 160
- Satellite 11, 42
- Scrambling 78, 80, 89, 100, 105, 108, 122, 131, 149, 158, 159, 161, 162, 209, 215, 233
- Scrambling Code 80, 89, 100, 105, 122, 131, 158, 159, 162, 207, 209, 215, 233
- Secondary Common Control Physical Channel (S-CCPCH) 84, 113, 153, 185–6
- Secondary Common Pilot Channel (S-CPICH) 84
- Secondary context activation 174
- Secondary PDP context activation 174
- Secondary Synchronization Channel (S-SCH) 85, 186
- Security mode control 157, 170
- Segmentation 91, 132–5, 137, 141–2, 146, 156
- Sequence chart 184, 186
- Sequence number 134, 135, 137–42, 144–5, 169, 176, 209
- Service Access Point Identifier (SAPI) 158, 234
- Service Access Point (SAP) 104, 133–4, 137, 150, 229
- Service Data Unit (SDU) 133
- Serving GPRS Support Node (SGSN) 144, 147–9, 154, 168, 169, 170, 175, 217, 222
- Serving Radio Network Controller (SRNC) 162
- Serving Radio Network Subsystem (SRNS) 144
- Session management 49, 173, 182
- SF/2 114, 115
- SFN-SFN Observed Time Difference 205
- Short Message Service (SMS) 13, 49, 66, 140, 146–8, 150, 168, 175–7, 237
- Short Message Service Switching Centre (SMS-SC) 147, 148, 150, 175, 176
- Signal Analyzer 107
- Signal generator 19, 24, 71, 92, 93, 107–9, 113, 117
- Signal-to-Interference Ratio (SIR) 85, 86, 88, 89, 94, 95, 114, 115, 124, 158, 161, 207
- Signal-to-Noise Ratio (SNR) 78, 79, 80, 82, 85
- Signalling connection release 157
- Signalling procedures 5, 48, 184, 221
- Signalling Radio Bearer (SRB) 157–158, 191
- $S_{\text{intersearch}}$ 114, 199
- $S_{\text{intrasearch}}$ 114, 199
- Slotted ALOHA 130
- Snapshot 236, 238
- Soft Handover (SHO) 26, 154, 161, 162, 195, 203
- Special Mobile Group (SMG) 12
- Specific Absorption Ratio (SAR) 29, 59
- Spectrum allocations 9
- Spectrum Emission Mask (SEM) 73, 102–3, 212
- Spreading 11, 38, 78, 79, 89, 99, 111, 158
- Spreading Factor (SF) 38, 79, 83, 111, 158
- Spurious emissions 102–4, 113–14
- SRNS relocation 144–5
- $S_{\text{search}_{\text{RATn}}}$ 199
- State Transitions 48, 160, 194
- Status PDU 136, 137
- Structured type 232
- Subscriber Interface Module (SIM) 34, 51
- Suitable Cell 153, 198–9
- Super Field (SUFI) 138, 140–2
- Supplementary services 49, 66
- Symbol Rate 208
- Synchronization Channel (SCH) 83, 85, 111, 185, 186
- System Architecture Evolution (SAE) 222
- System Frame Number (SFN) 186, 187, 205
- System Information Block (SIB) 146, 155
- System information 20, 26, 39, 97, 113, 122, 124, 146, 151, 155–6, 160, 167, 169, 184, 185, 188–90, 192, 193, 195, 197–202
- System Simulator (SS) 24, 25, 65, 67, 107, 109, 117, 119, 148, 179
- Target Channel Type Field (TCTF) 125, 126, 128, 129, 130, 146
- Telecommunications and Internet Converged Services and Protocols for Advanced Networks (TISPAN) 216, 219
- Temporary Mobile Subscriber Identity (TMSI) 154, 170, 171, 188, 191, 192
- Terrestrial 11
- Test-fest 218
- Test house 7, 56, 57, 58, 118
- Testing
- acceptance 6, 7, 53, 64, 65, 67, 69, 171, 197
 - conformance 7–8, 12, 17, 20, 25, 29–61, 63, 65, 66, 72, 118, 145, 177, 197, 216, 219, 224–6
 - integration 7, 17, 19–20, 23–7, 92, 179, 215, 216, 220
 - interoperability 7, 8, 17–18, 20, 30, 39, 49, 63–9, 218
 - IP 218
 - manufacturing 7, 21, 57, 71–2, 73–4, 93
 - parallel 225
 - regression 18, 20, 26, 27, 69
 - transmitter testing 92
 - virtual 215
- Test loop 43, 48, 72, 93, 95, 96, 99, 101, 106, 108, 109, 113, 116, 141, 144, 225, 226
- Test network 20, 64, 66–8

- Test operator 69, 146, 189
- Test step 228, 238–40
- Test suite operation 141, 156, 163
- Test Suite overview 240
- Time Division Duplex (TDD) 10, 11, 33, 35, 46, 48, 50, 124
- Time Division Multiple Access (TDMA) 9, 10, 11, 162
- Time Division Synchronous Code Division Multiple Access (TD-SCDMA) 11
- Traffic Flow Template (TFT) 174
- Transfer Management Entity (TME) 150
- Transmission Control Protocol (TCP) 25, 144, 174, 218
- Transmission Time Interval (TTI) 86, 87, 88, 91, 99, 133, 159, 204, 212, 233
- Transmit Diversity 39, 84, 222
- Transmit window 139, 140, 142
- Transmitter Intermodulation 107–8
- Transmitter Power Control (TPC) 83, 84, 94–7, 100, 106, 109, 161
- Transparent Mode (TM) 108, 116, 124, 125, 127, 132, 133, 141, 143
- Transparent Mode RLC (TM RLC) 116, 125, 133, 143
- Transport Block Set (TBS) 90
- Transport Block (TB) 25, 85–8, 92, 99, 124, 155, 158, 183, 186
- Transport channel 82, 87, 88, 90, 91–2, 108, 121–9, 149, 158–61, 166, 186, 189, 205, 233
- Transport channel reconfiguration 159
- Transport Format Combination Index (TFCI) 83, 84, 86, 87, 88, 89, 98, 99, 114, 124, 209
- Transport Format Combination Set (TFCS) 86, 87, 88, 99, 204
- Transport Format Combination (TFC) 84, 86, 209
- Transport Format Set (TFS) 85, 87, 88, 90, 233
- Transport Format (TF) 84, 86, 87, 88, 133, 158, 186, 209–11
- Treselection_s 199
- TTCN2 31, 37, 47, 69, 179, 184, 219, 220, 240
- TTCN3 37, 218–20
- TTCN execution 235–8
- TTCN test suite 220, 226, 227, 229, 241
- Turbo coder 81
- Type approval 29–31, 53, 57
- UE Capability Information 157
- UE internal measurements 166
- UE measurement reporting 151
- UE Rx Tx time difference 166, 206
- UE Transmit timing 204
- UE Transmitted Power 166, 205
- UMTS Subscriber Interface Module (USIM) 13, 34, 35, 41, 44, 51, 59, 169, 171, 177, 198, 201
- UMTS Terrestrial Radio Access Network (UTRAN) 4, 12, 13, 33, 77, 147, 148, 152, 154–6, 161, 162–3, 166, 169, 194, 195, 199, 203
- UMTS Terrestrial Radio Access (UTRA) 101, 166, 205
- Unacknowledged Mode RLC (UM-RLC) 132–4, 137, 139, 141, 146
- Unacknowledged Mode (UM) 132–5, 141, 142, 158
- Uniform Resource Locator (URL) 173
- Universal Integrated Circuit Card (UICC) 44
- Universal Mobile Telecommunications System (UMTS) 4, 38, 43, 44, 46, 50
- Universal Serial Bus (USB) 27, 173
- Unpaired bands *see* unpaired spectrum
- Unpaired spectrum 10
- URA_PCH, *see* RRC STATES
- USAT 35, 51, 56
- User Datagram Protocol (UDP) 25
- User Equipment (UE) 3, 4, 5, 44, 46
- UTRA Absolute Radio Frequency Channel Number (UARFCN) 101, 105, 158
- UTRA Carrier RSSI 166, 205
- UTRAN Radio Network Temporary Identity (U-RNTI) 130
- UTRAN Registration Area (URA) 154
- Visited PLMN (VPLMN) 198
- Visitor Location Register (VLR) 156, 169, 170
- Voice over IP (VoIP) 216
- WARC 11
- White noise 36, 77, 78
- Wideband CDMA (WCDMA) 61
- Window size 139, 140
- Window stalling 139
- X.290 series 223

