

Index

- Accelerating voltages 200
- Acoustic phonons 22
- Al_2O_3 107
- Amorphous photo-resist layer 217
- Anisotropic
 - crystals 77
 - properties 18
- Antiferrodistortive 153
- Application specific silicon integrated circuit (ASIC) 221
- Atomic force microscopy (AFM) 189, 332
 - High voltage AFM 190
 - imaging 309
 - low and high voltage 195
 - low voltage technique 193
- Axis of revolution 82

- $\text{Ba}(\text{Mg}_{1/3}\text{Ta}_{2/3})\text{O}_3$ 107
- $\text{Ba}_x\text{Sr}_{1-x}\text{TiO}_3$ 107
- Ba-Nd-Ti-O 107
- Ba-Zn-Ta-O 107
- Barium titanate 17
- BaTiO_3 18, 26
- Berlincourt meters 46
- Biaxial indicatrix 83
- Birefringence 84
- Bismuth-layer-structured ferroelectric (BLSF) 122
- Boltzmann's constant 171
- Born approximation 96
- Bose statistics 104
- Bound surface charge density 243
- Bragg
 - angle 126, 179
 - condition 149
 - peaks 155
- Brillouin
 - scattering 292
 - zone 105
- Broad-band test devices 109
- Built-in polarization 246
- Burns temperature 278
- Butterfly loop 35, 146

- Ca-Ti-Nd-Al 107
- Calcite rhomb 79
- Cantilever 211
- Capacitance-voltage curve 33, 73
- Capillary forces 242
- CaTiO_3 107
- Chaotic behavior 263
- Charge amplifiers 254
- Chess board 201
- Clausius-Mossotti
 - equation 15
 - relation 106
- Clockwise response-field 257
- Clusters 200
- Coercive
 - field 17
 - voltage 59
- Cole-Davidson-type exponent 297
- Collimator 124
- Comparison of noise and signal 225
- Complex
 - impedances 108
 - reflection and transmission coefficients 108
- Controlling chaos 269
- Converse piezoelectric effect 252
- Cooper pairs 101
- Coplanar
 - ridge structure waveguide 93
 - transmission lines 114
- Core-Shell structures 28

- Coulomb force 243
- Coupled electro-mechanical 257
- Coupling
 - coefficient 43, 170
 - ports 111
 - strength 111
- Courtney 114
- Critical incident angle 126
- Cross-sectional TEM 132
- Crystal
 - bulk 180
 - truncation rod (CTR) 154
- Crystalline system 11
- Curie-von-Schweidler behavior 36
- Curie-Weiss law 17, 19, 282
- Current step method 58
- Czochralski technique 172

- De-aging procedure 69
- Debye
 - Scherrer ring 125
 - relaxation 103
- Depolarization
 - energy 214
 - field 190
- Depth
 - selective piezoelectric response 359
 - profile 127
- Dielectric
 - constant 14, 92
 - function 16
 - losses 16
 - nonlinear series-resonance circuit 263
 - permittivity 358
 - polarization 13
 - properties 227
 - surface layer 248
 - susceptibility 14, 166
- Diffractionmeter 119
- Diffuse phase transitions 27
- Dip-pen nanolithography (DPN) 211
- Domain
 - boundary 347
 - broadening 212
 - coalescence 215
 - elongation 206
 - energy 203, 214
 - forward growth 202
 - in BaTiO₃ single crystal 306
 - inverted \sim 321
 - reorientation 144
 - shape invariant 206
 - structure 31
 - surface energy 214
 - density 207
 - switching 149
 - two-dimensional structure 197
- Domain wall
 - in PZT 310
 - motion 33, 209
 - polarization 15
- Doping 27
- Double
 - beam interferometry 48
 - refraction 78
- Downscaling of ferroelectric capacitors 367
- Duffing equation 264
- Dynamic
 - hysteresis measurement 59
 - switching 249

- Effective
 - coefficients 47
 - dielectric polarization P_z 241
 - electro-optic coefficient 177
 - microwave index 93
 - trap density 177
- Eigenmode 112
- Elastic compliance 43
- Electrical
 - breakdown 87
 - channels 191
 - characterization of ferroelectrics 53
 - conductivity 211
 - resistivity 231
 - stray field energy 30
- Electromechanical
 - hysteresis 251
 - properties 138
- Electron
 - hole competition factor 179
 - beam (EB) lithography 198
 - injection 246
 - quasi-drop 202
- Electronic
 - harmonic oscillator 84
 - polarization 15
- Electrooptic

- coefficient 85, 172
- effect 83
- media 164
- needle 90
- tensor 85
- Ellipsoid equation 86
- Ellipsometry 244
- Elliptically polarized 84
- Energy minimum 215
- Excitation signal 54
- External screening process 216
- Extrinsic contribution 40, 138, 149
- Fast pulse measurements 340
- Fatigue 355
 - excitation signal 67
 - measurement 66
- FeRAM 62
 - chain ~ 338
- Ferroelectric
 - domain 30
 - breakdown 189
 - limit 352
 - materials 24, 27
 - phase transition 154
 - polarization 17
 - switching 35
 - transition 155
- Fiber-texture 125
- Filling factor 112
- Finite element method (FEM) 337
- First order phase transition 20
- Flipchip 116
- Fluorite-SBTN 131
- Focused ion beam (FIB) 330
- Form immobile electron 217
- Free charge injection 208
- Free energy 19, 149, 212
- Frequency dependence 16
- Frozen polarization nano domains 361
- Gain factor 177
- Gaussian beam 89
- Gibb's free energy 141
- Ginzburg-Landau theory 18
- Glan-Thomson prism 172
- Grain
 - diameter 350
 - size effects 26
- Grating vector 170
- Grazing incidence X-ray diffraction (GIXRD)
 - 121, 122, 132, 134
- Griffiths temperature 278
- H. A. Lorentz 83
- Half-ellipsoidal domain 213
- Half-wave symmetry 256
- Hamiltonian 279
- Harmonic oscillators 103
- Helmholtz double layer 246
- Heteroepitaxial 154
- HF etching 200
- High-resolution synchrotron
 - X-ray diffraction 137, 145
- High-resolution synchrotron 149
- High-temperature
 - XRD 143
 - superconductor (HTS) 101
- Higher order nonlinear dielectric microscopy
 - 312
- Hooke 94
- Huyghens 78
- Image charges 204
- Impedance 100
- Imprint 68
- In situ X-ray studies 151, 153, 154
- Inclination 81
- Indirect electron beam exposure 194
- Infrared light 97
- Initial state of polarization 338
- Integrated optics 89
- Interaction energy 204
- Interaxial angle 128
- Interference patterns 88
- Intrinsic
 - contribution 40, 138
 - deformation 149
 - strain 146, 147
 - unipolar strain 147
- Inversely-polarized nanodomains 372
- Ionic polarization 15
- Ising model 275
- Isotropic substance 82
- Johnson noise 225
- L- α -alanin doped TGS-crystal 270

- LaAlO₃ 107
- Landau-Ginzburg-Devonshire theory 18, 157, 192, 233, 275
- Laser 93
- Lateral domain size 213
- Lattice
 - deformation 149
 - disorder 277
 - distortion 141, 143, 149
 - potential 33
 - vibrations period 203
- Lead titanate nano-grain 348
- Leakage measurement 65
- Light
 - amplification 171
 - damping 171
 - propagation 77
- LiNbO₃ 189
- Linear stripe 157
- Linearly polarized 84
- LiTaO₃ (lithium tantalate) 319
 - congruent ~ (CLT) 320
 - stoichiometric ~ (SLT) 320
- Local
 - dielectric constant 248
 - electric field 14
 - perturbations 181
- Lock-in techniques 253
- Lorentz 94
 - polarization 125
- Loss tangent 73, 99
- Low temperature co-fired ceramics (LTCC) 108, 115
 - process 108
- Lyddane-Sachs-Teller relation 23

- Mach-Zehnder 88
- Macroscopic switching 255
- Maxwell's equations 95, 100
- Measurement
 - methods 53
 - of $\epsilon_{31,f}$ 50
 - of physical parameters 227
 - set-up 56
- Mechanical stresses 149
- Meissner effect 101
- Metalorganic chemical vapor deposition (MOCVD) 151
- Microphonic noise 227
- Micropolar regions 28
- Microstrip line 114
- Microwave losses 103
- Microwaves 91, 99
- Mobile nanoelectrodes 193
- Monochromator 119
- Monoclinic phase 142–145
- Monolithic microwave integrated circuits (MMICs) 114
- Monte Carlo simulation 198
- Morphotropic composition 138
- Morphotropic phase boundary (MPB) 24, 121, 138
 - PZT 129, 134
- Multibounce 119, 120
- Multidiffractions 119
- Multiple tip arrays 210
- Multipole filter 110
- Mutual compensation 208

- Nano-scale 359
 - 180° structure 307
 - ferroelectric domain 308
 - hysteresis loops 364
- Nanodomain
 - formation in LiTaO₃ 320
 - mapping 360
 - reversal 191
 - structure, rewritable 194
 - tailoring 189
- Negative piezoelectric phase 258
- Noise-equivalent power NEP 225
- Non-contact interaction 243
- Non-destructive 241
- Non-invasive 241
- Nonlinear
 - dielectric
 - coefficients 313
 - imaging 304
 - dynamics 264
 - optics 93
 - resonant system 264
 - wave equation 95
- Normal-incidence laser 152
- Nucleation activation energy 203

- Off-band rejection 113
- Ohm's law 100
- On-off-amplitude modulator 88

- One-dimensional domain configuration 197
- Optic
 - axis 80
 - phonons 22
 - sign 79
- Optical
 - characterization 77
 - field 94
 - methods 45
 - modulator electrode 92
 - pathlength 87
 - rectification 98
 - retarder 88
 - second harmonic 201
 - wave 91
 - waveguides 89
- Optocommunication applications 92
- Orientation polarization 15
- Parallel domain writing 217
- Parasitic holograms 169
- $\text{PbTiO}_3\text{-PbZrO}_3$ (PZT) 24
- Penetration depth 199
- Periodic refractive index 196
- Phase
 - reversal electrodes 93
 - delay 87
 - diagram for PZT 24
 - difference 90
 - identification 127
 - matching 98
 - mismatch 90
 - modulators 87
 - portrait of a harmonic oscillator 265
 - portraits 266
 - transition 18, 23, 166
 - velocity 91
- Phonon spectrum 22
- Photo-induced light scattering 163
- Photonic
 - devices 191
 - sensor 253
- Photorefraction 164
- Photovoltaic effect 168
- Piezo-imaging 309
- Piezoelectric
 - coefficient 11, 45, 47
 - constants 39
 - displacement 249
 - effect 39, 226, 242, 344
 - measurements 46
 - property determination 231
 - resonance 43
- Piezoelectricity 11, 39
- Piezoresponse force microscopy (PFM) 195, 343, 359
 - High-resolution (PFM) 292
- Pinning center 255
- Planar
 - resonators 114
 - transmission line 109
 - tuneable HTS 108
- Plastic deformation 208
- Pneumatic loading methods 49
- Pockels effect 83
- Point defects 103
- Polar
 - nanoregions 277
 - structure 180
- Polarization
 - configuration in a fatigued PZT thin film 375
 - density 94
 - irreversible \sim 32
 - order parameter 280
 - reversal 146, 193
 - reversible \sim 32
 - switching 253
- Polycapillaries 119, 125
- Polyetheretherketone (PEEK) 129
- Positive saturation 59
- Prepolarization pulse 60
- Pseudo-Voigt function 139
- Pulse measurement 61
- Pulsed lasers 97
- Pyroelectric
 - ceramics 221
 - ceramics thin films 234
 - coefficient 226, 229
 - detectors 222
 - devices 221
 - effect 221
 - materials 232
 - response 222
 - thin films 221
- PZT-SKN 145
- Quadratic electro-optic effect 280

- Quartz reference sensor 254
- Quasi-static
 - hysteresis loop 63
 - measurements 45
- Random-field Ising model 279
- Real-time studies 152
- Reference
 - capacitor 56
 - resistance 57
- Refractive index 81, 170, 171, 280
- Relative permittivity 171
- Relaxed remanent polarization 58
- Relaxor ferroelectrics 28, 166, 275
- Remanent polarization 17, 58
- Removable electrodes 371
- Resolution function 122
- Resonator 110
- Retention measurement 71
- Rochelle salt 270
- Rocking curve 134
 - scan 126
- Sapphire 105
- Satellite intensities 156, 158
 - odd-order positions 156
- Sawyer Tower method 56
- SBTN 119, 122, 131, 134
- Scanning
 - nonlinear dielectric microscope (SNDM) 303
 - probe microscopy (SPM) 50, 210
- Scattered optical field 96
- Screening 190
- Second
 - harmonic
 - generation 96
 - radiation 97
 - order
 - nonlinear optics 96
 - phase transition 19
- Secondary pyroelectric coefficient 226
- Seed scattering 183
- Self
 - polarization 244
 - polarized polarization mechanism 31
 - pumped phase conjugation 164
- Shunt method 57
- Single cell capacitors 329
- Size
 - effect 351
 - induced polarization instability 368
- Small signal measurements 73
- SNDM
 - domain engineering system 320
 - imaging 309
- Soft mode concept 22
- Space charge polarization 15
- Specific detectivity D^* 225
- Split-post resonator 114
- Spontaneous polarization 12, 172
- SrBi₂Ta₂O₉ 25
- SrTiO₃ 107
 - thin film varactors 116
- Static hysteresis measurement 63
- Step shaped voltage waveform 65
- Strain 39
 - contribution 147
 - irreversible \sim 34
 - reversible \sim 34
- Stray capacitance 337
- Stress 39
- String-like domains 202
- Stripe
 - domain formation 158
 - domains 155
 - period 157
- Stripline 110
- Strontium-barium-niobate 163
- Sub-unit-cell accuracy 152, 154
- Substitution 27
- Superlattices 192
- Surface
 - impedance 100
 - phase diagram 153
- Switching
 - current 35
 - polarization 355
 - time 35
- Symmetry classes 86
- Synchrotron x-ray scattering 151
- Tapping 242
- TE_{01 δ} 113
- Temperature coefficient 106
- TGS-crystal 267, 270
- Thermal
 - capacity H 232

- conductance G_T 232
- diffusivity κ 224
- properties 231
- Thermally stimulated currents (TSC) 228
- Three-dimensional measurement technique 316
- TiO₂ 107
- Tip apex capacitance 206
- Topographical images 346
- Trap density 171
- Treatment signal 58
- Tuneability 99
- Tungsten-bronze structure 165
- Ultrahigh memory storage 194
- Uniaxial
 - crystals 80
 - indicatrix 80
 - relaxors 166
- Unloaded quality factor 112
- Vibration direction 81
- Virtual ground
 - measurements 329
 - method 57
- Vogel-Fulcher
 - ($V-F$) equation 288
 - temperature 288
- Volume holographic memories 164
- Wave
 - fronts 78
 - vector 169
- Wavelet 79
- Whispering gallery 113
 - modes 112
- X-ray diffraction (XRD) 137, 138, 141
 - reciprocal space mapping (XRD-RSM) 121
- XPS 335
- Zr-Sn-Ti-O 107