

# Index

- AND gate 216
- ASTM E119 standard fire 98
- automatic notification 164, 180
- automatic suppression 89
- available evacuation time 134
  
- boundary element 106
- BRANZFIRE 76
- buoyancy force 115
  
  
- central alarm 139, 218
- CESARE-RISK 206
- CFAST 76
- checklist method 36, 50
- CIB W14 100
- Code-compliant design 207
- combustion efficiency 77
- compartment fire 72
- compartment geometry 78, 87
- computer evacuation model 148
- controlling parameter 18
- cost-effective design 209
- critical smoke conditions 135
  
- delay start time 141
- design fire 80
- detection and warning time 137
- deterministic input parameter 76
- direct perception 139
- door self closer 87, 124
  
- EFC 205
- ERL 204
- equivalent design 207
- event tree 10, 42, 55
- evacuation training and drill 142, 152, 220
- exhaust flow rate 79, 114
- expected fire cost 204
- expected risk to life 204
  
- fault tree analysis 215
- FBIM 172
- FDS 76, 79, 80, 122
- FIERAsystem 206
- flame radiant loss 77
- flammability property 77
- FOSM 193
- FiRECAM 172, 206
- fire department dispatch time 168
- fire department intervention time 163, 171
- fire department notification time 164
- fire department preparation time 169
- fire department response scenario 182
- fire department response time 163, 170
- fire department setup time 170
- fire department travel time 169, 207
- fire event 8
- fire extinguishment effectiveness 173
- fire growth scenario 88
- fire hazard 33, 50

- fire incident data 23
- fire loss data 23
- fire protection measure 9
- fire resistance rating 96
- fire scenario 8, 33, 56
- fire spread 96, 107
- fire statistics 23
- fire type 88
- flashover fire 73, 88
- fractional incapacitating dose 176
- fuel arrangement 78, 82, 87
- fuel load 78, 86
- fuel type 77, 85
  
- Hasofer-Lind transformation 194
- heat detector 138, 164
- heat of combustion 77
- heat release rate 73
- house fire 21
- hydrocarbon standard fire 98
- hypersphere 194
- hypersurface 191
  
- ignition location 78, 87
- ignition source 78, 87
- inherent fire risk 42, 53
- inspection 213
- ionization smoke detector 138
- ISO 834 standard fire 98
  
- live voice message 143, 152
- local alarm 39
- logic gate 216
  
- maintenance 213
- Monte Carlo method 192
- multi-dimensional space 191
  
- night club fire 19
- non-flashover flaming fire 73, 88
- normal distribution 104
  
- occupant evacuation scenario 155
- occupant fatality 175
- occupant movement time 144
- optical density 136
- OR gate 216
  
- parametric study 199
- PHOENICS 122
  
- photoelectric smoke detector 138
- photoluminescent material 153
- physical parameter 20
- pre-movement action 144
- probability distribution 103, 193
- probability of fire initiation 88
- property loss 179
  
- qualitative fire risk assessment 33
- quantitative fire risk assessment 49
  
- radiant loss fraction 77
- random input parameter 78
- real-world fire 100
- refuge area 154
- reliability 90, 205, 214, 218
- required evacuation time 135, 147
- rescue effectiveness 173
- residual consequence multiplier 59
- residual fire risk 42, 51
- residual multiplication factor 53
- residual probability multiplier 58
- risk indexing 50
- risk matrix 34
  
- safe elevator 154
- safe region 191
- security staff 143, 164
- Simulex Model 148
- smoke alarm 38, 53, 151
- smoke control system 114
- smoke detector 138, 164
- smoke extraction 125
- smoke hazard 178
- smoke mass density 136
- smoke spread 120
- smoke spread scenario 126
- smouldering fire 74, 85, 88
- soot concentration 79, 114
- specific extinction coefficient 136
- sprinkler 90, 218
- stack effect 117
- stairwell pressurization 125
- standard fire resistance test 97
- structural collapse 96
- structural failure 96
  
- temporal three signal 142
- toxic gases 114
- t-squared fire 81
  
- unsafe region 191

ventilation condition 78, 87  
voice message 139

warning by others 139  
warning by firefighters 139

warning signal interpretation 143  
warning signal recognition 142  
wind effect 119  
 $\beta$  reliability index 193