

INDEX

- active badge, 487–488
- activity scheduling, 346–347, 355
- actor networks, 25–29
- aggregation function, 509–510
 - duplicate sensitive, 509
 - exemplary or summary, 509
 - monotonic, 509
 - partial state, 510
- ALOHA, 254
- anchor/beacon nodes, 278–279
- angle of arrival, 283
- anonymity issues, 449–451
 - sender and path anonymity, 451
- applications, 5–14, 419
 - environmental applications, 6–9
 - military applications, 5–6
- approximation ratio, 348
- architecture, 25–27
- area coverage, 360–374, 426
 - centralized, 365–366
 - hexagonal, 364–365
 - localized, 366–368
 - mobile sensors, 371–373
 - multiple, 368–370
 - neighbor cooperation, 365
 - threshold based, 361–363
 - variations, 370–371
- attacks on location discovery, 166–169
- backbone construction, 343–355
 - GAF, 351
 - grid partitioning, 351–352
 - MPR (multi-point relay), 351–352
- bat system, 488
- Bayes classifier, 478
- beaconless routing, 403
 - BLR, 404
 - contention-based forwarding, 403
 - implicit geographic forwarding, 403
- Bluetooth scatternet formation, 326–327
- broadcast authentication, 141–172
 - DOS attacks, 149–153
 - μ TESLA, 142–153
- broadcasting, 343–360, 434–435
 - blind flooding, 346
 - minimum energy broadcasting, 359–360
 - MPR based, 358
 - neighbor elimination, 356–358
 - taxonomy, 355–356
 - two-tier data dissemination, 444
- calibration, 199–237
 - case studies, 232–234
 - classes, 231–232
 - collaborative in-place, 233–234
 - parameter estimation, 232–233
 - system model, 231
- carrier sense multiple access, *see* CSMA
- classes of synchronization, 208–211
 - continuous lifetime, 208–209
 - clock synchronization, 210
 - offset synchronization, 209–210
 - on-demand lifetime, 208–209
 - internal versus external, 208
 - rate synchronization, 209
 - scope, 209
 - time instants, 211
 - time intervals, 211
 - timescale transformation, 210
- cluster routing, 394–395
- clustering, 429–431, 349–351
- code division multiple access, 249–250
- collaborative signal processing, 474–475
 - distributive processing, 475
 - information fusion, 475
 - on-demand processing, 475
- communication models, 313–314
- cone-based topology, 326

- configuration, 204
- congestion control, 521–522
- connectivity, 332–338
- contention access protocols, 253
- cooperative reachback, 42
- coordinate system registration, 300–304
- coordinate system stitching, 294–296
- covering and connectivity properties, 363–364
- cricket, 488
- critical node degree, 333–334
- critical nodes and links, 336–338
- critical total power, 334
- critical transmission range, 332–333
- cryptographic services, 141–172
- CSMA, 255–261

- data aggregation, 18–22, 123–129, 422–423, 432–433, 442–443, 483–484
 - lossless aggregation, 128–129
- data-centric protocols, 417–456
- data-centric storage, 433
- data dissemination, *see* broadcasting
- data fusion, 493–526
 - basic operations, 508
 - parameter estimation, 508, 512–513
 - redundancy suppression, 508–513
 - system architecture, 513–515
 - tradeoffs, 515–516
- data gathering, 428, 437–438, 493–526
 - basic functions, 509
 - classification, 500–507
 - grid, 505
 - tree, 505–507
 - cluster, 505–506
 - LEACH, 428, 506
- data storage, 22–23
- data transport, 516–517
 - energy awareness, 520
 - flow conservation, 519
 - flow control and routing, 519–520
 - flow indivisibility constraint, 519
 - latency, 520
 - quality-driven utility function, 520
 - utility based, 517–521
- database systems, 29–30, 496–499
 - Cougar, 498
 - TinyDB, 498
 - TinySQL, 498
- Delaunay triangulation, 324–325
- demand assignment protocols, 250
- dense networks, 42–43
- deployment strategies, 423
- depth-first search, 387–389
- design challenges, 2–5, 15
- design guidelines, 429–431
- design metrics, 15
- dFSK receiver simulation, 66–70
- diffusion, 288, 502–504
 - APIT, 291–293
 - bounding box, 289
 - directed, 21, 30, 428, 503
 - gradient, 290
 - one phase pull, 502
 - push, 503
 - relaxation, 293–294
 - SPIN, 503–504
 - two phase pull, 502
- distributed frequency shift key, 64–66
 - modulation scheme, 65–66
 - wavelet generation, 64–65
- distributed prediction tracking, 484–486
 - assumptions, 484–485
 - DPT algorithm, 485–486
 - failure recovery, 486
 - selection algorithm, 486
- distributed signal processing, 41–73
- dominating sets, 347–348, 391
 - enhanced dominating sets, 354–355

- EAR, 261–264
- eavesdrop-and-register protocols, 261–264
- embedded operating systems, 173–197
- energy reservoirs, 77–87
 - macroscale batteries, 78–79
 - microscale batteries, 79–80
 - microfuel cells, 80–83
 - micro-heat engines, 83–86
 - ultracapacitors, 80–81
- energy resources, 202–203
- energy scavenging, 75–105

- face routing, 389–394
- fixed assignment protocols, 246
- frequency division multiple access, 246–247
- fusion, *see* data fusion

- Gabriel graph, 24, 322–323, 390
- generating random unit graphs, 315
- geocasting, 435–436, 441–442
- geographic routing, 23–24, 381–415
 - greedy routing, 23, 383–386
 - guaranteed delivery, 387–394
 - memorization, 387–389

- MFR, 383–384
 - progress, distance, direction, 383–384
- greedy-face-greedy (GFG), 23–24, 389–394
 - GOAFR+, 392–394
- GPSR, *see* greedy-face-greedy
- hardware, 10–12, 31
 - Mica mote, 10–12
- IEEE 802.15.4, 269–271
- infrastructure, 203–204
- key management, 141–172
- key predistribution, 153–166
 - closest pairwise key scheme, 164–165
 - grid based, 160–163
 - location aware deployment model, 163–164
 - random, 153–166
 - random pairwise keys, 155–160
- localization, 17–18, 113–116, 277–310, 460–473
 - angle of arrival, 18
 - APS, 17–18, 465–466
 - cluster structure, 117
 - coarse-grain localization, 113–116
 - computational complexity, 471–473
 - distance to anchors, 466–467
 - DV-hop, 467
 - dynamic coordinate system, 116–117
 - environmental obstacles, 284–285
 - GPS-less outdoor, 469–470
 - hardware, 278–283
 - lateration, 460–461
 - multilateration 17, 461–463
 - node density, 284
 - nonconvex topologies, 284
 - pattern matching, 463
 - resource constraints, 283–284
 - time-based, 468–469
 - trilateration 461–463
- localized algorithms, 345
- location discovery, *see* localization
- MAC layer, 29, 239–276
 - channel occupancy, 244
 - CSMA, 33
 - deadlock, 242
 - fairness, 241, 243
 - function, 240–245
 - latency, 241, 243
 - livelock, 241
 - power consumption, 242–243
 - quasi-stationary, 244
 - scalability, 244
 - self-maintenance, 244
 - self-organization, 244
 - TDMA, 33
 - throughput, 243
 - unlicensed frequency bands, 244
- MACA, 259–261
- MANTIS, 174, 188–192
 - com, dev, net layers, 189–191
 - kernel, 188
 - memory management, 188–189
 - power management, 191
- maximum likelihood, 479
- MDS-MAP, 287
- message complexity, 345
- microsensor node hardware, 175–177
 - EEPROM, 175–176
 - flash, 175
 - peripheral interfaces, 176
 - power systems, 176–177
 - radios, 176
 - SRAM, 175
- minimal spanning tree, 317–318, 332, 390, 434–435
 - LMST, 318–322, 332, 337, 434–435, 441–442, 443
- minimum power topology, 325–326
- mobile sensors, 445
- mobile sink, 444–445
- modeling, 109–110, 344
 - genetic material, 110
- multicasting, 395–396, 437
- multidimensional scaling, 304–308
- multilateration, 298–300
- multiple access control, *see* MAC
- neighbor discovery, 315–316
- network dynamics, 203
- network management, 186
- network reliability, 31
 - packet reliability, 32–33
 - PicoRadio network, 31
- operating systems, 34–35, 173–197
 - applications, 181–182
 - bridging to IP networks, 185–186
 - comparison summary, 192–194
 - CPU bandwidth, 179
 - data memory, 178–179
 - design principles, 177–182

- operating systems (*Continued*)
 - dynamic network reprogramming, 182–183
 - features, 182–186
 - file system, 184–185
 - maintenance, 182
 - managing hardware, 177
 - networking, 181
 - power management, 179–182
 - program memory, 179
 - resource constraints, 178
 - sensing, 181
 - task coordination, 177–178
- PAGER, 397
- PAMAS, 264–266
- path exposure, 457–491
- physical layer, 404–408
- polling, 250–251
- power and cost aware routing
 - 397–402
 - enclosure graph, 398
 - guaranteed delivery, 402
- power consumption, 76–77
- power distribution, 87–88
 - acoustic emitters, 88
 - electromagnetic RF power distribution, 87–88
 - light, 88
 - wires, 88
- power scavenging, 88–100
 - human power, 91
 - photovoltaics (solar cells), 88–90
 - pressure variations, 92–93
 - temperature gradients, 90–91
 - time-varying structural strain, 93–95
 - vibrations, 96–100
 - wind and airflow, 91–92
- protocol stack, 27–29, 31–32
- queries, 496–497
 - event-triggered, 496
 - historical, 496
 - long-running, 496
 - multidimensional range, 496
 - snapshot, 496
- query processing, 29–30, 422
 - Cougar, 29
 - TinyDB, 30
- RADAR, 488–489
- radio hop count, 280–281
- radioactive power sources, 86–87
- rate based data propagation, 448–449
- reachback communication, 42
- realistic physical layer, 41–73, 313–314, 358–359, 370, 404–408
 - fuzzy unit graph, 314
- real-time communication, 386–387
- received signal strength indication, 279–280
- reference broadcast synchronization, 220–221
- relative neighborhood graph, 320–322, 328
- reporting to sink, 438–442
 - PEGASIS, 441
- reservation, 251–252
- routing, 123–136, 381–415
 - energy efficient, 129–136, 432
 - sector routing, 433
- RSSI, *see* received signal strength indication
- security, 141–172
- semi-definite programming, 286–287
- sensor-MAC, 266–269
- services, 14–24
- shortcut-based routing, 391
- SMACS, 261–264
- software clocks, 205–206
- support vector machine, 479–480
- synchronization, 112–113
 - frequency hopping, 112–113
 - task based, 123
- synchronization techniques, 211–229
 - asynchronous diffusion, 224
 - beacon based distributed algorithms, 288–292
 - benchmark challenges, 229
 - case studies, 218–224
 - centralized algorithms, 286–287
 - clock drift, 229
 - clustering, 217
 - combining multiple time estimates, 214–216
 - combining multiple time intervals, 216
 - combining synchronization error, 225
 - evaluation strategies, 224–229
 - flooding, 223
 - in rounds, 214
 - interval-based, 223
 - lightweight, 221–222
 - linear regression, 215
 - measurements, 226–228

- message delays, 228
 - one sample, 211
 - out-of-band synchronization, 217
 - performance evaluation, 226
 - phase-locked loops, 215–216
 - precision, 225
 - reference broadcasting, 213–214
 - round trip, 212–213
 - simulation, 228–229
 - steady state and convergence time, 225–226
 - synchronization of multiple nodes, 216–218
 - system organization, 285
 - systems and topologies, 227–228
 - time diffusion, 224
 - timing-sync protocol, 222
 - tiny-sync and mini-sync, 221
 - tree construction, 217–218
 - TSync, 222
 - unidirectional synchronization, 211–212
 - unstructured, 218
- target classification, 478
 - k-nearest neighbor, 478–479
 - minimum error, 478
 - target location, 457–491
 - target tracking, 473–489
 - cooperative binary detector, 480–484
 - deployability, 474
 - multiple, 477
 - piecewise linear approximation, 480
 - power constraints, 474
 - scalable coordination, 474
 - single, 476–477
 - space-time cells, 475–480
 - tracking accuracy, 474
 - task based data processing, 122–123
 - TDoA, *see* time difference of arrival
 - time difference of arrival, 282–283
 - time division multiple access, 248–249
 - time synchronization, 14, 43, 199–237, 423–425
 - bounded-drift model, 205
 - bounded-drift-variation model, 205
 - clock models, 45–47, 204–205
 - communication models, 206–207
 - communication pulses, 50
 - constant-rate model, 205
 - delay uncertainty, 206–207
 - implicit versus explicit, 206
 - multihop synchronization, 58–59
 - observation model, 47–49
 - one-hop synchronization, 57–58
 - optimality conditions, 56–57
 - physical layer, 54–60
 - propagation model, 49–50
 - randomly shifted pulses, 52–53
 - signal-reception model, 50–51
 - simulation, 60–64
 - symmetrical versus asymmetrical links, 206
 - synchronization errors, 207
 - synchronization protocol, 54–56
 - synchronization pulse trains, 51
 - system model, 204–207
 - unicast versus multicast, 206
 - time-stamp synchronization, 218–220
 - TinyOS, 174, 186–188
 - components, 187
 - execution model, 187
 - nesC language, 187–188
 - topology construction, 23, 311–341
 - fault tolerance, 334–335
 - heterogeneous networks, 327–331
 - k-vertex topologies, 335–336
 - topology control, 425–426
 - tracking objects, 445–491
 - mobicast, 447
 - network based, 463–464
 - tree reconfiguration, 446
 - training protocol, 111, 117–122, 424
 - corona training, 118–122, 424–425
 - transport layer, 421–422
 - trunking, 252–253
- virtual infrastructure, 107–140
 - Voronoi diagrams, 385–386
- Yao graph, 325
- ZigBee, 269–271