

INDEX

Symbols

- !=, 476
- \$
 - Bash, 394
 - PATH, 430
- \$\$, 472
- \$? , 472, 475
- \$@ , 472
- %@ , 268
- & , 157
 - AppleScript, 493
 - strings, 399
 - variables, 185
- * , 460
 - < , 462
 - AppleScript, 511
 - dereferencing, 158
 - Desktop, 452
 - pointers, 157
- */ , 156
- + , 460
 - AppleScript, 511
 - JavaScript, 556
- /
 - AppleScript, 511
 - find, 437
- /* , 156
- < , 414, 440
 - * , 462
 - AppleScript, 512
 - cat, 459
- == , 476
- >
 - AppleScript, 512
 - new.html, 463
- ?. ? , 452
- [...] , 460
- \ , 474
 - line continuation symbol, 205
- \! , 430
- _ , 320
 - Python, 406
- |
 - AppleScript, 491
 - pipes, 392
 - regular expressions, 461
- || , 476
- ~
 - Bash, 430
 - HOME, 444, 481
 - ((...)), 475
 - (...), 461
 - ; , 236
 - ; , 236
 - . , 460
 - PATH, 430
 - struct, 194
 - (), AppleScript, 512
 - , AppleScript, 511
 - = , AppleScript, 502, 512
 - ¬ , AppleScript, 493
 - ; , if, 475
 - ++ , JavaScript, 556
 - += , JavaScript, 556
 - , JavaScript, 556
 - // , main, 156
 - @ , Ruby, 415
 - [], 236, 453
 - HTML, 462
 - “ , ” 185
 - /0, 472
 - \0, 180

A

- a, 477
- \A, 430
- absolute, position, 566, 572
- absolute path, 7, 433
- abstract class, Command, 281, 282
- Abstract Data Type (ADT), 210, 268
- abstract entities, 348
- Access Control Lists (ACL), 449
- accessor(s), 241–242
 - getter, 264
 - memory, 242
 - naming conventions, 242, 252–253
 - setter, 264
- accessor methods, Objective-C, 261–288
- ACL (Access Control Lists), 449
- actions, 292–293
 - arguments, 535
 - events, 535
 - ImageWindowController, 320
 - Interface Builder, 293
 - methods, 535
 - Objective-C, 292, 536
- activate, 398
- Activity Monitor, 39
- ADC. *See* Apple Developer Connection

- add:, 356
- addObserver:forKeyPath:
 - options:context:, 384
- address-of operator, 157
- addWindowController:, 325
- ADT (Abstract Data Type), 210, 268
- Ajax (Asynchronous JavaScript and XML), 417
- album, 525
- alert windows, 103
- alloc, 244
- Alloc..., 210
- allocation, 253
- AllowMultipleInstances, 565
- American National Standards Institute (ANSI), 146
- ancestors, 244
- and, AppleScript, 512
- animation, 16, 572
- anInt, 154
- anonymous struct, 194
- ANSI (American National Standards Institute), 146
- API. *See* application program interface
- AppKit, 17
 - Cocoa, 291
 - documents, 314
 - NSAutoreleasePool, 302
 - NSDocument
 - Controller, 332
 - NSImage, 325
 - NSOpenPanel, 362
 - validateMenuItem:, 325
- AppKit.framework, 534
- Apple Developer Connection (ADC), 23, 631
 - developer tools, 46–50
 - documentation, 47–48
 - Reference Library, 39, 40–41
- Apple Events, 490–491
- Apple Human Interface Guidelines, 17, 19–20, 42
- Interface Builder, 107
- menus, 99
- AppleScript, 35, 396–400, 487–551
 - &, 493
 - =, 502
 - |, 491
 - ~, 493
 - applications, 531–549
 - classes, 521
 - coercion, 491
 - control statements, 501–507
 - data types, 491–496
 - elements, 515–517
 - exception handling, 506–507
 - glue languages, 527
 - GUI, 390, 487
 - handlers, 497–501
 - immutable strings, 492
 - index, 545
 - inheritance, 519
 - Interface Builder, 535–536
 - loops, 502–504
 - Objective-C, 531–533
 - objects, 518–520
 - OOP, 491
 - operators, 511–515
 - scripts, 518–520
 - strings, 492–493
 - variables, 491–496
 - Xcode, 533–535
- AppleScript Editor, 488–489
- AppleScriptObjC, 532–533
- AppleScriptObjC.framework, 534
- applets, 490
- Application, 102
 - Cocoa, 106
- application(s), 7, 117–144
 - AppleScript, 531–549
 - Cocoa, 313–339
 - Preferences, 137–142
 - recordable, 490
 - scriptable, 490
 - UI, 117
- application program interface (API), 9
 - reference, 43–44
- AppDelegate, 382
- applicationDidFinishLaunching_, 545
- /Applications, 117
- ApplicationServices, 15, 18
- /Applications/Utilities, 7, 392, 427
 - QuickTime Player, 527
 - Terminal, 8
- Aqua, 17, 19, 426
- Architecture Review Board (ARB), OpenGL, 15
- archiving, 342–343
- argc, 183
- argument(s), 175
 - actions, 535
 - find, 483–484
 - JavaScript, 557
- argument count, 183
- argument values, 183
- argv, 183
- Array, 555
- arrays
 - C, 156–163
 - elements, 156–157
 - enum, 194
 - NSArrayController, 304
 - offset, 157
 - pass-by-value, 178
 - variables, 156, 470
- arrayWithObjects, NSArray, 283
- assembler, 146
- assign, 264
- asynchronous, sheet windows, 365
- Asynchronous JavaScript and XML (Ajax), 417
- Attributed String, 306
- attributes, 230
 - elements, 493
 - metadata, 456
 - properties, 493
- autorelease, 255, 257, 258

autoreleasing, 26
 Autoresize, 583
 Autosizing, 111, 112, 596
 availableData, 269
 awakeFromInsert, 372
 awk, 407, 461

B

background
 commands, 436–437
 processes, 463–464
 backgroundColor, 559
 backtick, 474
 backtrace, 25
 ~/Backups, 617
 Bash, 390–396
 \$, 394
 ~, 430
 conditional branching, 474
 configuration, 429–433
 directories, 446–449
 ditto, 615
 file system, 443–446
 files, 446–449
 find, 615
 floating-point numbers, 471
 globbing, 452–453
 interaction, 426
 I/O, 438–443
 scripts, 391, 426, 468–469
 shell scripts, 391
 shells, 425–485
 system_profiler, 453
 Terminal, 427
 variables, 469–473
 bash, 38, 469
 basic regular expressions, 460
 begins with, 515
 beginSheetForDirectory:
 file:types:
 modalForWindow:
 modalDelegate:
 didEndSelector:
 contextInfo:, 365–366
 bin, 430

/bin, 39, 434–435
 binding, 252–253
 Dashcode, 586
 Bindings, 242
 Bindings Inspector, 306
 blocks, 175–179
 body, 555
 boolean, 491, 492
 Booleans, 152, 251
 bounds rect, 336
 Bourne Shell, 391
 branching, 163–168
 break, 166, 169
 breakpoints, 84
 BUFFER_BLOCK_SIZE, 204
 bufferSize, 203
 BUFFER_SIZE, 204
 Bug Reporter, 50
 Build and Run, 73
 Build Results, 74
 Build Styles, 75
 build tools, 24
 bundle(s), 117
 building, 127–137
 executable code, 122
 global resources, 122
 localized resources, 122–123
 structure of, 118–123
 Versions, 119–120
 widgets, 560–561
 bundle bits, metadata, 119
 buttons
 add:, 356
 Inspector, 107
 key equivalents, 106, 107
 remove:, 356
 by, 503
 byte code, source code, 554

C

%c, 184
 .c, 206
 C (programming language),
 145–228
 arrays, 156–163

blocks, 175–179
 characters, 179–184
 conditional branching,
 163–168
 data structures, 193–196
 functions, 175–179
 I/O, 184–193
 Java, 145
 loops, 168–174
 main, 146
 memory, 196–200
 Objective-C, 145
 operators, 152–156
 pointers, 156–163
 preprocessor, 200–206
 programs, 206–227
 strings, 179–184
 Xcode, 148
 C compiler, 37
 C Programming Language
 (Kernighan and
 Ritchie), 146
 Calculate.c, include, 594
 call tree, 27
 calls, 497–498
 Canvas, 575
 canvas, 575
 Carbon, 17–18, 24, 98
 Cascading Style Sheets (CSS), 416
 Dashboard, 561
 DOM, 559
 case, 66, 474, 477
 switch, 595
 case-sensitive
 -i, 463
 shells, 12
 casting, 491
 cat, 395, 459
 catch, 507
 @catch, 239
 categories, 233
 cc/gcc, 36–37
 cd, 443
 Desktop, 454
 central processing unit (CPU), 8, 39
 CFBundleDocumentTypes, 120

- CFBundleExecutable, 120
- CFBundleGet
 - InfoString, 121
- CFBundle
 - IconFile, 121
- CFBundle
 - Identifier, 141, 565
- CFBundleName, 121
- CFBundlePackageType, 121
- CFBundleShort
 - VersionString, 565
- CFBundleSignature, 121
- CFBundleVersion, 121
- chaining, 245
- ChangeToDesktop
 - AndList, 480–481
- char, 180
- char*, 180, 232
 - stringWithCString:
 - encoding, 240
- characters, C, 179–184
- chat room, CocoaDev, 632
- CheckExitStatus, 483
- child process, 437
- chmod, o-rx, 455
- choice, 284
- choose from list, 525
- CHUD (Common Hardware Understanding Development Tools), 30
- class
 - initialize, 283
 - NSObject, 283
- class(es), 230
 - abstract, 281, 282
 - AppleScript, 521
 - immutable, 268, 275
 - Interface Builder, 299, 329
 - model, 268
 - Objective-C, 231–234
 - OOP, 405
 - protocols, 249
 - singleton, 273, 274, 382, 383
 - Xcode, 299
- class extension, 234
- class methods, 235–236
- Clean, 75
- clearTimeout, 575
- CLI (command-line interface), 425–426
- clickedOK:, 300
- close, 409
- Close if the Shell Exited Cleanly, 427
- closures, 557
- Cocoa, 6, 17, 291–311
 - AppKit, 291
 - Application, 106
 - applications, 313–339
 - autorelease, 258
 - Autosizing, 111
 - Booleans, 251
 - Core Data, 341–386
 - dealloc, 255
 - documents, 313–339
 - File’s Owner, 106
 - first responder, 106
 - Foundation, 281, 291
 - Foundation Framework
 - Reference, 87
 - interapplication
 - communication, 491
 - Interface Builder, 24, 98
 - menus, 99–101, 330–336
 - MVC, 309–310
 - NSImage, 548
 - NSMutableArray, 493
 - NSObject, 255
 - NSString, 245
 - NSZombie, 261
 - Objective-C, 145, 238
 - resizable windows, 108–112
 - singleton class, 274
- Cocoa Bindings, 302–309
 - Core Data, 348–361
 - NSColor, 384
 - NSController, 378
 - NSUserDefaults
 - Controller, 378
 - Panther, 292
- Cocoa Dev Central, 631
- CocoaDev, 631
 - chat rooms, 632
- Cocoa.framework, 534
- coercion, AppleScript, 491
- collections, JavaScript, 555–556
- color, 607
- colors
 - NSColor, 378
 - NSKeyedArchiver, 384
 - NSUserDefaults, 384
 - Xcode, 68
- comm, 284
- Command
 - abstract class, 281, 282
 - NSArray, 282
 - NSMutableDictionary, 284
 - NSString, 284
 - requestCommand
 - InfoFromUser:, 284
- commandClasses, 283
- commandClass
 - ForChoiceDict, 284
- commandDescription, 282
- commandIdentifier, 282
- command-line interface
 - (CLI), 425–426
- command-line tools, 9–12, 36–39
- commands
 - background, 436–437
 - foreground, 436
 - loops, 478–480
 - Unix, 434–438
- commClass
 - Nil, 284
 - objectForKey, 284
- comments, 149
 - functions, 483
- Common Hardware
 - Understanding Development Tools (CHUD), 30
- compile, 407
- compiled languages, 390
 - Java, 417, 554
- compilers
 - header files, 207
 - programming language, 74
 - readonly, 264
 - Xcode, 74
- concatenation operators, 513–514

- conceptual documentation, 40–43
 - conditional branching, 501–502
 - Bash, 474
 - C, 163–168
 - if, 474, 557
 - JavaScript, 557
 - configurePersistentStore
 - CoordinatorForURL:
 - ofType:
 - modelConfiguration:
 - storeOptions:error:, 361
 - Connections Inspector, 297
 - considering, 505
 - const, 167
 - const char *, 91
 - constructors. *See* initializers
 - contains, 514–515
 - Content, 122
 - Contents, 120
 - contiguous memory, 157
 - control statements, AppleScript, 501–507
 - Control-dragging, 297
 - Controller, 221–224
 - main, 284
 - requiredInfoIdentifiers, 283
 - controller(s), 310
 - controller key, 306
 - selection, 355
 - copy, 520
 - NSDate, 263
 - NSObject, 258
 - NSString, 263
 - retain count, 258
 - copyWithZone, 260
 - Core Animation, 16
 - Core Data
 - Cocoa, 341–386
 - Cocoa Bindings, 348–361
 - new documents, 366–370
 - Objective-C, 342–343
 - objects, 343–348
 - open panels, 362–366
 - PreferencesWindow
 - Controller, 376–384
 - root objects, 357–361
 - sort, 370–372
 - transient objects, 372–376
 - UI, 348–361
 - URLs, 372–376
 - Xcode, 344
 - Core Library, Snow Leopard, 87
 - Core Services, 18
 - CoreGraphics, 15
 - Java, 19
 - Python, 402
 - CountWords, 408, 415
 - fileExt, 415
 - countWords, 405, 407
 - cp, 447, 591
 - cpio, 591
 - CpMac, 591
 - CPU (central processing unit), 8, 39
 - createCat, 260
 - creationDate, 372
 - CSS. *See* Cascading Style Sheets
 - curl, 467
 - current application, 544
 - current directory, 10
 - currentHost, 141
 - currentNode, 199
- ## D
- D, 464
 - %d, 184
 - d, 477, 617
 - \d, 430
 - daemons, 464
 - Darwin, 6–7
 - command-line tools, 9–12
 - Dashboard, 418, 560–576
 - CSS, 561
 - HTML, 561
 - Dashcode, 576–589
 - binding, 586
 - JSON, 586
 - XML, 586
 - dashcode, 588
 - data driven systems, 349
 - data hiding, Objective-C, 240–242
 - Data Sources, 584
 - data structures, C, 193–196
 - data types, AppleScript, 491–496
 - dataOfType:error:, 325, 609
 - dataRepresentation
 - OfType:, 325
 - DATA_SIZE, 173
 - dataSource, 545
 - dataUsingEncoding, 269
 - date, 262
 - dealloc, 381, 612
 - Cocoa, 255
 - instance variables, 263
 - nil, 265
 - NSObject, 244
 - retain count, 257
 - SubClass, 244
 - Dealloc..., 211
 - Debug, 75
 - Debugger Console
 - Build and Run, 73
 - source code editor, 85
 - debugging
 - breakpoints, 84
 - commands, 84
 - gdb, 37–38
 - Xcode, 38, 78–85
 - declarations, 150, 151
 - instance variables, 232
 - declared properties, 242
 - def, 414
 - default answer, 524
 - default answer "" as string, 398
 - default button, 524
 - DefaultImage, 565
 - defaultManager, 274
 - defaults, 141–142
 - delegate, 251, 296
 - delegates
 - NSObject, 332
 - protocols, 250
 - dereferencing, 158

descendents, 244
 description, 268–269
 NSString, 239
 descriptionWith
 CalendarFormat:
 timeZone:locale:, 87
 designed initializer, 254–255
 Desktop, 444
 *, 452
 cd, 454
 gnu, 455
 ls, 474
 sourcedir, 448
 destdir, 448
 destination path, 446
 DetachVolume, 395
 Developer Documentation,
 39–40
 Developer Technical Support, 50
 developer tools, 23–51
 ADC, 46–50
 documentation, 39–46
 mailing lists, 49
 /Developer/Applications, 24
 /Developer/Applications/
 Instruments, 591
 device drivers, 8
 dialog boxes, 103
 dialog windows, 365
 diff, 36–37
 dig, 467
 directories, Bash, 446–449
 diskutil, 467
 display dialog, 398, 524
 record, 525
 displayDetails, 519–520
 display_error_message, 524
 Distributed Objects (DO), 491
 ditto, 615
 div, 512
 Django, 615
 DO (Distributed Objects), 491
 do, 415
 *.doc, 437
 document(s)
 AppKit, 314

 Cocoa, 313–339
 Info.plist, 598
 menus, 333–336
 document, getElementById,
 567–568
 Document Object Model (DOM),
 417, 420–421, 554
 CSS, 559
 HTML, 559
 JavaScript, 558
 this, 558
 document windows, 102
 documentation
 ADC, 47–48
 developer tools, 39–46
 Documents, 448
 does not contain, 515
 DOM. *See* Document Object
 Model
 doSomething, 247
 dot notation, 265–266
 double, 152
 downcasting, 246
 drag-and-drop, Interface
 Builder, 103
 drawings, Quartz Composer, 13
 drawRect:, 361, 612
 @dynamic, 264
 dynamically typed programming
 languages, 248
 Python, 401
 variables, 492

E

-E, 460
 -e, 477
 echo, 11, 444, 452, 457
 variables, 470
 Editable flag, NSTextView, 306
 egrep, 407
 element(s)
 AppleScript, 515–517
 arrays, 156–157
 attributes, 493
 element specifiers, 515–517

ElementById, 558
 elif, 476
 #elif, 203
 else, 162, 474
 if, 501–502
 #else, 203
 emacs, 428, 435
 empty menus, 102
 encapsulation, 230
 end, 414, 415
 handlers, 498
 repeat, 502
 end class, 406
 end def, 406
 end repeat, 398
 ends with, 515
 Entity table, 348
 enum, 193, 194
 enumerated type, variables, 193
 environment variable, 429
 equality operators, 513
 Errors and Warnings, 63, 74
 esac, 474
 /etc/bashrc, 429
 /etc/profile, 430
 eval, 438
 events, 520
 actions, 535
 exception handling,
 AppleScript, 506–507
 executable code, bundles, 122
 Execution, 248–250
 exists, 509
 exit, 39
 exit repeat, 398
 EXIT_STATUS, 483
 export, 469
 Exposé, 13
 extended regular expressions, 460
 eXtensible Markup Language
 (XML), 402, 586

F

-f, 477
 fast enumeration, 240

- fclose, 188
 - fence-post bugs, 171
 - fgetc, 189
 - fgets, 189, 192
 - fi, 474
 - FILE, 188, 240
 - file, 409
 - file(s)
 - Bash, 446–449
 - Xcode, 58–63
 - file descriptor, 440
 - File menu, 102
 - file mode, 445
 - file path, 7
 - file permissions, 449–451
 - file system, Bash, 443–446
 - fileExistsAtPath:, 274
 - fileExt, 415
 - fileHandleWith
 - StandardInput, 269
 - fileHandleWith
 - StandardOutput, 269
 - FileMerge, 31–32
 - fileNameRegex, 408
 - filenames, ls, 11
 - File’s Owner, Cocoa, 106
 - Filter Search, 107
 - finalize, 257
 - find, 126, 413, 457
 - /, 437
 - arguments, 483–484
 - Bash, 615
 - name, 437
 - /tmp, 457
 - Finder, 122–126
 - Find.find, 415
 - finishHit, 573
 - first responder, 297
 - Cocoa, 106
 - nib files, 331–332
 - firstNode, 199
 - flags, 10
 - flattening, 342–343
 - float, 152, 262
 - RAND_MAX, 174
 - sizeof, 197
 - floating-point numbers, 152
 - Bash, 471
 - randNum, 174
 - floating-point-values, linked lists, 197–198
 - folders, word directory, 430
 - Fonts & Colors, Xcode, 68
 - fopen, 188
 - NULL, 218
 - for, 408
 - in, 479–480
 - bugs, 171
 - loops, 170–171
 - while, 169
 - foreground
 - commands, 436
 - processes, 463
 - Format menu, 102
 - Foundation, 17, 281, 291
 - Foundation Framework
 - Reference, 87
 - Foundation.framework, 534
 - fprintf, 187
 - frame rects, 321, 335
 - frames, 25
 - Framework Reference, 43
 - frameworks, 4
 - Java, 18
 - UI, 16–17
 - free, 197
 - Free Software Foundation, 37, 396
 - free store, 196
 - fs HFS+, 394
 - fscanf, 187
 - ftp, 467
 - full path, 7, 433
 - function body, 175
 - function calls, 147, 480–481
 - functions, 147
 - C, 175–179
 - comments, 483
 - implementation, 176
 - JavaScript, 557–558
 - memory, 210
 - objects, 230
 - parameters, 175
 - pointers, 178
 - programs, 25
 - scripts, 480–481
 - strings, 182
- ## G
- G, 477
 - garbage collection, 257
 - GCC. *See* GNU Compiler Collection
 - gcc, 200
 - gdb, 36–38
 - GDB: Program received
 - signal: "EXEC_BAD_ACCESS", 88
 - getchar, 189
 - getDataSource, 588
 - getElementById, 559, 567–568
 - getObject, 236
 - gets, 189
 - getter, 264
 - given, 499
 - global resources, bundles, 122
 - global scope, variables, 191–192
 - globbing, Bash, 452–453
 - glue languages, 391, 527
 - GLUT, 15
 - gnu, 455
 - GNU Compiler Collection (GCC), 200
 - gnutar, 454
 - Google, 401
 - GPU (graphics processing unit), 18
 - Grand Central Dispatch, 179
 - graphical user interface (GUI), 17
 - AppleScript, 390, 487
 - CLI, 426
 - graphics, 12–16
 - graphics processing unit (GPU), 13
 - grep, 438, 460–461
 - index.html, 459
 - regular expressions, 460
 - Table, 440

Groups & Files, 62
 GUI. *See* graphical user interface
 gunzip, 467
 gutter, 68
 gzip, 467, 484

H

-h, 466
 \H, 430
 \h, 430
 handlers
 AppleScript, 497–501
 end, 498
 hard coding, 197
 hasSelection, 586–587
 hdiutil, 393–394, 467
 head, 555
 header files, 57, 146, 206
 compilers, 207
 heaps, 196–197
 Height, 565
 Height, windows, 111
 HFS+, 12
 hidePow, 574
 hitCoords, 573
 hitting, 573
 HOME, ~, 444, 481
 HTML, 391, 402
 [], 462
 Dashboard, 561
 DOM, 559
 JavaScript, 417, 554

I

I, 464
 %i, 184
 -i
 case-sensitive, 463
 mv, 447
 IBAction, 293, 299
 IBOutlet, 299
 iChat, 16
 .icns, 32

Icon Composer, 31, 32–33
 id, 235, 248, 568
 id <Execution>, 249
 if, 162
 ;, 475
 conditional branching, 474, 557
 else, 501–502
 name, 410
 nil, 274
 NOT, 154
 NULL, 193
 self, 253
 setDate, 262
 strstr, 193
 while, 169
 #ifdef, 203
 if/else, 162
 if/else if/else, 165
 #ifndef, 203
 ignoring, 505
 UIImageView, 335
 image
 model key path, 355
 UIImage, 348
 URLs, 372–376
 image wells, 317
 ImageDocument
 UIImage, 325
 #pragma mark, 326
 saveAs:, 326
 ImageKit, UIImageView, 335
 ImageWindowController, 320
 img, 421, 568
 immutable classes, 268, 275
 immutable strings,
 AppleScript, 492
 implementation, 176
 @implementation, 264
 implementation block, 233
 protocols, 249
 import, 413
 #import, 238
 importFolderAtPath, 370
 in, 479–480
 include, 594
 #include, 191, 201, 238

indentation, Xcode, 68–71
 index, 156
 AppleScript, 545
 Objective-C, 545
 index.html, 440
 grep, 459
 Sites, 463
 inequality operators, 513
 infoDict, 284
 Info.plist, 120–122,
 325, 564
 documents, 598
 MyDocument, 350
 property lists, 120
 Xcode, 136–137
 inheritance, 230
 AppleScript, 519
 single, 242
 init
 NSObject, 255
 singleton class, 273
 SubClass, 244
 init, 409
 Init..., 211
 initialFirstResponder,
 296, 300, 332
 initialize, 256, 414, 605
 class, 283
 initializers, 253
 designated, 254–255
 initWithContentsOfFile:,
 604
 initWithContentsOfFile:
 encoding:error,
 NSString, 342
 initWithData:encoding, 269
 initWithFile:, 274
 initWithWindowNibName:,
 381, 384
 innerHTML, 558
 inpFile, 188
 input/output (I/O)
 Bash, 438–443
 C, 184–193
 Inspector
 buttons, 107

- Interface Builder, 98
 - Key Equiv, 106
- Installer, PackageMaker, 33
- instance methods, 235
 - OOP, 405
- instance variables, 230
 - dealloc, 263
 - declarations, 232
 - @synthesize, 265
 - tagRegEx, 415
- instances, 292
- instanceVar, 245
- instantiation, Objective-C, 253–257
- instruments, 25–26
- int, 150
 - main, 147
 - rand, 174
- integer, 491
- integers, 150
- interaction, Bash, 426
- interactive login shell, Terminal, 429
- interapplication communication, 490, 491
- @interface, 231
- interface block, 231–232
- Interface Builder, 24, 95–114
 - actions, 293
 - Apple Human Interface Guidelines, 107
 - AppleScript, 535–536
 - Autosizing, 111, 112
 - Carbon, 98
 - classes, 299, 329
 - Cocoa, 98
 - drag-and-drop, 103
 - Inspector, 98
 - Library, 98, 102, 107
 - menus, 99–102
 - NSImageView, 327–330
 - objects, 98
 - outlets, 293, 536
 - Size Inspector, 335
 - springs, 112
 - templates, 96

- text labels, 107
- window editor, 107
- windows, 102–112
 - windows resizable, 108–112
 - Xcode, 24, 299
- interfaces, programs, 210
- interpreted languages, 390
- intro, 593
- inverted call tree, 27
- invoked methods, 234
- I/O. *See* input/output
- IOUtility.h, 281
- IOUtility.m, 281
- iPhone, 257
- iPhone Developer Program, 47
- iPhoto, 525
- is in, 515
- is not in, 515
- isAtEnd, 275
- iterations, 168

J

- Java, 18–19
 - C, 145
 - compiled languages, 417, 554
 - single inheritance, 242
- Java Virtual Machine (JVM), 18–19, 417, 554
- JavaScript, 417–421, 554–576
 - +, 556
 - ++, 556
 - +=, 556
 - , 556
 - arguments, 557
 - collections, 555–556
 - conditional branching, 557
 - Dashboard, 561
 - DOM, 558
 - functions, 557–558
 - HTML, 417, 554
 - loops, 556–557
 - OOP, 587
 - quotation marks, 556
 - variables, 555

- JSON, 586
- JVM. *See* Java Virtual Machine

K

- kernel, 8
- Kernighan, Brian, 146
- Key Bindings, 70
- Key Equiv, 106
- key equivalents, 106, 107
- keyboard, text controls, 297
- +keyPathsForValuesAffectingValueForKey, 309
- keys, NSDictionary, 256
- Key-Value Coding (KVC), 252, 308–309
- key-value observation (KVO), 309, 588
- kill, 465
- killall, 466
- killall.sudo, 466
- KVC. *See* Key-Value Coding
- KVO. *See* key-value observation

L

- labeled parameters, 498
- Language Project (lproj), 123
- launch, QuickTime Player, 531
- launchctl, 467
- launchd, 467
- Leaks, 26
- left, 421
- left-hand side (LHS), 254
- let, 475
- Library
 - Filter Search, 107
 - Interface Builder, 98, 102, 107
- Library/Preferences, 140
- /Library/Preferences, 141
- ~/Library/Preferences, 140
- ~/Library/Preferences/ByHost, 140
- /Library/Scripts, 400

- line continuation symbol, 205
 - linked lists, 197–198
 - linkers, 74
 - linking, 74
 - List, 199
 - list, 504, 521
 - ListNode, 198
 - lists, 398
 - literals, 150
 - load script, 521
 - localizations, 117, 602
 - localized resources, 122–123
 - locate, 457
 - long int, 150
 - long list, 10
 - loops
 - for, 170–171
 - AppleScript, 502–504
 - C, 168–174
 - commands, 478–480
 - JavaScript, 556–557
 - main, 284
 - while, 168–170
 - .lproj, 123
 - lproj (Language Project), 123
 - ls, 10, 438, 445
 - Desktop, 474
 - filenames, 11
 - ls -l, 10–11
 - gnutar, 454
- M**
- .m, 233
 - machine code, 146
 - mach_msg_trap, 592
 - Macintosh Developer
 - Program, 47
 - MacOS, 122
 - MacOSClassic, 122
 - macros, 201–202
 - MacRuby, 411
 - MacScripter, 631
 - MacTech, 632
 - MacTech Magazine, 632
 - mailing lists, 632
 - developer tools, 49
 - Main, 409
 - main, 64, 269
 - //, 156
 - C, 146
 - Controller, 284
 - int, 147
 - loops, 284
 - NSAutoreleasePool, 238
 - stdio.h, 149
 - while, 284
 - "_main_", 410
 - main menu bar, 101
 - main.c, 56, 67–68
 - MainHTML, 565
 - main.m, 534
 - MainMenu
 - nib files, 295
 - NSApplication, 320
 - MainMenu.xib, 534
 - makeWindowControllers, 325
 - malloc
 - Alloc..., 210
 - stdlib.h, 197
 - void pointers, 197
 - man, 11
 - man -a intro, 593
 - man -a-w, 593
 - man -k intro, 593
 - man pages, 45–46
 - Math.random, 420
 - MAX, 205
 - maxIndex, 179
 - MAX_STRING_LENGTH, 191
 - media layers, 12–16
 - memory
 - accessors, 242
 - alloc, 244
 - autorelease, 255
 - C, 196–200
 - contiguous, 157
 - dealloc, 255
 - functions, 210
 - Leaks, 26
 - Objective-C, 257–261
 - protected, 8
 - RAM, 4
 - release, 244, 255
 - top, 39
 - Menu Item, 102
 - menus
 - Apple Human Interface
 - Guidelines, 99
 - Cocoa, 99–101, 330–336
 - documents, 333–336
 - empty, 102
 - Interface Builder, 99–102
 - modifier keys, 102
 - pre-built, 102
 - messaging
 - Objective-C, 246–247
 - protocols, 490
 - metadata, 456
 - bundle bits, 119
 - methods, 230
 - accessor, 261–288
 - actions, 535
 - class, 235–236
 - instance, 235, 405
 - invoked, 234
 - Objective-C, 234–240
 - OOP, 405
 - overloading, 245
 - overriding, 245
 - parameters, 234–235
 - protocols, 250
 - mImageView, 320
 - Minimum Size, windows, 111
 - missing value, 536
 - mkdir, 449, 455, 473
 - mktemp, 617
 - mod, AppleScript, 512
 - modal dialog box, 103
 - model class, 268
 - model key path, 306
 - image, 355
 - models, 309
 - Model-View-Controller
 - (MVC), 224, 309–310
 - modifier keys, menus, 102
 - modInt, 154
 - mount_afp, 467

- moveimage, 420
 - mv, 447
 - MVC. *See* Model-View-Controller
 - MyDocument, 349–351
- N**
- ++n, 218
 - n++, 218
 - \n, 149, 185
 - {n}, 460
 - name, 437
 - <name>, 398, 399
 - _name_, 410
 - named parameters, 499
 - name_offset, 399
 - naming conventions, 242, 252–253
 - Nano, 428–429
 - navigation bar, 68
 - netstat, 467
 - /Network/Library/Preferences, 141
 - new, 416
 - newDate, 262
 - newFromFolderWithOpenPanel, 369
 - new.html, >, 463
 - nextKeyView, 296, 297, 300
 - nextNode, 199
 - NeXTSTEP, 17
 - .nib, 122
 - nib files, 95
 - First Responder, 331–332
 - MainMenu, 295
 - MyDocument, 350
 - ownership, 318–321
 - nice, 468
 - Nil, 284
 - nil
 - dataRepresentationOfType:, 325
 - dealloc, 265
 - if, 274
 - NULL, 247
 - outputString, 284
 - self, 254
 - static, 274
 - nodes, 198
 - NOT, 154
 - not, 513
 - NSApp, 383
 - NSApplication, 457
 - applicationDidFinishLaunching_, 545
 - MainMenu, 320
 - NSApp, 383
 - NSArray, 240, 342, 604
 - arrayWithObjects, 283
 - Command, 282
 - commandClasses, 283
 - NSArrayController, 304, 355
 - NSAttributedString, 308
 - NSAutoreleasePool, 258, 260, 269
 - AppKit, 302
 - main, 238
 - NSDate, 263
 - run, 284
 - NSBox, 295, 317
 - NSButton, 320
 - NSCell, 356
 - NSCharacterSet, 269
 - NSClipView, 336
 - NSCoding, 342
 - NSColor, 343
 - Cocoa Bindings, 384
 - colors, 378
 - NSCompositeSourceOver, 544
 - NSControl, 302
 - NSController, 378
 - NSCopying, 260
 - NSData, 325, 378
 - initWithData:encoding, 269
 - NSDocument, 343
 - NSKeyedUnarchiver, 384
 - NSTextView, 308
 - rich text, 306
 - writeToFile:atomically:, 342
 - NSDate, 87, 92, 378
 - copy, 263
 - date, 262
 - NSAutoreleasePool, 263
 - setDate, 263
 - [NSDate date], 372
 - NSDictionary, 256–257, 342, 604
 - keys, 256
 - NSMutableDictionary, 275
 - NSDirectoryEnumerator, 370
 - NSDocument, 314
 - custom subclass, 321–327
 - NSData, 343
 - NSDocumentController, 332, 610–611
 - NSDocumentInit, 360–361
 - NSEntityDescription, 361
 - NSError**, 325
 - NSException, 239
 - NSFetchRequest, 361
 - NSFileHandle
 - fileHandleWithStandardInput, 269
 - fileHandleWithStandardOutput, 269
 - NSNumber, 342
 - NSString, 342
 - so, 240
 - WriteToStandardOutput, 269
 - NSFileHandling
 - PanelOKButton, 544
 - NSFileManager, 274
 - NSFullUserName, 90
 - NSHomeDirectory, 603
 - NSImage, 308
 - AppKit, 325
 - Cocoa, 548
 - image, 348
 - ImageDocument, 325
 - NSImageView, 308, 310, 315
 - Interface Builder, 327–330
 - NSScrollView, 326–327
 - scrollable, 316–318
 - SlideImageView, 329
 - NSInputStream, 342

- NSKeyedArchiver, 342, 343, 384
 - NSKeyedUnarchiver, 384
 - NSKeyValueObserving
 - OptionNew, 384
 - NSLog, 239
 - NSMainNibFile, 121
 - NSManagedObject, 344, 376
 - NSManagedObjectContext, 355
 - NSMutableArray, 493
 - NSMutableDictionary, 273, 275
 - Command, 284
 - NSDictionary, 275
 - NSObjectController, 304
 - NSMutableString, 246
 - NSString, 275
 - printUserOptions, 282
 - NSNotFound, 240
 - NSNumber, 378
 - NSFileHandle, 342
 - NSObject, 231–232, 243
 - alloc, 244
 - class, 283
 - Cocoa, 255
 - copy, 258
 - dealloc, 244
 - delegates, 332
 - init, 255
 - parent, 544
 - respondsToSelector, 251
 - retainCount, 261
 - NSObjectController, 304–306
 - NSOpenPanel
 - AppKit, 362
 - pointers, 365
 - NSOutputStream, 342
 - NSPersistentDocument, 351
 - configurePersistentStore
 - CoordinatorForURL:
 - ofType:model
 - Configuration:
 - storeOptions:
 - error:, 361
 - NSPoint, 320–321
 - NSPrincipalClass, 121
 - NSRange, 240
 - NSRect, 320–321
 - NSRTFPboardType, 598
 - NSRunLoop, 284
 - NSSavePanel, 362
 - NSScanner, 275
 - NSScroll, 336
 - NSScrollView, 315, 317–318
 - NSImageView, 326–327
 - SlideImageView, 330
 - NSSelectorFromString, 247
 - NSSize, 320–321
 - NSSplitView, 356
 - NSStream, 342
 - NSString, 90–91, 309, 378, 603, 604
 - Cocoa, 245
 - Command, 284
 - copy, 263
 - dataUsingEncoding, 269
 - description, 239
 - initWithContentsOfFile:
 - encoding:error, 342
 - initWithData:
 - encoding, 269
 - NSFileHandle, 342
 - NSMutable
 - String, 275
 - rangeOfString, 240
 - ReadFromStandard
 - Input, 269
 - stringWithContents
 - OfFile, 275
 - stringWithFormat:, 268
 - writeToFile:atomically:
 - encoding:error, 342
 - NSString*, 232
 - NSTextField, 302
 - NSTextView, 295, 310
 - Editable flag, 306
 - NSAttributedStrings, 308
 - NSData, 308
 - resultTextView, 302
 - setString, 302
 - NSUserDefaults, 256
 - colors, 384
 - singleton class, 383
 - NSUserDefaults
 - Controller, 304
 - Cocoa Bindings, 378
 - NSView
 - bounds rect, 336
 - frame rects, 335
 - NSWindowController, 314
 - makeWindowControllers, 325
 - windowDidLoad, 320, 372
 - NSZombie, 261
 - nt, 477
 - NULL
 - currentNode, 199
 - fopen, 218
 - if, 193
 - nil, 247
 - pointers, 183
 - strings, 183
 - while, 192
-
- O**
 - O, 477
 - objc_msgSend, 246–247
 - object(s), 230
 - AppleScript, 518–520
 - Core Data, 343–348
 - functions, 230
 - Interface Builder, 98
 - Objective-C, 231–234
 - outlets, 293, 536
 - scripts, 518–520
 - variables, 230
 - object code, 74
 - object graph, 343–348
 - object variable, 230
 - object variables, id, 248
 - ObjectAlloc, 26
 - objectAtIndex, 603
 - objectForKey, 273
 - commClass, 284

- Objective-C, 17, 92, 229–290
 - accessor methods, 261–288
 - actions, 292, 536
 - AppleScript, 531–533
 - C, 145
 - class, 231–234
 - Cocoa, 145, 238
 - Core Data, 342–343
 - data hiding, 240–242
 - dot notation, 266
 - index, 545
 - instantiation, 253–257
 - memory, 257–261
 - messaging, 246–247
 - methods, 234–240
 - naming conventions, 242, 252–253
 - objects, 231–234
 - OOP, 229–231
 - protocols, 247–252
 - runtime, 246
 - single inheritance, 242
 - subclassing, 242–246
 - object-oriented programming (OOP), 210
 - AppleScript, 491
 - classes, 405
 - instance methods, 405
 - JavaScript, 587
 - localizations, 602
 - methods, 405
 - Objective-C, 229–231
 - Python, 390, 401
 - Ruby, 390, 411
 - scripts, 518
 - structured programming, 230
 - observeValueForPathKey:
 - ofObject:change:
 - context:, 384, 613
 - of, 499
 - off-by-one bugs, 171
 - offset, 510
 - <name>, 399
 - offset, arrays, 157
 - Omni Group, 632
 - on error, 524
 - try, 506–507
 - onclick, 421, 558–559, 629
 - onhide, 567
 - online documentation, Xcode, 85–92
 - onmouseover, 573
 - onshow, 567
 - ooblick.com, 396
 - OOP (object-oriented programming), 210
 - opacity, 572
 - opaque directories, 118–119
 - open, 467
 - open filename, 427
 - open panels, 362–366
 - Open Scripting Architecture (OSA), 490–491
 - OpenGL, 12, 15
 - openPage, 629
 - openPanelDidEnd:
 - returnCode:
 - contextInfo:, 366
 - OPENSTEP, 232
 - Operate, 179
 - OperatingSystem, 519
 - OperationBlock, typedef, 179
 - operators
 - address-of, 157
 - AppleScript, 511–515
 - C, 152–156
 - concatenation, 513–514
 - equality, 513
 - inequality, 513
 - precedence, 154, 155
 - redirection, 440
 - ternary, 166–167
 - Option, Groups & Files, 62
 - @optional, 251
 - or, 513
 - o-rx, 455
 - os, 405
 - OSA (Open Scripting Architecture), 490–491
 - osascript, 522
 - os.path.join, 408
 - ot, 477
 - outError, 325
 - outFile, 188
 - outlets, 293
 - Connections Inspector, 297
 - Control-dragging, 297
 - ImageWindowController, 320
 - Interface Builder, 536
 - objects, 536
 - outputString, 284
 - overloading, 245
 - overriding, 245
 - ownership
 - nib files, 318–321
 - variables, 219
- ## P
- %p, 184
 - PackageManager, 31, 33–34
 - packages, 117
 - Panther, 292
 - parameter list, 147
 - parameters
 - functions, 175
 - labeled, 498
 - methods, 234–235
 - named, 499
 - positional, 472, 498
 - parent, 544
 - pass-by-reference, 500
 - pass-by-value, 177, 325, 500
 - arrays, 178
 - Pass-by-value argument
 - in function call is undefined, 77–78
 - password, sudo, 451
 - PATH, 429
 - \$, 430
 - ., 430
 - path(s)
 - absolute, 7, 433
 - destination, 446
 - file, 7
 - source, 446
 - Unix, 433–434

- path(s) (*continued*)
 - which, 435
 - path_helper, 429
 - PDF. *See* Portable Document Format
 - performance
 - scripting languages, 401
 - tools, 24–31
 - Perl, 390, 421
 - Ruby, 410–411, 414
 - permissions, file mode, 445
 - persistence, 217
 - Peters, Tim, 400
 - PHP, 391, 422
 - PID, 464
 - pipes, 392, 438
 - Pixie, 31, 34
 - pmset, 467
 - pointers
 - *, 157
 - arithmetic, 157
 - C, 156–163
 - dereferencing, 158
 - functions, 178
 - heaps, 196–197
 - NSOpenPanel, 365
 - NULL, 183
 - sender, 293
 - value, 158
 - variables, 156
 - polymorphism, 231
 - printUserOptions, 282
 - Portable Document Format (PDF), 14
 - possessive reference, 497
 - position, absolute, 566, 572
 - positional parameters, 472, 498
 - pow, 594
 - PowerPC (PPC), 122
 - powTimerId, 575
 - #pragma mark,
 - ImageDocument, 326
 - pre-built menus, 102
 - precedence, operators, 154, 155
 - preemptive multitasking, 8
 - Preferences, applications, 137–142
 - PreferencesWindow Controller
 - Core Data, 376–384
 - singleton class, 382
 - preprocessor
 - C, 200–206
 - directive, 146, 201
 - print, 409
 - \n, 149
 - PrintAndReturnString, 246
 - printf, 91, 181, 185–186, 593–594
 - %s, 183
 - Printf, NSLog, 239
 - printUserOptions, 281–282
 - NSMutableString, 282
 - polymorphism, 282
 - @private, 240–242
 - process control, 463–466
 - process identity, 438
 - processes, 7, 437
 - background, 463–464
 - foreground, 463
 - processUserChoice, 284
 - .profile, 430
 - profilers, 25
 - programming languages. *See also specific languages or language types*
 - compilers, 74
 - dynamically typed, 248
 - Java, 18
 - statically typed, 248
- programs, 7
- C, 206–227
 - functions, 25
 - interfaces, 210
- <Project
- Name>AppDelegate.
 - applescript, 534
- <Project Name>-Info.plist, 534
- Project Symbols, Xcode, 63
 - properties, 343
 - attributes, 493
 - @property, 264
 - property declaration attributes, 264
 - property declarations, 264
 - Property List Editor, 31, 35, 141, 564
 - property lists, 35
 - Info.plist, 120
 - @protected, 240–242
 - protected memory, 8
 - protocols
 - class, 249
 - delegates, 250
 - implementation block, 249
 - messaging, 490
 - methods, 250
 - Objective-C, 247–252
 - ps, 464, 465
 - PS1, 430
 - @public, 240–242
 - PWD, 443
 - PyObjC, 402
 - Python, 400–410
 - _, 406
 - CoreGraphics, 402
 - dynamically typed programming languages, 401
 - Google, 401
 - OOP, 390, 401
 - PyObjC, 402
 - strongly typed language, 401
- QuickTime, 12, 15–16

QuickTime movies, 5–6
 QuickTime Player, 16
 /Applications/Utilities,
 527
 launch, 531
 Snow Leopard, 527
 QuickTime X, 16
 QuitCommand, 283
 quotation marks
 JavaScript, 556
 shells, 473–474
 strings, 185

R

R, 464
 -r, 477
 RAM (random access memory), 4
 rand, int, 174
 RAND_MAX, 174
 float, 174
 randNum, 173
 floating-point numbers, 174
 random access memory
 (RAM), 4
 rangeOfString, 240
 raw strings, 407–408
 re, 405
 compile, 407
 read, 409
 readFromData:ofType:
 error:, 609
 ReadFromStandardInput, 281
 NSString, 269
 readonly, 264
 real, 491
 record, 521
 display dialog, 525
 recordable, applications, 490
 recursion, 176
 redirection operators, 440
 _reduceString, 405
 countWords, 407
 self, 405
 TagRemovingWord
 Counter, 408
 reference counting, 26
 iPhone, 257
 Xcode, 257
 Reference Library, ADC, 39,
 40–41
 registerDefaults, 256
 regular expressions, 63, 460–461
 basic, 460
 extended, 460
 fileNameRegex, 408
 grep, 460
 tagRegex, 407
 Re-Indent, 70–71
 relationships, 343
 relative path, 7, 433
 Release, 75
 release, 255–256
 instanceVar, 245
 memory, 244
 retain count, 257
 reloadData, 545
 remove:, 356
 renice, 468
 repeat, 398, 549
 end, 502
 list, 504
 until, 503
 while, 503
 repeat while, 525
 requestCommandInfo
 FromUser:, 284
 require, 413
 @required, 251
 requiredInfo
 Identifiers, 283
 Controller, 283
 resizeModeTo
 FitImage, 320
 Resources, 122
 responder chain, 332
 respondsToSelector, 251
 Restart, 84
 result, 525
 resultTextView
 NSTextView, 302
 -setString:, 302
 retain, 257–258
 newDate, 262
 retain count
 copy, 258
 dealloc, 257
 release, 257
 retainCount, 261
 return, 147, 481, 498
 return type, 147
 return value, 175, 498
 RHS. *See* right-hand side
 rich text, 306
 right-hand side (RHS), 154–155
 Ritchie, Dennis, 146
 root, 451, 463, 466
 root directory, 7
 root objects, 357–361
 Ruby, 410–417
 @, 415
 OOP, 390, 411
 Perl, 410–411, 414
 Ruby on Rails, 410
 run, 519
 NSAutoreleasePool, 284
 try, 524
 Run Log, Xcode, 57, 73
 run script, 521
 runModalForDirectory:file:
 types:, 370
 runModalForWindow:, 383
 runtime, Objective-C, 246

S

S, 464
 %s, 184
 printf, 183
 Safari, 16
 sample, 36, 38
 saveAs:, 326
 /sbin, 435
 scanf, 185–186, 594
 scanString:intoString, 276
 scanUpToStringinto
 String, 275
 script, 420, 554–555

- Script Editor, 31, 35–36
- scriptable, applications, 490
- scriptfile.sh, 469
- scripting bridge, 396, 487
- scripting languages, 389–424.
 - See also specific languages*
 - performance, 401
- scripts
 - AppleScript, 518–520
 - Bash, 391, 426, 468–469
 - functions, 480–481
 - objects, 518–520
 - OOP, 518
 - shells, 38
- scrollable, UIImageView, 316–318
- SDKs (Software Development Kits), 49
- searchStringRange, 240
- sed, 407, 461–462
- SEL, 326
- selectedObjects, 611
- selection, 355, 629
- @selector, 247
- @selector(), 326
- selectors, 247
- self, 414
 - if, 253
 - nil, 254
 - _reduceString, 405
 - taskExecutionShouldBegin, 251
- self-documenting, 236
- sender, 293
- Separator Menu Item, 102
- serializing, 342–343
- set, 499
- setDate
 - if, 262
 - NSDate, 263
- setDate:, 253
- setDelegate, 251
- setFrameSize:, 329
- setNeedsDisplay, 380
- setObject:forKey, 273
- setPrimitiveValue:
 - forKey:, 376
- setString, 302
- setString:, 302
- setter, 264
- setTimeout, 574, 575
- setValueForKeyPath, 588
- sh, 38
- sharedInstance, 382
- Shark, 30–31
- sh/bash/tcsh, 36
- shebang, 404, 469
- sheet windows, 103
 - asynchronous, 365
- shells, 11–12. *See also* Bash
 - case-sensitive, 12
 - quotation marks, 473–474
 - scripts, 38
 - Unix, 392
- shift, 479
- short int, 150
- Simulate Interface, 98–99
- single inheritance, 242
 - Java, 242
 - Objective-C, 242
- singleton class
 - Cocoa, 274
 - init, 273
 - NSUserDefaults, 383
 - PreferencesWindowController, 382
- Sites, 463
- Size Inspector, Interface Builder, 335
- sizeof, 197
- sleep, 464–466
- .slim, 135–136
- smart groups, 63
- Snow Leopard
 - Core Library, 87
 - OperatingSystem, 519
 - QuickTime Player, 527
 - QuickTime X, 16
 - Static Analyzer, 75–78
 - Xcode, 24
- so, 240
- SOAP, 491
- software bridge, 531
- Software Development Kits (SDKs), 49
- somefile, 446
- _some_variable, 491
- sort, Core Data, 370–372
- source, 438
- source code, byte code, 554
- source code editor
 - Debugger Console, 85
 - Xcode, 63–68
- source files, Xcode, 57
- source path, 446
- sourcedir, 448
- Spin Doctor, 26, 27–28
- spinin, 572
- split, 407
- Spotlight, 455
- springs, Interface Builder, 112
- printf, 186–187
- square brackets, 236
- sscanf, 186–187
- ssh, 468
- stack frames, 85
- Stack Overflow, 632
- stacks, 25, 196
 - Xcode debugging, 85
- Standard Additions, 506
- standard error, 440
- standard input, 162
- StartAndStop, 249
- startHit, 573
- STAT, 464
- static, 283
 - nil, 274
- Static Analyzer, 75–78
- statically typed programming languages, 248
 - variables, 492
- stdio.h, 146
 - main, 149
- stdlib.h, 174
 - malloc, 197
- Step Into, 84
- Step Into Instruction, 84

- Step Out, 84
 - Step Over, 84
 - store script, 521
 - str, 405
 - strcat, 182
 - strcmp, 182, 218
 - strcpy, 181–182
 - string, 405
 - variables, 476
 - string(s)
 - &, 399
 - AppleScript, 492–493
 - C, 179–184
 - functions, 182
 - immutable, 492
 - NULL, 183
 - quotation marks, 185
 - raw, 405, 407–408
 - String Commands Suite, 510
 - stringByAppendingPath
 - Component, 603
 - stringByTrimming
 - CharactersInSet, 269
 - string.h, 181–182
 - fgets, 192
 - .strings, 122
 - string.split, 407
 - stringValue
 - NSControl, 302
 - NSTextField, 302
 - textFieldChanged:, 302
 - stringWithContentsOf
 - File, 275
 - stringWithCString:
 - encoding, 240
 - stringWithFormat:, 268
 - +stringWithFormat:, 302
 - strlen, 182
 - strncat, 182
 - strncmp, 182
 - strncpy, 182
 - strongly typed language, 401
 - strstr, 182
 - if, 193
 - struct, 188, 194–196, 210, 392
 - ., 194
 - List, 199
 - variables, 194
 - structured programming, 193, 210
 - OOP, 230
 - struts, 111–112
 - style, 421, 559
 - SubClass, 243
 - dealloc, 244
 - init, 244
 - subclassing, Objective-C, 242–246
 - Submenu Menu Item, 102
 - subprocess, 426, 437
 - sudo, 455
 - password, 451
 - summing, 498
 - super, 245
 - SuperClass, 243–244
 - superClassInt, 243
 - SuperDuperClass, 244
 - switch, 66, 281
 - case, 595
 - switch/case, 165–166
 - symbolic links (symlinks), 119
 - synchronous, dialog windows, 365
 - syntax coloring, 65
 - Syntax-Aware Indenting, 68, 70
 - @synthesize, 264–265, 380
 - instance variables, 265
 - sys, 405
 - sys.argv, 409
 - system library, 9
 - system_profiler, 440, 443, 467
 - Bash, 453
- T**
- T, 464
 - \T, 430
 - \t, 430
 - Tab, text controls, 297
 - Table, 440
 - tagRegex
 - _init_, 407
 - instance variable, 415
 - regular expressions, 407
 - TagRemovingWordCounter, 408
 - tar, 468
 - target, Xcode, 75
 - Task, 248–249
 - TaskDelegate, 250–251
 - taskExecutionDidStop, 251
 - taskExecutionShould
 - Begin, self, 251
 - taskExecutionShouldStop, 251
 - TaskObserver, 251
 - Tcl, 422
 - TCSH, 392, 438
 - tcsh, 39
 - Technology Overview, 42–43
 - tell, 504–505
 - tell/end tell, 399
 - templates
 - Interface Builder, 96
 - Xcode, 347
 - Terminal, 7, 122–126
 - /Applications/Utilities, 8
 - Bash, 427
 - interactive login shell, 429
 - text editing, 427
 - top, 39
 - terminating null character, 180–181
 - ternary operators, 166–167
 - test, 476–477
 - text controls
 - keyboard, 297
 - Tab, 297
 - text editing
 - Terminal, 427
 - Xcode, 427
 - text labels, Interface Builder, 107
 - Text menu, 102
 - TextEdit, 427
 - textFieldChanged, 300
 - +stringWithFormat:, 302

textFieldChanged:, 302
 this, 421, 559
 DOM, 558
 Thompson, Ken, 146
 Thread States, 26, 28–29
 threads, 28–29
 throw, 506
 TIME, 464
 Time Profiler, 26, 27–28, 30
 title, 629
 title, 629
 /tmp, 457
 to one relationship, 343
 to path, 509
 To-Many relationships,
 343, 370
 weakness of, 361
 top, 36, 39, 421
 touch, 458
 transient objects, Core Data,
 372–376
 troff, 46
 try
 on error, 506–507
 run, 524
 @try, 239
 .txt, 452
 typedef
 enum, 194
 OperationBlock, 179
 typeName, 325

U

U, 464
 %u, 184
 UI. *See* user interface
 underscore, 320
 Unified Modeling Language
 (UML), 343
 universal binaries, 122
 Unix, 6, 433–468
 command-line tools, 9–12
 commands, 434–438
 file permissions, 449–451
 paths, 433–434

shells, 392
 symlinks, 119
 Unix Manual, 11
 unsigned int, 150
 until, 478
 repeat, 503
 unzip, 468
 updateText, 558–559
 URLs, 372–376
 USE_MEDIUM_BUFFER, 203
 user events, Quartz
 Compositor, 13
 user interface (UI), 26,
 29–30
 applications, 117
 Core Data, 348–361
 frameworks, 16–17
 USE_SMALL_BUFFER, 202, 203
 /usr/bin, 435, 454
 /usr/include, 9
 /usr/lib/libSystem.B
 .dylib, 9
 /usr/share/man, 46
 UTF8String, 91
 utility windows, 102

V

validateMenuItem:,
 325–326
 -validateMenuItem:, 326
 value, 158
 value, char, 180
 Value stored to 'answer'
 is never read, 77
 valueForKeyPath, 588
 van Rossum, Guido, 401
 variables, 147. *See also* instance
 variables
 &, 185
 AppleScript, 491–496
 arrays, 156, 470
 Bash, 469–473
 char, 180
 dynamically typed programming
 languages, 492

echo, 470
 enumerated type, 193
 environment, 429
 export, 469
 global scope, 191–192
 integers, 150
 JavaScript, 555
 names, 151
 objects, 230, 248
 ownership, 219
 pointers, 156
 statically typed
 programming
 languages, 492
 string, 476
 struct, 194
 /var/log/apache2/, 445
 /var/tmp, 188
 Versions, bundles,
 119–120
 vi, 428
 views, 310
 void, 175–176, 235
 IBAction, 293
 void pointers, 197

W

-w, 477
 \W, 430
 \w, 430
 walk, 408
 .wdgt, 560
 Web Objects, 49
 WebKit Animation, 572
 which, 435
 while, 398, 478–480
 for, 169
 break, 169
 currentNode, 199
 if, 169
 isAtEnd, 275
 loops, 168–170
 main, 284
 NULL, 192
 repeat, 503

- widget
 - onhide, 567
 - onshow, 567
 - widgets, 418
 - bundles, 560–561
 - Quartz, 575
 - Width, 565
 - Width, windows, 111
 - window editor, Interface
 - Builder, 107
 - windowDidLoad, 381
 - NSWindowController, 320, 372
 - windowNibName, 324–325
 - windows
 - Height, 111
 - Interface Builder, 102–112
 - Minimum Size, 111
 - Quartz Compositor, 13
 - resize, 108–112
 - struts, 111–112
 - Width, 111
 - with properties, 399
 - WithType:error:, 360–361
 - word directory, folders, 430
 - wordCount, 409
 - WordCounter, 409
 - wrappers, 117
 - writeToFile:, 274
 - writeToFile:atomically:, 342, 604
 - writeToFile:atomically:
 - encoding:er,
 - NSString, 342
 - writeToFile:options:
 - error:, 342
 - WriteToStandard
 - Output, 269
 - WritetoStandard
 - Output, 281
- ## X
- x, 465, 477
 - X11, 426
 - .xcdatamodel, 344
 - Xcode, 49, 53–94
 - AppleScript, 533–535
 - Build Styles, 75
 - C, 148
 - classes, 299
 - Clean, 75
 - colors, 68
 - compilers, 74
 - Core Data, 344
 - debugging, 38, 78–85
 - Developer Documentation, 39–40
 - Errors and Warnings, 63
 - FileMerge, 32
 - files, 58–63
 - Fonts & Colors, 68
 - gcc, 37
 - gutter, 68
 - indentation, 68–71
 - Info.plist, 136–137
 - Interface Builder, 24, 299
 - Key Bindings, 70
 - online documentation, 85–92
 - Project Symbols, 63
 - reference counting, 257
 - Re-Indent, 70–71
 - Release, 75
 - Run Log, 57, 73
 - Snow Leopard, 24
 - source code editor, 63–68
 - source files, 57
 - stacks, 85
 - Static Analyzer, 75–78
 - target, 75
 - templates, 347
 - text editing, 427
 - xcodeproj, 598
 - XML (eXtensible Markup Language), 402, 586
 - XML-RPC, 491
 - xterm, 426
- ## Y
- Yukihiro Matsumoto, 410
- ## Z
- z, 464
 - The Zen of Python* (Peters), 400
 - zip, 468
 - zoomActualSize:, 330–331
 - disabling, 335
 - zoomIn:, 330–331
 - disabling, 335
 - zoomOut:, 330–331
 - disabling, 335