

INDEX

Note: Page numbers followed by t and f indicate tables and figures, respectively.

- Admittance
 - frequency-selective surface (FSS), 364–367
 - metamaterial, 364–367
- Advanced Design System (ADS), simulations of
 - leaky-wave antennas, 161–162
- Alù, A., 65, 67
- Anisotropic metamaterial, 90, 117, 121, 122f
- Antenna(s)
 - arrays
 - scan angle characteristics of, 152, 152f
 - series-fed, with reduced beam squinting, 150–152, 151f–153f
 - artificial magnetic conductor for, metamaterial realization of, 76–79, 77f–80f
 - bandwidth, 293–295, 303
 - bent-wire, 299–300, 299f
 - circularly polarized, 335–339
 - curl
 - on EBG ground plane, 335–337, 335f, 336f
 - on PEC ground plane, 335–337, 336f
 - dipole, 375
 - on EBG ground plane, 327–330
 - performance of, 333
 - radiation mechanism, 333–334
 - near patch-loaded ground slab,
 - performance of, 331–333, 332f, 334f
 - radiation mechanism, 333–334
 - radiating circularly polarized waves, 337–339, 338f, 339f
 - directive, 274–279
 - radiation patterns for, 275–277, 277f
 - efficient electrically small dipole
 - DNG nested shells, 62–69
 - ENG nested shells, 70–72, 70f–72f
 - HFSS simulations of dipole–ENG shell systems, 73–75, 73f–75f
 - electrically scanned (ESAs), 286–287
 - electromagnetic bandgap materials in, 274–279
 - electronically steerable, 302–303, 303f
 - engineering, artificial ground planes in, 311–344
 - feed networks, 150–151
 - Global Positioning System (GPS), high-precision, 250, 252, 252f
 - high-impedance surfaces and, 297–300, 393, 395
 - horizontal wire, 299f, 300
 - leaky-wave. *See* Leaky-wave antenna(s) (LWA)
 - low-profile, 299–300, 299f, 312. *See also* Resonance cone antenna(s)
 - curl design, 335–337, 335f, 336f
 - dipole, 327–329, 328f, 328t
 - resonance cone refraction effects in, 181–188
 - unidirectional radiation patterns of, 187–188, 188f
 - microstrip, 322–326, 324f, 325f
 - arrays, 325–326, 326f
 - monopole, 297, 298f, 334
 - bent, 340–342, 341f, 342f, 343f
 - phased array, 237
 - phone, 250, 253–254, 253f
 - radiation efficiency of, 293
 - reconfigurable, 339–343, 341f–344f
 - resonance cone. *See* Resonance cone antenna(s)
 - ring. *See* Ring antenna(s)
 - surface wave, for wireless communications, 331–334

- Antenna(s), (*continued*)
 two-CLL-deep metamaterial AMC block for, 76–78, 77f, 78f
 Vivaldi, 244, 244f
 wearable, 250, 254
 zero-index metamaterials for, 80–82, 82f
 zero-order, 207–208, 208f
- Antidirectional couplers, 53, 54f
- Artificial electric conductor (AEC), 76, 77f
- Artificial ground planes. *See* Ground plane(s)
- Artificial magnetic conductor (AMC), 61, 349, 375, 382, 385
 for antenna applications, metamaterial realization of, 76–79, 77f–80f
 as thin absorbers, 375, 377, 389
- Artificial materials, 7
 historical perspective on, 5
- Backward bands, 305–306, 306f
- Backward wave(s), 16–17, 16f, 93–94, 143, 191
 in rectangular waveguide filled with 2D uniaxial MNG metamaterial, 101, 102f
 in rectangular waveguide filled with isotropic double-negative (DNG) material, 93, 93f
 split-ring resonator (SRR) array and, 90
 verification method for, 101
- Backward-wave antennas, 10
- Backward-wave media, 6
- Balun(s), 153–157
 designs, 153
 distributed-TL, 153
 lumped-element, 153
 metamaterial, 153, 154f
 isolation, measured versus simulated, 154, 155f
 output differential phases, measured versus simulated, 156, 157f
 phase responses, measured versus simulated, 156, 156f
 return loss magnitude for port 1, measured versus simulated, 154, 155f
 through magnitude response, 154, 155f
 TL, output differential phases, measured versus simulated, 156, 157f
- Bandgaps, 215, 237, 238. *See also* Electromagnetic bandgap (EBG) materials
 of artificial ground planes, 312, 313–315
 dispersion diagram for surface waves and, 290–292, 292f
 sensitivity to systematic dimensional variations, 243
 surface wave, 317
- Band structure, 221
 of photonic crystals, calculation of, plane-wave method, 222–225
- Bandwidth, 114
 high-impedance surfaces and, 293–295, 297
- Beam steering
 leaky-wave, 303–304, 304f, 305f
 reflective, 301–303, 302f, 303f
- Bianisotropic media, 5, 117t, 128
- Biaxial media, 117–118
- Bilayer, concentric spherical, of paired metamaterials, 57
- Bloch boundary conditions, 262–263
- Bloch-Floquet theorem, 196, 262–263
- Bloch waves, 263–266, 265f–266f
 vectors, tangential component, conservation of, 274, 274f
- Bluetooth technology, 250, 253
- Bose, J. C., 5
- Brillouin, L., 237
- Brillouin region, 360
 irreducible, 362
- Brillouin zone (BZ), 223–224, 266, 305, 306f
- Broadband matching, 194
- Broadband response, phase-shifting lines and, 149
- Broadband Wilkinson balun, using microstrip metamaterial lines, 153–157
- Bulk metamaterials
 with inclusions, types of, 88–91
 testing, free-space method for, 87
- Capacitance
 distributed, in transmission line (TL) model of rectangular waveguide, 94, 94f
 of electrically small electric dipole antenna, 62–63
 fringing, 295
 of high-impedance surfaces, 295–297
 parallel plate, 295
- Capacitively loaded loop (CLL) metamaterial, 61
 as artificial magnetic conductor, 76, 77f
- Capacitive element, of ENG shell combined with dipole antenna, 70–71, 70f
- Capacitive gaps, in leaky-wave antennas, 160
- Causality, in double-negative media, 9–10, 11–13
- Cerenkov radiation, 10
- Channeling, 24
- Characteristic frequency, 8
- Characteristic impedance (Z_c), 192
- Cheng, C.-Y., 21
- Chiral materials, 5
- Choke rings, in Global Positioning System (GPS), 252, 252f
- Chromatic dispersion, and superprism effect, 271–273, 272f, 273f

- Circuit model
 effective, 288
 lumped-element, 288
 of waveguide applications, 48–50, 51f
- Closed stop band, 146
- CMA diagram, 172, 173f
- Compact resonator, 57
- Compensator
 metamaterial, 23, 23f
 phase, 19–20
- Composite media, 5
- Composite right/left-handed (CRLH) structures,
 191, 192–195
 balanced case, 194
 microstrip implementations, 197, 197f, 198f
- Composite right/left-handed (CRLH)
 transmission line
 cutoff frequency, 195
 dispersion relation, 196
 network implementation, 195–197
- Composite right/left-handed (CRLH)
 transmission line metamaterials, 192–197,
 193f
- Continuous-wave (CW) excitation, 10
- Continuous-wave (CW) Gaussian beam, 19–20,
 20f
- Coplanar waveguide (CPW), 147
- Core-shell systems, subwavelength cylindrical
 and spherical, 54–59
- Corrugation(s), in metal slab, 285, 286f
- Coupler(s). *See also* Impedance coupler(s); Phase
 coupler(s)
 complete backward coupling, 201
 even/odd modes, 198, 201, 201f
 geometry for, 198, 199f
 metamaterial, 198–204
 phase coupling condition, 202–204, 203f, 204f
 port designation of, 198, 199f
- Coupling coefficient (χ_L), 8
 impedance coupler, 200–201
- Cross-polarization, in ring antenna HFSS
E-plane, 157
- Cutoff frequency, 195
- Cylindrical core-shell systems, subwavelength,
 54–59
- Damping coefficient (Γ_L), 8, 10
- Debye model, 8
- Deep X-ray lithography (LIGA), 217–218, 239
- Diamond lattice, 216
 photonic crystal, 216, 224–225, 225f
 band structure of, 224–225, 225f
 density of states (DOS), 224–225, 225f
- Dielectric media, with losses, FDTD study of,
 230
- Dielectric structure, periodic, 216, 237–238
- Diffraction limits, 52, 162
- Dipolar scattering, 56
- Dipole-AMC block, 76–79, 77f, 78f, 79f, 80f
- Dipole antenna. *See* Antenna(s), dipole
- Dipole-DNG shell system, 62
 resonant electric, magnetic field distribution,
 magnitude of real part of, 65, 65f
- Dipole-ENG shell system, 70–72, 70f–72f
 HFSS simulations of, 73–75, 73f–75f
- Directional etching, 240
- Discontinuity
 mode-matching analysis of, 47–48, 47f
 V-shaped, 44
- Dispersion, 94, 117–118, 119t, 120t
 in double-negative media, 11–13, 12f
 in effective surface impedance model, 290
 for odd surface modes supported by DPS and
 DNG materials, 52, 52f
 of planar NRI transmission line media,
 164–167
 for transverse electric polarization, 45, 46f
- Dispersion compensation, in transmission line,
 using double-negative medium, 21–23
- Dispersion diagram
 of artificial surface, 349–350
 of patch-loaded grounded slab, 322, 323f
 for surface waves, 290–292, 290f, 291f
- Dispersion equation, of frequency-selective
 surfaces (FSSs), 355
 analytical form of, 367
 in terms of accessible modes, 358–359
- Dispersion relation, calculation of, plane-wave
 method, 222–225
- Dog house arrangement, 245
- Double-negative (DNG) metamaterials, 5, 6, 7f
 based on thin wires and SRRs, 91, 91f, 220,
 220f
 2D isotropic, rectangular waveguide filled
 with, 105–106, 105f
 dispersive, 11–13, 12f
 experimental characterization of, 87–110
 nondispersive, 11–13
 paired with double-positive media, 43, 44
 waveguide and antenna applications, 43
- Double-positive (DPS) metamaterials, 7, 7f
 isotropic, rectangular waveguide filled with,
 92–93, 93f
 paired with double-negative metamaterials, 43,
 44
 waveguide and antenna applications, 43
- Double-ring inclusion, 99, 99f
 uniaxial MNG metamaterial based on,
 100–105
- Drude model, 8, 10–11, 76, 115f, 116–118,
 230

- Dual-band ring antenna(s), 208, 209f
 Dual-grid reflector (DGR), 250
- Effective circuit model, 288
 Effective medium, 114, 116, 144
 with negative constitutive parameters, 116–122
 Effective surface impedance model, 289–292, 290f
 Electric damping factor, 116
 Electric excitation of magnetic resonance (EEMR), 221
 Electric field, distribution, HFSS-predicted, for dipole–ENG shell system, 74–75, 74f, 75f
 Electric plasma frequency, 116
 Electric susceptibility, 7
 Electromagnetic bandgap, zero-index, 33
 Electromagnetic bandgap (EBG) materials, 215–219, 311
 applications of, 238, 250–254
 in antennas, 274–279
 bandgap characterization of, 313–315
 Brillouin's work on, 237
 characterization of, 238, 243–250
 commercial development of, 238
 development of, 238
 electromagnetic properties of, 311
 fabrication, tolerances in, 239, 243
 frequency range, 238–239, 246–247
 gain enhancement with, 251–252
 ground planes, 327–329, 327f, 328f, 328t
 parametric study of, 317–319, 318f
 historical perspective on, 216, 237–238
 and light propagation, 215
 as metamaterial, 259
 in microstrip antennas, 322–326, 324f, 325f
 microwave systems, 238
 (sub)millimeter-wave systems, 238
 miniaturization of, 217–218
 mushroomlike structure, 312, 313, 313f
 with offset vias, 319, 321f
 patch width, 317
 periodic boundary conditions, 315–317, 316f
 polarization-dependent, 319–321, 320f, 321f
 realization of, 238
 reflectivity, 243
 measurement of, 246–248, 246f–248f
 structure
 modal diagram and, 315–317, 316f
 operational frequency band of, 329–330, 330f, 331f
 scattering analysis of, 315–317
 structure of, 215
 surface
 frequency-selective surface-based, 349–373
 with offset vias, 319, 321f
 surface wave attenuation, 243, 244–245, 244f, 245f
 terahertz reflection measurements, 239, 248–250, 249f
 three-cylinder structure, 217–218, 218f
 three-dimensional (3D)
 Fan structure, 241–242, 242f
 manufacturing of, 239–243
 by growth, 242–243
 by machining from solid, 217–218, 239–240
 by stacking, 240–242, 242f. *See also* Woodpile structure
 transmission, 243
 measurements of, 248–250
 Electromagnetic energy, propagation of, 266–268
 Electromagnetic field, 260, 260f
 force-free, 37
 Electronically scanned phased arrays, 250–252
 Electron-negative (ENG) medium, paired with double-negative media, 43
 Engheta, N., 65, 67
 Epsilon-negative (ENG) metamaterials, 7, 7f
 isotropic two-dimensional, 89
 rectangular waveguide filled with, 96–98, 97f
 nested shells, source and scattering resonances, analysis, 70–72, 70f–72f
 thin-wire, 88–89, 88f
 Evanescent wave(s), and plane-wave scattering from double-negative material slab, 14–16
- Fabry–Perot components, 45
 Face-centered-cubic (fcc) structure, 224, 241
 Feed networks, antenna, 150–151
 metamaterial-based, 150–152
 transmission line-based, 150–152
 Field coupling at plane interface, 263–266, 265f–266f
 Filling ratio, 55–56
 Finite-difference time-domain (FDTD)
 simulation, 222, 228–232, 231f, 232–233
 of artificial ground planes, 312–317, 314f, 315f
 of dipole antennas over PEC, PMC, and EBG ground planes, 327–329, 328f, 328t
 of double-negative media, 10–11
 electric field intensity distribution for phase compensation confirmed with, 20, 20f
 electric field intensity distribution for subwavelength focusing in double-negative medium, 24–27, 25f, 26f, 28f
 Gaussian beam focusing, 27–29, 29f, 30f

- line source driven at center of zero-index cylinder, 34–37, 36f
- NIR behavior confirmed with, 17–18, 17f
- one-dimensional, 11, 11f
- time-domain electric fields predicted by, 11, 12f
- of infinite EBG structure, 315–317, 316f
- spectral method, 316f, 317
- of zero-index slab terminated in PMC sheet, 81–82, 82f
- Floquet–Bloch transform, 262–264
- Floquet waves, 350, 351
- Focusing, 118, 121–122
- Forward waves, in rectangular waveguide filled with general metamaterial, 92
- Foster’s theorem, 101, 352, 363–364
- Four-region (three-nested-sphere) geometry, 70
- Free-space method, for testing bulk metamaterials, 87
- Frequency-selective surfaces (FSSs), 24, 237, 311
 - accessible mode admittance network, 355–359
 - admittance, 364–367
 - admittance matrix, diagonalization of, 361–363, 362f
 - aperture-type
 - accessible modes, 357–358
 - method-of-moments (MoM), 354–355
 - capacitive, 351–352, 364
 - dispersion analysis, pole–zero matching method, 351–352, 359–371
 - dispersion diagrams for, 367–371, 368f, 369f, 371f
 - dispersion equation of, 355
 - analytical form of, 367
 - in terms of accessible modes, 358–359
 - dominant-mode two-port admittance network, 359–361, 360f
 - EBG surfaces based on, 349–373
 - inductive, 351–352, 364
 - multiport network, 356
 - patch-type
 - accessible modes, 357
 - method-of-moments (MoM), 352–354
 - poles and zeros, 351–352, 364–367
 - quasi-static admittance models, 350–351, 350f, 351f
- Fresnel coefficients, 118
- Fringing capacitance, 295
- Front-to-back ratio, with resonant interaction
 - between dipole antenna and two-CLL-deep-based AMC block, 77–79, 78f
- Fundamental spatial harmonic, 160–162
- Gaussian beam, 118
 - continuous-wave (CW), 19–20, 20f
 - focusing, FDTD simulation of, 27–29, 29f, 30f
- Global Positioning System (GPS), high-precision, 250, 252, 252f
- Grating lobes, 150
- Grounded slab, loaded with periodic patches, 322, 323f
- Ground plane(s)
 - artificial, 344
 - in antenna engineering, 311–344
 - comparison to perfect electric conductors, 312, 312f
 - electromagnetic bandgap (EBG), 327–329, 327f, 328f, 328t
 - dipole antenna on, 327–330
 - parametric study of, 317–319, 318f
 - high-impedance, 375, 391
 - and low-profile antennas, 299–300, 299f
 - and monopole antenna, 297, 298f
 - perfect electric conductors (PEC), 327–329, 327f, 328f, 328t
 - perfect magnetic conductor (PMC), 327–329, 327f, 328f, 328t
- Group velocity (v_g), 192, 266–268
 - and superprism effect, 269–270, 270f
- Gyrotropic materials, 7
- Heyman, E., 9
- High Frequency Structure Simulator (HFSS)
 - ring antenna patterns, E - and H -plane, 157–159, 158f
 - simulations of dipole–ENG shell system, 73–75, 73f–75f
- High-pass behavior, of waveguide filled with isotropic double-positive material, 92–93, 93f
- Hilbert curve, 376, 376f
 - bandwidth of, 377, 377f
 - current distribution, 377–378, 377f, 378f
 - length of, 376, 376t
 - polarization dependence, 378
 - resonant frequency, 378
- Hilbert high-impedance surface, 385–389, 385f
 - angle of incidence, 385–386
 - bandwidth of, 385
 - parametric study of, 385, 386f–387f
 - reflection coefficient of, 385
 - short dipole antenna above, 375, 377, 391–395, 392f, 393f, 394f
 - as thin absorber, 389
 - waveguide measurement of, 387–390, 390f
 - zero-degree phase transition of, 386f, 388

- Impedance coupler(s), symmetric, 198–202, 199f–202f
- Inclusions, 5–6, 6f
- Incremental circuit model
 - of composite right/left-handed (CRLH) transmission line, 193–194, 193f
 - of uniform left-handed (LH) transmission line, 192, 192f
- Index of refraction, 18
 - of double-negative materials, 9–10
 - effective, 304
 - surface waves and, 291–292
 - for medium characterized by Drude model, 115f, 116
 - for medium characterized by Lorentz model, 114, 115f
 - zero, metamaterials with, 32–37
- Inductance, distributed, in transmission line (TL) model of rectangular waveguide, 94, 94f
- Inductive element, of ENG shell combined with dipole antenna, 70–71, 70f
- Infinite rods, 125
- Infinite wavelength, 194
- Interface, 43
- Interface resonance, 44–45, 54, 55

- KKR electronic band structure of calculation, 233
- Kock, W. E., 5
- Kramers-Krönig relation, 9

- Lasers, in EBG fabrication by stacking, 241–242, 242f
- Layer-by-layer structure, 216, 217f, 241, 242f
- Leaky-wave antenna(s) (LWA), 303–304, 304f
 - backward, 304
 - radiating in its fundamental spatial harmonic, 160–162
 - TL-based, 160–161, 160f
 - electrically small transverse dimension, 160
 - forward, 161–162, 304
 - method-of-moments simulations of, 161
 - steerable, 303–304, 304f
 - unidirectional
 - forward, 161–162
 - simulation results for, 160, 160f, 161f
- Leaky-wave beam steering, 303–304, 304f, 305f
- Left-handed (LH) materials, 6, 119, 143, 191, 219–221
- Lens
 - flat, with anisotropic metamaterial, 121, 122f
 - microwave, 5
 - perfect, 15, 23, 122
 - planoconcave double-negative medium, 30–32, 31f
 - superresolving NRI transmission line, 162–164
 - Veselago, 162–163
 - planar version, 163, 163f
- Liao boundary conditions, 230
- Light line, in dispersion diagram for surface waves, 290, 290f
- Lindman, K. F., 5
- Lorentz model, 7–8, 11, 114–118, 115f, 116
- Loss tangents (LT), 64

- Macrocells, in resonance cone antennas, 182, 183, 185f, 186f
- Magnetic conductor, artificial, 289, 292–293, 299–300
- Magnetic damping factor, 114
- Magnetic field
 - distribution
 - HFSS-predicted, for dipole–ENG shell system, 74–75, 74f, 75f
 - with resonant DPS–DNG system behaving as TM resonator, 68–69
 - force-free, 37
- Magnetic resonant frequency, 114
- Magnetic susceptibility (χ_m), 7–8
- Magnetization, 8, 10
- Matched condition, 14
- Matched pair(s)
 - DNG–DPS, 61
 - DPS–DNG, 61
 - ENG–MNG, 61
- Maxwell-Garnett mixing formula, 395
- Maxwell's equations, 34, 43, 48, 194
 - in isotropic materials, 222
 - time-dependent, 228
- Meander line approach, 150–151, 151f
- Measurement
 - of rings, 125–137
 - techniques, 123–137
- Metamaterials
 - admittance, 364–367
 - anisotropic, 90, 117, 121, 122f
 - electromagnetic response functions of, 5–6
 - isotropic, 117
 - macroscopic view of, 116–122
 - microscopic view of, 114–116
 - modeling, 116–118
 - properties of, 118–122
 - synthesis of, historical perspective on, 5
- Metamaterial slabs, high-impedance, as artificial magnetic conductors, 76–79, 77f–80f
- Method-of-moments (MoM), 350, 352–355
- Microcells, in resonance cone antennas, 182, 183, 185f
- Micromachining, 238, 311

- Microstrip antenna(s), 322–326, 324f, 325f
 arrays, 325–326, 326f
- Microstrip dispersion, 21–23, 23f
- Microstrip technology, implementation, 197, 197f, 198f
- Microwave filtering, 254
- Microwave lenses, 5
- Microwave network, 195–197
- Mobile phone antenna(s), 250, 253–254, 253f
- Mode-matching analysis, of discontinuity, 47–48, 47f
- Monomodality, 47
- Monopole antenna. *See* Antenna(s), monopole
- Multiconductor transmission line (MTL) theory, 165–167, 166f
- Multiple-scattering (MS) method, 233
- Multipoles, scattering, 56–57
- Mu-negative (MNG) metamaterials, 7
 paired with double-negative media, 43
 split-ring resonator (SRR) array, 89–91, 90f, 91f
 two-dimensional isotropic, rectangular waveguide filled with, 99–100, 99f
 two-dimensional uniaxial, rectangular waveguide filled with, 100–105
 uniaxial, 93–94, 100–105
- Mutual coupling, in microstrip antenna arrays, 325–326, 326f
- Negative group velocity, 149
- Negative index of refraction (NIR), 10, 11–13, 12f, 17–18, 17f, 113, 191, 219–221
- Negative-refractive-index (NRI) media, 143–144
 planar transmission line, 144–145
 two-dimensional, 144, 144f, 145
- Nested metamaterial shells, 65–66
- Nihilism, metamaterials exhibiting, 37
- Noble metals, 7
- Nonpropagating mode, evanescent, 48
- Omega media, 5
- Optics, physical arguments of, 261
- Parallel plate capacitance, 295
- Parameter extraction procedure, 197
- Paraxial focusing, 24
- Passband, 195
 of low-profile antenna, 187
- Pass region, of low-profile antenna, 187
- Patch width, of electromagnetic bandgap (EBG) materials, 317
- Peano curve, 375, 376, 376f
 bandwidth of, 378
 current distribution, 379f, 380
 electrical footprint, 380
 length of, 376, 376f
 polarization dependence, 380
 resonant frequency, 378
- Peano high-impedance surface, 381–383, 389
 bandwidth of, 383–384, 383f, 384f
 interelement spacing, 383–384, 383f, 384f
 parametric study of, 383–384, 384f
 polarization dependence of, 383–384
 reflection coefficient of, 381–382, 381f
 short dipole antenna above, 375, 377, 393
 substrate height, 383–384, 383f, 384f
 as thin absorber, 389
- Pendry, J., 162, 220–221
- Perfect electric conductors (PEC), 44, 60–61, 60f, 81, 312, 312f
 ground planes, 327–329, 327f, 328f, 328t
- Perfect magnetic conductor (PMC), 81, 246–247, 311
 ground planes, 327–329, 327f, 328f, 328t
- Periodic boundary conditions (PBCs), for
 electromagnetic bandgap (EBG) materials, 315–317, 316f
- Permeability (μ), 6–7, 10
 and dispersion relation, 118, 119t, 120t
 of DNG metamaterial based on thin wires and SRRs, 91
 effective, 87, 221
 of isotropic MNG metamaterial, 100
 of space-filling curve double-negative (DNG) media, 395, 397f
 of split-ring resonator (SRR) array, 89, 90f
 extracted effective relative, for uniaxial MNG metamaterial based on double-ring inclusions, 104–105, 104f
 longitudinal, of isotropic SRR-based MNG metamaterial, 90–91
 for medium characterized by Drude model, 115f, 116
 for medium characterized by Lorentz model, 114, 115f
 negative, 113, 143
 scalar, 116
 transversal, 93
 of isotropic SRR-based MNG metamaterial, 90–91
 uniaxial anisotropic, 91
- Permittivity (ϵ), 6–7, 10
 and dispersion relation, 118, 119t, 120t
 of DNG metamaterial based on thin wires and SRRs, 91
 effective, 87, 221
 negative, 143
 of space-filling curve double-negative (DNG) media, 395, 397f

- Permittivity (ϵ), (*continued*)
- of wire array, 88–89, 88f
 - of ENG wire-based metamaterial, 98
 - extracted relative, 97f, 98
 - isotropic scalar, 91
 - for medium characterized by Drude model, 115f, 116
 - for medium characterized by Lorentz model, 114, 115f
 - negative, 113, 143
 - relative, of wire array, 88–89, 88f
 - scalar, 116
- Phase compensation
- with conventional TL and BW lines, 145, 145f, 146f
 - with double-negative media, 14, 19–21
- Phase conjugation, 19
- Phase coupler(s), asymmetric, 198, 202–204, 203f, 204f
- Phase distribution, of subwavelength resonator, 109–110
- Phase-shifting lines
- and broadband response, 149
 - metamaterial, 145–146, 146f
 - advantages of, 147
 - applications of, 147–149
 - nonradiating, 149–150, 149f, 150f
 - zero-degree, 145–149
- Phase velocity (v_p), 192
- and superprism effect, 270–271, 271f
- Phone antenna(s), 250, 253–254, 253f
- Photolithography, 217–218, 238, 239
- Photonic bandgap (PBG) materials, 215, 238. *See also* Electromagnetic bandgap (EBG) materials; Photonic crystals (PC)
- Photonic crystals (PC), 215–219, 238, 259. *See also* Electromagnetic bandgap (EBG) materials
- A7 class, 216
 - advantages of, 216
 - band structure of, calculation, transfer matrix method, 225–228
 - colloidal suspensions, 219
 - diamond lattice, 216, 224–225, 225f
 - EM wave propagation in, studies of
 - numerical methods, comparisons of, 232–233
 - theoretical and numerical methods, 221–232
 - fabrication of, 216–217
 - geometry, hypotheses on, 261, 261f
 - plane interface, field coupling at, 263–266, 265f–266f
 - refractive properties of, 260–268, 269f
 - general hypotheses on, 260–261
 - rigorous theory of, 262–268
 - regular waveguide, 219
 - self-supported membrane, 219
 - submicrometer, 217–219
 - testing of, 216–217
- Photonic integrated circuits (PIC), 219
- Photonic-KKR method, 233
- Photopolymerization, 242–243
- Pin-bed arrays, 285
- Plane wave(s), 311
- reflection phase, 316f, 317
- Plane-wave excitation, 87–88
- Plane-wave incidence, obtaining, 123–125, 124f
- Plane-wave (PW) method, 222–225, 232–233
- Plane-wave scattering, from double-negative material slab, 13, 13f
- Plasma, electromagnetic wave propagation in, 88
- wire array and, 88
- Plasma frequency (χ_D), 8, 10, 89, 98, 114, 221
- Plasmons, surface, 287
- Polaritons, 56
- Polarization, 116–118
- Polarization-dependent electromagnetic bandgap (EBG) materials (PDEBG), 319–321, 320f, 321f
- Pole–zero matching, 351–352, 359–371
- Poynting power, 113
- Poynting theorem, 145
- Poynting vector, 43
- angles of transmission, in metamaterials, 118, 119t
 - with backward waves, 16–17, 16f
 - in mode-matching analysis of discontinuity, 47–48, 47f
 - with oblique scattering, 17–18
- planar metamaterial, corner-fed, anisotropic grid resonance cone antenna, 180, 181f
- resonance cone refraction effects and, in
- low-profile antenna, 185, 187f
- in transmission line (TL) model of rectangular waveguide, 94, 94f
- Prism, 118
- refraction experiment using, 121
 - S-based solid-state, transmission through, 137, 138f
 - solid-state, transmission through, 135, 136f
- Propagating mode, 45–48, 47f
- Propagation passband, in rectangular waveguide filled with 2D uniaxial MNG metamaterial, 101, 102f
- Radiated power gain
- for dipole–ENG shell system, 71, 71f
 - for electrically small electric dipole antenna, 64–65, 64f

- HFSS-predicted, for dipole–ENG shell system, 73–74, 73f
- Radiation, surface waves and, 291
- Reactance
 - capacitive, electrically small antenna and, 62
 - inductive, electrically small antenna and, 62
- Reciprocal scattering problem, 63f, 66–69, 66f–68f
- Reconfigurable antenna(s), wire, with radiation pattern diversity, 339–343, 341f–344f
- Reflection (r) amplitude, of finite slabs of photonic crystals and left-handed materials, 225–228
- Reflection coefficient, 116, 118
 - of finite slabs of photonic crystals and left-handed materials, calculation, 226–228
 - of Hilbert high-impedance surface, 385
 - of Peano high-impedance surface, 381–382, 381f
 - of photonic crystals and left-handed materials, calculation, 229
 - for plane-wave scattering from double-negative material slab, 13, 13f
- Reflection phase
 - of artificial surface, 349–350
 - and beam steering, 301–303, 302f, 303f
 - of EBG surface, 328t, 329–330
 - of high-impedance surface, 299–300, 299f
 - of patch-loaded grounded slab, 322, 323f
 - of perfect electric conductors (PEC), 328t
 - of perfect magnetic conductors (PMC), 328t
 - of plane waves, 316f, 317
 - for textured surface, 292–293, 293f
 - of tunable impedance surface, 300–301, 301f
- Reflector(s)
 - dual-grid, 250
 - electromagnetic bandgap (EBG) materials for, 250, 251f
- Refraction, 118, 119–121. *See also* Index of refraction; Refraction, negative
 - anomalous, 6
 - at boundary between photonic crystal and homogeneous medium, 259
 - negative, 17–19, 17f, 143, 220–221, 259, 268, 269f
 - in waveguide environments, 113–138
- Refractive boundary, in resonance cone antennas, 182
- Refractive index, negative, 6
- Resonance cone(s), 171–172, 172f
 - containment, 181, 183f
 - directions at frequencies higher or lower than diagonal cone frequency, 182, 184f
 - double-square pattern, 182, 184f
 - vortices, 183–187
- Resonance cone antenna(s), 171–189
 - CMA diagram, 172, 173f
 - image currents, 171
 - planar anisotropic grid of, 171, 180, 181f
 - planar metamaterial, corner-fed, anisotropic grid, 172–180
 - absorbed power distribution, 176, 177f
 - double-sloped, 180, 182f
 - flat, 173–174, 174f, 175f
 - grid-over-ground configuration, 173, 174f
 - horizontal-plane vertically polarized radiation pattern, 174, 175f
 - phase reversals, 173, 175f
 - sloped, 176–180, 178f–180f, 181f
 - vertical-plane radiation pattern, 174, 176f
 - vertical currents, 171
- Resonance cone refraction, and low-profile antenna, 181–188
- Resonant scatterer, 54
 - subwavelength conjugate pair of shells and, 56
- Resonators. *See also* Dual-band ring antenna(s); Zero-order antenna(s)
 - composite right/left handed (CRLH)
 - negative resonance in, 205–207
 - positive resonance in, 205–207
 - zero-order resonance in, 205–207
 - excitations, open- and short-ended, 206
 - metamaterial, 205–208
- Retrieval algorithms, 114
- Ring antenna(s)
 - dual-band, 208, 209f
 - low-profile, 157–159, 158f
 - metamaterial, 157–159, 158f
 - small, 157–159, 158f
- Rings, 114–116
 - measurement of, 125–137
- Rods, 114–116
 - infinite, 125
- RT/Duroid substrates, 318–319, 324
- Salisbury screen, 389–391
- Scan angle, of series-fed linear array, 152, 152f, 153f
- Scattering
 - dipolar, 56
 - from double-negative material slab, 13–16
 - higher-order, resonances of, 56
 - multipoles, 56–57
 - total, cross-section, normalized by unity, in DPS–DNG shell system, 69, 69f
- Scattering chamber, 87, 89

412 INDEX

- Scattering coefficient
 - for DPS–DPS spherical scatterer, 57, 58f
 - for ENG–DPS spherical scatterer, 57, 58f
- Schultz, S., 6
- Shell(s)
 - coaxial cylindrical, 54–59
 - concentric spherical, 54–59
- Shorted stubs, 160
- Sievenpiper mushroom surfaces, 76, 166
- Silicon, woodpile structure, terahertz
 - time-domain spectroscopy of, 249–250, 249f
- Single-negative (SNG) materials, experimental characterization of, 87–110
- Slab, 118
 - anisotropic, focusing by, 122
 - isotropic, focusing by, 122
 - refraction experiment using, 119–121
 - transmission through, 118–119
- Smith, D. R., 6
- Snell's law, 17, 81, 118
- Solid-state metamaterials, 131–135, 133f, 134f, 135f, 136f
- Space-filling curve double-negative (DNG) media, 377, 395
 - effective parameters, 395, 397f
 - Hilbert curve dipole moments, 395, 396f
 - Hilbert curve inclusions, 395
 - Peano curve multifunction media, 395
 - polarizability tensors, 395
- Space-filling curves, 375, 389, 395
 - iteration order number N , 376, 376t
 - resonances of, 377–380
- Spherical core–shell systems, subwavelength, 54–59
- Split-ring resonator (SRR), 99, 114–116, 191, 220, 220f
 - as anisotropic particle, 90
 - axially symmetric, 116, 117t, 125–127, 126f–129f
 - broadside, 116, 117t, 125, 136
 - closed, transmission coefficient versus
 - frequency of, calculation, 228, 228f
 - edge-coupled, 116, 117t, 125
 - omega, 116, 117t, 128–130, 130f–132f
 - rectangular, transmission coefficient versus
 - frequency of, calculation, 228, 228f
- Split-ring resonator (SRR) array, 89–91, 90f, 91f
- S ring, 116, 117t, 135–137, 136f, 137f, 138f
- Stop band, 127, 128f
- Stop-band, of low-profile antenna, 187
- Stop region, of low-profile antenna, 187
- Struts, in symmetric reflector antenna array, 250
- Subwavelength cavities, 43
- Subwavelength cylindrical core–shell systems, 54–59
- Subwavelength focusing, 15, 163, 163f
 - with double-negative medium, 23–32
- Subwavelength resonator, 106–110
 - experimental, 108–110, 108f
 - transmission line model of, 106–107, 106f
- Subwavelength unit cell, for 2D TL-based NRI metamaterial, 144f, 145
- Superprism effect, 259, 269–273
 - chromatic dispersion and, 271–273, 272f, 273f
 - group velocity and, 269–270, 270f
 - phase velocity and, 270–271, 271f
- Surface(s)
 - artificial, 311
 - corrugated, 285, 286f
 - hard, 285, 311, 349
 - high-impedance, 286f, 288–289, 375, 377, 381. *See also* Hilbert high-impedance surface; Peano high-impedance surface
 - antenna applications, 297–300
 - in antenna design, 393, 395
 - bandwidth, 293–295, 297, 303
 - capacitance, 295–297
 - design procedure for, 295–297, 295f, 296f
 - electromagnetic properties of, factors affecting, 295–297, 296f
 - inductance of, 296–297
 - mushroom, 286
 - polarization-dependent EBG designs (PDEBG), 319–321, 320f, 321f
 - soft, 285, 311, 349
 - textured, 285–286, 292
 - thumbtacklike, 286
 - tunable impedance, 300–301, 301f, 305
- Surface capacitance, 288–289, 289f
- Surface impedance, 288–289, 289f. *See also* Surface(s), high-impedance; Surface(s), tunable impedance
- Surface plasmons, 287
- Surface wave(s), 287–288, 287f, 288f, 311, 333–334, 349
 - backward, 304, 305
 - bandgap, 317
 - bands, 289–292
 - dispersion diagram for, 290–292, 290f, 291f
 - forward, 304
 - transverse electric (TE), 87, 286, 287–288, 288f, 290–292, 290f, 291f, 292f
 - transverse magnetic (TM), 286, 287–288, 288f, 290–292, 290f, 291f, 292f
- Surface wave antenna(s), for wireless communications, 331–334
- Telegrapher equations, 192, 194
- Textured surface, reflection phase for, 292–293, 293f

- Textured surface(s), 285–286, 292
- Thin wire
 double-negative (DNG) metamaterials based on, 91, 91f
 epsilon-negative (ENG) metamaterials based on, 88–89, 88f
 split-ring resonator (SRR) structures, 91, 91f, 191, 220, 220f
- Three-region (two-nested-sphere) geometry, 63, 63f
- Time-domain spectroscopy, terahertz, 248–250, 249f
- Total impedance (Z_{Total}), 60–61
- Transfer matrix method (TMM), 222, 225–228, 232–233, 318
- Transition frequency (ω_0), 194
- Transition regions, in resonance cone antennas, 182
- Transmission (t) amplitude, of finite slabs of photonic crystals and left-handed materials, 225–228
- Transmission coefficient, 116, 118
 of finite slabs of photonic crystals and left-handed materials, calculation, 226–228, 228f
 of photonic crystals and left-handed materials, calculation, 229
 for plane-wave scattering from
 double-negative material slab, 13, 13f
 of waveguides filled with uniaxial MNG materials, 102f, 103–104, 103f
- Transmission line (TL)/Transmission line (TL) model(s), 48–50, 49t, 51f, 94, 191. *See also* Multiconductor transmission line (MTL) theory
 backward wave, 101, 102f, 106–107, 106f, 107f, 109, 109f, 192
 C–C, 96
 C–L, 96, 147
 composite right/left-handed (CRLH) metamaterials, 192–197
 equivalent circuit, 94–95, 94f
 for waveguides filled with different types of metamaterials, 95, 95t
 forward wave, 106–107, 106f, 107f, 109, 109f
 L–C, 95, 147
 left-handed (LH), 192
 effectively homogeneous, 192
 loss mechanism in, 192
 uniform, incremental circuit model of, 192, 192f
 L–L, 95
 negative-refractive-index (NRI), 144–145
 planar media, dispersion of, 164–167
 superresolving lens, 162–164
 phase distribution in, 101, 102f
 planar
 media, with negative refractive index, 144–145
 with negative refraction index, 143–145, 144f
 positive-refractive-index (PRI), 145
 of rectangular waveguide, 94, 94f
 right-handed (RH), 192
 of subwavelength resonator, 106–107, 106f
 TEM, 94
 zero-degree phase-shifting, 145–149
- Transmission ($ABCD$) matrix formalism, 195
- Transmission properties, of finite photonic crystal or left-handed slabs, 221
- Transparency, 57–59, 59f
- Transverse electric (TE) polarized wave, 87, 286, 287–288, 288f, 290–292, 290f, 291f, 292f, 349
- Transverse electromagnetic (TEM) wave, 88, 312
- Transverse magnetic (TM) surface waves, 286, 287–288, 288f, 290–292, 290f, 291f, 292f, 349
- Transverse magnetic with respect to r -direction (TM_r), for dipole–metamaterial shell systems, 66–68, 66f, 67f, 68f, 71–72, 74–75
- Two-time-derivative Lorentz metamaterial (2TDLM) model, 9, 76
- UCLA UC-PBG surface, 76
- Ultrarefraction, 259, 275
- Uniaxial medium, 171
- Veselago, V. G., 6, 143–144, 162
- Vivaldi antennas, 244, 244f
- Wave(s). *See also* Surface wave(s)
 Bloch, 263–266, 265f–266f
 evanescent, 261
 amplification of, 122
 in superresolving NRI transmission line lens, 162–164, 164f
 transmission line models, 48–50, 49t
 Floquet, 350, 351
 leaky, steerable, 287
 transverse electric (TE) propagating, transmission line models, 48–50, 49t
 transverse magnetic (TM) propagating, transmission line models, 48–50, 49t
- Wave equation, for rectangular waveguide filled with general metamaterial, 91–92
- Waveguide(s)
 coplanar, 147

- Waveguide(s) (*continued*)
- cutoff frequency, 93, 99, 101, 102f, 103
 - DNG slab
 - comparison to DPS slab, 52, 53f
 - power flow properties of, 53, 54f
 - DPS–DNG, 45, 46f
 - discontinuity between, mode-matching analysis of, 47–48, 47f
 - DPS–DPS, 45, 46f, 50, 51f
 - DPS–ENG, 50
 - DPS–MNG, 50
 - DPS slab, comparison to DNG slab, 52, 53f
 - ENG–MNG, 45–47, 50
 - metamaterial, anomalous behavior of, 50–52, 51f
 - miniaturization of, 103
 - parallel-plate, 44–45, 44f, 46f, 50, 51f, 113, 116
 - rectangular, 285
 - filled with 2D isotropic DNG material, 105–106, 105f
 - filled with 2D isotropic ENG material, 96–98, 97f
 - filled with 2D isotropic MNG material, 99–100, 99f
 - filled with 2D uniaxial MNG material, 100–105
 - filled with isotropic double-negative (DNG) material, 93, 93f
 - filled with isotropic double-positive material, 92–93, 93f
 - filled with isotropic ENG material, 93
 - capacitance, 95–96
 - filled with isotropic MNG material, 93
 - filled with metamaterial, 91, 92f
 - theoretical analysis of, 91–96
 - filled with uniaxial MNG material, 93–94
 - in quasi-optical power combining, 254
 - and refraction experiments, 113–138
 - transverse electromagnetic (TEM), 194
 - walls, contacting issue with, 125
 - Waveguide experiments, 87–110
 - Wave impedance (Z_w), of waveguide filled with lossless metamaterial, 95
 - Wave vector(s)
 - angles of transmission, in metamaterials, 118, 119t
 - with backward waves, 16–17, 16f
 - with oblique scattering, 17–18
 - Wilkinson balun
 - broadband, using microstrip metamaterial lines, 153–157
 - transmission line (TL), distributed, 156–157
 - Wire media, 5, 88–89, 88f, 91
 - Woodpile structure, 216, 217f, 218
 - bandgap parameters, sensitivity to systematic dimensional variations, 243
 - manufacturing of, 240–241, 241f
 - silicon, terahertz time-domain spectroscopy of, 249–250, 249f
 - Yablonovite, 237
 - Zengerle, R., 259
 - Zero-degree phase-shifting lines, 145–149
 - Zero-index infinite cylinder, matched, 33–37, 35f, 36f
 - Zero-index media, 32–37, 33f
 - Zero-index metamaterials, for antenna applications, 80–82, 82f
 - Zero-order antenna(s), 207–208, 208f
 - Ziolkowski, R. W., 9, 21, 33, 62
 - Zirconium tin titanate (ZTT) based ceramics, 241