

Index

Note to the Reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

A

access-enable command, 193
 access layer, 47, **49**
 access-list command, 195
 access-profile command, 193
 access-template command, 193
 Acknowledgment number
 field, 78
 acknowledgments, 20–21, 21
 AD (administrative distances)
 IP routing, 389–390
 static routing, 375
 Add DHCP Pool dialog box,
 243, 243
 Address Resolution
 Protocol (ARP)
 IP routing process,
 344–348, 351–352
 operation, 46, 93–96, 94
 addresses
 ARP for, 46, 93–96, 94
 Ethernet networking,
 34–35, 34
 internetworking, 3–4, 3
 IP. *See* IP addresses
 learning, 435–437,
 436–437
 MAC. *See* MAC (Media
 Access Control)
 addresses
 RARP for, 95, 95
 administrative distances (ADs)
 IP routing, 389–390
 static routing, 375
 AES-CCMP encryption, 476
 agencies for wireless
 technologies, 465
 agents in SNMP, 75
 aggregate rates, 33
 all 1s broadcasts, 99–100
 all networks address, 99
 all nodes address, 100
 anonymous FTP users, 73
 Application layer
 attacks, 488
 tasks, 14–15

Application-Specific
 Integrated Circuits
 (ASICs), 25, 433–434
 archive command, 193
 ARP (Address
 Resolution Protocol)
 IP routing process,
 344–348, 351–352
 operation, 46, 93–96, 94
 arp command, 155
 ASICs (Application-Specific
 Integrated Circuits), 25,
 433–434
 ASs (autonomous systems),
 388–389
 ATM (Asynchronous Transfer
 Mode), 508
 attack profiles, 488–490
 AUIs (Attachment Unit
 Interfaces), 38
 authentication
 PPP, 513–515
 RIPv1 vs. RIPv2, 404
 wireless networks,
 474–475
 auto command, 193
 auto-detect mechanisms, 33
 autonomous system (AS)
 number, 404
 autonomous systems (ASs),
 388–389
 autorouter attacks, 488
 aux command, 204
 auxiliary passwords, 204–205
 auxiliary ports, 182

B

back door attacks, 488
 backbones, 430–431, 431
 backoff algorithms, 31–32
 Backspace command, 196
 backups
 IOS, 276–277, 326
 router, 287–289
 hands-on lab, 327
 SDM, 292–296,
 293–295
 bandwidth
 default, 231
 displaying, 230–231
 IGRP, 405
 serial links, 509
 UDP, 80
 bandwidth command, 224
 banner command, 201–202
 banners, 201–203
 baseband technology, 37–38
 baseline information, 75
 basic router information,
 command-line interface
 for, 200
 Basic Service Set (BSS),
 471–473, 473
 bfe command, 193
 BGP (Border Gateway
 Protocol), 388–389
 binary numbering system
 conversions with, 26–30,
 54–56
 for IP addresses, 97
 binding, 12
 bit-oriented protocols, 511
 bits, 26–29, 96
 block sizes
 summarization, 144
 VLSMs, 144–148
 blocked ports in STP, 443
 blocking state in STP, 443
 BNC connectors, 38
 Boot default ROM software
 bit, 267
 Boot field, 267–268
 Boot image from ROM
 field, 268
 boot sequence, 265–266, 271
 boot system commands,
 273–274
 bootstrap protocols,
 264–265
 Border Gateway Protocol
 (BGP), 388–389
 BPDU (Bridge Protocol Data
 Unit), 442–444
 Break disabled bit, 267
 breaks, 271
 Bridge Protocol Data Unit
 (BPDU), 442–444

596 bridges – command-line interface (CLI)

- bridges
 - Data Link layer, 25–26
 - identifiers for, 442
 - for network segmentation, 5–10, 8
 - STP, 442
 - vs. switches, 435
 - before switching, 432
 - bringing up router interfaces
 - no shutdown command, 217–218
 - steps, 184–187
 - broadcast addresses, 96, 103–105
 - broadcast domains, 3–4, 53, 53
 - breaking up, 5–10, 5–6, 8–9
 - layer 2 switching, 434
 - broadcast storms, 440–441, 440
 - broadcasts, 23
 - brute force attacks, 489
 - BSS (Basic Service Set), 471–473, 473
 - Buffer Full message, 90
 - buffers
 - connection-oriented communication, 18
 - IP routing process, 345
 - byte-oriented protocols, 511
 - bytes, 26–29, 96
-
- C**
- cabling
 - Catalyst switches, 446
 - Ethernet networking, 39–41, 39–42
 - WANs, 508–510, 509–510
 - calendar command, 194
 - call set-up,
 - connection-oriented communication, 17
 - Capability field, 298
 - carets (^) as error indicators, 195
 - Carrier Sense Multiple Access with Collision Detect (CSMA/CD)
 - 2.4 GHz wireless, 468–469, 468
 - operation, 31–32, 32
 - Catalyst switch configuration, 445–447, 445–446
 - Core, 449–451
 - S1, 447–448
 - S2, 448–449
 - cd command, 194, 278, 280
 - CDP (Cisco Discovery Protocol), 296, 327–328
 - neighbor information, 297–301
 - network topology, 304–307, 305, 307
 - port and interface information, 302–304
 - timers and holdtime information, 296–297
 - traffic information, 302
 - cdp enable command, 297, 302
 - cdp holdtime command, 296–297
 - cdp timer command, 296–297
 - central office (CO), 505
 - Challenge Handshake Authentication Protocol (CHAP), 514
 - Channel Service Unit/Data Service Unit (CSU/DSU)
 - Physical layer, 30
 - WANs, 510, 510
 - CHAP (Challenge Handshake Authentication Protocol), 514
 - Checksum field, 79
 - CIDR (Classless Interdomain Routing), 120–122
 - circuit switching, 506, 506
 - Cisco Discovery Protocol (CDP), 296, 327–328
 - neighbor information, 297–301
 - network topology, 304–307, 305, 307
 - port and interface information, 302–304
 - timers and holdtime information, 296–297
 - traffic information, 302
 - Cisco IOS. *See*
 - IOS (Internetwork Operating System)
 - Class A networks, 98–99, 98
 - format, 100–101
 - reserved address space, 102
 - subnetting, 119–120, 138–141
 - Class B networks, 98–99, 98
 - format, 101
 - reserved address space, 102
 - subnetting, 119–120, 131–138
 - Class C networks, 98–99, 98
 - format, 101–102
 - reserved address space, 102
 - subnetting, 119–120, 122–131, 124, 126
 - Class D addresses, 98–99, 98
 - Class E addresses, 98–99, 98
 - classes of protocols, 390
 - classful networks, 142, 142
 - classful routing, 386, 395–396
 - Classless Interdomain Routing (CIDR), 120–122
 - classless networks, 141–142
 - classless routing, 395
 - clear command, 194
 - clear counters command, 232–233
 - clear line command, 311
 - Clear To Send (CTS) signal, 468
 - clearing
 - counters, 232–233
 - Telnet connections, 311
 - CLI. *See* command-line interface (CLI)
 - clock command, 194–195
 - clock rate command, 223–224, 234, 357
 - clock set command, 195
 - clocking, 222–224, 234
 - closing Telnet sessions, 310–311
 - cns command, 194
 - CO (central office), 505
 - Code bits field, 79
 - collapsed backbones, 430–431, 431
 - collision domains, 3, 5–10, 5–6, 8–9
 - identifying, 53, 53
 - layer 2 switching, 434
 - switches for, 26
 - collisions
 - 2.4 GHz wireless, 468–469
 - CSMA/CD for, 31–32, 32
 - COM1 Properties dialog box, 41, 41
 - command-line interface (CLI), 188–189
 - for banners, 201–203
 - for basic routing information, 200
 - for configurations
 - deleting, 226–227
 - saving, 225, 250
 - verifying, 227–236, 235
 - viewing, 226
 - for descriptions, 212–213, 253
 - do command, 213–214
 - editing and help features, 193–198, 249–250
 - for hostnames, 200, 252

- for logging onto routers, 248–249
- from non-ISR routers, 189
- for passwords
 - auxiliary, 204–205
 - console, 205–206
 - encrypting, 209–212
 - example, 401–402, 401
 - setting, 203–204, 250–252
 - Telnet, 206–207
- prompts, 191
 - for interfaces, 191–192
 - line commands, 192
 - for routing protocol configurations, 193
 - for subinterfaces, 192
- for router interfaces, 214–217
- router modes, 190
- for SSH, 207–209
- composite metrics, 404
- config-register command, 269, 271, 273
- configuration
 - backing up
 - IOS, 225, 276–277, 326
 - router, 250, 287–289, 327
 - SDM, 292–296, 293–295
 - Catalyst switch, 445–447, 445–446
 - Core, 449–451
 - S1, 447–448
 - S2, 448–449
 - command-line
 - deleting, 226–227
 - saving, 225, 250
 - verifying, 227–236, 235
 - viewing, 226
 - copying
 - to NVRAM, 288–289
 - to TFTP server, 289
 - DHCP, 219–220
 - erasing, 226–227, 290
 - IFS for, 290–292
 - IP address, 218
 - IP routing, 353–354, 355
 - 871W router, 371–372
 - 1242AP router, 373–374
 - Corp router, 355–358
 - R1 router, 358–361
 - R2 router, 361–364
 - R3 router, 364–371, 364–371
 - verifying, 384–385, 405–413, 411
 - PPP, 514–515, 517–518, 517
 - restoring, 289–290, 292–296, 293–295
 - RIP, 417–418
 - 871W router, 399
 - Corp router, 395–396
 - example, 401–402, 401
 - R1 router, 396–397
 - R2 router, 397
 - R3 router, 397–399, 398
 - saving, 225, 250
 - verifying. *See* verifying
 - viewing, 226
 - configuration registers, 265
 - bits in, 266–267
 - boot system commands, 273–274
 - changing values, 268–269
 - checking values, 268
 - for password recovery, 270–273
 - configure command, 190, 194
 - configure memory command, 190
 - configure network command, 190
 - configure terminal command, 190
 - connect command, 194
 - Connect To dialog box, 41, 41
 - Connection Description dialog box, 41, 41
 - connection-oriented communication, 17–18, 17, 19, 78
 - connectionless protocols, 81
 - connections
 - console port, 182
 - routers, 182–184, 182–183
 - Telnet, 309–310
 - WANs, 505–506, 506
 - connectivity, 317
 - debugging, 320–322
 - ping command for, 317–318
 - processes, 322–323
 - SDM for, 318–319, 318–319
 - traceroute command for, 319–320
 - connectors, WANs, 509
 - console
 - connections to, 182
 - passwords for, 205–206
 - port commands from, 205–206
 - console command, 204
 - Console line speed field, 267
 - console ports, 182, 445
 - converged routing tables, 392, 392
 - convergence, 444, 444
 - conversions, number system, 26–30, 54–56
 - copy command, 194, 278, 280
 - copy flash tftp command, 277
 - copy running-config
 - startup-config command, 225, 272–273, 287
 - copy running-config tftp command, 288–289
 - copy source-url destination-url command, 279
 - copy startup-config running-config command, 272–273, 289
 - copy startup-config tftp command, 287
 - copy tftp flash command, 278
 - copy tftp running-config command, 289
 - copy tftp startup-config command, 289
 - core layer, 47, 48
 - Core switch configuration, 449–451
 - Corp router configuration
 - IP routing, 355–358
 - RIP, 395–396
 - static, 376–378
 - Counter Mode Cipher Block Chaining-Message Authentication Code (CBC-MAC) Protocol, 476
 - counters, clearing, 232–233
 - counting to infinity, 393
 - CPE (customer premises equipment), 505
 - CRC (cyclic redundancy check)
 - Ethernet frames, 35–36, 46
 - IP header, 88
 - IP routing process, 344–348
 - TCP segment, 79
 - UDP segment, 81
 - Create New Connection option, 365
 - crossover cables
 - Catalyst switches, 446
 - Ethernet networking, 40, 42
 - crypto command, 194
 - crypto key generate rsa command, 208
 - crypto pki command, 243

- CSMA/CD (Carrier Sense Multiple Access with Collision Detect)
 - 2.4 GHz wireless, 468–469, 468
 - operation, 31–32, 32
 - CSU/DSU (Channel Service Unit/Data Service Unit)
 - Physical layer, 30
 - WANs, 510, 510
 - ct-isdn command, 194
 - Ctrl+A command, 196
 - Ctrl+D command, 196
 - Ctrl+E command, 196
 - Ctrl+F command, 196
 - Ctrl+R command, 196
 - Ctrl+Shift+6 command, 309
 - Ctrl+U command, 196
 - Ctrl+W command, 196
 - Ctrl+Z command, 196
 - CTS (Clear To Send) signal, 468
 - customer premises equipment (CPE), 505
 - cut-through switching method, 451
 - cyclic redundancy check (CRC)
 - Ethernet frames, 35–36, 46
 - IP header, 88
 - IP routing process, 344–348
 - TCP segment, 79
 - UDP segment, 81
-
- D**
- DA (Destination address) field, 35–36
 - data communications equipment (DCE)
 - Physical layer, 30
 - WANs, 510, 510
 - data encapsulation
 - internetworking, 43–46, 43–44
 - PPP, 515
 - Data field
 - Ethernet frames, 35
 - IP header, 88
 - TCP segment, 79
 - UDP segment, 81
 - data frames, 24
 - Data Link layer, 23–25, 24
 - Ethernet networking at, 34–36, 34–35
 - number system
 - conversions, 26–30
 - switches and bridges at, 25–26, 25
 - data packets, 22, 43
 - data terminal equipment (DTE)
 - Physical layer, 30
 - WANs, 510, 510
 - datagrams, 43
 - DCE (data communications equipment)
 - Physical layer, 30
 - WANs, 510, 510
 - de-encapsulation, 44–45
 - debug command, 194, 320–321
 - debug all command, 321
 - debug ip rip command, 322, 408–410
 - debugging connectivity, 320–322
 - decimal number conversions, 26–30, 54–56
 - dedicated lines, 505, 506
 - defaults
 - administrative distances, 389–390
 - bandwidth, 231
 - gateways, 343–344, 346
 - routes, 100
 - routing, 385–388, 387–388
 - delay, 405
 - delete command, 194, 278, 280–281
 - deleting configurations, 226–227, 290
 - demarcs, 505
 - denial of service (DoS)
 - attacks, 488
 - description command, 212–213
 - descriptions, command-line interface for, 212–213, 253
 - designated ports, STP, 443
 - desktop layer, 49
 - Destination address (DA) field, 35–36
 - destination addresses, 345–353
 - destination hosts, 344–345
 - Destination IP address field, 88
 - destination network
 - parameter, 375
 - Destination port field, 78, 81
 - destination ports, 84–85
 - Destination Unreachable message, 90
 - Device ID field, 298
 - DHCP (Dynamic Host Configuration Protocol)
 - configuring, 219–220
 - IP addresses, 76–77
 - diagnostic addresses, 153
 - Digital, Intel, Xerox (DIX)
 - group, 37
 - dir command, 278, 280
 - Direct Sequence Spread Spectrum (DSSS)
 - technique, 469
 - disable command, 189, 194
 - disabled state in STP, 443
 - disconnect command, 194, 310–311
 - discontiguous networks, 404
 - Discover messages, 76
 - distance-vector protocols, 390–394, 391–393
 - distribution layer, 47, 48–49
 - DIX (Digital, Intel, Xerox)
 - group, 37
 - DNS (Domain Name System), 4, 75, 315–317
 - do command, 213–214
 - DoD model and TCP/IP, 70–72, 71–72
 - dollar signs (\$) for scrolling, 196
 - Domain Name System (DNS), 75, 315–317
 - domains
 - broadcast, 3–4, 53, 53
 - breaking up, 5–10, 5–6, 8–9
 - layer 2 switching, 434
 - collision, 3, 5–10, 5–6, 8–9
 - identifying, 53, 53
 - layer 2 switching, 434
 - switches for, 26
 - DoS (denial of service)
 - attacks, 488
 - dotted-decimal notation, 97
 - DSSS (Direct Sequence Spread Spectrum) technique, 469
 - DTE (data terminal equipment)
 - Physical layer, 30
 - WANs, 510, 510
 - duplex in Ethernet
 - networking, 33–34
 - Dynamic Host Configuration Protocol (DHCP)
 - configuring, 219–220
 - IP addresses, 76–77
 - dynamic NAT, 162

dynamic routing, 341
 IGRP. *See* IGRP
 (Interior Gateway
 Routing Protocol)
 IP, 388–390
 RIP. *See* RIP (Routing
 Information Protocol)

E

e-mail
 Application layer for, 15
 SMTP for, 74
 Edit Interface/Connection tab,
 241, 241
 editing features in
 command-line interface,
 193–198, 249–250
 EEPROM (electronically
 erasable programmable
 read-only memory), 184
 EGP (Exterior Gateway
 Protocol), 388–389
 EIA/TIA-232-C standard, 512
 802.11 standards, 466–471,
 468–469, 471
 871W router configuration
 IP routing, 371–372
 RIP, 399
 RIPv2, 411
 static routing, 383–384
 1841 router, 183, 183
 EIGRP (Enhanced IGRP), 389
 electronically erasable
 programmable read-only
 memory (EEPROM), 184
 employees, security threats
 from, 487
 enable command, 189, 193,
 203–204, 308
 Enable diagnostic messages
 bit, 267
 enable passwords
 secret, 204
 setting, 203–204
 show running-config
 for, 212
 Telnet, 308–309
 enabling RIPv2, 411–413, 411
 encapsulation
 internetworking, 43–46,
 43–44
 PPP, 515
 WANs, 506–507
 encapsulation command,
 506–507
 encrypt secret command, 273
 encryption
 password, 209–212
 wireless networks, 476
 Enhanced IGRP (EIGRP), 389
 erase command, 278, 280
 erase start command, 358
 erase startup-config command,
 226–227, 290, 355
 erasing configurations,
 226–227, 290
 error checking and detection
 Ethernet frames, 35–36
 TCP, 78
 Esc+B command, 196
 Esc+F command, 196
 ESS (Extended Service Set),
 472–473, 473
 Ethernet networking, 31–33, 32
 addressing in, 34–35, 34
 cabling, 39–41, 39–42
 at Data Link layer, 34–36,
 34–35
 frames, 35–36, 35
 half-duplex and
 full-duplex, 33–34
 at Physical layer, 37–39, 37
 exam essentials
 Internet protocols,
 105–106
 internetworking, 50–51
 IOS, 245–247
 IP routing, 413–414
 layer 2 switching and
 STP, 452
 management, 324–325
 security, 496
 subnetting, 165–166
 WANs, 516
 wireless networks, 477
 exec banners, 202
 EXEC sessions, 181
 exec-timeout command,
 205–206
 exit command
 for logging out, 191
 Telnet, 310–311
 exitinterface parameter, 375
 exponents, 118
 Express Setup HTTP screen,
 446, 446
 Extended Service Set (ESS),
 472–473, 473
 Exterior Gateway Protocol
 (EGP), 388–389
 external EIGRP, default
 ADs, 390
 extranet VPNs, 495

F

Fast Ethernet technology, 38
 FastForward switching
 method, 451
 fault tolerance, 48
 FCC (Federal
 Communications
 Commission), 465
 FCS (Frame Check
 Sequence) field
 Ethernet frames, 35
 IP routing process,
 344–348
 UDP segment, 82
 Federal Communications
 Commission (FCC), 465
 file prompt command, 279
 File Transfer Protocol (FTP),
 73–74
 files, transferring, 73–74
 filter tables, 433
 filtering, 437
 firewalls, 486, 487
 5GHz wireless, 469–471, 469
 Flags field, 87
 flapping, 394
 flash memory
 loading, 184
 managing, 283–287,
 283–286
 routers, 265
 verifying, 275–276
 flow control, 16–17
 format command, 278, 280
 forward/filter decisions,
 437–438, 438
 forward/filter tables, 435–441,
 436–437
 forwarding ports in STP, 443
 forwarding state in STP, 443
 FQDNs (Fully Qualified
 Domain Names), 75, 315
 Fragment offset field, 88
 FragmentFree switching
 method, 452
 Frame Check Sequence
 (FCS) field
 Ethernet frames, 35
 IP routing process,
 344–348
 UDP segment, 82
 Frame Relay, 507
 frames
 Data Link layer, 44
 Ethernet, 35–36, 35
 filtering, 437

600 FTP (File Transfer Protocol) – interface range command

FTP (File Transfer Protocol),
73–74
full duplex
 in networking, 33–34
 Session layer, 16
Fully Qualified Domain
 Names (FQDNs), 75, 315

G

gateways
 IP routing, 343–344, 346
 of last resort, 386, 387
Generic Routing
 Encapsulation (GRE)
 IP header, 90
 VPNs, 495
geographical distances,
 subnetting for, 117
Gigabit Media Independent
 Interface (GMII), 38
global commands, 192
global configuration mode,
 190, 193
global NAT names,
 162–163, 165
GMII (Gigabit
 Media Independent
 Interface), 38
gossip protocol, 399
GRE (Generic Routing
 Encapsulation)
 IP header, 90
 VPNs, 495
guest-mode command, 363

H

half duplex
 Ethernet networking,
 33–34
 Session layer, 16
hands-on labs
 IOS, 248–254
 IP routing, 415–418, 415
 management, 325–330
 WANs, 517–519, 527
handshakes, 17
hardware addresses, 87, 341
 Data Link layer, 34
 Ethernet addressing, 34
 IP routing process,
 346–348
HDLC (High-Level Data Link
 Control) protocol
 description, 507
 hands-on lab, 519
 operation, 511, 511
Header checksum field, 88
Header length field
 IP header, 87
 TCP segment, 78
help features in command-line
 interface, 193–198,
 249–250
hexadecimal numbering
 system, 35
 conversions, 26–30, 54–56
 IP addresses, 97
 notation for, 267
hierarchical addressing, 97
hierarchical internetworking
 model, 46–49, 47
High-Level Data Link Control
 (HDLC) protocol
 description, 507
 hands-on lab, 519
 operation, 511, 511
history, command, 197
holddown timers, 395
holddowns in IP routing, 394
Holdtime field, 298
holdtime information,
 296–297
hop counts
 IGRP, 404–405
 maximum, 393–394
 RIPv1 vs. RIPv2, 403
 routing tables, 23
hops, 389–390
Hops message, 90
host addresses, 97
host tables, 313–314
host-to-host layer, 71,
 71–72, 77
 key concepts of, 82–83
 port numbers in, 83–86, 83
 TCP, 77–80, 79
 UDP, 80–82, 81
hostname command, 200, 514
hostnames
 command-line interface
 for, 200, 252
 host tables for, 313–314
 resolving, 75, 312–317,
 329–330
hubs, 3, 3
 at Physical layer, 30
 vs. switches, 26
 before switching,
 431–432, 432

hybrid protocols, 390
HyperTerminal program, 41,
 41, 271

I

ICMP (Internet Control
 Message Protocol),
 90–92, 91, 93
 in IP header, 89
 in IP routing process,
 343, 346, 348,
 350–351, 350
Identification field in IP
 header, 87
IEEE (Institute of Electrical
 and Electronics
 Engineers), 465
IEEE 802.11 standards,
 466–471, 468–469, 471
IFS (IOS file system), 278–280
 for configuration, 290–292
 for IOS upgrades, 280–283
Ignore NVRAM contents
 bit, 267
IGP (Interior Gateway
 Protocol), 388
IGRP (Interior Gateway
 Routing Protocol),
 404–405
 default ADs, 389
 EIGRP, 389
 in IP header, 90
iinteface command, 219–220
in-band management, 182
incoming banners, 202
Industrial, Scientific, and
 Medical (ISM)
 bands, 465
infinite networks, 394
infrastructure-ssid
 command, 363
inside NAT networks,
 163, 165
Institute of Electrical and
 Electronics Engineers
 (IEEE), 465
Integrated Services Digital
 Network (ISDN), 507
interface command, 191–192
interface ethernet
 command, 215
interface fastethernet
 command, 215–216
interface range command, 494

- interface serial command, 214–216
- interface type number sequence, 215
- interfaces, 191, 214–217
 - bringing up, 184–187, 217–218
 - CDP for, 302–304
 - CLI prompts for, 191–192
 - DHCP configuration on, 219–220
 - displaying, 233–234
 - IP address configuration on, 218
 - pipes, 221–222
 - in routing tables, 22
 - serial, 222–224, 222
 - traffic information for, 302
- Interior Gateway Protocol (IGP), 388
- Interior Routing Gateway Protocol (IRGP), 404–405
 - default ADs, 389
 - EIGRP, 389
 - in IP header, 90
- internal router components, 264–265
- internal routers, 486, 487
- International Organization for Standardization (ISO), 11
- Internet Control Message Protocol (ICMP), 90–92, 91, 93
 - in IP header, 89
 - in IP routing process, 343, 346, 348, 350–351, 350
- Internet layer, 71, 71–72, 86–87
 - ARP, 93–96, 94
 - ICMP, 90–92, 91, 93
 - IP, 87–90, 88–89
 - RARP, 95, 95
- Internet Protocol (IP), 87–90, 88–89
- Internet protocols
 - and DoD model, 70–72, 71–72
 - exam essentials, 105–106
 - host-to-host layer. *See* host-to-host layer
 - Internet layer, 86–87, 88
 - ARP, 93–96, 94
 - ICMP, 90–92, 91
 - IP, 87–90
 - RARP, 95, 95
- IP addresses. *See* IP addresses
- IP addresses
 - process/application layer, 72–77, 77
 - review questions, 107–113
 - summary, 101
 - Version 6, 90
 - written labs, 106, 114
- Internetwork Operating System. *See* IOS (Internetwork Operating System)
- internetworking, 2
 - addresses, 3–4, 3
 - basics, 3
 - data encapsulation, 43–46, 43–44
 - Ethernet. *See* Ethernet networking
 - exam essentials, 50–51
 - hubs, bridges, routers, and switches, 5–10, 5–6, 8–9
 - models, 11–12
 - OSI reference model. *See* OSI (Open System Interconnection) reference model
 - review questions, 57–62
 - summary, 49
 - three-layer hierarchical model, 46–49, 47
 - written lab, 51–56, 53, 63–67
- IOS (Internetwork Operating System), 180–181
 - backing up, 276–277, 326
 - for bringing up routers, 184–187
 - command-line interface. *See* command-line interface (CLI)
 - for connecting to routers, 182–184, 182–183
 - exam essentials, 245–247
 - flash memory
 - managing, 283–287, 283–286
 - verifying, 275–276
 - hands-on lab, 248–254
 - IFS for, 278–283
 - restoring, 278, 326–327
 - review questions, 255–261
 - summary, 244–245
 - upgrading, 278, 280–283
 - written labs, 247, 262
- IOS file system (IFS), 278–280
 - for configuration, 290–292
 - for IOS upgrades, 280–283
- IP (Internet Protocol), 87–90, 88–89
- ip address command, 218
- IP addresses, 3–4, 87, 96
 - broadcast, 103–105
 - command-line interface for, 253
 - configuring, 218
 - DHCP, 76–77
 - hierarchical scheme, 97
 - Class A addresses, 100–101
 - Class B addresses, 101
 - Class C addresses, 101–102
 - network addressing, 97–100, 98
 - in IP routing process, 345–353
 - IPv6, 90
 - NAT. *See* Network Address Translation (NAT)
 - private, 102–103
 - terminology in, 96
 - troubleshooting, 153–160, 153, 156–160
- IP broadcast with all zeros bit, 267
- IP broadcasts do not have net numbers bit, 267
- ip classless command, 386
- ip default-network command, 387–388
- ip dhcp command, 243
- ip dhcp pool command, 219
- ip dhcp pool admin command, 363
- ip domain-lookup command, 315
- ip domain-name command, 315
- ip excluded-address command, 363
- IP headers, 87–89, 88–89
- ip host name command, 313
- ip http command, 237, 239
- ip name-server command, 315
- ip route command, 375–376
- IP routing, 340
 - basics, 341–343, 342
 - configuration, 353–354, 355
 - 871W router, 371–372

602 IP spoofing – MAC (Media Access Control) addresses

1242AP router, 373–374
 Corp router, 355–358
 R1 router, 358–361
 R2 router, 361–364
 R3 router, 364–371, 364–371
 verifying, 384–385, 405–413
 default routing, 385–388, 387–388
 dynamic routing, 388–390
 exam essentials, 413–414
 examples, 349–353, 349–352
 hands-on lab, 415–418, 415
 holdddowns, 394
 maximum hop counts, 393–394
 process, 343–348, 343–344
 protocols
 administrative distances in, 389–390
 classes, 390
 distance-vector, 390–394, 391–393
 IGRP, 404–405
 RIP, 394–404
 review questions, 419–426
 route poisoning, 394
 routing loops, 393–394, 393
 split horizon, 394
 static routing, 375–376
 871W router, 383–384
 Corp router, 376–378
 R1 router, 378–380
 R2 router, 380–381
 R3 router, 381–383, 382
 summary, 413
 written lab, 414–415, 427
 IP spoofing, 488–489
 ip ssh command, 208
 ip subnet-zero command, 117, 148
 IP Unnumbered option, 368
 ipconfig command, 155
 IPv6 protocol, 90
 ISDN (Integrated Services Digital Network), 507
 ISM (Industrial, Scientific, and Medical) bands, 465
 ISO (International Organization for Standardization), 11

J

jam signals, 31–32, 32

K

keys, wireless networks, 476
 keystroke loggers, 489

L

L2F (Layer 2 Forwarding), 495
 L2TP (Layer 2 Tunneling Protocol)
 defined, 495
 in IP header, 90
 LAN switches, 451–452, 451
 LAN Wizard, 369–370, 369–370
 LAPB (Link Accessed Procedure, Balanced), 507
 LAPD (Link Access Procedure, D channel), 507
 last-resort command, 203
 latency, 25
 Layer 2 broadcasts, 103
 Layer 2 Forwarding (L2F), 495
 layer 2 switching, 430
 address learning by, 435–437, 436–437
 benefits, 433–434
 vs. bridging, 435
 exam essentials, 452
 forward/filter decisions by, 437–438, 438
 LAN switch types, 451–452, 451
 limitations, 434–435
 loop avoidance, 440–441, 440–441
 review questions, 454–460
 STP in. *See* STP (Spanning Tree Protocol)
 summary, 452
 switching before, 430–433, 431–433
 written lab for, 453, 461
 Layer 2 Tunneling Protocol (L2TP)
 defined, 495
 in IP header, 90
 layered architecture, 11–12

learning state in STP, 443
 lease command, 219
 leased lines, 505
 Length field, 35
 Length of segment field, 81
 licensing for wireless technologies, 465, 466
 line command, 192, 204
 line aux command, 204
 line console command, 192, 205
 Line Printer Daemon (LPD), 74
 line vty command, 206–207
 Link Access Procedure, D channel (LAPD), 507
 Link Accessed Procedure, Balanced (LAPB), 507
 link-establishment phase for PPP sessions, 513
 link-state protocols, 390
 listening state in STP, 443
 LLC (Logical Link Control) layer, 25
 load balancing, 391
 Local Interface field, 298
 local loops, 505
 local NAT names, 162–163, 165
 logging into routers, 248–249
 logging synchronous
 command, 205–206
 logical addresses, 87, 341
 Logical Link Control (LLC) layer, function, 25
 login banners, 202–203
 login command, 204
 logout command, 189
 loopback addresses, 153
 loopback tests, 100
 loops
 avoiding, 440–441, 440–441
 routing, 393–394, 393
 LPD (Line Printer Daemon), 74

M

MAC (Media Access Control) addresses, 24–25
 Data Link layer, 34
 Ethernet addressing, 3–4, 34–35, 34
 RARP for, 95

- security, 492–494
 - wireless network authentication, 474–475
 - MAC (Media Access Control) layer
 - Ethernet, 38
 - function, 24
 - MAC forward/filter tables, 435–441, 436–437
 - MAC frame format in Ethernet frames, 34–35
 - major commands, 192
 - man-in-the-middle attacks, 489
 - management of routers, 264
 - CDP for, 296–307, 327–328
 - configuration backups and restoration
 - backups, 287–289
 - erasing, 290
 - IFS for, 290–292
 - restoring, 289–290
 - SDM for, 292–296, 293–295
 - configuration registers, 266–274
 - exam essentials, 324–325
 - hands-on lab, 325–330
 - hostname resolution, 312–317, 329–330
 - and internal router components, 264–265
 - IOS backups and restoration, 275, 275
 - backups, 276–277
 - flash memory management, 283–287, 283–286
 - flash memory verification, 275–276
 - IFS for, 278–283
 - restoring and upgrading, 278
 - network connectivity, 317–323, 318–319
 - review questions, 331–337
 - and router boot sequence, 265–266
 - subnetting for, 117
 - summary, 323
 - Telnet for, 307–312, 328
 - written lab, 325, 338
 - mask parameter, 375
 - masks, subnet, 119–120, 141–142
 - maximum hop counts, 393–394
 - Maximum Transmission Units (MTUs)
 - displaying, 230–231
 - Ethernet, 38
 - IGRP, 404
 - Media Access Control (MAC) layer
 - Ethernet, 38
 - function, 24
 - Media Access Control addresses. *See* MAC (Media Access Control) addresses
 - Media Independent Interface (MII), 38
 - media translation, 30
 - metrics
 - IGRP, 404
 - routing tables, 22–23
 - MII (Media Independent Interface), 38
 - MIMO (Multiple-Input Multiple Output), 471
 - mini-OS component, 265
 - mkdir command, 278, 280
 - mobile devices, security threats to, 487
 - modified cut-through switching method, 452
 - more command, 278, 280
 - MOTD banners, 202–203
 - MTUs (Maximum Transmission Units)
 - displaying, 230–231
 - Ethernet, 38
 - IGRP, 404
 - multicast group addresses, 104
 - multicasts, 103, 435
 - multiple devices, Telnet with, 309
 - Multiple-Input Multiple Output (MIMO), 471
-
- N**
- names
 - DHCP pools, 219
 - NAT, 162–163, 165
 - R3 router configuration, 365, 365
 - NAT. *See* Network Address Translation (NAT)
 - NCP (Network Control Protocol), 512–513
 - neighbors, 297–301
 - Network Access layer, 71, 71–72
 - Network Address Translation (NAT), 102, 161
 - names, 162–163, 165
 - operation, 163–165, 165
 - types, 162
 - uses, 161–162, 161
 - network addresses, 96
 - IP addressing, 97–100, 98
 - routing tables, 22
 - network command, 219, 396
 - network connectivity, 317
 - ping command for, 317–318
 - traceroute command for, 319–320
 - Network Control Protocol (NCP), 512–513
 - Network File System (NFS), 73–74
 - Network Interface Cards (NICs), 34, 34
 - Network layer
 - encapsulation, 45–46
 - OSI reference model, 21–23, 22–23
 - network-layer protocol phase in PPP sessions, 513
 - network performance, subnetting for, 117
 - network reconnaissance attacks, 489
 - network segmentation, 5–10, 5–6, 8–9
 - network traffic, subnetting for, 117
 - networks
 - classless, 141–142
 - topology documentation, 304–307, 305, 307
 - next-hop_address parameter, 375
 - NFS (Network File System), 73–74
 - nibbles, 26–29, 38
 - NICs (Network Interface Cards), 34, 34
 - no banner login command, 202
 - no cdp enable command, 297, 303
 - no cdp run command, 297, 302

604 no ip domain-lookup command – ports and port numbers

no ip domain-lookup command, 315
 no ip host command, 314
 no login command, 204, 308
 no shutdown command, 231
 node addresses, 97
 non-volatile RAM (NVRAM), 184
 copying configuration to, 288–289
 displaying, 290–291
 for startup-config file, 265–266, 270
 nondesignated ports, 443
 nonroot bridges, 442
 number system conversions, 26–30, 54–56
 NVRAM (non-volatile RAM), 184
 copying configuration to, 288–289
 displaying, 290–291
 for startup-config file, 265–266, 270

O

o/r command, 272
 octets, 96
 OEM bit enabled bit, 267
 OFDM (Orthogonal Frequency Division Multiplexing) technique, 469
 100BaseFX technology, 38
 100BaseTX technology, 38
 1000BaseCX technology, 38
 1000BaseLX technology, 38
 1000BaseSX technology, 38
 1000BaseT technology, 38
 open-access mode in wireless networks, 474
 Open Shortest Path First (OSPF) protocol
 default ADs, 390
 in IP header, 90
 as link-state protocol, 390
 optimized network performance, subnetting for, 117
 Options field
 IP header, 88
 TCP header, 79
 Organizationally Unique Identifiers (OUIs), 34

Orthogonal Frequency Division Multiplexing (OFDM) technique, 469
 OSI (Open System Interconnection) reference model, 11–14, 13–14, 51–53
 Application layer, 14–15
 Data Link layer, 23–29, 24–25
 Network layer, 21–23, 22–23
 Physical layer, 30
 Presentation layer, 15
 Session layer, 16
 Transport layer, 16–21, 17, 19–21
 OSPF (Open Shortest Path First) protocol
 default ADs, 390
 in IP header, 90
 as link-state protocol, 390
 OUIs (Organizationally Unique Identifiers), 34
 out-of-band management, 182
 outside NAT names, 162–163, 164
 overloading NAT, 163–165, 164

P

Packet InterNet Group command. *See* Ping (Packet Internet Groper) command
 packet sniffer attacks, 489
 packet switching, 506, 506
 packets, 22, 43
 PAP (Password Authentication Protocol), 513–514
 passive-interface command, 402
 passive interfaces, 398
 password attacks, 489
 Password Authentication Protocol (PAP), 513–514
 password command for enable passwords, 203
 in PPP, 514
 passwords
 attacks on, 490–491
 auxiliary, 204–205
 console, 205–206
 enable. *See* enable passwords
 enable passwords
 encrypting, 209–212
 FTP, 73
 R3 router configuration, 365, 365
 recovering, 270–273
 SDM, 239
 setting, 203–204, 250–252
 Telnet, 206–207, 308–309
 wireless networks, 476
 PAT (Port Address Translation), 163–165, 164
 PDUs (Protocol Data Units), 43, 43–44
 performance, subnetting for, 117
 perimeters, 486, 487
 permanent parameter, 376
 Physical layer, 30, 37–39, 37
 Ping (Packet Internet Groper) command
 ICMP, 91–92
 IP addresses, 153–155
 for network connectivity, 317–318
 protocols with, 227–228
 TFTP, 277
 for verifying configuration, 384–385
 ping of death attacks, 488
 pinhole congestion, 391, 391
 pipes, 221–222
 Platform field, 298
 PoE (Power over Ethernet) light, 446
 point-to-point connections, 505
 Point-to-Point Protocol. *See* PPP (Point-to-Point Protocol)
 Point-to-Point Tunneling Protocol (PPTP), 495
 points of presence (POPs), 505
 poison reverse updates, 394
 poisoning, route, 394
 POPs (points of presence), 505
 Port Address Translation (PAT), 163–165, 164
 Port ID field, 298
 port redirection attacks, 489
 port-security command, 439–440
 ports and port numbers
 Catalyst switches, 445
 CDP for, 302–304
 console commands for, 205–206

- forward/filter decisions, 439–440
 - host-to-host layer protocols, 83–86, 83
 - security for, 439–440, 492–494
 - TCP, 78, 83–86
 - Transport layer, 45, 45
 - UDP segment, 81
 - positive acknowledgment with retransmission technique, 20
 - POST (power-on self test) in bringing up routers, 184–185
 - as router component, 264–265
 - Power over Ethernet (PoE) light, 446
 - powers of 2, 118
 - PPP (Point-to-Point Protocol), 512–513, 512
 - authentication, 513–515
 - configuring, 514–515, 517–518, 517
 - description, 508
 - encapsulation, 515
 - sessions, 513
 - ppp authentication command, 515
 - PPTP (Point-to-Point Tunneling Protocol), 495
 - Pre-Shared Key (PSK), 476
 - preambles in Ethernet frames, 35
 - prefix routing, 395
 - Presentation layer, 15
 - priorities, datagrams, 87
 - Priority field, 87
 - private IP addresses, 102–103
 - privileged mode defined, 193
 - entering, 189, 272
 - Process/Application layer, 71–77, 71–72, 77
 - processes, connectivity, 322–323
 - prompts in command-line interface, 191
 - for interfaces, 191–192
 - line commands, 192
 - for routing protocol configurations, 193
 - for subinterfaces, 192
 - propagations in RIP, 402
 - Protocol Data Units (PDUs), 43, 43–44
 - Protocol field, 88–90
 - protocols. *See also specific protocols by name*
 - administrative distances in, 389–390
 - classes, 390
 - CLI prompts for, 193
 - Proxy ARP (Proxy Address Resolution Protocol), 95–96
 - PSK (Pre-Shared Key), 476
 - pwd command, 278, 280
-
- Q**
- question marks (?) for commands, 193–195
-
- R**
- R1 router configuration
 - IP, 358–361
 - RIP, 396–397
 - RIPv2, 411
 - static routing, 378–380
 - R2 router configuration
 - IP, 361–364
 - RIP, 397
 - RIPv2, 411–412
 - static routing, 380–381
 - R3 router configuration
 - IP, 364–371, 364–371
 - RIP, 397–399, 398
 - static routing, 381–383, 382
 - verifying, 405–413
 - radio frequencies (RF) for wireless technologies, 464
 - RAM (random access memory), 265
 - range command, 494
 - RARP (Reverse Address Resolution Protocol), 95, 95
 - RARP servers, 95
 - read-only memory (ROM), 265
 - recovering passwords, 270–273
 - redirection attacks, 489
 - redistribution, RIP, 403
 - reduced network traffic, subnetting for, 117
 - reference models. *See* OSI (Open System Interconnection) reference model
 - registered jack (RJ) connectors
 - console ports, 182–183
 - Ethernet, 37, 41, 42
 - registers, configuration, 265
 - bits in, 266–267
 - changing values, 268–269
 - checking values, 268
 - for password recovery, 270–273
 - Registry, hexadecimal addresses in, 97
 - reliability, 230
 - reliable data delivery, 20–21, 21
 - reliable networking, 16
 - reloading, 272
 - remote client machines, Telnet for, 73
 - remote VPNs, 495
 - repeaters, 30
 - “request timed out” message, 347
 - Request To Send (RTS) signal, 468
 - reserved addresses, 99–100, 102
 - Reserved field, 79
 - reset command, 271–272
 - Reset Router option, 365
 - resolving host names, 75, 312–317, 329–330
 - restoration
 - configuration, 289–290, 292–296, 293–295
 - IOS, 278, 326–327
 - Reverse Address Resolution Protocol (RARP), 95, 95
 - RF (radio frequencies) for wireless technologies, 464
 - RIP (Routing Information Protocol), 394–395
 - configuration, 417–418
 - 871W router, 399
 - Corp router, 395–396
 - example, 401–402, 401
 - R1 router, 396–397
 - R2 router, 397
 - R3 router, 397–399, 398
 - default ADs, 390
 - load balancing, 391
 - need for, 402–403
 - propagations, 402

606 RJ connectors – show ip arp command

RIPv2
 enabling, 411–413, 411
 vs. RIPv1, 403–404
 timers, 395
 verifying routing tables, 399–401

RJ connectors
 console ports, 182–183
 Ethernet, 37, 41, 42

rmdir command, 278, 280

rolled cable, 40–41, 40

ROM (read-only memory), 265

ROM monitor
 component, 265

ROM monitor mode field, 267

rommon 1 prompt, 271

root bridges, 442

root ports in STP, 443

round-robin load
 balancing, 391

route flush timers, 395

route invalid timers, 395

route poisoning, 394

route redistribution, 403

route summarization, 144

route update packets, 22

route update timers, 395

routed protocols, 22

router rip command, 395–396

routers, 23, 23
 attack mitigation, 491–492
 boot sequence, 265–266, 271
 bringing up, 184–187
 configuring. *See* configuration
 connecting to, 182–184, 182–183
 interfaces for.
See interfaces
 logging into, 248–249
 managing. *See* management of routers
 Network layer, 22
 network segmentation, 5–10, 6, 8–9
 reloading, 272
 before switching, 430–431

routing
 command-line interface for, 200
 Internet layer protocols for, 86–87
 IP. *See* IP routing
 routing by rumor, 391
 Routing Information Protocol.
See RIP (Routing Information Protocol)

routing loops, 393–394, 393

routing metrics
 IGRP, 404
 routing tables, 22–23

routing protocols, 22, 193. *See also specific routing protocols by name*

routing tables, 22, 22, 399–401

RTS (Request To Send)
 signal, 468

running-config file, 185
 for configuration, 226, 287
 for interface status, 217
 for passwords, 209–210

RXBOOT component, 265

S

S1 Catalyst switch
 configuration, 447–448

S2 Catalyst switch
 configuration, 448–449

SA (Source Address) field, 35

saving configurations, 225, 250

scalability, RIPv1 vs. RIPv2, 403

scrolling command lines, 196

SDM (Security Device Manager), 183, 236
 backups and restores, 292–296, 293–295
 configuring, 236–244, 238–243, 254
 connectivity, 318–319, 318–319
 downloading, 236
 flash memory management, 283–287, 283–286
 Telnet protocol, 311–312, 312

secondary command, 218

secret command, 203

Secure Shell (SSH), 207–209

security, 486
 attack profiles, 488–490
 exam essentials, 496
 forward/filter decisions, 439–440
 overview, 486–487, 487
 review questions, 497–500
 summary, 495
 threat mitigation, 490–494
 threats, 487–488
 wireless networks, 474–476
 written lab for, 496, 501

Security Device Manager.
See SDM (Security Device Manager)

segment format
 TCP, 78–80, 79
 UDP, 81–82, 81

segmentation, 5–10, 5–6, 8–9

Sequence number field, 78

sequencing, 78

serial interface commands, 222–224, 222

serial transmissions, 509

service password-encryption command, 210–211, 514

Service Set Identifiers (SSIDs), 472, 474–475

Session layer, 16

sessions
 PPP, 513
 Telnet, closing, 310–311

setup command, 187

setup modes, 187, 193

SFD (Start Frame Delimiter)/
 Synch field, 35

shared keys, 476

shortest-path-first protocols, 390

show cdp command, 296

show cdp entry * command, 299–301

show cdp interface command, 302

show cdp neighbors command, 297–298

show cdp neighbors detail command, 298–299, 304

show cdp traffic command, 302

show commands, do for, 213–214

show controllers command, 234–236, 235, 358

show file command, 280–282, 290–291

show flash command, 269–270, 276, 281

show history command, 197

show hosts command, 313–314, 316

show interface command
 interface status, 217
 PPP, 515
 verifying configurations, 228–233

show interface fastethernet command, 229

show interface serial command, 231

show ip arp command, 155

show ip interface command – TCP (Transmission Control Protocol) 607

- show ip interface command, 233, 407
 - show ip interface brief command, 233–234
 - show ip protocols command, 406–407
 - show ip route command, 342
 - default routes, 387–388
 - RIP routes, 400–401
 - routing tables, 357, 360
 - static routes, 377–383
 - show mac address-table command, 438
 - show port-security command, 493
 - show processes command, 322–323
 - show protocols command, 234
 - show running-config command
 - configuration, 226, 287
 - documentation, 305–306
 - interface status, 217
 - passwords, 211
 - show sessions command, 309–311, 314
 - show startup-config command, 226, 288
 - show terminal command, 197–198
 - show users command, 311
 - show version command, 199, 268–269
 - shutdown command, 217, 494
 - Simple Mail Transfer Protocol (SMTP), 74
 - Simple Network Management Protocol (SNMP), 75
 - simplex modes, 16
 - simplified management, subnetting for, 117
 - site-to-site VPNs, 495
 - smart-serial cable, 509
 - SMTP (Simple Mail Transfer Protocol), 74
 - SNMP (Simple Network Management Protocol), 75
 - software addresses, 87
 - Source Address (SA) field, 35
 - Source IP address field, 88
 - Source port field
 - TCP segment, 78
 - UDP segment, 81
 - source ports in TCP, 83–84
 - spanning-tree algorithm (STA), 441
 - Spanning-Tree Protocol. *See* STP (Spanning Tree Protocol)
 - special purpose addresses, IP, 99
 - specific configuration modes, 193
 - split horizon protocols, 394
 - spoofing, 488–489
 - SSH (Secure Shell), 207–209
 - SSIDs (Service Set Identifiers), 472, 474–475
 - STA (spanning-tree algorithm), 441
 - Stacheldraht attacks, 488
 - Start Frame Delimiter (SFD)/Synch field, 35
 - startup-config file, 185, 225–226
 - deleting, 290
 - displaying, 226, 288
 - password recovery, 270
 - router boot sequence, 266
 - state transitions, 30
 - static NAT, 162
 - static routing, 341, 375–376
 - 871W router, 383–384
 - Corp router, 376–378
 - default ADs, 389
 - hands-on lab, 416–417
 - R1 router, 378–380
 - R2 router, 380–381
 - R3 router, 381–383, 382
 - status, interface, 217
 - sticky command, 439
 - store-and-forward switching method, 452
 - STP (Spanning Tree Protocol), 441–442, 442
 - Catalyst switches, 445–447, 445–446
 - Core, 449–451
 - S1, 447–448
 - S2, 448–449
 - convergence, 444, 444
 - exam essentials, 452
 - port states, 443–444
 - review questions, 454–460
 - summary, 452
 - terminology, 442–443
 - written labs, 453, 461
 - straight-through cable, 39, 39
 - subcommands, 192
 - subinterfaces, 192
 - subnet masks
 - need for, 119–120
 - VLSMs, 141–142
 - subnet-zero command, 117, 148
 - subnets and subnetting, 116–117
 - CIDR, 120–122
 - Class A addresses, 138–141
 - Class B addresses, 131–138
 - Class C networks, 122–131, 124, 126
 - creating, 118–119
 - exam essentials, 165–166
 - ip subnet-zero, 117
 - review questions, 169–175
 - subnet masks for, 119–120
 - summarization, 144
 - summary, 165
 - written labs, 166–168, 176–177
 - subscribers to group addresses, 104
 - summarization, 144
 - supernetting, 144
 - switch port security, 492–494
 - switches
 - attack mitigation, 491–492
 - Catalyst, 445–447, 445–446
 - Core, 449–451
 - S1, 447–448
 - S2, 448–449
 - Data Link layer, 25–26, 25
 - vs. hubs, 26
 - layer 2. *See* layer 2 switching
 - for network segmentation, 5–10, 5–6, 8–9
 - switchport mode access command, 494
 - switchport port-security command, 439–440, 493
 - syn packet acknowledgments, 85–86
 - system LED, 446, 446
-
- T**
- T-connectors, 38
 - Tab command, 196
 - tables for VLSMs, 144–150, 145, 147, 149
 - TCP (Transmission Control Protocol), 78
 - destination ports, 84–85
 - key concepts, 82–83
 - port numbers, 83–86, 83
 - segment format, 78–80, 79
 - source ports, 83–84
 - syn packet
 - acknowledgments, 85–86

608 TCP/IP (Transmission Control Protocol/Internet Protocol) – UTP (unshielded)

- TCP/IP (Transmission Control Protocol/Internet Protocol). *See also* Internet protocols and DoD model, 70–72, 71–72
IP addresses. *See* IP addresses
TCP SYN flood attacks, 488
telnet command, 155, 227–228
Telnet protocol, 73, 307–308, 328
closing sessions, 310–311
for configuration information, 227–228
connections, 309–310
with multiple devices, 309
passwords, 206–207, 308–309
for router connections, 182
SDM for, 311–312, 312
users, 310
10Base2 technology, 37–38
10Base5 technology, 38
10BaseT technology, 38
terminal emulation, 73
terminal history size command, 198
terminal monitor command, 408
TFN (Tribe Flood Network) attacks, 488
TFTP (Trivial File Transfer Protocol), 73, 277, 288–289
tftp-server command, 278
thicknet, 37–38
thin protocols, 80
thinnet, 37
this network or segment address, 99
thrashing of MAC tables, 441
threats, security, 487–488
three-layer hierarchical model, 46–49, 47
three-way handshakes, 17
Time To Live (TTL), 88
timers
CDP for, 296–297
RIP, 395
toll networks, 505
topology, 304–307, 305, 307
Total length field, 87
traceroute command
ICMP, 91, 155, 228
for network connectivity, 319–320
traffic information, CDP for, 302
transferring files, 73–74
Transmission Control Protocol. *See* TCP (Transmission Control Protocol)
Transmission Control Protocol/Internet Protocol. *See also* Internet protocols and DoD model, 70–72, 71–72
IP addresses. *See* IP addresses
transparent bridging, 26
Transport layer, 16
acknowledgments, 20–21, 21
connection-oriented communication, 17–18, 17, 19
flow control, 16–17
port numbers, 45, 45
windowing, 19–20, 20
traps, 75
Tribe Flood Network (TFN) attacks, 488
Trivial File Transfer Protocol (TFTP), 73, 277, 288–289
Trojan horse attacks, 489
troubleshooting
connectivity, 320–322
debug ip rip for, 409–410
IP addresses, 153–160, 153, 156–160
show ip protocols for, 406–407
trust exploitation attacks, 489
trusted networks, 486
TTL (Time to Live), 88
tunneling, 35
2.4GHz wireless, 468–469, 468, 471
1242AP router configuration, 373–374
2500 routers
configuration, 272
2501 routers, interfaces and connections, 182, 182
2600 routers
bringing up, 185–187
configuration, 271–272
interfaces and connections, 182–183, 183
2800 routers
bringing up, 184–185
interfaces and connections, 183–184, 183
Type field in Ethernet frames, 35
Type of Service field, 87
-
- ## U
- UDP (User Datagram Protocol), 80–81
key concepts, 82–83
port numbers, 83–86, 83
segment format, 81–82, 81
undebug all command, 321–322
unicasts, 103
unified wireless solution, 474–476
UNII (Unlicensed National Information Infrastructure), 465, 466, 469–470, 469
universal bit, 34
unreliable protocols, 81
unshielded twisted-pair (UTP), 37, 41, 42
untrusted networks, 486
unused ports, securing, 494
updates with holddown timers, 394
upgrading IOS, 278, 280–283, 326–327
Urgent pointer field, 79
URLs in IFS, 279
use-tacacs command, 203
User Datagram Protocol (UDP), 80–81
key concepts, 82–83
port numbers, 83–86, 83
segment format, 81–82, 81
user mode, 189
user EXEC mode, 193
username command, 238, 514
usernames
FTP, 73
PPP, 514
SDM, 238–239
users, Telnet, 310
UTP (unshielded twisted-pair) wiring, 37, 41, 42

V

V.24 standard, 512
 V.35 standard, 512
 valid host IDs
 Class A addresses, 101
 Class B addresses, 101
 Class C addresses, 102
 variable-length subnet masks. *See* VLSMs (variable-length subnet masks)
 verifying
 configurations
 IOS, 227–236, 235
 IP routing, 384–385, 405–413
 PPP encapsulation, 515
 RIP routing tables, 399–401
 router, 287–288, 384–385
 flash memory, 275–276
 version 2 command, 404
 Version field, 87
 viewing configurations, 226
 virtual circuits
 port numbers, 83
 TCP, 78
 virtual private networks (VPNs), 494–495
 virus attacks, 489
 VLSMs (variable-length subnet masks), 141–142, 142
 benefits, 143–144
 designing, 142–144, 143, 152–153, 152
 implementing, 144–152, 145–151
 RIPv1 vs. RIPv2, 403–404

VPNs (virtual private networks), 494–495
 vty command, 204
 VTY passwords, 308

W

WAN Wizard, 366–368, 366–368
 WANs (wide area networks), 504–505
 cabling, 508–510, 509–510
 connection types, 505–506, 506
 DTE and DCE for, 510, 510
 exam essentials, 516
 hands-on lab, 517–519, 527
 HDLC for, 511, 511
 PPP for, 512–513, 512
 authentication, 513–515
 configuration, 514–515
 encapsulation, 515
 sessions, 513
 review questions, 520–526
 summary, 516
 support, 506–508
 terminology, 505
 written lab, 516–517
 well-known port numbers, 83
 WEP (Wired Equivalency Protocol), 474–475
 Wi-Fi Alliance, 465
 Wi-Fi Protected Access (WPA), 475–476
 wildcards, 385
 Window field, 79
 windowing, 19–20, 20
 Windows Registry,
 hexadecimal addresses in, 97
 Wired Equivalency Protocol (WEP), 474–475
 wireless networks, 464
 802.11 standards, 466–471, 468–469, 471
 Basic Service Set, 471–473, 473
 exam essentials, 477
 overview, 464–466, 466
 review questions, 478–483
 security, 474–476, 487
 summary, 476–477
 written labs, 477, 484
 workgroup layer, 48–49
 WPA (Wi-Fi Protected Access), 475–476
 written labs
 Internet protocols, 106, 114
 internetworking, 51–56, 53, 63–67
 IOS, 247, 262
 IP routing, 414–415, 427
 layer 2 switching and STP, 453, 461
 management, 325, 338
 security, 496, 501
 subnetting, 166–168, 176–177
 WANs, 516–517
 wireless networks, 477

X

X Window system, 75

