

Index

A

- Abbe error 12–13, 47–52, 73, 121, 298, 345–347
 - Abbe offset 52, 210, 363
 - adjustment
 - electrical 67, 126, 214
 - mechanical 6, 7, 16, 206, 283, 291
 - optical 7, 9, 350
 - adsorption, of water 252, 435
 - aperture
 - mechanical 96, 423, 507
 - optical 54, 96, 133, 423
 - optical, illumination 11
 - optical, numerical 134, 141, 323
 - optical, correction 11, 323, 324
 - optical, correction factor 323, 326, 328, 329, 330
 - atomic force microscopy (AFM)
 - see* microscopy
- ### C
- calibration 186, 231, 232
 - accuracy 221
 - certificates 249
 - coefficient 202
 - device 4, 166–169
 - guideline 173–192, 256
 - intervall 178, 221
 - method 120, 251
 - mode 120
 - plan 179
 - procedure 78, 123, 173–192, 240, 250, 254, 266, 469
 - range 41, 80, 83
 - scheme 183
 - software 207, 213
 - standard 99, 119, 184, 234, 240, 245, 259–268, 282–294, 300–302, 365, 375, 469
 - strategy 61, 175, 179
 - uncertainty 27, 188, 216, 220, 228, 249
 - of instruments and sensors 205, 283–294, 324
 - of cantilever (tip) signal 123
 - of capacitive sensors 14, 78
 - of displacement transducer 41, 252
 - of ellipsometer 255, 256
 - of force 35, 157, 165–167
 - of laser interferometer 345–358
 - of particle counters 361
 - of profilometer 157, 234, 259–268
 - of scanner axes 183–189, 193, 222, 246, 362–372, 394
 - of SEM 375–377
 - of SPM 12, 15, 74, 174–178, 193, 205, 246, 256, 367, 444, 469
 - of artefact or standards 13, 25, 74, 205, 222, 251
 - of flatness 259
 - lateral 183–186, 195, 201, 211, 246, 282, 469
 - of layer thickness 255
 - of linewidth 374, 376
 - of mass 434–442
 - of particle diameter 361–374
 - of pitch 404
 - of roughness 73
 - of step height 27, 190, 252
 - of tip geometry 18, 246, 300
 - vertical 183–188, 223
- cantilever 6–7, 58, 200, 221–223, 252, 445–450
 - deflection 4, 62–67, 75–78, 196, 119–128, 312, 368
 - detection system 4–7, 76, 119–121, 312
 - non-contact 317, 364
 - piezoresistive 7, 91, 157–170
- capacitive transducer (sensor) 4–16, 23, 74–79, 120–126, 134, 177, 181, 193–194, 207–208, 213, 245, 361–364

- certified reference material 282–294
 - certified standards 70, 190, 213, 252
 - charging 385–403
 - cleaning 424, 432, 434–442
 - closed loop 51–53, 63, 181, 186
 - closed loop SPM 123, 177, 186, 193–204, 221, 475
 - combined techniques
 - combined optical and x-ray interferometry 22–37
 - combined shear force and tunnelling microscope 144–156
 - combined SPM and interference microscopy 3–21
 - combined SPM and confocal microscope 131–143
 - combined SPM, optical and X-ray interferometry 38–44
 - comparison
 - measurements, international 18, 88–91, 205–219, 256, 387
 - of results, internal 12, 13, 40, 278, 346–348, 384, 413–418, 484, 493–494
 - pitch 206–211
 - step height 55, 221
 - confocal microscope *see* microscopy
 - contact area 465–479
 - contact mode 58, 75, 222–223, 364, 368–369
 - contamination *see* surface
 - coordinate measuring machine (CMM) 4, 9, 48–49, 95–96, 132, 194
 - cosine error 52, 81
 - creep 157, 194
 - creep of PZT 179, 187, 194, 221, 485–491, 506
 - critical dimension (CD) 23, 375–384, 385–403
- D**
- deformation 301, 332, 465
 - detection, integrated
 - detection, piezoresistive 7, 91, 157–167
 - detection, strain gauges 7
 - detection, tuning fork 9, 91, 112, 131–135, 140–141
 - digital signal processor (DSP) 78, 119–121, 134, 364
 - dimensional metrology 3–4, 38–40, 132, 205, 375
 - displacement 30–36, 51, 96, 207
 - actuator 29, 41, 213
 - measurement 22–31, 39–43, 49, 222, 256, 340–343, 363–364, 375, 416, 466
 - position 30, 484–491
 - range 227, 468
 - sensor 222–226, 325, 404
 - stage 10, 100–103, 139, 206–213, 363–365
 - vector 32
- E**
- e-beam 144, 311
 - edge operator 68, 385–386
 - electrostatic field 443–449
- F**
- feedback control 95–100, 140, 180–187
 - film thickness *see* standard
 - finite element 158, 169, 444, 474
 - flatness *see* standard or measurement
 - fractal 71, 452–462
 - frequency
 - analysis 163, 265
 - comparison 348
 - cut-off 417–418
 - beat 35, 52
 - filter 418
 - folding 417
 - resonance 16, 73–78, 113, 135, 149–150, 222–223, 265, 364, 368
 - response 35, 66, 415, 430
 - sampling 99, 417, 422
 - scanning 98
 - shift 405
 - spatial 82, 292, 323–330, 333, 338, 424–426, 430–432, 458
 - spectrum 417
 - stability 35, 78
 - stabilized 52, 78, 406
 - transmission function 186
 - fringe, optical 33, 38–44, 112–114, 120, 147–148, 274, 325, 331–344
 - contrast 34, 507
 - counting 112, 118, 364
 - interpolation 31, 124
 - pattern 34, 323–327, 331–344
 - period 30, 31, 33, 323–326, 331
 - fringe, x-ray 30, 32, 38–44

G

 - grating 25–28, 43, 80–91, 193–204, 206–211, 283–286, 291–294, 396, 404–406
 - constant (pitch) 25–26, 43, 251, 292–293, 407
 - material contrast 293

H

- hardness 414, 465–477
 - indentation 57, 465
 - indenter 18
 - measurement 18, 157–158, 465–480
- heterostructure *see* multilayer
- Heydemann correction 14, 40, 124–127, 364, 408
- hysteresis
 - of PZT 4, 100–103, 186–187, 194, 221–225, 245, 485
 - of PZT, model 101

I

- image analysis 105–107, 208, 213, 465–467, 478–479, 481–499
- inductive sensor (transducer) 4, 74, 177, 245
- interaction 261, 345, 413–423, 503
 - tip-sample (probe-surface) 95, 140, 144, 176, 182, 221, 256, 261, 303, 310, 361, 368–369, 374
 - tip-sample, as interference 105, 302, 310, 316–318, 362–365, 370, 374, 379
- interference
 - (disturbance) 7, 181, 247
 - microscope 9–12, 85, 132, 179–180, 205–206, 212–214, 247, 252, 269–281, 323–324, 330
 - objective 10
 - optical 3, 11, 33, 274, 324–325, 331–334, 340–342, 405, 500–514
 - pattern 7, 32–33, 112–114, 331–334
 - x-ray 32–33
- interferometer, displacement
 - non-linearity 3, 14, 40–41, 78–79, 80, 86, 97–98, 119–127, 187, 211, 350
 - optical 14–15, 23, 29–32, 38–44, 63, 77–86, 112–118, 187, 207–213, 345–352, 375–377, 408, 500–514
 - optical, glass fibre 62, 144–154, 312
 - optical, heterodyne 49, 54, 95–97, 207, 213–214, 404–408
 - x-ray 29–32, 38–44
 - imaging 11, 33–36
- intermittent contact 74, 131, 135, 364

L

- lateral
 - lateral calibration *see* calibration
 - lateral resolution 9, 11, 54–55, 68–70, 74, 99, 112, 132, 282–283, 288–294, 323, 430, 442
 - lateral standard *see* standard
 - lattice parameter 29–30, 38, 40

- least squares fit (LSF) 256
- length *see* measurement 345
- line spread function 286–290
- linewidth *see* measurement
- Littrow setup 25, 207

M

- mass standards *see* standard
- measurement
 - accuracy 444
 - area 5–11, 64, 80–88
 - circle 111, 179, 347
 - deviation 346–350, 405
 - flatness 86, 180, 188, 259–268
 - force 157–170
 - length 3, 345, 355, 404, 500–514
 - linewidth 23, 311, 376, 390
 - method 112–113, 138, 206–213, 283, 381, 467
 - particle diameter 352, 361–374
 - position 73, 80, 119–130, 177
 - range 31, 40–52, 75–76, 85, 135, 264, 427
 - roughness 58, 74, 86–88, 231–234, 254, 365, 424–433, 470
 - speed 73, 75, 91, 119, 128
 - step height 7, 12, 55, 205, 220–229, 232–233
 - uncertainty 26–30, 52–58, 105–106, 190, 195–202, 210–216, 264–265, 328–330, 346–356, 367–374, 394–396, 509–511,
 - strategy 71, 80–81, 271
 - topographic 7, 74, 323, 418
- metrology, scanning probe microscope
 - for 3–21, 23–25, 74, 173–192, 363–365
- micro milling 230, 414
- microscope, microscopy
 - confocal 136, 141, 323
 - confocal scanning probe 131–133, 141
 - scanning capacitance (SCM) 443
 - scanning electron (SEM) 183, 220, 283, 299, 413, 420
 - scanning force (SFM) 5, 15, 58, 60, 73, 91, 119, 144, 220, 250, 276, 311, 444
 - scanning near-field optical (SNOM) 6–9, 424–427
 - scanning probe (SPM) 4, 15, 23, 43, 48, 109, 141, 150, 173, 206, 217, 221, 254, 415
- Monte Carlo calculation 162, 375–384, 385–401
- multilayer 283–284

N

- Nano Measuring Machine (NMM) 15, 73–75, 91
- nano roughness *see* standard
- nanobalance 22, 34–35
- nanohardness *see* hardness
- nanindentation 131, 135, 141, 467
- nanometrology 3, 27, 47, 205–206, 245, 254, 331
- near-field 6, 9, 424–428
- Newton-Raphson iteration 101
- Newton's algorithm 305
- Newton's rings 33, 332–342
- noise
 - level 77, 86, 88, 103, 106, 138, 148, 163, 175, 407, 427
 - acoustic 76
 - analysis 163, 169
 - electronic 127, 186, 332
 - measurement 163
 - quantum 332
 - random 103
 - signal 148, 179, 376
- non-contact mode 74, 91, 131, 135, 141, 312, 425, 454
- nonlinearity *see* interferometer or piezoelectric actuator
- numerical aperture (NA) 134–141, 323–324, 328–330

O

- operator
 - exponential fit 392, 394
 - Gauss fit 398
 - signal decay 398
- optical interferometer *see* interferometer

P

- piezo
- piezo electric cantilever *see* cantilever
- sensor *see* cantilever
- actuator (transducer) 30, 40, 51, 63–64, 77, 120, 122, 126, 220–229
- actuator, nonlinearity 221, 233
- actuator, hysteresis *see* hysteresis
- actuator, creep *see* creep
- pitch *see* calibration
- position measurement *see* measurement
- positioning range 15, 52
- positioning system 4–16, 63–65, 75, 140, 416
- power spectral density (PSD) 427, 431

- probe *see* tip
- probing system 3–4, 61, 131–132

Q

- quantitative measurement 23, 144, 154, 173, 177
- quantum dots, InAs *see* standard 9

R

- reconstruction of tip shape 297–310
- resonance frequency *see* frequency
- roughness *see* standard or measurement
- roughness standard *see* standard

S

- scanner 70, 74, 100, 104, 121, 141, 174–192, 220–228, 247, 269, 272, 362–363, 469–478
- scan range 85, 102, 126, 138, 179, 186, 270, 272
- scanner bow 179–180, 247
- scanning
 - capacitance microscopy (SCM) 443
 - electron microscopy (SEM) 183, 220, 283, 300, 413, 416, 420
 - force microscopy (SFM) 4–5, 15, 74, 104, 311
 - probe microscopy (SPM) 4, 15, 19, 22, 43, 48, 150, 173, 206, 207, 221, 245, 256
 - speed 31, 55–58, 116, 119–120, 128–130, 136, 372
- scan-on-the-fly 15
- sensor *see* capacitive transducer
- silicon facets 264–265
- spectral density 34, 426, 431
- sputtering 230, 237–239
- standard
 - flatness 16–17, 86, 179–180, 188, 246, 259–262
 - lateral 83–85, 180
 - mass 424–426, 431, 435, 438
 - nano roughness 254
 - roughness 87, 234, 254, 266, 269
 - step height 11, 58, 129, 189, 212–214, 324–325
 - thin film 254–256
 - tip characterizer 175, 248
- step height *see* measurement, calibration
- strain gauge 4, 7, 74, 158, 177, 245
- stray field 443–445
- strip pattern 282–294
- stylus instrument 88, 91, 167–169, 213–214, 259–268, 421–422, 427
- surface

- contamination 438
- roughness 23, 132, 231, 237–239, 270, 313, 416–423, 424–433, 452–454, 470–471
- texture 417, 422, 505
- topography 70, 119, 128, 141, 280, 414–423, 428, 444

T

- tapping mode 7, 361, 364–374
- thermal expansion 52, 179, 345, 348–356, 405, 501–503
- time of flight secondary mass spectrometer (TOF-SIMS) 284–285, 434, 436–442
- tip
 - characterization 175, 248
 - characterizer 248, 314, 367
 - apex 318, 428, 443–444
 - diameter 313–314
 - characterization 183, 257, 306, 315
 - material 9

- radius 249, 276, 305–309, 318, 366–372, 383, 423, 443–450, 468–479
- shape 23, 88, 182–183, 193, 202, 248, 297, 307, 311–320, 362–374, 443, 469, 475
- tolerances 35, 40, 230–240, 298, 313
- traceability 25, 29, 48, 73, 78, 95, 174, 177, 205–214, 251, 266, 324–328, 348
- tuning fork 8–9, 112–113, 131–143

V

- verification 158, 174–181, 246, 263, 435, 465

W

- wavefront 332
- Wiener-Khintchine theorem 163

Y

- Young's fringe 332–335, 341

