

CONTENTS

| | |
|---|-----------|
| 1. Introduction | 1 |
| 1.1 Background | 1 |
| 1.2 Electrical Transmission Networks | 1 |
| 1.3 Conventional Control Mechanisms | 3 |
| 1.3.1 Automatic Generation Control (AGC) | 3 |
| 1.3.2 Excitation Control | 4 |
| 1.3.3 Transformer Tap-Changer Control | 5 |
| 1.3.4 Phase-Shifting Transformers | 5 |
| 1.4 Flexible ac Transmission Systems (FACTS) | 6 |
| 1.4.1 Advances in Power-Electronics Switching Devices | 7 |
| 1.4.2 Principles and Applications of Semiconductor Switches | 8 |
| 1.5 Emerging Transmission Networks | 12 |
| References | 13 |
| 2. Reactive-Power Control in Electrical Power Transmission Systems | 16 |
| 2.1 Reactive Power | 16 |
| 2.2 Uncompensated Transmission Lines | 18 |
| 2.2.1 A Simple Case | 18 |
| 2.2.1.1 <i>Load Compensation</i> | 18 |
| 2.2.1.2 <i>System Compensation</i> | 19 |
| 2.2.2 Lossless Distributed Parameter Lines | 19 |
| 2.2.2.1 <i>Symmetrical Lines</i> | 21 |
| 2.2.2.2 <i>Midpoint Conditions of a Symmetrical Line</i> | 22 |
| 2.2.2.3 <i>Case Study</i> | 23 |
| 2.3 Passive Compensation | 33 |
| 2.3.1 Shunt Compensation | 34 |
| 2.3.2 Series Compensation | 34 |
| 2.3.3 Effect on Power-Transfer Capacity | 35 |
| 2.3.3.1 <i>Series Compensation</i> | 36 |
| 2.3.3.2 <i>Shunt Compensation</i> | 37 |

| | |
|--|-----------|
| 2.4 Summary | 39 |
| References | 39 |
| 3. Principles of Conventional Reactive-Power Compensators | 40 |
| 3.1 Introduction | 40 |
| 3.2 Synchronous Condensers | 41 |
| 3.2.1 Configuration | 41 |
| 3.2.2 Applications | 42 |
| 3.2.2.1 <i>Control of Large-Voltage Excursions</i> | 42 |
| 3.2.2.2 <i>Dynamic Reactive-Power Support at HVDC Terminals</i> | 42 |
| 3.3 The Saturated Reactor (SR) | 43 |
| 3.3.1 Configuration | 43 |
| 3.3.2 Operating Characteristics | 45 |
| 3.4 The Thyristor-Controlled Reactor (TCR) | 47 |
| 3.4.1 The Single-Phase TCR | 47 |
| 3.4.2 The 3-Phase TCR | 52 |
| 3.4.3 The Thyristor-Switched Reactor (TSR) | 56 |
| 3.4.4 The Segmented TCR | 56 |
| 3.4.5 The 12-Pulse TCR | 56 |
| 3.4.6 Operating Characteristics of a TCR | 59 |
| 3.4.6.1 <i>Operating Characteristics Without Voltage Control</i> | 59 |
| 3.4.6.2 <i>Operating Characteristic With Voltage Control</i> | 61 |
| 3.5 The Thyristor-Controlled Transformer (TCT) | 62 |
| 3.6 The Fixed Capacitor–Thyristor-Controlled Reactor (FC–TCR) | 63 |
| 3.6.1 Configuration | 63 |
| 3.6.2 Operating Characteristic | 64 |
| 3.6.2.1 <i>Without Step-Down Transformer</i> | 64 |
| 3.6.2.2 <i>With Step-Down Transformer</i> | 65 |
| 3.7 The Mechanically Switched Capacitor–Thyristor-Controlled Reactor (MSC–TCR) | 70 |
| 3.8 The Thyristor-Switched Capacitor (TSC) | 71 |
| 3.8.1 Switching a Capacitor to a Voltage Source | 71 |
| 3.8.2 Switching a Series Connection of a Capacitor and Reactor | 72 |
| 3.8.2.1 <i>The Term Involving Fundamental Frequency, ω_0</i> | 73 |

| | | |
|-----------|---|-----------|
| 3.8.2.2 | <i>The Terms Involving Natural Resonance Frequency, ω_n</i> | 74 |
| 3.8.2.3 | <i>Practical Switching Strategies</i> | 75 |
| 3.8.3 | Turning Off of the TSC Valve | 78 |
| 3.8.4 | The TSC Configuration | 78 |
| 3.8.5 | Operating Characteristic | 81 |
| 3.9 | The Thyristor-Switched Capacitor–Thyristor-Controlled Reactor (TSC–TCR) | 82 |
| 3.9.1 | Configuration | 82 |
| 3.9.2 | Operating Characteristic | 83 |
| 3.9.2.1 | <i>A Practical Example</i> | 83 |
| 3.9.3 | Current Characteristic | 84 |
| 3.9.4 | Susceptance Characteristic | 86 |
| 3.9.5 | Mismatched TSC–TCR | 87 |
| 3.10 | A Comparison of Different SVCs | 89 |
| 3.10.1 | Losses | 89 |
| 3.10.2 | Performance | 91 |
| 3.11 | Summary | 91 |
| | References | 91 |
| 4. | SVC Control Components and Models | 93 |
| 4.1 | Introduction | 93 |
| 4.2 | Measurement Systems | 93 |
| 4.2.1 | Voltage Measurement | 94 |
| 4.2.1.1 | <i>ac/dc Rectification</i> | 95 |
| 4.2.1.2 | <i>Coordinate Transformation</i> | 95 |
| 4.2.1.3 | <i>Fourier Analysis</i> | 96 |
| 4.2.1.4 | <i>Measurement of Squared Voltage</i> | 97 |
| 4.2.2 | The Demodulation Effect of the Voltage-Measurement System | 98 |
| 4.2.2.1 | <i>Addition</i> | 98 |
| 4.2.2.2 | <i>Modulation</i> | 101 |
| 4.2.2.3 | <i>Fourier Analysis–Based Measurement System</i> | 101 |
| 4.2.2.4 | <i>Coordinate Transformation–Based Measurement Systems</i> | 104 |
| 4.2.2.5 | <i>ac/dc Rectification–Based Measurement Systems</i> | 104 |
| 4.2.2.6 | <i>Filtering Requirements</i> | 104 |
| 4.2.3 | Current Measurement | 106 |
| 4.2.4 | Power Measurement | 109 |
| 4.2.5 | The Requirements of Measurement Systems | 110 |

| | | |
|-----------|---|------------|
| 4.2.5.1 | <i>Phasor Transducers</i> | 112 |
| 4.2.5.2 | <i>Optical Sensors</i> | 112 |
| 4.3 | The Voltage Regulator | 112 |
| 4.3.1 | The Basic Regulator | 112 |
| 4.3.2 | The Phase-Locked Oscillator (PLO) Voltage Regulator | 118 |
| 4.3.2.1 | <i>The Basic Single-Phase Oscillator</i> | 118 |
| 4.3.2.2 | <i>The 3-Phase Oscillator</i> | 120 |
| 4.3.3 | The Digital Implementation of the Voltage Regulator | 121 |
| 4.3.3.1 | <i>Digital Control</i> | 122 |
| 4.4 | Gate-Pulse Generation | 123 |
| 4.4.1 | The Linearizing Function | 124 |
| 4.4.2 | Delays in the Firing System | 125 |
| 4.4.2.1 | <i>Thyristor Deadtime</i> | 125 |
| 4.4.2.2 | <i>Thyristor Firing-Delay Time</i> | 126 |
| 4.5 | The Synchronizing System | 127 |
| 4.6 | Additional Control and Protection Functions | 128 |
| 4.6.1 | The Damping of Electromechanical Oscillations | 128 |
| 4.6.2 | The Susceptance (Reactive-Power) Regulator | 129 |
| 4.6.3 | The Control of Neighboring Var Devices | 131 |
| 4.6.4 | Undervoltage Strategies | 132 |
| 4.6.5 | The Secondary-Overvoltage Limiter | 132 |
| 4.6.6 | The TCR Overcurrent Limiter | 133 |
| 4.6.7 | TCR Balance Control | 133 |
| 4.6.8 | The Nonlinear Gain and the Gain Supervisor | 133 |
| 4.7 | Modeling of SVC for Power-System Studies | 134 |
| 4.7.1 | Modeling for Load-Flow Studies | 134 |
| 4.7.1.1 | <i>SVC Operation Within the Control Range</i> | 134 |
| 4.7.1.2 | <i>SVC Operation Outside the Control Range</i> | 135 |
| 4.7.2 | Modeling for Small- and Large-Disturbance Studies | 136 |
| 4.7.3 | Modeling for Subsynchronous Resonance (SSR) Studies | 137 |
| 4.7.4 | Modeling for Electromagnetic Transient Studies | 137 |
| 4.7.5 | Modeling for Harmonic-Performance Studies | 137 |
| 4.8 | Summary | 138 |
| | References | 138 |
| 5. | Concepts of SVC Voltage Control | 142 |
| 5.1 | Introduction | 142 |
| 5.2 | Voltage Control | 142 |
| 5.2.1 | <i>V-I Characteristics of the SVC</i> | 142 |

| | | |
|---------|---|-----|
| 5.2.1.1 | <i>Dynamic Characteristics</i> | 142 |
| 5.2.1.2 | <i>Steady-State Characteristic</i> | 145 |
| 5.2.2 | Voltage Control by the SVC | 145 |
| 5.2.3 | Advantages of the Slope in the SVC Dynamic Characteristic | 147 |
| 5.2.3.1 | <i>Reduction of the SVC Rating</i> | 147 |
| 5.2.3.2 | <i>Prevention of Frequency Operation at Reactive-Power Limits</i> | 148 |
| 5.2.3.3 | <i>Load Sharing Between Parallel-Connected SVCs</i> | 148 |
| 5.2.4 | Influence of the SVC on System Voltage | 149 |
| 5.2.4.1 | <i>Coupling Transformer Ignored</i> | 149 |
| 5.2.4.2 | <i>Coupling Transformer Considered</i> | 151 |
| 5.2.4.3 | <i>The System Gain</i> | 152 |
| 5.2.5 | Design of the SVC Voltage Regulator | 154 |
| 5.2.5.1 | <i>Simplistic Design Based on System Gain</i> | 155 |
| 5.2.5.2 | <i>Design That Considers Generator Dynamics</i> | 163 |
| 5.3 | Effect of Network Resonances on the Controller Response | 163 |
| 5.3.1 | Critical Power-System Parameters | 166 |
| 5.3.2 | Sensitivity to Power-System Parameters | 166 |
| 5.3.2.1 | <i>Response Variation With Regulator-Transient Gain, K_T</i> | 170 |
| 5.3.2.2 | <i>Response Variation With System Strength, $ESCR_0$</i> | 170 |
| 5.3.2.3 | <i>Voltage-Sensitivity Transfer Function</i> | 170 |
| 5.3.3 | Sensitivity to TCR Operating Point | 172 |
| 5.3.4 | Choice of Transient Gain | 175 |
| 5.3.5 | Certain Features of the SVC Response | 176 |
| 5.3.6 | Methods for Improving the Voltage-Controller Response | 177 |
| 5.3.6.1 | <i>Manual Gain Switching</i> | 177 |
| 5.3.6.2 | <i>The Nonlinear Gain</i> | 177 |
| 5.3.6.3 | <i>Bang-Bang Control</i> | 178 |
| 5.3.6.4 | <i>The Gain Supervisor</i> | 178 |
| 5.3.6.5 | <i>Series-Dynamic Compensation</i> | 180 |
| 5.3.6.6 | <i>ac-Side Control Filters</i> | 183 |
| 5.4 | The 2nd Harmonic Interaction Between the SVC and ac Network | 186 |
| 5.4.1 | Influence of the 2nd Harmonic Voltage on the TCR | 186 |
| 5.4.2 | Causes of 2nd Harmonic Distortion | 191 |
| 5.4.2.1 | <i>Fault Clearing</i> | 191 |

| | | |
|-----------|--|------------|
| 5.4.2.2 | <i>Reactor/Transformer Switching Near an SVC</i> | 193 |
| 5.4.2.3 | <i>Geomagnetically Induced Currents</i> | 195 |
| 5.4.2.4 | <i>Noise or Imbalance in the Control Systems</i> | 195 |
| 5.4.3 | TCR Balance Control | 195 |
| 5.5 | Application of the SVC to Series-Compensated ac Systems | 199 |
| 5.5.1 | ac System–Resonant Modes | 199 |
| 5.5.1.1 | <i>Shunt-Capacitance Resonance</i> | 199 |
| 5.5.1.2 | <i>Series-Line Resonance</i> | 201 |
| 5.5.1.3 | <i>Shunt-Reactor Resonance</i> | 201 |
| 5.5.2 | SVC Transient Response With Series-Compensated ac-Transmission Lines | 203 |
| 5.5.2.1 | <i>Reactor Switching</i> | 204 |
| 5.5.2.2 | <i>Fault Application and Clearing</i> | 207 |
| 5.5.3 | Effect of the Shunt-Reactor Mode on the SVC Voltage Controller | 209 |
| 5.5.3.1 | <i>Effect of the TCR Operating Point</i> | 211 |
| 5.5.3.2 | <i>Filtering of the Shunt-Resonant Mode</i> | 211 |
| 5.6 | 3rd Harmonic Distortion | 214 |
| 5.7 | Voltage-Controller Design Studies | 217 |
| 5.7.1 | Modeling Aspects | 217 |
| 5.7.2 | Special Performance-Evaluation Studies | 217 |
| 5.7.3 | Study Methodologies for Controller Design | 217 |
| 5.7.3.1 | <i>Impedance-Versus-Frequency Computation</i> | 217 |
| 5.7.3.2 | <i>Eigenvalue Analyses</i> | 218 |
| 5.7.3.3 | <i>Simulation Studies</i> | 218 |
| 5.8 | Summary | 218 |
| | References | 218 |
| 6. | SVC Applications | 221 |
| 6.1 | Introduction | 221 |
| 6.2 | Increase in Steady-State Power-Transfer Capacity | 221 |
| 6.3 | Enhancement of Transient Stability | 224 |
| 6.3.1 | Power-Angle Curves | 225 |
| 6.3.2 | Synchronizing Torque | 226 |
| 6.3.2.1 | <i>Uncompensated System</i> | 227 |
| 6.3.2.2 | <i>SVC-Compensated System</i> | 228 |
| 6.3.3 | Modulation of the SVC Bus Voltage | 229 |
| 6.4 | Augmentation of Power-System Damping | 232 |
| 6.4.1 | Principle of the SVC Auxiliary Control | 233 |

| | | |
|-------|--|-----|
| 6.4.2 | Torque Contributions of SVC Controllers | 235 |
| | 6.4.2.1 <i>Effect of the Power System</i> | 235 |
| | 6.4.2.2 <i>Effect of the SVC</i> | 236 |
| 6.4.3 | Design of an SVC PSDC | 239 |
| | 6.4.3.1 <i>Controllability</i> | 240 |
| | 6.4.3.2 <i>Influence of SVC Sites and the Nature of Loads</i> | 240 |
| | 6.4.3.3 <i>Selection Criteria for PSDC Input Signals</i> | 242 |
| | 6.4.3.4 <i>Input Filtering</i> | 243 |
| | 6.4.3.5 <i>General Characteristics of PSDC Input Signals</i> | 243 |
| | 6.4.3.6 <i>Performance of PSDC Input Signals</i> | 244 |
| | 6.4.3.7 <i>SVC PSDC Requirements</i> | 245 |
| | 6.4.3.8 <i>Design Procedure for a PSDC</i> | 248 |
| | 6.4.3.9 <i>Case Study</i> | 249 |
| 6.4.4 | Composite Signals for Damping Control | 252 |
| | 6.4.4.1 <i>Frequency of Remotely Synthesized Voltage</i> | 252 |
| | 6.4.4.2 <i>Case Study</i> | 254 |
| 6.4.5 | Alternative Techniques for the Design of SVC Auxiliary Controllers | 256 |
| 6.5 | SVC Mitigation of Subsynchronous Resonance (SSR) | 257 |
| | 6.5.1 Principle of SVC Control | 257 |
| | 6.5.2 Configuration and Design of the SVC Controller | 260 |
| | 6.5.3 Rating of an SVC | 262 |
| 6.6 | Prevention of Voltage Instability | 263 |
| | 6.6.1 Principles of SVC Control | 263 |
| | 6.6.1.1 <i>A Case Study</i> | 263 |
| | 6.6.2 Configuration and Design of the SVC Controller | 265 |
| | 6.6.3 Rating of an SVC | 266 |
| 6.7 | Improvement of HVDC Link Performance | 268 |
| | 6.7.1 Principles and Applications of SVC Control | 269 |
| | 6.7.1.1 <i>Voltage Regulation</i> | 269 |
| | 6.7.1.2 <i>Suppression of Temporary Overvoltages</i> | 269 |
| | 6.7.1.3 <i>Support During Recovery From Large Disturbances</i> | 269 |
| | 6.7.2 Configuration and Design of the SVC Controller | 271 |
| | 6.7.2.1 <i>Interactions Between the SVC and the HVDC</i> | 272 |
| | 6.7.3 Rating of the SVC | 272 |

| | |
|--|------------|
| 6.8 Summary | 272 |
| References | 272 |
| 7. The Thyristor-Controlled Series Capacitor (TCSC) | 277 |
| 7.1 Series Compensation | 277 |
| 7.1.1 Fixed-Series Compensation | 277 |
| 7.1.2 The Need for Variable-Series Compensation | 277 |
| 7.1.3 Advantages of the TCSC | 278 |
| 7.2 The TCSC Controller | 279 |
| 7.3 Operation of the TCSC | 280 |
| 7.3.1 Basic Principle | 280 |
| 7.3.2 Modes of TCSC Operation | 281 |
| 7.3.2.1 <i>Bypassed-Thyristor Mode</i> | 282 |
| 7.3.2.2 <i>Blocked-Thyristor Mode</i> | 283 |
| 7.3.2.3 <i>Partially Conducting Thyristor, or Vernier, Mode</i> | 283 |
| 7.4 The TSSC | 284 |
| 7.5 Analysis of the TCSC | 285 |
| 7.6 Capability Characteristics | 290 |
| 7.6.1 The Single-Module TCSC | 292 |
| 7.6.2 The Multimodule TCSC | 294 |
| 7.7 Harmonic Performance | 295 |
| 7.8 Losses | 298 |
| 7.9 Response of the TCSC | 301 |
| 7.10 Modeling of the TCSC | 304 |
| 7.10.1 Variable-Reactance Model | 304 |
| 7.10.1.1 <i>Transient-Stability Model</i> | 305 |
| 7.10.1.2 <i>Long-Term-Stability Model</i> | 308 |
| 7.10.2 An Advanced Transient-Stability Studies Model | 309 |
| 7.10.2.1 <i>TCSC Controller Optimization and TCSC Response-Time Compensation</i> | 310 |
| 7.10.3 Discrete and Phasor Models | 311 |
| 7.10.4 Modeling for Subsynchronous Resonance (SSR) Studies | 311 |
| 7.11 Summary | 312 |
| References | 313 |
| 8. TCSC Applications | 315 |
| 8.1 Introduction | 315 |
| 8.2 Open-Loop Control | 315 |
| 8.3 Closed-Loop Control | 316 |

| | | |
|-----------|---|------------|
| 8.3.1 | Constant-Current (CC) Control | 316 |
| 8.3.2 | Constant-Angle (CA) Control | 317 |
| 8.3.3 | Enhanced Current Control | 319 |
| 8.3.4 | Constant-Power Control | 319 |
| 8.3.5 | Enhanced Power Control | 320 |
| 8.3.6 | Firing Schemes and Synchronization | 321 |
| 8.4 | Improvement of the System-Stability Limit | 321 |
| 8.5 | Enhancement of System Damping | 322 |
| 8.5.1 | Principle of Damping | 323 |
| 8.5.2 | Bang-Bang Control | 325 |
| 8.5.3 | Auxiliary Signals for TCSC Modulation | 325 |
| 8.5.3.1 | <i>Local Signals</i> | 325 |
| 8.5.3.2 | <i>Remote Signals</i> | 325 |
| 8.5.4 | Case Study for Multimodal Decomposition–Based PSDC Design | 326 |
| 8.5.4.1 | <i>Selection of the Measurement Signal</i> | 326 |
| 8.5.4.2 | <i>Selection of the Synthesizing Impedance</i> | 327 |
| 8.5.5 | H_∞ Method–Based PSDC Design | 330 |
| 8.5.6 | Alternative Techniques for PSDC Design | 334 |
| 8.5.7 | Placement of the TCSC | 334 |
| 8.6 | Subsynchronous Resonance (SSR) Mitigation | 334 |
| 8.6.1 | TCSC Impedance at Subsynchronous Frequencies | 335 |
| 8.6.2 | A Case Study | 340 |
| 8.6.2.1 | <i>Transient-Torque Minimization</i> | 342 |
| 8.6.2.2 | <i>Criteria for SSR Mitigation by the TCSC</i> | 342 |
| 8.7 | Voltage-Collapse Prevention | 343 |
| 8.8 | TCSC Installations | 345 |
| 8.8.1 | Imperatriz–Serra da Mesa TCSCs in Brazil | 346 |
| 8.8.1.1 | <i>TCSC Power-Oscillation Damping (POD) Control</i> | 348 |
| 8.8.1.2 | <i>Phasor Estimation</i> | 350 |
| 8.8.1.3 | <i>Performance of Both TCSCs</i> | 352 |
| 8.8.2 | Stode TCSC in Sweden | 353 |
| 8.9 | Summary | 355 |
| | References | 355 |
| 9. | Coordination of FACTS Controllers | 359 |
| 9.1 | Introduction | 359 |
| 9.2 | Controller Interactions | 359 |
| 9.2.1 | Steady-State Interactions | 360 |
| 9.2.2 | Electromechanical-Oscillation Interactions | 360 |
| 9.2.3 | Control or Small-Signal Oscillations | 361 |

| | | |
|---------|--|-----|
| 9.2.4 | Subsynchronous Resonance (SSR) Interactions | 361 |
| 9.2.5 | High-Frequency Interactions | 361 |
| 9.2.6 | The Frequency Response of FACTS Controllers | 362 |
| 9.2.6.1 | <i>The Frequency Response of the SVC</i> | 362 |
| 9.2.6.2 | <i>The Frequency Response of the TCSC</i> | 364 |
| 9.3 | SVC–SVC Interaction | 364 |
| 9.3.1 | The Effect of Electrical Coupling and Short-Circuit Levels | 364 |
| 9.3.1.1 | <i>Uncoupled SVC Buses</i> | 364 |
| 9.3.1.2 | <i>Coupled SVC Buses</i> | 365 |
| 9.3.2 | The System Without Series Compensation | 366 |
| 9.3.3 | The System With Series Compensation | 371 |
| 9.3.3.1 | <i>Shunt-Reactor Resonance</i> | 373 |
| 9.3.4 | High-Frequency Interactions | 374 |
| 9.3.5 | Additional Coordination Features | 379 |
| 9.3.5.1 | <i>Parallel SVCs</i> | 379 |
| 9.3.5.2 | <i>Electrically Close SVCs</i> | 380 |
| 9.4 | SVC–HVDC Interaction | 381 |
| 9.5 | SVC–TCSC Interaction | 382 |
| 9.5.1 | Input Signal of the TCSC–PSDC With Bus Voltage | 384 |
| 9.5.2 | Input Signal of the TCSC–PSDC With a System Angle | 387 |
| 9.5.3 | High-Frequency Interactions | 387 |
| 9.6 | TCSC–TCSC Interaction | 393 |
| 9.6.1 | The Effect of Loop Impedance | 393 |
| 9.6.1.1 | <i>Low-Loop Impedance</i> | 393 |
| 9.6.1.2 | <i>High-Loop Impedance</i> | 394 |
| 9.6.2 | High-Frequency Interaction | 394 |
| 9.7 | Performance Criteria for Damping-Controller Design | 399 |
| 9.8 | Coordination of Multiple Controllers Using Linear-Control Techniques | 401 |
| 9.8.1 | The Basic Procedure for Controller Design | 401 |
| 9.8.1.1 | <i>Derivation of the System Model</i> | 401 |
| 9.8.1.2 | <i>Enumeration of the System Performance Specifications</i> | 402 |
| 9.8.1.3 | <i>Selection of the Measurement and Control Signals</i> | 402 |
| 9.8.1.4 | <i>Controller Design and Coordination</i> | 402 |
| 9.8.1.5 | <i>Validation of the Design and Performance Evaluation</i> | 403 |
| 9.8.2 | Controller Coordination for Damping Enhancement | 403 |

| | | |
|------------|--|------------|
| 9.8.3 | Linear Quadratic Regulator (LQR)–Based Technique | 405 |
| 9.8.4 | Constrained Optimization | 405 |
| | 9.8.4.1 <i>Techniques Without Explicit Robustness Criteria</i> | 405 |
| | 9.8.4.2 <i>Techniques With Explicit Robustness Criteria</i> | 405 |
| 9.8.5 | Nonlinear-Constrained Optimization of a Selective- Model-Performance Index | 405 |
| 9.8.6 | Global Coordination Using Nonlinear-Constrained Optimization | 407 |
| 9.8.7 | Control Coordination Using Genetic Algorithms | 408 |
| 9.9 | Coordination of Multiple Controllers Using Nonlinear- Control Techniques | 409 |
| 9.10 | Summary | 409 |
| | References | 410 |
| 10. | Emerging FACTS Controllers | 413 |
| 10.1 | Introduction | 413 |
| 10.2 | The STATCOM | 413 |
| | 10.2.1 The Principle of Operation | 415 |
| | 10.2.2 The <i>V-I</i> Characteristic | 417 |
| | 10.2.3 Harmonic Performance | 419 |
| | 10.2.4 Steady-State Model | 421 |
| | 10.2.5 SSR Mitigation | 425 |
| | 10.2.5.1 <i>A Study System</i> | 425 |
| | 10.2.5.2 <i>STATCOM Performance</i> | 426 |
| | 10.2.6 Dynamic Compensation | 428 |
| | 10.2.6.1 <i>A Multilevel VSC–Based STATCOM</i> | 428 |
| | 10.2.6.2 <i>A Selective Harmonic-Elimination Modulation (SHEM) Technique</i> | 431 |
| | 10.2.6.3 <i>Capacitor-Voltage Control</i> | 431 |
| | 10.2.6.4 <i>STATCOM Performance</i> | 433 |
| 10.3 | The SSSC | 437 |
| | 10.3.1 The Principle of Operation | 437 |
| | 10.3.2 The Control System | 440 |
| | 10.3.3 Applications | 442 |
| | 10.3.3.1 <i>Power-Flow Control</i> | 442 |
| | 10.3.3.2 <i>SSR Mitigation</i> | 443 |
| 10.4 | The UPFC | 444 |
| | 10.4.1 The Principle of Operation | 444 |
| | 10.4.2 Applications | 448 |

| | |
|--|------------|
| 10.5 Comparative Evaluation of Different FACTS Controllers | 449 |
| 10.5.1 Performance Comparison | 450 |
| 10.5.2 Cost Comparison | 452 |
| 10.6 Future Direction of FACTS Technology | 453 |
| 10.6.1 The Role of Communications | 455 |
| 10.6.2 Control-Design Issues | 455 |
| 10.7 Summary | 456 |
| References | 457 |
| | |
| Appendix A. Design of an SVC Voltage Regulator | 462 |
| A.1 Study System | 462 |
| A.2 Method of System Gain | 464 |
| A.3 Eigenvalue Analysis | 465 |
| A.3.1 Step Response | 466 |
| A.3.2 Power-Transfer Studies | 471 |
| A.4 Simulator Studies | 472 |
| A.4.1 Step-Response Studies | 472 |
| A.4.2 Power-Transfer Limits | 474 |
| A.5 A Comparison of Physical Simulator Results With Analytical and Digital Simulator Results Using Linearized Models | 475 |
| References | 477 |
| | |
| Appendix B. Transient-Stability Enhancement in a Midpoint SVC-Compensated SMIB System | 478 |
| | |
| Appendix C. Approximate Multimodal Decomposition Method for the Design of FACTS Controllers | 481 |
| C.1 Introduction | 481 |
| C.2 Modal Analysis of the i th Swing Mode, λ_i | 483 |
| C.2.1 Effect of the Damping Controller | 485 |
| C.3 Implications of Different Transfer Functions | 486 |
| C.3.1 Controllability | 486 |
| C.3.2 Observability | 486 |
| C.3.3 The Inner Loop | 486 |
| C.4 Design of the Damping Controller | 486 |
| C.4.1 The Controller-Phase Index (CPI) | 487 |
| C.4.2 The Maximum Damping Influence (MDI) Index | 487 |
| C.4.3 The Natural Phase Influence (NPI) Index | 488 |
| References | 489 |

| | |
|--|------------|
| Appendix D. FACTS Terms and Definitions | 490 |
| D.1 Definitions of Basic Terms | 490 |
| D.2 Definitions of Facts Controller Terms | 490 |
| Reference | 492 |
| Index | 493 |