

Index

- 3GPP 24.008, 141–44
 3GPP 24.022, 139
 3GPP 25.211, 74
 3GPP 25.215, 332
 3GPP 25.302, 74
 3GPP 25.321, 95
 3GPP 25.322, 98
 3GPP 25.323, 140
 3GPP 25.324, 141
 3GPP 25.331, 113
 3GPP 25.413, 128
 3GPP 25.415, 134
 3GPP 25.423, 126
 3GPP 25.427, 93
 3GPP 25.433, 124
 3GPP 25.855, 9
 3GPP 26.111, 143
 3GPP 27.001, 138
 3GPP 27.002, 138
 3GPP 27.003, 138
 3GPP 33.102, 46, 122
 3GPP, 10, 27, 38, 41, 43, 45, 54, 150, 159,
 167, 171, 172, 187, 281, 283, 310, 311,
 312, 315, 320, 326, 412, 420, 421, 439,
 472, 482, 501, 502
 AAL, 82, 90f, 91
 AAL2, 7, 8, 59, 62f, 81–86, 92, 131–33, 172,
 173, 182, 187, 188, 196, 200, 203, 209,
 214, 220, 222, 226, 227, 231, 236, 238,
 258, 266, 271, 279, 375, 410, 411, 417,
 418, 439f, 458f
 AAL2L3, 83, 92, 109, 131–33, 182–83,
 187
 AAL5, 92
 ABM, 139
 ABR, 91
 Absolute Radio Frequency Code Number,
 492
 Abstract Syntax Notation One, 111
 AC, 32
 Access network, 13
 Access Service Class, 95, 121
 Access Stratum, 2, 31, 33, 192
 ACCH, 75
 Acknowledged Data Transfer Mode,
 99
 Acknowledged Data Transfer, 99
 Acknowledged Mode, 101, 199
 Acquisition Indication Channel, 188
 Activate PDP Context, 145, 396
 Activate Secondary PDP Context, 397
 Adaptive Multi-Rate Codec, 85
 ADM, 139
 Admission Control, 32, 190
 Advanced Intelligent Network. *See* AIN
 AICH, 74, 188, 184, 332
 AIN, 471, 511
 ALCAP, 59, 62f, 82–86, 90, 92, 97f, 131,
 149, 150, 172f, 179f, 182, 183, 185,
 187–88, 192f, 195–96, 214, 265, 287,
 292, 293, 295, 305, 308, 310, 328, 330,
 346, 348, 354, 361, 375, 402, 434, 450

- ALERT, 216, 223f, 277f, 376, 382, 461
Allocation/retention priority, 40
AM, 60, 98, 101, 211, 270
AMD PDU, 103
AMR IF1, 138
AMR IF2, 123
AMR Speech Codec, 137
AMR, 10, 76f, 84, 85, 134–38, 214
APCR, 228–30, 265, 389f, 390
APDU, 482–87, 494–95, 498–500
Application data, 102
Application Transport Mechanism, 460
ARFCN, 300, 409, 492, 498, 504, 508
ARIB, 2
ARQ, 100
AS. *See* Access Stratum
ASC, 95
ASN.1, 111, 308, 502
Associated Control Channel, 75
Association of Radio Industries and Businesses, 2
Asynchronous Balanced Mode, 139
Asynchronous Disconnected Mode, 139
ATAC, 205, 264, 384–87
ATM Adaptation Layer Type 2 – Layer 3, 131
ATM Adaption Layer. *See* AAL
ATM, 70, 76–9, 117, 119
ATRJ, 384
ATRQ, 204, 261, 264
Attach Accept, 191f, 204, 384
Attach Reject, 157, 158
Attach Request, 191f, 264
Attach, 169, 239
AuC, 47, 53, 471
Authentication Center. *See* AuC
Authentication, 47
AUTREP, 197, 200, 209–10, 221, 275–76, 365, 368, 373, 380–81, 442, 450, 459
AUTREQ, 187, 200, 209, 210f, 221, 227f, 228, 275, 365f, 368, 373, 380–81, 442, 449, 450f, 459f
Available Bit Rate Service, 91
Background class, 41
Backward Handover, 427f
Base Station Color Code, 495
Base Station Controller, 5
Base Station Identity Code, 300
Basic Call State Model. *See* BCSM
Basic Encoding Rules, 111
BCC, 410, 495
BCCH, 79, 120, 498f
BCH, (Duplicacy)
BCH, 73–79, 95, 117, 250
BCSM, 511, 512
Bearer Independent Call Control. *See* BICC
Bearer, 39–40, 46, 15, 60, 61, 84, 109, 114
Begin Ack, 115
Begin, 115
BG, 86
BGAK, 115
BGN, 115
BICC, 453–54, 458–61, 483–87, 495
Billing System, 468
BLER, 78, 249, 348
BMC Functions, 141
BMC, 84, 141, 142f
Border Gateway, 86
Broadcast/Multicast Control, 141
Broadcast/Multicast Protocol, 84
Broadcast Channel, 74, 75, 95
BS. *See* Billing System
BSC, 5, 44, 462f, 486–94, 498, 501, 506
BSIC, 300
BSS, 4–6
BSSAP, 75, 95, 87, 469–71, 488f
BSSMAP, 487–95
C/T field, 97
Call Admission Control, 33
Call Control, 83, 211
CAMEL Service Entity, 510
CAMEL, 9, 11, 399–406
CAP, 22f, 510, 514
CBC, 141
CBM, 141
CBR, 91
CBS, 101, 141
CC Functions, 143

- CC, 110, 142
- CCCH, 121, 127
- CCONF, 221, 381f
- CCPCH, 73, 76, 77, 122, 175, 184, 351
- CCS#7, 184, 351
- CCTrCh, 75, 343, 344
- CDMA, 1, 4, 33, 65, 66
- CDMA2000, 4
- Cell breathing, 70–71f, 283, 413
- Cell Broadcast Center, 141
- Cell Broadcast Messages, 117, 141
- Cell Broadcast Service, 101
- Cell categories, 239
- Cell Configuration Management, 30, 125
- Cell ID, 173, 175, 483, 500
- cell loss priority, 90
- Cell Radio Network Temporary Identity, 97
- Cell Reselection, 62, 115, 257, 412, 413, 508
- CELL UPDATE, 122
- CELL_DCH, 104–105, 251f, 260f, 265f
- CELL_FACH, 104–105, 250, 256, 260–61
- CELL_PCH, 134f, 135f
- Cell-ID, (Duplicacy)
- CellSetup, 175, 176, 177
- CGF, 464, 468
- Channel type switching, 259–61, 268, 309, 322, 329
- Channelization, 66, 70t
- CHAP, 229, 396
- Charging Gateway Function. *See* CGF
- Charging Gateway, 87
- Charging ID. *See* C-ID
- Charging information, 467–469, 513
- Charging, 87, 463, 464, 512–16
- China Wireless Telecommunication Standard, 2
- CID, 92, 132, 133, 149–51, 172–73, 179, 183–85, 192, 196, 203, 207, 209, 211, 212, 215f, 226f, 232f, 237, 241, 246, 251, 254, 270, 274, 277, 279f, 304, 305, 308, 310, 326, 375, 443, 444, 447–51, 488, 494
- C-ID, 175–77, 179–80, 185, 188, 193, 265, 270, 287–91, 335–37, 352, 353, 430f, 468, 469
- Ciphering, 33, 42f, 48, 59, 60f, 62, 228
- closed loop power control, 80f
- CMSREJ, 209
- CMSREQ, 209, 210f, 275, 287f, 372, 441, 448, 459, 356
- Code Allocation, 33
- Common Channel Signaling System #7. *See* CCS#7
- Common Control Physical Channel. *See* CCPCH
- Common Packet Channel, 96
- Common Part Sublayer, 92
- Common Physical Channel ID, 175
- Common Physical Channel, 160, 173f, 175
- Common Pilot Channel, 73, 77
- Common Transport Channel ID, 175, 179
- Common Transport Channel, 74, 75, 125t, 127, 149, 173, 181, 187
- CONACK, 215f, 216, 277, 287f, 376f, 382f, 461f
- Concatenation, 100
- Congestion Control, 33
- Connected Mode States, 115
- Connection Confirm, 110
- Connection Control, 105
- Connection Frame Number, 94, 121
- Connection Refused, 110
- Connection Request, 110, 366
- CONNECTION SETUP, 57, 225–26
- Constant Bit Rate Service, 91
- Control plane, 16, 72, 81
- Convergence Sublayer, 91
- Conversational class, 40
- Core network, 2, 6f, 7f
- CPCH, 73, 116
- CPCS, 91, 93f
- CPICH, 73, 77, 175, 240–45, 277, 288, 298, 413
- CPROC, 210, 212, 276, 374, 459
- CPS, 92
- CR, 110
- CRC, 90
- CREF, 110
- CRNC Communication Context Identifier, 125
- CRNC Communication Context, 125, 278, 288, 333, 344, 411

- CRNC, 34, 125, 193, 239, 265, 278, 293, 305, 334, 337, 405
- C-RNTI, 97
- CS domain, 4, 85
- CTCH, 96, 102f, 117, 141, 180, 182, 186, 189
- Customized Application for Mobile Network Enhanced Logic, 509–16
- CWTS, 2
- Data Form, 368
- DCCH, 76f, 95–98, 102–03, 115–17, 121–24, 151, 172, 191f–93, 197, 199, 202, 203, 205–07, 209, 211–12, 215, 217–19, 222, 224–26, 229, 235–41, 246, 247, 250, 251, 255–61, 264–66, 268, 271, 273, 274, 278–80, 283–84, 287–88, 292, 293, 310, 343, 350–51, 356, 359, 363–64, 370–72, 379, 384–85, 387, 398–99, 401–03, 410, 412–15, 419 436, 440, 446
- DCH, 72, 75, 115, 149
- Deactivate PDP context, 234
- Dedicated Physical Channel, 72–74
- Dedicated Physical Control Channel, 72, 73
- Dedicated Physical Data Channel, 73
- Dedicated traffic channel. *See* DTCH
- Dedicated Transport Channel, 75, 96
- Delivery of erroneous SDUs, 40, 136
- Destination Point Code. *See* DPC
- DL NODE SYNCHRONIZATION, 94
- DLR, 368
- DMTAP, 485
- Downlink direct transfer, 124
- Downlink Shared Channel, 74, 75
- DPC, 107f, 110
- DPCA, 234, 392f
- DPCCH, 72
- DPCH, 70f, 73, 122, 193
- DPCR, 234f, 391
- DPDCH, 70, 73
- Drift RNC. *See* DRNC
- DRNC, 34, 97, 401f
- DSAID, 132
- DSCH Radio Network Temporary Identity, 97
- DSCH TFCI SIGNALING, 94
- DSCH, 74, 75, 96, 116, 127
- DSCH-RNTI, 96f
- DT1, 110
- DTAP, 487–90, 492f, 498–501
- DTCH, 76f, 95–98, 102–03, 106, 107, 172, 206, 210f, 212, 214–15, 217–19, 223–25, 228, 231–32, 234, 250, 253–61, 265–66, 268, 270, 271, 273, 277–79, 309, 310, 320, 348, 359, 371–72, 374, 376, 379, 387–88, 401–03, 405, 406, 410, 412, 413, 415, 417, 419, 426f, 435f, 436f, 494f
- DTMF, 511
- Duplex methods, 64
- E.164, 9, 132, 406, 409, 414, 443, 460, 469–71, 473, 476f, 477, 495, 498
- E.212, 415, 476, 482
- Eb/N0, 32, 69, 71
- EDGE, 1, 4, 25
- EIR, 4, 471, 472f
- Encryption, 45, 58, 424, 430, 435f
- End-to-End, 40
- Enhanced data rates for GSM, 1
- Error correction by selective retransmission, 104
- Error reporting to layer management, 105
- Error-free delivery, 99
- ETSI, 2
- European Telecommunications Standards Institute, 2
- FACH, 73–77, 95–98, 114–18, 120–23, 149–50, 172–73, 184–88, 192, 196, 197, 200, 203–04, 207, 209, 219, 220, 227, 238, 241f, 251, 258–66, 271, 275, 291, 293, 302–04, 320, 324, 340, 346, 413, 419
- Fake BTS, 41
- Fast power control, 74, 79
- FCS, 140
- FDD, 27, 35, 64, 73f, 116, 164
- FDMA, 64
- Flags, 108
- Flow control, 100, 107, 506
- Forward Access Channel, 94, 95, 320
- Forward Handover, 412
- FP. *See* Framing Protocol

- Fragment offset, 108
- Frame check sequence, 140
- Frame number, 134, 136, 175
- Frame quality classification, 136
- Frame quality indicator, 138
- Framing protocol, 82, 93, 184
- Frequency division duplex, 64
- frequency division multiple access, 27, 65f, 341
- Frequency Hopping, 66
- Gateway GPRS Support Node – Call Detail Record, 468
- Gateway GPRS Support Node, 3
- Gateway MSC, 5
- G-CDR, 468
- GERAN, 7, 462, 506
- GGSN, 3, 5, 11, 21, 86, 144, 260, 463, 465, 468
- Global System for Mobile Communication, 1
- Global Title Translation, 110
- GMM Functions, 144
- GMM, 144–45
- GMSC, 5, 438, 460
- Gn, 87, 304
- GPRS Attach procedure, 181, 206, 225
- GPRS Detach, 235–38, 399, 470
- GPRS Mobility Management, 144
- GPRS Support Node. *See* GSN
- GPRS Tunneling Protocol user, 87
- GPRS Tunneling Protocol, 87, 387, 462
- GPRS Tunneling Protocol. *See* GTP
- GPRS, 1, 3, 25, 87, 144, 157, 202, 235, 513
- GSN, 462
- GT, 109
- GTP, 468
- GTP, 87, 134, 225, 304, 387, 388, 391, 426, 462–65, 468, 508
- GTP-C, 87, 462–65
- GTP-U, 87, 134, 462–64
- GTT, 10, 110
- Guaranteed bitrate, 39
- Handover Command, 489, 490, 492, 495, 499, 501
- Handover Detect, 489, 493, 495
- Handover, 33, 114f, 163f, 273, 481, 488–90, 493, 501, 505
- Hard handover, 240, 291, 292, 312, 480, 506
- HE, 9, 45, 53
- High Speed Uplink Packet Access, 12, 323
- HLR, 4, 23, 51, 157, 231, 465, 470–77
- HODET, 492, 493, 499
- Home Environment, 47
- Home Location Register, 5
- HSDPA, 1, 12, 16, 291, 301–12, 318, 320–25, 333
- HSDSCH, 307, 309, 311, 315, 323, 333
- HSS, 6, 9, 519
- HSUPA, 12, 17–19, 155, 320, 323–30, 332–33
- HTTP, 259
- Hybrid Modulation, 66
- HyperText Transfer Protocol. *See* HTTP
- Immediate Delivery, 86
- IMS, 9–11, 21, 24, 26, 517–18
- IMSI Attach, 191, 192, 197f, 201f, 202f, 469f
- IMSI, 21, 45, 48, 113, 121, 128f, 142, 144, 157, 158, 191–93, 196–97, 199–204, 206–07, 209, 219–20, 225–27, 235–38, 273–75, 287, 320, 333, 364–65, 367, 369, 372–73, 379–81, 385–86, 388f, 390, 398–91, 403, 414f, 416, 423, 441–43, 447–50, 459f, 465–66, 469–71, 475–77, 482, 488, 489, 491, 494, 495, 502
- IMT-2000, 3, 36
- INAP, 510–11
- Initial Direct Transfer, 227, 264, 369
- Initiating Message, 174f, 193, 292, 335, 502
- Inner loop power control, 78, 334
- In-sequence delivery, 99–102
- Intelligent Network Application Part. *See* INAP
- Inter PDU Timing Interval, 136
- Interactive class, 40
- Inter-Cell InterFrequency Handover, 353–55
- Interference Signal Code Power, 344
- International Mobile Subscriber Identity. *See* IMSI

- International Telecommunication Union, 2
- Internet Protocol, 84, 107
- Inter-Node B Handover, 315, 356, 357f, 359–361
- Intersystem handover, 87, 427
- InterWorking Function, 24, 85
- Intra-Cell Inter-Frequency Handover, 341, 352, 353f, 361
- IP Multimedia Subsystem, 9, 10, 26, 517
- IP version 4, 107, 466
- IP-based packet protocols, 84
- IPTI, 136
- IPv4, 107, 466
- ISCP, 332, 344
- ISDN User Part, 87
- ISDN, 5
- ISO/IEC 8824–1, 111
- ISO/IEC 8825, 111
- ISO/IEC 8825–1, 111
- ISUP, 21, 85–87, 107f, 453–58, 460, 473, 480f, 483–88, 492, 511
- ITU-T I.363.2, 102
- ITU-T I.363.5, 102
- ITU-T Q.2110, 104
- ITU-T Q.2140, 106
- ITU-T Q.2150, 108
- ITU-T Q.2630, 131
- ITU-T Q.711–716, 119
- Iu UP protocol, 134, 138
- Iu UP Support Mode Control Frames, 136
- Iu UP support mode data frames, 135f
- Iu UP transparent mode, 135f
- Iu User Plane Protocol, 134
- Iub, 8, 28f–30, 32, 34, 59, 61–63, 82–84, 93, 150–53, 170–73, 191–193, 202–07, 221–28, 250–51, 273–81, 286–90, 292–93, 304–05, 307–10, 318–19, 330, 339, 359, 363–65, 370–89, 398, 401–03, 405–06, 411–21, 436, 440, 443–46, 451, 478–482, 501–04
- IuCS, 29, 153, 363
- IuPS, 29, 86, 153, 384
- Iur, 29, 84, 109, 155
- IWF, 139, 144
- Java, 10
- Keep Alive, 105
- Keystream block, 61f, 62
- KPI, 9, 156–158, 396
- L2R, 139
- LA, 36
- LAPD, 139, 502
- Link Access Procedures on the D-channel, 139
- Local Data Retrieval, 105
- Location Area, 35, 36, 414
- Location Management, 465
- Location Update, 142, 158f, 191–93, 200, 202, 209, 363–65, 369–71, 373, 469
- Logical channel, 83, 95f, 102f
- LUACC, 200, 201, 369
- LUREJ, 201, 364f
- LUREQ, 154, 200, 363–67, 369
- M3UA, 84, 454
- MAC Control SAP, 96
- MAC Data PDU, 96
- MAC Header, 98
- MAC Logical Link Priority, 95
- MAC, 13, 18, 56, 95
- MAC-b, 95
- MAC-c/sh, 95
- MAC-d, 96
- Macrodiversity, 68, 281, 283
- MAP, 86, 111, 157, 438, 465, 471–78, 480–87, 490, 512
- Mapping of Transport Channels onto physical channels, 75
- Master Information Block. *See* MIB
- Maximum bitrate, 39
- MCC, 36, 199, 367, 370, 469, 476, 482
- M-CDR, 468
- Media Gateway, 8, 10, 152
- Medium Access Control, 83
- Medium Access Protocol, 95
- Message Transfer Part Level 3-broadband (MTP3-B), 85, 106
- MGW, 8
- MIB, 118, 120, 177, 178
- Microdiversity, 35, 67
- MLP, 95

- MM Functions, 142
- MM, 83
- MNC, 23, 36, 367, 370, 469, 476, 482
- Mobile Application Part. *See* MAP
- Mobile Country Code. *See* MCC
- Mobile Network Code. *See* MNC
- Mobile Originated Call. *See* MOC
- Mobile Station Roaming Number, 455
- Mobile Station. *See* MS
- Mobile Switching Center. *See* MSC
- Mobile Terminated Call. *See* MTC
- Mobile Termination, 24, 25
- Mobility Management–Call Detail Record, 468
- Mobility Management, 35, 59, 83, 112, 141, 144, 157, 310, 363, 367, 370, 465, 468
- MOC, 206, 207, 210, 211f, 215f, 217–220, 223, 225–26, 231, 234, 272–79, 285, 287, 371–74, 376–79, 381–83, 423, 431, 459, 461, 493
- Modulation, 65
- MS Classmark, 39, 221
- MS Radio Access Capability, 39
- MS, 178, 197, 199, 205f, 214, 250, 254, 257, 274f, 277, 283f, 291, 296f, 300, 308, 310, 311f, 319, 335–41, 344, 348, 363f, 367, 370, 386, 394, 398, 404f
- MSC Handover, 477, 480–500, 502
- MSC Server, 8
- MSC, 5, 8, 20, 85, 139, 154, 363–65, 368, 371–75, 399, 402, 428–29, 435–42, 446, 453–54, 460, 477–86, 489–95, 510–11
- MSISDN, 221, 381, 438, 450, 455, 464, 476, 477, 514
- MSRN, 455, 483
- MT, 36, 38, 85, 139, 446–52
- MTC, 217, 219–25, 234, 378–84, 402, 493
- MTP, 153, 472–3, 488
- MTP3–B, 83–6, 106–8, 454
- Multi Radio Mode, 38f
- Multipath, 67
- Multiple Access Method, 64
- Multiradio Mode, 38
- Multi-Service Call, 327, 356–7, 356, 359, 360f, 361
- Mutual authentication, 41, 48
- NAS, 2
- NAS. *See* Non-Access Stratum
- NBAP Elementary Procedures, 125
- NBAP Functions, 124
- NBAP SuccessfulOutcome, 174, 177, 182, 412, 418
- NBAP, 59, 82–3, 111–2, 124–6, 149–50, 159–60, 164, 172–3, 185, 188–212, 214–5, 217, 219–32, 235–9, 253f, 259, 265–69, 272, 274–80, 284–301, 305, 311–2, 328–32, 334–36, 344–48, 352–54
- NCC, 410, 495
- Near-Far-Effect, 71, 80
- Network Color Code, 410, 495
- Network Indicator, 107
- Network Switching Subsystem, 4
- Network Transactions, 63
- Network-to-Network interface, 104
- NNI. *See* Network-to-Network interface
- Node B Application Part. *See* NBAP
- Node B Setup, 118, 150, 172–73, 177, 179f, 185f, 262, 420
- Node B, 6–9, 12–13, 16–19, 28–35, 68–73, 77–83, 124–26, 147, 149–50, 159–60, 164, 167, 172–93, 196–97, 199–207, 210f, 215–4, 226–8, 235, 237–9, 253–4, 261–2, 265, 267–9, 271–2, 278, 280, 286–97, 299, 301–02, 304–17, 323–24
- Non-Access Stratum, 2, 17, 47, 70, 107, 170, 258, 264, 266, 267, 271f, 351, 393, 2, 31, 33, 113f, 191
- nonreturn to zero, 66
- NRZ. *See* Nonreturn to zero
- NSAPI, 227–9, 357, 390, 394, 396, 509
- NSS. *See* Network Switching Subsystem
- OPC, 108, 454–6, 458
- Open Loop Power Control, 78–9
- Originating Point Code. *See* OPC
- Orthogonal Codes with Variable Spreading, 65
- OSAID, 132
- Outer loop power control, 33, 78–9, 93
- Out-of-sequence delivery, 99
- OVSF. *See* Orthogonal Codes with Variable Spreading

- Packed Encoding Rules, 111
 Packet Control Unit, 5
 Packet Data Convergence Protocol, 83, 140
 Packet Data Network. *See* PDN
 Packet Identifier, 140
 PAD. *See* Padding
 Padding bit, 91
 Padding, 92
 paging channel, 340
 Paging Channel, 73–74, 95, 173, 184
 Paging Indicator Channel. *See* PICH
 PAP, 229, 396
 Path-ID, 179, 183, 185f, 196, 459, 460f
 PCCH, 117, 120
 P-CCPCH, 61–3
 PCH, 150, 151, 157–66, 219f, 302, 341, 380f
 PCM-24, 453, 458
 PCM-30, 453–54, 351f
 PCPCH, 73, 74
 P-CPICH, 73, 166, 167, 241, 293, 349
 PCU. *See* Packet Control Unit
 PDCP. *See* Packet Data Convergence Protocol
 PDF Context Creation, 464
 PDN, 462, 464, 467f
 PDP Context Activation, 21, 144, 223, 225f, 309, 330, 390, 431
 PDP Context. *See* PDPC
 PDPC, 223, 225, 226, 228–9, 231, 233, 234, 248, 250–61, 263, 264f, 265, 267–9, 271f, 272f, 387–94, 514
 PDSCH, 73–4
 PDU type 0, 135
 PER, 85
 Permanent Virtual Connections, 90
 Physical Channel Reconfiguration, 250–61, 295, 299, 303, 312
 Physical Channel, 74, 173f, 179
 Physical Common Packet Channel, 73, 76f
 Physical Downlink Shared Channel. *See* PDSCH
 Physical Random Access Channel. *See* PRACH
 Physical Uplink Shared Channel. *See* PUSCH
 PICH, 74, 114, 117, 179, 184, 219, 379
 PID. *See* Packet Identifier
 PLMN, 3–5, 29, 36, 85, 120, 139, 229, 414–15, 462, 509–10
 PN. *See* Pseudo-Noise codes
 POI. *See* Points of Interconnection
 Points of Interconnection, 10, 107
 POLL-PDU, 106
 POLL-STAT procedure, 106
 Power Control, 33, 77–81
 Power Management, 30, 113
 PRACH, 73–4, 76, 122
 PRES, 221, 380f, 448
 Primary Common Control Physical Channel. *See* P-CCPCH
 Primary Common Pilot Channel. *See* CPICH
 Primary Scrambling Code, 162, 173f, 175, 196, 204, 435–36
 Primary Synchronization Channel. *See* P-SCH
 Procedure Identification Code, 125
 Processing Gain, 70–71
 Profiles, 15, 25, 30
 Protocol Error Detection and Recovery, 101, 105
 PS domain, 4, 6, 21, 86, 477
 PS Streaming Video Call, 395–98
 P-SCH, 73, 77, 160
 Pseudo-Noise codes, 69
 PSTN, 5, 9, 10
 P-TMSI, 21, 50, 113–14
 Public Land Mobile Network. *See* PLMN
 Public Switched Telephone Network. *See* PSTN
 PUSCH, 74, 116
 PVC. *See* Permanent Virtual Connections
 QoS, 1, 8, 10–12, 18–19, 22, 24, 33, 69, 71, 79, 100, 107, 115, 137, 143–45, 165–66, 206, 225, 228, 231, 259, 265, 290, 323–25
 Quality of Service. *See* QoS
 RA. *See* Routing Area
 RAB Assignment procedure, 134, 137
 RAB SubFlow Combination Indicator. *See* RFCI

- RAB, 8, 30, 32, 59–60, 130, 131, 134–8,
143, 169, 206, 211, 214, 217, 225, 227,
255, 265, 297–8, 304, 307–10, 328, 330,
348, 357–9, 371–2
- RACH, 73–6, 95–8, 115–7, 121–2, 149–50,
172–3, 184, 188–90, 192–3, 202–3, 207,
219–20, 226, 236, 237f, 250–2, 255,
257–65, 268–70, 274f, 328, 364, 372,
380f, 385f, 400f, 414
- Radio Access Bearer. *See* RAB
- Radio Access Network Application Part. *See*
RANAP
- Radio Access Network. *See* RAN
- Radio Access Technology. *See* RAT
- Radio Bearer control function, 112
- Radio Bearer Management, 33
- Radio Bearer Service, 40, 167–8
- Radio Bearer Setup, 199, 206, 216, 225f,
255, 260, 266, 298, 308, 318–20
- Radio Interface Parameter Update, 94
- Radio interface, 63, 68, 71f, 93–94
- Radio Link Addition Request, 354
- Radio Link Control Protocol, 83
- Radio Link Control. *See* RLC
- Radio Link Protocol, 85, 139–40
- Radio Link Reconfiguration, 184, 192, 203,
398
- Radio Link Setup, 206, 212, 214, 225,
293–94, 298, 328–9, 347–8, 353, 396,
501, 505–6
- Radio Network Controller. *See* RNC
- Radio network layer, 81, 132, 136, 236
- Radio Network Subsystem Application Part.
See RNSAP
- Radio Network Subsystem, 30
- Radio Network Temporary Identity. *See*
RNTI
- Radio Network, 97
- Radio Resource Control, 112
- Radio Signaling Link. *See* RSL
- RAKE receiver, 67, 69
- RAN, 2, 4, 6, 26, 95
- RANAP, 56, 85f, 86f, 87, 109–12, 128–31,
134–8, 143–4, 150, 153, 320, 364–6,
368–79, 381
- RAND, 49, 50
- Random Access Channel. *See* RACH
- RAT, 4
- RAU, 465, 466, 469, 508
- Reassembly, 90, 100
- Registration Area, 36, 117, 177
- REL, 180, 183, 195f, 201f, 211–13, 216,
236, 245f, 260–62, 282, 287, 295–6, 353,
355, 358, 362, 391
- RELCMP, 216, 217f, 223, 224, 285f, 289f,
377
- Release complete, 110, 123
- RELEASE, 123, 133, 216, 217, 223, 285,
377
- Relocation, 419–37, 467, 478, 480–7, 489,
490–6, 498–500, 502
- Reset ack PDU, 104
- Reset PDU, 104
- Residual bit error ratio, 40
- RFC 791, 107
- RFICI, 135f, 138
- RLC architecture, 102–3
- RLC Functions, 100–2
- RLC, 60–2, 82–4, 98–104, 110, 113, 121f,
122, 123, 124f, 140–2, 151, 152f, 165,
184, 193, 199–205, 209, 210f, 211,
221–4, 226–8, 252f, 254f, 257–85,
293–4, 293, 319, 365
- RLP. *See* Radio Link Protocol
- RLSD, 110
- RNC, 2, 16–17, 20–3, 28, 30–5, 55, 58–63,
83, 90, 106, 110, 112, 123–6, 153–4, 169,
172, 182–93, 201–12, 221–8, 267–69,
272–85, 294–301, 303,–05, 309, 329,
364–75, 401–02, 420–32
- RNS. *See* Radio Network Subsystem
- RNSAP Functions, 126–7
- RNSAP, 16, 85, 126–9, 154–5, 402
- RNTI, 74, 95–7, 121–3, 128, 193, 197–9,
251–2, 256–8, 261–70, 308, 312,
329–30, 366, 402–7, 417–9, 423–5,
430–1, 481–4
- Routing Area Update, 158, 465, 466, 508,
509
- Routing Area, 36, 414, 470
- Routing Label, 153, 365–6, 368, 454,
458

- RRC CONNECTION
 RE-ESTABLISHMENT request, 122
 RRC CONNECTION REJECT, 57, 121
 RRC CONNECTION RELEASE
 COMPLETE, 123
 RRC Connection Release, 122–4
 RRC Connection Request, 58, 80f, 121, 161, 192, 199, 218, 237, 239
 RRC Connection Setup, 196, 199, 200, 240, 251, 253, 256, 263, 287, 293
 RRC Measurement Control, 200, 239, 240, 241, 245, 275, 287, 293, 299
 RRC Measurement Report, 244, 256, 288, 297, 298, 301, 314, 315, 347, 428, 430
 RRC Measurement Types, 239
 RRC Measurement, 239–45, 248, 253, 256, 260–61, 269, 283, 296, 297
 RRC state machine, 113
 RRC States, 113–8
 RSL, 491–93, 498
 RX TIMING DEVIATION, 94
- SAAL. *See* Signaling AAL
 SACC, 227f, 228, 253
 SAID. *See* Signaling Association Identifiers
 SAP. *See* Service Access Points
 SCCP Subsystem Number. *See* SSN
 SCCP, 109–10, 144, 153–5, 363–85, 390–1, 399, 402–3, 410–12, 414f, 414–9, 421, 424–6, 439f, 440–52, 469–71, 473–77, 488, 491–5, 498–500
 S-CCPCH, 73–74, 76–77, 117, 122, 160, 184
 SCF, 510
 SCH. *See* Synchronization channel
 SCP, 510
 SCR. *See* Source Controlled Rate
 Scrambling code, 69, 72, 77, 162, 175
 Scrambling, 65, 69
 SCTP, 84, 88, 89
 SCTP. *See* Stream Control Transmission Protocol
 SDF, 510
 SDH, 82, 89
 SDU, 39, 91, 96, 98f
 Secondary Common Control Physical Channel. *See* S-CCPCH
 Secondary Synchronization Channel. *See* S-SCH
 S-SCH
 Segmentation Sublayer, 91
 Segmentation, 90f, 91, 100
 Send Routing Information Response, 465
 Sequence Integrity, 92, 104
 Served User Generated Reference. *See* SUGR
 SUGR
 Service Accept, 145, 209
 Service Access Points, 128
 Service Control Function. *See* SCF
 Service Control Point. *See* SCP
 Service Data Function. *See* SDF
 Service Data Unit, 39, 96f
 Service Indicator, 107, 108
 Service Request, 144, 145, 201
 Service Specific Connection Oriented Protocol, 83, 104–6
 Service Specific Convergence Sublayer, 92
 Service Specific Coordination Function, 83, 106
 Service Switching Function. *See* SSF
 Serving GPRS Support Node. *See* SGSN
 Serving RNC. *See* SRNC
 Session Initiation Protocol, 9
 SETUP, 206, 210f, 211–2, 221, 222f, 230, 276, 374, 381, 459
 SF. *See* Spreading Factor
 SGSN delivered Short message Mobile Originated – Call Detail Record, 468
 SGSN delivered Short message Mobile Terminated – Call Detail Record, 468
 SGSN Relocation, 467
 SGSN, 20–22, 49, 51, 56–58, 86–87, 144, 157, 169, 202, 225–7, 304, 384–5, 387–8, 396–9, 402, 421–2, 425–6, 437–8, 440, 463–73, 476–8, 506–9, 513, 515, 517
 SGSN. *See* Serving GPRS Support Node
 SHCCH, 83
 Short Message Control Protocol, 337, 341
 Short Message Routing Protocol, 337, 341
 Short Message Service Center, 5
 Short Message Service, 437, 438, 468
 Short Message Service. *See* SMS
 SIB, 118–9, 121, 177–9, 184, 188, 239, 249–50, 293

- Signaling AAL, 104
- Signaling Association Identifiers, 132
- Signaling Connection Control Part, 85, 109
- Signaling connection release, 124
- signaling integrity function, 41
- signaling integrity, 41
- Signaling Link Set. *See* SLS
- Signaling Point Code. *See* SPC
- signaling radio bearers, 292, 295, 296, 325, 327–28, 343, 346–48, 357, 412, 503
- Signaling Transfer Points, 5
- Signaling Transport Converter, 83, 108–9
- Signal-to-Interference ratio, 33
- SIM, 8, 37
- SIO, 108
- SIP. *See* Session Initiation Protocol
- SIR. *See* Signal-to-Interference ratio
- Site Selection Diversity Transmission, 81, 281
- Site Selection Diversity Transmission. *See* SSDT
- SLS, 454
- SM Functions, 144
- SM, 83, 144
- SMpSDU. *See* Support mode for predefined SDU size
- SMS, 201, 437–40, 442f, 443, 446, 450, 468
- SMSC. *See* Short Message Service Center
- Soft handover, 150, 165–6, 239, 242, 245, 272–79, 281–3, 285f, 288, 293, 333
- Softer Handover, 67, 68, 286–90
- Source Controlled Rate, 137
- SPC, 106, 153, 365, 414, 454–6, 460f
- Specialized Resource Function. *See* SRF
- Spreading Factor, 65, 68
- Spreading factor, 169
- spreading, 65, 68
- SREQ, 227, 253, 390
- SRF, 511
- SRIR. *See* Send Routing Information Response
- SRNC, 13, 18, 30t, 33–34, 79–81, 97, 128f, 197–98, 239–42, 261–62, 273–75, 304–7, 358–60, 401–6, 410–37, 442–3, 452, 467, 478–81, 483, 485, 490, 492, 498, 502, 505, 507–8 (26)
- SRNS Relocation, 140, 419–20, 422, 424, 426–8, 430, 434–7, 447, 478, 480
- SRNS, 97, 136
- SSCF. *See* Service Specific Coordination Function
- S-SCH. *See* secondary Synchronization channel
- S-SCH. *See* Secondary Synchronization Channel
- SSCOP. *See* Service Specific Connection Oriented Protocol
- SSCS. *See* Service Specific Convergence Sublayer
- SSDT, 91, 196
- SSF, 510
- S-SMO-CDR, 468
- S-SMT-CDR, 468
- SSN, 109, 154, 469–73, 476
- Standards Committee T1 Telecommunications, 2
- Start Field, 92
- STAT, 105, 106
- STATUS PDU, 103, 104
- STC. *See* Signaling Transport Converter
- STF. *See* Start Field
- STP. *See* Signaling Transfer Points
- Stream Control Transmission Protocol, 84
- Streaming Class, 41
- Subsystem number, 109
- Successful Outcome Message, 126
- SUGR, 131, 179f, 182, 185f, 375, 460
- Support mode for predefined SDU size, 134
- SVC. *See* switched virtual connections
- Switched virtual connections, 90
- Synchronized Radio Link Reconfiguration, 214, 293, 297–8, 300, 307–8, 310, 312, 328–9, 347, 353, 505, 506
- Symbol rate, 66
- Synchronization Channel, 73, 76, 410
- Synchronization, 73, 93–4, 139, 175, 184, 266, 301, 412
- System Information Block, 118, 119, 177, 179, 249
- System Information Blocks. *See* SIB
- System Information Change Indication, 120

- System information, 39, 119
- System Network Layer, 81
- T1, 2
- T300, 121, 122
- T308, 123
- TAF. *See* Terminal Adaptation Function
- TB. *See* Transport Block
- TBS. *See* Transport Block sets
- TC. *See* Transcoder
- TCAP, 86, 472–7, 482–8, 491, 494–5, 498–501, 512–7
- TCP, 87, 89, 190, 259–61
- TCTF, 96
- TDD, 7, 27, 35, 73, 116
- TDMA. *See* Time Division Multiple Access
- TD-SCDMA, 26–28, 239, 324, 339–61, 363
- TEID, 389–91, 464–67
- Telecommunication Technology Committee, 2
- Telecommunications Technology Association, 2
- Temporary Mobile Subscriber Identity. *See* TMSI
- Terminal Adaptation Function, 85, 138
- Terminal Adapter, 36
- Terminal Equipment, 37
- TFI. *See* Transport Format Indicator
- TFS, 59, 83, 95, 179, 185, 187, 265, 270, 307, 403
- Time Division Multiple Access, 1, 65f
- Time Hopping, 66
- Time of Arrival, 94, 184
- Timing Adjustment, 94
- Timing Advance, 44
- TIO, 211, 229f, 230, 232–34, 390–91, 396–98, 485, 486f, 487f
- TMSI, 113, 142, 192f, 196–7, 200–5, 207, 219–22, 226, 252, 273–75, 287, 333, 346, 364f, 369, 372–3, 379–80, 385, 390, 399, 400f, 440
- ToA, 184
- TPC. *See* Transmit Power Control
- Traffic class, 39
- Traffic handling priority, 40
- Transaction Capabilities Application Part. *See* TCAP
- Transaction Id value, 211, 229, 232, 234
- Transcoder, 137
- Transfer delay, 40
- Transfer of user data, 100, 140
- Transmission control protocol. *See* TCP
- Transmission time interval, 13
- Transmit Power Command, 80
- Transmit Power Control, 78
- Transparent Data Transfer, 99
- Transparent Mode, 101
- Transport Block Sets, 93
- Transport Block, 93, 94
- Transport channel, 93
- Transport Format Indicator, 93
- Transport Format Set, 59, 179, 193, 203, 212, 278, 403, 405, 416, 419
- Transport network layer, 81
- Transport network, 2, 153f
- TRCMD, 221
- TRCMP, 201, 221, 369
- TTI. *See* Terminal Adaptation Function
- Tunnel Endpoint Identifier. *See* TEID
- UARFCN, 175, 346, 408, 435, 436
- UBR, 91
- UDP, 87, 108, 140, 270, 442
- UE, 13, 18–21, 31–39, 55–60, 62–68, 72–83, 95–98, 112–23, 127–31, 140–45, 164, 166–69, 172–73, 191–93, 196–97, 199–200, 239–41, 249–50, 256–63, 266–67, 269f, 272–73, 278–282, 292–302, 304–6, 314–20, 322–25, 329–37
- UE-Id, 96, 98f, 405
- UICC, 8, 37, 58, 59
- UL NODE SYNCHRONIZATION, 94
- UL SYNCHRONIZATION, 94
- UM, 102, 103, 113f, 121–23
- UMD PDU, 93
- UMSC, 6
- UMTS absolute radio frequency code number, 175
- UMTS channel, 72

- UMTS Domain, 31
- UMTS Registration Area. *See* URA
- UMTS Rel. 5, 9, 10
- UMTS Release 4, 7
- UMTS Release 5, 8
- UMTS Release 99, 5
- UMTS Terrestrial Radio Access Network.
See UTRAN
- UMTS, 1
- Unacknowledged Data Transfer, 99
- Unacknowledged Mode. *See* UM
- UNI, 82f, 104,
- Unique delivery, 99
- Universal Integrated Circuit Card. *See* UICC
- Universal Mobile Telecommunications
System. *See* UMTS
- Unspecified Bitrate Service. *See* UBR
- Unsuccessful Outcome Message, 129
- UP FP, 93f
- Uplink Common Packet Channel, 74
- Uplink direct transfer, 124
- Uplink Shared Channel. *See* USCH
- URA UPDATE, 122
- URA, 35, 36, 114–17, 122, 127t, 128f, 177,
446
- URA.PCH, 104f, 105f
- USCH, 76, 116, 127
- User Datagram Protocol. *See* UDP
- User Equipment. *See* UE
- User Plane Framing Protocol. *See* UP FP
- User Plane, 16, 55f
- User-Network Interface. *See* UNI
- USIM, 31, 37, 46–49, 51–59, 61, 62, 157,
192, 375, 453
- UTRAN Radio Network Temporary Identity,
97
- UTRAN, 2, 5–10, 12, 16, 22f, 26, 27, 29–41,
47f, 59, 65, 68, 77, 81, 97, 102, 111–16,
118–24, 130, 137, 141, 147, 148, 156,
159, 164, 167, 169, 240, 248, 256, 260,
290, 292, 295, 305, 312, 313, 315, 339,
402, 406, 409, 414, 427, 429, 437, 438,
453, 462, 463f, 467, 472f, 477, 478, 490,
492, 493, 499, 501–05, 507, 508
- value tag, 118
- VBR, 81
- VCI, 90, 96, 149–51, 153–54, 172, 173,
179f, 183–85, 196, 212, 304–05, 308,
310, 325–27, 348, 391, 440–41, 443–44,
448–51, 460
- VHE, 510
- Virtual Home Environment. *See* VHE
- Visitor Location Register. *See* VLR
- VLR, 5–8, 28, 47–51, 53, 56–58, 82f, 85–86,
109, 143, 193, 200, 226, 363, 365, 369,
399, 438, 469–73, 478f, 507, 508
- VPI, 90, 106, 149–51, 153–54, 172–73, 179,
183–85, 192, 196, 203f, 207f, 211, 212,
236–37, 279, 304–05, 308, 310, 325–27,
330, 348, 391, 440f, 441, 443, 447–51,
460

