

# INDEX

- Absolute threshold generalized selection
  - combining (AT-GSC)
  - average error probability
    - evaluation, 519–520
    - performance, 515–516
  - defined, 512
  - outage probability performance, 521–523
  - performance comparisons, with NT-GSC, 524–531
- Additive white Gaussian noise (AWGN)
  - average error probability performance, 142
  - characteristics of, generally, 19, 25, 38, 46, 55, 61, 62, 65, 67, 70, 76
  - coded communication, 761, 772–773, 775, 777, 783
  - fading channel capacity, 869–874
  - Gaussian  $Q$ -function, 84
  - multicarrier DS-CDMA systems, 745, 748
  - multichannel receivers, 312, 317, 331
  - multichannel transmission, 801–802, 818
  - optimum combining, 683, 699
  - optimum receivers, 189–190, 195, 199, 201, 211, 215, 218
  - performance, detection methods
    - binary signaling, generic results, 251
    - differentially coherent, 245–251
    - ideal coherent, 224–237
    - noncoherent, 242
    - nonideal coherent, 237–241
    - partially coherent, 242–245
  - single carrier DS-CDMA systems, 738
  - single-channel receivers, 223–251
- Alamouti's diversity technique, using two transmit antennas
  - characteristics of, 803–809
  - combined with multidimensional trellis-coded modulation, 812–818
  - generalization to orthogonal space-time block code designs, 809–812
- Amount of fading
  - implications of, 12–13
  - multichannel receivers, dual-branch diversity combining, 567, 578–581
- Amplitudes, fading channel
  - known
    - known delays, unknown phases, 198–199
    - known phases and delays, 191–195
  - unknown
    - known delays and unknown phases, 199–219
    - known phases and delays, 195–198
    - unknown phases and delays, 219–222
- Antennas
  - Alamouti's diversity technique, *see* Alamouti's diversity technique
  - diversity system, *see* Multiple-input/multiple-output (MIMO) antenna diversity systems
  - multiuser communication systems, multiple transmit and receive
    - correlation between receiver antenna pairs, 726
    - distribution of antenna elements, 726
    - numerical examples, 727–729
    - optimum weight vectors and output SIR, 723
    - outage probability, 723–725
    - PDF of output SIR, 723–724

*Digital Communication over Fading Channels, Second Edition.*

By Marvin K. Simon and Mohamed-Slim Alouini

ISBN 0-471-64953-8 Copyright © 2005 John Wiley & Sons, Inc.

- Antennas (*Continued*)
  - special cases, 725–726
  - system, channel, and signal models, 721–722
- Antipodal signaling, 52
- Arbitrary two-dimensional signal constellation
  - error probability integral, 142–144
- Automatic gain control (AGC), 314
- Average fading power, multichannel receivers, 316
- Average outage duration (AOD)
  - multichannel receivers
    - average level crossing rate and, 586–589
    - I.I.D. Rayleigh fading, 589–591
    - numerical examples, 591–594
    - overview, 584–585
    - system and channel models, 585
    - multiuser communication system, 667–671
- Beckmann distribution, 28–30
- Bessel function, 94, 96, 100–103, 114–115, 239, 346, 619, 650, 657
- Beta function, 138, 140
- Bhattacharyya parameter, 766
- Binary DPSK (BDPSK), multichannel receivers
  - multiple-symbol differential detection (MSDD), 370
  - outage probability, 411–413
  - selection combining, 415
  - switch-and-examine combining, 445
  - switched diversity, 464–465
- Binary frequency-shift-keying (BFSK)
  - average error probability performance, 137
  - defined, 58
  - multichannel receivers
    - coherent, 413–415
    - coherent equal gain combining, 334, 339
    - noncoherent, BDPSK and, 411–413
    - noncoherent equal gain combining, 343, 365
    - post-detection combining, 564–565
  - optimum combining, 694
  - optimum receivers, detection of, 203–204, 207, 210
  - single-channel reception
    - characteristics of, 243
    - fading channels, 267, 270, 273, 279–280, 283
- Binary phase-shift-keying (BPSK)
  - characteristics of, 51, 68
  - multichannel receivers
    - characteristics of, 546–549, 552
    - correlation models, 401
    - differentially encoded, 235
    - selection combining, 415–417, 485–487
    - switch-and-examine combining, 441
    - switched diversity, 428, 469
  - multichannel transmission, 853
  - optimum combining, 698, 701, 710, 715
  - selection combining, 533–537
- Binomial expansion, 10
- Bit error probability (BEP), average
  - alternative closed-form expressions, 135–137
  - coded communication
    - differentially coherent detection, 783
    - over fading channels, 759–760
    - transfer function bound, 772–774
    - TUB, comparison with union-Chernoff bounds, 788–791
  - conditional, 319–320
  - for decision statistic, quadratic form of complex Gaussian random variables, 619–625
  - integrals involving
    - arbitrary two-dimensional signal constellation error probability integral, 142–144
    - Gaussian- $Q$  function, 123–131, 144–145
    - incomplete gamma function, 137–141
    - Marcum- $Q$  function, 131–135
    - $M$ -PSK error probability integral, 141–142, 145–148
- Marcum  $Q$ -function, 100
- multichannel receivers
  - bounds on, 352–353
  - characteristics of, generally, 317, 320, 619–624
  - noncoherent equal gain combining, 334, 338–339
  - scan-and-wait combining, 448, 452, 454–455
  - selective combining, 519–520, 525–528, 530
- multichannel transmission
  - characteristics of, 801–803, 845
  - fast-fading channel model, evaluation of, 827–828
  - slow-fading channel model, evaluation of, 829–830
- optimum combining
  - diversity combining receivers, 685
  - multiple arbitrary power interferers and, 718
  - multiple-symbol differentiation detection (MSDD), 718–720
  - Nakagami- $m$  fading, 695–697
  - number of interferers and, 701–703, 705, 710, 712
  - Rayleigh fading, 682, 686–692

- optimum receivers and, 203–204, 207, 210–212
- as performance criterion, 6–12
- single-channel receivers
  - implications of, 223–229, 232–234, 236, 238, 241, 247–248, 251
  - fading channels, 273–281
- space-time trellis-coded modulation
  - approximate evaluation of, 827–830
  - transfer function upper bound evaluation, 831–833
- Bit error rate (BER), average
  - coded communication, 785
  - multicarrier DS-CDMA systems, 749–750
  - multichannel receivers
    - correlation models, 400
    - multiple-symbol differential detection with diversity combining, 368–371
    - noncoherent equal gain combining, 351
    - outdated/imperfect channel estimates, 463–464
    - post-detection combining, 540–553, 557, 561–565
    - selection combining, 480–487, 498
    - switch-and-examine combining, 441, 443, 445–446
    - switch-and-stay combining, 435–436, 438–439
    - switched diversity, 463–465, 469
    - noncoherent equal gain combining, 347–352
- Bivariate Rayleigh CDF, 172–174
- Bivariate Rayleigh PDF, 170–172
  
- Carrier reconstruction loop, 64
- Carrier synchronization
  - architectures, 65, 273–274
  - loop, 64
- Carrier-to-interference ratio (CIR), outage
  - probability, 639, 648, 657–661, 664–667
- Carrier-to-noise ratio (CNR), 639, 648, 660–661, 664
- Carrier tracking loop, 53
- CDMA code/codewords, 801
- Cellular mobile radio system, 644
- Channel state information (CSI), 191, 193, 760, 764–771, 773–774, 781, 785
- Characteristics function (CHF), 11n
- Chernoff bound, 85–86, 97–98, 231, 249, 759, 765–766, 773
- Chi-square distribution, 550
- Chi-square variates in outage probability,
  - multiuser communication systems, 640–645
- Classical functions, alternative representations
  - Gaussian  $Q$ -function, 84–93, 120–122
  - Marcum  $Q$ -function, 93–113, 118
  - Nuttall  $Q$ -function, 113–117
  - overview of, 83, 117–118
- Closed-form expressions, 135–137, 141, 143, 147
- Co-channel interferers (CCI), 681, 700, 706, 711, 721–722
- Coded communication systems
  - coherent detection
    - example of, 775–781
    - pairwise error probability, evaluation of, 763–771
    - system model, 761–763
    - transfer function bound
      - alternative formulation of, 774–775
      - on average bit error probability (BEP), 772–774
  - differentially coherent detection
    - example of, 785–787
    - performance evaluation, 783–785
    - system model, 781–783
  - true upper bounds (TUBs), comparison with Union-Chernoff bounds, 787–792
- Code-division multiple access (CDMA), 311, 697
- Coding gain, 798
- Coherent detection
  - differentially, 71–78, 117
  - ideal, 45–58
  - noncoherent, 66–68, 117
  - nonideal, 62–66
  - optimum receivers, 191–195, 217–219, 221–222
  - partially, 68–71
- Coherent equal gain combining, multichannel receivers
  - average output SNR, 332–333
  - characteristics of, generally, 331
  - exact error rate analysis
    - approximate, 340–341
    - asymptotic, 342
    - binary signals, 333–339
    - $M$ -PSK signals, extension to, 339–340
  - outage probability
    - combining, 380–382
    - performance, 380–381
  - receiver structure, 331
- Combined (time-shared) shadowed/unshadowed fading, 37
- Communication, types of
  - coded, *see* Coded communication
  - differentially coherent detection
    - conventional detection (two-symbol observation), 73–74

- Communication, types of (*Continued*)
- $M$ -ary differential phase-shift-keying ( $M$ -DPSK), 71–73, 117–118
  - multiple-symbol detection, 76–78
  - ideal coherent detection
    - $M$ -ary frequency-shift-keying ( $M$ -FSK), 56–58
    - $M$ -ary phase-shift-keying ( $M$ -PSK), 50–54, 75
    - minimum-shift-keying (MSK), 58–62
    - multiple amplitude modulation ( $M$ -AM), 47–49
    - multiple amplitude-shift-keying ( $M$ -ASK), 47–48
    - offset QSPK (OQPSK), 55–56
    - overview of, 45–47
    - $\pi/4$ -QSPK, 54–55
    - quadrature amplitude modulation (QAM), 48–50
    - quadrature amplitude-shift-keying (QASK), 48–50
    - staggered QPSK (SQPSK), 55–56
    - noncoherent detection, 66–68, 117
    - nonideal coherent detection, 62–66
    - partially coherent detection, conventional detection
      - multiple-symbol observation, 69–71
      - one-symbol observation, 68–69
    - $\pi/4$ -differential QPSK ( $\pi/4$ -DQPSK), 78
  - Complementary CDF (CCDF), 450–451
  - Composite gamma/log-normal distribution, 33–34
  - fading channel, 21
  - Composite log-normal shadowing/Nakagami- $m$  fading channel
    - characteristics of, generally, 140–141
    - Gaussian- $Q$  function and, 128–131
    - Marcum- $Q$  function and, 134–135
  - Composite microscopic-macroscopic diversity, 315
  - Composite multipath/shadowing
    - characteristics of, generally, 33
    - composite gamma/log-normal distribution, 33–34
    - $K$  distribution, 34–35
    - Rician shadowed distribution model, 36
    - Suzuki distribution, 34
  - Computer software packages, 171, 173, 685
  - Conditional BEP, 6–7, 9
  - Continuous-phase-frequency-shift-keying (SPFSK), 58–59
  - Correlation models, channel
    - dual branches with nonidentical fading, 390–392
    - dual correlation model, 396
    - exponential correlation model, 396–397
    - identically distributed branches
      - with constant correlation, 392–394
      - with exponential correlation, 394
    - intraclass correlation/constant correlation model, 396
    - nonidentically distributed branches with arbitrary correlation, 395–398
    - numerical examples, 399–404
    - overview, 389–390
    - tridiagonal correlation model, 397
  - Correlative fading, PDF and CDF
    - bivariate Rayleigh, 170–147
    - for maximum of two Nakagami- $m$  random variables, 177–180
    - for maximum of two Rayleigh random variables, 175–177
    - two log-normal random variables
      - maximum of, 180–183
      - minimum of, 183–185
  - Costas loop, 64, 238–239, 273
  - Cumulative distribution function (CDF)
    - bilateral RVs, 9–10
    - bivariate Rayleigh, 172–174
    - inverse Laplace transform, numerical techniques, 625–627
  - Marcum  $Q$ -function and, 100
  - multichannel receivers
    - average duration outage, 589
    - dual-branch diversity combining, 567, 570
    - multiple-input/multiple-output (MIMO) antenna diversity system, 597–598
    - post-detection combining, 541–543, 550–551, 556, 559
    - selection combining, 497, 518, 521
    - switch-and-examine combining, 440, 444
    - switch-and-stay combining, 433–434
    - switched diversity, 420–421, 424
    - optimum combining, 724
    - outage probability
      - implications of, 5–6
      - multiuser communication systems, 640–643, 649, 661–662, 674–678
      - Weibull distribution, 26
  - Decay, power delay profile (PDP), 38
  - Decision matrices, diversity combining, 367–368
  - Definite integrals, 634–635
  - Degradation, 274
  - Degrees of freedom, 550, 640–643, 674–678
  - Deinterleaving, 759, 784
  - Delays, fading channel
    - known
      - known amplitudes and phases, 191–195

- known amplitude and unknown phases, 198–199
- known phases and unknown amplitudes, 195–198
  - unknown amplitudes and phases, 199–219
  - unknown, amplitudes and phases, 219–222
- Delay statistic, multichannel receivers, 448–450
- Demodulation, 51–52, 57, 64–65, 76
- Desired forms, 8
- Differential decoding, 53–54
- Differential detection/detectors, 64, 73
- Differential encoding, 53–55, 144
- Differentially coherent detection
  - AGWN performance
    - $M$ -ary differential phase-shift-keying ( $M$ -DPSK), 245–250
    - $\pi/4$ -differential QPSK ( $\pi/4$ -DQPSK), 250–251
  - conventional detection (two-symbol observation), 73–74
  - in fading communications
    - characteristics of, 284–285
    - $M$ -ary differential phase-shift-keying ( $M$ -DPSK), fast fading, 290–293
    - $M$ -ary differential phase-shift-keying ( $M$ -DPSK), slow fading, 285–290
  - $M$ -ary differential phase-shift-keying ( $M$ -DPSK), 71–73, 117–118
  - multiple-symbol detection, 76–78
  - optimum receivers
    - characteristics of, 211–214, 217–218
    - Nakagami- $m$  fading, 217, 218–219
    - Rayleigh fading, 214–216, 218
  - single-channel receivers,  $M$ -ary differential phase-shift-keying ( $M$ -DPSK)
    - conventional detection, two-symbol observation), 245–249
    - with multiple-symbol detection, 249–250
- Differentially coherent receivers, 199
- Differentially encoded BPSK, single-channel receivers and, 235, 240
- Differential phase encoding, 53, 215
- Differential phase-shift-keying (DPSK)
  - multichannel receivers, 343
  - optimum combining, 698
- Differential quadrature phase-shift-keying (DQPSK), multichannel reception, 343, 370–371
- Differentiation, 4
- Digital portable communications, 315
- Dirac delta function, 515
- Direct-sequence code-division multiple access (DS-CDMA)
  - channel models
    - multicarrier, 743
    - single, 737–738
  - numerical examples, 750–754
  - overview of, 735–736, 741–742, 744
  - performance
    - multicarrier, 745–750
    - single, 739–741
  - receiver
    - multicarrier, 743–744
    - single, 738
  - transmitter
    - single, 736–737
    - multicarrier, 742–743
- Diversity combining
  - complexity-performance tradeoffs, 316
  - concept, 312
  - mathematical modeling, 312–313
  - multichannel receivers
    - multiple-symbol differential detection (MSDD), 367–375
    - optimum, 375–379
  - techniques, survey of, 313–316
- Diversity gain, 797
- Diversity order, 797
- Diversity-rich environments, combining in
  - generalized selection combining
    - based on log-likelihood ratio, 532–537
    - characteristics of, 469–512
    - with threshold test per branch (T-GSC), 512–531
  - generalized switched diversity (GSSC), 531–532
  - two-dimension diversity schemes, 466–469
- Diversity selection combining, 158
- Diversity systems, 12, 32
- Dual-branch diversity combining schemes, over
  - log-normal channels
    - characteristics of, 566
    - maximal-ratio combining, 568–571
    - selection combining, 571–575
    - switched combining, 575–584
    - system and channel models, 566–568snr)
- Dual-branch post-detection combining
  - identically distributed, 542, 544–547
  - nonidentically distributed, 542–543, 547–548
- Dual-branch selective combining
  - outage probability, multiuser communication system
    - fading and systems models, 661
    - numerical examples, 664–667
    - outage performance with minimum signal power constraint, 661–663
- Dual-diversity combining receiver, 169

- Eigenvalue, noncentral complex wishart matrices, 596–604
- 800/900 MHz frequency, 25
- Envelope fluctuations, in fading channels, 17–18
- Equal gain combining (EGC)
  - coded communication, evaluation of, 768
  - defined, 11
  - multichannel receivers
    - dual-branch diversity combining, 571
    - noncoherent, *see* Noncoherent equal gain combining
    - switched diversity, 467–468
  - noncoherent, *see* Noncoherent equal gain combining
  - optimum receivers, detection of, 203
- Euler summation-based technique, 625–626
  
- Fading channel capacity
  - channel and system model, 863–864
  - channel inversion with fixed rate
    - characteristics of, 869–870
    - no diversity, 870
    - maximal-ratio combining, 870–871
  - $I_n(\mu)$ , evaluation of, 880–881
  - MIMO fading channels, 876–877
  - numerical examples, 871–876
  - optimum rate adaptation with constant transmit power
    - characteristics of, 867–868
    - no diversity, 868–869
    - maximal-ratio combining, 869
  - optimum simultaneous power and rate adaptation
    - characteristics of, 865
    - no diversity, 865–866
    - maximal-ratio combining, 866–867
  - $T_n(\mu)$ , evaluation of, 878–880
- Fading channels, *see specific types of fading channels*
  - capacity of, *see* Fading channel capacity
  - characteristics of, generally
    - envelope fluctuations, 17–18
    - fast fading, 18
    - frequency-flat fading, 18–19
    - frequency-selective fading, 18–19
    - phase fluctuations, 17–18
    - slow fading, 18
  - multichannel receivers, noncoherent equal gain combining, 356–364. *See* Correlation models, channel
  - optimum receivers for
    - known amplitudes and delays, unknown phases, 198–199
    - known amplitudes, phases, and delays, 191–195
    - known delays, unknown amplitudes and phases, 199–219
    - known phases and delays, unknown amplitudes, 195–198
    - overview of, 189–191
    - unknown amplitudes, phases, and delays, 219–222
  - outage probability, multiuser communication systems, 643–644
  - performance detection
    - differentially coherent, 284–294
    - ideal coherent, 252–267
    - imperfect channel estimation, 294–301
    - noncoherent detection, 281–282
    - nonideal coherent, 267–281
    - partially coherent, 282–284
  - SNR and, 21
- Fading distribution, multichannel receivers, 316
- Fast fading, 18, 784
- First propagation, 38–39
- Fixed-rate transmission, 869–871, 874
- Flat-fading channels
  - implications of, 381
  - modeling of
    - characteristics of, 19–20
    - combined (time-shared) shadowed/unshadowed fading, 37
    - composite multipath/shadowing, 33–37
    - log-normal shadowing, 32–33
    - multipath fading, 20–32
- Fourier transform, 10, 337
- Frequency-flat fading, 18–19
- Frequency mismatch, 62
- Frequency-selective fading, characteristics of, 18–19
  
- Gauss-Chebyshev quadrature-based technique, 510, 626–627
- Gauss-Chebyshev quadrature rules, 10
- Gaussian-Hermite quadrature integrals, 123, 128–129, 134, 317, 338, 639
- Gaussian noise, 118
- Gaussian probability integral, 84
- Gaussian  $Q$ -function
  - characteristics of, generally, 7, 179
  - coded communication, 765
  - higher powers, alternative representations of, 90–93
  - integrals involving
    - composite log-normal shadowing/ Nakagami- $m$  fading channel, 128–131
    - higher-order integer powers, 144–145
    - log-normal shadowing channel, 128
    - Nakagami- $m$  fading channel, 126–127, 145

- Nakagami- $n$  (Rice) fading channel, 126
- Nakagami- $q$  (Hoyt) fading channel, 125
- overview of, 123–124
- Rayleigh fading channel, 125, 144–145
- multichannel receivers
  - dual-branch diversity combining, 567
  - implications of, 320, 334–335
  - switched diversity, 429
  - symbol error rate (SER), 324
- one-dimensional case, 84–86, 88–90
- optimum combining, 704
- optimum receivers, 196
- proofs of alternative forms, 120–122
- single reception, 225–226, 229–232, 236, 239–240
- symbol error rate (SER), 330
- two-dimensional case, 86–90
- Generalized selection combining (GSC),
  - multichannel receivers
    - based on log-likelihood ratio (LLR)
      - envelope-based, 536
      - optimum for equiprobable BPSK, 533–536
      - optimum for noncoherently detected equiprobable orthogonal BPSK, 536–537
    - performance analysis
      - characteristics of, 470–473
      - I.I.D. Nakagami- $m$  case, 497–502
      - I.I.D. Rayleigh case, 472–492
      - I.I.D. Weibull case, 510–512
      - non-I.I.D. Rayleigh case, 492–497
      - partial-MGF approach, 502–510
      - with threshold test per branch (T-GSC), 512–531
- Generalized switched diversity (GSSC), 531–532
- Generic closed-form formula, 640
- Global optimization, 465
- Global System for Mobile (GSM), 697
- Gradshteyn-Ryzhik equation, 325
- Gray code bit mapping, 225, 227, 232–233, 246
  
- Hamming distance, 775–776
- Harmonics, 57
- High-speed data transmission, 864
- Hoyt distribution, *see* Nakagami- $q$  (Hoyt) distribution
- Hoyt fading channel
  - characteristics of, 21–23, 28–29
  - Gaussian- $Q$  function and, 125
  - incomplete gamma functions and, 139
  - Marcum- $Q$  function and, 133
  - multipath fading, 22–23
- Hybrid diversity schemes, multichannel receivers
  - generalized techniques, 315
  - multidimensional techniques, 315–316
  
- Ideal coherent detection
  - in communication systems
    - $M$ -ary frequency-shift-keying ( $M$ -FSK), 56–58
    - $M$ -ary phase-shift-keying ( $M$ -PSK), 50–54
    - minimum-shift-keying (MSK), 58–62
    - multiple amplitude modulation ( $M$ -AM), 47–49
    - multiple amplitude-shift-keying ( $M$ -ASK), 47–48
    - offset QSPK (OQPSK), 55–56
    - overview of, 45–47
    - $\pi/4$ -QSPK, 54–55
    - quadrature amplitude modulation (QAM), 48–50
    - quadrature amplitude-shift-keying (QASK), 48–50
    - staggered QPSK (SQPSK), 55–56
  - fading channels
    - differentially encoded  $M$ -ary phase-shift-keying ( $M$ -PSK), 258–261
    - $M$ -ary frequency-shift-keying ( $M$ -FSK), 262–267
    - $M$ -ary phase-shift-keying ( $M$ -PSK), 256–258
    - minimum-shift-keying (MSK), 267
    - multiple amplitude-shift-keying ( $M$ -ASK), 253–254
    - multiple amplitude modulation, ( $M$ -AM), 253–254
    - offset QPSK (OQPSK), 262
    - $\pi/4$ -QPSK, 258–261
    - quadrature amplitude modulation (QAM), 254–256
    - quadrature amplitude-shift-keying (QASK), 254–256
    - staggered QPSK (SQPSK), 262
  - single channel receivers, performance over AWGN channel
    - $M$ -ary frequency-shift-keying ( $M$ -FSK), 236–237
    - $M$ -ary phase-shift-keying ( $M$ -PSK), 228–235
    - minimum-shift-keying (MSK), 237
    - multiple amplitude modulation ( $M$ -AM), 224–225
    - multiple amplitude-shift-keying ( $M$ -ASK), 224–225
    - offset QPSK (OQPSK), 235–236
    - $\pi/4$ -QPSK, 234–235
    - quadrature amplitude modulation (QAM), 225–234

- Ideal coherent detection, single channel
  - receivers (*Continued*)
  - quadrature amplitude-shift-keying (QASK), 225–234
  - staggered QPSK (SQPSK), 235–236
- Imperfect channel estimation, single-channel receivers
  - characteristics of, generally, 294–295
  - Rayleigh fading, signal model and symbol error probability evaluation, 295–297
  - special cases
    - $M$ -PSK, 297–300
    - $M$ -QAM, 300–301
- Incomplete gamma functions, integrals involving
  - characteristics of, 137–137
  - composite log-normal shadowing/Nakagami- $m$  fading channel, 140–141
  - log-normal shadowing channel, 140
  - Nakagami- $m$  fading channel, 140
  - Nakagami- $n$  (Rice) fading channel, 139
  - Nakagami- $q$  (Hoyt) fading channel, 139
  - Rayleigh fading channel, 138
- Interference, error probability performance, 137
- Interference-limited systems, outage probability
  - average outage duration (AOD), 667–671
  - channel fading models, 643–644
  - desired and interference signals models, 644
  - dual-branch SC and SSC diversity
    - fading and systems models, 661
    - outage performance with minimum signal power constraint, 661–667
  - overview, 659–661
  - generic formula for, 644–46
  - with minimum desired signal power constraint
    - models and problem formulation, 648–649
    - Nakagami/I.I.D. Rice scenario, 654–659
    - Rice/I.I.D. Nakagami scenario, 649–654
  - outage rate, 667–671
  - related to CDF of the difference of two
    - chi-square variates with different degrees of freedom, 640–643, 674–678
- Interleaving, 759–780, 784
- Irreducible error probability, 274, 293
- $K$  distribution, 34–35
- Land-mobile satellite systems, 33, 37
- Laplace transform
  - characteristics of, generally, 6, 124–126, 129, 132–134, 138–139, 143–144
  - coded communication, 769–770, 785–786
  - correlation models, 394
  - inverse, implications of, 361
  - multichannel receivers, selection combining, 475, 497, 521
  - optimum combining, 704
- Largest eigenvalue of certain quadratic forms in complex Gaussian vectors, distributions of, 732–734
- Level crossing rate (LCR)
  - average outage duration
    - multichannel receivers, 585–589, 591–594
    - multiuser communication system, 667–668
  - defined, 14
- Line-of-sight (LOS) path, Rayleigh fading, 20
- Log-likelihood ratio (LLR), selection combining, 532–537
- Log-normal random variables, PDF and CDF
  - maximum of, 180–183
  - minimum of, 183–185
- Log-normal shadowing
  - characteristics of, 21, 32–33
  - Gaussian- $Q$  function and, 128
  - incomplete gamma functions and, 140
  - Marcum- $Q$  function and, 133–134
- Loop SNR, 64, 273–274
- MacLaurin series expansion, 273, 276, 279
- Macrodiversity, 316
- $M$ -ary communication system, 10–11
- $M$ -ary differential phase-shift-keying ( $M$ -DPSK)
  - coded communication, 782–783
  - communications, 71–73, 117
  - optimum receivers, detection of, 211
  - single-channel receivers
    - characteristics of, 229
    - conventional detection, two-symbol observation, 245–249
    - fast fading, 290–293
    - multiple-symbol detection, 249–250
    - slow fading, 285–290
- $M$ -ary frequency-shift-keyed ( $M$ -FSK)
  - characteristics of, generally, 56–58, 68
  - multichannel receivers
    - noncoherent equal gain combining, 353–367
    - optimum diversity combining, 378–379
  - orthogonal extension, multichannel receivers
    - post-detection combining, 552–566
  - single-channel receivers, 236–237, 242–243, 262–267
- $M$ -ary phase-shift-keyed ( $M$ -PSK) signal
  - characteristics of, generally, 7, 50–54, 66, 68–69, 71, 73, 75, 77–78
  - coded communication
    - characteristics of, 762, 765, 774–775, 781–782
    - differential detection of sequences, association with MGF, 793–795
  - differentially encoded, single-channel receivers, 258–261

- error probability performance, *see* *M*-PSK
  - average error probability performance
- multichannel receivers
  - coherent equal gain combining, 339–340
  - selection combining, 481, 489
  - symbol error rate (SER), 322–323, 326, 330, 339–340
- multichannel transmission, 806, 810, 812, 815
- optimum combining, 715–718
- optimum receivers, detection of, 213–214, 217
- single-channel receivers
  - characteristics of, generally, 227–234
  - differentially encoded, 234–235
  - fading channels, 256–258, 297–300
  - partially coherent detection, 244
- Maple V, 171
- Marcum *Q*-function
  - bounds on, 97–100, 105–113, 118
  - characteristics of, 172–174, 179
  - for decision statistic, quadratic form of
    - complex Gaussian random variables, 619–621, 623–624
  - defined, 7
  - first-order, 93–100, 105–108, 114, 116
  - fourth order, 106–108
  - generalized (*m*th order), 100–113
  - integrals involving
    - composite log-normal shadowing/
      - Nakagami-*m* fading channel, 134–135
    - log-normal shadowing channel, 133–134
    - Nakagami-*m* fading channel, 133
    - Nakagami-*n* (Rice) fading channel, 133
    - Nakagami-*q* (Hoyt) fading channel, 133
    - overview of, 131–132
    - Rayleigh fading channel, 132
  - multichannel receivers, switched diversity, 423, 432
  - noncoherent equal gain combining, 346
  - outage probability, multiuser communication systems, 641–642, 650, 655
  - second order, 106–108
  - single-channel receivers, 242
- Mathematica, 171, 173, 685
- MATLAB, 171, 650
- Maximal-ratio combining (MRC)
  - characteristics of, generally, 5
  - coded communication, 765
  - fading channel capacity, 864, 866–867, 869–871
  - multichannel receivers
    - average outage duration (AOD), 590
    - correlation models, 398–399
    - dual-branch diversity combining, 568–571
    - MGF-based approach, 320–326
  - multiple-input/multiple-output (MIMO)
    - antenna diversity system, 595–596
  - outage probability performance, 379–380, 386, 388, 426–427
  - outdated/imperfect channel estimates, 457–458, 464
  - scan-and-wait combining, 453–454
  - selection combining, 469–472, 477, 481, 485, 487, 499, 519, 523–526
  - switch-and-stay combining, 438
  - switched diversity, 424, 430–432, 464, 466–468
- multichannel transmission, 801, 803, 807, 809, 816
- optimum receivers, 193, 710–714
- outage probability, multiuser communication systems, 640, 644
- overview of, 316–317
- PDF-based approach, 319
- receiver structure, 317–318
- selection combining, 410
- SER expressions, bounds and asymptotic, 326–330
- Maximum a posteriori (MAP), 64
- Maximum-likelihood (ML) decision rule, 191, 534
- Maximum-likelihood (ML) receiver, 763
- Maximum-likelihood sequence estimation (MLSE), 367, 763
- Minimum mean-squared error (MMSE), 294, 298–299
- Minimum-shift-keying (MSK)
  - characteristics of, 58–62
  - single-channel reception, 237, 267, 273
- Mobile communication system, 798
- Modulation diversity, 799
- Moment generating function (MGF)
  - average bit error rate probability, 12
  - average error probability performance, 143
  - coded communication
    - characteristics of, 770–771, 779, 781, 784, 786
    - differential detection of *M*-PSK sequences, association evaluation, 793–795
  - composite gamma/log-normal, 21
  - log-normal shadowing, 21, 32
  - multichannel receivers
    - correlation models, 392–396, 398
    - noncoherent equal gain combining, 356–359
    - selection combining, 405–406, 473–474, 476, 480, 483, 493–494, 499–510, 516–517, 531–532
    - switch-and-examine combining, 440–441, 445

- Moment generating function (MGF),
  - multichannel receivers (*Continued*)
    - switch-and-stay combining, 434–435, 437
    - switched diversity, 422
  - multichannel transmission, 816, 823–824, 833, 837
  - Nakagami- $m$  fading, 21, 25
  - Nakagami- $n$  (Rice) fading, 21
  - Nakagami- $q$  (Hoyt) fading, 21–22
  - optimum combining, 682, 684–687, 689, 697, 703, 708
  - outage probability, 5–6
    - multiuser communication systems, 652, 654
  - Rayleigh fading, 21–22
  - signal-to-noise ratio, 4–5
  - Weibull distribution, 27
  - unconditional, 9
- Moment generating function (MGF)-based
  - approach, multichannel receivers, 320–326
- Monte Carlo simulations, 665–666, 721, 728–729
- $M$ -PSK average error probability performance
  - characteristics of, 141–142, 151–152
  - integer powers of
    - characteristics of, 145–146
    - Rayleigh fading channel, 146–148
  - characteristics of, generally, 141
  - integer powers of
    - overview, 145–146
    - Rayleigh fading channel, 146–148
  - Nakagami- $m$  fading channel, 142
  - Rayleigh fading channel, 142
- $M$ -QAM
  - multichannel receivers
    - average SER, 324–326, 330
    - selection combining, 481
  - single-channel reception, 300–301
- Multicarrier code-division systems (MC-CDMA)
  - characteristics of, 741–742
  - numerical examples, 750–754
  - performance analysis
    - average BER, 749–750
    - conditional SNR, 745–749
  - system and channel models
    - channel, 743
    - notation, 744
    - receiver, 743–744
    - transmitter, 742–743
- Multichannel receivers, performance of
  - average outage duration
    - and average level crossing rate, 586–589
  - I.I.D. Rayleigh fading, 589–591
  - numerical examples, 591–594
  - overview, 584–585
  - system and channel models, 585
- bit error probability, 619–624
- coherent equal gain combining
  - approximate error rate analysis, 340–341
  - asymptotic error rate analysis, 342
  - average output SNR, 332–333
  - characteristics of, generally, 331
  - exact error rate analysis, 333–340
  - receiver structure, 331
- definite integrals, 634–635
- diversity combining
  - complexity of, 316
  - concept, 312
  - mathematical modeling, 312–313
  - techniques, survey of, 313–316
- diversity-rich environments, combining in
  - generalized selection combining, 469–512
  - generalized selection combining based on
    - log-likelihood ratio, 532–537
  - generalized selection combining with
    - threshold test per branch (T-GSC), 512–531
  - generalized switched diversity (GSSC), 531–532
  - two-dimension diversity schemes, 466–469
- dual-branch diversity combining schemes over
  - log-normal channels
    - characteristics of, 566
    - maximal-ratio combining, 568–571
    - selection combining, 571–575
    - switched combining, 575–584
    - system and channel models, 566–568
- fading correlation, impact of
  - identically distributed branches with
    - constant correlation, 392–394
  - identically distributed branches with
    - exponential correlation, 394
  - nonidentically distributed branches with
    - arbitrary correlation, 395–398
    - numerical examples, 399–404
  - overview, 389–390
  - two correlated branches with nonidentical
    - fading, 390–392
- hybrid combining techniques, *see* Hybrid
  - diversity schemes, multichannel receivers
- maximal-ratio combining (MRC)
  - MGF-based approach, 320–326
  - overview of, 316–317
  - PDF-based approach, 319
  - receiver structure, 317–318
  - SER expressions, bounds and asymptotic, 326–330

- multiple-input/multiple-output (MIMO)
  - antenna diversity systems
  - characteristics of, 594
  - largest eigenvalue of noncentral complex Wishart matrix, distribution of, 596–604
  - optimum weight vectors and output SNR, 595–596
  - system, channel, and signal models, 594–595
- noncoherent and differentially coherent equal gain combining
  - DPSK, DQPSK, and BFSK, 343–353
  - $M$ -ary orthogonal FSK, 353–367
  - multiple-symbol differential detection (MSDD) with diversity combining, 367–375
- numerical techniques, inversion of Laplace transform of CDFs
  - Euler summation-based technique, 625–626
  - Gauss-Chebyshev quadrature-based technique, 626–627
- optimum diversity combining, noncoherent FSK
  - characteristics of, 375–377
  - comparison with noncoherent equal gain combining receiver, 377–378
  - extension to  $M$ -ary orthogonal FSK case, 378–379
- outage probability
  - characteristics of, 379
  - coherent EGC, 380–381
  - MRC and noncoherent EGC, 379–380
  - numerical examples, 381–388
- outdated or imperfect channel estimates
  - characteristics of, 456–457
  - maximal-ratio combining, 457–458
  - noncoherent EGC over Rician fast fading, 458–460
  - numerical results, 464–466
  - selection combining, 461–462
  - switched diversity, 462–464
- power correlation coefficient of correlated Rician random variables relation with correlation coefficient of their underlying complex Gaussian random variables, 627–631
- pure techniques, *see* Equal gain combining (EGC); Maximal-ratio combining (MRC); Selection combining; Switched combining
- selection combining
  - average output SNR, 406–409, 475–476, 494
  - average probability of error, 411–417, 480–487
  - average SER, 494–496
  - CDF of output SNR, 497
  - characteristics of, 404–405
  - GSC input joint PDF, 472–473, 492–493
  - GSC input joint statistics, 499
  - MGF of GSC output, 499–502
  - MGF of output SNR, 405–406, 473–474, 493–494
  - outage probability, 409–411, 476–480, 497
  - PDF of output SNR, 474–475, 496–497
  - SNR penalty, 487–492
- switched diversity
  - characteristics of, 417–418
  - dual-branch switch-and-stay combining, 419–439
  - multibranch switch-and-examine combining, 439–456
  - theorem proofs, 473–474, 631–634
- Multipath diversity, 316
- Multipath fading
  - Beckmann distribution, 28–30
  - defined, 20
  - Nakagami- $m$  model, 24–25
  - Nakagami- $n$  (Rice) model, 23–24
  - Nakagami- $q$  (Hoyt) model, 22–23
  - Rayleigh model, 20–22
  - spherically-invariant random process model (SIRP), 30–32
  - Weibull distribution, 25–28
- Multipath intensity profile (MIP), 38
- Multiple amplitude modulation, ( $M$ -AM)
  - characteristics of, 47–49
  - multichannel receivers, average SER, 323–324
  - single-channel receivers
    - characteristics of, generally, 224–225
    - fading channels, 253–254
- Multiple amplitude-shift-keying ( $M$ -ASK)
  - characteristics of, 47–48
  - single-channel receivers
    - characteristics of, generally, 224–225
    - fading channels, 253–254
- Multiple-input/multiple-output (MIMO) systems
  - antenna diversity systems, multichannel receivers
    - characteristics of, 594
    - largest eigenvalue of noncentral complex Wishart matrix, distribution of, 596–604
    - optimum weight vectors and output SNR, 595–596
    - system, channel, and signal models, 594–595
  - outage probability, multiuser communication systems, 660
  - transmission, 798

- Multiple-input/single-output (MISO) system, 601, 603, 726, 876
- Multiple interferers, optimum combining, 697–718
- Multiple symbol detection, *see* Differentially coherent detection
- Multiple-symbol differential detection (MSDD)
  - multichannel receivers
    - asymptotic behavior, 371
    - average bit error rate performance, 368–371
    - decision metrics, 367–368
    - numerical results, 372–375
  - optimum combining
    - average BEP, 718–720
    - decision metric, 718
- Multiple trellis-coded modulation (MTCM), 799
- Multiuser communication systems
  - direct-sequence code-division multiple access (DS-CDMA), 735–756
  - optimum combining, 681–734
  - outage performance, 639–680
- Nakagami- $m$  fading channel
  - characteristics of, generally, 21, 24–25
  - composite gamma/log-normal distribution, 33
  - correlative PDF and CDF, 177–180
  - evaluation of definite integrals associated with
    - bounds, upper and lower, 165–167
    - exact closed-form results, 149–165
  - Gaussian- $Q$  function and, 126–127, 145
  - incomplete gamma functions and, 140
  - Marcum- $Q$  function and, 133
  - $M$ -PSK error probability integrals, 142, 146
  - multicarrier systems, DC-CDMA, 750
  - multichannel receivers
    - characteristics of, generally, 323
    - coded communication, 778, 781
    - coherent equal gain combining, 340
    - correlation models, 392, 397–398, 403
    - multiple-symbol differential detection (MSDD), 372–375
    - noncoherent equal gain combining, 353
    - outdated/imperfect channel estimates, 461
    - post-detection combining, 548
    - selection combining, 497–502, 509–512, 518
    - switch-and-stay combining, 435–436
    - switched diversity, 420, 422–423, 426, 429, 465, 469
  - optimum combining, 692, 695–697, 703, 712
  - optimum receivers
    - characteristics of, 196–198
    - detection by, 206–211, 217–219, 221
  - outage probability, multiuser communication systems
    - characteristics of, 640, 643–644, 648
    - Nakagami/I.I.D. Rice scenario, 654, 656–657
    - Nakagami/Nakagami scenario, 645–646, 678–680
    - Nakagami/Rice scenario, 647
  - outage rate and average outage duration, multiuser communication systems, 667–671
  - single carrier systems, DS-CDMA, 740–741
  - single-channel receivers, 275, 279, 282, 289
- Nakagami- $n$  (Rice) fading, *see* Rician fading channel
- Nakagami- $q$  (Hoyt) fading, *see* Hoyt fading channel
- Narrowband land-mobile satellite modeling, 33
- Noisy reference loss, 273–281
- Noncentrality parameter, 94
- Noncoherent detection
  - optimum receivers
    - characteristics of, 199–200, 219
    - Nakagami- $m$  fading, 206–211, 221
    - Rayleigh fading, 201–206, 220–221
  - single-channel receivers
    - AWGN channel performance, 242
    - fading channels, 281–282
- Noncoherent equal gain combining
  - multichannel receivers
    - DPSK, DQPSK, and BFSK, 343–353
    - $M$ -ary orthogonal FSK, 353–367
    - multiple-symbol differential detection with diversity combining, 367–375
    - outage probability performance, 379–380
    - optimum diversity, comparison with, 377–378
- Noncoherent frequency-shift-keying (FSK), optimum diversity combining
  - characteristics of, 375–377
  - comparison with noncoherent equal gain combining receiver, 377–378
  - $M$ -ary orthogonal FSK, extension to, 378–379
- Nonideal coherent detection, single-channel receivers
  - AWGN channel performance, 237–241, 267
  - fading channels, 267–281
- Nonlinear phase estimation techniques, 65
- Normalized threshold generalized selection combining (NT-GSC)
  - average error probability
    - evaluation, 520
    - performance, 516–519
  - defined, 512
  - outage probability performance, 523
  - performance comparisons, with AT-GSC, 527–531

- Numerical techniques, inversion of Laplace transform of CDFs
  - Euler summation-based technique, 625–626
  - Gauss-Chebyshev quadrature-based technique, 626–627
- Nuttall  $Q$ -function, 113–117, 650, 657
- Offset QPSK (OQPSK)
  - characteristics of, 55–56, 59–60, 63
  - single-channel receivers
    - AWGN channel performance, 235–236, 241
    - fading channels, 262, 267, 273
- Optical scintillation, 35
- Optimum combining (OC)
  - characteristics of, 681–682
  - defined, 681
  - distributions of largest eigenvalue, quadratic forms in complex Gaussian vectors, 732–734
  - diversity combining receivers
    - comparison with results for MRC in presence of interference, 710–714
    - multiple arbitrary interferers, 715–718
    - multiple equal power interferers, 697–710
    - multiple-symbol differential detection in presence of interference, 718–720
    - single interferer, 682–697
  - with multiple transmit and receive antennas
    - correlation between receiver antenna pairs, 726
    - distribution of antenna elements, 726
    - numerical examples, 727–729
    - optimum weight vectors and output SIR, 723
    - outage probability, 723–725
    - PDF of output SIR, 723–724
    - special cases, 725–726
    - system, channel, and signal models, 721–722
- Optimum diversity combining, noncoherent FSK
  - characteristics of, 375–377
  - comparison with noncoherent equal gain combining receiver, 377–378
  - extension to  $M$ -ary orthogonal FSK case, 378–379
- Optimum reception, performance evaluation
  - fading channels, optimum receivers for, 189–222
  - multichannel receivers, 311–635
  - single-channel receivers, 223–309
- Orthogonal signaling, 58
- Orthogonal systems, noncoherent, 10
- Outage duration
  - average, multichannels receivers
    - and average level crossing rate, 586–589
    - I.I.D. Rayleigh fading, 589–591
    - numerical examples, 591–594
    - overview, 584–585
    - system and channel models, 585
  - as performance criterion, 13–14
- Outage performance, multiuser communication systems
  - average outage duration, 667–671
  - with dual-branch SC and SSC diversity, 659–667
  - interference-limited systems, 640–647, 678–680
  - with minimum desired signal power constraint, 648–659
  - outage rate, 667–671
  - overview of, 639
- Outage probability
  - diversity combining, 170
  - multichannel receivers
    - characteristics of, 379
    - coherent EGC, 380–381
    - dual-branch diversity combining, 570–571
    - MRC and noncoherent EGC, 379–380
    - multiple-input/multiple-output (MIMO) antenna diversity system, 599–600, 604
    - numerical examples, 381–388
    - selection combining, 409–411, 476–480, 497
  - multiuser communication systems, optimum combining with multiple transmit and receive antennas, 723–725
  - as performance criterion, 5–6
- Outdated or imperfect channel estimates, multichannel receivers
  - characteristics of, 456–457
  - maximal-ratio combining, 457–458
  - noncoherent EGC over Rician fast fading, 458–460
  - numerical results, 464–466
  - selection combining, 461–462
  - switched diversity, 462–464
- Pair-state method, 774
- Pair-state transition diagram, 774–775
- Pairwise error probability (PEP)
  - coded communication, evaluation of known channel state information, 764–767
  - overview of, 759, 763–764
  - unknown channel state information, 768–772
  - defined, 244
  - multichannel transmission, Rician fading evaluation

- Pairwise error probability (PEP), multichannel transmission (*Continued*)
  - fast, 814–817, 820–821
  - slow, 821–824
- Parseval's theorem, 11
- Partial-band interference (PBI), multicarrier systems, DS-CDMA, 747–749
- Partially coherent detection
  - conventional detection
    - multiple-symbol observation, 69–71, 244–245
    - one-symbol observation, 68–69, 242–244
  - single-channel receivers, AWGN performance, 242–245
- Paths estimation, scan-and-wait combining, 450–451
- Phase fluctuations, in fading channels, 17–18
- Phase-locked loop (PLL)
  - noisy reference loss, 273
  - nonideal coherent detection and, 64
  - single reception, 238
- Phases, fading channel
  - known
    - known amplitudes and delays, 191–195
    - known delays and unknown amplitudes, 195–198
  - unknown
    - known amplitudes and delays, 198–199
    - known delays and unknown amplitudes, 199–219
    - unknown amplitudes and delays, 219–222
- Phase-shift-keying (PSK), 7
  - $\pi/4$ -differential QPSK ( $\pi/4$ -DQPSK)
    - defined, 78
    - single-channel receivers, detection of, 250–251
  - $\pi/4$ -QPSK, single-channel receivers, 54–55, 234–235, 258–261
- Pilot-symbol-assisted modulation (PSAM), 294, 298
- Pilot tone-aided detection, 64
- Post-detection combining, multichannel receivers
  - average BER analysis, 540–543
  - channel model, 537, 539
  - operation
    - switching strategy, 539–540
    - switching threshold, 540
  - orthogonal  $M$ -FSK, extension to, 552–566
  - Rayleigh fading, 543–548
  - receiver, 539
  - severity of fading, impact of, 548–552
  - system description, 537–538
- Power correlation coefficient of correlated Rician random variables relation with correlation coefficient of their underlying complex Gaussian random variables, 627–631
- Power decay factor, 39
- Power delay profile (PDP), 38, 201, 403, 469
- Precoded MSK, 60, 62–63
- Probability density function (PDF)
  - bit error rate probability, 10
  - bivariate Rayleigh, 170–172
  - coded communication, 764, 770, 783–784
  - composite gamma/log-normal, 21
  - fading channel capacity, 864
  - Gaussian- $Q$  function, 125
  - log-normal shadowing, 21
  - Marcum  $Q$ -function and, 93
  - multichannel receivers
    - average duration outage, 586–589
    - characteristics of, 319
    - coherent equal gain combining, 336–337
    - correlation models, 390–393, 395
    - dual-branch diversity combining, 567, 571, 575, 577
    - multiple-input/multiple-output (MIMO)
      - antenna diversity system, 598–602
    - post-detection combining, 559
    - selection combining, 472–475, 477, 492–493, 496–497, 499–500, 502, 516, 518, 520–521, 531
    - switch-and-examine combining, 440, 444
    - switch-and-stay combining, 434, 437
    - switched diversity, 421–422, 424, 467
  - multichannel transmission, 807
  - multiuser communication systems
    - multiple transmit and receive antennas, 723–724
    - optimum combining, 685–686, 689, 694–695, 697, 704, 707, 710, 715
    - outage probability, 640, 648, 654–656, 661, 723–724
- Nakagami- $m$  fading, 21
- Nakagami- $n$  (Rice) fading, 21, 23–24
- Nakagami- $q$  (Hoyt) fading, 21
- optimum combining, 723–724
- optimum receivers, 192, 195–196, 198–199, 201, 219–221
- outage probability, 5, 640, 648, 654–656, 661, 723–724
- Rayleigh fading, 21
- signal-to-noise ratio and, 5
- Weibull distribution, 25–26
- Quadrature amplitude modulation (QAM)
  - average error probability performance, 130, 142, 151, 153
  - characteristics of, 48–52

- defined, 7
- single-channel receivers
  - characteristics of, 225–234
  - fading channel, 254–256, 267, 273, 279–280
- Quadrature amplitude-shift-keying (QASK)
  - characteristics of, 48–50
  - single-channel receivers, 225–234, 254–256
- Quadrature phase-shift-keying (QPSK), *see* Quadrature amplitude modulation (QAM)
- Radar clutter, 35
- RAKE receivers
  - multicarrier DS-CDMA systems, 746
  - multichannel, 315, 321, 381, 384, 468–469, 471, 514
  - optimum combining, 683
  - single carrier DS-CDMA systems, 736, 738
- Rayleigh fading channel
  - capacity of, 871–876
  - CDF, 175–177
  - characteristics of, 20–22, 28
  - coded communication, 760, 778–779, 781, 786, 789
  - evaluation of definite integrals associated with
    - bounds, upper and lower, 165–167
    - exact closed-form results, 149–165
  - Gaussian- $Q$  function and, 125, 144–145
  - incomplete gamma functions and, 138
  - Marcum- $Q$  function and, 132
  - $M$ -PSK error probability integral, 142, 145–148
  - multicarrier DS-CDMA systems, 749
  - multichannel receivers
    - average outage duration, 589–591
    - coherent equal gain combining, 332
    - multiple-input/multiple-output (MIMO) antenna diversity system, 600, 603
    - noncoherent equal gain combining, 353, 360–364
    - outage probability, 410, 426, 428
    - post-detection combining, 543–548, 557–559
    - scan-and-wait combining, 453–454
    - selection combining, 407–408, 472–497, 418–520
    - switch-and-examine combining, 443–444
    - switched diversity, 420–422, 424, 426, 467
    - symbol error rate (SER), 323, 325–326
  - multichannel transmission, 823, 838
  - noisy reference loss evaluation, 273–281
  - optimum combining
    - average bit error probability, 682, 686–692, 698–699, 703
    - number of interferers, 706, 711
  - optimum receivers
    - characteristics of, 195–196
    - detection by, 201–206, 214–216, 218, 220–221
  - outage probability, multiuser communication systems
    - characteristics of, 643–644, 660
    - multiple Rayleigh interferers, 651
    - Rayleigh/I.I.D. Rice scenario, 654–656
    - selective combining, 664–667
    - single Rayleigh interferer, 650–651
  - PDF, 175–177
  - single-channel receivers
    - characteristics of, 277, 279–281
    - signal model and symbol error probability evaluation for, 295–297
- Rayleigh/log-normal PDF, 34–35
- Receive diversity, multichannel transmission, 800–803
- Received vector, 229, 232
- Rician fading channel
  - characteristics of, 21, 23–24, 28–29, 37
  - coded communication, 760, 767, 778
  - Gaussian- $Q$  function and, 126
  - incomplete gamma functions and, 139
  - Marcum- $Q$  function and, 133
  - multicarrier DS-CDMA systems, 749
  - multichannel receivers
    - characteristics of, generally, 323
    - multiple-input/multiple-output (MIMO) antenna diversity system, 601
    - noncoherent equal gain combining, 363–364
    - outdated/imperfect channel estimates, 458–460
    - post-detection combining, 550, 552, 559–561, 564
    - selection combining, 509, 511, 518
    - switched diversity, 421–422, 426, 429
  - multichannel transmission
    - fast, 814–817, 820–821
    - slow, 817–818, 821–822
  - multipath fading, 23–24
  - optimum combining, 692–693, 695, 706, 711
  - outage probability, multiuser communication systems
    - characteristics of, 643–644, 648
    - Rice/I.I.D. Rayleigh scenario, 657–659
    - Rice/Nakagami scenario, 647, 649, 652
    - Rice/Rayleigh scenario, 649–650
    - Rice/Rice scenario, 646
  - pairwise error probability performance
    - fast, 820–821
    - slow, 821–824, 840–841

- Rician fading channel (*Continued*)
  - shadowed distribution model, 36
  - single-channel receivers, 276–278
  
- Scan-and-wait combining (SWC), multichannel receivers
  - defined, 440
  - numerical examples, 452–456
  - operating assumptions, 446–447
  - performance of, 447–456
  - system and channel models, 446
- Scattering, 35
- Selection combining (SC)
  - characteristics of, 169–170
  - instantaneous, 178
  - multichannel receivers
    - average output SNR, 406–409, 475–476, 494, 574–575, 577–581
    - average probability of error, 411–417, 480–487
    - average SER, 494–496
    - CDF of output SNR, 497
    - characteristics of, 404–405
    - GSC input joint PDF, 472–473, 492–493
    - GSC input joint statistics, 499
    - MGF of GSC output, 499–502
    - MGF of output SNR, 405–406, 473–474, 493–494
    - outage probability, 409–411, 476–480, 497, 575, 581–584
    - outdated/imperfect channel estimates, 461–462
    - partial-MGF approach, 502–510
    - PDF of output SNR, 474–475, 496–497
    - SNR penalty, 487–492
- Self-adaptive receivers, 191
- Set partitioning method, 761
- Severity of fading, multichannel receivers, 316
- Shadowing, multichannel receivers, 316
- Signal vector, 229
- Signal-to-interference plus noise ratio (SINR), optimum receivers, 681–682, 685, 710
- Signal-to-interference ratio (SIR), optimum combining, 712, 716, 719–720, 723–724, 727
- Signal-to-noise ratio (SNR)
  - average, as performance criterion, 4–5
  - coded communication, 767, 784, 791
  - conditional, in multicarrier DS-CDMA, 745–749
  - equivalent loop, 238–239
  - fading channel capacity, 864, 866–867, 870, 875, 877
  - instantaneous, 123–126, 128, 131–133, 175, 178, 233, 274, 313, 358, 469–470, 499, 515–519, 521, 567
  - large-symbol, 225, 227
  - multichannel receivers
    - average bit error rate, 321
    - average output, 406–409
    - coherent equal gain combining, 331–333, 380–381
    - correlation models, 395, 401–402
    - dual-branch diversity combining, 566–569, 571–572, 574–581
    - MGF of output, 405–406
    - multiple-input/multiple-output (MIMO) antenna diversity system, 595–596, 599–603
    - multiple-symbol differential detection (MSDD), 373, 375
    - noncoherent equal gain combining, 347, 353, 367
    - optimum receivers and, 193, 196–197, 203, 210
    - outage probability, 424–426
    - outdated/imperfect channel estimates, 462–463, 465
    - post-detection combining, 544, 546–547, 559, 562–564
    - receiver structure and, 319
    - scan-and-wait combining, 447–448, 452–456
    - selection combining, 404, 406–409, 415–417, 471–476, 487–494, 496–498, 513–518, 521, 525–527, 529–533
    - switch-and-examine combining, 441, 443
    - switch-and-stay combining, 419–420, 423–424, 435, 437–438, 443–446
    - switched combining, 314–315
    - switched diversity, 423–424, 464–465, 467–468
    - symbol error rate (SER), 327–330
    - multichannel transmission, 801, 805, 816
    - optimum combining, 683–684, 695–696, 705
    - single carrier DS-CDMA system, 739
    - single-channel receivers, 225, 227–228, 230–231, 238, 273–275
- Single carrier systems, DS-CDMA
  - performance analysis
    - characteristics of, 739–740
    - general case, 740
    - Nakagami- $m$  fading channels, 740–741
  - system and channel models
    - channel model, 737–738
    - receiver, 738
    - transmitter, 736–737

- Single-input/multiple-output (SIMO) MRC systems, 594, 601, 603, 726, 864, 876–877
- Single-input/single-output (SISO) systems, 876
- Single interferers, optimum combining, 682–697
- Slow fading, characteristics of, 18, 145, 788
- Space-time block coding (STBC), defined, 799
- Space-time coding
  - defined, 798
  - disclaimer, 858–859
- Space-time trellis code (STTCs) designs, multichannel transmission
  - orthogonal, 809–812
  - super-orthogonal space-time trellis codes
    - average bit error probability (BEP), approximate evaluation of, 845
    - characteristics of, 834
    - extension to, with more than two transmit antennas, 844
    - numerical results, 848–850
    - pairwise error probability evaluation, 836–844
    - parameterized class and system model, 834–836
    - transfer function upper bound, evaluation on average bit error probability, 846–848
  - super-quasi-orthogonal space-time trellis codes
    - characteristics of, 850
    - examples of, 853–857
    - numerical results, 857–858
    - pairwise error probability, evaluation of, 852–853
    - signal model, 850–851
- Space-time trellis-coded modulation
  - average bit error probability, approximate evaluation of
    - fast-fading channel model, 827–828
    - slow-fading channel model, 829–830
  - characteristics of, 818–819
  - defined, 798
  - example of, 824–826
  - multichannel transmission, system design, *see* Space-time trellis-coded (STTC) designs, multichannel transmission
  - pairwise error probability performance on Rician fading channels, evaluation of
    - fast, 820–821
    - slow, 821–824
  - transfer function upper bound evaluation on average BEP
    - fast-fading channel model, 831–833
    - slow-fading channel model, 833
- Spacing technique, 497
- Spherically-invariant random process model (SIRP), 30–32
- Spherically-invariant RV (SIRV), 30–32
- Spread-spectrum (SS) technique, 735
- Square-law detection, 66, 68
- Staggered QPSK (SQPSK), *see* Offset QSPK
- Stein's unified analysis of error probability performance, 304–309
- Super-orthogonal space-time trellis codes
  - average bit error probability (BEP), approximate evaluation of, 845
  - characteristics of, 834
  - extension to, with more than two transmit antennas, 844
  - numerical results, 848–850
  - pairwise error probability evaluation
    - fast Rician fading channels, 836–840
    - slow Rician fading channels, 840–844
  - parameterized class and system model, 834–836
  - transfer function upper bound, evaluation on BEP, 846–848
- Super-quasi-orthogonal space-time trellis codes
  - characteristics of, 850
  - examples of, 853–857
  - numerical results, 857–858
  - pairwise error probability, evaluation of, 852–853
  - signal model, 850–851
- Suzuki distribution, 34
- Switch-and-examine combining (SEC)
  - defined, 418
  - multichannel receivers
    - characteristics of, 439–440
    - multibranch, 440–446
    - scan-and-wait combining, 446–456
- Switch-and-stay combining (SSC)
  - characteristics of, 315
  - multichannel receivers
    - branch correlation, effect of, 436–439
    - branch unbalance, effect of, 433–436
    - outdated/imperfect channel estimates, 462–463
    - performance over independently identically distributed branches, 419–432
  - outage probability, multiuser communication systems
    - fading and systems models, 661
    - numerical examples, 664–667
    - outage performance with minimum signal power constraint, 663–664
- Switched diversity
  - branch correlation, effect of, 436–439
  - branch unbalance, effect of, 433–436

- Switched diversity (*Continued*)  
 characteristics of, 417–418  
 dual-branch switch-and-stay combining (SSC)  
 branch correlation, effect of, 436–439  
 branch unbalance, effect of, 433–436  
 performance over independently identically distributed branches, 419–432  
 multibranch switch-and-examine combining  
 characteristics of, 439–440  
 classical multibranch SEC, 440–443  
 multibranch SEC with post-selection, 443–446  
 scan-and-wait combining, 446–456  
 multichannel receivers, outdated/imperfect channel estimates, 462–464
- Symbol error outage (SEO), 328
- Symbol error probability (SEP)  
 defined, 7  
 multichannel receivers, selection combining, 482–483  
 optimum combining, 715–718  
 single-channel receivers and, 223–226, 229, 234, 246, 248–250, 295–297
- Symbol error rate (SER)  
 multichannel receivers  
 asymptotic, 328–330  
 bounds, 326–328  
 coherent equal gain combining, 341–342  
 correlation models, 399–400  
 maximal-ratio combining (MRC), 317  
 $M$ -PSK signals, 322–323  
 post-detection combining, 557–560  
 selection combining, 481–482, 489–491, 494–496  
 square  $M$ -QAM signals, 324–326  
 optimum combining receivers, 692
- System performance measures  
 amount of fading (AF), 12–13  
 average outage duration (AOD), 13–14  
 bit error probability (BER), 6–12  
 outage probability, 5–6  
 signal-to-noise ratio (SNR), average, 4–5
- TDMA system, optimum combining, 697, 721–722
- Threshold test per branch, generalized selection combining with (T-GSC), multichannel receivers  
 average error probability evaluation, 519–520  
 average error probability performance, 516–519  
 characteristics of, 512–515  
 outage probability performance, 520–523  
 performance comparisons, 524–531
- Tikhonov distribution, 64, 73, 240
- Transfer function upper bound, evaluation on average BEP  
 fast-fading channel model, 831–833  
 slow-fading channel model, 833
- Transmit diversity  
 Alamouti's diversity technique, using two transmit antennas  
 characteristics of, 803–809  
 combined with multidimensional trellis-coded modulation, 812–818  
 generalization to orthogonal space-time block code designs, 809–812  
 historical perspective, 799–800  
 overview of, 797–799  
 receive diversity *vs.*, basic concepts of, 800–803
- Trellis-coded modulation (TCM)  
 characteristics of, 760, 773, 775, 787, 798  
 multidimensional, 812–818  
 space-time, *see* Space-time trellis coded modulation
- Tropospheric propagation, 35
- True upper bound (TUB), *see* Coded communication, coherent detection
- Two-dimension diversity schemes, 466–469
- UHF (ultrahigh frequency), 36
- Unified MGF-based approach, 8
- Uniform error probability (UEP) codes, 773
- Urban environment, 38
- Viterbi algorithm, 761, 763
- Weibull distribution, 25–28
- Weibull fading channels, 510–512
- Wise-Gallagher representation, 32
- Wishart matrices, noncentral complex, 596–604