

# INDEX

---

180° hybrid, 152

90° hybrid, 150

ABCD parameters, 45

acceptance band in spur plot, 279

actual gain, 315

additive noise, effect of loop on, 262

AGC, 84

Allan Variance, 271

AM

radio, Example 7.13, 211

suppression, 225

transfer from LO, 225

amplifiers, combining

180° hybrid, 152

90° hybrid, 150

anomalous IMs, 115

appendixes, use of, 3

architectures that improve linearity, 149

Ch. 6 Summary, 163

asymmetry, filter, 286

attenuator noise factor, 55

available gain, 313

average gain, 19

band conversion

Example 7.3, 182

Example 7.7, 193

bandwidth

noise, 48, 246

with feedforward, 161

bilateral

and unilateral modules combined, 28

modules in cascade, 24

binomial coefficient, 345

cable gain, 18

Example 2.1, 21

maximum, 19

minimum, 19

calculator

frequency conversion, 170

receiver, 289

synthesizer, 291

carrier recovery loop, effect on phase noise, 260

cascade

analysis of combiner tree, 157

optimizing, 139

phase shift of, 27

processing phase noise in, 252

standard, 16

CATV

Second-Order IMs in, 134

Third-Order IMs in, 136

changes, parameter, on spreadsheet, 43

changing standard impedance, Appendix I, 321

circle, constant noise, 61

- class B, 154
- combiner tree, 156
  - cascade analysis, 157
- combining
  - amplifiers
    - 180° hybrid, 152
      - harmonics, 153
      - intermods, 153
    - 90° hybrid, 150
      - harmonics, 151
      - intermods, 151
  - parallel, 149
  - parameters on one spreadsheet, 139
  - SWRs, 306
- complex  $Z_0$ , 45
- composite
  - distortion, 133
    - second-order, 133
    - triple beat, 133
  - S parameters, Appendix S, 349
- compression
  - from third-order response, 102
  - in a cascade, Example 4.6, 119
  - in mixer, 166
- constant-noise circle, 61
- contaminating signal, 219
  - in nonlinearities, summary of Ch. 8, 243
  - LO, 228
    - summary, 236
- contents, vii
- control(s)
  - gain, 84
  - level, 86
  - using on spreadsheets, 147
- conversion
  - arithmetic, Appendix C, 289
  - direct, 195
  - double, 202
  - frequency
    - in receivers, 167
    - in synthesizers and exciters, 170
  - loss, 166
- coupler, directional, 159
- cross modulation, 102
- crossover spur, 170, 182
  - Appendix X, 359
- crystal video receiver, 129
  - with preamplification, 129
- CSO, 133
- CTB, 133
- data
  - clock, transfer of phase noise from, 256
  - effect of phase noise on, 258
    - errors, 247
      - effect of phase noise on, 263
  - DC term, 93
    - from noise, 126
  - decibel, 303
  - decomposition of single sideband, 220
  - density
    - noise, 126
      - phase-power spectral, 246
      - power spectral, 125
      - single-sideband, 246
  - desensitization, 102
    - receiver, 249
  - design process, 1
  - detection, 93
  - difference-frequency term, 93
  - diplexer, 67, 90
  - direct conversion, 195
  - directional coupler, 159
  - distortion, composite
    - second-order, 133
    - triple beat, 133
  - double conversion, 202
  - downconversion
    - limitation due to two-by-twos, 206
    - multi-band, Example 7.15, 212
  - dynamic range, 137
    - other limitations, 139
    - spurious free, 137
  - effective power gain, 19
  - end elements in cascade, 26
  - end notes, 5
  - enhancements, spreadsheet, 146
  - error probability, 258
  - errors, data, 247
  - evanescent fields, 45
  - even-order terms, other, 97
  - Example 2.1 Cable Gain, 21
  - Example 2.2 Effect of Mismatch, 22
  - Example 2.3 Cascade Calculations, 27
  - Example 2.4 Composite from Bilateral and Unilateral Modules, 30
  - Example 2.5 Attenuator in Cascade, 35
  - Example 2.6 Sensitivities Using Spreadsheet, 42
  - Example 2.7 Changes Using Spreadsheet, 43
  - Example 3.1 Cascade Noise Figure, 51
  - Example 3.2 Noise Figure to Meet System Requirement, 52
  - Example 3.3 Cascade Noise Factor, 56
  - Example 3.4 Effect of Image Noise, Simple Front End, 69
  - Example 3.5 Spreadsheet with Image Noise, Broadband System, 70

- Example 3.6 Parameters Differing at Image Frequency, 72
- Example 3.7 (NF) Combined with Interconnects ..., 74
- Example 3.8 Noise Factor in Mixed Cascade, 80
- Example 3.9 AGC, Gain Determines Input, 84
- Example 3.10 AGC, Input Determines Gain, 85
- Example 3.11 Level Control, Open-Loop, 87
- Example 3.12 Level Control, Closed-Loop, 88
- Example 4.1 Second Harmonic, 94
- Example 4.2 Third-Order IM, 100
- Example 4.3 Computing IMs of a Cascade, 111
- Example 4.4 ... IMs That Do Not Add, 111
- Example 4.5 Coherent and Noncoherent Addition, 115
- Example 4.6 Compression in the Cascade, 119
- Example 5.1 NPR, 132
- Example 5.2 CSO and CTB, 136
- Example 5.3 ISFDR, 138
- Example 5.4 Combined Parameters, Standard Cascade, 141
- Example 5.5 Combined Parameters, Less Ideal Cascade, 141
- Example 5.6 Simplified Combined Spreadsheet, 143
- Example 5.7 Optimization, 143
- Example 7.1 Spur Levels, 175
- Example 7.2 Mixer IM, 177
- Example 7.3 band conversion, 182
- Example 7.4 Relative Level of LO Leakage, 184
- Example 7.5 Conversion to a Single IF, 186
- Example 7.6 Conversion to an IF Range, 192
- Example 7.7 Band Converters, 193
- Example 7.8 Zero IF, 195
- Example 7.9 Filter Requirements Table, 197
- Example 7.10 Plotting the Filter Requirements, 200
- Example 7.11 IF Filter, 201
- Example 7.12 Limitation Due to  $2 \times 2$  Spurs, 206
- Example 7.13 AM Radio, 211
- Example 7.14 Switched Preselector, 211
- Example 7.15 Multi-Band Downconverter, 212
- Example 7.16 Design Aid for Switched Preselectors, 212
- Example 8.1 Sideband Transfer from LO, 227
- Example 8.2 FM Contaminant Transferred from LO to IF, 230
- Example 8.3 SSB Contaminant on Verge of Transfer, 230
- Example 8.4 SSB Contaminant Not Transferred, 232
- Example 8.5 SSB Contaminant on Verge at Other End, 232
- Example 8.6 SSB Contaminant Not Transferred at Other End, 232
- Example 8.7 LO Contaminant Converted into IF, 234
- Example 8.8 LO contaminant leaking into IF, 234
- Example 8.9 LO Contaminant Equivalent Sideband Leaking into IF, 235
- Example 8.10 Mixer Noise Factor Increase Due to LO Noise, 237
- Example 8.11 Noise with High-Ratio Up Conversion, 239
- Example 8.12 Frequency Divider Spectrums In and Out, 241
- Example 8.13 Frequency Multiplier Spectrum In and Out, 243
- Example 9.1 Desensitization, 249
- Example 9.2 Contribution of Phase Noise to Data Errors, 263
- example of frequency conversion, Appendix E, 293
- Example Z.1 Cascade Gain, Nonstandard Modules, 365
- expected value of noise figure, 58
- feedback, 158
- feedforward, 159
- and bandwidth, 161
- harmonics with, 160
- intermods with, 160
- files, getting from Wiley site, xix
- filter
- asymmetry, 286
- filtering of phase noise by, 254
- IF, 168
- requirements, 200
- image rejection, 66
- requirements table, Example 7.9, 197
- RF, 168
- requirements, 197
- shape factor, 184, 196
- filtering
- of LO noise, 238
- of noise
- by filters, 254
- by PLLs, 253
- flicker noise, 48
- FM, transfer from LO, 226
- footnotes, 5
- formulas for IMs and harmonics, Appendix H, 317

- frequency
  - bands in spur plot, Appendix B, 279
  - conversion, 165
    - calculator, 170
    - design method, 170
    - effect on IM addition, 111
    - example of, 171
      - Appendix E, 293
    - higher values of  $m$ , 209
    - in feedback path, 217
    - in receivers, 167
    - in synthesizers and exciters, 170
    - operating regions, 203
  - frequency dividers
    - effect on contaminants, 240
    - internal noise, 242
    - sampling in, 241
  - frequency multipliers, effect on contaminants, 242
  - frequency, functions of, 7
- gain, 7
  - actual, 315
  - available, 313
    - ratio to transducer gain, 64
  - average, 19
  - cable, 18
    - variance, 22
  - cascade of nonstandard modules, 365
  - controls, 84
  - effective, 19
  - insertion, 315
  - maximum available, 313
    - nonstandard module, 366
  - mean cable, 20
  - module, 15
    - nonstandard relative to tested, 363
  - round-trip, 18
  - simple, 8
  - summary of Ch. 2, 43
  - tolerance, 8
  - transducer, 314
    - ratio to available gain, 64
  - types of power, Appendix G, 313
  - variance of a cascade, 25
  - variation due to SWR, 21
  - with parallel combining, 155
- getting files, xix
- glossary, xxi
- hard limiting, 223
- harmonic
  - formulas for, Appendix H, 317
  - second, 93
    - third, 100
      - with feedforward, 160
- heterodyning, 165
- homodyne, 195
- HRC CATV system, 133
- hybrid
  - 180°, 152
  - 90°, 150
- i (direction of propagation), 9
- IF
  - Filter Requirements, 200
    - Example 7.11, 201
  - mixer output, 165
  - range, conversion to, Example 7.6, 192
- IIP, 94
- image
  - frequency, parameters differing at, 72
  - noise, 65, 67
    - standard cascade, 74
  - rejection filter, 66
- impedance
  - match, 8
    - with hybrid, 151
  - nonstandard, 8
  - transformations in cables, 310
- IMs
  - adding
    - coherently, 106
    - randomly, 108
  - anomalous, 115
  - formulas for, Appendix H, 317
  - in cascade, spreadsheet for, 111
  - in mixers, Appendix P, 345
  - measuring, 116
  - relative phases at modules, Table 4.1, 108
  - second order, 93
  - that do not add, 109
  - third-order terms at input frequency, Appendix T, 353
  - two-signal in mixer, 176
    - with feedforward, 160
- in (direction of propagation), 9
- insertion gain, 315
- instantaneous SFDR, 137
- integration of phase noise, 258
  - limits for, 252
- intercept point
  - effect of mismatch on, 110
  - second order, 93
  - third-order, 99
- interconnect
  - in nonstandard cascade, 367
  - noise factor, 56, 334

- with mismatch, 335
  - reflection at, 39
  - transmission line, 16
- intermediate frequency, 165. *See* IF
- intermods. *See* IMs
- intermodulation of noise, 123
- internal spur, 168
- introduction, 1
- IRC CATV system, 133
- isolation, mixer, 167
  
- jitter, 248, 269
- Johnson noise, 48
  
- leakage
  - LO-to-IF on spur plot, 184
  - LO-to-RF on spur plot, 184
- level control, 86
- limiting
  - distortion in, 225
  - hard, 223
  - soft, 223
- limits of integration in computing phase
  - variance, 259
- linearity, architectures that improve, 149
- literature, use of technical, 5
- LO
  - components, mixing between, 228
  - contamination, effect on noise figure, 236
  - filtering, 238
  - mixer input, 165
  - summary of troublesome frequency ranges
    - in, 236
  - transfer from, of
    - AM, 225
    - FM, 226
    - phase noise, 255
    - single sideband, 226
  - troublesome frequency ranges in, 228
- load, power delivered to, 23
  - Appendix L, 325
- local oscillator, 165. *See* LO
- look-up tables, 146
- lossy interconnections, 32
  
- m*, high values in frequency conversion, 209
- matching impedance with hybrid, 151
- matrix multiplication, Appendix M, 327
- maximum available gain, 313
  - finding for a nonstandard module, 366
- maximum SWR from multiple reflections, 306
- mean cable gain, 20
- measurement of
  - IMs, 116

- NPR, 131
- S parameter, 10
- T parameter, 13
- minimum SWR, multiple reflections, 306
- mismatch, effect
  - of, 16
    - Example 2.2, 22
  - on intercept points, 110
  - on interconnect noise factor, 335
- mixer, 165
  - doubly balanced, 166
  - IF output, 165
  - IMs in, Appendix P, 345
  - LO input, 165
  - noise factor
    - due to LO contamination, 236
    - effective, 66
  - parameters, 166
  - RF input, 165
  - singly balanced, 166
  - terminations, 174
  - transfer from LO, 225
- mixing between LO components, 228
- modules
  - bilateral in cascade, 24
  - nonstandard, Appendix Z, 363
  - unilateral, 8
- multiband downconverter, Example 7.15, 212
  
- noise
  - additive, effect of loop on, 262
  - and nonlinearity, 123
    - summary of Ch. 5, 147
  - bandwidth, 48, 49, 246
  - density, 49, 126
  - effect of loop on additive, 262
  - factor, 47. *See* also noise figure
    - attenuator, 55
    - cascade, 50
      - module contribution, 50
    - effect from LO contamination, 236
    - effect of source impedance on, 341
    - equivalent for voltage amplifier, 79
    - impedance dependent, 59
      - representation, 59
    - implication re phase noise, 255
    - mixer, due to LO contamination, 236
    - of interconnect, 56, 334
    - of mixer, effective, 66
    - Op-Amp calculations, Appendix A, 273
    - parallel combining, 156
    - single-sideband, 66
    - standard, 54, 331
      - relation to theoretical, 62

- standard and theoretical, Appendix N, 329
- summary of Ch. 3, 88
- summary of relationships, 53
- theoretical, 54, 329
  - relation to standard, 62
  - using, 64
    - summary, 65
- two-element cascade, 51
- voltage amplifier, 74
  - with unilateral modules, 79
  - with extreme mismatch, 74
- figure, 47. *See also* noise factor
  - expected value, 58
  - sensitivity, 79
  - sensitivity, Appendix V, 355
  - spot, 49
  - variance, 58
  - variance, Appendix V, 355
- flicker, 48
- image, 65, 67
- intermodulation of, 123
- Johnson, 48
- phase, 245
- power ratio, 131
- products
  - DC term, 126
  - second-order, 125
  - third order, 130
- sidebands, oscillator, 238
- source, isolated, 59
- temperature, 47, 48
  - cascade, 51
  - in operational environment, 52
  - system, 51
  - with operational source, 52
- thermal, 48
- nonideal effects
  - in parallel combining, 162
  - other, 121
- nonlinear products
  - frequency dependence, 102
  - general cascade, 105
  - in cascade, 102, 103
  - relationship between, 102
  - two-module cascade, 104
- nonlinearity
  - and noise, 123
  - in signal path, 91
    - summary of Ch. 4, 121
  - representing, 91
- nonstandard
  - impedances, 40
  - interface impedance, 8
  - modules, Appendix Z, 363
- normalized waves, 11
- notes, end, 5
- NPR, 131
  - Measurement, 131
- o (direction of propagation), 9
- odd-order terms, other, 101
- OIP2, 93
- Op-Amp noise factor, Appendix A, 273
- operating regions, frequency conversion, 203
- optimizing cascades, 139
- organization of the book, 2
- oscillator
  - noise sidebands, 238
  - phase noise representations, 252
- out (direction of propagation), 9
- parallel combining, 149
  - gain with, 155
  - noise factor, 156
  - nonideal performance in, 162
- parameters
  - mixer characterized by, 166
  - range in composite modules, 39
  - S, 9
  - scattering, 9
  - T, 12
  - two-port, 9
- passband in spur plot, 279
- performance, deviations from desired, 4
- phase
  - noise, 245
    - adverse effects, 247
    - effect of carrier recovery loop on, 260
    - effect on data, 258
    - effect on data errors, 263
    - implication of noise figure, 255
    - integration of, 258
    - low frequency, 268
    - measures of, 269
    - oscillator spectrum, 250
    - sources of, 250
    - transfer from LO, 255
  - power spectral density, 246
  - shift of a cascade, 27
  - variance, limits of integration, 259
  - variation, 24
- PLLs, filtering of phase noise by, 253
- plotting filter requirements, Example 7.10, 200
- power
  - delivered to load, 23
    - Appendix L, 325
  - gain, 8
    - ratio for two noise factors, 342

- in a traveling wave, 12
- spectral density, 125
- PPSD, 246
- predictable spur levels, power range for, 177
- preface, xvii
- processing phase noise in a cascade, 252
- propagation direction subscript, 9
- PSD, 125
- push–pull, simple, 154
  
- random-walk FM, 251
- range of parameters in composite modules, 39
- ratio of power gains, standard and theoretical noise factors, 342
- receiver
  - calculator, 289
  - crystal video, 129
  - desensitization, 249
- references, 5, 371
- reflection coefficient, 8, 304
- reflections
  - at interconnects, 39
  - other, 82
- relative sideband
  - amplitude, 245
  - density, 246
- response, standard cascade, 25
- return loss, 8
- RF mixer input, 165
- round-trip gain, 18
  
- S parameters, 9
  - composite, Appendix S, 349
  - measurement, 10
  - nonstandard
    - cascade, 368
    - module, 367
  - relative to T parameters, 13
- sampling in frequency dividers, 241
- scattering parameters, 9
- second harmonic, Example 4.1, 94
- second-order
  - IMs in CATV, 134
  - products
    - mathematical representation, 95
    - of noise, 125
  - terms, 92
- sensitivity
  - noise figure, 79
    - Appendix V, 355
    - using, 82
  - use of to find variations, 40
- severe nonlinearities, 219
- SFDR, instantaneous, 137

- shape factor
  - definitions, 197
  - filter, 184, 196
- sideband
  - amplitude, relative, 245
  - density, relative, 246
- signal with noise, effect of, 128
- simple push–pull, 154
- simulation, 3
- single
  - frequency spur, 168
  - IF, conversion to, Example 7.5, 186
- sideband
  - decomposition of, 220
  - density, 246
  - transfer from LO, 226
- Smith Chart, 310
- soft limiting, 223
- source impedance, effect on noise factor, 341
- source resistance, effect on Op-Amp noise factor, 274
- specifications, creating and using, 1
- spectrum, oscillator, 250
- spot noise figure, 49
- spreadsheet
  - enhancements, 146
  - getting from Wiley site, xix
  - spur plot, 180
  - use of, 2, 3
- spur(ious), 168
  - crossover, 170, 182
    - Appendix X, 359
  - free dynamic range, 137
  - internal, 168
  - level
    - chart, 168
    - in DBM from balance parameters, 217
    - in mixer, 168, 171
      - dependence on signal strength, 171
      - estimating, 173
- m*-by-*n*, 168
- plot
  - IF reference, 186
  - LO reference, 180
  - normalized to LO, 184
  - representation of bands, Appendix B, 279
  - spreadsheet, 180
  - single-frequency, 168
- standard
  - cascade, 16
    - overall response, 25
  - CATV system, 133
  - impedance, 8
    - changing, Appendix I, 321

- noise factor, 331
- state variables, standard cascade, 18
- sum-frequency term, 93
- superheterodyne, 165
- switched preselector
  - design aid for, Example 7.16, 212
  - Example 7.14, 211
- SWR(s), 8, 304
  - combining, 306
  - maximum sum, 306
  - minimum sum, 306
  - variation in, 38
- symbols, list of, xxi
- synthesis calculator, 291
- system design process, 1
  
- T matrices, 14
  - multiplying, 14
- T parameter(s), 12
  - measurement, 13
  - other definitions, 45
  - relative to S parameters, 13
  - restrictions on, 14
- Table 3.1 Summary of Noise Relationships, 53
- Table 4.1 Phases of Close (in frequency)
  - Signals and IMs Formed at Two Different Locations, 108
- Table 5.1 Effects of Redistributing Amplifiers, 146
- Table 7.1 Ratio ( $r$ ) of Largest IM to Mixer Spur, 176
- Table 7.2 Values for Fig. 7.38, 215
- Table 8.1 Characteristics of Troublesome Ranges in LO with Attenuation from LO to IF shown for SSB contaminant, 236
- Table A.1 Op Amp Noise Factors for Various Parameter Values, 277
- Table P.1 Binomial Coefficients, 346
- Table S.1 S Parameters for Composite of Two Modules, 352
- Table X.1 Crossover Spurs, 359
- Taylor series, 91
- technical literature, use of, 5
- terminations, mixer, 174
- terms, list of, xxi
  
- test, 3
- theoretical noise factor, 329
- thermal noise, 48
- third-order
  - IMs in CATV, 136
  - IP, 99
    - Example 4.2, 100
  - products
    - mathematical representation, 100
    - of noise, 130
  - terms, 97
- time dependence, 92
- tolerance, gain, 8
- transducer gain, 314
- transfer of phase noise from data clock, 256
- transformation of impedance by cable, 310
- transmission line interconnection, 16
- triplexer, 67, 90
- troublesome frequency ranges in the LO, 228
  - summary, 236
- two-by-twos, 206
- two-port parameters, 9
- two-signal IMs in mixer, 176
  
- unilateral modules, 8
  - bilateral modules
    - becoming effectively, 33
    - combined with, 28
  - simplification with, 15
  
- variance
  - cable gain, 22
  - noise figure, 58
    - Appendix V, 355
- variation
  - in SWRs, 38
  - phase, due to reflection, 24
- waves, normalized, 11
  
- $Z_0$ , imaginary component, 45
- zero IF
  - conversion to, 195
  - Example 7.8, 195