

Index

- 3GPP, 59
- 3GPP2, 62
- 16-QAM, 368, 369, 449
- 64QAM, 449

- access service class, ASC, 143
- active set update, 165, 237
- ACTS, 53
- acquisition indication channel, AICH, 95, 111, 122
- adaptive antennas, 132, 343
- adjacent channel interference, 105, 281
- adjacent channel leakage ratio, ACLR, 509
- adjacent channel selectivity, 523
- admission control, 256
- amplifier linearization, 512
- AMR speech codec, 10
 - ACELP, 10
 - capacity, 319, 337
 - coverage, 304
 - wideband, 12
- antenna diversity, 308, 453
- ARIB, 57

- beamforming, 132, 343
- broadcast and multicast service center (BM-SC), 423
- broadcast channel, 94, 119
- broadcast control channel, BCCH, 143
- broadcast/multicast control protocol, BMC, 151

- call session control function, CSCF, 89
- capacity
 - AMR speech codec, 319, 337
 - downlink, 312
- cdma2000, 58
 - standardisation, 59

- cell radio network temporary identity, C-RNTI, 142
- cell update, 168
- channel coding
 - AMR, 117
 - common channels, 118
 - convolutional, 116
 - dedicated channel, 118
 - TFCI, 118
 - turbo, 117
- channel quality indicator, 364
- channelisation codes, 96
- CIF, 14
- ciphering
 - MAC layer, 143
 - RLC layer, 147
- co-existence
 - TDD-FDD, 296
- common control channel, CCCH, 143
- common control physical channel
 - primary, 119
 - secondary, 120
- common packet channel, CPCH, 95, 112
- common pilot channel, 118
 - diversity, 118
 - primary, 118
 - secondary, 118
- common traffic channel, CTCH, 144
- common transport channels, 93
- congestion control, 259
- continuous packet connectivity (CPC), 456
- control plane, 73
- core network, 67
- coverage
 - AMR speech codec, 304
 - downlink, 311

- coverage (*continued*)
 - effect of antenna diversity, 308
 - effect of bit rate, 302
 - link budget, 177
- CS networks, 69
- Cu interface, 68
- cubic metric, 472, 513
- CWTS, 59
- cyclic prefix, 468, 469
- cyclic redundancy check, CRC, 109

- data link layer, 139
- data rates
 - downlink, 114
 - uplink, 109
 - HSDPA, 345
 - TDD, 485
- dedicated channel
 - downlink, 112
 - uplink, 106
- dedicated control channel, DCCH, 143
- dedicated physical control channel, DPCCH, 106, 112
- dedicated physical data channel, DPDCH, 106, 112
- dedicated traffic channel, DTCH, 144
- dedicated transport channel, DCH, 93
- despreading, 41
- dimensioning, 176
- direct tunnel, 460
- discontinuous transmission, 457
- discontinuous reception, 457
- downlink modulation, 103
 - synchronisation channel SCH, 105
- downlink scrambling, 104
 - primary scrambling codes, 105
 - secondary scrambling codes, 105
- downlink spreading, 103
 - downlink shared channel, DSCH, 104
 - synchronisation channel, SCH, 105
- dual channel QPSK, 99
- DVB-H, 440
- dynamic channel allocation, 292

- E-DCH absolute grant channel, 408, 412
- E-DCH HARQ indicator channel, 408, 411
- E-DCH relative grant channel, 408, 412
- E-DCH, 404
- EDGE, 4, 61
- EGSM, 4
- email, 16
- enhanced DPCCH, 408
- enhanced DPDCH, 408
- enhanced FACH, 446
- enhanced uplink DCH, E-DCH, 404
- equalizer, 397, 441, 453

- erlang, 194
- ETSI, 54

- fast fading margin, 177
- fast power control, 224
- FFT, 468
- flat architecture, 459, 466
- flexible RLC, 450
- forward access channel, FACH, 94, 120, 143, 187
 - user data transmission, 116
- fractional DPCCH, 399
- frame protocol, FP, 81
- FRAMES, 53
- frequency accuracy, 106
- frequency domain generation, 471

- gaming, 21
- GGSN, 69
- GMSC, 69
- GSM core network, CN, 69

- H.263, 14
- H.324M, 14
- handover, 237
 - active set update rate, 246
 - algorithm, 237
 - compressed mode, 129
 - GSM, 129
 - inter-frequency, 250
 - inter-mode, 129
 - inter-system, 129, 246
 - intra-mode, 128
 - measurement procedure, 129
 - soft handover gains, 241, 306
 - soft handover probabilities, 244
 - soft handover, 128
- happy bit, 411
- hard handover, 165
- high speed dedicated physical control channel, HS-DPCCH, 368
- high speed downlink packet access, HSDPA, 363
- high speed downlink shared channel, HS-DSCH, 364, 368
- high speed shared control channel HS-SCCH, 368
- high speed uplink packet access, HSUPA, 363
- home location register, HLR, 69
- home subscriber server, HSS, 88, 467
- HS-DPCCH pre/post-amble, 399
- HSDPA link budget, 393
- HSPA+, 445
- HSUPA link budget, 393
- HSUPA link budget, 419

- HSUPA retransmission, 405
- HSUPA scheduling, 413, 417

- IFFT, 468
- IMT-2000, 62
- IMT-RSCP, 63
 - ITU-R TG8/1, 62
- integrity protection of signalling, 157
- interference cancellation, 350
- interference margin, 177
- interleaving
 - first, 110
 - second, 111
- inter-system cell reselection, 165
- inter-system handover, 165
- IP multimedia subsystem, IMS, 88
- IP RAN, 86
- I-Q multiplexing, 99
- IS-2000. *See* cdma2000
- IS-95, cdmaOne, 5
- Iu Interface, 70, 74
 - Iu CS, 74
 - Iu PS, 74
 - protocol stacks, 74
- Iub dimensioning, 396
- Iub dimensioning, HSPA, 396
- Iub dimensioning, MBMS, 438
- Iub interface, 70
- Iupc interface, 86
- Iur interface, 70, 80
- Iur-g interface, 86

- joint detection, *See* multiuser detection.

- link budget, 177
- link budget, HSPA, 393
- link budget, WCDMA, 177
- load
 - estimation of downlink load, 255
 - estimation of uplink load, 253
- load control, 259
- load factor, 180
- logical channels
 - broadcast control channel, BCCH, 143
 - common control channel, CCCH, 143
 - common traffic channel, CTCH, 144
 - dedicated control channel, DCCH, 143
 - dedicated traffic channel, DTCH, 144
 - mapping between logical channels and transport channels, 144
 - paging control channel, PCCH, 144
- logical O&M, 84
- LTE functional split, 465, 476
- LTE link budget, 480
- LTE multiple access, 464, 467
- LTE requirements, 463

- LTE RRC States, 477
- LTE RRC, 476

- MAC segmentation, 450
- maximal ratio combining, MRC, 46
- MBMS notification indicator channel (MICH), 431
- MBMS point-to-multipoint control channel (MCCH), 430
- MBMS point-to-multipoint scheduling channel (MSCH), 430
- MBMS point-to-multipoint traffic channel (MTCH), 430
- MBMS selective combining, 433
- MBMS soft combining, 433
- MBMS, 423
 - measurement control, 157
 - measurement reporting, 157
 - measurements, 131
 - media gateway control function, MGCF, 89
 - media resource function, MRF, 89
 - medium access control protocol, MAC, 140, 141
 - messaging, 16
- MMS, 15
- mobile equipment, ME, 68
- mobile services switching centre/visitor location register, MSC/VLR, 69
- mobile-TV, 423
- mobility management entity, 467
- MPEG-4, 14, 18
- multi-mode radio, 527
- multi-carrier CDMA. *See* cdma2000
- multicast, 425
- multimedia broadcast multicast service, MBMS, 152
- multipath diversity, 305
- multiple input multiple output (MIMO), 448, 465, 477
- multiplexing
 - downlink, 114
 - uplink, 109
- multiuser detection, 350

- NBAP, 83
- network planning
 - dimensioning, 176
 - GSM co-planning, 175
 - inter-operator interference, 281
 - optimisation, 198
- node B, 68
- noise rise, 177, 182

- ODMA, 56
- OFDMA, 56, 467
- Okumura-Hata, 179
- open loop power control, 124, 170

- orthogonal codes, 312
- outer loop power control, 182, 231
- OVSF codes, 97
- packet bundling, 459
- packet data convergence protocol, PDCP, 140, 150
- paging
 - channel, 94, 120
 - control channel, 143
 - indicator channel, 122
 - procedure, 124
- pay load unit, PU, 149
- PDN SAE Gateway, 465, 466
- phase discontinuity, 514
- physical downlink shared channel, 474
- physical uplink shared channel, 474
- PLMN, 68
- policy and charging rules function (PCRF)
- positioning, 27
 - A-GPS 30
 - network assisted GPS, 29
- power consumption, 456, 508, 513
- power control, 33
 - compressed mode, 123
 - CPCH, 124
 - fast closed loop, 123
 - fast, 224
 - headroom, 131
 - open loop, 124
 - outer loop, 231
 - RACH, 125
- power rise, 177
- processing gain, 43
- PS networks, 69
- Push-to-talk over cellular, PoC, 19, 288
- Quality of service, QoS, 29
- radio link control protocol, RLC, 145
 - acknowledged mode, AM, 146
 - transparent mode, Tr, 146
 - unacknowledged mode, UM, 146
- radio network controller, RNC, 70
 - drift RNC, 71
 - serving RNC, 72
- radio network sub-system, RNS, 71
- radio resource control protocol, RRC, 152
- Rake receiver, 44
- RANAP, 77
- random access channel, RACH, 94, 111, 121
- rate matching
 - downlink, 114
 - uplink, 106
- Rayleigh fading, 30
- receiver
 - downlink, 108
 - uplink, 107
- reciprocal channel, 282
- refarming, 2, 217
- resource block, 474
- RNSAP, 80
- round trip time, 268
- round trip time, HSPA, 397
- round trip time, WCDMA, 268
- S1_MME, 466
- S1_U, 466
- SAE architecture, 466
- SC-FDMA, 470
- scrambling, 96
- SDD, 485
- serving SAE gateway, 466
- SGSN, 69
- shared channel
 - downlink, 115
 - high speed, 363
- single frequency network (SFN), 440
- soft capacity, 194
- soft(er) handover, 50, 237
- spectrum allocation, 2
- spreading, 41
- streaming, 23
- sub-carrier spacing, 467, 473
- synchronisation channel, 105, 119
- TDD, 485
 - handovers, 498
 - user data rates, 495
- TD-SCDMA, 485
- terminal power consumption, 513
- time division duplex. *See* TDD
- TR46.1, 59
- traffic termination point, 83
- transmission control protocol, TCP, 261
- transmission time interval, TTI, 108, 110
- transmit diversity, 243
 - closed loop, 127
 - open loop, 113
 - TDD, 485
 - time-switched, 105
- transmitter noise leakage, 519
- transport channels, 92
- transport format and resource combination
 - TFRC, 377
- transport format combination indicator, TFCI, 92, 108
- transport format indicator, TFI, 92
- transport network control plane, 73
- transport network user plane, 74
- TTA, 58

- UMTS subscriber identity module, USIM, 68
- unicast, 425
- unlicensed mobile access (UMA), 21
- uplink modulation, 98
- uplink scrambling, 101
- uplink spreading, 101
- URA update, 155
- user equipment, UE, 67
- user plane, 73
- UTRA TDD. *See* TDD
- UTRA, 59
- UTRAN architecture, 68
- UTRAN radio network temporary identity
 - U-RNTI, 145
- UTRAN, 67
- uu interface, 70
- UWC-136, 58
- video sharing, 17
- virtual private network, VPN, 25
- voice over IP, VoIP, 21, 291, 458
- WARC, world administrative radio conference, 2
- WCDMA N/A, 58
- wideband TDMA, 55
- wideband TDMA/CDMA, 55
- windowing, 469
- WP-CDMA, 56
- X2 interface, 466, 477

