

Index

• Numerics •

100 Trying SIP response, 53
180 Ringing SIP response, 54
183 Session Progress SIP response, 54
200 OK SIP response, 54–55
300 Multiple Choices SIP response, 55
301 Moved Permanently SIP response, 55
302 Moved Temporarily SIP response, 55–56
305 Use Proxy SIP response, 56
380 Alternate Service SIP response, 56
400 Bad Request SIP response, 56
401 Unauthorized SIP response, 56
403 Forbidden SIP response, 56
404 Not Found SIP response, 56
405 Method Not Allowed SIP response, 56
408 Request Timeout SIP response, 56–57
410 Gone SIP response, 57
415 Unsupported Media Type SIP response, 57
480 Temporarily Unavailable SIP response, 57
487 Request Terminated SIP response, 57
500 Server Internal Error SIP response, 57
503 Service Unavailable SIP response, 57–58
504 Service Time-Out SIP response, 58
505 Version Not Supported SIP response, 58
600 Busy Everywhere SIP response, 58
603 Decline SIP response, 58
604 Does Not Exist Anywhere SIP response, 58
606 Not Acceptable SIP response, 58
911 calls, 145–146

• A •

access codes, 288
access fees, 16–17
accounts, resold, 32–33
ACK method, 46–47
activating
 billing structure, 177–178
 deployment report, 176–177
 overview, 165
 scheduling install, 166
 test plan, 166–176
active call, 168
additive noise, 118
ALG (Application Level Gateway), 301
“all circuits are busy” message, 258
analog cards, 333
analog phones
 analog phone call compared with VoIP
 phone call, 10–11
 line bypass, 287–288
 testing, 174–175
Analog Telephone Adapter (ATA), 21–22, 150
analyzing
 bandwidth, 107–109
 call quality, 262–263
 call route, 191–193
 calling profile, 153–154
 calls, 335–336
 intermittent problems, 141
 network design, 100–102
 non-network problems, 142
 stare and compare, 254
 systemic problems, 139–140
ANI (Automatic Number Identifier), 161
Application layer, 118–119
Application Level Gateway (ALG), 301

- area codes
 - North American dialing plan, 90–91
 - overlay, 36, 265
 - split, 265
- assessment reports, 199–200
- Asterisk/AsteriskNOW
 - benefits, 22–23
 - disadvantages, 323
 - software, 18
 - Web site, 18, 334
 - wiki Web site, 358
- ATA (Analog Telephone Adapter), 21–22, 150
- AT&T access code, 288
- attributes
 - providing unique, 65–68
 - ptime, 70–71
 - sendrcv, 72
- audio
 - gain, 262
 - no-way, 303
 - one-way, 299–303, 345–346
- Automatic Number Identifier (ANI), 161

• B •

- bandwidth
 - analyzing, 107–109
 - for call forwarding, 12
 - consumption, 140
 - handling latency with prioritization, 110–111
 - managing, 109–114
 - myths, 15, 317–319
 - overview, 107
 - Re-INVITE method to reduce, 76
 - relationship with access fees, 16–17
 - resolving latency with packet shaping, 111
 - separating VoIP from data with subnets, 112–113
- Simple Network Management Protocol (SNMP), 108
- T1, 332

- VLAN (Virtual LAN), 113–114
- VoIP compression, 331
- VoIP and traditional use, 318
- wasted, 77
- Wireshark, 109
- billing increments, 95
- billing structure, 177–178
- Billing Telephone Number (BTN), 31–32, 161
- Boolean values, 135
- branding transmissions with Caller ID, 44
- BTN (Billing Telephone Number), 31–32, 161
- buffers, 105
- Bus LAN, 100–101
- busy signal
 - confirming treatment for, 169–170
 - fast, 259
- BYE method
 - compared with CANCEL method, 210–211
 - ending calls with, 48
- bypassing
 - analog line, 287–288
 - Internet providers, 284–286
 - VoIP carrier, 286–287

• C •

- calculating, calls per second, 125–128
- Call Detail Records (CDR)
 - analyzing calls with, 335–336
 - components, 124
 - using, 94–95
- call examples
 - defined, 275
 - providing, 275–279
 - shelf life, 276
 - VoIP-specific requirements, 277
- call forwarding
 - limiting, 44
 - problems, 12–13
 - using VoIP for, 92

- call plan
 - advanced phone features, 86–95
 - basic phone features, 82–86
 - overview, 80–82
 - phone system, 79–82
 - validating features, 175–176
- call quality
 - analyzing, 262–263
 - due diligence, 268–269
 - evaluating with MOS, 190
 - myths, 320–321
 - problems, 142
 - relationship with codecs, 72
- call route analysis, 191–193
- call volume
 - determining peak, 123–125
 - overview, 158–159
- Called Party Number (CPN), 161
- Caller ID
 - advantages, 142–144
 - branding transmissions with, 44
 - disadvantages, 142–144
 - manipulating, 343–345
 - troubleshooting, 309–311
- calling profile, 153–154
- calls. *See* phone calls
- calls per second, calculating, 125–128
- CANCEL method
 - canceling SIP calls with, 210–214
 - compared with BYE method, 210–211
 - ending calls with, 48
- canceling SIP calls, 210–214
- capture
 - listening to in Wireshark, 237–238
 - locating touch tones, 238–240
 - packets remotely, 195–197
 - with tcpdump, 220, 226–228
 - with Wireshark, 220, 228–229
- cards
 - analog, 333
 - Digium interface, 23
 - interface, 80
- carriers
 - bypassing, 286–287
 - local, 329–330
 - long-distance, 288, 326–327
 - relationships, 348–349
 - support, 362–363
 - trouble reporting structure, 274–275
 - uniformity of process, 350–351
- carryover, relationship with CDR, 95
- CDR. *See* Call Detail Records (CDR)
- cell phone, identifying global problems
 - with, 293–294
- central office (CO)
 - reallocation to new, 266
 - relationship with call routing, 261
- change fees, 34
- checking
 - fax transmission, 170–171
 - T.38 fax calls in Wireshark, 240–243
 - voicemail, 175–176
- choosing
 - codecs, 156
 - fax choices, 160
 - IP provider, 158
 - protocol, 155–156
- class 4 switch, 145–146
- class 5 switch, 145–146
- clipping
 - calls, 262–263
 - defined, 71
- CO. *See* central office (CO)
- codecs
 - elements, 72
 - Mean Opinion Score (MOS), 73–74
 - overview, 72–74
 - selection, 156
 - types, 73, 318
 - using, 74–78
- comfort noise, 119
- compatibility
 - myths, 18–19, 321–322
 - Wireshark, 220–221
- completed calls, reviewing, 206–209
- complexity myths, 322–324
- compressed VoIP charges, 17
- compression
 - ratio of codecs, 74
 - VoIP, 331

- computer programming, 339
 - conference calls, 83–84
 - configuration information
 - call volume details, 158–159
 - listing servers, 154–155
 - local loop replacement, 148–149
 - ordering VoIP, 150–151
 - overview, 147
 - signaling basics, 155–158
 - standard usage, 151–154
 - confirming
 - billing structure, 177–178
 - privacy, 162–164
 - treatment for busy calls, 169–170
 - treatment for failed calls, 169–170
 - connection, host, 111
 - console mode, 94
 - consumption of bandwidth, 140
 - contracts, 353
 - costs
 - access fees, 16–17
 - hardware costs, 17
 - hidden, 347–348
 - Internet port, 317
 - LNP (Local Number Portability), 33–35
 - local loop, 317
 - myths, 15–16, 315–317
 - overview, 16
 - CPN (Called Party Number), 161
 - creating, one-way audio, 345–346
 - customer service, first-tier, 274–275
- **D** •
- Daisy Chain LAN, 100–101
 - Data Link, 116–117
 - datagrams, 117
 - dead air, 259
 - deconstructing local calls, 254–257
 - Denial of Service (DOS)
 - attacks, 341–343
 - relationship with overloaded servers, 14
 - deployment
 - Packet Island software, 182
 - report, 176–177
 - deprecates, 129
 - design
 - analyzing network, 100–102
 - basic LAN, 100–101
 - process of VoIP, 138–139
 - desired noise, 119
 - determining
 - MOS (Mean Opinion Score), 121–122
 - peak call volume, 123–125
 - devices
 - managing, 108
 - Packet Loss Concealment (PLC), 105
 - dial plan
 - advanced phone features, 86–95
 - basic phone features, 82–86
 - overview, 80–82
 - phone system, 79–82
 - validating features, 175–176
 - dialing
 - calls, 157
 - toll-free numbers, 145–146
 - Digium interface cards, 23
 - distribution (distro), 222
 - DNC (Do Not Call) list, 162
 - DNS (Domain Name System), 42
 - Do Not Call (DNC) list, 162
 - Domain Name System (DNS), 42
 - DOS. *See* Denial of Service (DOS)
 - double-clicking, 183
 - downloading
 - Wireshark for Linux, 222–224
 - Wireshark for Windows, 221–222
 - dropped calls, 260–261
 - DS-1 benchmark, 126
 - DS-3 benchmark, 126
 - DTMF (Dual Tone Multi Frequency)
 - In-band transmission, 128
 - locating tones, 238–240
 - problems, 306–307
 - tones, 28, 66–68, 128–129

Dual Tone Multi Frequency. *See* DTMF
(Dual Tone Multi Frequency)
due diligence, performing, 267–269

● E ●

E.164 industry standard, 43, 157
e-bonded, 29
echo, 262
echo cancellers (echo cans), 262
end user of record, 33
Enterprise gateway, 21
environment, 19–20
error messages, 258
escalation list
 sample, 364
 support, 363–365
 trouble tickets, 281–282
establishing, telephone-event
 parameters, 71–72
estimating usage, 352–353
Ethereal. *See* Wireshark
evaluating
 call quality with MOS, 190
 network, 197–199
extensions
 building, 86
 Wireshark, 221

● F ●

failed calls, 169–170
fast busy signal, 259
fax requirements
 overview, 129
 sending uncompressed FoIP with G.711,
 129–130
 T.37, 130–131
 T.38, 131–135
fax transmissions
 checking, 170–171
 over VoIP, 28
 selecting choices, 160
Feature Server, 25–26

fees
 access, 16–17
 change/modification, 34
 installation, 34
 LNP (Local Number Portability), 34
 migrating, 34
 monthly recurring, 34
fiber cut, 265–266
fill bit removal T.38 fax parameter, 133
filtering calls, 236–237
find-me-follow-me service, 333
finding
 touch tones in captures, 238–240
 VoIP calls, 232–238
firewall traversal options, 301–303
first-tier customer service, 274–275
500 Server Internal Error SIP
 response, 57
503 Service Unavailable SIP response,
 57–58
504 Service Time-Out SIP response, 58
505 Version Not Supported SIP
 response, 58
flap, 106–107
FoIP (Fax over Internet Protocol),
 129–130
Foreign Exchange Office (FXO) ports, 23
Foreign Exchange Station (FXS) ports, 23
forwarding
 limiting, 44
 problems, 12–13
 using VoIP for, 92
400 Bad Request SIP response, 56
401 Unauthorized SIP response, 56
403 Forbidden SIP response, 56
404 Not Found SIP response, 56
405 Method Not Allowed SIP
 response, 56
408 Request Timeout SIP response,
 56–57
410 Gone SIP response, 57
415 Unsupported Media Type SIP
 response, 57

- 480 Temporarily Unavailable SIP response, 57
- 487 Request Terminated SIP response, 57
- frequency of call problems, 263–265
- fully integrated VoIP and data network, 23–24
- future of VoIP, 339–340
- FXO (Foreign Exchange Office) ports, 23
- FXS (Foreign Exchange Station) ports, 23

• G •

- G.711
 - sending uncompressed FoIP with, 129–130
 - using RFC2833 with, 159
- gateways, 21
- gathering media-level information, 63–68
- generating assessment reports, 199–200
- graphing calls in Wireshark, 234–236
- growing with VoIP, 331–333

• H •

- H.323
 - Gatekeeper, 38
 - overview, 38–39
- Hall, Jon, *Red Hat Fedora Linux 2 For Dummies*, 2
- handling
 - bandwidth, 109–114
 - calls with Packet Island, 203
 - devices, 108
 - latency, 103–107
 - one-way audio, 299–303
 - systemic problems, 139–140
 - touch tones, 128–129
 - trouble tickets, 279–282
- hardware
 - costs, 17
 - gateways, 21–22
 - LAN, 20
 - nodes, 24
 - overview, 21–24, 332–333

- phone system, 80
- servers, 25–28
- SIP end points, 24–25
- header
 - message, 43–44
 - privacy, 162
- help. *See* support
- hidden costs, 347–348
- host connection, 111

• I •

- ICE (Interactive Communications Establishment), 302–303
- ICMP traffic flow, 193
- icons used in this book, 4
- identifying
 - frequency of call problems, 263–265
 - global problems with cell phone, 293–294
 - variables, 251–257
- IEEE Computer Society Digital Library, 105
- IETF (Internet Engineering Task Force)
 - Web site, 205
- IMT (Inter Machine Trunk) failure, 308
- In-band transmission, 128
- inbound calls
 - checking source, 295–297
 - identifying global problems with cell phone, 293–294
 - problems, 305–306
 - provisioning, 294–295
 - routing, 91
 - toll-free, 292
 - troubleshooting, 291–297
- industry contacts, 356–357
- industry diplomacy, 340
- industry standards, E.164, 43, 157
- installing
 - fees, 34
 - scheduling, 166
 - tcpdump, 225–226
 - Wireshark, 221–224

- Inter Machine Trunk (IMT) failure, 308
 - Interactive Communications
 - Establishment (ICE), 302–303
 - Interactive Voice Response (IVR)
 - system, 92
 - interface card, 80
 - intermittent problems, 278–279
 - international problems, 290–291
 - international standards, 205–206
 - Internet
 - port cost, 317
 - support, 358–359
 - Internet Engineering Task Force (IETF)
 - Web site, 205
 - Internet Protocol. *See* IP (Internet Protocol)
 - Internet providers, bypassing, 284–286
 - InterOperability (InterOp) testing, 18, 351–352
 - INVITE method
 - allowing methods, 44
 - Call ID, 44
 - investigating Request-Line, 41–43
 - limiting forwarding, 44
 - Message Header, 43–44
 - overview, 40–41
 - Re-INVITE, 45
 - T.38 fax, 132–133
 - IP (Internet Protocol)
 - choosing providers, 158
 - overview, 43–44
 - priority levels, 110
 - sending, 117
 - isolating patterns, 265–267
 - issues. *See also* troubleshooting
 - call completion, 142, 257–261
 - call forwarding, 12–13
 - call quality, 142
 - cell phone, 293–294
 - DTMF (Dual Tone Multi Frequency), 306–307
 - frequency, 263–265
 - intermittent, 141
 - international, 290–291
 - LAN (Local Area Network) failure, 307–308
 - non-network, 142
 - non-voice, 306–307
 - systemic, 139–140
 - IVR (Interactive Voice Response)
 - system, 92
- 1 ●
- JIP (Jurisdictional Indicator Parameter), 144, 161
 - jitter
 - buffers, 105
 - defined, 187
 - LAN testing, 136–137
 - latency, 105
 - seeing, 187–188
 - Jurisdictional Indicator Parameter (JIP), 144, 161
- L ●
- lag, 95
 - LAN (Local Area Network)
 - converging technology, 336–337
 - design, 100–101, 339
 - failure problems, 307–308
 - hardware challenges, 20
 - packet loss on, 188–190
 - reporting on, 199–203
 - transmission types, 110
 - LAN (Local Area Network) testing
 - jitter, 136–137
 - latency, 136
 - overview, 135–136
 - packet loss, 137–138
 - latency
 - defined, 12, 103
 - flap, 106–107
 - handling with prioritization, 110–111
 - jitter, 105
 - LAN testing, 136
 - network, 103–107

- latency (*continued*)
 - overview, 103
 - pinging, 103–104
 - resolving with packet shaping, 111
- layers
 - Application, 118–119
 - Media, 116–117
 - Network, 117
 - Physical, 116
 - Presentation, 118–119
 - Session, 118–119
 - Transport, 117–118
- LCR. *See* Least Cost Routing (LCR)
- Least Cost Routing (LCR)
 - overview, 86–89, 305
 - preventing fraud, 89–91
 - routing incoming callers, 91
- LERG (Local Exchange Routing Guide)
 - database, 87
- Letter of Authorization (LOA), 29
- Line LAN, 100–101
- Linux
 - downloading Wireshark for, 222–224
 - YUM development tool package, 223
- listening
 - to captures in Wireshark, 237–238
 - for tones and tags, 258–259
- listing servers, 154–155
- LNP (Local Number Portability)
 - advantage of VoIP, 337–338
 - costs, 33–35
 - defined, 29
 - process, 30
 - rejections, 31–32
 - resold accounts, 32–33
 - responsibilities, 35–36
 - tips, 29–30
- LOA (Letter of Authorization), 29
- local calls
 - deconstructing, 254–257
 - Web site guide, 88
- local carriers, 329–330
- Local Exchange Routing Guide (LERG)
 - database, 87

- local loop
 - cost, 317
 - defined, 16, 149
 - VoIP replacing, 148–149
- Local Number Portability. *See* LNP (Local Number Portability)
- local users group, 359–360
- locating, VoIP calls, 232–238
- locating touch tones in captures, 238–240
- long-distance calls
 - manipulating Caller ID for cheaper, 343–345
 - reviewing outbound, 251–253
- long-distance carriers
 - calling out over, 288
 - myths, 326–327

• M •

- m (media-level description), 61–62
- managing
 - bandwidth, 109–114
 - calls with Packet Island, 203
 - devices, 108
 - latency, 103–107
 - one-way audio, 299–303
 - systemic problems, 139–140
 - touch tones, 128–129
 - trouble tickets, 279–282
- manipulating Caller ID, 343–345
- manual configuration, 302
- max bit rate T.38 fax parameter, 133
- max buffer T.38 fax parameter, 134
- max datagram T.38 fax parameter, 134
- maximum concurrent calls, 124
- Mean Opinion Score. *See* MOS (Mean Opinion Score)
- media
 - defined, 10, 60
 - overview, 63–65
 - transmitting with SDP, 60–82
- Media Layer, 116–117
- Media-level description (m), 61–62

Message Header, 43–44
 messages (error), 258
 methods
 BYE, 48, 210–211
 CANCEL, 48, 210–214
 INVITE, 40–45, 132–133
 NOTIFY, 51–52
 OPTIONS, 49–50
 PINT, 51–52
 PRACK, 51–52
 Re-INVITE, 45, 75–76, 214–217
 REFER, 45–46
 REGISTER, 47–48
 SUBSCRIBE, 51–52
 UNSUBSCRIBE, 51–52
 UPDATE, 50
 migrating
 fees, 34
 phone numbers, 34–35, 337–338
 Minutes of Usage (MOU) report, 153
 Misc traffic flow, 193
 modes, console, 94
 modification fees, 34
 monitoring traffic flows, 193–195
 monthly recurring fees, 34
 MOS (Mean Opinion Score)
 for codecs, 73–74
 determining, 121–122
 evaluating call quality with, 190
 MOU (Minutes of Usage) report, 153
 moving phone number(s), 34–35, 337–338
 multi-node calls, 209–210
 myths
 bandwidth, 15, 317–319
 call quality, 320–321
 compatibility, 18–19, 321–322
 complexity, 322–324
 cost, 15–16, 315–317
 long-distance carriers, 326–327
 non-VoIP phone features, 327–328
 phone bill, 325–326
 quality, 19

route path, 319–320
 troubleshooting, 324–325

• N •

NAT (Network Address Translation)
 firewall traversal options, 301–303
 overview, 300–301
 network
 analyzing bandwidth, 107–109
 analyzing design, 100–102
 evaluating, 197–199
 gateway, 21
 latency, 103–107
 managing bandwidth, 109–114
 MOS (Mean Opinion Score), 121–122
 OSI Model, 114–121
 outage, 265–266
 overview, 99
 VoIP Lifecycle Management (VLM), 102–103
 Network Address Translation. *See* NAT (Network Address Translation)
 network analysis
 intermittent problems, 141
 non-network problems, 142
 overview, 139
 retesting, 141–142
 systemic problems, 139–140
 Network Layer, 117
 Network Management System (NMS), 108
 Network OSI Model
 Application layer, 118–119
 first layer, 116
 overview, 114–116
 Presentation layer, 118–119
 second layer, 116–117
 Session Layer, 118–119
 third layer, 117
 transmitting UDP on fourth layer, 117–118
 911 calls, 145–146
 NMS (Network Management System), 108

- nodes, 24
- noise types, 118–119
- non-network problems, 142
- nonpromiscuous mode monitoring, 227
- non-traditional troubleshooting, 360–362
- non-voice features
 - opening up SIP-T, 160–161
 - overview, 159, 159–161
 - privacy, 162–164
 - selecting fax choice, 160
- non-voice problems, 306–307
- non-VoIP phone features, 327–328
- North American dialing plan area codes, 90–91
- NOTIFY method, 51–52
- no-way audio, 303
- “the number you have called has been disconnected or is no longer in service” message, 258

● 0 ●

- Olejniczak, Stephen, *Telecom For Dummies*, 11, 161, 282
- 100 Trying SIP response, 53
- 180 Ringing SIP response, 54
- 183 Session Progress SIP response, 54
- one-way audio
 - creating, 345–346
 - managing, 299–303
- opening up SIP-T, 160–161
- OPTIONS method, 49–50
- ordering
 - new phone numbers, 36
 - VoIP, 150–151
- organization of this book, 3–4
- OSI Model
 - Application layer, 118–119
 - first layer, 116
 - overview, 114–116
 - Presentation layer, 118–119
 - second layer, 116–117
 - Session layer, 118–119
 - third layer, 117

- transmitting UDP on fourth layer, 117–118
- out call setup, 168–169
- outbound calls
 - failures, 304
 - over another long-distance carrier, 288
 - troubleshooting, 282–291
 - troubleshooting international problems, 290–291
- Out-of band RFC2833, 129
- overhead
 - defined, 269
 - of phone calls, 10–11
- overlay area code, 36, 265
- over-modulation, 119

● p ●

- packet capture
 - listening to in Wireshark, 237–238
 - locating touch tones, 238–240
 - remote, 195–197
 - with tcpdump, 220, 226–228
 - with Wireshark, 220, 228–229, 306
- Packet Island GUI
 - call quality, 190
 - jitter, 187–188
 - overview, 182–185
 - packet loss, 188–190
 - packets per second, 186–187
 - stream info, 191
- Packet Island VoIP Lifecycle
 - Management software. *See also* Packet Island GUI
 - analyzing Call Route, 191–193
 - deploying, 182
 - evaluating VoIP network, 197–199
 - managing calls with, 203
 - overview, 179–181
 - recommendations, 120, 136
 - remotely capturing packets, 195–197
 - reporting on VoIP LAN, 199–203
 - traffic flows, 193–195
 - Web site, 180, 324

- packet loss
 - on LAN, 188–190
 - LAN testing, 137–138
 - Packet Loss Concealment (PLC)
 - devices, 105
- Packet Loss Concealment (PLC) devices, 105
- packet sampling size, 156
- packet shaping, 111
- Packets Per Second (PPS)
 - overview, 20
 - reading, 186–187
- parameters
 - establishing telephone-event, 71–72
 - JIP (Jurisdictional Indicator Parameter), 144, 161
 - T.38 fax, 133–134
- P-Asserted-ID (PAID), 162–164
- pattern isolation, 265–267
- pattern matching
 - to prevent fraud, 89–91
 - routing incoming callers, 91
- payload
 - defined, 10
 - types (PT), 64–65
- Payphone Service Provider (PSP), 161
- PDD (Post-Dial-Delay), 53, 259
- performance monitors (PMs), 263
- performing due diligence, 267–269
- permissive dialing period, 266
- phone bill
 - billing increments, 95
 - billing structure, 177–178
 - myths, 325–326
- phone calls
 - active, 168
 - analog compared with VoIP, 10–11
 - analyzing, 335–336
 - canceling SIP, 210–214
 - clipping, 71, 262–263
 - completion due diligence steps, 268
 - completion problems, 142, 257–261
 - components, 10–11
 - conference, 83–84
 - deconstructing local, 254–257
 - dialing, 157
 - dropped, 260–261
 - ending with BYE method, 48
 - ending with CANCEL method, 48
 - failed, 169–170
 - filtering, 236–237
 - graphing in Wireshark, 234–236
 - inbound, 91, 291–297, 305–306
 - local, 88, 254–257
 - long-distance, 251–253, 343–345
 - maximum concurrent, 124
 - outbound, 282–291, 304
 - overhead, 10–11, 269
 - problem frequency, 263–265
 - queue, 84–86
 - redirected, 14
 - reviewing completed, 206–209
 - reviewing long-distance outbound, 251–253
 - routing, 261
 - setup, 10
 - toll-free, 292
 - treatment, 257
 - troubleshooting outbound, 282–291
 - viewing multi-node, 209–210
 - volume, 158–159
- phone features
 - Call Detail Records (CDR), 94–95, 124, 335–336
 - call forward, 12–13, 44, 92
 - call queue, 84–86
 - conference calls, 83–84
 - console mode, 94
 - extension, 86
 - Interactive Voice Response (IVR)
 - system, 92
 - Least Cost Routing, 86–91, 305
 - non-VoIP, 326–327
 - voicemail, 82–83, 175–176
 - X10, 93
- phone numbers
 - area codes, 36, 90–91, 265
 - BTN (Billing Telephone Number), 31–32, 161

- phone numbers (*continued*)
 - moving, 337–338
 - ordering new, 36
 - porting, 29–36
 - prefix, 36
 - phone system
 - overview, 79–82
 - taking control, 334–335
 - phones
 - analog, 10–11, 174–175, 287–288
 - cell, 293–294
 - Physical layer, 116
 - PIC (Primary Interexchange Carrier)
 - Freeze, 32
 - picking up dropped calls, 260–261
 - pinging, 103–104
 - PINT method, 51–52
 - PLC (Packet Loss Concealment) devices, 105
 - plug-ins (Wireshark), 221
 - PMs (performance monitors), 263
 - Point to Point LAN, 100–101
 - porting phone numbers, 29–36
 - ports
 - Foreign Exchange Office (FXO), 23
 - Foreign Exchange Station (FXS), 23
 - Internet, 317
 - signaling, 156
 - transmission, 111
 - validating quality, 152
 - Post-Dial-Delay (PDD), 53, 259
 - PPS. *See* Packets Per Second (PPS)
 - PRACK method, 50
 - prefix, 36
 - Presentation Layer, 118–119
 - Primary Interexchange Carrier (PIC)
 - Freeze, 32
 - privacy
 - confirming, 162–164
 - header, 162
 - problems. *See also* troubleshooting
 - call completion, 142, 257–261
 - call forwarding, 12–13
 - call quality, 142
 - cell phone, 293–294
 - DTMF (Dual Tone Multi Frequency), 306–307
 - frequency, 263–265
 - intermittent, 141
 - international, 290–291
 - LAN (Local Area Network) failure, 307–308
 - non-network, 142
 - non-voice, 306–307
 - systemic, 139–140
 - processing
 - codecs, 72–78
 - software programs, 59
 - profile, calling, 153–154
 - programming, 339
 - promiscuous mode monitoring, 227
 - propagation delay, 74
 - protocol
 - choosing, 155–156
 - traditional telephony calls, 11
 - tree (Wireshark), 232
 - providing
 - call examples, 275–279
 - unique attributes, 65–68
 - proving
 - out call setup, 168–169
 - tear-down, 168–169
 - proxy server
 - defined, 26
 - SIP, 26–28
 - PSP (Payphone Service Provider), 161
 - PSTN (Public Switched Telephone Network), 21–22
 - PT (payload types), 64–65
 - p*time attribute, 70–71
 - Public Switched Telephone Network (PSTN), 21–22
 - purchasing analog cards, 333
- *Q* •
- QoS (Quality of Service), 158, 191
 - quality
 - myths, 19
 - validating port, 152

Quality of Service (QoS), 158, 191
 queue, call, 84–86
 Qwest access code, 288

• **R** •

rate management T.38 fax parameter, 134
 rate shaping, 111, 195
 Rawshark, 221
 Re-INVITE method
 G.729 with Proxy server, 75
 overview, 214–217
 Proxy unable to, 77–78
 to reduce bandwidth, 76
 sending, 45
 reading packets per second, 186–187
 reallocation to new central office (CO), 266
 real-time MOS score, 121–122
 Real-Time Transport Protocol. *See* RTP (Real-Time Transport Protocol)
 recordings, 260
Red Hat Fedora Linux 2 For Dummies (Hall and Sery), 2
 redirected VoIP call, 14
 REFER method, 45–46
 REGISTER method, 47–48
 rejections, LNP (Local Number Portability), 31–32
 remote packet capture, 195–197
 Remote Party ID (RPID), 162–164
 reporting
 structure, 274–275
 on VoIP LAN, 199–203
 reports
 activating deployment, 176–177
 assessment, 199–200
 MOU (Minutes of Usage), 153
 requesting deployment, 176–177
 SLA (Service Level Agreement), 202–203
 verification, 200–201
 Verify (Standard), 199
 VoIP Assess (Premium), 199

VoIP Assess (Standard), 199
 VoIP SLA (Standard), 199
 Request For Comments (RFCs), 18, 205–206, 357–358
 requesting deployment reports, 176–177
 Request-Line, 41–43
 requirements
 fax, 129–135
 VoIP-specific, 277
 resold accounts, 32–33
 retesting, 141–142
 reviewing
 completed calls, 206–209
 outbound long-distance calls, 251–253
 RFC2833, 159
 RFCs (Request For Comments), 18, 205–206, 357–358
 Ring LAN, 100–101
 route path myths, 319–320
 routing
 calls, 261
 incoming callers, 91
 RPID (Remote Party ID), 162–164
 RTP (Real-Time Transport Protocol)
 overview, 59
 payload types (PT), 64–65

• **S** •

SBC (Session Boarder Controller)
 capacity restrictions, 128
 deploying, 301
 failure, 308
 scheduling installs, 166
 SDP (Secession Depletion Protocol)
 gathering media-level information, 63–68
 overview, 59, 60–61
 responding to, 69–72
 session, 61–63
 transmitting media, 60–82
 Secession Depletion Protocol. *See* SDP (Secession Depletion Protocol)

- Seccession Initiation Protocol. *See* SIP (Seccession Initiation Protocol)
- seeing jitter, 187–188
- selecting
 - codecs, 156
 - fax choice, 160
 - IP providers, 158
 - protocol, 155–156
- sending
 - IP (Internet Protocol), 117
 - Re-INVITES, 45
 - uncompressed FoIP with G.711, 129–130
- sendrcv attribute, 72
- separating VoIP from data with subnets, 112–113
- servers
 - Feature Server, 25–26
 - listing, 154–155
 - overloaded, 14
 - overview, 25
 - SIP Proxy, 26–28
 - SIP Registrar, 25
- Service Level Agreement (SLA) report, 202–203
- Sery, Paul G., *Red Hat Fedora Linux 2 For Dummies*, 2
- Session Boarder Controller. *See* SBC (Session Boarder Controller)
- Session Layer, 118–119
- Session-level description, 61–62
- setup
 - call, 10
 - out call, 168–169
 - T.38 specifics, 133–135
- shelf-life of call examples, 276
- showing stream info, 191
- signaling. *See also* SIP (Seccession Initiation Protocol)
 - choices, 37–40
 - choosing IP providers, 158
 - choosing protocols, 155–156
 - how to dial, 157
 - overview, 155
 - port, 156
 - specifics, 156
 - telephony, 80
- Signaling System 7 (SS7), 160–161
- signing off methods, 48
- Simple Network Management Protocol (SNMP), 108
- Simple Traversal of UDP through NAT (STUN), 302
- SIP (Seccession Initiation Protocol). *See also* SIP (Seccession Initiation Protocol) methods; SIP (Seccession Initiation Protocol) responses
 - call trees, 217
 - canceling calls, 210–214
 - end points, 24–25
 - hardphone, 25
 - info method of DTMF, 129
 - node, 24
 - overview, 38–40
 - Proxy, 26–28, 157
 - Registrar, 25
 - SIP-T, 160–161
 - softphone, 25
 - User Agents (UA), 24
- SIP (Seccession Initiation Protocol) methods. *See also* SIP (Seccession Initiation Protocol) responses
 - ACK, 46–47
 - BYE, 48, 210–211
 - CANCEL, 48, 210–214
 - INVITE, 40–45, 214–217
 - NOTIFY, 51–52
 - OPTIONS, 49–50
 - overview, 39
 - PINT, 51–52
 - PRACK, 50
 - REFER, 45–46
 - REGISTER, 47–48
 - SUBSCRIBE, 51–52
 - UNSUBSCRIBE, 51–52
 - UPDATE, 50

- SIP (Seccession Initiation Protocol)
 - responses. *See also* SIP (Seccession Initiation Protocol) methods
 - 100 Trying, 53
 - 180 Ringing, 54
 - 183 Session Progress, 54
 - 200 OK, 54–55
 - 300 Multiple Choices, 55
 - 301 Moved Permanently, 55
 - 302 Moved Temporarily, 55–56
 - 305 Use Proxy, 56
 - 380 Alternate Service, 56
 - 400 Bad Request, 56
 - 401 Unauthorized, 56
 - 403 Forbidden, 56
 - 404 Not Found, 56
 - 405 Method Not Allowed, 56
 - 408 Request Timeout, 56–57
 - 410 Gone, 57
 - 415 Unsupported Media Type, 57
 - 480 Temporarily Unavailable, 57
 - 487 Request Terminated, 57
 - 500 Server Internal Error, 57
 - 503 Service Unavailable, 57–58
 - 504 Service Time-Out, 58
 - 505 Version Not Supported, 58
 - 600 Busy Everywhere, 58
 - 603 Decline, 58
 - 604 Does Not Exist Anywhere, 58
 - 606 Not Acceptable, 58
 - codes, 39
 - overview, 52–53
 - 600 Busy Everywhere SIP response, 58
 - 603 Decline SIP response, 58
 - 604 Does Not Exist Anywhere SIP response, 58
 - 606 Not Acceptable SIP response, 58
 - SLA (Service Level Agreement) report, 202–203
 - Snapback process, 34
 - SNMP (Simple Network Management Protocol), 108
 - softphone
 - hardphone, 25
 - SIP, 25
 - software. *See also* Packet Island VoIP Lifecycle Management software; Wireshark
 - Asterisk/AsteriskNOW, 18
 - Call Plan, 80–82
 - Packet Island VoIP Lifecycle Management, 120
 - packet-capturing, 226–229
 - processing, 59
 - T.38 fax parameter, 133
 - tcpdump, 220
 - X10, 93
 - split area codes, 265
 - Sprint access code, 288
 - SS7 (Signaling System 7), 160–161
 - standard usage
 - calling profile, 153–154
 - overview, 151–152
 - port quantity, 152
 - standards
 - E.164 industry, 43, 157
 - international, 205–206
 - Star LAN, 100
 - stare and compare analysis, 254
 - static, 263
 - stream info, 191
 - structure
 - billing, 177–178
 - VoIP compared with traditional telephone calls, 12
 - STUN (Simple Traversal of UDP through NAT), 302
 - subnets, separating VoIP from data with, 112–113
 - SUBSCRIBE method, 51–52
 - subtractive noise, 118–119
 - summary metrics, 121
 - Summary window (Wireshark), 231
 - support
 - escalation list, 363–365
 - industry contacts, 356–357
 - Internet, 358–359
 - local users group, 359–360
 - non-traditional, 360–362
 - overview, 355

support (*continued*)

RFCs, 357–358

starting over, 365–366

vendors, 356

VoIP carrier, 362–363

wiki, 359

switches, 145–146

systemic problems, 139–140

• T •

T1 bandwidth, 332

T.37 fax, 130–131

T.38 fax

checking, 170–171

checking in Wireshark, 240–243

INVITE, 132–133

overview, 131–132

parameters, 133–135

setting up specifics, 133–135

tree, 172

tags, 258–259

TCP (Transmission Control Protocol)

overview, 20, 43–44

traffic flow, 193

tcpdump. *See also* Wireshark

capturing packets with, 220, 226–228

installing, 225–226

software, 220

Web site, 225

teardown

overview, 10

proving, 168–169

Telecom For Dummies (Olejniczak), 11, 161, 282

Telecordia Web site, 87

telemarketing companies. *See* Caller ID

telephone bill

billing increments, 95

billing structure, 177–178

myths, 325–326

telephone calls

active, 168

analog compared with VoIP, 10–11

analyzing, 335–336

clipping, 71, 262–263

completion due diligence steps, 268

completion problems, 142, 257–261

components, 10–11

conference, 83–84

deconstructing local, 254–257

dialing, 157

dropped, 260–261

ending with BYE method, 47

ending with CANCEL method, 48

failed, 169–170

filtering, 236–237

graphing in Wireshark, 234–236

inbound, 91, 291–297, 305–306

local, 88, 254–257

long-distance, 251–253, 343–345

maximum concurrent, 124

outbound, 282–291, 304

overhead, 10–11, 269

problem frequency, 263–265

queue, 84–86

redirected, 14

reviewing completed, 206–209

reviewing long-distance outbound,
251–253

routing, 261

setup, 10

toll-free, 292

treatment, 257

troubleshooting outbound, 282–291

viewing multi-node, 209–210

volume, 158–159

telephone features

Call Detail Records (CDR), 94–95, 124,
335–336

call forward, 12–13, 44, 92

call queue, 84–86

conference calls, 83–84

console mode, 94

extension, 86

Interactive Voice Response (IVR)
system, 92

Least Cost Routing, 86–91, 305

- non-VoIP, 326–327
- voicemail, 82–83, 175–176
- X10, 93
- telephone numbers
 - area codes, 36, 90–91, 265
 - BTN (Billing Telephone Number), 31–32, 161
 - moving, 337–338
 - ordering new, 36
 - porting, 29–36
 - prefix, 36
- telephone system
 - overview, 79–82
 - taking control, 334–335
- telephone-event parameters, 71–72
- telephones
 - analog, 10–11, 174–175, 287–288
 - cell, 293–294
- telephony, traditional, 339
- telephony signaling, 80
- test plan
 - activating, 166–167
 - busy calls, 169–170
 - failed calls, 169–170
 - fax transmission, 170–171
 - out call setup, 168–169
 - tear-down, 168–169
 - testing all VoIP phones, 173–174
 - testing residual analog phones, 174–175
 - touch tones, 171–173
 - validating Dial Plan features, 175–176
- testing
 - all VoIP phones, 173–174
 - analog phones, 174–175
 - InterOperability (InterOp), 18, 351–352
 - LAN, 134–138
 - retesting, 141–142
 - touch tones, 171–173
 - VoIP calls, 119–121
- 300 Multiple Choices SIP response, 55
- 301 Moved Permanently SIP response, 55
- 302 Moved Temporarily SIP response, 55–56
- 305 Use Proxy SIP response, 56
- 380 Alternative Service SIP response, 56
- “throwing your carrier under the bus,” 348
- time of day, relationship with call problems, 266–267
- timelines for trouble tickets, 280
- toll quality, 74
- toll-free calls, 292
- toll-free numbers, 145–146
- tones. *See also* touch tones
 - DTMF (Dual Tone Multi Frequency), 28, 66–68, 128–129
 - listening for, 258–259
 - tri-, 258
- tools (Wireshark), 222
- touch tones
 - handling, 128–129
 - locating in a capture, 238–240
 - pushing, 28
 - testing, 171–173
- traditional telephony, 339
- traffic flows
 - categories of, 193
 - defined, 193
 - monitoring, 193–195
- traffic pattern, 20
- traffic protocol, 111
- transceiver, 93
- transcoding JBIG, T.38 fax parameter, 134
- transcoding MMP, T.38 fax parameter, 134
- translation, 261
- Transmission Control Protocol. *See* TCP (Transmission Control Protocol)
- transmissions
 - branding with Caller ID, 44
 - checking fax, 170–171
 - delay, 77
 - In-band, 128
 - LAN (Local Area Network), 110
 - media with SDP, 60–72

- transmissions (*continued*)
 - non-voice calls, 28
 - port, 111
 - UDP (User Datagram Protocol), 117–118
 - Transport Layer, 117–118
 - Traversal Using Relay NAT (TURN), 302
 - Tree LAN, 101
 - tri-tones, 258
 - trouble tickets
 - database, 279
 - defined, 274
 - escalation list, 281–282
 - overview, 279–280
 - timelines, 280
 - troubleshooting
 - call completion problems, 257–261
 - call forwarding, 12–13
 - call problem frequency, 263–265
 - call quality, 142, 262–263
 - call routing, 261
 - Caller ID, 309–311
 - carrier trouble reporting structure, 274–275
 - crossed-audio situation, 269–271
 - defined, 249
 - identifying variables, 251–257
 - inbound calls, 291–297, 305–306
 - intermittent problems, 141
 - international problems, 290–291
 - isolating patterns, 265–267
 - LCR design, 305
 - managing trouble tickets, 279–282
 - myths, 324–325
 - non-network problems, 142
 - non-traditional, 360–362
 - non-voice problems, 306–307
 - no-way audio, 303
 - one-way audio, 299–303
 - outbound calls, 282–291, 304
 - overview, 311–312
 - performing due diligence, 267–269
 - progressively diminishing returns, 307–309
 - providing call examples, 275–277
 - providing multiple call examples, 278–279
 - steps, 271–272
 - using diplomacy, 250–251
 - using logic, 271–272
 - with Wireshark, 243–245
 - Tshark, 221
 - TURN (Traversal Using Relay NAT), 302
 - 200 OK SIP response, 54–55
- U •
- UA (SIP User Agents), 24
 - UAC (User Agent Client), 24
 - UAS (User Agent Server), 24
 - UDP (User Datagram Protocol)
 - message header, 44
 - protocol tree, 232
 - retransmission potential, 20
 - traffic flow, 193
 - transmitting, 117–118
 - UdpEC (UDP Error Control) T.38 fax parameter, 134
 - UDP-RTP traffic flow, 193
 - uncompressed VoIP charges, 17
 - undesired noise, 119
 - Uniform Resource Identifier (URI), 41, 157
 - Uniform Resource Locator (URL), 42
 - uniformity of process, 350–351
 - UNSUBSCRIBE method, 51–52
 - UPDATE method, 50
 - URI (Uniform Resource Identifier), 41, 157
 - URL (Uniform Resource Locator), 42
 - usage estimations, 352–353
 - User Agent Client (UAC), 24
 - User Agent Server (UAS), 24
 - User Datagram Protocol. *See* UDP (User Datagram Protocol)
 - user's guide, Wireshark, 222

• **V** •

validating

- Dial Plan features, 175–176
- port quality, 152

variables, 251–257

vendor support, 356

verification report, 200–201

verifying

- fax transmissions, 170–171
- T.38 fax calls in Wireshark, 240–243
- voicemail, 175–176

viewing

- jitter, 187–188
- multi-node calls, 209–210
- stream info, 191

VLAN (Virtual LAN), 113–114

VLM (VoIP Lifecycle Management)

- determining MOS scores with, 121–122
- overview, 102
- stages, 102–103

Voice over Internet Protocol. *See* VoIP
(Voice over Internet Protocol)

voice portion of calls, 10–11

voicemail

- checking, 175–176
- overview, 82–83

VoIP (Voice over Internet Protocol)

- advantages, 329–340
- Assess (Premium) report, 199
- Assess (Standard) report, 199
- call forwarding, 92
- challenges, 20
- compression, 17, 331
- connection compared with traditional
local loop, 149
- disadvantages, 341–353
- future of, 339–340
- growing with, 331–333
- nuances, 340
- ordering, 150–151
- overview, 9

process, 138–139

relationship with traditional
provisioning, 151separating from data with subnets,
112–113

SLA (Standard) report, 199

traditional use of bandwidth, 318

Verify (Standard) report, 199

Wiki Web site, 358

VoIP (Voice over Internet Protocol)

carriers

- bypassing, 286–287
- local, 329–330
- long-distance, 288, 326–327
- relationships, 348–349
- support, 362–363
- trouble reporting structure, 274–275
- uniformity of process, 350–351

VoIP (Voice over Internet Protocol)

phone calls

- compared with analog phone call,
10–11
- finding, 232–238
- redirected, 14
- testing, 119–121
- traditional forwarding, 13

VoIP Lifecycle Management. *See* VLM
(VoIP Lifecycle Management)

Voip-Info.org Web site, 360

VoIP-specific troubleshooting

- Caller ID, 309–311
- inbound call problems, 305–306
- LCR design, 305
- no-way audio, 303
- non-voice problems, 306–307
- one-way audio, 299–303
- outbound call failures, 304
- overview, 311–312
- progressively diminishing returns,
307–309

volume, determining peak call, 123–125

• W •

wasted bandwidth, 77

.WAV files, 83

Web sites

Asterisk/AsteriskNOW, 18, 334

Asterisk wiki, 358

British version of VoIP Wiki, 358

Digium, 23

Internet Engineering Task Force (IETF),
205

local calling guide, 88

Packet Island, 136, 180, 324

RFCs, 357

tcpdump, 225

Telecordia, 87

VoIP quality test, 120, 135

VoIP Wiki, 358

Voip-Info.org, 360

Wireshark, 224

wikis, 358–359

Windows (operating system)

 downloading Wireshark for, 221–222

 pinging from XP, 103–104

Wireshark. *See also* tcpdump

 bandwidth, 109

 capturing packets, 220, 228–229, 306

 compatibility, 109

 defined, 219

 downloading for Linux, 222–224

 downloading for Windows, 221–222

 extensions, 221

 filtering calls, 236–237

 finding VoIP calls, 232–238

 gathering details, 109

 graphing calls, 234–236

 handling DTMF tones, 238–240

 installing, 221–224

 listening to captures, 237–238

 overview, 219–221

 plug-ins, 221

 Summary window, 231

 T.38 fax calls, 240–243

 troubleshooting with, 243–245

 Web site, 224

Wireshark GUI

 main window components, 229–231

 protocol tree, 232

 Summary window, 231

working the system, 281

• X •

X10 software, 93

• Y •

“your call cannot be completed as
dialed” message, 258

YUM development tool package, 223

