

## Index

- $V(\lambda)$ -curve, 85
- $\cos^4$ -law, 323
- $f$ -number, 240
- 1/f noise, 422
- 1394 Trade Association, 446
- 3D reconstruction, 653–666
- 64-bit PCI, 428
  
- a posteriori probability, 672
- a priori probability, 672, 674
- A/D conversion, 400
- aberration, 212
- aberrations, 316
- absorbance, 110, 113, 127
- absorbing filter, 141
- absorption, 113
- accommodation, 3, 5, 29
- accumulator array, 642–645
- accuracy, 605–606, 695, 711, 718, 720, 759, 764, 765
  - contour moments, 566
  - edges, 520, 607–612
  - gray value features, 520
  - gray value moments, 562–563, 566
  - hardware requirements, 611–612
  - region moments, 562–563
  - subpixel-precise threshold, 520
- achromatic axis, 12
- acquisition, 481
- action potentials, 18
- active pixel sensor, 376
- ActiveX, 477
- adaptation, 13, 14, 17, 20, 29
  - contrast, 29
  - light/dark, 29
  - motion, 29
  - tilt, 29
  - to optical aberrations, 30
  - to scaling, 29
- adaptive lighting, 134, 195
- additive mixed illumination colors, 117
- additive noise, 309
- additivity, 288
- adjustment, 713, 714, 717, 727
- adjustment vs. calibration, 727
  
- AFE, 398
- affine transformation, 537–538, 559, 626, 646
- afocal system, 262
- aging, 102
- AIA, 437
- Airy disc, 278, 280
- algebraic distance, 619
- algebraic error, 619
- aliasing, 542–543, 632
- aliasing effect, 305, 307
- aliasing function, 315
- aliasing potential, 315
- aliasing ratio, 315
- alignment, 537
- amacrine cells, 19, 21
- amplitude distribution in the image plane, 276
  
- analog, 428
- analog front end, 398
- analog processing, 396
- analog video signal, 429
- analyzer, 123
- Ando filter, 598
- angel
  - kappa, 3
- anisometry, 558, 562, 564, 669
- anterior chamber, 3
- anti-reflection coating, 323
- anti-reflective coating, 143
- AOI, 406
- aperture, 235, 521
- aperture correction, 392
- aperture stop, 235, 236
- API, 475, 476
- Application Programming Interface, 476
- application-package, *see* systems, application-package
- applications
  - code recognition, 695
  - completeness check, 695, 752, 754, 757
  - object recognition, 695, 760
  - position recognition, 695, 763
  - shape and dimension check, 695
  - surface inspection, 696

- types, 696
  - AR, 143
  - area, 556, 562, 564, 565
  - area MT, 26
  - area of interest, 406
  - artificial astigmatism, 140
  - aspect ratio, 742
  - astigmatism, 5, 12
  - asynchronous, 411, 443, 446
  - asynchronous reset, 499
  - asynchronous shutter, 366
  - attention, 25, 26
  - auto shutter/gain, 400
  - axial magnification ratio, 229, 266
  - axons, 3, 13, 18, 19, 21
  
  - b/w, 382
  - Back Porch, 430
  - back porch, 431, 432
  - backlight, 199
  - backlighting, 158
  - band-limited system, 307
  - bandpass filter, 142
  - bandwidth, 138, 410, 415, 417, 425, *see*  
signal, bandwidth
  - bar codes, *see* codes, bar codes
  - batch production, *see* production, batch
  - Bayer, 446, 454, 480, 489, 490
  - BAYER pattern, 396
  - Bayer pattern, 389
  - Bayes decision rule, 672, 673
  - Bayes's theorem, 672
  - beam converging lens, 222
  - beam diverging lens, 222
  - Bessel function, 278
  - Big Endian, 419
  - bilateral telecentric systems, 262
  - binarization, 502
  - binary image, 513, 552, 556, 566, 567, 569,  
573, 579
  - binning, 382, 385, 386, 406
  - binocular stereo reconstruction, 653–666
  - bipolar cells, 18
    - OFF, 15
    - ON, 15
  - bit depth, 486
  - Bitmap, 491
  - black light, 122
  - blemish pixel, 378
  - blobs, 23, 26
  - blocks, 484
  - blooming, 372
  - BMP, 491
  - boundary, 553, 560, 573–574
  - boundary condition, 273
  - bounding box, 559–560, 565, 669
  - BP, 142
  
  - brightfield illumination, 158
  - brightness, 235
  - brightness behavior, 104
  - brightness control, 189
  - brightness perception, 86
  - buffer, 481, 501
  - buffering, 471, 500
  - bundle adjustment, 346
  - Bus\_Id, 418, 419
  
  - C, 476
  - C-mount, 362
  - cables, 457
  - calcium, 15
  - calibration, 727, 746, 748, 764–766
    - geometric, 610, 611, 654
      - camera coordinate system, 654
      - distortion coefficients, 654, 658
      - exterior orientation, 611
      - focal length, 654
      - interior orientation, 611, 654
      - pixel aspect ratio, 654
      - pixel size, 654
      - principal distance, 654
      - principal point, 654
      - relative orientation, 654
  - radiometric, 519–524, 610
    - calibration target, 520
    - chart based, 520–521
    - chart-less, 521–524
    - defining equation for chart-less  
calibration, 522
    - discretization of inverse response  
function, 522–523
    - gamma response function, 520, 524
    - inverse response function, 522
    - normalization of inverse response  
function, 523
    - polynomial inverse response  
function, 524
    - response function, 520, 521, 524
    - smoothness constraint, 523–524
- calibration vs. adjustment, 727
- camera, 511–512
  - fill factor, 563, 608, 611
  - gamma response function, 520
  - gray value response, 519–520
    - linear, 519, 610, 611
    - nonlinear, 520, 610
  - inverse response function, 522
  - response function, 520, 521, 524
  - shutter time, 521
- camera bus, 427, 428
- camera calibration, 333
- camera constant, 209
- Camera Link, 383, 426, 437, 439, 455–458
- candela, 125

- Canny filter, 594–595, 599, 606
  - edge accuracy, 607, 608
  - edge precision, 606
- cardinal elements, 219
- Cat5, 458
- CCD, 361, 364
- CCIR, 379, 429, 456, 457
- CCTV, 362
- CDS, 388
- center of gravity, 557–558, 562, 565, 614, 615
- center wavelength, 96, 138
- central disc, 278, 283
- central moments, 557–558, 562, 565, 613
- central perspective, 338
- central projection, 208, 251
- centre of perspective, 208
- CFA, 489
- chamfer-3-4 distance, 581
- change-over, 714, 746, 748
- channel, 496
- channel capacity, 12, 18
- characteristic function, 513, 561, 562, 583
- charge, 373, 384
- chessboard distance, 580, 581
- chief ray, 236
- chip size, 382
- Chroma, 392, 430–432
- chromatic aberration, 5, 9, 11
  - longitudinal, 11
  - transverse, 11
- circle fitting, 617–619
  - outlier suppression, 617–618
  - robust, 617–618
- circle of confusion, 241
  - permissible size, 249
- circles of confusion, 245
- circular aperture, 278
- city-block distance, 580, 581
- classification, 669, 672–688
  - a posteriori probability, 672
  - a priori probability, 672, 674
  - Bayes classifier, 674–677
  - classification accuracy, 685
  - classifier types, 674
  - curse of dimensionality, 675, 682
  - decision theory, 672–674
    - Bayes decision rule, 672, 673
    - Bayes's theorem, 672
  - error rate, 674
  - expectation maximization algorithm, 676
  - features, 669
  - Gaussian mixture model classifier, 676–677, 687
  - generalized linear classifier, 682
  - $k$  nearest neighbor classifier, 675
  - linear classifier, 677–678
  - neural network, 677–681, 685–687
    - hyperbolic tangent activation function, 680
    - logistic activation function, 680
    - multi-layer perceptron, 678–681, 685–687
    - multi-layer perceptron training, 680–681
    - sigmoid activation function, 680
    - single-layer perceptron, 677–678
    - softmax activation function, 680
    - threshold activation function, 677, 679
    - universal approximator, 679, 680
  - nonlinear classifier, 678–687
  - polynomial classifier, 682
  - rejection, 686–687
  - support vector machine, 681–687
    - Gaussian radial basis function kernel, 684
    - homogeneous polynomial kernel, 684
    - inhomogeneous polynomial kernel, 684
    - kernel, 684
    - margin, 682
    - separating hyperplane, 682–683
    - sigmoid kernel, 684
    - universal approximator, 684
  - test set, 674
  - training set, 674, 681
  - training speed, 685–686
- closed circuit television, 362
- closing, 577–578, 584–586
- cloudy day illumination, 171
- clutter, 638, 641, 646
- CMOS, 362, 373
- coaxial diffuse light, 160
- coaxial directed light, 162
- coaxial telecentric light, 163
- code recognition, *see* codes, recognition
- coded light, 166
- codes
  - bar codes, 695
  - DataMatrix, 695, 702, 726, 731
  - recognition, 695
- coherent light, 99
- cold light source, 90
- color, 382
  - color alias, 405
  - color burst, 431
  - color constancy, 27, 28
  - color contrast, 27, 28
  - color correction, 406
  - color difference, 392
  - color filter, 148, 397
  - color filter array, 489

- color information, 404
- color interpolation, 404
- color perception, 85
- coma, 12
  - horizontal, 5
- combined lighting technique, 184
- compact systems, *see* systems, compact systems
- compact vision system, 427
- compactness, 560, 669
- CompactPCI, 464, 465
- CompactPCI Express, 466
- complement, 567
- complementary color, 116
- complementary colour filter, 389
- completeness check, *see* applications, completeness check
- complex cells, 25
- component labeling, 552
- composite video format, 430
- computer bus, 427, 428
- cone pedicle, 18
- cones, 7, 14, 17, 18, 27, 29, 30
- configuration management, 704, 705, 767
- connected components, 551–552, 667
- connectivity, 551–552, 567, 574, 580
- constancy of luminance, 128
- continuous production, *see* production, continuous
- contour, 515–516
- contour feature, *see* features, contour
- contour length, 560
- contour segmentation, 620–624, 638
  - lines, 620–622
  - lines and circles, 623–624
  - lines and ellipses, 623–624
- contrast, 134, 504
- contrast adaptation, 12
- contrast enhancement, 517–519
- contrast normalization, 517–519
  - robust, 517–519, 671
- contrast sensitivity function, 19, 20
- contrast threshold, 19
- control, *see* evaluation, control
- control signals, *see* data, control signals
- controlled lighting, 190
- convex hull, 560, 565
- convexity, 560
- convolution, 530–531
  - kernel, 530
- convolution integral, 292
- convolution theorem, 295, 304
- coordinates
  - homogeneous, 537, 538
  - inhomogeneous, 537, 538
  - polar, 544
- cornea, 1, 3, 5
- correct perspective viewing distance, 243
- corrected image, 403
- correction data, 403
- correlated double sampling, 387
- CPU, 480
- CRC, 410
- cross talk, 307
- crystalline lens, 1
- cumulative histogram, 519, 561
- cutoff spatial frequency, 7
- cutoff wavelength, 138
- cuton wavelength, 138
- cycle start packet, 411
- cycle time, *see* production, cycle time
- dark current noise, 421
- dark field lighting, 173
- dark noise, 17
- dark signal non uniformity, 378
- darkfield illumination, 159
- data
  - control signals, 727, 732
  - images, 729, 731
  - type data, 729, 767–769
- data acquisition, 497
- data packets, 410
- data payload size, 417
- data rate, *see* signal, data rate
- data structures
  - images, 511
  - regions, 513–515
  - subpixel-precise contours, 515–516
- Data Valid, 439
- DataMatrix code, *see* codes, DataMatrix
- daylight suppression filter, 144
- DCAM, 406
- decision theory, 672–674
  - a posteriori probability, 672
  - a priori probability, 672, 674
  - Bayes decision rule, 672, 673
  - Bayes's theorem, 672
- deferred image transport, 404
- definition, 486
- defocused image plane, 282
- deighborhood, 551–552
- delay time, 190
- depth of field, 244, 246, 267
- depth of field T, 246
- depth of focus, *see* focus, depth of
- depth of focus T, 247
- depth-first search, 552
- Deriche filter, 595, 607
  - edge accuracy, 607, 609
  - edge precision, 607
- deriche filter, 599
- derivative
  - directional, 589

- first, 587, 591
  - gradient, 589
  - Laplacian, 590
  - partial, 589, 598, 599
  - second, 588, 591
- determinism, 459
- deterministic system, 288
- deviation from telecentricity, 325
- dichromatic, 27
- difference, 567
- diffraction, 114, 268
- diffraction integral, 269, 270
- diffraction limit, 5
- diffraction limited, 275
- diffraction limited depth of focus, 282
- diffraction-limited MTF, 5
- diffuse area lighting, 161
- diffuse bright field incident light, 160
- diffuse bright field transmitted lighting, 177
- diffuse dark field incident light, 173
- diffuse directed partial bright field incident light, 169
- diffuse lighting, 155
- diffuse on axis light, 160
- diffuse transmitted dark field lighting, 184
- digital camera specification, 418
- digital I/O, *see* interface, digital I/O
- dilation, 568–570, 573–574, 583, 604
- dimension check, *see* applications, dimension check
- DIN 1335, 233
- DIN 19040, 231
- diplopia, 29
- Dirac comb, 304, 307
- direct linear transformation, 353
- Direct Memory Access, 476
- directed bright field incident light, 162
- directed bright field transmitted lighting, 178
- directed dark field incident light, 173
- directed lighting, 155
- directed on axis light, 162
- directed reflection, 108
- directed transmission, 112
- directed transmitted dark field lighting, 184
- DirectFirePackage, 420
- direction of light, 220
- directional properties of the light, 155
- DirectX/DirectShow, 420
- discharging lamp, 88, 91
- discrete Fourier transform, 309
- disk, 485
- disparity, 29, 31, 660–661
- dispersion, 118
- dispersion of light, 210
- display, 481
  - image, 492
- distance
  - chamfer-3-4, 581
  - chessboard, 580, 581
  - city-block, 580, 581
  - Euclidean, 581
- distance transform, 580–582, 639, 641
- distortion, 320, 336
- distribution of illuminance, 131
- DMA, 410, 476, 480
- DNL, 401
- doise
  - variance, 592, 606
- don-maximum suppression, 596
- dormalized moments, 557, 562, 565
- dorsal stream, 25, 26, 29
- downshift, 493
- drift, 90, 98, 102
- driver, 480
- driver software, 427, 429
- DSNU, 379
- duality
  - dilation–erosion, 573, 584
  - hit-or-miss transform, 575
  - opening–closing, 578, 584
- DV, 445
- dynamic range, 374, 423
- dynamic thresholding, 548–550, 586, 667
- edge
  - amplitude, 589, 598
  - definition
    - 1D, 587–589
    - 2D, 589–590
  - gradient magnitude, 589, 598
  - gradient vector, 589
  - Laplacian, 590, 604–605
  - nonmaximum suppression, 588, 596, 600–601
  - polarity, 589
- edge extraction, 587–612, 638
  - 1D, 591–597
    - Canny filter, 594–595
    - Deriche filter, 595
    - derivative, 587, 588, 591
    - gray value profile, 591–593
    - nonmaximum suppression, 596
    - subpixel-accurate, 596–597
  - 2D, 597–605
    - Ando filter, 598
    - Canny filter, 599, 606
    - Deriche filter, 599, 607
    - Frei filter, 598
    - gradient, 589
    - hysteresis thresholding, 601–602
    - Lanser filter, 600, 607

- Laplacian, 590, 604–605
- nonmaximum suppression, 600–601
- Prewitt filter, 598
- Sobel filter, 598
- subpixel-accurate, 602–605
- edge filter, 593–595
  - Ando, 598
  - Canny, 594–595, 599, 606
    - edge accuracy, 607, 608
    - edge precision, 606
  - Deriche, 595, 599, 607
    - edge accuracy, 607, 609
    - edge precision, 607
  - Frei, 598
  - Lanser, 600, 607
    - edge accuracy, 607
    - edge precision, 607
  - optimal, 594–595, 599–600
  - Prewitt, 598
  - Sobel, 598
- edge spread function, 317
- effective f-number, 247
- EIA (RS170), 379
- Eikonal equation, 206
- EISA, 428, 462
- electromagnetic wave, 205
- electronic shutter, 368
- electronic shutter , 365
- ellipse fitting, 619–620
  - algebraic error, 619
  - geometric error, 619
  - outlier suppression, 619–620
  - robust, 619–620
- ellipse parameters, 557–558, 560, 562, 564, 565, 614, 615, 619
- embedded vision systems, 479
- EMC, 93
- emmetropia, 3
- enclosing circle, 559–560, 565
- enclosing rectangle, 559–560, 565, 669
- encoder, 497
- engineering framework, 744
- entocentric perspective, 253
- entrance pupil, 227, 238
- entrance window, 239
- epipolar image rectification, 659–660
- epipolar line, 656
- epipolar plane, 655
- epipolar standard geometry, 658–659
- epipole, 656
- erosion, 571–574, 583–584
- error of second order, 182
- errors of the first order, 182
- ESF, 317
- Ethernet, 450, 459, *see* interface, Ethernet
- Euclidean distance, 581
- evaluation
  - control, 698, 699, 763
  - inspection, 698, 699, 752, 754, 757
  - monitoring, 698, 699
  - recognition, 698
  - verification, 698, 699, 752, 754, 757, 760
- event, 410
- exit pupil, 227, 239
- exit window, 239
- exposure, 131, 136
- exposure time, 136
- extensibility, 705, 707, 771
- exterior orientation, 335, 611
- extraneous light, 200
- EXView HAD, 381
- eye lens, 1
- eye movement, 11, 13, 31
- eye protection, 121
- face-distortion aftereffect, 30
- facet model, 602
- far cells, 29
- far point, 245, 256
- feature extraction, 555–566
- features
  - contour, 556, 565–566
    - area, 565
    - center of gravity, 565
    - central moments, 565
    - contour length, 565
    - ellipse parameters, 565
    - major axis, 565
    - minor axis, 565
    - moments, 565
    - normalized moments, 565
    - orientation, 565
    - smallest enclosing circle, 565
    - smallest enclosing rectangle, 565
  - gray value, 556, 560–564
    - $\alpha$ -quantile, 561
    - anisometry, 562, 564
    - area, 562, 564
    - center of gravity, 562
    - central moments, 562
    - ellipse parameters, 562, 564
    - major axis, 562, 564
    - maximum, 517, 560
    - mean, 561
    - median, 561
    - minimum, 517, 560
    - minor axis, 562, 564
    - moments, 561–564
    - normalized moments, 562
    - orientation, 562
    - standard deviation, 561
    - variance, 561

- region, 556–560
  - anisometry, 558, 669
  - area, 556, 562
  - center of gravity, 557–558, 562
  - central moments, 557–558
  - compactness, 560, 669
  - contour length, 560
  - convexity, 560
  - ellipse parameters, 557–558, 560
  - major axis, 557–558
  - minor axis, 557–558
  - moments, 557–559
  - normalized moments, 557
  - orientation, 557–558, 560
  - smallest enclosing circle, 559–560
  - smallest enclosing rectangle, 559–560, 669
- Fermat's principle, 206
- field angle
  - object side, 231
- field bus, *see* interface, field bus
- field integration, 367, 368
- field programmable gate array, 393
- field readout, 391
- field stop, 236
- fields, 430
- FIFO, 404
- files, *see* interface, files
- fill factor, 365, 563, 608, 611
- filter
  - anisotropic, 532, 600
  - border treatment, 528–529
  - convolution, 530–531
    - kernel, 530
  - definition, 530
  - edge, 593–595
    - Ando, 598
    - Canny, 594–595, 599, 606
    - Deriche, 595, 599, 607
    - Frei, 598
    - Lanser, 600, 607
    - optimal, 594–595, 599–600
    - Prewitt, 598
    - Sobel, 598
  - Gaussian, 532–534, 543, 548–550, 595, 599, 632
    - frequency response, 533
  - isotropic, 533, 600
  - linear, 530–531, 591
  - mask, 530
  - maximum, *see* Morphology, gray
    - value, dilation
  - mean, 527–530, 534, 543, 549, 550, 592, 632
    - frequency response, 531–532, 632
  - median, 534–536, 549, 550
  - minimum, *see* Morphology, gray
    - value, erosion
  - nonlinear, 534–536, 584
  - rank, 536, 584
  - recursive, 530, 531, 533, 584
  - runtime complexity, 529–530
  - separable, 529, 531, 533
  - smoothing, 525–536
    - optimal, 532–533, 595, 599
    - spatial averaging, 527–530
    - temporal averaging, 526–527
- filter combination, 149
- filter factor, 139
- finite extension of ray pencils, 234
- Fire4Linux, 420
- FirePackage, 420
- FireWire, 383, *see* interface, FireWire
- first Bessel function, 20
- fitting
  - circles, 617–619
    - outlier suppression, 617–618
    - robust, 617–618
  - ellipses, 619–620
    - algebraic error, 619
    - geometric error, 619
    - outlier suppression, 619–620
    - robust, 619–620
  - lines, 613–617
    - outlier suppression, 614–617
    - robust, 614–617
- fixation, 710, 711, 717
- fixed pattern noise, 422
- fixed-pattern noise, 377
- flash, 367
- flash duration, 93
- flash light, 98
- flash lighting, 190
- flash mode, 190
- flash repeating frequency, 190
- flash time, 193
- fluorescent lamp, 93
- focal length
  - image side, 219
  - object side, 219
- focal point
  - image side, 216
  - object side, 216
- focus
  - depth of, 712, 739
- focussing plane, 241, 244
- Fourier transform, 273, 531
- fovea, 3, 11
- FPGA, 393
- FPN, 422
- fps, 418
- frame, 430
- frame grabber, 388, 428, 432, 475, 498, 500

- frame integration, 367
- frame memory, 404
- frame rate, 457
- frame rates, 415
- frame readout, 369
- frame transfer, 365, 366
- Frame Valid, 439
- framework, *see* engineering framework
- Fraunhofer approximation, 274
- Frei filter, 598
- frequency, 210, *see* signal, frequency
- Fresnel's approximation, 273
- FTP, *see* interface, network
- full dynamic, 493
- full frame, 365
- full well capacity, 424
- fuzzy membership, 562–564
- fuzzy set, 562–564
  
- gain, 400
- gamma correction, 502, 504
- gamma function, 401
- gamma LUT, 401, 402
- gamma response function, 520, 524
- gamut, 390
- ganglion cells, 13, 19, 21, 23, 24, 27, 31
- gauge capability, 712, 718, 719, 760
- Gaussian filter, 532–632
- gaussian filter, 534
  - frequency response, 533
- Gaussian optics, 212, 268
- generalized Hough transform, 642–646
  - accumulator array, 642–645
  - R-table, 644
- geometric camera calibration, 610, 611, 654
  - exterior orientation, 611
  - interior orientation, 611, 654
    - camera coordinate system, 654
    - distortion coefficients, 654, 658
    - focal length, 654
    - pixel aspect ratio, 654
    - pixel size, 654
    - principal distance, 654
    - principal point, 654
  - relative orientation, 654
    - base, 655
    - base line, 656
- geometric error, 619
- geometric hashing, 646–648
- geometric matching, 646–652
- geometrical optics, 205, 206
- geometrical path, 206
- Gigabit Ethernet, 383, 426, 428, 450, 457, 475
- given range, 493
- global shutter, 377
- glutamate, 15
  
- grab, 482
- gradient, 589
  - amplitude, 589, 598
  - angle, 589, 643
  - direction, 589, 642, 643
  - length, 589
  - magnitude, 589, 598
  - morphological, 586
- gradient algorithm, 135
- gradient index lens, 5
- grating acuity, 9, 20
- gray value, 512
  - 1D histogram, 517–519, 546–548, 561
    - cumulative, 519, 561
    - maximum, 546–548
    - minimum, 546–548
    - peak, 546–548
  - 2D histogram, 522–523
  - $\alpha$ -quantile, 561
  - camera response, 519–520
    - linear, 519, 610, 611
    - nonlinear, 520, 610
  - feature, *see* features, gray value
  - maximum, 517, 560
  - mean, 561
  - median, 561
  - minimum, 517, 560
  - normalization, 517–519
    - robust, 517–519, 671
  - profile, 592
  - robust normalization, 670
  - scaling, 517
  - standard deviation, 561
  - transformation, 516–519, 561, 564
  - variance, 561
- gray value difference, 134
- grey filter, 146
  
- half-power points, 138
- half-width, 96
- halogen lamp, 89
- handling, *see* production, part handling
- handshaking, *see* interface, handshaking
- hardware trigger, 408
- harmonic wave, 295
- Hausdorff distance, 640–642
- Helmholtz equation, 270
- Hessian normal form, 613
- HF-ballast, 94
- high speed imaging, 375
- high-speed inspection, 191
- higher order aberrations, 5
- HiRose, 388, 414
- histogram
  - 1D, 517–519, 546–548, 561
    - cumulative, 519, 561
    - maximum, 546–548

- minimum, 546–548
  - peak, 546–548
  - 2D, 522–523
- hit-or-miss opening, 576
- hit-or-miss transform, 574–575, 579
- HMI, *see* human machine interface
- hole accumulation Diode, 381
- homocentric pencil, 207, 211
- homogeneity, 288
- homogeneous coordinates, 537, 538
- homogenous lighting, 171
- horizon line, 256
- horizontal mirror, 403
- horizontal synchronization, 431
- host, 428, 449
- HSL, 432, 486
- Hsync, 431–434
- HTTP, *see* interface, network
- Huber weight function, 615
- human machine interface, 731, 743–745, 747, 748, 775
- human perception, 135
- hyperacuity, 29
- hypercentric perspective, 258
- hypercolumn, 26
- hyperfocal depth
  - near limit, 248
- hyperfocal distance, 248
- hyperparization, 15
- hyperpolarization, 15, 17
- hypothesize-and-test paradigm, 646
- hysteresis thresholding, 601–602
  
- ideal lens transformation, 276
- idealized impulse, 289
- IEEE 1394, 402, 420, 428, 442, 443, 446, 447, 449, 454, 456, 457, 475
- IEEE 1394a, 425
- IEEE 1394b, 412, 425, 443
- IEEE-1394 plug, 412
- IEEE1394, *see* interface, IEEE1394
- IIDC, 399, 406, 407, 409, 410, 418, 446, 447, 454
- illuminance, 125, 127, 128, 192
  - at image sensor, 130
- illuminations component, 78
- image, 481, 511
  - binary, 513, 552, 556, 566, 567, 569, 573, 579
  - bit depth, 512
  - complement, 584
  - domain, *see* region of interest
  - enhancement, 516–536
  - function, 512–513
  - gray value, 512
  - gray value normalization, 517–519
    - robust, 517–519, 671
  - gray value scaling, 517
  - gray value transformation, 516–519
  - label, 513, 552
  - multi-channel, 512
  - noise, *see* Noise
  - pyramid, 632–636
  - real, 214
  - RGB, 512
  - segmentation, *see* segmentation
  - single-channel, 512
  - smoothing, 525–536
  - spatial averaging, 527–530
  - temporal averaging, 526–527
  - transformation, 539–544
  - virtual, 214
- image circle, 292
- image circle diameter, 241
- image construction
  - graphical, 223
- image orientation, 213
- image quality, 316
- image reconstruction, 496
- image side focal length, 219
- image space, 218, 229
- images, *see* data, images
- imaging equation
  - general, 227
- imaging equations, 224
  - Newtonian, 226
- imaging optics, 153
- impulse response, 272, 275, 276
- incandescent emission, 88
- incandescent lamp, 89
- incident light, 171, 198
- incident lighting, 157
- incoherent imaging, 277
- incoherent light, 157
- incoherent transmission chain, 304
- incoming light, 107
- industrial lighting, 78
- information theoretical aspect, 288
- inhomogeneous coordinates, 537, 538
- INL, 401
- input, 414
- input voltage, 414
- inspection, *see* evaluation, inspection
- integration time, 15, 17, 19
- intelligent camera, *see* systems, compact systems
- intensity distribution near focus, 281
- interface
  - digital I/O, 723, 724, 728–730
  - Ethernet, 723–725, 729, 731, 733, 750, 766
  - field bus, 723, 724, 730, 731
  - files, 732
  - handshaking, 732, 733, 736, 765

- multithreading, 734
  - network, 731
  - serial, 729
  - USB, 722–724, 729, 731
- interface card, 427, 428
- interface device, 427
- interference filter, 142
- interior orientation, 335, 611, 654
  - camera coordinate system, 654
  - distortion coefficients, 654, 658
  - focal length, 654
  - pixel aspect ratio, 654
  - pixel size, 654
  - principal distance, 654
  - principal point, 654
- interlaced, 369, 430
- interlaced scan, 365, 367
- interline transfer, 365–367, 370
- intermediate pupil, 239
- International System of Units, 125
- interpolation, 405
  - bilinear, 541–542, 553, 593
  - nearest neighbor, 539–541, 593
- interrupt, 410, 480
- interrupt service routine, 480
- intersection, 567
- invariant moments, 558
- IP, 451
- IR, 82, 367, 386
- IR cut filter, 386, 395
- IR suppression filter, 146
- irregular diffuse reflection, 108
- irregular diffuse transmission, 112
- ISA, 428, 462
- ISO9001:2000, 81
- isochronous, 410, 411, 441, 443, 444, 446, 450
- isoplanasie condition, 291
- isoplanatic region, 292
- ISR, 480
- jitter, 409
  - job-shop production, *see* production, job-shop
- Joint Photographic Experts Group, 491
- JPEG, 491
- Keplerian telescope, 262
  - kernel mode, 475
  - knee point, 375
  - koniocellular pathway, 23, 28
  - kT/C noise, 387
- L cone, 11, 27, 28, 30
- label image, 513, 552
- labeling, 552
- LabVIEW, 476, 477
- Lambert radiator, 132, 155
- Lanser filter, 600, 607
  - edge accuracy, 607
  - edge precision, 607
- Laplacian, 590, 604–605
- laser, 88, 99
- laser protection classes, 99
- latency, 409
- law of reflection, 208
- law of refraction, 208, 210
- LCD shutter, 365
- LED, 88, 95
- lens
  - aperture, 521
  - vignetting, 520
- lens aberrations
  - astigmatism, 610
  - chromatic, 610
  - coma, 610
- LGN, *see* lateral geniculate nucleus, *see* lateral geniculate nucleus
- libdc1394, 420
- lifetime, 89–91, 93, 94, 96, 98, 100, 401
- light, 82, 205
  - infrared, 82
  - ultraviolet, 82
  - visible, 82
- light color, 116
- light deflection, 199
- light distribution, 131
- light emitting diode, 95
- light filter, 138
- light perception, 84
- light propagation, 83
- light ray, 83, 205
- light shielding, 715, 716
- light source, 88
  - life-span, 717
  - wavelength, 718
- light-slit method, 167
- lighting control, 186
- lighting systematic, 154
- lighting technique, 150, 154
- lighting with through-camera view, 170
- limit switch, 497
- line
  - Hessian normal form, 613
- line fitting, 613–617
  - outlier suppression, 614–617
  - robust, 614–617
- line frequency, 741–743
- line scan, 436, 458
- line spread function, 301, 317
- Line Valid, 439
- line-scan processing, 740
- linea camera model, 243
- linear, 289

- linear system, 288
- linearity, 401
- Linux, 479
- Lommel, 278
- Lommel functions, 280
- look-up table, 401, 502, 517, 522
- low pass filter, 297
- LSF, 317
- Luminance, 126, 432
- luminance channel, 23, 27
- luminance distribution, 132
- luminance indicatrix, 132
- luminance of the object, 128
- luminescence radiator, 88
- luminous efficiency, 89
- luminous intensity, 125
- LUT, 401, 502, *see* Look-up table
- LVDS, 428, 436
- LWP, 142
  
- M cone, 11, 27, 30
- machine vision, 362
- machine vision hardware, 152
- machine vision software, 152
- magnification ratio, 214
- magnocellular pathway, 23, 27
- major axis, 557–558, 562, 564, 565, 614, 615
- manufacturing tolerances, 325
- marginal ray, 236
- market growth, 694
- mass production, *see* production, mass
- material flow, 695
- mathematical operator, 288
- maximum filter, *see* Morphology, gray value, dilation
- maximum likelihood estimator, 676
- mean filter, 527–530, 534, 543, 549, 550, 592, 632
  - frequency response, 531–532, 632
- mean squared edge distance, 639–640
- measuring error, 182
- mechanical shutter, 365
- median filter, 534–536, 549, 550
- memory, 485
- memory handling, 500
- metal vapor lamp, 91
- microlens, 381
- microlenses, 381
- minimum filter, *see* Morphology, gray value, erosion
- Minkowski addition, 568–569, 573, 583
- Minkowski subtraction, 570–571, 573, 583
- minor axis, 557–558, 562, 564, 565, 614
- mirror, 200
- missing codes, 401
- modulation transfer function, 6, 19, 321
  
- moiré pattern, 7
- moments, 557–559, 561–564
  - invariant, 558
- monitoring, *see* evaluation, monitoring
- monochromatic aberration, 9
- monochromatic light, 96, 99, 116
- morphological adaptation, 9
- morphology, 566–586, 667
  - duality
    - dilation–erosion, 573, 584
    - hit-or-miss transform, 575
    - opening–closing, 578, 584
  - gray value
    - closing, 584–586
    - complement, 584
    - dilation, 583
    - erosion, 583–584
    - gradient, 586
    - Minkowski addition, 583
    - Minkowski subtraction, 583
    - opening, 584–586
    - range, 586
  - region, 566–582
    - boundary, 573–574
    - closing, 577–578
    - complement, 567
    - difference, 567
    - dilation, 568–570, 573–574, 604
    - distance transform, 580–582, 639, 641
    - erosion, 571–574
    - hit-or-miss opening, 576
    - hit-or-miss transform, 574–575, 579
    - intersection, 567
    - Minkowski addition, 568–569, 573
    - Minkowski subtraction, 570–571, 573
    - opening, 575–577
    - skeleton, 578–580
    - translation, 567
    - transposition, 567
    - union, 566–567
  - structuring element, 567–568, 574, 583
- mosaic, 454
- motion blur, 697, 735–739
  - computation, 738, 739
- motion sensitivity, 3, 23
- motional blurring, 137, 192
- movements, 714, 721, 735, 737, 750, 765
  - adjustment, 714
  - change-over, 714, 717
  - process, 714
- MTF, 321
  - semiconductor imaging device, 302
- multi coated lens, 144
- multi-drop, 464

- multithreading, *see* interface, multithreading
- myopia, 3
- natural light, 122
- natural vignetting, 129, 323
- near cells, 29
- near limit, 248
- near point, 245
- negative principal points, 227
- neighborhood, 574, 580
- neural network, 677–681, 685–687
  - activation function
    - hyperbolic tangent, 680
    - logistic, 680
    - sigmoid, 680
    - softmax, 680
    - threshold, 677, 679
  - multi-layer perceptron, 678–681, 685–687
    - training, 680–681
  - single-layer perceptron, 677–678
  - universal approximator, 679, 680
- neutral density filter, 143, 146
- neutral filter, 146
- Node\_Id, 418, 419
- noise, 420, 525–526
  - suppression, 526–536
  - variance, 525, 527, 528, 533–534
- noise floor, 423
- nondestructive overlays, 492, 494
- nonintegrating sensors, 374
- nonmaximum suppression, 588, 600–601
- normal distribution, 676
- normalized cross correlation, 628–631, 663
- normalized moments, 557–615
- NTSC, 429, 456, 457
- null direction, 21
- numerical aperture, 240
  - image side, 262
- Nyquist band pass, 309
- Nyquist frequency, 315, 321
- Nyquist limit, 8
- Nyquist sampling theorem, 307
- object
  - virtual, 215
- object field angle, 231
- object field stop, 239
- object plane, 158
- object recognition, *see* applications
- object side field angle, 231, 241
- object side focal length, 219
- object side telecentric perspective, 257
- object side telecentric system, 260
- object space, 218, 229
- obliquity factor, 271
- occlusion, 638, 641, 646
- OCR, *see* optical character recognition
- ocular dominance column, 26
- ON and OFF channels, 21
- onboard memory, 501
- one shot, 409
- one-chip, 396
- one-dimensional representation, 300
- opening, 575–577, 584–586
- optic nerve, 11, 13, 30
- optic nerve head, 3
- optical axis, 3, 212
  - eye, 3
- optical character recognition, 519, 537, 538, 555, 556, 666–688
  - character segmentation, 667–668
    - touching characters, 667–668
  - classification, *see* Classification
  - features, 669–671
  - image rectification, 541, 543, 667
- optical density, 139
- optical path difference, 274
- optical path length, 140
- optical transfer function, 296
- orientation, 334, 557–558, 560, 562, 565
  - exterior, 611
  - interior, 611, 654
    - camera coordinate system, 654
    - distortion coefficients, 654, 658
    - focal length, 654
    - pixel aspect ratio, 654
    - pixel size, 654
    - principal distance, 654
    - principal point, 654
  - relative, 654
    - base, 655
    - base line, 656
- orientation column, 26
- OTF, 296
  - multiplication rule, 315
- outlier, 613, 614
- outlier suppression, 614–620
  - Huber weight function, 615
  - random sample consensus, 617
  - RANSAC, 617
  - Tukey weight function, 616
- output, 414
- overtemperature, 103
- PAL, 429, 456, 457
- palettes, 494
- parallax, 29
- parallel capturing, 739
- parallel lighting, 156
- parallel offset, 140
- parameter data, *see* data, parameters
- parasitic sensitivity, 378

- paraxial region, 212
- part handling, *see* production, part handling
- partial bright field illumination, 159
- parvocellular pathway, 23, 27
- PC-based systems, *see* systems, PC-based
- PCI, 428, 464, 470
- PCI Express, 428, 465, 466, 470
- PCI-X, 428, 466, 470
- performance, 479
- permissible defocusing tolerance, 281
- permissible size for the circle of confusion, 249
- perspective, 251
- perspective transformation, 538–539, 543, 667
- pharoid ray, 237
- Phase Lock Loop, 432
- photo response nonuniformity, 422
- photodiodes, 374
- photogrammetry, 333
- photometric inverse square law, 127
- photometric quantity, 125
- photon, 15, 83
- photon counter, 27
- photon noise, 17, 21, 421
- photoreceptor, 1, 3, 6, 8, 13, 14, 27, 29, 30
- phototransduction, 14, 30
- photovoltaic effect, 373
- pinhole camera, 208, 252
- pinning
  - cameras, 711
- pipelined global shutter, 377
- pixel, 302, 305, 364, 370–377, 379, 381, 382, 384, 386–389, 392, 396–398, 400–403, 405–407, 410, 421, 511–512
- pixel sensitivity function, 302
- plane wave, 270
- platform, 479
- PLC, 708, 726, 728–733, 746, 748, 749, 769
- PLL, 388, 432
- PNG, 491
- point spread extension, 284
- point spread function, 291
- Poisson statistics, 15
- polar coordinates, 544
- polar transformation, 544, 667
- polarization, 122
- polarization filter, 142, 147
- polarization phenomena, 269
- polarized light, 122
  - circular, 122
  - elliptical, 122
  - linear, 122
  - unpolarized, 122
- polarizer, 123
- polling, 480
- polygonal approximation, 620–622
  - Ramer algorithm, 621–622
- Portable Network Graphics, 491
- pose, 536–537, 625
- position recognition, *see* applications, position recognition
- position variation, 712
- power, 414
- power supply, 721, 722, 753
  - uninterruptible, 722
- precision, 605–606, 718
  - edge angle, 645
  - edges, 606–607
  - hardware requirements, 607
- preferred direction, 21, 24, 31
- presynaptic, 15
- Prewitt filter, 598
- primary colors, 370, 396
- principal plane, 217
  - image side, 217
  - object side, 217
- principal point, 340, 654
- principal ray, 236
- principle of triangulation, 166
- prism, 199
- PRNU, 422
- processing, 482
- processing time, 135
- production
  - batch, 696
  - continuous, 696, 697, 734, 737
  - continuous motion, 732, 737
  - cycle time, 735, 758, 759
  - discrete motion, 735, 742
  - discrete unit, 697, 699, 736
  - job-shop, 698
  - mass, 696, 698
  - part handling, 735
- progressive scan, 365, 367, 369–371, 383, 431
- projection, 182
- projection centre, 208, 209, 243, 253
- projective transformation, 208, 538–539, 543, 626, 667
- PSF, 291
- pulse mode, 189
- pulse-duty-factor, 96, 104
- pupil, 5, 11, 14, 31
- pupil function, 278
- pupil magnification ratio, 229, 242, 267
- PXI, 464–466
- quadrature encoder, 499
- quantization noise, 423
- r-table, 644

- radial spatial frequency, 301
  - radiant intensity, 125
  - Radii of curvature, 220
  - radiometric camera calibration, 519–524, 610
    - calibration target, 520
    - chart based, 520–521
    - chart-less, 521–524
      - defining equation, 522
    - gamma response function, 520, 524
    - inverse response function, 522
      - discretization, 522–523
      - normalization, 523
      - polynomial, 524
      - smoothness constraint, 523–524
    - response function, 520, 521, 524
  - radiometric quantity, 125
  - Ramer algorithm, 621–622
  - rank filter, 536, 584
  - rapid-prototyping, 705
  - RGB to YUV, 406
  - real object
    - real, 214
  - receptive field, 20, 21, 23, 24, 31
  - recipes, *see* data, type data
  - reciprocity equation, 225
  - recognition, *see* evaluation, recognition
  - reduced coordinates, 279
  - reflectance, 107, 110, 127
  - reflection, 107, 205
    - directed, 108
    - irregular diffuse, 108
    - regular diffuse, 108
  - reflection law, 107
  - refraction, 115, 205
  - refraction law, 83
  - refractive index, 210
  - region, 513–515
    - as binary image, 513, 552, 556, 566, 567, 569, 573, 579
    - boundary, 560, 573–574
    - characteristic function, 513, 561, 562, 583
    - complement, 567
    - connected components, 551–552, 667
    - convex hull, 560
    - definition, 513
    - difference, 567
    - feature, *see* features, region
    - intersection, 567
    - run-length representation, 514–515, 552, 556, 557, 566, 567, 569, 579
    - translation, 567
    - transposition, 567
    - union, 566–567
  - region of interest, 504, 513, 537, 539, 570, 582, 604, 626
  - regular diffuse reflection, 108
  - relative illumination, 323
  - relative irradiance, 323
  - relative orientation, 654
    - base, 655
    - base line, 656
  - remote maintenance, 750, 773
  - removal of surface reflexes, 123
  - representation, 294
  - representation space, 294
  - reproducibility, 711, 716, 717
  - reset noise, 422
  - Resolution, 455
  - resolution, 382, 485
  - resolution limit, 321
  - result data, *see* data, results
  - retina, 3, 6, 12, 13, 21, 30, 31
  - RGB, 432, 486
  - rhodopsin, 17
  - rigid transformation, 625, 637, 647
  - ring, 483
  - ring light, 169
  - rod photoreceptor, 14
  - rods, 7, 14, 17, 18, 21, 30
  - ROI, 504, *see* region of interest
  - rolling curtain, 376
  - rotation, 538, 541, 559, 625, 637, 667
  - RS-170, 429, 456, 457
  - RS-232, 414
  - RS-422, 428, 436
  - RS-644, 436
  - RS232, *see* interface, serial
  - run-length encoding, 514–515, 552, 556, 557, 566, 567, 569, 579
- 
- S cone, 11, 27
  - S-Video, 433
  - sampling interval, 6
  - sampling theorem, 7
  - saturation, 14, 30, 135
  - scaling, 538, 542–543, 559, 625, 637
  - scattering, 107
  - secondary wavelet, 268
  - security, *see* systems, security
  - segmentation, 544–555
    - connected components, 551–552, 667
    - dynamic thresholding, 548–550, 586, 667
    - hysteresis thresholding, 601–602
    - subpixel-precise thresholding, 553–555, 604
    - thresholding, 545–548, 667
      - automatic threshold selection, 546–548, 667
  - sensitivity, 365, 382, 423
  - sensor, 511–512
  - sequence, 483

- SG pulse, 384
- shading correction, 402, 507
- shading images, 403
- Shannon, 7
- shape check, *see* applications, shape check
- shift theorem, 313
- shifting property, 289
- short-wavelength pass filter, 142
- shutter efficiency, 378
- shutter speed, 739
- shutter time, 136, 193, 521
- SI, 125
- signal
  - bandwidth, 723, 724, 748, 750
  - frequency, 723, 741–743, 768
- signal to noise ratio, 401, 424
- signal-to-noise ratio, 594, 606, 607, 645
- similarity measure, 626–631
  - normalized cross correlation, 628–631, 663
  - sum of absolute gray value differences, 626–630, 662
  - sum of squared gray value differences, 626–628, 662
- similarity transformation, 626, 637, 647
- simple cells, 24
- skeleton, 578–580
- skew, 538
- slant, 538
- smallest enclosing circle, 559–560, 565
- smallest enclosing rectangle, 559–560, 565, 669
- smart camera, 427, *see* systems, compact systems
- smart cameras, 479
- smear, 365, 372
- smoothing filter, 525–536
  - Gaussian, 532–534, 543, 548–550, 595, 599, 632
  - frequency response, 533
  - mean, 527–530, 534, 543, 549, 550, 592, 632
  - median, 534–536, 549, 550
  - optimal, 532–533, 595, 599
  - spatial averaging, 527–530
  - temporal averaging, 526–527
- snap, 481
- SNR, 401
- Sobel filter, 598
- solid angle, 126
- solid state material, 96
- space variant nature of aliasing, 312
- space-invariance, 291
- spatial averaging, 527–530
- spatial depth, 251
- spatial frequencies, 274
- spatial frequency, 5–7, 12, 31, 296
- spatial frequency components, 298
- SPC, *see* statistical process control
- speckle, 157
- speckle pattern, 99
- spectral band, 91
- spectral opponency, 23
- spectral response, 84, 139
  - Gaussian filter, 533
  - mean filter, 531–532, 632
  - sensor, 512
- spectral sensitivity, 386, 390, 394, 398
- spectral transmittance, 323
- spectrum, 90
- spectrum of light, 82
- speed, 382
- spherical aberration, 5
- spherical wave, 270
- spikes, 18, 19
- spontaneous spike activity, 19
- spurious resolution, 7
- square pixel, 371
- stabilization, 90
- standardization, 702, 709, 717, 725, 771
- standardized viewing distance, 250
- static lighting, 190
- statistical process control, 699
- stereo geometry, 654–661
  - corresponding points, 655
  - disparity, 660–661
  - epipolar line, 656
  - epipolar plane, 655
  - epipolar standard geometry, 658–659
  - epipole, 656
  - image rectification, 659–660
- stereo matching, 662–666
  - robust, 665–666
    - disparity consistency check, 665
    - excluding weakly textured areas, 665
  - similarity measure
    - normalized cross correlation, 663
    - sum of absolute gray value differences, 662
    - sum of squared gray value differences, 662
  - subpixel accurate, 664
  - window size, 664–665
- stereo reconstruction, 653–666
- stereopsis, 29, 31
- stochastic process, 525, 527
  - ergodic, 527
  - stationary, 525
- streaking light, 174
- Strehl ratio, 281
- strobe, 370
- strobe light, 497
- strongly translucent part, 184

- structured bright field incident light, 165
- structured light, 166
- structured lighting, 157
- structuring element, 567–568, 574, 583
- sub sampling, 369
- sub-pixel region, 302
- sub-sampling, 382
- subpixel-precise contour, 515–516
  - convex hull, 565
  - features, *see* features, contour
- subpixel-precise thresholding, 553–555, 604
- sum of absolute gray value differences, 626–630, 662
- sum of squared gray value differences, 626–628, 662
- superdiffuse ring lights and shadow-free lighting, 171
- SuperHAD, 381
- superposition integral, 271
- support vector machine, 681–687
  - kernel, 684
    - Gaussian radial basis function, 684
    - homogeneous polynomial, 684
    - inhomogeneous polynomial, 684
    - sigmoid, 684
  - margin, 682
  - separating hyperplane, 682–683
  - universal approximator, 684
- surface inspection, *see* applications, surface inspection
- SVGA, 379
- SWP, 142
- synaptic plasticity, 30
- sync bit, 410
- sync pulse, 388
- synchronization, 194
- synchronization of flash lighting, 193
- system of lenses, 231
- systems
  - application-package, 705, 706
  - compact systems, 703, 704, 707, 723–725, 729
  - library-based, 705
  - PC-based, 703–705, 750, 751
  - security, 704, 705, 750
  - types of, 700–708
  - vision controllers, 704
  - vision sensors, 702, 707, 725, 741
- Tagged Image File Format, 491
- tangential spatial frequency, 301
- tap, 496
- TCP, 451
- TCP/IP, 724, 725, 729, 731, 750, 766
- telecentric bright field incident light, 163
- telecentric bright field transmitted lighting, 180
- telecentric lighting, 156, 180
- telecentric objective, 156
- telecentric on axis light, 163
- telecentric perspective, 260
- telecentric system, 251
  - object side, 260
- telescope magnification, 263
- temperature compensation, 189
- temperature radiator, 88
- template matching, 624–653, 667
  - clutter, 638, 641, 646
  - erosion, 572
  - generalized Hough transform, 642–646
    - accumulator array, 642–645
    - R-table, 644
  - geometric hashing, 646–648
  - geometric matching, 646–652
  - Hausdorff distance, 640–642
  - hierarchical search, 633–636
  - hit-or-miss transform, 574
  - hypothesize-and-test paradigm, 646
  - image pyramid, 632–636
  - linear illumination changes, 628
  - matching geometric primitives, 648–652
  - mean squared edge distance, 639–640
  - nonlinear illumination changes, 638, 646
  - occlusion, 638, 641, 646
  - opening, 576
  - robust, 638–653
  - rotation, 637–638
  - scaling, 637–638
  - similarity measure, 626–631
    - normalized cross correlation, 628–631, 663
    - sum of absolute gray value differences, 626–630, 662
    - sum of squared gray value differences, 626–628, 662
  - stopping criterion, 629–631
    - normalized cross correlation, 630–631
    - sum of absolute gray value differences, 629–630
  - subpixel accurate, 636–637
  - translation, 626–636
- temporal averaging, 526–527
- temporal control, 189
- test object, 105, 152
- thermal noise, 17
- thickness of the lens, 220
- thin films, 143
- thin lens, 221
- three field readout, 369
- thresholding, 545–548, 667

- automatic threshold selection, 546–548, 667
  - subpixel-precise, 553–555, 604
- throughput, 469
- TIFF, 491
- tilt rule, 216
- time response, 409
- time-invariant system, 291
- timing, 497
- topography, 168
- total reflection, 111
- traceability, 694, 726, 728, 732
- transfer function, 295
- transfer function of the pixel, 304
- transformation
  - affine, 537–538, 559, 626, 646
  - geometric, 536–544, 667
  - gray value, 516–519
  - image, 539–544
  - perspective, 538–539, 543, 667
  - polar, 544, 667
  - projective, 538–539, 543, 626, 667
  - rigid, 625, 637, 647
  - rotation, 538, 541, 559, 625, 637, 667
  - scaling, 538, 542–543, 559, 625, 637
  - similarity, 626, 637, 647
  - skew, 538
  - slant, 538
  - translation, 538, 558, 567, 625, 637
- translation, 538, 558, 567, 625, 637
- transmission, 110, 112, 138, 139
  - diffuse, 112
  - directed, 112
  - irregular diffuse, 112
- transmission
  - through the lens, 129
- transmission chain, 304
- transmittance, 112, 127
- transmitted lighting, 158
- transposition, 567
- trichromatic, 27
- trigger, 407, 459, 697, 701, 713, 732, 738–740, 742
- triggering, 497
- triggering pulse, 190
- tristimulus theory, 396
- tukey weight function, 616
- two field readout, 369
- type data, *see* data, type data
  
- UART, 439
- UDP, 451
- ultraviolet light, 121
- uninterruptible power supply, *see* power supply, uninterruptible
- union, 566–567
  
- unit production, *see* production, discrete unit
- Universal Serial Bus, 428
- unpolarized light, 122
- UPS, *see* power supply, uninterruptible
- USB, 383, 440, 441, 457, 475, *see* interface, USB
- USB2.0, 425
- user interface, *see* human machine interface
- user mode, 475
- UV, 82, 121, 386
- UV blocking filter, 144
  
- variable height acquisition, 499
- VB.NET, 477
- veiling glare, 325
- velocity of light, 206
- ventral stream, 25
- verification, *see* evaluation, verification
- vertical synchronization, 431
- vertices, 220
- VGA, 379
- VHA, 499
- vibrations, 736
- video data format, 410
- video formats, 406
- video signal, 305
- video standard, 379
- vignetting, 132, 520
- VIS, 82, 116, 118
- visible light, 116, 118
- vision controllers, *see* systems, vision controllers
- vision sensors, *see* systems, vision sensors
- Visual Basic, 476
- visual cortex, 13, 23, 25, 26, 29
- vitreous chamber, 3
- Vsync, 431–434
- VxWorks, 479
  
- wave equation, 205
- wave nature of light, 268
- wave number, 270
- wave–particle dualism, 83
- wavefront
  - plane, 207
  - spherical, 207
- wavefront aberration, 281
- waveguides, 8
- wavelength, 210, *see* light source, wavelength
- WDM, 420
- Web server, *see* interface, network
- weight function
  - Huber, 615
  - Tukey, 616
- white balance, 399

- white balancing, 490
- white light, 118
- Windows, 479
- windows, 239
- wiring, 725, 739
- wood effect, 120
- working distance, 140, 710–712
- world coordinates
  - from single image, 611
  - from stereo reconstruction, 653–666
  
- Xenon flash lamp, 92
- Xenon lamp, 92
  
- YUV, 480
  
- zero crossing, 588, 590, 604