

Index

Page numbers followed by *t* indicate tables.

- A interface, 3
- A-bis interface, 1
- Abstract syntax notation, 26–28
- Access point name, 227
 - Network identifier, 227
 - Operator identifier, 227
- Active location retrieval, 278–280
- Activity test, 79, 175, 248
- Additional calling party number, 77, 174
- Address complete message, 53, 311
- Advanced IN, 11
- Advice of charge, 4, 106, 252, 310
- Age of location, 52, 190
- Alerting pattern, 52, 141
- Answer (ISUP message), 16
- Any time interrogation, 44, 90
 - Any time interrogation for CS domain, 334–335
 - Any time interrogation for PS domain, 335–336
- Any time modification, 281–283, 336
- Any time subscription interrogation, 281
- Application context, 28, 173, 200, 351, 371
- Apply charging, 33, 97, 121, 246
- Apply charging report, 97, 247
- Arming, 17–18, 248
 - Dynamic arming, 71
 - Explicit disarming, 18
 - Implicit disarming, 18
 - Static arming, 71
 - Transparent arming, 76
- Assist request instructions, 133
- Authentication centre, 1

- Base station, 190
- Base station controller, 1

- Base station system application part (BSSAP), 3
- Base transceiver station (BTS), 1
- Basic call handling, 46, 162
- Basic call state model (BCSM), 15–17, 69–75, 162–173
 - O-BCSM, 69, 162–169, 196, 380
 - T-BCSM, 70, 169–173, 297
- Basic encoding rules, 27–28
- Basic end, 17
- Basic service, 6–9, 46, 151, 261, 319
 - Compound basic service, 151
- Bearer capability, 7, 323
- Bearer independent call control, 369
- Bearer services, 7
- Bellcore, 11
- Billing gateway, 104
- Bothway through connection, 122

- Call barring, 9*t*, 46, 180–181, 270, 306
- Call deflection, 181, 215, 319
- Call detail record, 43, 269–270, 355–359
 - CAMEL destination number, 124*t*, 358
 - CDR correlation, 269–270, 367
 - Composite CDR, 359
 - G-CDR, 258, 358
 - Global call reference, 369–370
 - Level of CAMEL service, 259, 358
 - M-CDR, 258, 358
 - S-CDR, 258
- Call forwarding, 41, 113, 207, 318, 359
 - Call forwarding notification, 96, 112–117, 207, 318–319
 - Conditional call forwarding, 61, 114
 - Early call forwarding, 51, 113–114, 205
 - Forwarding counter, 171

- Call forwarding, (*continued*)
 - Forwarding interrogation, 214
 - Forwarding pending indicator, 141
 - Late call forwarding, 55, 96
 - SCP-induced call forwarding, 171, 222
 - Unconditional call forwarding, 170, 319
- Call gap, 211–213
- Call hold, 178
- Call information report, 102–104
- Call information request, 121
- Call party handling, 290–305, 370
 - Call segment, 291
 - Call segment association, 290
 - Parallel alerting, 302
 - Signalling Transparency, 303–305
 - Surrogate leg, 294
- Call period, 96, 218, 316
- Call progress, 311
- Call reference number, 367–368
- Call waiting, 65, 178
- Called party bcd number, 77, 232, 341, 380
- Called party number, 79, 136, 197, 339, 378
- Calling line identity, 209, 331
- Calling name presentation, 270
- Calling party number, 78, 120, 268, 381–382
- Calling party's category, 77
- CAMEL, 6, 19, 40, 100, 187, 288, 357, 371
 - CAMEL application part, 24–26, 75–79, 350–351
 - CAMEL capability handling, 161, 198, 350
 - CAMEL capability negotiation, 22, 86, 228, 309, 371
 - CAMEL service information, 37
 - Offered CAMEL4 CSIs, 335
 - Offered CAMEL4 functionalities, 378
 - Partial CAMEL Phase 4 support, 289
 - PSI-enhancement, 372
 - Supported CAMEL Phases, 23, 228, 287
- Cancel, 128
- Capability set, 11, 126
- Carrier selection, 140, 203
- Cause, 79, 165
 - Cause code, 79, 165
 - Cause diagnostics, 223–224
 - Location code, 169
- Cell global Id, 192
- Cell Id, 192
- Charge advice information, 106
- Charging gateway function, 355
- Charging Id, 258
- Circuit switched, 3, 219
- Clearing house, 365–366
- Closed user group, 180
- Code division multiple access, 11, 190
- Collect information, 380
- Completion of calls to busy subscriber, 179
- Connect (CAP operation), 138, 214
- Connect (ISUP message), 305
- Connect to resource, 91
- Connected line identity, 210
 - Additional connected number, 382
 - Connected number, 210, 381–382
- Consultative Committee for International Telegraphy and Telephony (CCITT), 30
- Content delivery system, 378
- Continue, 17, 76
- Continue with argument, 200
- Core network, 1, 24, 81, 190, 355
- Correlation Id, 81, 134
- Country code, 5, 191
- CSI-active, 212
- Current location, 63, 279, 309
- D interface, 3
- D-CSI, 198–199
- D-IM-CSI, 353
- Default call handling, 67–68, 101, 358
- Delete subscriber data, 43
- Detection point, 70–72, 163–169, 202, 315
 - Event detection point – interrupt, 16
 - Event detection point – notify, 16
 - Trigger detection point, 67, 265*t*, 328*t*
- Dialled service, 197, 373,
 - Enhanced dialled service, 373–375
 - Serving network based dialled services (N-CSI), 380
- Dialled services, 288,
 - Subscribed dialled services, 196–202
- Dialogue, 17–19, 79, 135, 239, 286
 - Assisting dialogue, 133
 - Dialogue correlation, 134
 - Dialogue portion, 245
 - Long dialogue, 373
 - Short dialogue, 200, 373
- Digital subscriber signalling, 16, 379
- Direct transfer application part, 3, 12
- Disconnect forward connection, 130
- Disconnect forward connection with argument, 383

- Disconnect leg, 297
- Dual tone multi frequency(DTMF), 126, 312
- E-parameters, 106
- E.164 number, 6, 174, 193, 345
- Ellipsis, 26, 279, 325, 361
- Emergency call, 6, 151
- End-user address, 256
- Enhanced data rates for GSM evolution, 260
- Entity released, 259
- Equal access, 139–141
- Equipment identification register, 1
- Establish temporary connection, 141, 200, 378
- ETSI technical specification, 19
- European norm, 93
- European telecommunication standardisation institute, 11
- Event report BCSM, 76, 164
- Explicit call transfer, 177–178, 208
- Extension container, 26–27
- Extension marker, 26, 361, 371
- Facility, 107, 304_t
- Final assembly code, 6
- Finite state machine, 72, 130, 239
 - Idle, 64, 284, 332
 - Monitoring, 74, 143, 245
 - Waiting for instructions, 47, 164, 266, 329
- Follow-on calls, 171
- Forwarded-to-number (FTN), 87, 284
 - Long FTN, 213
 - Short FTN, 147–149
- Fraud detection system, 144, 223
- Fraud information gathering system, 144
- Free format data, 105, 215–216
 - Append indicator, 215
- Freephone, 203, 353
- Furnish charging information, 121, 266, 329
- Gateway GPRS service node, 189_t
- Gb interface, 190_t
- Ge interface, 190_t
- General packet radio service (GPRS), 224–260, 324–325, 358
 - GPRS control scenario, 237
 - GPRS reference number, 244–245
 - GPRS session, 229–230
- Generic number, 77, 359, 382
- Generic tunneling protocol (GTP), 225
 - GTP-C, 225
 - GTP-U, 225
- Geodetic information, 193
- Geographical information, 192–193
- Gi interface, 190_t
- Global title, 30–31
 - Global title translation, 30
 - Translation type, 341
- Gn interface, 190_t
- Gp interface, 190_t
- GPRS-CSI, 228–229, 325
- gprsSSF, 239–240
- Gs interface, 190_t
- GSM association, 359
- gsmSCF, 47, 111, 242, 308, 372
- gsmSRF, 129–131, 303
 - External gsmSRF, 129–131
 - Integrated gsmSRF, 129–131
- gsmSSF, 33, 73–74, 101, 203, 312, 374
 - Assisting gsmSSF, 131, 137
- Gy interface, 260
- Handover notification, 375
 - Notification criteria, 375
- High layer compatibility, 9
- High speed circuit switched data, 185
- HLR interrogation, 40, 183, 322
 - First interrogation, 53
 - Second interrogation, 53
- Home location register, 1
- Home zone, 63, 315, 375
- IN application part, 11
- Information element, 13, 60, 114, 268, 311
- Information flow, 42–67, 89–91, 275, 335
- Initial address message, 27, 40, 196
- Initial DP, 17, 75, 141, 322, 372
- Initiate call attempt, 305, 373
- Insert subscriber data, 30, 282
- Integrated Services Digital Network (ISDN), 3
- Intelligent networks, 11–36
- Intelligent peripheral, 137–138
- International mobile equipment identifier, 6, 323–324
- International mobile subscriber identity, 4–5
- International mobile telephony 2000, 187
- International Standards Organisation, 28
- International Telecommunication Union, 11

- Internet, 242, 336
- Internet engineering task force, 196
- Internet protocol, 342
- Invoke Id, 131
- IP Multimedia system, 342
 - ARPA, 344
 - Back-to-back user agent, 349
 - Call session control function, 343
 - Domain name server, 226, 344
 - Enum server, 344
 - Home subscriber system, 343
 - IM-SSF, 346, 347
 - IMS Service control, 344
 - Initial filter criteria, 344
 - SIP Application Server, 344
 - User agent, 349
- ISDN user part (ISUP), 3, 11, 48, 168, 223, 303, 376
 - ISUP 97, 136
 - Overlap sending, 380
- Iu interface, 190*t*
- Iu-bis interface, 190*t*
- Iu-cs interface, 190*t*
- Iu-ps interface, 190*t*
- Iur interface, 190*t*

- Lawful intercept, 176, 269
- Lightweight directory access protocol, 272
- Load sharing, 34–35, 177
- Local exchange, 339
- Local service area, 194
- Location area code, 192
- Location area identifier, 192, 375
- Location information, 63, 174, 189–194, 335
- Location services, 278
- Location update, 22–24, 46, 228, 333
- Low layer compatibility, 319

- M-CSI, 275, 287
- Media gateway, 195, 317
- Megaco, 196
- Message transfer part, 29
- MG-CSI, 332
- Mid-call detection, 312–314
- MO-SMS-CSI, 263, 325
- Mobile application part (MAP), 3, 261*t*
 - MAP segmentation, 30
- Mobile country code, 5, 191
- Mobile equipment, 4, 323
- Mobile forwarded call, 45, 139
- Mobile network code, 5, 191
- Mobile number portability, 40, 336–342
- Mobile originated call, 46–49, 140, 191
- Mobile services switching centre (MSC), 189*t*
 - Anchor MSC, 255, 315
 - Gateway MSC, 1, 39, 379
 - GMSC number, 53
 - MSC number, 193
 - Serving MSC, 2, 22, 67, 106, 269, 359, 373
 - Split-MSC architecture, 194–196, 313
 - Visited MSC, 3, 39, 132, 379
- Mobile station, 4, 12, 152, 262, 357
 - GPRS MS class, 336
 - Mobile station classmark, 334
- Mobile station ISDN number, 5–6, 339
- Mobile station roaming number, 6, 43, 204
- Mobile subscriber identification number, 5
- Mobile terminated call, 2, 63, 153–154, 221
- Mobility management, 273–276, 331–333
 - CS mobility management, 273, 332
 - PS mobility management, 332
- Move leg, 296
- MSC service area, 4, 95
- MT-SMS-CSI, 328
- Multi party, 179–180
- Multiple association control function, 137
- Multiple subscriber profile, 186, 219–223

- N-CSI, 202, 353, 375
- National destination code, 5, 194
- Network determined user busy, 54
- Network-initiated call establishment, 305–309
 - New call (NC call), 100, 294
 - New call party (NP call), 294
- Node-B, 225
- Notify subscriber data change, 283, 347
- Number portability, 40, 337
 - Mobile number portability, 40, 336–342
 - Signaling relay function, 63, 339–340

- O-CSI, 66–68, 161, 197, 318, 374
 - O-CSI applicable, 77, 319
 - Suppress O-CSI, 319
- O-IM-CSI, 353
- Object identifier, 28
- Open System Interconnection, 28
- Operation, 24, 76, 130, 233, 295
 - Linked operation, 299
 - Operation argument, 27
 - Operation class, 324

- Operation error, 25, 317
- Operation parameters, 22
- Operation result, 79, 166
- Operation timer, 159, 247
- Operator determined barring, 259
- Optimal routing, 55, 182, 184, 202, 309–310
 - Basic optimal routing, 182–184, 310
 - Optimal routing at late call forwarding, 115, 214
- Original called party Id, 78, 378
- Packet data protocol (PDP), *see* PDP Context, 225
- Packet switched, 187
- PDP Context, 225–227, 343, 358
 - Network-initiated PDP context, 256
 - PDP address, 256
 - PDP establishment, 236
 - PDP establishment acknowledgement, 237
 - PDP initiation type, 226*t*
 - Secondary PDP context, 256–257
- Permanent reference document, 359
- Personal communication system, 11, 188*t*
- Play announcement, 125
- Play tone, 317
- Point in call, 311
- Post-paid, 92, 272
- Pre-arranged end, 17, 242
- Pre-paging, 284
- Pre-paid, 80–82, 92, 205, 338, 365
- Premium rate, 203, 353, 379
- Prompt and collect user information, 126
- Protocol data unit, 226
 - T-PDU, 226
- Provide roaming number, 43*t*, 306
- Provide subscriber information, 193
- Public land mobile network (PLMN), 1
 - Home PLMN, 2
 - Interrogating PLMN, 2
 - Visited PLMN, 2, 66
- Public switched telephone network, 11
- Quality of service (QoS), 252–253
 - Negotiated QoS, 253
 - Requested QoS, 253
 - Subscribed QoS, 253
- Radio access network, 1, 146, 225
- Radio network controller, 189*t*
- Radio network system, 190*t*
- Real distance charging, 63
- Real-time transport protocol, 196
- Redirecting party Id, 61
- Redirection information, 78, 209
- Relationship, 18–19, 39, 228
 - Control relationship, 18, 241
 - Monitor relationship, 19, 241
- Release (ISUP message), 223
- Release call, 78, 117
- Remote Authentication Dial-In User Service, 260
- Request for comments, 342
- Request report BCSM, 76
- Reset timer, 142–143, 242
- Restore data, 43*t*
- Resume call handling, 45, 173
- Roaming, 3, 24, 95, 259
 - Inbound roaming, 2, 24, 357
 - Outbound roaming, 2
 - Roaming leg, 53, 95, 205, 357
- Route select failure, 218, 352
- Routing area code, 192
- Routing area update, 254–256, 333*t*
- SCP Id, 81
- Send charging information, 121, 201
- Send routing information, 214
- Serial number, 323
- Service area, 192, 333
- Service control function, 15, 39
- Service control point, 39
- Service data point, 93
- Service interaction control, 207–211
 - Backward call indicators, 311
 - Forward call indicators, 210
- Service interaction indicators two, 128
- Service key, 67, 257, 364
- Service logic, 16, 177, 324
- Service network, 345
- Service switching function, 14–15, 39
- Service switching point, 40
- Serving GPRS service node, 189*t*
- Short message service (SMS), 260–273
 - Data coding scheme, 268
 - Mobile Originated SMS, 222
 - Mobile Terminated SMS, 223, 330
 - Short message peer-to-peer, 262
 - Short messages service centre, 2
 - SMS command, 267
 - SMS delivery, 262, 326, 358

- Short message service (SMS), (*continued*)
 - SMS report, 264
 - SMS submission, 262
 - smsSSF, 266, 331
 - Validity period, 268
- Signalling connection control part, 29
 - Blue SCCP, 30, 215
 - Signaling link selection, 246
 - Signaling point code, 35, 157, 327
 - Signaling transfer point, 28, 327
 - White SCCP, 30
- Signalling system no. 7, 28
- Signalling transport, 28
- Single association control function, 137
- Specialized resource function, 196, 312
- Specialized resource report, 125
- Split leg, 292
- SS invocation notification, 146
- SS-CSI, 161, 223
- Stage 1, 2, 3, 21
- State transition, 73, 243, 380
 - Basic state transition, 162
 - Transition beyond basic call, 73, 163
- Subscribed in services, 37
- Subscriber identity module, 227
- Subscriber number, 81, 194, 309
- Subscription data control, 280–283, 336
- Subsystem number, 31–32
- Supplementary service, 9–10, 22, 46, 106, 219
- Supplementary service invocation notification, 144
- Suppression of announcements, 77–78

- T-CSI, 66, 88, 204
 - Suppress T-CSI, 53, 306
- Tariff switch, 110, 252
- Tariff zone, 109–111, 252
- Technical specification, 10, 21, 342
- Tele services, 7
- Temporary connection, 131, 378
- TIF-CSI, 162
- Time division multiple access, 1
- Time division multiplex, 196
- Time zone, 141, 267
- Timer, 74, 123, 200
 - T7, 164
 - T9, 167
 - TC guard timer, 246–247
 - Tccd, 218
- Tcp, 105
- Tdelta, 98
- Tssf, 74–75, 142, 242
- Tsw, 109
- TO-CSI, 379
- Transaction capability application part, 17
 - Blue TCAP, 33
 - TCAP segmentation, 242–247
 - Transaction identifier, 32, 244
 - White TCAP, 32
- Transceiver, 1
- Transfer account procedure, 144, 216, 359–361
 - CAMEL invocation fee, 366
 - CAMEL service level, 366
- Transit exchange, 339
- Translation information flag, 162
- Translation type, 341
- Triggering, 81, 151, 202
 - Conditional triggering, 149, 330–331
 - Number-based triggering, 14
 - Subscription-based triggering, 14
 - Trunk-originated triggering, 379
- Tromboning, 82
- Type approval code, 6

- U-CSI, 157
- UG-CSI, 157
- Um interface, 3
- UMTS subscriber identity module, 227
- Universal computer protocol, 262
- Universal mobile telecommunications system (UMTS), 187
- Universal resource locator, 344
- Universal terrestrial radio access network, 190, 319
- Unstructured supplementary service data, 154
- Update location, 335
- User datagram protocol, 196
- User determined user busy, 54
- User equipment, 6
- User interaction, 121–122, 200, 300, 378
- User-to-user information, 181, 376
- User-to-user signaling, 181, 376
- Uu interface, 190*r*

- Video telephony, 129, 319–321, 376
 - 3G-324M terminal, 320
 - Service change and UDI/RDI fallback, 286*r*, 376
 - Unrestricted digital information, 129, 320*r*

Virtual private network, 79–80
Visitor location register, 1
 VLR number, 193
VT-CSI, 204, 353
 Suppress VT-CSI, 307
VT-IM-CSI, 348

Warning tone, 99–100
 Flexible warning tone, 316–317
 Tone burst, 316
 Tone injection, 317
Wideband CDMA, 225, 320
Wireless IN, 11