

# Index

- AAA, 246
- Access network selection, 307
- Access Point scanning, 171
- Access point, 165
- Access Provider Network, 246
- Access-Accept, 253
- Access-Reject, 253
- Access-Request, 253
- Address Ownership, 101
- Address Resolution Protocol, 15
- Address resolution, 15
- AH, 27
- Alignment requirement, 12
- All-nodes multicast addresses, 14
- All-routers multicast addresses, 14
- Alternate Care-of Address, 86, 96
- Alternate CoA
  - IPsec ESP, 120
- Application Mobility, 44
- Authentication and authorization, 27
- Authentication Header, 27
- Authentication Protocol, 248
- BCE, 346
- Bidirectional tunneling, 55
- Binding Acknowledge (BAck), 91
- Binding Authorization Data option, 94
- Binding Authorization Data, 102
- Binding Cache management, 55, 77
- Binding Cache, 52, 55
  - mobile prefix, 156
- Binding de-registration, 134
- Binding Error, 93
- Binding lifetime, 86
- Binding Management Key, 52
- Binding Management key, 103
- Binding Refresh Advice option, 97
- Binding Refresh Request, 92
- Binding Update, 55, 60, 82
  - 'H' flag, 144
  - 'I' flag, 144
  - 'R' flag, 156
  - Correspondent Node processing, 90
  - Home Agent processing, 84
  - Mobile Node processing, 88
- Binding, 52
- Call State Control Function, 260
- Candidate Access Router Discovery, 172
- CARD, 172
  - centralized approach, 172
  - decentralized approach, 172
- Care-of Address Test (CoT), 102
- Care-of address, 51
- Care-of address, 52
- Care-of Address
  - co-located, 70
  - Foreign Agent, 70
- Care-of Init Cookie, 106
- Care-of Keygen Token, 104
- Care-of keygen token, 107
- Care-of Test (CoT), 65

- Care-of Test Init (CoTI), 65
- Care-of Test Initiate (CoTI), 102
- Care-of Test, 103
- CDMA
  - Packet Control Function, 247
  - Radio Resource Control, 247
- Certificate Authorities, 61
- Challenge Handshake Authentication Protocol (CHAP), 249
- CHAP
  - Challenge, 249
  - CHAP-Password, 249
- Compression Profile Type, 314
- Connectivity latency, 168
- Contact, 258
- Context data representation, 227
- Context feature hierarchy, 227
- Context Transfer
  - context establishment, 226
  - Handover Signaling, 229
  - Header Compression, 224, 311
  - Performance Study, 317
  - predictive, 231
  - QoS, 224
  - Timing, 314
- Cookies, 103
- Core network transparency, 41
- Correspondent Node, 53
- CoC, 103, 108, 354
- CoTI, 106, 353
- CSCF, 260
- DAD probe, 20
- DAD, 18, 88
- Data origin authentication, 27
- DDOS, 111
- Dead Peer Detection, 268
- Delay, 165
- Deregistration
  - Alternate Care-of Address Option, 96
- Destination Options extension header, 12
- DHAAD
  - Reply, 148
  - Request, 148
- DHCPv6, 38
- Diffie-Hellman key exchange, 32
- Digital certificates, 26
- DNS, 3
- Do no harm, 56
- Do No Harm, 63
- Dual-stack, 352
- Duplicate Address Detection, 18, 88
- Dynamic Home Agent Address Discovery, 148
- Dynamic Host Configuration Protocol (DHCP), 17
- Dynamic Host Configuration Protocol for IPv6, 38
- Eager switching, 240
- Encapsulating Security Payload, 27
- Encapsulation, 68
- Encapsulation, 125
  - IPsec, 126
  - IPv6-in-IPv6, 125
- ESP, 27
  - Confidentiality, 27
- EV-DO, 297, 300
- Extension headers, 10
- Fast Binding Acknowledge, 178
- Fast Binding Acknowledgment, 215
- Fast Binding Update, 176, 207
- Fast Handover and Context Transfer Experiments, 322
- Fast Handover, 165
- Fast handover, 167
- Fast Neighbor Advertisement, 180
- FBack, 178, 215
- FBU, 176, 207
- Feature Profile Type, 227
- Flow Label, 9
- FNMA, 180, 220
- FPI, 227
- General Packet Radio System, 41
- Global address, 13
- Global Positioning System, 332
- GPRS, 41
- HAck, 178
- Handover Acknowledge, 178
- Handover Initiate, 178, 218
- Handover planning, 171
- Handover, 4
- Header Compression
  - compressor, 312
  - Context Identifier (CID), 314
  - decompressor, 312
  - First Order, 312
  - Full Header, 312
  - Reference State, 314
  - Second Order, 312
- HI, 178, 218
- Hierarchical Mobile IPv6
  - HMIIPv6, 235
- Home AAA, 246
- Home Address destination option, 78, 126
- Home Address Test (HoT), 102
- Home address, 51
- Home address, 53
- Home Agent Address Discovery Reply, 252
- Home Agent Address Request, 252
- Home Agent Discovery, 71
- Home Agent Information Option, 150
- Home Agent List, 150
- Home Agent option with Home Link Prefix Length, 251
- Home agent
  - BU 'K' bit processing, 121

- BU processing, 121
- Home De-registration, 86
- Home IP Network, 246
- Home Keygen Token, 103
- Home keygen token, 107
- Home Link Prefix, 251
- Home network, 51
- Home network, 53
- Home Test (HoT), 65
- Home Test Init (HoTI), 65
- Home Test Initiate (HoTI), 102
- Home Test, 103
- Hop Limit, 10
- Host AP Driver, 289
- Host-internal triggers, 175
- Hostpart, 257
- HoT, 103, 107, 354
- HvFL, 104, 353
- Identifiers, 29
- IEEE 802.11
  - STA
    - AP, 280
- IEEE
  - 802.11i, 280
  - 802.1X, 280
- IKE phase 2 identifier, 119
- IKE SA, 33
- IKE, 26, 32, 118, 267
  - Aggressive mode, 32
  - DOI, 32
  - Identifier, 33
  - IDs, 29
  - Initiator, 32
  - Main mode, 32
  - Quick mode, 32
  - Responder, 32
- Ingress filtering, 78
- Integrity Key, 253
- Integrity protection, 27
- Inter-packet separation delay, 299
- Interface identifier, 8
- Interface management, 308
- Interface selection, 306
- Interface, 8
- Internet Key Exchange, 26
- Internet Security Association and Key Management Protocol, 32
- Inverse Neighbor Discovery, 15
- INVITE, 258
- IP Multimedia Subsystem (IMS), 256
- IP Reachability Service, 255
- IP-in-IP encapsulation, 56
- IP-within-IP encapsulation, 69
- IPsec SA, 33
- IPsec, 26, 266
- IPv4 Fast Handovers, 274
- IPv6 anycast address, 14
- IPv6 Mobility Header messages, 77
- IPv6 multicast address, 14
- IPv6 packet, 9
- IPv6-in-IPv4 encapsulation, 352
- IPv6-in-IPv6 encapsulation, 129
- IPv6CP, 250
  - Configure-Ack, 250
  - Configure-Request, 250
- K<sub>home</sub>*, 52, 104
- L2 triggers, 174, 235
  - Link Down, 174
  - Link Going Down, 174
  - Link Up, 174
- LBU, 237, 239
- LCoA, 236
- LCP
  - Configure-Ack, 249
  - Configure-Nak, 249
  - Configure-Reject, 249
  - Configure-Request, 248
- Link Control Protocol, 248
- Link switching, 168
- Link, 8
- Link layer address, 8
- Link-local address, 13
- Local Binding Update, 237
- Local Mobile Node, 156
- Location Privacy problem, 331
- Location privacy, 235
- Location Privacy
  - Disclosing the CoA, 346
  - privacy-tag with reverse tunneled binding updates, 337
  - privacy-tag with route-optimized binding updates, 341
  - problem illustration, 335
  - revealing Care of Address, 334
  - revealing home address, 334
- Location update, 308
- Locator, 50
- Loopback address, 14
- Loose source routing, 69
- MAP discovery, 237
- MAP packet forwarding, 240
- MAP registration, 239
- MAP, 236
- Message Authentication Code
  - AES, 66
  - MD5, 66
  - SHA-1, 66
  - SHA-256, 66
- Message Identifier Option, 253
- Middle-box management, 266
- Minimal encapsulation, 69
- MLD, 20

- Mobike, 267
- Mobile IP
  - IKE identities, 118
  - Mobike, 269
  - SPD entries, 119
- Mobile IPv6 Terminology, 52
- Mobile Network Node, 154
- Mobile Prefix Advertisement, 149
- Mobile Prefix Solicitation, 149
- Mobile Router, 154
- Mobility Anchor Point, 236
- Mobility Header LLA option, 215
- Mobility Header, 60, 78, 80
- Mobility Options, 93
- Mobility Security Association, 53
- Movement detection, 72, 168
- Movement Detection
  - active approach, 142
  - passive approach, 142
- MS - AAA Authentication Option, 252
- Multiaccess, 297
- Multicast address
  - global, 14
  - link-local, 14
  - node-local, 14
  - site-local, 14
- Multicast Listener Discovery, 20
- NAI Option, 253
- NAI, 224
- Neighbor Advertisement, 18
- Neighbor Cache, 18
  - Incomplete, 18
  - Reachable, 18
  - Stale, 19
- Neighbor Discovery protocol, 15
- Neighbor Discovery
  - Neighbor Unreachability Detection, 142
  - PROBE state, 143
  - STALE state, 143
- Neighbor Solicitation, 18
- Neighbor Unreachability Detection, 21, 54
- Neighborhood discovery, 170
- Neighborhood discovery, 307
- NEMO Basic protocol, 154
- NEMO Route Optimization, 158
- NEMO
  - Corresponding Router, 159
  - Explicit Mode, 157
  - Implicit Mode, 157
  - Prefix Delegation, 160
  - Prefix Information, 157
  - Prefix Table, 158
- Nested tunneling, 130
- Network access authorization, 307
- Network Access Identifier, 224, 246
- Network Control Protocol, 248
- Network Mobility (NEMO), 154
- Network mobility, 153
- Network-controlled mobility, 42
- Network-generated triggers, 175
- Next Header, 10
- Nonce Indices option, 95
- Nonce Indices, 91, 102
- Nonces, 91
- NUD, 21, 54, 142
- On-Link CoA, 236
- On-link, 9, 16
- Overlay, 43
- Packet Data Service, 246
- Packet Data Session, 246
- Packet Delivery
  - BU to home agent, 127
  - correspondent node to mobile node directly, 127
  - from home network to mobile node, 127
  - mobile node to correspondent node directly, 127
  - mobile node to correspondent node through the home agent, 127
- Packet loss, 165, 299
- Pad Options, 97
- Pad1, 97
- PadN, 98
- Password Authentication Protocol (PAP), 249
- Payload Length, 10
- PDSON, 245, 247
- Personal mobility, 256
- PPP, 30
- Plain Old Telephone Service, 265
- Populate From Packet, 30
- Portability, 2
- POIS, 265
- PPP protocol, 248
- PPP Session, 246
- PPP, 303
- Preauthentication, 292
- Predictive handover, 179
- Prefix Interval option, 73
- Prefix Length, 17
- Prefix list, 154
- Prefix Table, 155
- Prefix, 8
- Prefix, 17
- Privacy
  - profiling, 333
- Private key, 61
- Profile Types
  - QoS
    - Compression, 227
- Protocol messaging delay, 299
- Proxy Router Advertisement, 170
- Proxy-CSCF, 260
- PrRtAdv, 170, 199
- Public key cryptography, 61

- Public key, 61
- QoSPI, 173
- R-P Session, 246
- RCoA, 236
- Re-INVITE, 255
- Reactive handover, 180
- Real-time handovers, 266
- Real-time mobility management, 40
- Reauthentication, 309
- Reception latency, 168
- Redirect, 21
- Regaining IP connectivity, 308
- Regional Care-of Address, 236
- REGISTER, 257
- Registration Reply, 301
- Registration Request, 301
- Replay attacks, 83
- Resolving Access Points, 170
- Return Routability tests, 65
- Return Routability, 101
- Return Routability
  - address ownership, 112
- Return Routability
  - data hijacking, 111
  - Design Constraints, 103
  - distributed denial-of-service, 111
  - threat models, 111
- Returning home, 134
- Reverse ARQ, 15
- Roaming, 3
- Route optimization for IPv4, 352
- Route optimization with preconfigured key, 114
- Route-optimized communication, 52
- Router Advertisements, 15
- Router Solicitation for Proxy Advertisement, 170
- Router Solicitations, 15
- Routing Header type 2, 125
- Routing Header type 2, 130
- Routing Header, 11
- RTP, 300
- RtSolPt, 170, 194
- SA
  - Home Agent, 117
- SAD, 29
- SCTP, 39
- Secure mobility, 266
- Secure Socket Layer, 26
- Secure Traffic Processing, 117
- SecureID card, 266
- Security Association Database (SAD), 118
- Security Association Database, 29
- Security association, 27
- Security associations, 26
- Security Parameter Index, 27
- Security Policy Database (SPD), 118
- Security Policy Database, 29
- Selectors, 29
- Serving CSCF, 260
- Session Description Protocol (SDP), 258
- Session Initiation Protocol (SIP), 256
- Session Mobility, 44
- Signal strength, 301
- Signal to Noise Ratio, 282
- Simple IP, 246
- SIP Proxy, 257
- SIP Universal Resource Indicator (URI), 257
- Skype, 300
- Smooth handover, 167
- Soft handoff, 298
- Solicited-node multicast address, 14
- Source routing, 69
- SPD, 29
- SPI, 27, 30
- SSL, 26
- Stateless address autoconfiguration, 17
- Stateless Dynamic Host Configuration Protocol, 251
- Stream Control Transmission Protocol, 39
- Strict source routing, 69
- Subnet movement detection, 54
- Switching flows, 308
- Symmetric key, 61
- Symmetric Keys, 62
- TCP Slow Start, 177
- Test Init, 103
- TLS, 26
- Traffic Class, 9
- Triangular routing, 114
- Transport Layer Security, 26
- Transport mode SA, 27
- Triangular routing, 68
- Tunnel mode SA, 27
- Tunnel, 9
- Tunnel, 54
- Tunneling, 43, 129
- Type 2 routing header, 11
- Unicast address, 13
- Uniform Resource Identifiers, 38
- Unique Local address, 13
- Unspecified address, 14, 143
- URI, 38
- Uri-parameters, 257
- User-generated triggers, 175
- Userinfo, 257
- Version, 9
- Via, 258
- Virtual network, 54
- Virtual Private Network, 33
- Visited AAA, 246
- Visited network, 53
- Visiting Mobile Node, 156
- VoIP, 167

- VPN Mobility
  - firewall state management, 272
- VPN, 33
- WLAN
  - 4-way authentication, 284
  - 802.1X, 281
  - association request response, 280
  - association, 280
  - DCF Inter-Frame Space(DIFS), 283
  - Handover delay analysis, 291
  - Key generation, 284
  - Master Key, 284
  - MaxChannelTime, 282
  - MinChannelTime, 282
  - Pairwise Master Key, 281
  - Pairwise Transient Key, 281
  - Pre-authentication, 281
  - probe request response, 280
  - PrtRtAdv, 287
  - RSSI, 287
  - RtSolPr, 287
  - scan, 280, 282
  - Short Inter-Frame Space(SIFS), 283
  - SSID, 280

