

Index

Page numbers followed by ‘*f*’ indicate figures and ‘*t*’ indicate tables.

- Abstract Windowing Toolkit (AWT), 94
- Acceleration sensor, 41
- Access/mobility provider, 65
- Access Point (AP), 229, 325
- Actors, 315
- Ad hoc and sensor networks, 433
 - ad hoc networking, 434*f*
 - address self-configuration, 440
 - cooperation and fairness
 - detection-based approaches, 434
 - effect of cooperation approaches, 436
 - motivation-based approaches, 435
 - topology control (TC), 436
 - current approaches to, 439
 - ideal features, 438
 - optimization of energy efficiency, 436
 - optimization of network capacity, 437
- Adaptation provider, 65
- Adaptive beamforming, 157*f*
- Adaptive Radio Multi-Homing (ARMH), 405
 - JRRM deploying, resource allocation
 - balancing system load, 408
- Address self-configuration, 440
- Advanced Research and Development on Embedded Intelligent Systems (ARTEMIS), 3, 7
- Air-interfaces, 131–215
 - broadband frequency domain-based, 132–150
 - duplexing, 171–177
 - frequency domain-based systems, 133–134
 - parallel modulation methods, 133–134
 - serial modulation methods, 134
 - handoff, 184
 - partial, 184
 - inter-cell coordination, 184–187
 - interference, 184–187
 - OFDM/OffsetQAM, 142–143
 - operating principles of, 230–231
 - orthogonal frequency division multiplexing (OFDM)
 - resource allocation, 177–183
 - scheduling, 177–183
 - considerations in, 183
- Ambience monitor, 87
- Ambience Sensor, 87
- AmbienceInfoAggregator, 88
- AmbiencePredictor, 89
- AmbienceStorage, 88
- Ambient communication networks
 - security for, 129
- Ambient Intelligence (AmI), 111
- Ambient Networks, 21
- AmI. *See* Ambient Intelligence (AmI)

- Analogue to Digital Conversion (ADC), 412
- Antenna arrays, 195–198
 angle of arrival (AoA), 195
 angle of departure (AoD), 195
- Antenna correlation
 reconfigurability to, 160^f
- Application layer configuration controller (CCM_AP)
 changes in applications requirements, 346
- Application Programming Interfaces (APIs), 368
- Application scenarios, 314–325
 actors, 315–317
 in end-to-end reconfigurable systems, 321^f
 business models, 315
 E2R requirements and constraints reconfigurations, 314
 end-to-end reconfigurable system, 319–322
 operational, administrative dimension, 320
 Responsibility Chain Concept, 322–323
 roadmap business models, 319
 end-to-end scenarios, 315
 methodology for, 314–315
 for reconfigurability, 314–325
 reconfigurability applications
 Cognitive Radio Approach, 323
 deployment roadmaps for, 322^f
 reconfigurability roadmaps, 323–325
 dynamic radio mode, standard switching, 323
 System prototyping, 325
 use-case scenarios, 323
 reconfigurable systems and roadmaps, 325
 scenarios analysis process, 315^f
 key reconfigurability elements, 315
 scenarios evaluation, 317–318
 service level agreement, 316
 system requirements, 318
 Analysis, Test points, 318
 levels of priority, 319
 technology roadmaps and business paths, 314
- Application-Specific Integrated Circuit (ASIC), 235, 326
- Appropriate Functional Entity (AFE), 350
- Artificial Intelligence (AI), 100
- Association of Radio Industries and Businesses (ARIB), 25
- Audio and video players, 45
- Authentication, Authorization, and Accounting (AAA), 436
- Automatic Prefix Delegation Protocol, 426
- Automatic ReConfiguration Protocol (ARCP), 427
- Automatic Repeat Request (ARQ), 407
- Avalanche photodiode (APDs), 282
- B3G/4G Activities, 4–10
 European framework programme for research, 6–7
 international initiatives, 5–6
 regional initiatives, 6–9
 standardization initiatives, 9–10
- Backward compatibility, 70
- Band switching duplexing, 175, 175^f
- Bandwidth Management Module (BMM), 376
- Base station (BS), 229, 325, 348
 self-organization of, 187
- Base Transceiver Station (BTS), 381
- Basic research framework
 composite reconfigurable networks, 314
- BD. *See* Block diagonalization (BD)
- Bell labs Layered Space-Time (BLAST), 155
- BER. *See* Bit-error rate (BER)
- Beyond the third Generation (B3G), 313
 cooperative networks and reconfigurability concepts, 313
 wireless-access infrastructure, 388
- BICM. *See* Bit-interleaved coded modulation (BICM)

- Binary Phase-Shift Keying (BPSK), 143
- Bit-error rate (BER), 132, 230
- Bit-interleaved coded modulation (BICM), 138
- BLAST. *See* Bell labs Layered Space-Time (BLAST)
- Block diagonalization (BD), 161
- Bluetooth (BT), 34
- BPSK. *See* Binary Phase-Shift Keying (BPSK)
- Broadband, 11
- Broadband MIMO systems, 234*f*
- Broadband Radio Access Networks (BRANs), 313
- Broker
 - concept of, 85*f*
 - service aggregation by, 86*f*
- Brokering, 85–86
- Built-in display, 42
- Built-in keypad, 40
- Busy Hours (BH), 381
- Buzzer, 43

- Cache Negotiation (CN), 375
- Camera, 42
- Carrier Sense, Multiple-Access (CSMA)/(CA), 268
- Carrier wave (CW) signals, 194
- CCI. *See* Cross-Channel Interference (CCI)
- CDC. *See* Connected Device Configuration (CDC)
- CDMA. *See* Code Division Multiple-Access (CDMA)
- CDMA Development Group (CDG), 3
- Central Processing Unit (CPU), 115
- Channel impulse response (CIR), 133
- Channel modeling, 190*f*, 206–213
 - data postprocessing, 210–211
 - generic model, 207
 - indoor MIMO, 204
 - indoor UWB MIMO, 205
 - measurement parameters of, 209*t*
 - measurements of, 207–210
 - performance evaluation, 211–213
 - system requirements, 206–207
- Channel models
 - classification of, 189
 - standardized, 192
- Channel state information (CSI), 133, 228
 - minimizing dependency, 246–247
- China Communications Standards Association (CCSA), 8
- Choreography, 85
- CIR. *See* Channel impulse response (CIR)
- CMM_NS
 - constructor supporting equipment, 343
- Code Division Multiple-Access (CDMA), 9, 132, 243, 366
- Code-Division Test Bed (CODIT), 192
- CODIT. *See* Code-Division Test Bed (CODIT)
- COM+, 97
- Common Object Request Broker Architecture (CORBA), 83
- Common Open Policy Service (COPS), 441
- Common phase error (CPE), 239
- Common Signaling Mode (CSM), 267
- Communications Business Model
 - Software provider, 317
 - Over-the-Air (OTA), 318
- Communications channel, 287*f*
- Complementary Metal-Oxide Semiconductor (CMOS), 300
- Complementary sequence inversion keying (CSIK), 283
- Component orchestration, 85
- Compound events, 83
- Computer & Information Science & Engineering (CISE), 8
- Computer and Network Systems (CNS), 8
- Computer security, 112
- Computing and Communication Foundations (CCF), 8
- Configurable Execution Modules (CEM), 358
- Configuration Control Module (CCM), 326, 330

- Configuration Control Module (CCM),
 - (*continued*)
 - equipment management architecture, 327
 - Reconfigurable Protocol Stack Framework (RPS_FW), 327
- Execution Environment, 326
 - Application-Specific Integrated Circuit (ASIC), 326
- Reconfigurable Protocol Stack (RPS), 326, 327
- reconfiguration functions, 330
- Configuration Execution Modules (CEM), 331, 358
 - configuration functionality, 331
 - operational software entity, 331
 - Operational Software Module, 331
 - Security architecture, 332*f*
- Configuration Management Module (CMM), 325, 328
 - CMM_MD
 - functional entity, 341
 - composition of layer, from generic and specific functions, 352, 352*f*
- Configuration downloads, 329
- Exemplary composition of, layer (N), 354*f*
- Monitoring and Discovery' procedure
 - identification of, alternate RAT, 341
- multimode protocol architecture, 351*f*
- negotiation functionality, 329
- network-initiated reconfiguration, 328
- Network-initiated trigger, downloading reconfiguration procedure, 345*f*
- protocol layer, conforming to reference model, 352*f*
- reconfiguration management modules, 339
- Reconfiguration Module Controller,
 - relationship of, 348
- reconfiguration procedure
 - core of, 338
- relationships of, CMM modules and different CCMs, 345*f*
- Secure diagnostic, 342*f*
- Security Manager, 333
 - Access Manager Entity, 333
 - standard negotiation protocols, 329
 - terminal reconfiguration management, 336
 - Terminal-initiated SW download, 344*f*
- Connected Device Configuration (CDC), 93
- Connected Limited Device Configuration (CLDC), 93
- Content handling, 74
- Content provider, 64, 65
- Content routing, 75
- Context aware menus, 56
- Context awareness function, 77
- Context data management, 69
- Context gathering, 74
- Context interpretation, 74
- Context management framework, 76
- Context Perspective Framework, 27
- Context reasoning, 74
- ContextServiceAdapter, 89
- Cooperation in Scientific and Technical Research (COST), 192
- Cooperative networks concept, 313
 - advanced management functionality, 313, 388
 - BRAN/WLAN and DVB systems, 313
 - cellular (2.5G/3G mobile networks), 313
 - reconfigurability concept, 388
 - time zones and spatial regions, 313
- CORBA. *See* Common Object Request Broker Architecture (CORBA)
- CORBA Event Service, 96
- COST. *See* Cooperation in Scientific and Technical Research (COST)
- Coverage investigation
 - SIMO and MIMO channel measurements for, 199–203
- CP. *See* Cyclic Prefix (CP)
- CPU. *See* Central Processing Unit
- Cross layer optimisation technology
 - optimum end-to-end communication rates, 409

- Cross-Channel Interference (CCI), 178
CSI. *See* Channel state information (CSI)
CW signals. *See* Carrier wave signals
Cyclic prefix (CP), 133, 237
- DAML. *See* Darpa Agent Markup Language (DAML)
Darpa Agent Markup Language (DAML), 98
Data dissemination, 301
Data filtering, 92
Data link layer (DLL), 245, 350
Data postprocessing, 210–211
Data protection, 71
Decision-feedback equalization (DFE), 139
DECT. *See* Digital Enhanced Cordless Telecommunication (DECT)
Defense Advanced Research Projects Agency (DARPA), 3, 6, 272, 393
DARPA XG Program, unused spectrum on ‘instant-by-instant’ basis, 394
data communications protocols, 393
spectrum access technology, 393
Denial of Service (DoS), 126
Dense Multipath Component (DMC), 163
Deployment, 131–215
Device Form Factor
 evolution of, 46
 display, 47
 keypad, 46
DFE. *See* Decision-feedback equalization (DFE)
DFT. *See* Discrete Fourier transform (DFT)
Digital Audio Broadcast (DAB), 324
Digital content
 proliferation of, 12
Digital Enhanced Cordless Telecommunication (DECT), 199
Digital industry
 convergence of, 12
Digital Rights Management (DRM), 52, 61, 127
Digital Signal Processor (DSP), 169, 247, 331
Digital Video Broadcasting (DVB), 313
Direct Sequence Code Division Multiple-Access (DS-CDMA), 132
Direct-Sequence Spread-Spectrum (DSSS), 283
Direct-Sequence Ultra-Wideband (DS-UWB), 251
Direction pad, 41
Directive on Privacy and Electronic Communications (2002/58/EC), 71
Directorate General (DG), 22
Directory agents (DAs), 427
Discovery Provider, 87
Discrete Fourier transform (DFT), 133
Display, 47
DMC. *See* Dense Multipath Component (DMC)
Domain Name Server (DNS), 426
Doppler shifts, 149
Doppler spreads, 174
DoS. *See* Denial of Service (DoS)
Downlink (DL), 228
Downlink packet access
 Jointly Opportunistic Beamforming and Scheduling (JOBS), 182
DRM. *See* Digital Rights Management (DRM)
DS-CDMA. *See* Direct Sequence Code Division Multiple-Access (DS-CDMA)
DSP. *See* Digital signal processing (DSP)
Dual-polarized antenna, 197*f*
Duplexing, 171–177
 band switching, 175
 guards, 173–174
 link asymmetry, 171–172
 link budget, 173
 link continuity, 174
 link reciprocity, 172–173
 paired vs. unpaired spectrum, 171
 synchronicity, 173–174
 system synchronization, 172
 terminal complexity issues of, 174–175
Duplicate address detection (DAD), 425

- Dynamic frequency selection (DFS), 402
- Dynamic Host Configuration Protocol (DHCP), 424
- Dynamic Network Planning and Management (DNPM), 369
- Dynamic Source Routing (DSR), 435
- Dynamic spectrum allocation (DSA), 396
- Dynamic spectrum sharing (DSS), 396

- e-commerce, 12
- E2R, 21
- E2R scenarios, 24
- EADF. *See* Effective Aperture Description Function (EADF)
- Effective Aperture Description Function (EADF), 198
- Emotion
 - interpretation of, 50
- Encryption and Decryption Factory (EDF), 333
- End-users, 64, 69
- Environment monitoring, 90
- ETSI. *See* European Telecommunications Standards Institute (ETSI)
- European Communication Committee (ECC), 397
- European Conference of Postal and Telecommunications (CEPT), 250, 397
- European R&TTE Directive
 - Declaration of Conformity, 392
- European Telecommunications Standards Institute (ETSI), 3, 25, 144, 250
- Execution environment architecture, 336*f*
 - managing and control of processes, 334
- Execution environment hardware module (ExHW)
 - Control Bus, for exchanging control signals, 335
- ExESW
 - protocol software module interaction, 335
- eXtensible Markup Language (XML), 76, 119

- External display, 42
- External keyboard, 40
- External mouse, 41

- Fast Fourier transform (FFT), 133, 237
- FDD. *See* Frequency Division Duplex (FDD)
- FDOSS. *See* Frequency-domain orthogonal signature sequences (FDOSS)
- FEC. *See* Frequency Estimation for Channel (FEC)
- Federal Aviation Administration (FAA), 272
- Federal Communication Commission (FCC), 251, 393
 - concepts on, cognitive radio and interference temperature, 393
- FER. *See* Frame Error Rate (FER)
- FFT. *See* Fast Fourier transform (FFT)
- Field of View (FOV), 281
- Field Programmable Gate Arrays (FPGAs), 235, 331, 335
- Finite impulse response (FIR), 238
- Flexible Spectrum Allocation (FSA), 389
 - goal of, Spectrum Brokerage (SB), 396
 - Spectrum Pooling (SP), 396
- Flexible Spectrum Management and JRRM, 389
- FLOWS project, 26, 29
- FLOWS Scenarios, 31*f*
- Foundation Profile (FP), 93
- FP. *See* Foundation Profile (FP)
- Frame Error Rate (FER), 160
- Free-space optics (FSO), 278
- Frequency Division Duplex (FDD), 156, 390
 - guard bands in, 173*f*
 - multimode terminal, 390
- Frequency Estimation for Channel (FEC), 166
- Frequency offsets
 - effects of, 143
- Frequency reuse factor (FRF), 178
- Frequency-domain equalization (FDE), 265

- Frequency-domain orthogonal signature sequences (FDOSS), 132
- Frequency-Hopping Spread-Spectrum (FHSS), 250
- FRF. *See* Frequency reuse factor (FRF)
- Future Technology for Universal Radio Environment (FuTURE), 7
- General Packet Radio Service (GPRS), 9, 68, 115, 313
- General-Purpose Processors (GPP), 331, 335
- Generalized frequency domain (GFD), 132
- Generalized multicarrier (GMC), 132
- Generalized multicarrier receiver, 138*f*
- Generalized multicarrier signals, 134–138
- Generic Link Layer (GLL), 350
- Generic service element (GSE), 78–108
 - for adaptation, 90–92
 - for ambient awareness, 87–89, 91*f*
 - basic/low level, 85–86
 - building abstract services, 79–82
 - developing new services, 82
 - distributed, 81*f*
 - enabling middleware technologies for, 92–97
 - enabling technologies of, 78–108
 - environment monitoring, 90
 - interfaces, 80*f*
 - ontology
 - merging of, 103–104, 105*f*
 - ontology construction, 98
 - ontology integration, 100–103
 - for personalization, 86–87
 - for profiling, 86–87
 - reasoning, 105–107
 - rule-based systems, 105–107
 - semantic support, 97–107
 - ontologies, 97–104
 - user-centric, 86–92
- Gesture input, 50
- Gesture recognition, 56
- GFD. *See* Generalized frequency domain (GFD)
- Given Paired Spectrum (GPS), 172
- Global Pilot Channel Infrastructure, 317
- Global positioning system (GPS), 54, 74, 252, 439
- Global roaming
 - pilot channel provision, 317
- Global System for Mobile Communications (GSM), 9, 26, 113, 313, 388
- GMC. *See* Generalized multicarrier (GMC)
- GMC CDMA, 135
- GMITS. *See* Guidelines for the Management of Information Technology Security (GMITS)
- GPRS. *See* General Packet Radio Service (GPRS)
- GPS. *See* Given Paired Spectrum (GPS)
- Graphic menu, 44
- Graphical User Interface (GUI), 49, 94
- Ground Penetration Radar (GPR), 255
- GSE. *See* Generic service element (GSE)
- GSM. *See* Global System for Mobile Communications (GSM)
- GUI. *See* Graphical user interface (GUI)
- Guidelines for the Management of Information Technology Security (GMITS), 125
- HandOver (HO), 336
- Handwriting recognition, 43
- Haptic interfaces, 50
- Hardware Abstraction Layers (HAL), 336
- Harmonisation
 - vs technology neutrality, 398*f*
- HARQ. *See* Hybrid Automatic-Repeat-Request (HARQ)
- HDD. *See* Hybrid Division Duplexing (HDD)
- Headphones, 42
- Heating, ventilation, air-conditioning (HVAC), 298
- Hierarchical Radio Resource Management (HRRM), 389
- High data rates (HDRs), 228

- High power amplifier (HPA), 239
- High-Speed Downlink Packet Access (HSDPA), 166, 244, 363
- Highspeed Uplink Packet Access (HSUPA), 244
- Home networking
requirements for, 259*t*
- Home Reconfiguration Manager (HRM), 376
- Host auto-configuration, 424
stateful, 425
stateless, 425
- HSDPA. *See* High-Speed Downlink Packet Access (HSDPA)
- Hybrid Automatic-Repeat-Request (HARQ), 166
- Hybrid Division Duplexing (HDD), 175–177
cell structure of, 176, 176*f*
frequency plan of, 176, 176*f*
interferences in, 180*f*
scheduling algorithm for reduction, 180–181
- HyperText Transfer/Transport Protocol (HTTP), 76, 119, 429
- IAM. *See* Identity and access management (IAM)
- Iceberg model, 18*f*
- I-centric applications, 78
- ICT. *See* Information and Communication Technology (ICT)
- Identity and access management (IAM), 117
- Identity management (IdM), 111, 118*f*, 116–121
benefits of, 119
examples of, 119–120
facets of, 117*f*
principles of, 120–121
requirements for, 120–121
research issues, 121
- Identity provider (IdP), 65, 117
- IDFT. *See* Inverse Discrete Fourier Transform (IDFT)
- IdM. *See* Identity management (IdM)
- IdP. *See* Identity provider (IdP)
- IDS. *See* Intrusion Detection System (IDS)
- IEEE. *See* Institute of Electrical and Electronics Engineers (IEEE)
- IEEE 802.11n, 193
- IEEE 802.XX, 12
- IETF. *See* Internet Engineering Task Force (IETF)
- IFDMA. *See* Interleaved frequency division multiple-access (IFDMA)
- IlmProp channel, 163*f*, 164
- Impulse Radio (IR), 250
- IMS. *See* IP multimedia subsystem (IMS)
- In-phase and quadrature (IQ), 239
- Independent and identically distributed (i.i.d.), 231
- Information and Communication Technologies (ICT), 22, 121
- Information and Intelligent Systems (IIS), 8
- Information Society Technologies (IST), 6, 21, 324
- InfraRed (IR), 34
- Infrared Data Association (IRDA), 277
- Institute of Electrical and Electronics Engineers (IEEE), 1, 5, 178, 239
- Instruction Set Architectures (ISAs), 332
- Intelligent Text Prediction (ITAP), 43
- Inter-symbol interference (ISI), 133, 236
- Interface definition language (IDL), 96
- Interleaved frequency division multiple-access (IFDMA), 137
- Intermediate frequency (IF), 241
- International Mobile Telecommunications (IMT), 5, 397
- International Standards Organisation (ISO), 291, 350
- International Telecommunication Union (ITU), 3, 122, 188, 252, 404
recommendations for spectrum management, 404
- International Telecommunication Union-Radio Sector (ITU-R), 5, 192, 275

- Internet, 11
- Internet Engineering Task Force (IETF), 3, 9, 92, 125, 405, 427
- Internet Protocol (IP), 59, 115, 131, 230, 330
 - multicast, 84
- Internet Protocol Version six (IPv6), 424
 - auto-configuration, 424
 - stateful, 425*f*
 - stateless, 425*f*
 - Router Renumbering, 426
- Internet services, 61
- Intra-/Inter-domain handover
 - security for, 128
- Intra-/Inter-technology
 - security for, 128
- Intrusion Detection System (IDS), 125
- Inverse Discrete Fourier Transform (IDFT), 145
- Inverse fast Fourier transform (IFFT), 231
- IP multimedia subsystem (IMS), 129
- IP. *See* Internet protocol (IP)
- IPv6. *See* Internet Protocol Version six (IPv6)
- ISI. *See* Inter-symbol interference (ISI)
- Isotropic Orthogonal Transform Algorithm (IOTA), 143, 238
- IST Advisory Group (ISTAG) scenarios, 22
- ISTAG Visions for 2010, 78
- IT Technology Development
 - in Korea, 22
- IT Vision Project, 23
- IT839, 22, 23
- ITU. *See* International Telecommunication Union (ITU)
- ITU-R. *See* International Telecommunication Union-Radio Sector (ITU-R)
- J2EE. *See* Java Enterprise Edition (J2EE)
- J2ME optional packages, 93*t*
- J2ME technologies, 93
- Java
 - Delegation Event Model, 94
 - Distributed Event Model, 94–95
 - Java Enterprise Edition (J2EE), 95
 - Java Message Service (JMS), 94–96
 - Java Naming and Directory Interface (JNDI), 96
 - Java Specification Requests (JSRs), 93
 - JMS. *See* Java Message Service (JMS)
 - JNDI. *See* Java Naming and Directory Interface (JNDI)
 - JOBS. *See* Jointly Opportunistic Beamforming and Scheduling (JOBS)
 - Joint Radio Resource Management (JRRM)
 - HRRM, solution of, 391
 - JRRM concepts and algorithms, 404
 - network controlling mechanisms, 391
 - overview of, 391–392
 - performance of, multi-RAT network, 404
 - use cases of, 405*f*
 - Joint Session Admission Control (JOSAC)
 - RAT system load, 406
 - Jointly Opportunistic Beamforming and Scheduling (JOBS), 182
 - Joystick, 40
 - JSRs. *See* Java Specification Requests (JSRs)
 - Keypad, 46
 - Keyword speech recognition, 44
 - Knowledge plane, 443, 444*f*
 - Korea
 - future mobile scenarios from, 22
 - LA. *See* Liberty Alliance (LA)
 - Laboratory for Computer Science (LCS), 25
 - Lan/MAN Standards Committee (LMSC), 5
 - LBS. *See* Location-Based Services (LBS)
 - Liberty Alliance (LA), 119
 - License provider, 66

- Light emitting diodes (LEDs), 43, 279
- Light emitting diodes (LEDs) indicators, 43
- Light Emitting Diodes Digital Light Processing (LED DLP), 47
- Line-of-sight (LOS), 231
- Linear Time-Invariant (LTI), 264
- Link asymmetry, 171–172
- Link budget, 173
- Link continuity, 174
- Link reciprocity, 172–173
- Link State Advertisement (LSA), 426
- LMSC. *See* Lan/MAN Standards Committee (LMSC)
- Local area networks (LAN), 227
- Location Update Module (LUM), 376
- Location-Based Services (LBS), 122
- Loudspeaker, 42
- Low data rate (LDR), 255
- Low-Energy Adaptive Clustering Hierarchy (LEACH), 300
- Low-noise amplifiers (LNAs), 242
- Lower sideband (LSB), 240
- M-ary Bi-Orthogonal Keying (MBOK), 252, 283
- m-commerce, 12
- MAC. *See* Medium access control (MAC)
- Malicious code, 121–126
 - attack paths in convergent networks, 124*f*
 - background of, 122–123
 - research issues, 123–126
 - security goals, 123
 - security requirements for, 123–126
 - security standards, 125
- Management and control system
 - element management, 325–365
 - E2R system, 326*f*
 - flexible air interfaces and SDR, 325
 - flexible Air Interfaces and SDR, 325
 - hardware abstraction, 325
- Mass customization, 70
- Maximum-likelihood detection (MLD), 235
- MC-CDMA. *See* Multiple carrier CDMA (MC-CDMA)
- MCSSS. *See* Multicarrier spread spectrum signal (MCSSS)
- Medium Access Control (MAC), 131, 254
- MEMS. *See* Micro Electrical Mechanical Systems (MEMS)
- METRA. *See* MultiElement Transmit and Receive Antenna (METRA)
- Metropolitan Area Network (MAN), 5
- Micro Electrical Mechanical Systems (MEMS), 41, 50, 169
- Microsoft Message Queue Server (MSMQ), 94
- Middleware, 78, 92, 115
 - event-based, 94–97
- MIMO. *See* Multiple-input multiple-output (MIMO)
- Minimum Mean Squared Error (MMSE), 141, 235
- Ministry of Information and Communication (MIC), 22
- MIT Project Oxygen Scenarios, 25
- MMSE. *See* Minimum Mean Squared Error (MMSE)
- MNOs. *See* Mobile network operators (MNOs)
- Mobile Broadband for Emergency and Safety Applications (MESA), 25
- Mobile communication
 - deregulation and globalization of, 12
 - in 2005, 11
- Mobile communication system
 - IP networks, 388
 - Terminal, User, Service and Network, 390
- Mobile devices
 - improvement of, 55
 - increasing diversity of usage scenarios, 34
 - increasing diversity of user groups, 34
 - increasing number of features and functions, 33
 - problem with, 33
 - short term research issues, 55

- shrinking form factor, 34
- trusted computing platforms in, 128
- Mobile Execution Environment (ME_xE), 323
- Mobile IT Forum (mITF), 3, 8
- Mobile IT Forum (mITF) scenarios, 25
- Mobile network operator (MNO), 62, 64, 122
- Mobile networks, 60
- Mobile radio, 151
- Mobile radio networks
 - in future, providing higher QoS, 389
- Mobile station (MS), 158
- Mobile terminals (MTs), 229, 324
 - peak transmitter power requirement of, 146
- Mobiles
 - line-of-sight (LOS), 162
- MobiLife project, 21
- Mobility Management (MM), 322
- Modality fission, 74
- Modality fusion, 74
- Mode Identification and Monitoring
 - Module (MIMM), 374
- Mode Negotiation and Switching Module (MNMS), 375
- Modeling Service
 - purpose of, 90
- MOM. *See* Message-Oriented Middleware (MOM)
- Monopole elements
 - wideband spherical array of, 202 f
- MS. *See* Mobile station (MS)
- MSMQ. *See* Microsoft Message Queue Server (MSMQ)
- MU MIMO. *See* Multiuser multiple-input multiple-output (MU MIMO)
- MUI. *See* Multiuser interference (MUI)
- Multi-antenna multiuser communication
 - dirty-paper coding, 178
 - near capacity, 178–179
- Multiband line spectrum, 147 f
- Multicarrier (MC), 236
- Multicarrier CDMA, 139–141
- Multicarrier spread spectrum signal (MCSSS), 195
- Multicarrier transmitter, 135 f
- Multicast DNS-Service Discovery (mDNS-SD), 428
- Multichannel modeling
 - methods for, 190–192
- Multidimensional radio channel
 - issues in, 213–215
 - measurement of, 188–215
 - modeling of, 188–215
 - state of art, 190–206
 - switched, 196 f
- MultiElement Transmit and Receive Antenna (METRA), 191
- Multimedia Message Service (MMS), 34
- Multimedia services, 131
- Multimodality, 72
- Multiple-Access Interference (MAI), 391
 - multi-path phenomenon, 391
- Multiple carrier CDMA (MC-CDMA), 132
- Multiple-input multiple-output (MIMO), 135, 228, 363
 - multiple-access for, 244, 245
 - queuing theoretic analysis, 245–246
 - transceiver, 154–156
 - channel knowledge, 156
 - deployment environment, 156
 - reconfigurability with linear precoding, 157–161
 - reconfigurable, 156–161
 - TX antenna, 158
 - transceivers, 155 f
- Multiple-input multiple-output (MIMO) systems, 150–170
- Multitap, 43
- Multiuser GMC signals, 140 f
- Multiuser interference (MUI), 151
- Multiuser MIMO downlink precoding, 161–164
- Multiuser multiple-input multiple-output (MU MIMO), 170
- Narrowband (NB), 188
- National Science Foundation (NSF), 8, 394

- National Science Foundation (NSF),
(*continued*)
creation of, innovative wireless
networking systems, 395
Programmable Wireless Networking'
(NeTS-ProWiN), 394
- Natural interaction, 48
- NB. *See* Narrowband (NB)
- Near Field Communication (NFC), 52,
61, 303
- .NET, 97
- Network Architecture and Support
Services, 365–387
reconfigurability technologies, 365
- Network Capability Negotiation (NCN),
375
- Network Operators (NOs), 317
brand erosion, revenue loss, 317
Service Provider Network Operator,
317
- Network Planning
Capital of Expenditure (CAPEX), 410
and Operational Expenditure (OPEX),
410
for Reconfigurable Networks, 410
reduce cost of, network deployment,
411
- Network Provider (NP), 313
hot-spot situations, traffic demand
alterations, 313
RAT, 313
- Network provider (NP), 64
- Network technologies, 424
- Networks
trust development in, 128
trust management in, 128
- New services, provisioning of, 67
- Next-Generation Mobile Communications
(NGMC), 3, 8, 23
- NFC. *See* Near Field Communication
(NFC)
- (N)-Layer Modes Convergence Manager
(N)-MCM, 350
- Non-line-of-sight (NLOS), 231
- Notice of Inquiry (NOI), 272, 402
- NTT DoCoMo 'Vision 2010' Scenarios,
24
- Object management group (OMG), 89
- Object request broker (ORB), 93
- Object-Oriented Middleware (OOM),
92–93
- OFDM. *See* Orthogonal frequency
division multiplexing (OFDM)
- OFDM/IOTA, 134
- OFDM-FDMA. *See* Orthogonal
Frequency Division
Multiplexing-FDMA
(OFDM-FDMA)
- OFDMA. *See* Orthogonal Frequency
Division Multiple-Access (OFDMA)
- Offset quadrature amplitude modulation
(OQAM), 134, 238
- OIL. *See* Ontology Interference Layer
(OIL)
- OMA. *See* Open Mobile Alliance
(OMA)
- OMG. *See* Object management group
(OMG)
- On-off keying (OOK), 283
- Ongoing research projects
channel modeling in, 193
- Ontology construction, 98
- Ontology integration, 100–103
fragments for, 101*f*
- Ontology Interference Layer (OIL), 98
M.D
See Object-Oriented Middleware
(OOM)
- Open distributed computing
trust management in, 112
- Open Mobile Alliance (OMA), 9, 120
- Open service API
vs. internal interfaces, 80*f*
shell, 81
- Open Shortest Path First (OSPF), 426
- Open System Interaction
protocols
optimising communication, 390
- Open Systems Interconnection (OSI), 5,
166, 269, 327

- Open-content Web Sites, 432
 - Wiki, 432
 - Wikipedia, 433
- Operating system (OS), 63, 320
- Operation Expenses (OPEX), 68
- Operational management function, 77
- Operational Software Module (OSM), 331
- OPEX. *See* Operation Expenses (OPEX)
- Optical channel, 282–283
- Optical communication, 286*f*
- Optical filtering, 281
- Optical systems, 281
- Optical wireless (OW), 277
 - application areas for, 288–295
 - high-capacity LANs, 293–295
 - hot-spots, 291–293
 - narrow FOV, 288–291
 - point and shoot, 288–291
 - telematic, 291
 - outlook for, 295
 - longer term, 295
 - medium term, 295
 - short term, 295
 - research directions for, 296
- OQAM. *See* Offset quadrature amplitude modulation (OQAM)
- Organic Light Emitting Diode (OLED), 42
- Orthogonal Frequency Division
 - Multiple-Access (OFDMA), 132, 243
 - region division-based fractional loading method for, 178
- Orthogonal frequency division
 - multiplexing (OFDM), 132, 228, 363
 - base stations
 - load balancing, 186
 - minimizing over-the-air messaging in, 177
- Orthogonal Frequency Division Multiplexing-FDMA (OFDM-FDMA), 137
- OS. *See* Operating system (OS)
- OSI. *See* Open Systems Interconnection (OSI)
- Out-of-cell interference, 185–186
- Over-the-Air (OTA), 318
- OWL. *See* Web Ontology Language (OWL)
- OWL-S, 99–100
 - concepts of, 99*f*
 - grounding, 100
 - processModel, 100
 - serviceProfile, 100
- P2P systems, 73
- Packet error rate (PER), 131
- Pairwise Error Probability (PEP), 159
- PAN. *See* Personal area network (PAN)
- PAN/BAN. *See* Personal and body area network (PAN/BAN)
- Parallel Interface Cancellation (PIC), 156
- Parallel-modulated systems
 - bit-error-rate performance of, 138–139
- Partial handoff, 184, 185*f*
- PAS. *See* Power-Azimuth Profiles (PAS)
- PBP. *See* Personal Basis Profile (PBP)
- PDA. *See* Personal Digital Assistant (PDA)
- PDF. *See* Probability density function (PDF)
- PDP. *See* Power-Delay Profiles (PDP)
- Peak-to-average power ratio (PAPRs), 239
- Peer-to-peer networking (P2P), 429, 429*f*
 - structured P2P networks, 431
 - unstructured P2P networks, 429
 - centralized P2P networks, 430
 - hybrid unstructured P2P networks, 431
 - pure unstructured P2P networks, 430
- PEP. *See* Pairwise Error Probability (PEP)
- PER. *See* Packet error rate (PER)
- Periodic multi-sine signal, 195
- Personal and body area network (PAN/BAN), 205

- Personal area network (PAN), 68, 193
 Personal Basis Profile (PBP), 93
 Personal Digital Assistant (PDA), 29, 113, 257
 Personal Handyphone System (PHS), 241
 Personal identification number (PIN), 119, 282
 Personal Information Management (PIM), 34
 Personal profile (PP), 75
 Personalization, 61, 69
 Personalization function, 77
 Pervasive Ultra-Wideband Low Spectrum Energy Radio Systems (PULSERS), 193, 250
 Phase noise
 effects of, 143
 Physical Layer (PHY), 324
 PIC. *See* Parallel Interface Cancellation (PIC)
 PIN. *See* Personal Identification Number (PIN)
 Polarization, 204
 Policy decision point (PDP), 441
 Policy enforcement point (PEP), 441
 Policy-based cognitive radio, 412*f*
 Portal provider, 65
 POTS. *See* Plain old telephone services (POTS)
 Power amplifier
 efficiency of, 143–146
 Power delay profile (PDP), 192, 236
 Power-Azimuth Profiles (PAS), 192
 PP. *See* Personal profile (PP)
 Pragmatic trellis-coded modulation, 138
 bit-error-rate performance for, 139*f*
 PRBS. *See* Pseudorandom binary signals (PRBS)
 Pre-determined, 16
 Pre-matrix time-frequency selector, 136*f*
 Precoding, 161
 linear, 161
 nonlinear, 161
 scheduling, 162
 simulation, 162
 results of, 163–164
 Predictive text input, 43
 Presentation adaptation, 74
 Privacy and trust function, 77
 Probability density function (PDF), 158
 Profile management, 87
 Profile Provision System (PPS), 371
 Programmable Processing Elements (PPEs), 332
 Project MESA scenarios, 25
 Proxy Reconfiguration Manager (PRM), 373
 PRP. *See* Pseudo-random postfix (PRP)
 PRP-OFDM. *See* Pseudorandom-postfix OFDM (PRP-OFDM)
 Pseudorandom binary signals (PRBS), 195
 Pseudorandom-postfix (PRP), 134, 238
 Pseudorandom-postfix OFDM (PRP-OFDM), 141–142
 Public network (PN), 68
 Pulse shaping, 238–239
 Pulse-position modulation (PPM), 283
 PULSERS. *See* Pervasive Ultra-Wideband Low Spectrum Energy Radio Systems (PULSERS)
 QAM. *See* Quadrature amplitude modulation (QAM)
 QoS support
 optimized scheduling in, 182–183
 QoS-optimized access network, 179–180
 QPSK. *See* Quadrature Phase-Shift Keying (QPSK)
 Quadrature amplitude modulation (QAM), 133
 Quadrature Phase-Shift Keying (QPSK), 143, 251
 Quality of Service (QoS), 229, 313, 441
 Radio Access Network (RAN), 9
 Radio Access Technology (RAT), 313, 397
 Radio channel
 playback simulation, 205, 206*f*
 Radio channel sounders, 194–198

- Radio Communications Agency (RA)
 - spectrum trading, in United Kingdom, 401
- Radio Frequency (RF), 239, 359
- Radio Frequency IDentity Module (RFID), 52, 61, 296
- Radio multi-homing
 - use cases of, 405*f*
- Radio Network Access Point (RNAP), 392
 - multi-band capabilities, 393
- Radio Network Controller (RNC), 380
- Radio QoS Class (RQC), 179
- Radio Resource Management (RRM)
 - analysis of, 389
 - approaches and algorithms, 389
 - complex process, deploying of 4G networks, 390
 - in reconfigurability context, 389–391
- Radio RSF architecture, 373*f*
- Random graph, 444, 445
- Rapid single flux quantum (RSFQ), 262
- RCMAC. *See* Regulated Contention Medium Access Control (RCMAC)
- RDF. *See* Resource Description Framework (RDF)
- Real-Time Operating System (RTOS), 327
- Reasoning, 105–107
- Receiver, 281
- Reconfigurability, 313–415
 - roadmaps for, 319
- Reconfigurable Protocol Stack (RPS), 326
- Reconfigurable transmission, 150, 158*f*
- Reconfiguration Decision Authority (RDA), 379
- Reconfiguration Management Plane (RMP), 329
- Reflective middleware, 97
- Regular graph, 445
- Regulated Contention Medium Access Control (RCMAC), 182
- Regulatory agencies (RAs), 392
- Remote Event, 94
- Remote Method Invocation (RMI), 94
- Remote procedure call (RPC), 93
- Rendezvous Protocol, 428
- Research frameworks
 - hot-spots, 325
- Resource allocation, 177–183
- Resource Description Framework (RDF), 98
- Resource discovery, 73
- Resource handling, 74
- Resource usage efficiency
 - cross-layer optimization for, 179
 - QoS based adaptive MAC states for, 180
- Revenue sharing, 71
- RFID. *See* Radio Frequency Identification (RFID)
- Ring tones, 45
- RMI. *See* Remote Method Invocation (RMI)
- RNAP implementation scenario, 399*f*
- Router auto-configuration
 - IPv6 Router Renumbering, 426
 - router prefix delegation, 426
 - Zero router Automatic ReConfiguration Protocol (ARCP), 427
- Router prefix delegation, 426
- RPC. *See* Remote procedure call (RPC)
- RPS_FW
 - communication bootstrap, 340
- RQC. *See* Radio QoS Class (RQC)
- SAML. *See* Security Assertion Markup Language (SAML)
- SC-FDE. *See* Single carrier with frequency-domain equalization (SC-FDE)
- Scale-free graph, 446, 447*f*
- Scenario Connections, 30, 30*f*
- Scenario framework, 25
- Scenario planning, 16–17
 - aim of, 16
 - pre-determined, 16
 - predict-and-control approach, 16
 - uncertainties in, 17*t*
- Scenarios, 15
 - in design process, 20, 21*f*

- Scenarios, (*continued*)
- for development of Wireless Technologies and Services, 19–32
 - E2R, 24
 - history of, 16–17
 - IST Advisory Group (ISTAG), 22
 - MIT Project Oxygen, 25
 - Mobile IT Forum (mITF), 25
 - Project MESA, 25
 - review of, 21–24
 - role in development of wireless technology, 15–32
 - service provision, 29
 - use case, 18–19, 24
 - use in design community, 18
 - user-centered, 29
 - in user-centered design process, 19*f*
 - validation of, 20
 - working, 28
 - WWI, 24
- SCM AHG. *See* Spatial Channel Modeling AdHoc Group (SCM AHG)
- SCM Extension, 199
- Scrollwheel, 41
- SDF. *See* SW Download Provisioning (SDP)
- SDMA. *See* Space division multiple-access (SDMA)
- SDOs. *See* Super distributed objects (SDOs)
- Secured Incentive based Charging Protocol (SICP), 435
- Security
- usable, 127
- Security Assertion Markup Language (SAML), 119
- Security challenges, 127*f*
- Self-adaptation, 113
- Self-configuration, 113
- goal of, 424
 - in internet, 424–429
 - host auto-configuration, 424
 - Rendezvous Protocol, 428
 - router auto-configuration, 426
 - service auto-configuration, 427
 - Zeroconf Protocol, 428
- Self-organization
- in Ad hoc and sensor networks, 443
 - cooperation and fairness, 434
 - in communication networks, 423–449
 - graph-theoretical aspects of, 443
 - application to communication networks, 447
 - random graphs, 444
 - scale-free graphs, 446
 - small-world phenomenon, 445
 - meaning of, 423
 - in network management, 441
 - knowledge plane, 443
 - pattern-based management, 442
 - policy-based management, 441
 - potential and limitations of, 448
 - in today's internet, 424–433
 - open-content Web Sites, 432
 - peer-to-peer networking, 429
 - self-configuration in internet, 424
- Self-organization in Wireless World Systems (SIG3), 424
- goal of Special Interest Group, 424
- Self-protection, 113
- Semantic matching engine, 90
- Sensor networks, 61
- Sensor-MAC (S-MAC), 300
- Sequence inversion keying (SIK), 283
- Serial modulation, 134
- Serial-modulated systems, 138
 - bit-error-rate performance of, 138–139
- Service adaptation loop, 92*f*
- Service agents (SAs), 427
- Service architecture
- segmentation, 70
- Service auto-configuration, 427
 - service discovery service, 428
 - Service location protocol, 427
 - Universal-plug-and-play, 428
- Service broker, 65
- Service creation, 82
- Service Deployment Framework (SDF), 89

- Service developers, 64
- Service Discovery Service (SDS), 428
- Service execution environment, 79, 79*f*
- Service infrastructures, 59–108
 - networks in architectural view, 62*f*
 - platforms in architectural view, 62*f*
- Service Level Assignment (SLA), 426
- Service level specifications (SLS), 442
- Service location protocol (SLP), 427, 427*f*
- Service Negotiation (SN), 375
- Service platform architectures
 - consumers, 63
 - professionals, 62
 - requirements for, 60–77
 - service features
 - primary, 62–63
 - users, 62
- Service platform operator, 64
- Service Providers (SPs), 64, 65, 317
- Service Provision Scenarios, 29
- Service provisioning, 66
- Service provisioning and interaction
 - challenges in, 61–66
- Service provisioning function, 77
- Service Set Identifier (SSID), 104
- Service usage function, 77
- Services
 - dynamic combination and aggregation
 - by broker, 87*f*
- Short-range wireless communications, 227–303
- SIC. *See* Successive Interface Cancellation (SIC)
- Signal-to-Interference Ratio (SIR), 168
- Signal-to-Interference and Noise Ratio (SINR), 138, 228
- Signals
 - output power spectra of, 145*f*
- SIMO. *See* Single-input multiple-output (SIMO)
- Single carrier (SC), 236
 - modulation scheme, 134
- Single carrier with frequency-domain equalization (SC-FDE), 133
- Single sign on (SSO), 118
- Single-carrier CDMA, 139–141
- Single-input multiple-output (SIMO), 153
- Single-input single-output (SISO), 153
- Singular values (SVs), 233
- SINR. *See* Signal-to-Interference and Noise ratio (SINR)
- SIR. *See* Signal-to-Interference Ratio (SIR)
- SISO. *See* Single-input single-output (SISO)
- Small-world graph, 445
- Small-world Phenomenon, 445
- Smart antenna, 132, 150–170
 - benefits of, 151–153
 - cross-layer optimization, 166–167
 - efficiency of, 168
 - future deployment of, 169–170
 - link-level simulations, 167
 - MIMO channel modeling, 168
 - multiple-input multiple-output (MIMO), 153, 154*f*
 - performance evaluation of, 167–169
 - single-Input Multiple-Output system (SIMO), 153, 153*f*
 - single-input single-output (SISO), 153*f*
 - system-level simulations, 168
 - taxonomy of, 152*f*
- SMMSE. *See* successive minimum mean squared error (SMMSE)
- Software Component (SWC), 327
 - Reconfigurable protocol stack
 - framework (RPS_FW), 328*f*
- Software Defined Radio (SDR), 313, 356–365
 - evolution of, 388
 - Physical Layer Functions, 412
 - reconfigurability, 314
 - allocation of resources, 314
- Software Defined Radio Forum (SDRF), 6, 323
 - market aspects of, cognitive radio and spectrum efficiency, 395
- Software Download (SD), 317

- Software Download and Reconfiguration Controller (SDRC), 373
- Software Download Management (SDM), 375
- Software Provider, 320
- Software radio platform
 - configuration of, 339
- Software Updates CMM Installation, 340*f*
 - schedule of, protocol suite tasks, 341*f*
- Space division multiple-access (SDMA), 151, 246
- Space-Time Block Codes (STBC), 155, 160
- Space-Time Trellis Codes (STTC), 155
- Spaced vertical dipoles (SVD), 156
- Spatial antenna processing, 152
- Spatial multiplexing, 157
- Spatial multiplexing gain, 152
- Spectral efficiency
 - vs. number of antennas, 154*f*
- Spectrum and Radio Resource Management, 387–412
 - Network Planning approaches, 388
- Spectrum Brokerage (SB), 396
- Spectrum flexibility, 133, 146–149
- Spectrum landing zones, 272–276
 - regulatory bodies of, 272–275
 - standardization by IEEE, 275–276
- Spectrum Management
 - cognitive radio, 392
 - technical scope, 392*f*
 - with best band and frequency, 392
 - ITU recommendations for, 404
 - in Reconfigurability Context, 391
- Spectrum Management and Joint RRM
 - overview of, 390–391
 - RRM superset, 390
- Spectrum Management Research
 - Interference Temperature Metric, establishment of, 393
- Spectrum regulation authorities
 - new approaches to, 401
- Spectrum-sharing, 147*f*
- Speech interfaces, 48
- Speech output, 56
- Speech recognition, 55
- Sphere-Encoded Multiple Messaging, 178
- Spherical array, 201*f*
 - with 32 dual-polarized elements, 200*f*
- Spread spectrum multicarrier
 - multiple-access (SS-MC-MA), 132
- Spread-spectrum (SS), 283
- SS-MC-MA. *See* Spread spectrum multicarrier multiple-access (SS-MC-MA)
- SSID. *See* Service Set Identifier (SSID)
- SSO. *See* Single sign on (SSO)
- Stacked polarimetric uniform circular patch array (SPUCPA), 196, 199*f*
- Stakeholders
 - content providers, 64
 - end-users, 64
 - mobile network operator, 64
 - reseller/retailer, 65
 - roles of, 64–66
 - service developers, 64
 - service platform operator, 64
 - service providers, 64
 - third party, 64
 - trusted third party, 66
- Statistic based user profiler, 86
- STBC. *See* Space-Time Block Codes (STBC)
- Strategic planning scenario, 17
 - requirement for, 17
- STTC. *See* Space-Time Trellis Codes (STTC)
- Stylus, 41
- Subcarrier modulation (SCM), 283
- Subcarriers, 133
- Subscriber Identity Module (SIM), 52
- Successive Interface Cancellation (SIC), 156, 235
- Successive minimum mean squared error (SMMSE), 161
- Super distributed objects (SDOs), 89
- Superposition coding, 186
- Support Mobile Services (SMS), 34
- SVD. *See* Spaced vertical dipoles (SVD)
- SW Download Provisioning (SDP), 376

- Synchronicity, 173–174
- System
 - application and service requirements for, 72
 - business model requirements for, 70–71
 - context awareness requirements for, 75–76
 - functional requirements for, 66–76
 - general requirements for, 68–70
 - high-level user and stakeholder requirements for, 67–68
 - multimodal user interaction requirements for, 73–75
 - privacy and trust requirements for, 75
 - regulatory requirements for, 71–72
 - technological requirements for, 72–73
- System Abstraction Layer (SAL), 359
- System on Chip (SoC), 363
- System requirements
 - levels of priority
 - SHALL, SHOULD and MAY, 319
- System synchronization, 172
- Tapped delay line (TDL), 236
- TCP. *See* Transport Control Protocol (TCP)
- TCP parameters
 - reconfiguration of, 348
- TDD. *See* Time division duplexing (TDD)
- Technology Harmonisation
 - harmonised spectrum, 397
- Technology neutrality, 397
- Telecommunication Conformity
 - Assessment and Market (TCAM), 402
- Telecommunication network operators, 62
- Telecommunication service, 12
- Telecommunications
 - personalization, 61
- Terminal Capability Negotiation (TCN), 375
- Terminal provider, 65
- Terminal User
 - user and subscriber, 315
- Text menus, 44
- Text to speech (TTS), 45, 48
- 3rd Generation Partnership Project (3GPP), 9, 125
- THP. *See* Tomlinson-Harashima precoding (THP)
- 3GPP SCM, 192
- Time division duplexing (TDD), 138, 175, 227
 - guard bands in, 173f
 - interference, 243–244
 - MIMO–OFDM in, 228–249
 - application scenarios, 229–230
 - broadband MIMO channels, 231–236
 - channel modeling, 235
 - implementation of, 239
 - IQ imbalance, 239–241
 - peak-to-average power ratio (PAPR), 239
 - phase noise, 239
 - real-time implementation of, 247–248
 - requirements for, 229–230
- OFDM
 - FFT size, 237
 - motivation of, 236–237
 - prefix/postfix design, 237–238
 - principles of, 236–237
 - pulse shaping, 238–239
 - reciprocity, 241–243
 - time-variant channels, 242–243
 - transceiver calibration, 242
- Time Division Multiple-Access (TDMA), 243, 366
- Time Modulated Ultra-Wideband (TM-UWB), 252
- Today screen, 44
- Tomlinson-Harashima precoding (THP), 162
- Top Level Assignment (TLA), 426
- Topology control (TC), 434, 436
 - as self-organizing paradigm, 436
- Touchpad, 40
- Touchscreen, 40

- TPM. *See* Trusted Computing Platform (TPM)
- Traffic Engineering for Quality of Service in the Internet at Large Scale (TEQUILA), 442
- Transceiver calibration, 242
- Transmit channel state information (TCSI), 246
- Transmitted signal
characteristics of, 156
- Transmitter, 279–281
- Transparency, 113
- Transport Control Protocol (TCP), 166, 330, 429
- Travel Mobility Special Interest Group (IrTM), 291
- Trust evolution, 113
- Trust exploitation, 114
- Trust life cycle, 114*f*, 113–114
- Trust management, 114–115
- Trusted Computing Platform (TPM), 128
- Trusted third party, 66
- Two-way ranging
principle of, 271*f*
- Ubiquitous computing
trust
research issues, 115–116
trust life cycle, 114*f*, 113–114
trust management in, 112–116
trust requirements for, 113
- UCD. *See* User Centric Design (UCD)
- UHF. *See* Ultra High Frequency (UHF)
- UIs. *See* User interfaces (UIs)
- ULA. *See* Uniform Linear Array (ULA)
- Ultra High Frequency (UHF), 188
- Ultra-Wideband (UWB), 188, 249–277, 364
applications of, 254–260
high data rate, 257–258
home electronics, 258–259
home networking, 258–259
low data rate, 256–257
Wireless Body Area Networks (WBAN), 259–260
communication technologies in, 251–252
data throughput, 249*f*
home-networking setting, 258*f*
location issues, 269–271
medium access control (MAC), 266
multiple-access for, 267–269
radiation mask, 274*f*
regulations of, 252–253
standards for, 252–253
technology in, 260–266
A/D conversion, 261–262
antenna performance, 263–265
electronics, 261–262
interference, 265
signal propagation, 260–261
single- and multiband techniques, 262–263
waveform shaping, 265–266
tracking issues, 269–271
- Ultra Wide Band Audio Video Entertainment System (ULTRAWAVES), 250
- Ultra Wide band Working Group (UWBWG), 272
- UML structure
hardware abstraction, 362*f*
Parallel interference cancellation detector, 363*f*
- UMTS. *See* Universal Mobile Telecommunications System (UMTS)
- Unified Modelling Language (UML), 18
- Unified protocol approach, 383*f*
parity transmission approaches, 386*f*
transmission efficiency over leaf-node, 385*f*
- Uniform Linear Array (ULA), 162
- Unique Identifier Allocation Protocol (UIAP), 426
- Unitary-precoded OFDMA (UP-OFDMA), 137
- Universal accessibility, 12
- Universal Mobile Telecommunications System (UMTS), 3, 26, 102, 115, 160, 313
- Universal Modelling Language (UML), 361

- Universal Serial Bus (USB), 40
- Universal-Plug-and-Play (UPnP), 428
- Unlicensed frequencies, 73
- UP-OFDMA. *See* Unitary-precoded OFDMA (UP-OFDMA)
- Uplink (UL), 228
- Upper sideband (USB), 241
- Urban macrocell measurements, 203*f*
- Usability Gap, 33
- Usage scenarios, 18
 - increasing diversity of, 34
- Use case scenarios, 19, 24–25
 - in software engineering, 18–19
 - WWI scenarios, 24
- User agents (UAs), 427
- User Centric Design (UCD), 69
- User Datagram Protocol (UDP), 384, 429
- User Equipment (UE), 372
- User groups
 - increasing diversity of, 34
- User interface (UI), 15, 61
 - academic and industrial long-term research, 56
 - context-adaptive, 53
 - current state in, 38–46
 - acceleration sensor, 41
 - audio and video players, 45
 - built-in display, 42
 - built-in keypad, 40
 - buzzer, 43
 - camera, 42
 - direction pad, 41
 - external display, 42
 - external keyboard, 40
 - external mouse, 41
 - graphic menu, 44
 - handwriting recognition, 43
 - headphones, 42
 - joystick, 40
 - keyword speech recognition, 44
 - LED indicators, 43
 - loudspeaker, 42
 - multitap, 43
 - predictive text input, 43
 - ring tones, 45
 - scrollwheel, 41
 - stylus, 41
 - text menus, 44
 - text to speech (TTS), 45
 - today screen, 44
 - touchpad, 40
 - touchscreen, 40
 - virtual keyboard, 38
 - for future mobile devices, 32
 - evolution of, 46
 - of mobile devices
 - improvement of, 33
 - natural interaction, 48
 - gesture input, 50
 - haptic interfaces, 50
 - interpretation of emotion, 50
 - speech interfaces, 48
 - virtual spatialised 3D audio, 51
 - requirements for, 36
 - accessibility of, 36
 - consistency of, 37
 - desirability of, 38
 - efficiency of, 36
 - individuality of, 37
 - privacy of, 37
 - reliability of, 36
 - security of, 37
 - sociality of, 37
 - ubiquitous communications and information access, 51
 - device interconnectivity, 51
 - wearable elements of, 52
- User interface adaptation function, 77
- User Needs
 - UI-related, 36–38
- User-centered Scenarios, 29
- UWB. *See* Ultra-Wideband (UWB)
- V-BLAST. *See* Very-High-Data-Rate Blocked Asynchronous Transmission (V-BLAST)
- Value Added Services, 63
- Verification Configuration Procedure (VCP), 337
- Vertical polarized circular dipole array, 198*f*

- Very-High-Data-Rate Blocked Asynchronous Transmission (V-BLAST), 161
- Virtual keyboard, 38
- Virtual Machines (VM), 328
- Virtual Operating System (VOS), 336
- Virtual personal assistants, 55
- Virtual spatialised 3D audio, 51
- Visionary scenarios, 22
- Voice over Wireless Local Area Network (VoWLAN), 199
- VoWLAN. *See* Voice over Wireless Local Area Network (VoWLAN)

- W3C DOM events, 96
- Watts and Strogatz's scheme, 446
- WB. *See* Wideband (WB)
- Web Ontology Language (OWL), 98–99
- Web services
 - semantic mark-up language for, 99–100
- Web services description language (WSDL), 85
- Web Services Eventing (WS-Eventing), 97
- WG2
 - Value Added Services, 63
 - accounting, 63
 - adaptation, 63
 - authentication, 63
 - authorization, 63
 - billing, 63
 - charging, 63
 - context awareness, 63
 - identity management, 63
 - personalization, 63
 - privacy, 63
 - security, 63
 - service access control, 63
 - service discovery and composition, 63
 - trust, 63
 - usability, 63
- WG2 architecture
 - target area of, 60*f*
- Wide Area Network (WAN), 253
- Wideband (WB), 188
- WiFi. *See* Wireless Fidelity (WiFi)
- Wiki, 432
- Wikipedia, 432*f*, 433
- WiMAX. *See* Worldwide Interoperability for Microwave Access (WiMAX)
- WINNER project. *See* Wireless World Initiative New Radio (WINNER) project
- Wireless Body Area Networks (WBAN), 227, 259–260
- Wireless communication system
 - field tests of, 194
- Wireless communication transceivers, 156
- Wireless Communications, 313–415
 - short-range, 227–303
- Wireless CORBA, 93
- Wireless data networks
 - distributed scheduling with service differentiation, 181
- Wireless Fidelity (WiFi), 128
- Wireless foresight scenarios, 22
- Wireless Local Area Network (WLAN), 4, 29, 66, 115, 178, 227, 313
- Wireless network, 316
 - dynamic resource management, 316
 - reconfiguration management, 316
 - reconfiguration manager, 316
- Wireless optical communication, 277–296
 - link budget models, 284–288
 - optical communications, 286–288
 - radio communications, 285–286
 - modulation schemes, 283
 - optical channel, 282–283
 - optical wireless
 - vs. radio communications, 283–284
 - system components, 279–282
 - detectors/preamplifiers, 282
 - optical filtering, 281
 - optical systems, 281
 - receiver, 281
 - transmitter, 279–281
 - system configuration, 278–279

- Wireless sensor networks (WSN), 227, 296–303
 - applications of, 298*f*, 298–299
 - characteristics of, 299–302
 - network challenges, 301–302
 - node challenges, 299–301
 - penetration of, 297*f*
 - in smart home environment, 299*f*
 - standardization of, 302–303
- Wireless sensor networks (WSN), 227
- Wireless Strategic Initiative (WSI), 19
- Wireless technology
 - scenario planning, 16–17
 - scenarios, 17*f*
 - user requirements and expectations, 15–56
- Wireless World Initiative (WWI), 2, 19, 193
- Wireless World Initiative New Radio (WINNER) project, 193, 198
- Wireless World Research Forum (WWRF), 1, 11, 67, 122, 207, 424
 - goals of, 2–3
 - objectives of, 2–3
 - structure of, 4*f*, 3–4
- Wireless World Research Initiative (WWRI), 23
- Wireless-access technologies
 - requirements for support, 388
- WirelessNetwork, 101
- WirelineNetwork, 101
- WLAN. *See* Wireless local area network (WLAN)
- Work Areas of The Project (WAP), 24
- Working Group (WG), 16
- Working Scenarios, 28
- World Radio Conference (WRC), 5, 402
- Worldwide Interoperability for Microwave Access (WiMAX), 128, 388
- WS-Eventing. *See* Web Services Eventing (WS-Eventing)
- WWI. *See* Wireless World Initiative (WWI)
- WWI Scenarios, 24
- WWRF. *See* Wireless World Research Forum (WWRF)
- XML. *See* eXtensible markup language (XML)
- Zero-Padded OFDM (ZP-OFDM), 141–142
- Zero-Padding (ZP), 238
- Zero router Automatic ReConfiguration Protocol (ARCP), 427
- Zeroconf Protocol, 428
- ZP-OFDM. *See* Zero Padded OFDM (ZP-OFDM)

