

Index

- 60 GHz, 185
 - AFE: future development, 198–201
 - AFE: previous results, 195–198
 - analog front-end (AFE), 191–193
 - channel, 187–189
 - Demonstrator, 214
 - design consideration, 191–193
 - Propagation Measurements, 144
 - RMS delay for LOS and NLOS, 189
 - Sliding IF analog front-end, 193, 198–200
- Absorber, RF, 245
- Absorption coefficient, 294, 296, 311, 312, 320
- Acquisition
 - of impulse radio-based UWB signals, 62
 - of OFDM-based UWB signals, 63
 - of UWB signals, 61–4
- ADC
 - Figure of Merit, 119, 120
 - performance, 117, 118, 119
 - quantization, 225–27
 - technology, 118
- Advanced Interleaving Processing, 153
- Air Interface Design for 60GHz systems, 219
- Air interfaces for 60 GHz systems, 221
- Aloha, 92
- Alternative Methods, 41
- Ambient light interference, 338
- Amplification, 277, 295, 300
 - factor, 320, 321
- Amplifier
 - Erbium doped fibre (EDFA), 276, 285
 - optical, 276, 285
 - semiconductor optical (SOA), 277, 285, 319
- Analog to Digital Converter (ADC), 176–180
 - for UWB, 117
- Analog to Digital (A/D) and Digital to Analog (D/A) converters, 113, 114
- Anechoic chamber, 246
- Angle of arrival, 74
- Angular dispersion, 32
- Antenna, 227–36
 - 60-GHz microstrip line dipole on LTCC, 251
 - 60-GHz probe-fed patch on LTCC, 250, 251
 - adaptive, 239, 240, 247
 - aperture-coupled, 243
 - array, 227–34, 240, 241
 - beam forming, 239, 242, 247
 - beam pattern, 239
 - beam steering, 239, 242, 247
 - designing for LTCC, 243–252
 - diversity, 240
 - MIMO, 240
 - patch, 243
 - slot-coupled, 243
 - smart, 239
 - weight, 239
- Array Architecture for 60 GHz systems, 231
- Artefacts, in imaging, 105

- Auger recombination, 288
- Autocorrelator, 206
- Auto-focusing, 105
- Avalanche photodiode (APD), 276, 295–7, 302, 305, 306, 308, 310, 324

- Background subtraction, 105–7
- Band allocation in 60 GHz, 144
- Bandwidth, 271–6, 279, 285–6, 291–6, 298, 303, 305, 314, 316, 323
- Beamforming, 66, 194, 240–42
- Beam-squint, 240
- BICMOS, 227–29
- Binary Interleaving Benchmarking, 161
- Binary Interleaving Process, 156
- Broadband access, 272, 276–7
- Bussgang decomposition, 263

- Canonical Representation of the Impulse Response, 30
- Cap 4 - Pulse Shaping and Diversity, 39
- Cavity, 277, 286–8, 293–5, 304, 313
- Ceramic Substrates, 237
- Challenges in deterministic UWB channel modeling, 34
- Challenges in stochastic UWB channel modeling, 35
- Challenges in UWB coexistence, 123
- Challenge/Vision, 41, 43
- Channel Access, 22
- Channel capacity, 66
- Channel measurement, 65
- Channel modeling approaches, 30
- Channel modelling
 - In-room channel, 336
- Channel Propagation Characterization and Modeling of mm-wave Channels, 144
- Channel selection filter, 201
- Channel sounding, 29
- Channel, 271–4, 276, 278–9, 282–4, 286, 299, 300, 302–7, 311–315, 318, 324
- Channel
 - Fading multipath, 61
 - Frequency selective, 61
 - Multipath spread, 61
 - VI characteristics, 333
- Characterization of mm-wave Channels, 146
- Chirp, 275–6, 289
- Clipping and filtering (CF), 259
- CMOS, 227–31
 - implementation of UWB radios, 114
- Code, 274
- Coded modulation, 203
- Coexistence of UWB and narrowband systems, 63–4
- Cognitive networks, 93–95
- Cognitive radio, 93–94, 123, 124
- Communication architecture, 17
- Components in a 60 GHz Radio Transceiver, 229
- Conductivity, 244
- Confinement factor, 288, 321
- Connectivity, 21
- Continuous and discrete dynamics, 94
- Continuous Phase Modulation for 60 GHz systems, 223
- Conversion, 271–2, 275–6, 279, 285–6, 290, 293, 298–99, 300, 302, 303, 308–10, 313–14, 319, 323
- Convolutional codes, 202
- Cooperative concept for energy saving, 21
- Cooperative Wireless Networking, 15
- Coplanar waveguide, 243
- Correlative channel sounders, 30
- Cramer-Rao lower bound, 74
- Cross gain modulation, 319
- Cross phase modulation, 319
- Cross-correlation, 101
- Cutoff frequency, 231, 231
- Cyclic prefix, 221–22, 224

- DAA, 130, 131
- Data fusion, 98
- Data throughput evolution of communication systems, 4
- Decision-feedback, 261
- Delay dispersion, 32
- Delta-sigma ADC, 117
- Demodulation, 293, 299

- Design
 - Synchronization and timing issues, 61–4
- Designing rules for short-range systems, 16
- Detection, 97, 105
- Detector, 302, 323
- Differential
 - detection, 47
 - gain, 288
 - time difference of arrival, 86
- Diffusion coefficient, 289
- Digital Baseband, 181
- Digital to Analog Converter (DAC), 180
- Direction-of-arrival, 85
- Dispersion, 242, 275, 298, 312, 314, 324
- Distributed feedback lasers, 277
- Diversity, 42, 109, 111
- Driver circuits, 333
- Dynamic Interleaving Code, 160
- Dynamic range, 258
- Dynamic Subcarrier Mapping Allocation, 167

- ECMA, 186
- Effective signal bandwidth, 74
 - effects, 306
- EIRP, 186
- Electro-absorption Mach-Zehnder Interferometer, 286
- Electro-absorption modulator (EAM), 276, 299
- Electro-absorption process, 292
- Electro-absorption transceiver (EAT), 276, 290, 292
- Electro-optic,
 - device, 275
 - phase modulator, 319
- Electro-optical transfer function, 291
- Emerging uses of short-range technologies, 10
- Energy awareness, 17
- Envelope, 285, 297, 311–12
- Envelope detection, 47
- Equalization, 335
 - soft iterative, 261
- Erbium doped fibre amplifier (EDFA), 276–7, 285, 319

- Ethernet, 273
- European projects on 60 GHz: Overview, 137
- Extinction ratio, 292

- Fabry-Perot resonator, 294–5
- Feature size used in ADC, 118
- Ferro A6-S, 243, 244
- Fibre, 271–2, 274–6, 285–6, 293, 302, 311–16, 318–19, 324
- Filtering, 274, 322
- Fisher information matrix, 77
- Flash ADC challenges, 119, 120
- Flexible Spectrum, 23
- Flip-chip, 230, 235, 237
- Franz-Keldysh effect, 290
- Frequency domain equalizer, 222–23
- Frequency regulation, 141, 186
- Frequency, 273–6, 284, 286, 289, 291, 297–8, 300, 302–4, 307, 311, 312, 316, 319, 323

- Gain, 286–9, 295, 297, 300–2, 306, 308–9, 311, 314, 319–21
- Gaussian,
 - doublet, 319, 321–3
 - IR-UWB doublet, 318–19
 - monocycle, 273
 - probability density, 307
 - pulse, pulses, 319–23
 - random process, 289
 - tail, 307
- General classification of short-range communications, 6
- Generalized multiband transceiver, 58
- Goodput vs. payload size, 211, 212
- Grating, 319
- Grid implementation, 15
- Group velocity, 288, 308, 312

- HDTV, 213
- High power amplifier (HPA), 198
- Hybrid system modeling, 94–95

- I/Q modulator/demodulator, 199–200
- IEEE 802.15.4a, 91

- Imaging, 98
 - bat-type, 103
 - multistatic, 99
- Impact of Channels on Geolocation, 36
- Impedance matching, 245
- Implementation issues of 60 GHz systems, 227
- Impulse Based UWB Transceiver
 - Architectures, 87
- Impulse radio UWB (IR-UWB), 53–56
- Impulse response, 316
- Indoor Channel Properties, 87
- Indoor Localization, 85
- Input power backoff (IBO), 258
- Interconnect, 230, 235–37
- Interconnection Substrates, 235
- Interference analysis
 - Narrowband systems on UWB systems, 63–4
- Interferometer,
 - Mach-Zehnder, 276, 286, 319
 - optical, 298
- Interleaving
 - Algorithm, 155
 - Partitioning, 154
- Intermodulation,
 - distortion, 287, 290, 302–4, 307, 316
- Intrasystem interference, 121
- ISM band, 122
- ITRS, 229, 231

- Kirchhoff migration, 100, 105

- Langevin force, 289
- Laser, 285–91, 298, 309, 316, 324
- Laser,
 - bias current, 306
 - cavity, 304
 - chirp, 289
 - diode, 277, 286, 305
 - dynamics, 304
 - intensity, 286
 - modulation, 276, 303
 - noise, 289, 302
 - output, 306
 - power, 321
 - resonance frequency, 289
 - LDC, 129, 130, 132
- LED modulation bandwidth, 334
- Lightwave, 291
 - systems, 285, 293
- LiNbO₃, 286
- Linear Modulation Schemes for 60 GHz systems, 221
- Linearization, 255
- Line-of-sight, 76, 221
- Linewidth enhancement factor, 288–9, 319
- Link budget, 220
- Link Level Performance of UWB OFDM, 161
- Local area network, 273, 285, 313
- Localization, 73, 98–9, 105, 107
- Location base line,
 - elliptical, 109
 - hyperbolic, 110
- Loss tangent, 244
- Losses, 273, 276, 285–8, 291, 293, 296, 298–9, 301, 309, 312, 319–320, 323
- Low-power UWB Hardware, 113
- Low noise amplifier (LNA), 196
- Low temperature co-fired ceramic (LTCC), 243, 244, 245, 247
- LTCC technology, 248, 249

- MAC (Medium Access Control) protocol, 92, 210
- Mach-Zehnder Interferometer (see Interferometer, Mach-Zehnder)
- Matching stub, 243
- Maximum a posteriori
 - estimator for timing, 61–2
 - probability, 79
- Maximum likelihood, 78
 - estimator for timing, 61–2
- Maxwell's equations, 288
- Medium Access Control, 22, 92
- MEMS, 242
- Microstrip line, 243
- Microwave, 291–2, 297
 - components, 323
 - devices, 296–7
 - driving signal, 291
 - electromagnetic disturbances, 297
 - frequency, 291

- functions, 296
- loss, 291
- mixing, 298
- optical interactions, 293
- photonics, 293, 323–4
- photonic applications, 293
- photonic links, 296
- power, 276
- radio links, 290
- region, 290
- signals, 291, 297–8, 323
- wavelength, 291
- Millimeter-Wave Applications and Services, 138
- Minimum-Shift Key (MSK) system:, 173–175
- MMSE equalizer, 222–23, 225
- Mobile
 - peer-to-peer architecture, 11
 - social networks, 11
- Mode, 273, 277, 283, 286–9, 293, 316, 319
 - refractive index, 288
- Model, 307–11, 314
- Modulation, 273, 285–6, 290–1, 293, 298–9, 303, 308
 - bandwidth, 291, 298
 - conversion, 279, 298
 - depth, 290, 304–8
 - device, 286
 - efficiency, 287, 290–2
 - formats, 273
 - frequency, 286, 297
 - index, 314
 - method, 272
 - response, 287
 - schemes, 340
 - signal, 287
 - techniques, 318
 - technology, 273
 - type, 278
- Modulation,
 - amplitude, 288
 - biorthogonal, 274
 - cross-gain, 319
 - cross-phase, 319
 - direct, 286–7, 298, 304
 - direct laser, 276
 - electrical, 297
 - envelope, 274
 - external, 276, 286, 290, 298
 - frequency, 298
 - intensity, 286, 298
 - linear, 298
 - phase, 288
 - pulse, 274
 - ultra-wideband, 292
 - UWB, 275
- MOS transistor, 227–28
- MUI, 92
- Multiband communications, 58
- Multicarrier modulation, 257
- Multi-Carrier Subcarrier Mapping Allocation, 156
- Multi User Interference, 92
- Multipath, 221, 225–27
 - components, 102
 - Propagation Modeling, 147
- Multiple antenna, 193–194
- Multiple hops, 91
- Multiple input and multiple output (MIMO), 65, 98, 109–11
- Multiple-access interference, 81
- Multiquantum well, 277, 287, 290
- Narrowband interference (NBI), 56
 - Cancelation of, 63–4
 - Coexistence of UWB and narrowband systems, 63–4
- Navigation, 97–8
- Network, 271–9, 284–5, 290, 313, 323
- Network analyzers, 30
- NLOS, 99
- Noise, 272, 274, 276, 286–7, 289–90, 293, 295–6, 301–302, 304–8, 314, 316, 324
- Noise figure, 286–7
- Non line-of-sight, 76, 81, 221
- Noncoherent Detection for UWB, 47
- Nonideal analog parts, 253
- Nonlinear distortions, 253
- Nyquist-rate for ADC, 118
- Object recognition, 98
- OFDM, 185, 190–191, 202–210
 - Boosted Modes, 152

- OFDM-CPM, 254
- OFDM-PM, 254
- On-Off Keying, 48
- Opensor, 12
 - hardware, 14
- Operating ranges of typical short-range communication systems, 5
- Optical
 - amplifiers, 276, 285
 - communication systems, 285, 287
 - components, 323
 - fibres, 277, 319
 - filtering, 334
 - link, 273, 275–6, 285–7, 293, 298–9, 313–14, 316
- O-QPSK, 220–21
- Organic Substrates, 236
- Orthogonal Frequency Domain Multiplexing (OFDM) system, 174–175
- Orthogonal frequency-division multiplexing (OFDM), 202
- Out-of-band emissions, 122
- Overlay concept for energy saving, 20
- Oversampling factor, 259

- Packaging (RF), 230
- Packet aggregation, 212, 213
- Patch antenna, 230, 232–33
- Path loss, 31
- Peak-to-Average Power Ratio (PAPR), 190, 206, 258
- Performance of 60 GHz physical layer, 224
- Performance of noncoherent detection, 49–50
- Personal area networks (PAN), 135–6
- Personal networks (PN), 138–139
- Phase noise (impact of), 225–26
- Phase shifter, 240–2
- Phase-locked loop (PLL), 187, 200–201
 - RMS phase-error, 201
- Photodetector, 276, 292–3, 296, 302, 304–6, 313–14, 319, 324, 339
- Photodiode, 276–7, 299, 304, 310
- Phototransistor, 324
- Physical layer for mm-wave UWB-OFDM systems, 152, 158

- Physical layer, 202
- Point to point links, 336, 338
 - Channel plan, 186–187
 - Narrowband channel plan, 187
- Power
 - amplifier, 258
 - budget, 276, 301–2
 - consumption, 115
 - divider, T-junction, 244
 - efficiency, 114
- Preamble, 205
- Predistortion, 255
- Presence, 22
- Private PAN, 139
- Probe station,
 - GSG probe, 245, 246
 - on-wafer, 245
 - product, 290, 303–4
- Progressive phase,
 - factor, 242
 - shift, 244, 247
- Pulse, 273–5, 291, 311–13, 319–23
 - collision, 92
 - generators, 29
 - Shaping, 39
- Pulse-Position Modulation, 48

- QoS, 93
- QPSK, 220–21, 224–227
- Quantum
 - dot, 319
 - efficiency, 288–9, 294–6
 - well, 276, 287, 324
- Quantum dot semiconductor optical amplifier (QD SOA), 319–23
- Quarter-wave transformer, 244

- Radar, bistatic, 98
- Radar cross section, 109
- Radargram, 104
- RAKE receiver, 53
- Rate equations, 287–9, 320
- Received signal strength, 75
- Receiver, 272, 274, 276, 285, 293, 299, 300, 302, 305, 306, 310, 318, 324
- Receiver preamplifier, 339

- Recombination, 288
- References, 44
- Reflectarray, 240, 242
 - passive, 242
 - reconfigurable, 242
- Regeneration, 293, 300, 319
- Relative intensity noise (RIN), 276, 287, 289–90, 302, 305, 307, 316
- Relative permittivity, 243
- Retro-reflectors, 341
- RF Front-End, 177
- RF Packaging and Antenna Design for 60 GHz, 230
- Rise time, 322
- Router, 280
- SalehValenzuela model, 32
- Scalability, 21
- Schottky,
 - barrier, 295
 - photodiode, 293, 295
- Security and Privacy and Authentication, 23
- Self-organizing, 22
- Semiconductor
 - laser, 287–8
 - optical amplifier (SOA), 277, 285
- Sensor networks, 97–8
- Service Discovery, 22
- Service provisioning, 122
- SiGe BiCMOS, 195
- Signal, 271–5, 277–81, 283–7, 289–300, 302–3, 305, 308, 311, 313–16, 318–323
- Signal design, 254
- Signal Processing Solutions for 60GHz systems, 219
- Signaling and Traffic Channels, 20
- Signals
 - impulse radio, 62
 - orthogonal frequency-division multiplexing (OFDM), 63
 - transmitted reference, 62
 - ultrawideband (UWB), 61–4
- Signal-to-noise ratio (SNR), 286, 289
- Single-carrier frequency domain equalization (SC-FDE), 190–191
- Single-carrier transmission, 221
- SLAM, 111
- Small scale fading, 32
- SNR, 276, 286, 289–90, 318
- Soft limiter (SL), 259
- Software Defined Radio Design, 23
- Solid-state lighting, 331
- Space-time coding, 66
- Spectrum, 272–4, 278, 284–5, 316, 318, 322–3
- Spectrum sharing technology, 123
- Spurious emissions, 122
- Statistical UWB channel modeling, 31
- Standardisation, 341
- Subband, 57
- Substrate, 229–37
- Substrate Materials for 60 GHz Antennas, 232
- Switching diversity, 193
- Synchronization
 - algorithm, 204
 - blind, 55
 - temporal, 99
 - of UWB signals, 61–4
- System-in-a-package (SiP), 234
- System-in-package Integrated Antenna, 234
- System-on-a-chip (SoC), 234–35
- TCP/IP, 216
- Technologies for 60 GHz systems, 227
- Thermal noise, 272, 302, 305
- Thin-film Technology, 234–36
- THMA, 92
- Time difference of arrival, 86, 110
- Time estimation
 - Maximum likelihood, 61–2
 - Maximum a posteriori, 61–2
- Time Hopping Multiple Access, 92
- Time of arrival, 75, 85, 99
- Time of transmission, 86
- Time-frequency multiplexer, 58
- Tracking of persons, 97
- Transistor,
 - bipolar, 297
 - field-effect, 297
 - high-electron mobility (HEMT), 297

- Transmit power, 186
- Transmit-reference UWB systems, 53–56
- True time delay element (TTD), 242
- Two-path model, 189
- Two-way-ranging, 86

- Ultra-wideband-radio-over-optical-fibre (UROOF) technology, 271, 279, 282, 293, 313, 323
- unintentional out-of-band emission, 123
- UWB, 216
 - channel models: standardization activities, 32
 - Coexistence Scenarios, 121
- UWB Regulation, 127, 136
 - In US, 127
 - In Europe, 127
 - In Japan, 129
 - process, 123
 - Visionary approach, 131
- UWB standardization, 130, 136, 141
 - In US, 130
 - In Europe, 131

- UWB Transceiver for Indoor Localization, 85
- UWB, ultra wideband, 65

- Vertical-cavity-surface emitting laser (VCSEL) diode, 276, 286–9, 298–300, 302–4, 308–9, 313–14, 318
- Visible Light Communications Consortium, 331

- Wavelength, 273, 277, 290–2, 294, 296, 299, 300, 302, 309, 314, 316, 319, 324
 - conversion (WC), 319
 - division multiplexing (WDM), 285
- WDM, 299
- White-light LEDs, 332
- Wireless Grids, 16
- Wireless Sensor Networks, 12
- WWRF future research subjects in short-range, 8
- WWRF multisphere reference model, 4
- WWRF short-range white papers and briefings, 7

- Zero-forcing equalizer, 224–26
- zero-IF, 227, 230, 227, 230