

Index

Page references in **bold** indicate tables and references in *italics* indicate figures.

- accumulation mode 8
- ACGIH
 - inhalable fraction and 250
 - occupational exposure limits 294
 - particle size-selective aerosol sampling criteria 271
 - respirable fraction curve 271, 272
 - thoracic fraction curve 271, 272
 - TWA TLVs for selected substances occurring in workplaces as aerosols **295–296**
- aerobiology 473
- aeroconiscope 477
- aerodynamic diameter 4, 27–28, 268
- aerodynamic particle sizer (APS) 61, 64, 66, 67, 501, 502
- Aerogel-General glass cyclone sampler 485
- aerosizer 501
- aerosol concentrations 11, 228, 313, 320, 489, 490
- aerosol exposure 222–227, 291
 - definitions of 225–226
 - history 226, 231
 - human respiratory tract 223–225
 - indices of 313, 320–322
 - inhalation 223
 - occupational exposure limits 294–297
 - sampling frequency 231
 - typical cumulative 230, 231
 - variability of 227
- aerosol fractions, identification of 270
- aerosol mass concentration 9
- aerosol materials 57–59
- aerosol measurement 8–9
- aerosol mechanics 22–33
 - drag coefficient 22–23
 - general equation of motion under the influence of an external force 24–25
 - impaction 28–30
 - molecular diffusion 30–32
 - particle aerodynamic diameter 27–28
 - particle drag force and mobility 22
 - particle motion without external forces 25–26, 27
 - slip 23–24
 - turbulent diffusion 32–33
- aerosol particle size distribution *see* particle size distribution
- aerosol particle size selection after aspiration *see* particle size selection after aspiration
- aerosol sampler studies, experimental methods 35–70
 - assessment of collected aerosol 60–61
 - direct (trajectory) method 35–36, 37, 101
 - indirect (comparison) method 36–37, 60, 102
 - methodology for assessing sampler performance 35–38
 - protocols and procedures 61–68
 - reference methods 60
 - test aerosol generation 50–60
 - test facilities 39–50
- aerosol samplers
 - air and particle movement near single-entry 9, 10
 - in the ambient atmosphere, field experience with 575–598
 - line and point sink samplers 71–72
 - nature of air flow near 71–91
 - performance characteristics 9–12
 - rebound of particles from outer walls of 170
 - for the respirable fraction 359–385
 - scaling relationships 38–39
 - thick-walled tubes 75–76
 - thin-walled slot and tube entries 73–75
- aerosol samplers in the workplace 537–573
 - converting particle counts to particle mass 549–558
 - diesel particulate matter 568–569
 - future of workplace aerosol measurement 569–570
 - personal and static (or area) sampling 538–539
 - relationship between ‘total’ and inhalable aerosol 539–549
 - for respirable aerosol fraction 558–562

- aerosol sampling
 - analytical methods 228–229
 - at high altitude from aircraft 440, **441**
 - direct-reading instruments 318–319, 322, 489–515
 - framework for health-related 227–233
 - graph to show the effect of face velocity on the relationship between collection efficiency and particle diameter for a filter used for particle collection during 529
 - impaction efficiency 98
 - instrumentation 228
 - interference effects of external walls 165–173
 - interferences to 157–191
 - numerical values for aerosol fractions **274**
 - in occupational settings, summary of time lines of approaches to **319**
 - particle size-selective criteria for health-related 273, 274
 - personal sampling 229
 - sampling strategies 229–232
 - time lines of approaches to aerosol sampling in ambient atmospheric environment 322, **323**
 - in working, living and ambient environments 221–235
- aerosol sampling in calm air *see* calm air sampling
- aerosol sampling historical milestones 311–325
- ambient atmospheric 319–323
- occupational 312–319
- aerosol sampling in working, living and ambient environments
 - exposure to aerosols 222–227
 - framework for health-related 227–233
 - nonhealth-related standards 233–234
- aerosol shape analysis system (ASAS) 503, 512
- aerosol spectrometers 318, 447, 448–451, 452
- aerosol standards *see* standards
- aerosol tunnel sampler 430
- aerosols
 - biological origin 291
 - classification of 3, 4
 - classification of workplace 562–568
 - found in ambient environment 233
 - as hazards in the environment 222
 - mathematical model of aerosol behavior near thin-walled probes 112–113
 - particle size 3, 4
 - radioactively labeled test 260
 - scientific definition 3
 - standards for *see* standards
- AEROTRAK™ 9000 Nanoparticle Aerosol Monitor (NAM) 510
- AeroTrap™ 479
- aethalometer 579
- air ejectors 520
- air flow
 - flow rate through samplers 89
 - near cylindrical blunt sampler facing the wind 83
- air flow near aerosol samplers 71–91
- blunt samplers
 - facing the wind 76–81
 - with orientations other than facing the wind 82–89
- complex sampling systems 89
- freestream turbulence 90
- line and point sink samplers 71–72
- thick-walled tubes 75–76
- thin-walled slot and tube entries 73–75
- two-dimensional blunt sampling systems 76–80
- air moving systems 519–524
- pulsation damping 523–524
- pumps 520, 521
 - personal sampling 522–523
- air pollution 320
- air quality limit values, for UK particle size-selective aerosol fractions 299–300
- air velocity
 - of an aspirating thin-walled tube placed at an angle to the freestream 106, 107
 - axial distributions for flow in aspirating thin-walled tube facing into the wind 73
- air volume, three-dimensional elementary 13, 14
- airborne bacteria sampler (ABS) 479, 480
- airborne dust
 - comparison between workers' exposures as measured using the IOM personal inhalable aerosol sampler and the 37 mm closed-face cassette sampler in a nickel mine 548
 - CIS personal sampler in a carbon black production facility 545, 546
 - summary of historical data as measured by various methods in a nickel smelter **556**
- airborne lead, indices of particle size distribution for exposure at worksites in a large lead smelter 565, **566**
- airborne particulate matter, Research Triangle Park Particulate Matter Panel Study 592
- alumina 57–58
 - characteristics of aerosols generated from **59**
- alveolar deposition efficiency 265, 278
- ambient atmosphere
 - aerosol sampling 319–323, 417–445
 - classification of aerosols 593–596

- field experience with aerosol samplers in the 575–598
- meteorological sampling 440–442
- sampling for fine aerosol fractions in 432–440
- sampling for total suspended particulate in 425–432
- summary of time lines of approaches to aerosol sampling in the 322, **323**
- ambient atmospheric aerosol limits
 - black smoke and fine particles 297–298
 - EPA PM NAAQS limit values 298–300
 - for nonhealth-related aerosols 300–302
- ambient carbon particulate monitor 579
- ambient environments, framework for aerosol sampling in 221–235
- American Conference of Governmental Industrial Hygienists *see* ACGIH
- ammonium nitrate 297
- analysis of collected samples 60–61, 533–535
 - chemical analysis 511, 534–535
 - gravimetric methods 534
 - handling and transport of samples 533–534
- analytical models, for aspiration efficiency in calm air 138–144
- Andersen MK-II cascade impactor, modified 28.3 Lpm 566
- Andersen MK-II nonviable sampler 455, 456
- Andersen N-6 single-stage multi-orifice sampler 480, 481
- Andersen viable cascade impactors 481, 482
- animal dander 4
- apparent aspiration efficiency 10, 35
 - see also* aspiration efficiency
- area sampling 229
- asbestos 302, 315
- asbestos fibers 4, 279, 280
 - NIOSH recommended method for optical detection and counting of respirable 532
- asbestosis 302
- Aspect 503
- aspirating thin-walled tube
 - placed at an angle to the freestream 106
 - relationships for defining representative sampling 114–115
- aspiration 9, 131–156
 - controlling interference effects during 172
 - effects of electrostatic forces on 162–164, 165
 - effects of turbulence on 158–162
 - experimental conditions for experimental studies of aspiration characteristics of thin-walled cylindrical sampling tubes 99, **100**
 - interferences to aerosol sampling after 173–188
 - interferences to aerosol sampling during 157–173
 - options for aerosol particle size selection after 193–217
 - sampling in slowly moving air 149–154
- aspiration in calm air 131–149
- aspiration efficiency 10, 35, 93, 95, 97, 132
 - for an annular slot sampler in air moving very slowly 154
 - for an aspirating thin-walled tube facing upwards 142, 143, 149
 - placed at various angles to the freestream 105
 - for aspirating thin-walled cylindrical sampling tubes facing the freestream 95, 96
- in calm air
 - analytical models for 138–144
 - for upwards-facing aspirating thin-walled cylindrical tubes 135, 136
- comparison between measured and calculated aspiration efficiency for an aspirating thin-walled tube placed at various angles to the freestream 108
- descriptive modeling of 144–147
- determination by direct method 101
- determination by indirect method 102
- of the human head 238, 239, 244, 245, 246
 - combined nose and mouth (oronasal) breathing 246, 247
 - later results for 242, 243
 - nose breathing 246, 247
- of a sampler in calm air, Ter Kuile combination of parameters 148
- for sampling in calm air, general function expression 134
- set of trends as function of Stokes number for various velocity ratios, bluntness values, body widths and orifice widths 117, 118
- for single value of Stokes number for an aspirating thin-walled tube 102
- for a spherical blunt sampler in calm air 138, 139
- for thin-walled and blunt samplers placed with orifices at an angle of
 - 90 degrees to the freestream 124
 - 180 degrees to the freestream 124, 125
- variables for describing 38
 - see also* apparent aspiration efficiency
- aspiration in moving air 93–130
 - blunt samplers 116–127
 - thin-walled tube samplers 94–116
- aspiration in slowly moving air 149–154
 - intermediate conditions 152–154
- assessment of collected aerosol *see* analysis of collected samples
- asymmetry factor 503

- atmospheric aerosols 4
 chemical composition 594–595
- B. subtilis*, collection efficiency and relative recovery for 483, 484
- Baby-IOM inhalable aerosol sampler 349, 350, 523
- bacteria 4
- Bayes, Thomas 557
- BCIRA sampler 373
- Beijing, China, study to describe outdoor and indoor levels of aerosol fractions (PM₁₀, PM_{2.5} and PM₁) 591
- Belyaev and Levin model 103
- Berner impactor 457
- beta-attenuation mass balance 509
- beta-attenuation monitor 579
- bi-modal particle size distribution, in a coal mine 7
- bias maps
 percentage deviation of experimental data for aspiration efficiency of an aspirating thin-walled tube using two semi-empirical models for extended ranges of Stokes number and velocity ratio 103, 104
 to illustrate variation of departure of sampled mass from the desired ideal as function of particle size distribution as represented by MMAD and GSD 64, 65
- bioaerosol monitoring
 direct-reading aerosol sampling instruments 511–513
 fluorescence technology 511–512
 hybrid systems 512–513
 particle size and shape for bioaerosols 512
- bioaerosol sampling 473–488
 centrifugal samplers 485–486
 criteria for 477
 early 476–477
 electrostatic precipitation 486
 inertial samplers 477–483, 484
 performance indices 476
 technical issues 474–476
 thermal precipitation 486
 ‘total’ and inhalable bioaerosols 486
- bioaerosols 473
 diagram to indicate combination of measurement of particle size, particle shape and particle nature provides options for rapid detection and identification 512
 exposure limit values 303
 particle size and shape 512
 standards for 474
- biological exposure indices (BEIs) 291
- biological recovery efficiency 476
- BioSampler^R 482, 483, 484
- BioslideTM 479
- BioStage^R single-stage bioaerosol impactor 480
- bird-strike preventor 422
- black smoke 498
 air pollution expressed in terms of 320
 ambient atmospheric aerosol limits of fine particles and 297–298
 apportionment of the contributions to BS, PM₁₀ and PM_{2.5} for the city of Edinburgh from nearby and distant sources 581
 comparison between measurements of black smoke at a site beside a heavy-traffic urban road during October and November in a city using three direct-reading instruments together and BSI method 579
 European Community (EC) directive limit and guide values for 297, **298**
 methods for measuring 578–579
 and particle size fractions (PM₁₀ and PM_{2.5}) 580–582
 sampling for 423–425
 summary of comparisons between black smoke and PM₁₀ in a rural village in the Czech Republic 582
 summary of results of side-by-side comparisons of data collected at locations in Berlin for TSP and **580**
 total suspended particulate and 577–580
- blockage ratio 40
- blowers 520
- blunt samplers 116–127
 axisymmetric facing the wind 121
 bias maps to show percentage deviation of experimental data for aspiration efficiency of simple disk-shaped 122
 diagram of a simple axisymmetric blunt sampler facing the freestream 117
 facing vertically downwards, descriptive modeling of aspiration efficiency 146
 facing the wind 76–81
 impaction model for a blunt sampler facing the freestream 116–120
 mathematical and numerical approaches to 125–126
 model for disk-shaped sampler facing the wind 119
 orientation-averaged conditions 126–127
 with orientations other than facing the wind 82–89
 cylindrical blunt samplers 82–83
 of simple shape facing the wind, experimental investigations 120–123
 two and three-dimensional mathematical studies 126

- see also* cylindrical blunt samplers; disk-shaped blunt samplers; spherical blunt samplers
- blunt sampling systems
 - axially symmetric 80–81
 - two-dimensional 76–80
- boundary layers 16–18
- breathing zone 229–230
- British smoke shade sampler (BSS) 424
- British standard gauge 418, 419, 576
- British Standards Institution (BSI) 409
- Brownian motion *see* molecular diffusion
- BSI deposition gauge 418, 419, 576
- bubble flowmeter 525–526
- bulk powder material, dry dispersion 52–56
- Button personal inhalable aerosol sampler 347–348, 349, 486, 547
- cadmium, exposure to aerosols containing 291
- calm air, definition of 150–152
- calm air chambers 46, 47
- calm air sampling 45–48
 - Agarwal and Liu criteria for 148
 - by thin-walled probes, descriptive model 144
 - conditions corresponding to, based on Ogden's theory 151
 - criteria for representative 147–149
 - Levin expression for aspiration efficiency 140
 - using cylindrical tubes 141
- carbon, fixed and organic 297
- Carl Zeiss konimeter 360, 361
- cascade centipeter 450
- cascade cyclones 466–467
- cascade impactors 318, 466–467, 481, 482, 533
 - Casella Mk1 454, 455
 - earlier 454, 455
 - inversion procedures for 463–465
 - outline 452–454
 - personal 459–462
 - for stack sampling 462, 463
 - static cascade impactor-based samplers 454–459
 - testing of 563
- cassettes 334, 533
- CATHIA–T static thoracic aerosol sampler, collection efficiency 390, 391
- cement dust 4
- CEN, sampler testing guidelines 68
- centrifugation, aerosol particle size selection after aspiration 201–205
- centrifuges 450, 485–486
- CERL vertical dust gauge 422–423, 576, 577
- chemical analysis, of collected samples 534–535
- CIP10 personal samplers 336, 337, 341, 382, 389
 - collection efficiency 383
 - design of 390
 - performance of 342
- CIP10–T personal thoracic aerosol sampler, collection efficiency 390, 391
- CIS personal sampler *see* conical inlet sampler
- Climet, particle counting instrument 500
- closed-face cassette sampler (37 mm) 334, 540, 541
 - comparison between workers' exposures to airborne dust as measured using 543
 - airborne lead as measured using 542, 543
 - overall airborne dust as measured using 542
- coal dust 4
- coal industry, respirable aerosol exposures in 549–552
- coal mine
 - bi-modal particle size distribution in 7
 - dust exposures 560
- coal rank, relationship between MNI and 551, 552
- coal-fired power station, comparison between results obtained using two versions of the Mini-RAM sampler and the 10-mm nylon personal respirable aerosol sampler 561, 562
- coarse aerosol fractions
 - particle size-selective criteria for 237–254
 - personal samplers for 333–351
 - static (or area) samplers for 327–333
- coarse aerosols, sampling in workplaces *see* sampling for coarse aerosols in workplaces
- coarse dust method 115
- coarse mode 8
- coarse 'nuisance' aerosols
 - indices for 322
 - sampling for 417–423
- collection efficiency 418
- collection media 526–533
 - choices and applications 531–532
 - filters 526–527
 - filtration efficiency 527–528
 - mass stability 528–531
 - roles of various particle collection mechanisms 528
 - substrates 532–533
- colony forming units (CFUs) 316
- combustion-related aerosols 394–395
- comparative studies
 - summary of results for 37 mm closed-face plastic cassette sampler for 'total' aerosol versus the IOM personal inhalable aerosol sampler 543, 544
 - summary of results for various samplers versus the IOM personal inhalable aerosol sampler 546
 - workers' exposures to overall airborne dust as measured using the IOM personal inhalable

- comparative studies (*continued*)
 aerosol sampler and the CIS personal sampler
 in a carbon black production facility 545, 546
 complaints, determining likelihood of complaints for
 coarse dust/grit particles for daily levels measured
 using a dust deposit gauge 234
 condensation particle (nuclei) counter (CPC) 469,
 504–505
 conical inlet sampler 336, 347, 545
 conicyle 383–384
 Conifuge 450
 continuous ambient particulate monitor 510
 cooking related aerosols 4
 Coulter counter 61, 239
 countable biological agents 474
 CPM3 static sampler 368
 critical orifice 525
 culturable biological agents 474, 475
 cumulative distribution, particles 5, 6
 cumulative log-normal particle size distribution 7
 Cunningham slip correction factor 24
 cyclone-based sampling head, 16.7 Lpm 433, 434
 cyclones 202–204, 316, 485
 2 Lpm conductive plastic cyclone 375
 2.2 Lpm respirable dust cyclone 375
 2.5 Lpm respirable aluminum cyclone 375
 10 mm nylon (Dorr-Oliver) single-inlet 368, 369
 penetration as function of particle aerodynamic
 diameter 370, 371
 wind speed dependency 369
 GK2.69 cyclone-based personal sampler 375
 respirable fraction samplers 368–375
 results for penetration versus particle aerodynamic
 diameter for cyclone used for aerosol
 sampling 204
 reverse-flow 202, 203
 side-by-side field studies results **559**
 thoracic fraction samplers 386–387
 cylindrical blunt samplers 82–83
 facing away from the freestream, streamline pattern
 expected 84
 with a slot entry facing the wind, typical smoke
 tracer visualisation 84
 two-dimensional, general form of the streamline
 pattern near 82
see also blunt samplers; disk-shaped blunt samplers;
 spherical blunt samplers
 cylindrical thin-walled probes
 facing the wind, sampling errors associated with
 particle rebound from external sidewalls
 of 171, 172
 limitations of sampling with 404
 Danish personal passive aerosol samplers 355, 356
 Darwin, Charles, on bioaerosol sampling 476, 596
 DataRAM 4™ 497
 Davies criterion for representative sampling 148
 Dean number 180
 deposition, inside thin-walled tube at orientations other
 than forward-facing 184–185
 deposition of inhaled aerosols
 in the alveolar region 264–265
 studies of regional 255–268
 of very fine and ultrafine aerosols 266–268
 deposition losses
 inside a bent sampling tube 180–181
 inside a thin-walled tube facing into the
 wind 181–184
 deposition velocity 177
 for particles deposited inside a straight cylindrical
 tube by turbulent diffusion 179
 in a straight cylindrical tube as a function of
 dimensionless particle relaxation time 179, 180
 diaphragm pumps 520, 521
 diesel particulate matter (DPM) 568–569
 sampling cassette for 395
 differential mobility analyzer (DMA) 281, 504
 diffusion
 aerosol particle size selection after
 aspiration 211–212, 213
 deposition in flow through screens 212, 213
 deposition from laminar flow through
 tubes 211–212
 molecular 30–32
 turbulent 32–33
 diffusion batteries 467–469
 dilution, sampling probes for stack sampling 413–414
 direct method 35–36, 37, 101
 direct-reading aerosol sampling instruments 318–319,
 322, 489–515
 bioaerosol monitoring 511–513
 condensation nuclei/particle counters 504–505
 electrical particle measurement 503–504
 mechanical aerosol mass measurement 505–509
 nuclear mass detectors 509–510
 optical aerosol-measuring instruments 490–503
 surface area monitoring 510–511
 direct-reading stack-monitoring instruments 415
 diseases
 associated with particle inhalation 289
 beyond the respiratory tract 291–292
 of the respiratory tract 290–291
 disk-shaped blunt samplers
 effects of freestream turbulence 161

- facing the wind and exposed to aerosols of fused alumina, plot of experimental data 169, 171
- photograph of the flow pattern near 81
- see also* blunt samplers; cylindrical blunt samplers; spherical blunt samplers
- Dorr–Oliver nylon cyclone (10 mm) 558
- drag coefficient 22–23
- dry-dispersed dusts 52–56
- ducts
 - location of sampling points 404, 405
 - sampling in 403–416
- dust 4
 - comparison between workers' exposures as measured using the IOM personal inhalable aerosol sampler and the seven-hole personal sampler 547
 - suggested factors to convert personal exposures to 'total' aerosol 545
- dust deposit gauges 418, 419, 576
 - experimental results for performance of 420
- dust deposition (dustfall) 300, 418
- dust deposition limit values 300, 301
- DUSTTRAK™ 497
- dynamic shape factor 28, 29
- dynamical limit of Levin 140, 149
- dynamical sampling velocity 133

- electret sampler 547
- electret-based passive aerosol samplers 355
- electric charge effects 59–60
- electric single particle aerodynamic relaxation time analyzer 501
- electrical aerosol analyzer (EAA) 503, 504
- electrical low pressure impactor (ELPI) 457, 593
- electrical mobility spectrometers 503
- electrical particle measurement 503–504
- electronic balances, summary of LOD 530
- electrostatic effects, interferences after aspiration 186–188
- electrostatic forces
 - on aspiration 162–164, 165
 - effects on particle sampling under practical conditions 164
 - effects on sampler aspiration efficiency 164, 165
- electrostatic precipitation 213–214
- elemental carbon, measurement of 569
- elutriation 194–197
 - horizontal 195–197, 316
 - vertical 194–195
- EN 13205 sampler testing protocol 63–64, 352, 537–538
- entry efficiency (apparent aspiration efficiency) 10

- EPA
 - 16.7 Lpm EPA generic reference sampling system for PM_{2.5} 438
 - 16.7 Lpm EPA well impactor ninety-six (WINS) 435, 437
 - inlets and sampling systems used in the 1983/984 EPA intersampler comparisons 585
 - PM NAAQS limit values 298–300
 - sampler testing guidelines 68
- equivalent projected area diameter 4
- equivalent sulfidic fraction (ESP) 567
- equivalent surface area diameter 4
- equivalent volume diameter 4
- exponential size distribution parameter 550
- exposure limit values 289–307
 - bioaerosols 303
 - fibrous aerosols 302–303
 - special cases 301–305
 - ultrafine aerosols 304–305
- exposure limits 232–233
 - health-based exposure limits 293
 - no observed adverse effect level 232
 - regulatory exposure limits 293–294
 - see also* occupational exposure limits (OELs)
- exposure rate parameter 241
- exposure to aerosols *see* aerosol exposure
- external walls, aerosol sampling interference effects 165–173
- extrathoracic deposition, of inhaled aerosols 261–262, 263
- extrathoracic fraction 275–276
 - see also* thoracic fraction

- fans 520
- Federal Reference Method (FRM) 434, 575
- fibrous aerosol monitor (FAM) 500
- fibrous aerosols 500
 - exposure limit values 302–303
 - particle size-selective criteria for 279–280
 - results for deposition of 265–266
- fibrous filters 526–527
- field experience with aerosol samplers in the ambient atmosphere 575–598
 - black smoke and particle size fractions (PM₁₀ and PM_{2.5}) 580–582
 - 'nuisance' dust 576–577
 - personal exposures to PM₁₀ and PM_{2.5} 589–592
 - PM_{2.5} 589
 - PM₁₀ 585–589
 - transition to particle size-selective sampling 582–585
 - TSP and black smoke 577–580

- field experience with aerosol samplers in workplaces 537–573
 - diesel particulate matter 568–569
 - gravimetric mass sampling 558–559
 - personal and static (or area) sampling 538–539
 - for respirable aerosol 558–562
- field studies, results comparing aerosol concentrations
 - as measured by personal and static (or area) sampling for various samplers and indices of concentration **538**
- filter holders, open-face 328
- filter plane 9
- filters
 - collection media 526–527
 - summary of LOD for 530
- filtration, by porous foam media 197–201
- filtration efficiency, collection media 527–528
- fine aerosol fractions
 - criteria for 268–281, 282
 - thoracic and respirable aerosol fractions 273–275
 - very fine aerosol fractions 278–279
 - extrathoracic aerosol fraction criteria 275–276
 - historical overview 268–271, 272
 - particle size-selective criteria for 255–287
 - tracheobronchial and alveolar aerosol fractions 276–278
- fine dust method 115
- fine and ultrafine particles, efficiency of 266
- flow patterns 16, 17
- flow rate 524–526
 - flow control 525
 - flow measurement 525–526
- flow separation 18, 19
- flow stability 84–86
- flow through screens, deposition by diffusion in 212, 213
- flows, separation and reattachment 18, 19
- fluid mechanics 13–22
 - boundary layers 16–18
 - equations of fluid motion 13–15
 - potential flow 20
 - stagnation 18, 19
 - streamlines and streamsurfaces 15–16
 - turbulence 20–22
- fluidised-bed generators 55–56, 57
- fluorescence technology 511–512
- fluorescent aerodynamic particle sizer (FLAPS) 511
- fly ash 4
- foam media 198
 - calculated penetration 201
 - nominal porosity 200
 - penetration of a cylindrical plug of porous plastic foam media 199
- forward-scattering instrument 499
- freestream turbulence, effects on aerosol samplers 90
- frequency distribution, particle size distribution 6
- friction velocity 178
- Froude number (*Fr*) 26
- full-shift true breathing zone sampler 351
- fumes 4
 - suggested factors to convert personal exposures to ‘total’ aerosol **545**
- Gathercole model 554
- geometric diameter 4
- geometric standard deviation (GSD) 64, 65
- granular bed filters 527
- Gravicon 328
- gravimetric dust sampler, 2.5 Lpm MRE (Mines Research Establishment) Type 113A 166
- gravimetric mass sampling 558–559
- gravimetric methods
 - analysis of collected samples 534
 - EPA guidelines 534
- gravimetric samplers
 - for inhalable aerosol 317
 - for respirable fraction 316–317
 - for total aerosol 313–314, 317
- gravitational deposition of particles 175, 177
- gravity angle 185
- greases 533
- Greenberg–Smith impinger 362, 363
- GS-1 conductive plastic cyclone 374
- GS-3 respirable dust cyclone 370, 372
- hard rock mining, respirable aerosol exposures in 552–554
- Harvard impactor, field comparisons for side-by-side reference sampler for PM₁₀ and chosen ‘local’ samplers for PM₁₀ 587, **588**
- HAZ-DUST 1 497, 498
- ‘Hazard’ device 489
- Health and Safety Executive (UK), occupation exposure limits 294
- helmet-mounted personal samplers 351
- Hering low pressure impactor 457
- Hexhlet horizontal elutriator-based respirable aerosol sampler 364, 365
- Hi-Vol sampler for PM₁₀ 434, 436
- Higgins–Dewell sampler 373, 374, 558
- Hirst spore trap 479
- horizontal dust deposit gauges 418, **576**, 577

- horizontal elutriation 195–197
 - idealised uniform flow 196
 - penetration of rectangular horizontal elutriator 197
 - realistic parabolic laminar flow 196
- horizontal elutriator-based 2.5 Lpm MRE static respirable aerosol sampler 367
- horizontal elutriators 316, 364–368, 448–450
- horizontal thin-walled probes 146
- hot processes, suggested factors to convert personal exposures to ‘total’ aerosol **545**
- human head, aspiration efficiency of the *see* aspiration efficiency, of the human head
- human health, risk of aerosols to 222
- human respiratory tract 223–225
 - alveolar region 289
 - diseases of 290–291
 - extrathoracic region 289
 - regions of and deposition of inhalation particles during inspiration and expiration 256, 257
 - regions of 289
 - tracheobronchial region 289
- ‘Hurricane’ sampler 554
- hybrid systems, bioaerosol monitoring 512–513

- idealised test aerosols 50–52
- impaction 28–30
 - aerosol particle size selection after aspiration 205–211
 - conventional 205–208
 - low pressure and micro-orifice 209
 - virtual 209–211
- impaction efficiency 29
 - for aerosol sampling 98
 - for an aspirating thin-walled cylindrical sampling tube 98, 99
 - for an aspirating thin-walled cylindrical sampling tube from experiments using direct method by Belyaev and Levin 101
 - for an aspirating thin-walled tube facing the freestream
 - comparison between the experimental data of Zenker and the theoretical calculations of Volushchuck and Levin and Rüping 112
 - comparison between the theoretical calculations of Vitols and Belyaev and Levin 111
- impaction models
 - for a blunt sampler facing the freestream 116–120
 - for orientations other than forward-facing 105–109
 - for a thin-walled tube facing the freestream 96–98
- impactor-based sampling heads, for collecting fine atmospheric aerosol fractions 433

- impactors
 - 2 Lpm multi-orifice-size respirable aerosol 377
 - multi-orifice-size parallel impactor 376, 377
 - respirable fraction samplers 376–377
 - single-stage 478–481
 - thoracic fractions samplers 387–388
- impingers 314, 361–362, 363, 482–483, 484
- in-stack sampling probe 410
- incident plane 9
- indirect method 36–37, 60, 102
- inertial samplers
 - bioaerosol samplers 477–484
 - impingers 314, 361–362, 363, 482–483, 484
 - passive samplers 478
 - single-stage impactors 478–481
- inertial spectrometers 450–451, 452
- inhalability 249
 - at very low wind speeds 244–247
 - early experimental measurements of 237–241
 - Armbruster and Breuer 238, 239
 - Ogden 238, 239
 - Vincent and Mark 239, 240
 - experimental studies 237–247
 - later experimental results for aspiration efficiency of human head for various wind speeds 240, 241
 - physical basis of 241–242
 - for very large particles 242–244
- inhalability curves
 - for calm air 251
 - showing original ISO curve and the original ACGIH curve 249
 - for various wind speeds 251
- inhalable aerosol
 - personal samplers for coarse aerosol fractions 344–351
 - relationship between ‘total’ aerosol and 539–549
 - sampling for total suspended particulate in the ambient atmosphere 431–432
 - side-by-side comparative studies of ‘total’ aerosol and 540–547
 - static samplers for coarse aerosol fractions 328–333
- inhalable aerosol exposure concentrations, example of the history in a large nickel smelter from 1960 to 1979 557
- inhalable aerosol exposures, in the nickel industry 554–558
- inhalable aerosol samplers, analysis of performance data for 352–354
- inhalable fraction 252–253, 317
 - criteria for 248, 249–251
- inhalation 223

- inhalation experiments 259
- inlet sampling efficiency 476
- INSPEC inertial aerosol spectrometer 451, 452
- instrumentation, aerosol sampling 228, 309–515
- instruments
 - direct-reading 322, 489–515
 - stack-monitoring 415
 - optical aerosol-measuring instruments 490–503
- interception 30
- INTERCOMP2000 study 593, 594
- interferences to aerosol sampling after
 - aspiration 173–188
 - in complicated systems 186
 - deposition inside thin-walled tube at orientations other than forwards-facing 184–185
 - deposition losses
 - inside a bent sampling tube 180–181
 - inside a straight sampling tube 173–179, 180
 - inside a thin-walled tube facing into the wind 181–184
 - electrostatic effects 186–188
 - rebound of particles from internal walls 185–186
- interferences to aerosol sampling during
 - aspiration 157–173
 - electrostatic forces 162–164, 165
 - external wall effects 165–173
 - turbulence 158–162
- intermediate conditions 152–154
- intersampler comparisons, summary of locations 585, **586**
- 'inverted Frisbee' deposit gauge 420, 421, 576, 577
- IOM 2 Lpm personal inhalable aerosol sampler 344, 345, 486
 - performance in calm air 345, 346
 - performance in slowly moving air 346, 347
 - performance for various windspeeds 345, 346
- IOM 3 Lpm static inhalable aerosol sampler 330–332
 - complete assembled instrument 331
 - performance of 332
 - sampling head 331
- IOM 30 Lpm sampler 431, 432
- IOM personal inhalable aerosol samplers 379, 530, 540, 541
 - comparison between workers' exposures to airborne dust as measured using 541, 543
 - airborne lead as measured using 541, 542
 - overall airborne dust as measured using 541, 542
 - scaling relationships for the modified, low flow rate version **350**
 - summary of LOD and LOQ for different combinations of filter and cassette 531
- IOM personal inhalable dust spectrometer (PIDS), cumulative particle size distributions obtained using 565
- IOM static inhalable dust spectrometer (SIDS) 458
- isokinetic sampling 74, 114–116, 237
- Johannesburg curve 269
- konimeters 312, 314, 360, 361, 552–554
 - comparison between standardised konimeter counts and respirable silica concentration 555
 - field comparisons between four different models 553
- Kuile, Ter 148–149
- layer efficiency 198
- lead, exposure to aerosols containing 291
- Levin, aspiration efficiency of a point sink in calm air 139–140
- light attenuation-based monitors in stack sampling, single-pass and two-pass 493
- light extinction 491
- light scattering 491
- light scattering photometry 494–498
- limit of detection (LOD) 60, 529, 530–531
- limit of quantification (LOQ) 60, 529, 531
- limit values 289–307
 - aerosol-related health effects 289–292
 - ambient atmospheric aerosol limits 297–301
 - bioaerosols 303
 - fibrous aerosols 302–303
 - for nonhealth-related aerosols 300–302
 - occupational exposure limits (OELs) 292–297
 - standards setting 292
 - ultrafine aerosols 304–305
- limiting trajectory 28–29
- line and point sink samplers 71–72
- Litton large volume electrostatic air sampler (LVAS) 486
- Liu–Pui inlets 433, 435, 436
- living environments, framework for aerosol sampling in 221–235
- log-normal particle size distribution 6
- long-running thermal precipitator (LRTP) 315, 362, 550
- lung diseases, associated with exposure to bioaerosols 303
- lung, the, summary of morphological and physiological data for **224**
- Maddox sampler (aeroconiscope) 477

- Marple personal cascade impactor 460–461, 462, 563
 eight-stage 481, 482
 set of typical cumulative particle size distributions using 564
- Marple-type miniature eight-stage cascade impactor 559
- Marple-type personal cascade impactors 533
- mass balances 506–508
- mass measurement 505–509
- mass median aerodynamic diameter (MMAD) 6, 64, 65
- mass number index (MNI) 551
 relationships with other aspects of airborne dust in coal mines 552
- mass stability, collection media 528–531
- maximum exposure limit (MEL) 294
- Maxwell, James Clerk 491
- mechanical mobility 22
- membrane filters 527
- mesothelioma 302
- meteorological sampling 440–442
- metering dust generator 55, 56
- method of tangents 503
- micro impinger 483
- micro-orifice impactors 209
- micro-orifice uniform deposit impactor (MOUDI) 457, 458, 461
- midget impinger 314, 361–362, 483
- mine dust sampling, cotton-wool filters 313
- Mini-Ram light scattering based instrument 561
- Miquel sampler 479
- mist 4
 suggested factors to convert personal exposures to 'total' aerosol 545
- MMAD (mass median aerodynamic diameter) 6, 64, 65
- Model 3040 diffusion battery 467
- modified Andersen MK-II nonviable sampler 457
- molecular diffusion 30–32
- MOUDI, 2 Lpm personal sampler 457, 458, 461
- mouth breathing 256, 275
- moving air 40–45
 near a point sink, particle trajectories for 110
 streamline patterns 72
- MPG II, 46 Lpm (sampler) 364
- MRE respirable dust sampler 364, 367, 550
 comparison between output from two direct-reading optical instruments and respirable aerosol measured gravimetrically using the 561
- MRE Type 113A horizontal elutriator-based static respirable aerosol sampler 366
- multi-inlet respirable aerosol sampler 372
- multi-orifice-size parallel impactor 376
 penetration as function of particle aerodynamic diameter 377
- multi-stage liquid impinger (MSLI) 483
- multiple-jet single-stage impactors 480
- Nano-MOUDI 457
- Nanometer Aerosol Sampler (NAS) 439, 440
- nasal deposition, calculated results for efficiency 276
- National Ambient Air Quality Standards (NAAQS) 298, 299
- NBS dust feeder 55, 56
- next generation pharmaceutical impactor (NGI) 459, 460
- nickel industry, inhalable aerosol exposures in 554–558
- nicotinamide adenine dinucleotide phosphate [NAD(P)H] 511
- nonculturable organisms 474, 475
- nonviable organisms 474
- nose breathing 256
- nuclear mass detectors 509–510
- nucleation mode 8
- Nuclepore^R filter 527, 528
- 'nuisance' dust, samplers in the ambient atmosphere 576–577
- null-type probes 411, 412
- nylon cyclone samplers 163, 523
- occupational aerosol sampling 312–319
 aerosol exposure indices 313
 gravimetric samplers for respirable fraction
 gravimetric samplers 316–317
 sampling strategies and philosophies 312–313
 sampling to measure aerosol particle size distribution 317–318
 total and inhalable aerosol gravimetric sampler 317
- occupational exposure limits (OELs) 233, 292–297, 539
 for aerosols 294–297
 health-based exposure limits 293
 regulatory exposure limits 293–294
 tables of 292
see also exposure limits
- occupational exposure standard (OES) 294
- opacity monitors 494
- open-face 37 mm plastic cassette 334–335
- open-face filter holders 328
- open-plate deposition (OPD) 477
- optical aerosol-measuring instruments 490–503
 light scattering photometry 494–498

- optical aerosol-measuring instruments (*continued*)
 - optical particle counters 498–501, 502
 - particle size and shape 503
 - physical background 490–492
 - transmission/extinction monitoring 492–494
- optical and gravimetric aerosol samplers, workplace
 - comparisons between 559–562
- optical microscopy 469–470
- optical particle counters 498–501, 502
- optical particle sizing and counting 499
- optical processes, aerosol particle size selection after aspiration 215
- optical scattering instantaneous respirable (dust)
 - indication system (OSIRIS) 367, 495
- ORB (overall respirable burden) sampler 317, 328–330
 - smoke tracer visualisation of flow near 87, 89
- orifice size coefficient 141
- overall sampling efficiency (sampling effectiveness) 10
- Owens jet sampler 315, 361, 362

- P. fluorescens*, collection efficiency and relative
 - recovery for 483, 484
- Paik and Vincent model, measurements of aspiration
 - efficiency for thin-walled tubes 103–104
- paper thimble-type collectors 314
- parallel impactors 465–466
- particle aerodynamic diameter 4, 27–28, 268
- particle count samplers 314–316
- particle counts
 - converting to particle mass 549–558
 - for ultrafine aerosols 594
- particle drag force and mobility 22
- particle extinction coefficient 491, 492
- particle mass, converting particle counts to 549–558
- particle motion
 - general equation of motion under the influence of an external force 24–25
 - without external forces 25–26
- particle removal efficiency 476
- particle size
 - and chemical species fractions, summary
 - presentation of distributions of 568
 - distribution analysis, by microscopy 469–470
 - measurement and chemical speciation 566–568
 - statistics 5–8
- particle size classification, diagram to illustrate
 - principle of aerosol 449
- particle size distribution 5, 6, 7, 8
 - of ambient atmospheric aerosols 593–594
 - sampling for the determination of 317–318, 447–472
 - of workplace aerosols 562–565, 566
- particle size distribution parameter 551, 552
- particle size fractions (PM₁₀ and PM_{2.5}), black smoke
 - and 580–582
- particle size selection after aspiration 193–217
 - centrifugation 201–205
 - diffusion 211–212, 213
 - electrostatic precipitation 213–214
 - elutriation 194–197
 - filtration by porous foam media 197–201
 - impaction 205–211
 - optical processes 215
 - thermal precipitation 214–215
- particle size-selective criteria for coarse aerosol
 - fractions 237–254
 - experimental studies of inhalability 237–247
 - inhalable fraction 247–252
- particle size-selective criteria for fine aerosol
 - fractions 255–287
 - extrathoracic aerosol fraction 275–276
 - fibrous aerosols 279–280
 - history of 268–272
 - international harmonisation of sampling criteria 284
 - overview 282–284
 - studies of regional deposition of inhaled
 - aerosols 255–268
 - thoracic and respirable aerosol fractions 273–275
 - tracheobronchial and alveolar aerosol
 - fractions 276–278
 - ultrafine aerosols 280–281, 282
 - very fine aerosol fractions 278–279
- particle size-selective criteria for the inhalable
 - fraction 247–252
- particle size-selective sampling 582–585
 - criteria summary **252, 283, 284**
- particle velocity correction function 153
- particles
 - aerosol concentration 11, 228, 313, 320
 - charge conditions 186
 - composition and health effects 228
 - concentration units of airborne 271
 - converting particle counts to particle mass 549–558
 - cumulative distribution 6
 - equivalent projected area diameter 4
 - equivalent surface area diameter 4
 - equivalent volume diameter 4
 - frequency distribution 6
 - geometric diameter 4
 - ICRP model of particle deposition during inhalation
 - and exhalation 256, 257
 - log-normal particle size distribution 6
 - monodisperse 5

- options for aerosol particle size selection after aspiration 193–217
- particle size-selective criteria for the inhalable fraction 247–252
- penetration in laminar flow through vertical cylindrical tube associated with the Saffman lift force 175, 176
- penetration through sampling tubes 187
- penetration through straight cylindrical tubes 175
- polydisperse 5
- rebound from internal walls 185–186
- size statistics 5–8
- turbulent deposition of iron and aluminum in glass and brass tubes 178
- particulate matter (PM) 299, 395, 407–408, 425, 568–569, 592
- passive aerosol samplers
 - Danish personal 355, 356
 - electret-based 355
 - inertial samplers 478
 - sampling for coarse aerosols in workplaces 354–356
- Patterson-graticule 318
- PCI (precision cascade impactor) 459, 566
- penetration
 - for deposition by diffusion 212
 - in a single screen 213
 - for various Dean numbers 182
- permissible exposure limits (PELs) 248, 294
- personal aerosol sampling 229
- personal cascade impactors 459–462
- personal DataRAM 4™ 497
- personal environmental monitor (PEM) 388, 392
- personal inhalable aerosol samplers, comparison between performance of the 2 Lpm IOM and 0.3 Lpm Baby-IOM 350
- personal inhalable dust spectrometer (PIDS), 2 Lpm IOM 459, 461
- personal samplers
 - 2 Lpm conical inlet personal sampler 341
 - 2 Lpm personal closed-face 37 mm plastic cassette 339
 - 2 Lpm personal open-face 25 mm plastic cassette 340
 - 2 Lpm personal open-face 37 mm plastic cassette 339
 - 2 Lpm seven-hole personal sampler 341
 - 2 Lpm single-hole personal sampler 340
- CIP10 336, 337
- closed-face 37 mm plastic cassette 334
- for coarse aerosol fractions 333–351
 - inhalable aerosol 344–351
 - total aerosol 333–344
- conical inlet sampler 336
- fused alumina dust deposits on external surface 166, 167
- open-face 37 mm plastic cassette 334–335
- performance in calm air 343
- PERSPEC 337–338
- seven-hole sampler 335–336
- single-hole sampler 335
- for total aerosol
 - full-shift true breathing zone sampler 351
 - helmet-mounted sampler 351
- personal sampling 229
- personal sampling pumps 522–523
- personal and static (or area) sampling, field experience with aerosol samplers in workplaces 538–539
- PERSPEC personal samplers 337–338, 396
 - performance of the 2 Lpm 342
- phase contrast microscopy (PCM) method 279–280
- piezoelectric mass balance 506–508
- Pilat source test cascade impactor Mark I 462
- Pilat source test cascade impactor Mark III 464
- piston pumps 520, 521
- plastic samplers, deposition of particles inside 187
- PM_{2.5}
 - apportionment of the contributions for the city of Edinburgh from nearby and distant sources 581
 - measurement of 589
 - personal exposures to 589–592
 - sampling for fine aerosol fractions in workplaces 391–393
 - summary of averaged results for PM₁₀ ambient aerosol concentrations and **594**
 - summary of results for a number of Canadian cities 595
- PM₁₀ 321
 - apportionment of the contributions for the city of Edinburgh from nearby and distant sources 581
 - at kerbside of a busy road junction in Sunderland, comparisons between samplers for **588**
 - averaged results for PM_{2.5} ambient aerosol concentrations and **594**
 - comparisons between black smoke and PM₁₀ in a rural village in the Czech Republic 582
 - criterion 585–589
 - fraction 575
 - indoors mass concentration for both PM₁₀ and respirable (cyclone) samples 590, 591
 - mass concentration as function of respirable (cyclone) mass concentration for both indoors and outdoors 590, 591
 - personal exposures to 589–592
 - relationship between TSP concentrations and 584

PM₁₀ (continued)

results for a number of Canadian cities 595
 results of side-by-side comparisons of PM₁₀, PM₁₅
 and TSP at six locations in the US 583, **584**

PM₁₅, results of side-by-side comparisons of PM₁₀,
 PM₁₅ and TSP at six locations in the US 583, **584**
 'Pneumoconiosis Field Research' (PFR) 231, 549–550
 summary of respirable dust measurements made in
 British coal mines **551**

point sink in calm air, general pattern of streamlines
 and particle trajectories near 140

point sink samplers, line and 71–72

pollens 4

polystyrene latex (PSL) 500

porous foam pre-selector stage of the prototype 30
 Lpm IOM thoracic aerosol sampler, performance
 of 437

porous plastic foam filter samplers 67, 378–383
 penetration as function of particle aerodynamic
 diameter 378, 379

prototype designed for applications in sampling
 respirable welding fume 379, 380

prototype penetration as function of particle
 aerodynamic diameter 380

samplers for the thoracic fractions 388–391
 for TEOM ambient particulate monitor 381

porous plastic foam-based 2 Lpm sampler for
 simultaneous collection of inhalable thoracic and
 respirable aerosol 396

porous plastic foam-based modified 2 Lpm IOM
 sampler for thoracic aerosol sampler 389

porous plastic foam-based modified CIS sampler for
 PM_{2.5} aerosol 392

Portacount^R 505, 506

Porton graticule 469–470

potential flow 20

precision bands 283–284

precision cascade impactor (PCI) 459

pulsation damping 523–524

pumps 519–536

air moving systems 519–524

analysis of collected samples 533–535

collection media 526–533

flow rate 524–526

personal sampling 522–523

rapid acquisition method 67

rebound coefficient 172

for a thin-walled cylindrical sampling tube facing
 the wind 173

reference methods 60

reference worker 225

regional deposition of inhaled aerosols 255–268

alveolar region results 264–265

experiments for studying 259–260

extrathoracic deposition results 261–262

fibrous aerosols results 265–266

framework 255–258

theories, simulations and models 258–259

total deposition results 260–261

tracheobronchial deposition results 262–264

very fine and ultrafine aerosols results 266–268

regression analysis, relationship between standardized
 konimeter data and corresponding gravimetric data
 for respirable silica **555**

Respicon personal sampler 397–398

respirable aerosol exposures

in coal industry 549–552

in hard rock mining 552–554

respirable aerosol monitor (RAM) 496–497

respirable aerosols 359

respirable combustible dust (RCD) method 568

respirable fibers, sampling for 385

respirable fraction 269

aerosol samplers for 359–385

definition 273

gravimetric samplers for the 316–317

respiratory tract *see* human respiratory tract

reticulated polyurethane foam media 198

retrospective exposure assessment 311

Reuter centrifugal sampler (RCS) 485

Reynolds, Osborne, Sir 21

Reynolds number (*Re*) 15, 16, 18, 21

rotameter 525

rotary vane pumps 520, 521

rotating-table generators 53–54, 55

Rotorod sampler 428, 429, 478

Royco instruments 499

saddle point 132

Safety in Mines Light Scattering Instrument
 (SIMSLIN) 367, 495, 561

Saffman lift force 175, 176

sample equilibrium system (SES) 588

samplers

field experience for respirable aerosol 558–562

line and point sink 71–72

performance characteristics 9–12

rebound of particles from external surfaces of 168

for 'total' and inhalable bioaerosol 486

samplers with circular slit inlet, effect of freestream
 turbulence on 162

samplers for the respirable fraction 359–385

cyclones 368–375

- early samplers 360–364
- horizontal elutriators 364–368
- impactors 376–377
- porous plastic foam filter samplers 378–383
- sampling for 'respirable' fibers 385
- samplers for the thoracic fractions 385–391
 - cyclones 386–387
 - impactors 387–388
 - porous plastic foam filter samplers 388–391
 - vertical elutriators 386, 387
- samples
 - analysis of collected 533–535
 - handling and transport 533–534
- sampling
 - for black smoke 423–425
 - to measure aerosol particle size
 - distribution 317–318
- sampling for aerosols in the ambient
 - atmosphere 417–445
 - black smoke 423–425
 - coarse 'nuisance' aerosols 417–423
 - fine aerosol fractions 432–440
 - meteorological sampling 440–442
 - total suspended particulate 425–432
- sampling for bioaerosols *see* bioaerosol sampling
- sampling for coarse aerosols in workplaces 327–358
 - analysis of performance data for inhalable aerosol samplers 352–354
 - passive aerosol samplers 354–356
 - personal samplers 333–351
 - static (or area) samplers for coarse aerosol fractions 327–333
- sampling for the determination of particle size
 - distribution 447–472
 - aerosol spectrometers 448–451, 452
 - cascade impactors 452–465
 - cascade cyclones 466–467
 - cascade impactors 452–465
 - diffusion batteries 467–469
 - microscopy 469–470
 - parallel impactors 465–466
 - rationale 447–448
- sampling efficiency 359
- sampling for fine aerosol fractions in the ambient
 - atmosphere 432–440
 - PM_{2.5} 435–438, 439
 - PM₁₀ 432–434
 - ultrafine aerosols 439–440
- sampling for fine aerosol fractions in workplaces 359–402
 - PM_{2.5} 391–393
 - respirable fraction 359–385
 - simultaneous sampling for more than one aerosol fraction 395–398
 - thoracic fraction 385–391
 - thoracic particle size selection for fibrous aerosols 393–394
 - very fine aerosols 394–395
- sampling heads, performance of 435
- sampling in perfectly calm air 131–149
 - experimental studies for 135–138
 - qualitative description 131–134
- sampling plane 9
- sampling probes for stack sampling 410–414
 - dilution 413–414
 - null-type probes 411, 412
 - self-compensating probes 412–413
 - standard probes 410–411
 - velocity-sensing probes 411
- sampling for 'respirable' fibers 385
- sampling in stacks and ducts 403–416
 - basic considerations 403–404
 - direct-reading stack-monitoring instruments 415
 - sampling for determining particle size distribution in stacks 414–415
 - sampling probes for stack sampling 410–414
 - stack sampling methods 404–409
- sampling for total suspended particulate in the ambient
 - atmosphere 425–432
 - inhalable aerosol 431–432
 - total aerosol 425–430
- sampling train 407, 408, 409
- sampling tubes
 - deposition losses inside bent 180–181
 - deposition losses inside straight 173–179, 180
 - penetration of particles 187
- sampling for very fine aerosols
 - combustion-related aerosols 394–395
 - ultrafine aerosols 394
- scanning differential mobility analyzer (DMA) 504
- seven-hole personal sampler 335–336, 545
- sharp-cut cyclone (SCC) 438, 439
- short-term exposure limits (STELs) 294
- sieve samplers 480
- silicone grease 533
- SIMGARD sampler 364
- SIMPEDS sampler 373, 387
- SIMSLIN (Safety in Mines Light Scattering Instrument) 367, 495, 561
- single-hole personal sampler 335
 - measured sampling error as function of wind speed for dry fused alumina dust particles of various mean size 171
- single-jet impactor 205–206, 207

- single-stage impactors, inertial samplers 478–481
- Sioutas personal cascade impactor sampler 461, 463
- slip 23–24
- slit-type impactor 479
- slowly moving air 48–50
 - aspiration in 149–154
- smog 320–321
- smoke 4
- smokes, suggested factors to convert personal exposures to 'total' aerosol **545**
- spectrometers *see* aerosol spectrometers
- spherical blunt samplers
 - air flow about 86–89
 - in calm air, aspiration efficiency for 139
 - positions of stagnation 86, 87, 88
 - trajectories of particles near 137
 - see also* blunt samplers; cylindrical blunt samplers; disk-shaped blunt samplers
- spinning disk aerosol generator 51–52
- splash fragments 103
- split-flow electrostatic elutriator 503
- spray 4
- stack sampling
 - cascade impactors for 462, 463
 - sampling probes for 410–414
 - in the UK and elsewhere 409
 - in the USA 405–409
 - determination of particulate matter emissions from stationary sources 407–408
 - determination of PM₁₀ emissions 408
 - sample and velocity traverses for stationary sources 406
 - sample and velocity traverses for stationary sources with small stacks or ducts 407
- stack sampling methods 404–409
- stacks
 - direct-reading stack-monitoring instruments 415
 - and ducts, sampling in 403–416
 - sampling for determining particle size distribution in 414–415
- stagnation 18–19, 86, 87, 88
- standard thermal precipitator (STP) 315, 362, 363, 550
- standards
 - for aerosols 219–308
 - definition 222
 - for bioaerosols 474
 - EN 13205 63–64, 352, 537–538
 - nonhealth-related 233–234
 - processes of standards setting 292
 - 'total' aerosol 248
- static inhalable aerosol samplers
 - 3 Lpm 330–331
 - comparison between theory and experimental results 354
- static samplers for coarse aerosol fractions
 - inhalable aerosol 328–333
 - total aerosol 327–328
- stationary air, streamline patterns 72
- Stokes' law 22
- Stokes number 26, 27
- Stokes regime 22
- stop distance 25
- stratified counting 470
- stream surfaces 16
- streamline patterns 15–16, 72, 131–132
 - for aspirating thin-walled cylindrical sampling tube placed at an angle to the freestream 95, 96
 - aspirating thin-walled cylindrical tube facing the freestream 93, 94
 - aspirating thin-walled tube facing into the wind 73
- Strouhal number 84
 - experiment results for a cylindrical blunt sampler 85
- sub-isokinetic air aspiration rate 97
- sub-isokinetic conditions 74
- sugar tubes 313
- sulfate, summary of results for a number of Canadian cities 595
- sulfate ion 297
- sulfidic nickel, ranking of plant areas/worksites according to the mean level of equivalent exposure to **567**
- super-isokinetic conditions 74
- superconductive quantum interference devices (SQUIDS) 260
- superimposed particle trajectories, for aspirating thin-walled cylindrical sampling tube placed at an angle to the freestream 95, 96
- surface area monitoring 510–511
- suspended particulate matter (SPM) 425
- TAMU inlet 433, 435
- tapered element oscillating microbalance (TEOM^R) 380–381, 508–509, 587
- Tauber pollen collector 478
- TBF50 static sampler 368
- test aerosols
 - choosing type of 50
 - idealised 50–52
- test facilities for aerosol sampler studies 39–50
 - calm air 45–48
 - moving air 40–45
 - slowly moving air 48–50
- thermal precipitation, aerosol particle size selection after aspiration 214–215

- thermal precipitator 315, 362
- thermophoresis 214
- thermophoretic velocity 214
- thick-walled tubes 75–76
- thin-walled aerosol sampling probes facing the wind, mathematical models 109–114
- thin-walled cylindrical samplers in calm air and moving air, comparison between measured and modeled aspiration efficiency 153
- thin-walled cylindrical sampling tubes, aspirating tube facing the wind 97
- thin-walled cylindrical sampling tubes in calm air, aspiration efficiency for 138
- thin-walled sampling tubes
- comparison between measured and modeled aspiration efficiency 152
 - typical particle trajectories 136, 137
- thin-walled slots, and tube entries 73–75
- thin-walled tube samplers 94–116
- isokinetic conditions 95
 - qualitative description of aerosol transport 94–96
- thin-walled tubes
- comparison between measured and modeled aspiration efficiency for thin-walled tubes in calm air 147
 - experimental studies for sampler orientation 104–105
 - facing into the wind
 - axial distributions of air velocity 75, 76
 - deposition losses insides 181–184
 - nature of air flow pattern near entrance to aspirating 75
 - thin-walled tubes facing the freestream, experimental studies 98–104
- thoracic aerosol sampler, performance of the porous foam pre-selector stage of the prototype 436
- thoracic fraction 270, 273, 321
- definition 273
 - samplers for the 385–391
 - see also* extrathoracic fraction
- thoracic particle size selection for fibrous aerosols 393–394
- thoracic and respirable aerosol fractions 273–275
- threshold limit values (TLVs) 293, 294, **295–296**
- Timbrell spectrometer 449–450
- time-weighted average (TWA)
- aerosol concentrations 490
 - particle-number sampling 312
- TM-Digital respirable dust photometer 495–496, 561
- tobacco smoke 4
- tolerance bands 283–284
- 'total' aerosol
- converting personal exposures to 'total' aerosol using 37 mm closed-face plastic cassette sampler **545**
 - personal samplers for coarse aerosol fractions 333–344
 - sampling for total suspended particulate in the ambient atmosphere 425–432
 - sampling in workplaces 327–328
- 'total' aerosol deposition, experimental results for 260–261
- total airborne particulate 317
- 'total' and inhalable aerosol
- comparison between workers' exposures 549
 - gravimetric samplers for 317
 - relationship between 539–549
 - side-by-side comparative studies 540–547
- total suspended particulate (TSP) 237, 248, 321, 425–432
- and black smoke 577–580
 - comparison between results obtained using a high volume sampler and a Japanese 400 Lpm sampler 578
 - experimental results for overall sampling efficiency for samplers for collection of 426
 - experimental results for sampling efficiency of 429
 - results for a number of Canadian cities 595
 - results of side-by-side comparisons of data collected at locations in Berlin for black smoke and **580**
 - results of side-by-side comparisons of PM₁₀, PM₁₅ and TSP at six locations in the US 583
 - sketch of a sampler used for 427
- total suspended particulate (TSP) concentrations, study to examine relationship between PM₁₀ and 584
- total suspended particulate (TSP) sampler inlets 428
- total suspended particulate (TSP) samplers 579
- 'total' to inhalable aerosol measurement, practical impact of changes from 548–549
- tracheobronchial and alveolar aerosol fractions, criteria for 276–278
- tracheobronchial deposition, regional deposition of inhaled aerosols 262–264
- tracheobronchial deposition efficiency, calculated results for 277
- transmission/extinction monitoring 492–494
- transmissometers 494
- TSP *see* total suspended particulate (TSP)
- tube gravitational deposition parameter, dimensionless 182
- turbulence 20–22, 90
- effect on samplers with circular slit inlet 162
 - effects on aspiration 158–162
 - effects on the sampling efficiencies of thin-walled probes under anisokinetic conditions 162

- turbulence (*continued*)
 simulation of 40
 two-dimensional blunt sampling systems 76–80
 two-stage samplers 360
 Tyndallometer, comparison between scattered light intensity and the gravimetric respirable mass concentration obtained using the MRE sampler placed side-by-side 560
 Tyndalloscope 560
- ultimate cascade impactor 454
 ultrafine aerosols
 exposure limit values 304–305
 particle size-selective criteria for 280–281
 sampling for fine aerosol fractions in the ambient atmosphere 439–440
 sampling in the workplace 394
 ultrafine particles, calculated results for deposition efficiency for 282
- velocity potential 20
 velocity-sensing probes, sampling probes for stack sampling 411, 412
 vena contracta 66, 74, 185
 VeroTect instrument 513
 vertical elutriation 194–195
 vertical elutriators 386, 387
 very fine aerosol fractions, particle size-selective criteria for 278–279
 very fine and ultrafine aerosols, results for the deposition of 266–268
 very sharp-cut cyclone (VSCC) 438
 viable organisms 474
 vibrating-orifice aerosol generator (VOAG) 52, 53
 virtual impaction 209–211
 virtual impactor efficiency 209
 viruses 4
 Vitols theory 111
 volume scattering coefficient, relationship between particle size parameter and 492, 493
 volumetric spore trap, 7-day recording 479
 vortex shedding 84, 85
- water condensation particle counter 505
 Wedding inlet, performance of 433, 435
 weighted least squares (WLS) regression 541
 welding fume 4
 well impactor ninety-six 435
 wide-ranging aerosol classifier (WRAC) 465, 466, 520, 593
 wind speeds, simulation of 39–40
 wind tunnel experiments, aspiration characteristics of long cylindrical blunt body placed transverse to freestream with single circular sampling orifice facing into the wind 166, 167
 wind tunnels 40–45, 65, 430
 AEA Technology 44, 45
 Institute of Occupational Medicine 42–43
 low wind speed 49
 miniature 41
 UCLA 43–44
 ultralow wind speed 49, 50
 University of Cincinnati 42
 University of Michigan 45, 46, 49
 working environments, framework for aerosol sampling in 221–235
 workplace aerosol measurement, future of 569–570
 workplace aerosols, classification of 562–568
 workplaces
 bi-modal particle size distribution in 7
 comparisons between optical and gravimetric aerosol samplers 559–562
 field experience with aerosol samplers in 537–573
 sampling for fine aerosol fractions 359–402
 sampling in workplaces 327–358
 WRAC (wide-ranging aerosol classifier) 465, 466, 520, 593
 Wright dust feed 53, 54