

# Index

**Note to the Reader:** Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

## A

- A character
  - in ping character maps, 166
  - in traceroute, 169
- a option
  - in arp, 58–59, 71–72
  - in ipconfig, 62
  - in nbtstat, 80
  - in netstat, 75
  - in telnet, 60
- A option in nbtstat, 80
- aaa option in debug, 156
- AAL (ATM Adaptation Layer), 432
- AAL1 (ATM Adaptation Layer 1), 432
- AAL2 (ATM Adaptation Layer 2), 432
- AAL3/4 (ATM Adaptation Layer 3/4), 433
- AAL5 (ATM Adaptation Layer 5), 433
- AARP (AppleTalk Address Resolution Protocol), 433
- AARP probe packets, 433
- A&B bit signaling, 432
- ABM (Asynchronous Balanced Mode), 433
- ABRs (area border routers)
  - defined, 433
  - in OSPF, 213
- Abstract Syntax Notation One (ASN.1), 436
- accepting routing updates, 204
- access-class command, 227
- Access Control field, 105
- access layer, 433
- access links, 433
- access-list command, 227
- access lists
  - defined, 433
  - extended, 180–182, 181
  - information for, 138–139, 148
- in ISDN, 284–285
- named, 182–183
- in route control, 227
- standard, 178–180, 180
- access methods, 433
- access servers, 433
- accessibility of documentation, 27
- accounting option, 141
- acknowledgments, 433
- ACR (Allowed Cell Rate), 433
- action plans, 229
  - creating and implementing, 13–15
  - defined, 434
  - for Frame Relay, 267–268
  - for serial lines, 258–259
  - summary sheet for, 229–231
- Active Monitors
  - defined, 434
  - in fault recovery, 103
- Address family identifier parameter, 198
- Address field
  - in Frame Relay, 110
  - in PPP packets, 106
  - in RIP packets, 198
  - in SDLC, 107
- address masks, 434
- Address Resolution Protocol (ARP), 175–176
  - defined, 436
  - information for, 149
  - proxy, 176
- Address Translation Gateway (ATG), 437
- addresses
  - IP, 113–116, 114
    - defined, 460
    - obtaining, 172–175, 173
    - in router core dumps, 163
  - learning, 434
  - MAC. *See* MAC addresses
  - mapping, 434
  - in multicast, 466
  - resolution of, 434
  - in Token Ring, 105
- adjacencies
  - defined, 434
  - in OSPF, 210–211, 211
- adjacency option in debug, 156
- adjacency tables, 434
- administrative distances, 434
- administrative weight, 434
- ADSU (ATM Data Service Unit), 434
- advertised routes in EGP, 218
- advertising, 434
- AEP (AppleTalk Echo Protocol), 434
- AFI (Authority and Format Interface), 434
- AFP (AppleTalk Filing Protocol), 434
- Age field, 176
- aggregate bandwidth with switches vs. hubs, 321
- AIP (ATM Interface Processor), 435
- ALERT process in q.931, 293
- Alerts logging level, 161
- algorithms, 435
- alignment errors, 435
- all option in debug, 156
- /all option in ipconfig, 60–62
- all-routes explorer packets, 435
- Allowed Cell Rate (ACR), 433
- alternate mark encoding (AMI), 288
  - defined, 435
  - in ISDN, 288
- AM (Amplitude Modulation), 435
- American National Standards Institute (ANSI), 435
- American Standard Code for Information Interchange (ASCII), 436

**490** AMI (Alternate Mark Inversion) encoding – auxiliary ports

- AMI (Alternate Mark Inversion) encoding
  - defined, 435
  - in ISDN, 288
- amplitude, 435
- Amplitude Modulation (AM), 435
- analog transmissions, 435
- ANSI (American National Standards Institute), 435
- anycasts, 435
- APIs (Application Programming Interfaces), 435
- apple option in debug, 157
- AppleTalk Address Resolution Protocol (AARP), 433
- AppleTalk Control Program (ATCP), 437
- AppleTalk Echo Protocol (AEP), 434
- AppleTalk Filing Protocol (AFP), 434
- AppleTalk protocols, 435
- AppleTalk Remote Access (ARA), 436
- AppleTalk Session Protocol (ASP), 436
- AppleTalk Transaction Protocol (ATP), 99, 437
- AppleTalk Update-based Routing Protocol (AURP), 438
- Application layer
  - defined, 435–436
  - in end-system network configuration tables, 54
  - in OSI model, 93–94, 94
- Application Programming Interfaces (APIs), 435
- Application-Specific Integrated Circuits (ASICs), 436
- apportioned networks, 103
- ARA (AppleTalk Remote Access), 436
- area border routers (ABRs)
  - defined, 433
  - in OSPF, 213
- areas
  - defined, 436
  - in OSPF, 210–213
- ARM (Asynchronous Response Mode), 436
- ARP (Address Resolution Protocol), 175–176
  - defined, 436
  - information for, 149
  - proxy, 176
- arp command for end-systems for network configuration tables, 58–59
- for troubleshooting, 71–73
- arp option in debug, 157–158
- ARPA encapsulation, 142–143, 143
- ASBRs (Autonomous System Border Routers)
  - defined, 436
  - in OSPF, 212–213
  - in routing metrics, 221
- ASCII (American Standard Code for Information Interchange), 436
- ASICs (Application-Specific Integrated Circuits), 436
- ASN.1 (Abstract Syntax Notation One), 436
- ASP (AppleTalk Session Protocol), 436
- ASs (autonomous systems), 438
- AST (Automatic Spanning Tree), 436
- asterisks (\*) as response character in traceroute, 169
- Asynchronous Balanced Mode (ABM), 433
- Asynchronous Response Mode (ARM), 436
- Asynchronous Time-Division Multiplexing (ATDM), 437
- Asynchronous Transfer Mode (ATM), 437
- asynchronous transmissions, 436
- ATCP (AppleTalk Control Program), 437
- ATDM (Asynchronous Time-Division Multiplexing), 437
- ATG (Address Translation Gateway), 437
- ATM (Asynchronous Transfer Mode), 437
- ATM Adaptation Layer (AAL), 432
  - ATM Adaptation Layer 1 (AAL1), 432
  - ATM Adaptation Layer 2 (AAL2), 432
  - ATM Adaptation Layer 3/4 (AAL3/4), 433
  - ATM Adaptation Layer 5 (AAL5), 433
  - ATM ARP servers, 437
  - ATM Data Service Unit (ADSU), 434
  - ATM endpoints, 437
  - ATM Forum, 437
  - ATM Interface Processor (AIP), 435
  - ATM layer, 437
  - ATM Management (ATMM), 437
  - atm option
    - in debug, 157
    - for show interface, 141
  - ATM user-user connections, 437
  - ATP (AppleTalk Transaction Protocol), 99, 437
  - attenuation, 437
  - AURP (AppleTalk Update-based Routing Protocol), 438
  - AURP tunnels, 438
  - authentication passwords in OSPF, 210
  - Authority and Format Interface (AFI), 434
  - authority zones, 438
  - auto duplex, 438
  - automatic call reconnect, 438
  - Automatic Spanning Tree (AST), 436
  - autonomous confederations, 438
  - autonomous switching, 438
  - Autonomous System Border Routers (ASBRs)
    - defined, 436
    - in OSPF, 212–213
    - in routing metrics, 221
  - autonomous systems (ASs), 438
  - autoreconfiguration procedure, 438
  - auxiliary ports, 438

**B**

- B (Bearer) channels
  - defined, 438
  - in ISDN, 110–111, 287
- B8ZS (Binary 8-Zero Substitution), 438
- back ends, 438
- backbones
  - defined, 438
  - in OSPF, 212–213
- backup designated routers (BDRs), 210–211
- Backward-Explicit Congestion Notification (BECN) bit
  - defined, 439
  - in Frame Relay, 264
- bandwidth
  - in default-metric, 223
  - defined, 439
- baseband technology, 439
- baselines, 26–27, 439
- Basic Management setup mode, 439
- Basic Rate Interface (BRI)
  - defined, 440
  - in ISDN, 110, 286–287
- baud, 439
- BDRs (backup designated routers), 210–211
- beacons
  - defined, 439
  - in Token Ring, 104
- Bearer (B) channels
  - defined, 438
  - in ISDN, 110–111, 287
- BECN (Backward-Explicit Congestion Notification) bit
  - defined, 439
  - in Frame Relay, 264
- BGP (Border Gateway Protocol), 217
  - debug commands for, 219–220
  - defined, 439–440
  - eBGP vs. iBGP, 217–218
  - neighbor relationships in, 217
  - problems in, 220
  - show commands for, 218–219
- bgp option in debug, 158
- big buffer pools, 137
- Binary 8-Zero Substitution (B8ZS), 438
- Binary expression in ISL, 351
- binary numbering system, 439
- BIP (Bit Interleaved Parity), 439
- BISDN (Broadband ISDN), 439
- bit-oriented protocols, 439
- blue alarms, 439
- Boot ROM, 440
- boot-up errors in switched environments, 348
- Bootstrap Protocol (BootP), 174
  - defined, 440
  - for LAN connectivity, 174–175
  - troubleshooting, 175
- Border Gateway Protocol. *See* BGP (Border Gateway Protocol)
- border gateways, 440
- bottom-up troubleshooting
  - defined, 440
  - for end-systems, 66–67
- boundaries of dysfunctionality, 9, 440
- BPDU (Bridge Protocol Data Units), 440
- BRI (Basic Rate Interface)
  - defined, 440
  - in ISDN, 110, 286–287
- Bridge bits in ISL, 351
- Bridge Protocol Data Units (BPDUs), 440
- bridges, 320–321
  - defined, 440
  - vs. switches, 321
- Broadband ISDN (BISDN), 439
- broadband transmissions, 440
- broadcast and unknown servers (BUS), 441
- broadcast domains, 320, 441
- broadcast option in debug, 157
- broadcast storms, 441
- broadcasts
  - defined, 440
  - for name resolution, 64
  - with switches vs. hubs, 321
  - in VLANs, 359
- browsing, 441

- buffer pools in HDLC, 252–253
- Buffered command, 162
- buffers
  - displaying, 441
  - settings for, 135–137
- BUS (broadcast and unknown servers), 441
- bus topology, 441
- buses, 441
- BX.25 standard, 441
- bypass mode, 441
- bypass relays, 441
- byte-oriented protocols, 441

**C**

- c option in nbtstat, 80–81
- C/R field, 111
- cable ranges, 441
- cable testers
  - defined, 442
  - working with, 354–355
- cabling issues, 353–354
  - crossover cables for, 355–356, 356
  - multimeters and cable testers for, 354–355
  - TDRs and OTDRs for, 355
- CAC (Connection Admission Control), 442
- cache option in debug, 158
- caches
  - in Internet explorer, 79
  - for name resolution, 64
- calculating routing updates, 203–204, 204
- call admission control, 442
- call priority, 442
- CALL\_PROC process, 293
- call set-up time, 442
- call setup command, 292
- cancel command, 292
- Carrier Detect (CD) signal, 442
- carrier sense, multiple access/collision detection (CSMA/CD)
  - defined, 447
  - in Ethernet, 101
- case studies
  - command summary, 423

**492** cat command – command summaries

- Ethernet problems
  - file transfers, **410–416**, 410, 416
  - telnet, **406–409**, 406
- exam essentials, **422**
- generic router problems
  - 2600 series router, **376–388**, 378
  - ftp, **389–399**, 389
- review questions, **424–429**
- summary, **421–422**
- Token Ring problems, **416–421**, 417
- WAN connectivity
  - problems, **400–405**, 400
- cat command, **63**
- Catalyst system, **322**
  - CLI, **322**
    - hybrid CLI. *See* hybrid mode Catalyst CLI
    - RMON, **346**
- CBR (Constant Bit Rate), **442**
- cbus option in debug, **156**
- CCO (Cisco Connection Online), **442**
- CD (Carrier Detect) signal, **442**
- CDP (Cisco Discovery Protocol)
  - defined, **442**
  - for network topology diagrams, **41–43**
  - working with, **329–332**
- cdp option in debug, **156**
- CDVT (Cell Delay Variation Tolerance), **442**
- CEF (Cisco Express Forwarding), **442**, **444**
- cef option in debug, **158**
- Cell Delay Variation Tolerance (CDVT), **442**
- Cell Error Ratio (CER), **443**
- Cell Loss Priority (CLP), **445**
- Cell Loss Ratio (CLR), **445**
- cell payload scrambling, **443**
- cell relay, **443**
- Cell Transfer Delay (CTD), **447**
- cells, **442**
- Central Office (CO), **445**
- Centrex service, **443**
- CER (Cell Error Ratio), **443**
- cgmp option in debug, **159**
- Challenge Handshake Authentication Protocol (CHAP)
  - defined, **443**
  - in ISDN, **282–284**
- changes
  - documenting, **16**
  - in EIGRP, **205–206**, **206**
  - limiting in troubleshooting, **14**
- Channel Interface Processor (CIP), **443**
- channel option in debug, **157**
- Channel Service Unit (CSU)
  - defined, **447**
  - loopback tests for, **255–256**, **255**
- channelized E1, **443**
- channelized T1, **443**
- CHAP (Challenge Handshake Authentication Protocol)
  - defined, **443**
  - in ISDN, **282–284**
- chat option in debug, **156**
- Checksum field
  - in TCP, **119**
  - in UDP, **120**
- checksums, **443**
- choke packets, **443**
- CIDR (Classless Interdomain Routing), **443**
- CIP (Channel Interface Processor), **443**
- CIR (Committed Information Rate), **443**
- circuit switching, **444**
- Cisco Connection Online (CCO), **442**
- Cisco Discovery Protocol (CDP)
  - defined, **442**
  - for network topology diagrams, **41–43**
  - working with, **329–332**
- Cisco Express Forwarding (CEF), **442**, **444**
- Cisco FRADs (Cisco Frame-Relay Access Devices), **444**
- Cisco IOS software, **444**
- Cisco Technical Assistance Center, **444**
- CiscoFusion architecture, **444**
- CiscoSecure tool, **444**
- CiscoView program, **444**
- CiscoWorks tools, **445**
- Class A networks, **445**
- Class B networks, **445**
- Class C networks, **445**
- classical IP over ATM, **445**
- Classless Interdomain Routing (CIDR), **443**
- classless routing
  - defined, **445**
  - in EIGRP, **202**
- clear commands in CLI, **322**
- clear counters command
  - in file transfers case study, **413**
  - for serial lines, **248**
- clear counters serial command, **244**, **247**
- clear interface bri n command, **295–296**
- clear logging command, **162**
- clear vlan command, **363**
- CLI (command-line interface)
  - defined, **445**
  - hybrid. *See* hybrid mode Catalyst CLI
  - for switched Ethernet, **322**
- clients in VTP, **353**
- CLP (Cell Loss Priority), **445**
- CLR (Cell Loss Ratio), **445**
- CO (Central Office), **445**
- Code field, **119–120**
- collapsed backbones, **445**
- collision domains, **320–321**, **445**
- collisions, **445**
- command frame format, **105–106**, **105**
- command-line interface (CLI)
  - defined, **445**
  - hybrid. *See* hybrid mode Catalyst CLI
  - for switched Ethernet, **322**
- command option in route, **73**
- Command parameter in RIP packets, **198**
- command summaries
  - case studies, **423**
  - end-systems, **83**
  - Frame Relay, **270**
  - ISDN, **310–311**
  - network documentation, **45**

serial lines, 270  
 switched Ethernet, 366–367  
 TCP/IP connectivity  
   problems, 185–186  
 TCP/IP routing protocols,  
   232–235  
 troubleshooting. *See*  
   troubleshooting  
   commands

Committed Information Rate  
 (CIR), 443

Common Part Convergence  
 Sublayer (CPCS), 447

complexity  
   in documentation, 40  
   in EGP, 217  
   in internetworks, 2–3, 3

composite metrics, 445

CONFACK acknowledgments,  
 291

config-register, 397

configurable metrics  
   in EIGRP, 202  
   in IGRP, 201

configuration  
   syntax of, 134–135  
   viewing, 332–337

configuration registers, 446

configuration tables, network.  
*See* network configuration  
 tables

CONFREQ requests, 291

congestion, 446

congestion avoidance, 446

congestion collapse, 446

CONNECT\_ACK process, 293

connect command, 292

CONNECT process, 293

Connection Admission Control  
 (CAC), 442

connection IDs, 446

connection-oriented protocols,  
 95–96, 96  
   defined, 446  
   error control in, 98–99, 98  
   flow control in, 98, 98  
   sequenced data transfer in,  
   96, 97

connectionless protocols  
   defined, 446  
   operation of, 99–100

consistency in documentation,  
 26, 40

Console command, 162

console ports, 446

Constant Bit Rate (CBR), 442

control direct VCC  
   connections, 446

control distribute VCC  
   connections, 446

Control field in PPP packets,  
 106

convergence, 446

Control  
 frame in SDLC, 107

core dumps, 162–164

core layer, 446

costs, 446–447

count to infinity, 447

CPCS (Common Part  
 Convergence Sublayer),  
 447

CPE (Customer Premises  
 Equipment), 447

cpu option in show processes,  
 146–147

cpu utilization, 146–147

crankback technique, 447

CRC (cyclic redundancy check)  
   defined, 447  
   in token frames, 106

created information for buffer  
 pools, 136

Critical logging level, 161

crossover cables, 355–356, 356

CSMA/CD (carrier sense,  
 multiple access/collision  
 detection)  
   defined, 447  
   in Ethernet, 101

CSU (Channel Service Unit)  
   defined, 447  
   loopback tests for,  
   255–256, 255

CTD (Cell Transfer Delay), 447

current router status, 134

custom option for queuing, 140

Customer Premises Equipment  
 (CPE), 447

cut-through sframe switching,  
 447

cyclic redundancy check (CRC)  
   defined, 447  
   in token frames, 106

## D

D channels  
   defined, 448  
   in ISDN, 110–111, 287

-d option  
   in arp, 59, 72  
   in tracer, 70

data communications  
 equipment (DCE)  
   defined, 448  
   in Frame Relay, 109

Data Country Code (DCC),  
 448

data direct VCC connection,  
 448

Data Exchange Interface (DXI),  
 451

Data field  
   in Ethernet frames,  
   102–103  
   in PPP packets, 106  
   in SDLC, 108  
   in token frames, 106

data frame encapsulation, 448

data frame format in Token  
 Ring, 105–106, 105

Data-Link Connection  
 Identifiers (DLCIs)  
   defined, 450  
   in Frame Relay, 109–110,  
   260

data link control layer, 448

Data-Link layer  
   defined, 448  
   in OSI model, 93, 93–94  
   protocols and applications,  
   100  
   Ethernet/IEEE 802.3,  
   101–103, 102  
   Token Ring/IEEE 802.5,  
   103–106, 104–105

data rates in Ethernet, 101

Data Service Units (DSUs)  
   defined, 450–451  
   loopback tests for,  
   255–256, 255

Data Set Ready (DSR) circuit,  
 450

data terminal equipment (DTE)  
   defined, 451

**494** data terminal ready (DTR) circuit – Distance Vector Multicast Routing Protocol

- in Frame Relay, 109
- in HDLC, 254
- data terminal ready (DTR) circuit, 451
- Datagram Delivery Protocol (DDP), 448
- datagrams, 448
- DCC (Data Country Code), 448
- DCE (data communications equipment)
  - defined, 448
  - in Frame Relay, 109
- DDP (Datagram Delivery Protocol), 448
- DDR (dial-on-demand routing), 448
- DE bit, 449
- debug commands, 153–154
  - global, 156
  - for interfaces, 156–157
  - for IP, 158–160
  - limiting output from, 154–155
  - logging, 160–162
  - for protocols, 157–158
  - for RIP, 199
- debug arp command, 176
- debug bri command, 301–302
- debug dialer command, 304
- debug frame-relay events command, 266
- debug frame-relay lmi command, 265–266
- debug ip bgp command, 219
- debug ip bgp dampening command, 219
- debug ip bgp events command, 219
- debug ip bgp keepalives command, 219
- debug ip bgp updates command, 219
- debug ip eigrp command, 207
- debug ip eigrp neighbor command, 207
- debug ip eigrp notifications command, 207
- debug ip eigrp summary command, 207
- debug ip igmp events command, 201
- debug ip igmp transactions
  - command, 201
- debug ip ospf adj command, 214
- debug ip ospf events command, 214
- debug ip ospf flood command, 214
- debug ip ospf lsa-generation command, 214
- debug ip ospf packet command, 214
- debug ip ospf retransmission command, 214
- debug ip ospf spf command, 214–215
- debug ip ospf tree command, 214
- debug ip packet detail
  - command, 154–155
- debug ip packets command, 160
- debug ip rip command, 199
- debug ip rip events command, 199
- debug isdn q921 command, 289–290
- debug isdn q931 command, 292–294, 302–305
- debug ppp authentication command, 282–283
- debug ppp negotiation
  - command, 305–308
- debug ppp packet negotiation
  - command, 308–309
- debug serial interface
  - command, 244, 253–255
- debug vlan packet command, 361
- debugging, 449
- Debugging logging level, 161
- Decline message, 174
- default command for route maps, 226
- default gateways, 194–196, 195
- default-metric command, 223–224
- default routes, 449
- define problem step, 6
- delays, 449
- demarc points, 449
- demodulation, 449
- demultiplexing, 449
- Deny statements, 178–179
- description command, 363
- designated bridges, 449
- designated ports, 449
- Designated Routers (DRs)
  - defined, 449
  - in OSPF, 210–211
- Dest. IP Address field in IP packets, 113
- destination addresses, 449
- Destination field in Ethernet frames, 102
- destination option in route, 73
- Destination Port field
  - in TCP, 119
  - in UDP, 120
- Destination Service Access Points (DSAPs), 450
- DHCP (Dynamic Host Configuration Protocol)
  - defined, 449
  - for LAN connectivity, 174–175
  - troubleshooting, 175
- dhcp option in debug, 156
- dial-on-demand routing (DDR), 448
- dialer-list command, 285
- dialer map command
  - defined, 449
  - in ISDN, 284
- dialer map appletalk command, 284
- dialer map ip command, 284
- dialer option in debug, 156
- dialog in connection-oriented protocols, 95
- Diffusing Update Algorithm (DUAL), 451
- directed broadcasts, 449
- disconnect command, 292
- Discover messages, 174
- discovery mode, 450
- /displaydns option in ipconfig, 61, 78–79
- distance eigrp command, 223
- distance limitations with cabling, 353–354
- distance ospf command, 224
- Distance Vector Multicast Routing Protocol (DVMRP), 451

distance-vector routing  
 algorithm, 450

distribute-list command, 225

distribute lists  
 defined, 450  
 in protocol redistribution,  
 224–225, 225

distributed switching, 450

distribution layer, 450

divide-and-conquer  
 troubleshooting  
 defined, 450  
 for end-systems, 67

divide-by-half troubleshooting  
 defined, 450  
 operation of, 12, 12

DLCIs (Data-Link Connection  
 Identifiers)  
 defined, 450  
 in Frame Relay, 109–110,  
 260

dsw option in debug, 158

DNS (Domain Name System)  
 defined, 450  
 for name resolution, 64

documentation  
 of changes, 16  
 end-system  
 network configuration  
 tables, 54–63, 56,  
 452  
 network topology  
 diagrams, 63–66,  
 65, 452  
 network. *See* network  
 documentation

domain master browsers, 450

domain option in debug, 157

DRAM, displaying, 134

DRs (designated routers)  
 defined, 449  
 in OSPF, 210–211

DS-1 increments, 286

DSAPs (Destination Service  
 Access Points), 450

DSR (Data Set Ready) circuit,  
 450

DSUs (Data Service Units)  
 defined, 450–451  
 loopback tests for,  
 255–256, 255

DTE (data terminal equipment)  
 defined, 451

in Frame Relay, 109  
 in HDLC, 254

DTE LMI term, 262

DTR (data terminal ready)  
 circuit, 451

DUAL (Diffusing Update  
 Algorithm), 451

duplex command, 363

duplicate MAC addresses,  
 343–344

DVMRP (Distance Vector  
 Multicast Routing  
 Protocol), 451

DXI (Data Exchange Interface),  
 451

dynamic entries, 451

Dynamic Host Configuration  
 Protocol (DHCP)  
 defined, 449  
 for LAN connectivity,  
 174–175  
 troubleshooting, 175

dynamic routing  
 defined, 451  
 operation of, 197

dynamic VLANs, 451

## E

E.164 standard, 451

-e option  
 in netstat, 75  
 in telnet, 60

E1 transmissions, 451

EA field, 111

EARL (Encoded Address  
 Resolution Logic) ASICs,  
 451

eBGP (External BGP), 217–218

edge devices, 451–452

EEPROM (Electronically  
 Erasable Programmable  
 Read-Only Memory), 452

EFCI (Explicit Forward  
 Congestion Indication)  
 mode, 452

802.1D standard, 432

802.1s standard, 432

802.1w standard, 432

EIGRP (Enhanced IGRP),  
 202–203

debug commands for,  
 207–208

metrics in, 223

neighbor relationships in,  
 203–206, 204

show commands for, 207

stuck in active problem in,  
 209

eigrp option in debug, 158–159

EIP (Ethernet Interface  
 Processor), 452

ELANs (emulated LANs), 452

ELAP (EtherTalk Link Access  
 Protocol), 452

Electronically Erasable  
 Programmable  
 Read-Only Memory  
 (EEPROM), 452

Emergencies logging level, 161

emulated LANs (ELANs), 452

encapsulation  
 ARPA, 142–143, 143  
 defined, 452  
 HDLC. *See* HDLC  
 (High-level Data Link  
 Control)  
 ISL, 350–352, 350

encapsulation dot1Q  
 command, 352

encapsulation isl command,  
 359

Encapsulation term in Frame  
 Relay, 262

Encoded Address Resolution  
 Logic (EARL) ASICs, 451

encryption, 452

End Delimiter field, 106

end-systems  
 command summary, 83  
 documentation  
 network configuration  
 tables, 54–63, 56,  
 452  
 network topology  
 diagrams, 63–66,  
 65, 452

exam essentials, 82–83

key terms, 84

review questions, 85–90

summary, 81–82

troubleshooting, 66  
 arp for, 71–73  
 ipconfig for, 77–80

**496** Enhanced IGRP. See EIGRP (Enhanced IGRP) – Flag field

- by layer, 66–67
  - nbtstat for, 80–81
  - netstat for, 75–77
  - ping for, 68–69
  - route for, 73–75
  - trace route for, 69–71
  - Enhanced IGRP. *See* EIGRP (Enhanced IGRP)
  - enterprise networks, 453
  - entry option in debug, 156
  - EPROM (Erasable Programmable Read-Only Memory), 453
  - equal-cost load balancing, 202
  - error control
    - in connection-oriented protocols, 98–99, 98
    - defined, 453
  - error option in debug, 159
  - Errors logging level, 161
  - ESFs (Extended Superframes), 453
  - ET (exchange termination) points
    - defined, 463
    - in ISDN, 288
  - /etc/resolv.conf file, 62–63
  - eth\_addr option in arp, 59, 72
  - ethernet-interface option in debug, 157
  - Ethernet Interface Processor (EIP), 452
  - Ethernet networks and media case studies
    - file transfers, 410–416, 410, 416
    - telnet, 406–409, 406
    - defined, 453
  - Ethernet 802.3 protocol, 101–103, 102
  - switched. *See* switched Ethernet
  - ethernet option for show interface, 141
  - EtherTalk Link Access Protocol (ELAP), 452
  - EtherTalk product, 453
  - events, reporting, 327–328
  - exam essentials
    - case studies, 422
    - end-systems, 82–83
    - Frame Relay, 269
    - ISDN, 310
    - network documentation, 44–45
    - problem-solving model, 17
    - protocols, 121
    - serial lines, 269
    - switched Ethernet, 365–366
    - TCP/IP connectivity problems, 184–185
    - TCP/IP routing protocols, 231–232
    - troubleshooting commands, 184–185
  - exception command, 163
  - excess rate, 453
  - exchange termination (ET) points
    - defined, 463
    - in ISDN, 288
  - exclamation points (!) in ping character maps, 166
  - exec command, 163
  - EXEC modes
    - for ping commands, 165–168
    - for traceroute command, 170–172
  - existing neighbors in OSPF, 210
  - exit command, 226
  - expansion, 453
  - expedited delivery, 453
  - Explicit Forward Congestion Indication (EFCI) mode, 452
  - explorer packets, 453
  - extended addressing, 453
  - extended IP access lists, 180–182, 181, 453
  - extended IPX access lists, 453
  - extended keyword, 183
  - extended ping command
    - defined, 454
    - working with, 166–168
  - Extended Setup, 454
  - Extended Superframes (ESFs), 453
  - External BGP (eBGP), 217–218
- 
- F**
- f option
    - in route, 73
    - in telnet, 60
  - fact gathering step, 7
    - defined, 454
    - determine scope, 9–12, 9–12
    - identify symptoms, 7, 8
    - reproduce problem, 8
    - timeline, 8–9
  - failure domains, 454
  - failures information for buffer pools, 137
  - fair option for queuing, 140
  - fair-queue option for show interface, 141
  - fallback mechanisms, 454
  - Fast Ethernet, 454
  - Fast Serial Interface Processor (FSIP), 456
  - fast switching, 454
  - FastEthernet Interface Processor (FEIP), 454
  - fastethernet option in debug, 157
  - fault recovery, 103–104
  - FCS (Frame Check sequence) field
    - in Ethernet frames, 103
    - in PPP packets, 106
    - in SDLC, 108
  - FDDI (Fiber Distributed Data Interface), 454
  - FDM (Frequency-Division Multiplexing), 454
  - feasible successors in EIGRP, 205
  - FECN (Forward Explicit Congestion Notification)
    - defined, 454
    - in Frame Relay, 264
  - FEIP (FastEthernet Interface Processor), 454
  - Fiber Distributed Data Interface (FDDI), 454
  - File Transfer Protocol (FTP) case study for, 389–399, 389
    - defined, 456
  - file transfers case study, 410–416, 410, 416
  - FIP (Forwarding Information Base), 454
  - firewalls, 455
  - Flag field
    - in ISDN frames, 111

- in PPP packets, 106
- in SDLC, 107–108
- in TCP, 119–120
- flash memory, 455
- Flash updates, 201
- flat networks, 455
- FlexWAN module, 357
- flooding, 455
- flow control
  - in connection-oriented protocols, 98, 98
  - defined, 455
- /flushdns option in ipconfig, 60, 80
- formal neighbor relationships, 202
- Forward Explicit Congestion Notification (FECN)
  - defined, 454
  - in Frame Relay, 264
- Forwarding Information Base (FIB), 454
- FRADs (Frame Relay Access Devices), 455
- Fragment Offset field, 113
- fragmentation, 455
- Fragmentation Flags field, 113
- FragmentFree switch type, 455
- fragments, 455
- Frame Check sequence (FCS) field
  - in Ethernet frames, 103
  - in PPP packets, 106
  - in SDLC, 108
- frame errors field, 144
- frame formats in Token Ring, 105–106, 105
- Frame Relay Access Devices (FRADs), 455
- Frame Relay Access Support (FRAS), 456
- Frame Relay bridging, 456
- frame-relay interface-dlci
  - command, 389
- frame-relay map command, 388
- Frame Relay networks, 109–110, 110, 260–261, 260
  - command summary, 270
  - debug commands for, 265–266
  - defined, 455
  - exam essentials, 269

- key terms, 271
- review questions, 272–277
- show commands for, 261–264
  - subinterfaces with, 389
  - summary, 266–269
- frame-relay option in debug, 158
- Frame Relay switching, 456
- Frame Status (FS) field, 106
- frames and frame structures
  - defined, 455
  - in Ethernet, 102–103, 102
  - in Frame Relay, 110
  - in ISDN, 111, 111
  - in SDLC, 107–108, 108
  - in sequenced data transfer, 96
- framing, 456
- FRAS (Frame Relay Access Support), 456
- frequency, 456
- Frequency-Division Multiplexing (FDM), 454
- FS (Frame Status) field, 106
- FSIP (Fast Serial Interface Processor), 456
- FTP (File Transfer Protocol)
  - case study for, 389–399, 389
  - defined, 456
  - ftp option in debug, 159
- FTP server addresses in router core dumps, 163
- full-duplex
  - defined, 456
  - with switches vs. hubs, 321
- full mesh topology, 456

## G

- g option in arp, 58, 72
- gateway option in route, 73
- gateways in TCP/IP, 194–196, 195
- gather facts step, 7
  - determine scope, 9–12, 9–12
  - identify symptoms, 7, 8
  - reproduce problem, 8
  - timeline, 8–9

- generic router problems case studies
  - 2600 series router, 376–388, 378
  - ftp, 389–399, 389
  - WAN connectivity, 400–405, 400
- Generic Routing Encapsulation (GRE), 456
- Get Nearest Server (GNS) packets, 456
- global commands, 132–139, 156
- global protocol classifications
  - connection-oriented protocols, 95–99, 96–98
  - connectionless protocols, 99–100
- GNS (Get Nearest Server) packets, 456
- GRE (Generic Routing Encapsulation), 456
- guard bands, 456

## H

- H channels, 456
- h option in tracer, 70
- H response character in traceroute, 169
- half-duplex
  - defined, 456
  - with switches vs. hubs, 321
- handshakes
  - defined, 456
  - in TCP, 177–178
- hardware, network
  - configuration tables for. *See* network configuration tables
  - debug serial interface for, 253–255HDLC (High-level Data Link Control), 106, 245–246
  - defined, 457
  - show buffers for, 252–253
  - show controllers for, 250–251
  - show interface serial for, 246–250
- Header Checksum field, 113

**498** header options in ping – Interior Gateway Routing Protocol (IGRP)

- header options in ping, 168
  - help command for route maps, 226
  - help option in netstat, 76
  - helper addresses
    - defined, 457
    - for IP addresses, 174–175
  - hierarchical addressing, 457
  - High-level Data Link Control (HDLC). *See* HDLC (High-level Data Link Control)
  - High-Speed Communication Interface (HSCI), 457
  - High-Speed Serial Interface (HSSI), 457
  - HIP (HSSI Interface Processor), 457
  - historical baseline, 26–27
  - hits information for buffer pools, 136
  - holddown state, 457
  - hop counts
    - defined, 457
    - in RIP, 198
  - hops, 457
  - host addresses, 457
  - host option in telnet, 60
  - HOSTS file, 64
  - HSCI (High-Speed Communication Interface), 457
  - HSRP (Hot Standby Routing Protocol), 457
  - HSSI (High-Speed Serial Interface), 457
  - HSSI Interface Processor (HIP), 457
  - hssi option for show interface, 141
  - http option in debug, 159
  - hub go-ahead topologies, 107
  - hubs
    - collision domains on, 320
    - defined, 457
    - vs. switches, 321
  - huge buffer pools, 137
  - hybrid mode Catalyst CLI, 322
    - defined, 457
    - Native command conversions with, 363–364
  - show commands in, 323–324
  - show cam, 342–344
  - show cd, 329–332
  - show config, 332–337
  - show interface, 329
  - show logging, 327–328
  - show logging buffer, 329
  - show mac, 340–342
  - show port, 326–327
  - show spantree, 344
  - show system, 325
  - show test, 338–340
  - show version, 345
  - show vtp, 342
- 
- I-Frame (information frame), 107–108, 108
  - iBGP (internal BGP), 217–218
  - ICD (International Code Designator), 458
  - ICMP (Internet Control Message Protocol)
    - defined, 458
    - operation of, 117–118
  - icmp option in debug, 159
  - Identification field, 113
  - identify symptoms step, 7, 8
  - IEEE (Institute of Electrical and Electronics Engineers), 458
  - IEEE 802.1 specification, 458
  - IEEE 802.1Q specification, 352
  - IEEE 802.3 specification, 101–103, 102, 458
  - IEEE 802.5 specification, 103–106, 104–105, 458
  - if\_addr option in arp, 59, 72
  - IGMP (Internet Group Management Protocol), 458
  - igmp option in debug, 159
  - IGP (Interior Gateway Protocol), 458
  - IGRP (Interior Gateway Routing Protocol)
    - features and operation of, 200–202
    - metrics in, 223
  - igrp option in debug, 159
  - IHL (IP Header Length) field, 113
  - ILMI (Integrated Local Management Interface), 458
  - in-band management, 459
  - incremental routing updates, 202
  - Index field, 351
  - indicator lights, 346, 348
  - inet\_addr option in arp, 58, 72
  - information frame structure, 107–108, 108
  - Informational logging level, 161
  - input queues, 459
  - inside-out troubleshooting
    - defined, 459
    - operation of, 11, 11
  - Institute of Electrical and Electronics Engineers (IEEE), 458
  - insured bursts, 459
  - Integrated Local Management Interface (ILMI), 458
  - Integrated Services Digital Network. *See* ISDN (Integrated Services Digital Network)
  - inter-area routing, 459
  - Inter-Switch Link (ISL)
    - protocol defined, 460
    - for VLANs, 349–352, 350
  - Inter-Switch Link (ISL) routing, 460
  - interface buffers, 459
  - interface option in route, 73
  - interface processors, 459
  - interfaces, 140
    - debugging commands for, 156–157
    - troubleshooting commands for, 139–146
  - Interior Gateway Protocol (IGP), 458
  - Interior Gateway Routing Protocol (IGRP)
    - features and operation of, 200–202
    - metrics in, 223

- intermittent cabling problems, 354
- Internal BGP (iBGP), 217–218
- internal routers in OSPF, 213
- International Code Designator (ICD), 458
- International  
Telecommunication Union  
Telecommunication Standardization Sector (ITU-T), 461
- Internet, 459
- Internet Control Message Protocol (ICMP)  
defined, 458  
operation of, 117–118
- Internet explorer, caches in, 79
- Internet Group Management Protocol (IGMP), 458
- Internet Protocol (IP)  
debug commands for, 158–160  
defined, 459  
packet structure in, 112–113, 114  
traffic statistics for, 151–153
- internets, 459
- Internetwork Packet Exchange (IPX) protocol  
as connectionless protocol, 100  
defined, 460
- internetworking, 459
- internetworks  
complexity of, 2–3, 3  
defined, 459
- intra-area routing, 459
- Inverse ARP, 459–460
- IP (Internet Protocol)  
debug commands for, 158–160  
defined, 460  
packet structure in, 112–113, 114  
traffic statistics for, 151–153
- ip access-list extended  
command, 227
- IP access lists  
extended, 180–182, 181  
named, 182–183  
standard, 178–180, 180
- IP addresses, 113–116, 114  
defined, 460  
obtaining, 172–175, 173  
in router core dumps, 163
- IP Control Program (IPCP), 460
- ip default-network command, 196
- IP Header Length (IHL) field, 113
- ip interface command, 140
- ip option in debug, 158
- ip ospf cost command, 224
- ip ospf priority command, 224
- ip prefix-list command, 225
- IP route tables, information for, 149–150
- IP routed protocols, 112  
ICMP, 117–118  
information for, 149  
IP, 112–117  
TCP, 118–120  
UDP, 120
- ipconfig command, 61  
for default gateways, 195  
for end-system network configuration tables, 60–63  
for end-system troubleshooting, 77–80
- IPCP (IP Control Program), 460
- iphelper-address command, 174
- IPX (Internetwork Packet Exchange) protocol  
as connectionless protocol, 100  
defined, 460
- ipx option in debug, 158
- IPXCP (IPX Control Program), 460
- IPXWAN protocol, 460
- ISDN (Integrated Services Digital Network), 110–111, 111, 280–281  
command summary, 310–311  
debugging commands for, 301–309  
defined, 460  
exam essentials, 310
- key terms, 312
- misconfigured phone  
switches in, 289–294
- misconfigured routers with, 281–286
- physical layer connections  
in, 286–289, 287
- review questions, 313–317
- summary, 309
- troubleshooting commands  
for, 294–301, 294
- isdn autodetect command, 294
- isdn switch-type command, 293
- isis option in debug, 158
- ISL (Inter-Switch Link) protocol  
defined, 460  
for VLANs, 349–352, 350
- ISL (Inter-Switch Link) routing, 460
- ISL CRC field, 352
- ISL multicast address, 351
- isochronous transmissions, 461
- iterations step, 16
- ITU-T (International Telecommunication Union Telecommunication Standardization Sector), 461
- 
- ## J
- j option in tracert, 70
- 
- ## K
- KA IE (Keepalive Information Element) field, 265
- key terms  
end-systems, 84  
Frame Relay, 271  
ISDN, 312  
network documentation, 46  
problem-solving model, 18  
protocols, 122  
serial lines, 271  
switched Ethernet, 368

**500** -l option in telnet – LSAs (link-state advertisements)

- TCP/IP connectivity problems, 186
  - TCP/IP routing protocols, 235
- 
- L**
- l option in telnet, 60
  - LAN connectivity
    - ARP in, 175–176
    - IP addresses in, 172–175, 173
    - sample TCP connection, 177–178, 177
  - LAN Emulation (LANE), 461
  - LAN Emulation Address Resolution Protocol (LE ARP), 462
  - LAN Emulation Client (LEC), 462
  - LAN Emulation Configuration Server (LECS), 462
  - LAN Emulation Network-to-Network Interface (LNNI), 463
  - LAN Emulation Server (LES), 462
  - LAN Emulation User-to-Network Interface (LUNI), 463
  - LAN switches, 461
  - LANE (LAN Emulation), 461
  - LAP (Link Access Procedure), 111
  - LAPB (Link Accessed Procedure, Balanced), 461
  - LAPD (Link Access Procedure on the D channel), 289, 461
  - large buffer pools, 137
  - latency, 461
  - Layer 1 S/T interface
    - defined, 461
    - in ISDN, 288–289
  - Layer 2 protocols, 100
    - Ethernet/IEEE 802.3, 101–103, 102
    - for ISDN, 289–291
    - Token Ring/IEEE 802.5, 103–106, 104–105
  - Layer 3 and 4 protocols. *See* IP routed protocols
  - switches, 461
  - troubleshooting for ISDN, 292–293
  - Layer 7 information in network configuration tables, 54
  - layered architecture, 461
  - LCP (Link Control Protocol)
    - defined, 462
    - for PPP, 290–291
  - LDNs (Local Directory Numbers), 281–282
  - LE ARP (LAN Emulation Address Resolution Protocol), 462
  - leaky buckets, 462
  - learning addresses, 434
  - learning bridges, 462
  - learning routes, 218
  - leased lines, 462
  - LEC (LAN Emulation Client), 462
  - LECS (LAN Emulation Configuration Server), 462
  - LEDs, 346, 348
  - Length field
    - in ISL, 351
    - in UDP, 120
  - LES (LAN Emulation Server), 462
  - levels, logging, 161–162
  - limiting debug output, 154–155
  - line termination (LT) points
    - defined, 463
    - in ISDN, 288
  - Link Access Procedure (LAP), 111
  - Link Access Procedure on the D channel (LAPD), 289, 461
  - Link Accessed Procedure, Balanced (LAPB), 461
  - Link Control Protocol (LCP)
    - defined, 462
    - for PPP, 290–291
  - link-state advertisements (LSAs), 463
  - link-state routing algorithm, 462
  - LLAP (LocalTalk Link Access Protocol), 462
  - LLC (Logical Link Control), 463
  - LMHOSTS file, 64
  - LMI (Local Management Interface)
    - defined, 463
    - in Frame Relay, 261–262
  - LMI DLCI term, 262
  - LMI enq recvd term, 262
  - LMI enq sent term, 262
  - LMI stat recvd term, 262
  - LMI stat sent term, 262
  - LMI type term, 262
  - LMI upd recvd term, 262
  - LMI upd sent term, 262
  - LNNI (LAN Emulation Network-to-Network Interface), 463
  - load balancing
    - in EIGRP, 202
    - in IGRP, 201
  - lobe media checks, 104
  - Local Directory Numbers (LDNs), 281–282
  - local explorer packets, 463
  - local loops
    - defined, 463
    - in ISDN, 287
  - Local Management Interface (LMI)
    - defined, 463
    - in Frame Relay, 261–262
  - LocalTalk protocol, 463
  - LocalTalk Link Access Protocol (LLAP), 462
  - logging commands, 160–162
  - Logical Link Control (LLC), 463
  - loop topologies, 107
  - loopback tests
    - for CSU/DSU, 255–256, 255
    - defined, 463
    - in HDLC, 248, 255
  - Loose option in ping headers, 168
  - Loose source routing prompt in traceroute, 172
  - lost carrier field, 144
  - LSAs (link-state advertisements), 463

LT (line termination) points  
 defined, 463  
 in ISDN, 288  
 LUNI (LAN Emulation  
 User-to-Network  
 Interface), 463

## M

- M character  
 in ping character maps, 166  
 in traceroute, 169  
 MAC (Media Access Control)  
 layer, 463  
 mac-accounting option for  
 show interface, 141  
 mac-address-table aging time  
 command, 363  
 MAC addresses  
 in ARP, 176  
 defined, 463  
 duplicate, 343–344  
 mapping to IP addresses, 58  
 port relationships with,  
 340–344  
 MacIP protocol, 464  
 maintaining documentation, 27  
 man command, 58  
 Management Information Base  
 (MIB), 465  
 Manchester encoding, 464  
 MANs (metropolitan area  
 networks), 464  
 MASK option in route, 73  
 master browsers, 464  
 match command, 226  
 MAUs (multistation access  
 units), 104  
 max allowed setting, 136  
 max-free field, 137  
 Maximum Burst Size (MBS), 464  
 maximum bursts, 464  
 Maximum Cell Transfer Delay  
 (MCTD), 464–465  
 maximum rate, 464  
 maximum segment lengths in  
 Ethernet, 101  
 maximum transmission units  
 (MTUs)  
 in default-metric, 223  
 defined, 466  
 Maximum TTL prompt in  
 traceroute, 172  
 mbgp option in debug, 159  
 MBONE (Multicast  
 Backbone), 464  
 MBS (Maximum Burst Size),  
 464  
 mcache option in debug, 159  
 MCR (Minimum Cell Rate),  
 464  
 MCTD (Maximum Cell  
 Transfer Delay), 464–465  
 mds option in debug, 159  
 Media Access Control (MAC)  
 layer, 463  
 media in Ethernet, 101  
 memory option in show  
 processes, 147  
 memory problems, 139  
 messages in debugging, 153  
 METRIC option in route, 73  
 Metric parameter in RIP  
 packets, 198  
 metrics  
 defined, 465  
 in EIGRP, 202  
 in IGRP, 201  
 in protocol redistribution,  
 221–224  
 metropolitan area networks  
 (MANs), 464  
 MIB (Management  
 Information Base), 465  
 middle buffer pools, 137  
 min allowed setting, 136  
 min-free field, 137  
 mineseen data, 255  
 Minimum Cell Rate (MCR),  
 464  
 Minimum TTL prompt in  
 traceroute, 172  
 MIP (Multichannel Interface  
 Processor), 465  
 mips (millions of instructions  
 per second), 465  
 misconfigured phone switches  
 in ISDN, 289–294  
 misconfigured routers in ISDN,  
 281–286  
 misses information for buffer  
 pools, 136  
 mixed media support with  
 switches vs. hubs, 321  
 MLP (Multilink PPP), 465  
 MMP (Multichassis Multilink  
 PPP), 465  
 mobile option in debug, 159  
 modem eliminators, 465  
 modems, 465  
 modulation, 465  
 Monitor command, 162  
 monitor session command, 363  
 MOSPF (Multicast Open  
 Shortest Path First), 465  
 mpacket option in debug, 159  
 MPLS (Multiprotocol Label  
 Switching), 466  
 MPOA (Multiprotocol over  
 ATM), 465  
 mrouting option in debug, 159  
 msdp option in debug, 159  
 msec response character, 169  
 MSFC (Multilayer Switch  
 Feature Card)  
 defined, 466  
 working with, 357–359  
 mtag option in debug, 159  
 MTUs (maximum transmission  
 units)  
 in default-metric, 223  
 defined, 466  
 multicast  
 addressing in, 466  
 defined, 460, 466  
 Multicast Backbone  
 (MBONE), 464  
 Multicast Open Shortest Path  
 First (MOSPF), 465  
 multicast send VCC  
 connection, 466  
 Multichannel Interface  
 Processor (MIP), 465  
 Multichassis Multilink PPP  
 (MMP), 465  
 Multilayer Switch Feature Card  
 (MSFC)  
 defined, 466  
 working with, 357–359  
 multilayer switches, 466  
 Multilink PPP (MLP), 465  
 multimeters  
 for cabling, 354–355  
 defined, 466  
 multiplexing, 466  
 multipoint topologies, 107

## 502 Multiprotocol Label Switching (MPLS) – NVRAM (Non-Volatile RAM)

Multiprotocol Label Switching (MPLS), 466  
 Multiprotocol over ATM (MPOA), 465  
 multistation access units (MAUs), 104  
 myseq data, 254–255

### N

N in ping character maps, 166  
 -n option  
   in nbtstat, 80  
   in netstat, 76  
 -N if\_addr option in arp, 58, 72  
 NAKs (negative acknowledgments), 466  
 Name Binding Protocol (NBP), 466–467  
 name-resolution caches in Internet explorer, 79  
 name resolution in Windows, 64  
 named access lists, 182–183  
 NAT (Network Address Translation), 466  
 nat option in debug, 159  
 Native mode CLI, 322  
   defined, 466  
   Hybrid command conversions with, 363–364  
 NBP (Name Binding Protocol), 466–467  
 nbtstat command, 80–81  
 NCPs (Network Control Protocols), 106, 291  
 negative acknowledgments (NAKs), 466  
 neighbor relationships  
   in BGP, 217  
   in EIGRP, 203–206, 204  
   in OSPF, 210–211, 211  
   in Token Ring, 105  
 neighbor statement in RIP, 200  
 neighbor tables in EIGRP, 203  
 neighboring routers, 467  
 NetBEUI (NetBIOS Extended User Interface), 467  
 NetBIOS (Network Basic Input/Output System), 467  
 Netflow switching, 467  
 netmask option in route, 73  
 netstat command, 75–77  
 NetView product, 467  
 NetWare Link Services Protocol (NLSP), 468  
 NetWare operating system, 467  
 Network Address Translation (NAT), 466  
 network addresses, 467  
 network analyzers, 467  
 Network Basic Input/Output System (NetBIOS), 467  
 network configuration tables, 27–28  
   defined, 467  
   end-system, 54–63, 56  
   for routers, 29–33, 29  
   for switches, 33–38, 34  
 Network Control Protocols (NCPs), 106, 291  
 network documentation, 26  
   baselines, 26–27  
   command summary, 45  
   exam essentials, 44–45  
   key terms, 46  
   network configuration tables. *See* network configuration tables  
   network topology diagrams. *See* network topology diagrams  
   review questions, 47–52  
   summary, 44  
 Network File System (NFS), 468  
 network interface cards (NICs), 468  
 Network layer  
   defined, 467  
   in OSI model, 93, 93–94  
 Network Management Processor (NMP), 468  
 Network Monitor, 467  
 Network Neighborhood, 468  
 network termination 1 (NT1)  
   devices, 288, 469  
 network topology  
   diagramsnetwork termination 2 (NT2)  
   devices, 288, 469  
   components of, 38–39  
   creating, 39–43, 40–42  
   defined, 468  
   end-system documentation, 63–66, 65  
 next-hop attribute in BGP, 220  
 Next Hop Resolution Protocol (NHRP), 468  
 Next Hop Server (NHS), 468  
 NFS (Network File System), 468  
 NHRP (Next Hop Resolution Protocol), 468  
 NHS (Next Hop Server), 468  
 NICs (network interface cards), 468  
 NLSP (NetWare Link Services Protocol), 468  
 NMP (Network Management Processor), 468  
 no carrier field, 144  
 no command for route maps, 226  
 no ip forward-protocol command, 175  
 no ip proxy-arp command, 176  
 no memory field, 137  
 no shut command, 142  
 no vlan command, 363  
 node addresses, 468  
 nodes in SDLC, 107  
 non-stub areas, 468  
 Non-Volatile RAM (NVRAM), 469  
 nondesignated ports, 468  
 Not So Stubby Areas (NSSAs), 212  
 Notifications logging level, 161  
 Novell IPX protocol, 100  
 Novell SPX protocol, 99  
 NRZ (Nonreturn to Zero) encoding scheme, 469  
 NRZI (Nonreturn to Zero Inverted) encoding scheme, 469  
 nslookup command, 168, 170  
 NSSAs (Not So Stubby Areas), 212  
 NT devices, 111  
 NT1 (network termination 1), 288, 469  
 NT2 (network termination 2), 288, 469  
 Numeric display prompt in traceroute, 172  
 NVRAM (Non-Volatile RAM), 469

**O**

-o option in netstat, 76  
 objectives in documentation, 27  
 observations in case studies  
   2600 series router, 377–383, 386–387  
   file transfers, 410–413  
   ftp, 390–396  
   telnet, 406–408  
   Token Ring, 417–420  
   WAN connectivity, 400–403  
 observe results step, 15–16, 469  
 OCs (Optical Carriers), 469  
 octets, 469  
 Offer messages, 174  
 Offset field, 119  
 100BaseT standard, 432  
 100BaseTX standard, 432  
 1000Base-T standard, 432  
 ones density method, 469  
 Open Shortest Path First. *See* OSPF (Open Shortest Path First)  
 Open Systems Interconnection (OSI) reference model  
   defined, 469  
   layers in, 92–94, 93–94  
 opening TAC cases, 421  
 Optical Carriers (OCs), 469  
 optical TDRs (OTDRs), 355  
 optimum switching, 469  
 Option field in TCP, 119  
 Options field in IP packets, 113  
 Organization IDs, 351  
 Organizationally Unique Identifiers (OUIs), 470  
 Original frame field, 352  
 OSI reference model  
   defined, 469  
   layers in, 92–94, 93–94  
 OSPF (Open Shortest Path First), 209–210  
   areas in, 210–213  
   debug commands for, 214–216  
   defined, 470  
   metrics in, 224

neighbor and adjacency  
   formation in, 210–211, 211  
   problems in, 216  
   show commands for, 213–214  
 ospf option in debug, 159  
 OTDRs (optical TDRs), 355  
 OUIs (Organizationally Unique Identifiers), 470  
 out-of-band management, 470  
 out-of-band signaling, 470  
 output queues, 470  
 outside-in troubleshooting  
   defined, 470  
   operation of, 10, 10  
 overruns field, 144

**P**

P character  
   in ping character maps, 166  
   in traceroute, 169  
 P (Port Unreachable) messages, 169  
 P/F (Poll Final) bit, 107  
 -p option  
   in netstat, 76  
   in route, 73  
 Packet Internet groper program. *See* ping (Packet Internet groper) program  
 Packet Level Protocol (PLP), 471  
 packet option in debug, 159  
 Packet Switch Exchange (PSE), 474  
 packet-switched networks (PSNs), 474  
 packet switches, 470  
 packet switching, 470  
 packets  
   defined, 470  
   flow verification, 155  
   in IP, 112–113, 114  
   in PPP, 106  
   in RIP, 198  
   in sequenced data transfer, 96  
   in TCP, 118–120  
 PAP (Password Authentication Protocol), 470–471  
 parameters in  
   connection-oriented protocols, 95  
 parity checking, 471  
 partial mesh topology, 471  
 passive-interface command, 200  
 Password Authentication Protocol (PAP), 470–471  
 passwords in OSPF, 210  
 path determination, 471  
 PCR (Peak Cell Rate), 471  
 PDNs (Public Data Networks), 471  
 PDUs (protocol data units)  
   defined, 472  
   in sequenced data transfer, 96, 97  
 Peak Cell Rate (PCR), 471  
 peer option in debug, 159  
 periods (.) in ping character maps, 166  
 permanent buffer setting, 136  
 permanent field for buffer pools, 137  
 permanent virtual circuits (PVCs)  
   defined, 474  
   in Frame Relay, 260  
 permanent virtual paths (PVPs), 474  
 Permit statements, 178–179  
 PGP (Pretty Good Privacy), 471  
 phone switches in ISDN, 289–294  
 physical insertion in Token Ring, 105  
 Physical layer  
   defined, 471  
   in ISDN, 286–289, 287  
   in OSI model, 92, 93–94  
 physical test equipment, 471  
 pim option in debug, 159  
 ping (Packet Internet groper) program  
   in case studies  
     ftp, 395, 399  
     router, 386  
     telnet, 406  
   for default gateways, 196  
   defined, 471

**504** pipes – PTSP (PNNI Topology State Packet)

- for end-system network configuration tables, 56–58
- for end-system troubleshooting, 68–69
- EXEC modes for
  - privileged, 166–168
  - user, 165–166
- for ISDN, 295
- pipes, 95
- pleisochronous transmissions, 471
- PLP (Packet Level Protocol), 471
- PNNI (Private Network-Network Interface), 472
- PNNI Topology State Packet (PTSP), 474
- point-to-multipoint connections, 472
- point-to-point connections, 472
- Point-to-point Protocol (PPP), 106, 106
  - defined, 472
  - for ISDN, 285–286, 290–291
  - in SDLC, 107
- Points of Presence (POPs), 472
- poison reverse updates
  - defined, 472
  - in IGRP, 201
- policy control in VLANs, 359
- policy option in debug, 160
- Poll Final (P/F) bit, 107
- polling, 472
- POP (Post Office Protocol), 472
- POPs (Points of Presence), 472
- port mirroring, 346, 357, 472
- Port number prompt in traceroute, 172
- port option in telnet, 60
- port security, 472
- Port Unreachable (P) messages, 169
- ports
  - information on, 326–327
  - MAC relationships with, 340–344
- possibilities step in
  - problem-solving, 13
- Post Office Protocol (POP), 472
- PPP (Point-to-point Protocol), 106, 106
  - defined, 472
  - for ISDN, 285–286, 290–291
  - in SDLC, 107
- ppp auth command, 282
- ppp authentication chap callin command, 284
- ppp option in debug, 158
- Preamble field, 102
- prefix lists
  - defined, 472
  - in protocol redistribution, 224–225
- Presentation layer
  - defined, 473
  - in OSI model, 93, 93–94
- Pretty Good Privacy (PGP), 471
- PRI (Primary Rate Interface)
  - defined, 473
  - in ISDN, 110–111, 286
- primary nodes
  - defined, 473
  - in SDLC, 107
- print option in route, 74–75
- priority 1 situation, 473
- priority 2 situation, 473
- priority 3 situation, 473
- priority 4 situation, 473
- priority queuing, 140, 473
- Private Network-Network Interface (PNNI), 472
- privileged EXEC mode
  - for ping commands, 166–168
  - for traceroute command, 171–172
- Probe count prompt in traceroute, 172
- problem definition step
  - defined, 473
  - operation of, 6
- problem-solving model, 4–6, 4–5
  - action plans, 13–15
  - define problem step, 6
  - exam essentials, 17
  - gather facts step, 7–12, 8–12
  - iterations step, 16
  - key terms, 18
  - observe results step, 15–16
  - possibilities step, 13
  - review questions, 19–24
  - summary, 17
- process commands, 146–147
- process switching, 473
- PROM (programmable read-only memory), 473
- propagation delays, 473
- protocol analyzers, 473
- protocol data units (PDUs)
  - defined, 472
  - in sequenced data transfer, 96, 97
- Protocol field, 106
- protocol parameters, 474
- protocol stacks, 474
- protocols
  - connection-oriented, 95–99, 96–98
  - debug commands for, 157–158
  - defined, 473
  - exam essentials, 121
  - Frame Relay, 109–110, 110
  - ICMP, 117–118
  - IP routed. *See* IP routed protocols
  - ISDN, 110–111, 111
  - key terms, 122
  - Layer 2, 100–106, 102, 104–105
  - and OSI Reference Model, 92–94, 93–94
  - PPP, 106, 106
  - review questions, 123–128
  - SDLC, 106–108, 108
  - summary, 121
  - proxy ARP, 176, 474
  - PSE (Packet Switch Exchange), 474
  - PSNs (packet-switched networks), 474
  - PSTNs (Public Switched Telephone Networks), 474
  - PTSP (PNNI Topology State Packet), 474

Public Data Networks (PDNs),  
471  
PVCs (permanent virtual  
circuits)  
defined, 474  
in Frame Relay, 260  
PVP tunneling, 474  
PVPs (permanent virtual  
paths), 474

## Q

Q character  
in ping character maps, 166  
in traceroute, 169  
q.921 protocol  
defined, 474  
for ISDN, 289–290  
q.931 specification  
defined, 474  
for ISDN, 292–293  
QoS (Quality of Service), 474  
question marks (?)  
in ping character maps, 166  
in traceroute, 169  
queues  
configuration and  
operation of, 140–141  
defined, 474  
in EIGRP, 203  
interface command for, 140

## R

-r option  
in nbtstat, 80  
in netstat, 76  
in ping, 68  
-R option in nbtstat, 80  
R reference points  
defined, 474  
in ISDN, 288  
RAM (random access  
memory), 474  
RARP (Reverse Address  
Resolution Protocol), 475  
rate-limit option for show  
interface, 141  
rate queues, 475  
RCP (Remote Copy Protocol),  
475

RCP addresses in router core  
dumps, 163  
reachability in ICMP, 117  
read-only memory (ROM), 476  
Record option in ping headers,  
168  
Record prompt in traceroute,  
172  
Recurring Paths, 346  
red alarms, 475  
redirects in ICMP, 117  
redistribution of routing  
protocols, 221  
defined, 475  
distribute lists in, 224–225,  
225  
route maps in, 226–227  
routing metrics in, 221–224  
redundancy, 475  
reference points in ISDN, 288  
/registerdns option in ipconfig,  
60–61  
release command for ISDN,  
292  
/release option in ipconfig, 60,  
77  
reload command, 405  
reloads, 475  
remote configuration, 405  
Remote Monitoring (RMON)  
defined, 475  
working with, 346  
/renew option in ipconfig, 60,  
77  
Report Type Information  
Element (RT IE) field, 265  
reproducing problems, 8  
request initialization, 105  
Request to Send (RTS) signal,  
477  
required resources in  
connection-oriented  
protocols, 95  
resets field, 144  
resolv.conf file, 62–63  
Reverse Address Resolution  
Protocol (RARP), 475  
review questions  
case studies, 424–429  
end-systems, 85–90  
Frame Relay, 272–277  
ISDN, 313–317  
network documentation,  
47–52  
problem-solving model,  
19–24  
protocols, 123–128  
serial lines, 272–277  
switched Ethernet, 369–374  
TCP/IP connectivity  
problems, 187–192  
TCP/IP routing protocols,  
236–242  
troubleshooting commands,  
187–192  
.rhosts files, 163  
RIF (Routing Information  
Field), 475  
ring insertion in Token Ring,  
104–105  
ring topology, 475  
rings, 475  
RIP (Routing Information  
Protocol), 198–199, 198  
debug commands for, 199  
defined, 475  
problems in, 200  
RIP-1 and RIP-2, 199  
show commands for, 199  
rip option in debug, 160  
RJ connectors  
defined, 475  
in ISDN, 288  
RMON (Remote Monitoring)  
defined, 475  
working with, 346  
ROM (read-only memory), 476  
root bridges, 476  
route command, 73–75  
route-map command, 226  
route maps, 226–227  
route poisoning, 476  
Route Processors (RPs), 477  
route state information,  
204–205  
route summarization, 476  
Route/Switch Processors  
(RSPs), 477  
route tables  
defined, 477  
information, 149–150  
route tagging, 202  
routed protocols  
defined, 476  
IP. *See* IP routed protocols  
routers  
case studies

## 506 routing – set-based devices

- 2600 series router,
    - 376–388, 378
    - ftp, 389–399, 389
    - WAN connectivity,
      - 400–405, 400
  - core dumps for, 162–164
  - defined, 476
  - in ICMP, 117
  - network configuration
    - tables for, 29–33, 29
  - in OSPF, 210
  - VLANs across, 359–363
  - routing
    - defined, 476
    - in EIGRP, 202–205, 204, 206
    - in VLANs, 360
  - routing domains, 476
  - Routing Information Field (RIF), 475
  - Routing Information Protocol. *See* RIP (Routing Information Protocol)
  - routing metrics
    - defined, 476
    - in redistribution of routing protocols, 221–224
  - routing option in debug, 160
  - routing protocols, 477
  - Routing Table Management Protocol (RTMP), 477
  - RPs (Route Processors), 477
  - RR option in nbtstat, 81
  - RSPs (Route/Switch Processors), 477
  - rsvp option in debug, 160
  - RT IE (Report Type Information Element)
    - field, 265
  - RTMP (Routing Table Management Protocol), 477
  - RTS (Request to Send) signal, 477
  - running-config command, 134–135
- 
- S**
- s option
    - in arp, 59, 72
  - in nbtstat, 80
  - in netstat, 76
  - in ping, 68–69
  - S option in nbtstat, 80
  - S reference points
    - defined, 477
    - in ISDN, 288
  - S/T reference points
    - defined, 477
    - in ISDN, 288
  - SABME (Set Asynchronous Balanced Mode Extended)
    - message, 290
  - SAGE (Synergy Advanced Gate-Array Engine) chips, 477
  - SAINT (Synergy Advanced Interface and Network Termination), 477
  - SAMBA (Synergy Advanced Multipurpose Bus Arbiter) ASICs, 477
  - sampling rates, 477
  - SAP (Service Advertising Protocol), 477
  - SAPIs (service access point identifiers), 111, 290
  - SAPs (Service Access Points), 477
  - scope
    - of network documentation, 26
    - of problem determination, 9–12, 9–12
  - SCR (Sustainable Cell Rate), 478
  - SDLC (Synchronous Data Link Control)
    - defined, 478
    - working with, 106–108, 108
  - secondary nodes
    - defined, 478
    - in SDLC, 107
  - security option in debug, 160
  - seed devices, 478
  - seed routers, 478
  - segment lengths in Ethernet, 101
  - Send Sequence Number field, 108
  - Sequence Number field, 119
  - sequenced data transfer
    - in connection-oriented protocols, 96, 97
    - defined, 478
  - Sequenced Packet Exchange (SPX) protocol
    - as connection-oriented protocol, 99
    - defined, 481
  - Serial Line Internet Protocol (SLIP), 479
  - serial lines, 244
    - command summary, 270
    - CSU/DSU loopback tests in, 255–256, 255
    - exam essentials, 269
    - HDLC. *See* HDLC (High-level Data Link Control)
    - key terms, 271
    - review questions, 272–277
    - summary, 257–259, 268–269
  - serial option
    - in debug, 157
    - in show interface, 141
  - Serial Tunnel (STUN), 482
  - servers
    - defined, 478
    - in VTP, 352
  - service access point identifiers (SAPIs), 111, 290
  - Service Access Points (SAPs), 477
  - Service Advertising Protocol (SAP), 477
  - Service Profile Identifiers (SPIDs)
    - defined, 480
    - for ISDN, 281–282
  - service timestamps command, 153
  - service timestamps debug
    - datetime msec command, 301
  - session command, 357
  - Session layer
    - defined, 478
    - in OSI model, 93, 93–94
  - Set Asynchronous Balanced Mode Extended (SABME)
    - message, 290
  - set-based devices, 478

set command for route maps – show ip route command **507**

- set command for route maps, 226
- set commands in CLI, 322
- set cam agingtime command, 363
- set port duplex command, 363
- set port speed command, 363
  - set port name command, 363
- set span command, 363
- set span enable, 357
- set spantree command, 363
- set vlan command, 364
- /setclassid option in ipconfig, 61
- setup mode, 478
- SETUP process, 293
- SFs (super frames), 478
- shielded twisted-pair (STP), 482
- Shortest Path First (SPF) algorithm, 480
- show commands
  - in CLI, 323–324
  - frequently used, 130–132
  - for RIP, 199
- show access-lists command, 138–139
- show arp command, 143, 175–176, 407–409
- show buffers command, 135–137, 244, 252–253
- show cam command, 340, 342–344
- show cam dynamic command, 364
- show cdp command, 329–332
- show cdp neighbor command for network topology diagrams, 41–42
  - in WAN connectivity case study, 402–403
- show cdp neighbor detail command for network topology diagrams, 42–43
  - report output from, 330
- show config command, 134, 332–337
- show config all command, 332
- show controller bri command, 298
  - show controllers command, 250–251
  - show controllers serial command, 244
  - show controllers serial1 command, 250–251
  - show dhcp server command, 175
  - show diagnostic command, 364
  - show dialer command, 300
  - show flash command, 396
  - show frame-relay lmi command, 263
  - show frame-relay map command, 264, 387–388
  - show frame-relay pvc command, 263–264, 386
  - show interface command, 139–143, 329
    - in case studies
      - 2600 series router, 379–385
      - file transfers, 410–416
      - ftp, 394
      - telnet, 406
      - Token Ring, 417–419
    - WAN connectivity, 401
    - in Frame Relay, 261
    - vs. show port, 364
    - for switch network configuration tables, 36
    - for VLANs, 362
  - show interface bri n command, 296–297
  - show interface bri n 12 command, 297
  - show interface serial command, 244, 246–250
  - show interface serial0 command, 245
  - show ip access-list command, 148, 179
  - show ip arp command, 149
  - show ip bgp command, 218
  - show ip bgp neighbors command, 218–219
  - show ip bgp network command, 218
  - show ip bgp peer-group command, 219
  - show ip bgp summary command, 219
  - show ip eigrp events command, 207, 209
  - show ip eigrp interfaces command, 207
  - show ip eigrp neighbors command, 207–208, 404
  - show ip eigrp topology command, 207–208
  - show ip eigrp traffic command, 207, 209
  - show ip interface command, 145–146
    - for access lists, 179–180
    - for BGP, 219
    - for OSPF, 214
    - for RIP, 199
    - for router network configuration tables, 32
    - in WAN connectivity case study, 404
  - show ip interface brief command, 30–31
  - show ip interface e0/0 command, 31–33
  - show ip ospf command, 213
  - show ip ospf border-routers command, 213
  - show ip ospf database command, 213
  - show ip ospf interface command, 214
  - show ip ospf neighbor command, 214
  - show ip ospf process-id command, 213
  - show ip ospf request-list command, 214
  - show ip ospf retransmission list command, 214
  - show ip ospf summary-address command, 214
  - show ip ospf virtual-links command, 214
  - show ip protocols command, 31–32, 149
  - show ip route command, 149–150
    - for BGP, 219
    - for default gateways, 195–196
    - for EIGRP, 207

**508** show ip route bgp command – Source IP Address field

- in ftp case study, 393, 398–399
- for IGRP, 201
- for OSPF, 213
- for RIP, 199
- for static and dynamic routes, 197
- show ip route bgp command, 219
- show ip route eigrp command, 207–208, 221
- show ip route igrp command, 201
- show ip route ospf command, 213
- show ip route rip command, 199
- show ip traffic command, 151–153
- show isdn status command, 298–300
- show log command, 327–328
- show logging command
  - for error messages, 160–162
  - in WAN connectivity case study, 401
- show logging buffer command, 329
- show mac command, 340–342
- show mac-address-table
  - dynamic command, 364
- show memory command, 139
- show monitor command, 364
- show port command, 326–327
  - for MSFC, 358
  - vs. show interface, 364
  - for switch network
    - configuration tables, 36
    - for VLANs, 362
- show ppp multilink command, 300–301
- show processes command, 146–147
- show queue command, 140–141
- show queueing command, 140–141
- show running-config command
  - for access lists, 179
  - for BGP, 219
  - for EIGRP, 207
  - in ftp case study, 393
  - for IGRP, 201
  - for MSFC, 358
  - for OSPF, 213
  - for RIP, 199
  - in Token Ring case study, 418–419
- show span command, 364
- show spantree command, 344, 348
- show spantree vlan command, 37–38
- show stacks command, 137–138
- show startup-config command, 134–135, 179
- show system command, 325
- show tech-support command, 138
- show test command, 338–340, 364
- show-timezone localtime command, 301
- show trunk command, 37
- show version command, 133–134, 345, 364
  - for configuration tables
    - router, 29–30
    - switch, 34–35
  - in ftp case study, 397–398
- show vlan command, 364
- show vlans command, 360–361
- show vtp domain command, 342
  - vs. show vtp status, 364
  - for switch network
    - configuration tables, 35–36
- show vtp status command, 364
- /showclassid option in ipconfig, 61
- SIA (stuck in active) problem, 209
- Signal Quality Error (SQE), 481
- signaling methods in Ethernet, 101
- signaling packets, 478–479
- silicon switching, 479
- Silicon Switching Engine (SSE), 481
- Simple Mail Transfer Protocol (SMTP), 479
- Simple Network Management Protocol (SNMP), 346
- simplex mode, 479
- simplicity in documentation, 40
- sliding windows, 479
- SLIP (Serial Line Internet Protocol), 479
- slow file transfers, 410–416, 410, 416
- small buffer pools, 137
- SMDS (Switched Multimegabit Data Service), 479
- smooth round-trip timers (SRTTs), 203
- SMTP (Simple Mail Transfer Protocol), 479
- SNA (System Network Architecture), 479
- SNAP (Subnetwork Access Protocol), 479
- SNMP (Simple Network Management Protocol), 346
- snmp option in debug, 156
- snmp-server community command, 227
- sockets, 479
- SOF (start-of-frame) field, 102
- software, network
  - configuration tables for. *See* network configuration tables
- software test equipment, 479
- solutions in case studies
  - 2600 series router, 381–382, 384–388
  - file transfers, 413–416
  - ftp, 396–399
  - telnet, 408–409
  - Token Ring, 420–421
  - WAN connectivity, 403–405
- SONET (Synchronous Optical Network), 479
- Source address field in ISL, 351
- Source address prompt in traceroute, 172
- Source field
  - in TCP, 119
  - in UDP, 120
- source-interface command, 163
- Source IP Address field, 113

- Source MAC addresses field, 102
  - Source-Route Bridging (SRB), 481
  - Source-Route Translational Bridging (SR/TLB), 481
  - Source-Route Transparent (SRT) bridging, 481
  - Source Service Access Points (SSAPs), 481
  - spanning explorer packets, 480
  - spanning option in debug, 158
  - spanning tree algorithm (STA), 480
  - spanning-tree command, 363
  - Spanning Tree Protocol (STP), 346–348, 347, 480, 482
  - spanning trees, status of, 344
  - SPANs (Switched Port Analyzers), 346, 357, 480
  - speed command, 363
  - SPIDs (Service Profile Identifiers)
    - defined, 480
    - for ISDN, 281–282
  - split horizon, 480
  - spoofing, 480–481
  - spoolers, 481
  - SPs (Switch Processors), 480
  - SPX (Sequenced Packet Exchange) protocol
    - as connection-oriented protocol, 99
    - defined, 481
  - SQE (Signal Quality Error), 481
  - SR/TLB (Source-Route Translational Bridging), 481
  - SRB (Source-Route Bridging), 481
  - SRT (Source-Route Transparent) bridging, 481
  - SRTTs (smooth round-trip timers), 203
  - SSAPs (Source Service Access Points), 481
  - SSE (Silicon Switching Engine), 481
  - STA (spanning-tree algorithm), 480
  - stacks, displaying, 137–138
  - standard areas in OSPF, 212
  - standard IP access lists, 178–180, 180, 481
  - standard IPX access lists, 481
  - standard keyword, 183
  - star topology, 481
  - Start Delimiter field, 105
  - start-of-frame (SOF) field, 102
  - startup ranges, 482
  - static routes, 482
  - static routing, 197
  - static VLANs, 482
  - statistical multiplexing, 482
  - status
    - of routers, 134
    - of spanning trees, 344
    - of switches, 325, 338–340
  - status command for ISDN, 292
  - Status field
    - in EIGRP, 205
    - in HDLC, 254
  - StEnq data, 254
  - STM-1 (Synchronous Transport Module Level 1), 482
  - store-and-forward switch types, 482
  - STP (shielded twisted-pair), 482
  - STP (Spanning Tree Protocol), 346–348, 347, 480, 482
  - Strict option in ping headers, 168
  - Strict source routing prompt in traceroute, 172
  - stub area flags, 210
  - stub areas
    - defined, 482
    - in OSPF, 212
  - stub networks, 482
  - stuck in active (SIA) problem, 209
  - STUN (Serial Tunnel), 482
  - subarea nodes, 482
  - subareas, 482
  - subchannels, 482
  - subinterfaces
    - defined, 482
    - with Frame Relay, 389
  - subnet addresses, 482
  - subnet masks
    - defined, 483
    - information for, 114–116
  - Subnetwork Access Protocol (SNAP), 479
  - subnetworks, 483
  - super frames (SFs), 478
  - supervisor modules
    - defined, 483
    - IP configuration of, 329
  - supervisory frame structure, 107–108, 108
  - Sustainable Cell Rate (SCR), 478
  - SVCs (switched virtual circuits)
    - defined, 483
    - in Frame Relay, 260
  - switch fabric, 483
  - Switch Processors (SPs), 480
  - switched Ethernet
    - boot-up errors in, 348
    - cabling issues in, 353–356, 356
    - Catalyst system for, 322
    - CLI, 322
    - hybrid CLI. *See* hybrid mode Catalyst CLI
    - RMON, 346
  - command summary, 366–367
  - exam essentials, 365–366
  - key terms, 368
  - review questions, 369–374
  - spanning tree for, 346–348, 347
  - summary, 364–365
  - switches, bridges, and hubs in, 320–321
  - troubleshooting, 356
  - MSFC for, 357–359
  - SPANs for, 357
  - VLANs, 359–363
  - VLANs for, 349–353, 350
- switched LANs, 483
- Switched Multimegabit Data Service (SMDS), 479
- Switched Port Analyzers (SPANs), 346, 357, 480
- switched virtual circuits (SVCs)
  - defined, 483
  - in Frame Relay, 260
- switches, 320
  - vs. bridges and hubs, 321
  - collision domains on, 321
  - defined, 483
  - for ISDN, 293–294

**510** switching paths – three-way handshakes

network configuration  
 tables for, 33–38, 34  
 status of, 325, 338–340  
 VLANs across, 359–363  
 switching paths, 483  
 switchport access vlan  
 command, 364  
 symbols in documentation, 40  
 symptoms, identifying, 7, 8  
 Synchronous Data Link  
 Control (SDLC)  
 defined, 478  
 working with, 106–108,  
 108  
 Synchronous Optical Network  
 (SONET), 479  
 synchronous transmissions,  
 483  
 Synchronous Transport  
 Module Level I (STM-1),  
 482  
 Synergy Advanced Gate-Array  
 Engine (SAGE) chips, 477  
 Synergy Advanced Interface  
 and Network  
 Termination (SAINT),  
 477  
 Synergy Advanced  
 Multipurpose Bus Arbiter  
 (SAMBA) ASICs, 477  
 System Network Architecture  
 (SNA), 479

**T**

-t option  
 in ping, 68  
 in telnet, 60  
 T reference points  
 defined, 485  
 in ISDN, 288  
 T1 channels, 286  
 T1 transmissions, 483  
 T3 transmissions, 483  
 TA (terminal adapters)  
 defined, 484  
 in ISDN, 288  
 TAC (Technical Assistance  
 Center), 421  
 tacacs option in debug, 156  
 tag switching, 483  
 tagged traffic, 484  
 Target IP address prompt in  
 traceroute, 172  
 tbridge option in debug, 156  
 TCP (Transmission Control  
 Protocol)  
 as connection-oriented  
 protocol, 99  
 defined, 484  
 packets in, 118–120  
 three-way handshakes in,  
 177–178, 484  
 TCP/IP (Transmission Control  
 Protocol/Internet  
 Protocol)  
 commands for, 147–153  
 connectivity problems  
 command summary,  
 185–186  
 exam essentials,  
 184–185  
 IP access lists, 178–183,  
 180–181  
 key terms, 186  
 LAN, 172–178, 173,  
 177  
 review questions,  
 187–192  
 summary, 183–184  
 defined, 484  
 routing protocols  
 action plans in, 229–231  
 BGP, 217–220  
 command summary,  
 232–235  
 default gateways in,  
 194–196, 195  
 EIGRP, 202–209, 204,  
 206  
 exam essentials,  
 231–232  
 IGRP, 200–202  
 key terms, 235  
 OSPF, 209–216, 211  
 problems summary  
 sheet, 228–229  
 redistribution of. *See*  
 redistribution of  
 routing protocols  
 review questions,  
 236–242  
 RIP, 198–200, 198  
 static routing and  
 dynamic routing  
 in, 197  
 summary, 231  
 tcp option in debug, 160  
 TDM (Time Division  
 Multiplexing), 484  
 TDRs (time domain reflectors),  
 355  
 TE (terminal equipment), 484  
 TE1 (terminal equipment 1)  
 devices, 111, 288, 484  
 TE2 (terminal equipment 2)  
 devices, 111, 288, 484  
 tech-support command, 138  
 Technical Assistance Center  
 (TAC), 421  
 TEIs (terminal endpoint  
 identifiers), 111, 289–290  
 telcos, 484  
 telnet command, 59–60  
 telnet option in debug, 158  
 Telnet protocol  
 case study, 406–409, 406  
 defined, 484  
 for end-system network  
 configuration tables,  
 59–60  
 templates for documentation,  
 40  
 10BaseT standard, 432  
 terminal adapters (TAs)  
 defined, 484  
 in ISDN, 288  
 terminal emulation, 484  
 terminal endpoint identifiers  
 (TEIs), 111, 289–290  
 terminal equipment (TE), 484  
 terminal equipment 1 (TE1)  
 devices, 111, 288, 484  
 terminal equipment 2 (TE2)  
 devices, 111, 288, 484  
 terminal monitor command,  
 153  
 terminal no monitor command,  
 153–154  
 TFTP addresses in router core  
 dumps, 163  
 TFTP protocol, 484–485  
 Thicknet standard, 485  
 Thinnet standard, 485  
 three-way handshakes,  
 177–178, 484

- Time Division Multiplexing (TDM), 484
  - time domain reflectors (TDRs), 355
  - time intervals in OSPF, 210
  - Time To Live (TTL) value
    - defined, 486
    - in IP packets, 113
    - in traceroute, 69–70, 168–169
  - timeline in fact gathering, 8–9
  - Timeout prompt in traceroute, 172
  - timeouts in ICMP, 117
  - Timestamp option in ping
    - headers, 168
  - Timestamp prompt in traceroute, 172
  - timestamps
    - in debugging, 153
    - for ISDN, 301
  - token buses, 485
  - token frame format, 105–106, 105
  - token option in debug, 157
  - token passing, 485
  - Token Ring Interface Processor (TRIP), 485
  - Token Ring protocol
    - case study, 416–421, 417
    - defined, 485
    - operation of, 103–106, 104–105
  - tokens
    - defined, 485
    - in Token Ring, 103
  - toll networks, 485
  - top-down troubleshooting
    - defined, 485
    - for end-systems, 67
  - topologies
    - diagrams of. *See* network topology diagrams
    - in EIGRP, 204–205
    - in Ethernet, 101
  - TOS (Type of Service) field, 113
  - total buffer setting, 136
  - Total Length field, 113
  - Totally Stub areas, 212
  - trace command, 485
  - traceroute command, 168–169
    - for default gateways, 196
    - EXEC modes for
      - privileged, 171–172
      - user, 170–171
    - in ftp case study, 399
  - tracert command
    - for end-system troubleshooting, 69–71
    - in ftp case study, 393
  - traffic statistics, 151–153
  - translate option in debug, 158
  - Translation in VLANs, 359–360
  - Transmission Control Protocol (TCP)
    - as connection-oriented protocol, 99
    - defined, 484
    - packets in, 118–120
    - three-way handshakes in, 177–178, 484
  - Transmission Control Protocol/Internet Protocol (Transmission Control Protocol/Internet Protocol)
    - transparent bridging, 485
  - transparent mode in VTP, 353
  - Transport layer
    - defined, 485
    - in OSI model, 93, 93–94
  - Trap command, 162
  - trims information for buffer pools, 136
  - TRIP (Token Ring Interface Processor), 485
  - Troubleshooting Assistant, 486
    - troubleshooting commands, 130
    - command summary, 185–186
    - debug, 153–162
    - exam essentials, 184–185
    - global, 132–139
    - interface, 139–146
    - key terms, 186
    - ping, 164–168
    - process, 146–147
    - review questions, 187–192
    - router core dumps, 162–164
    - show, 130–132
    - summary, 183–184
    - TCP/IP, 147–153
    - traceroute, 168–172
  - troubleshooting model. *See* problem-solving model
  - trunk links, 486
  - TTL (Time to Live) value
    - Trunk Up-Down (TUD) protocol, 486
    - defined, 486
    - in IP packets, 113
    - in traceroute, 69–70, 168–169
  - TUD (Trunk Up-Down) protocol, 486
  - tunnel option in debug, 157
  - tunneling, 486
  - Type 1 (TE1) equipment, 111
  - Type 2 (TE2) equipment, 111
  - Type code in ISL, 351
  - Type-Length field, 102
  - Type of Service (TOS) field, 113
- 
- ## U
- U character
    - in ping character maps, 166
    - in traceroute, 169
  - U reference points
    - defined, 486
    - in ISDN, 288
  - UDP (User Datagram Protocol), 120
    - as connectionless protocol, 100
    - defined, 486
  - udp option in debug, 160
  - undebug all command, 154
  - underruns, 486
  - unequal-cost load balancing, 201
  - unicasts, 321
  - unnumbered frames
    - defined, 486
    - in SDLC, 107–108, 108
  - unshielded twisted-pair (UTP) cable, 486
  - updates in EIGRP, 203–206, 204, 206
  - Urgent Pointer field, 119

**512** User bits in ISL – zones

User bits in ISL, 351  
 User Datagram Protocol (UDP), 120  
   as connectionless protocol, 100  
   defined, 486  
 user EXEC mode  
   for ping commands, 165–166  
   for traceroute command, 170–171  
 user information command, 292  
 UTP (unshielded twisted-pair) cable, 486

**V**

value option in route, 73  
 Variable Bit Rate (VBR) class, 486  
 Variable Length Subnet Masking (VLSM), 113–114, 116–117, 487  
 VBR (Variable Bit Rate) class, 486  
 VCCs (Virtual Channel Connections), 487  
 VCs (virtual circuits), 486  
 Verbose option in ping headers, 168  
 Verbose prompt in traceroute, 172  
 verifying packet flow, 155  
 Versatile Interface Processors (VIPs), 487  
 Version field in IP packets, 113  
 Version number parameter in RIP packets, 198  
 versions, displaying, 133–134, 345  
 very big buffer pools, 137

VIPs (Versatile Interface Processors), 487  
 VIPs (Virtual IPs), 487  
 Virtual Channel Connections (VCCs), 487  
 virtual circuits (VCs), 486  
 virtual LANs. *See* VLANs (virtual LANs)  
 virtual rings, 487  
 VLAN IDs, 351  
 vlan option in debug, 158  
 VLAN Trunking Protocol (VTP)  
   defined, 487  
   information for, 342  
   working with, 352–353  
 VLANs (virtual LANs), 349  
   defined, 487  
   IEEE 802.1Q for, 352  
   ISL for, 349–352, 350  
   across routers and switches, 359–363  
   in switch network configuration tables, 37–38  
 VLSM (Variable Length Subnet Masking), 113–114, 116–117, 487  
 volt-ohm meters  
   for cabling, 354  
   defined, 487  
 VTP (VLAN Trunking Protocol)  
   defined, 487  
   information for, 342  
   working with, 352–353

**W**

-w option in tracert, 70  
 WANs (wide area network) case study, 400–405, 400

  defined, 487  
 Warnings logging level, 161  
 wildcards, 487  
 Window field, 119  
 window sizes  
   in connection-oriented protocols, 95  
   defined, 487  
 windowing, 487  
 Windows name resolution, 64  
 winipcfg.exe utility, 62  
 WINS (Windows Internet Name Service) servers, 64  
 WinSock interface, 487  
 workgroup switching, 488  
 write core command, 164  
 write term command, 134

**X**

X.25 standard, 488

**Y**

yellow alarms, 488  
 yourseen data, 254–255

**Z**

ZIP (Zone Information Protocol), 488  
 ZIP storms, 488  
 zones, 488