

INDEX

- 1R regeneration, 439
- 2R regeneration, 439
- 3R regeneration, 439, 461
- 802.1D spanning tree protocol (STP), 471
- 802.1p packet prioritization, 471
- 802.3 frame forwarding, 471

- AAL, 189
- Absorption edge, 48
- Access networks, 6, 7
- Acquisition time, 282
- ADC, 221
- Add-drop multiplexers (ADMs), 22, 114, 251, 432, 480
- Adiabatic, 46
- ADM, 22, 114, 251, 432, 480
- ADM rings, 115
- Advanced intelligent network (AIN), 460
- AIN, 460
- Amplification, 223, 226, 439
- Amplitude-modulated systems, 79
- Analog integrated circuits, 221
- Analog-to-digital conversion (ADC), 221
- Anomalous regime, 79
- Any-layer switch, at layer X, 449
- Any-layer switch, at layer X, protocol Y, 449
- APDs (avalanche photodiodes), 44, 45, 82
- Application layer, 139
- Application-specific integrated circuits (ASICs), 222
- APS, 23

- Arbitration bias, 421
- Arbitration computations, 423
- ASIC, 222
- ASON, 481, 501, 503, 506, 517
- ASON architecture principles, 518
- ASON/ASTN CP transport network (signaling network), 524
- ASON control plane, 520
- ASON functional architecture, 521
- ASON reference model, 503
- ASON reference points, 518, 521
- ASON standards, 507
- Assigning, 446
- Associated signaling, 525
- ASTN/ASON, 501
- Asynchronous time-division multiplexing, 15
- Asynchronous transfer mode (ATM), 18, 184, 188, 451, 465, 467, 480, 500
- ATM, 18, 184, 188, 451, 465, 467, 480, 500
- ATM adaptation layers (AALs), 189
- ATM switch, 21, 470
- Attenuation, 33
- Attenuation spectrum, 39
- Automatically switched optical network (ASON), 481, 501, 506
- Automatically switched optical network (ASON) switch, 450
- Automatic protection switching (APS), 123, 483
- Autonomous systems (ASs), 169
- Avalanche photodiodes (APDs), 44, 45, 82

- Bandwidth, 88
- Bang-bang detector, 279
- BFM, 259
- BGP, 185, 453
- Bicast, 303
- Bidirectional line-switched ring, 486
- Binary-phase detector, 279, 280
- Birefringence, 73
- BIST, 221
- Bit-sliced memory switches, 359
- Blocking, 366, 392
- Border gateway protocol (BGP), 185, 453
- Bottom-emitting vertical-cavity surface-emitting laser, 43
- Bottom-top methodology, 260
- Boundary scan (JTAG), 221
- Brillouin scattering, 80
- Broadcast service, 302
- Buffer layer, 52
- Buffer sharing, 400
- Buffer-sharing policies, 405
- Built-in shelf testing (BIST), 221
- Bus functional models (BFMs), 259

- Cable modems, 21
- Cable modem technology, 4
- CAD, 254
- Call rejection, 301
- CB, 48
- CBR, 189
- CD (chromatic dispersion), 63, 64, 65, 68, 92
- CDMA, 5
- CDR, 226, 233, 268, 283
- CDR architecture, 284
- CDR block diagram, 284
- CDR operation, 283
- Cells, 414
- Cell switching, 384
- Center of symmetry, 50
- Central memory packet-cell switches, 406
- Central memory TDM switches, 350
- Channelized SONET streams, 120
- Channel loss, 288
- Charge pump, 281
- Charge-pump-based PLL, 281
- Chip I/O interfaces, 231, 233
- Chirp, 79
- Chirped FBGs, 70
- Chirped fiber Bragg grating, 71
- Chromatic dispersion (CD), 63, 64, 65, 68, 92
- Circuit emulation, 434
- Circuit mode-based, 433
- Circuit switching, 11

- Cladding, 35
- Class of service, 386
- Clock and data recovery (CDR), 226, 233, 268, 283
- Clock and data recovery (CDR) circuit, 226
- Clock multiplexing, 227
- Clock multiplications (CMUs), 266, 268
- Clock synthesis unit (CSU), 227
- Clocking schemes in a SONET, 132
- Clos networks, 321
- CMISE, 497
- CMOS, 220
- CMU, 266, 268
- Coarse WDM (CWDM), 88, 91
- Coaxial cable, 3
- Code division multiple access (CDMA), 5
- Coherent amplifiers signal, 60
- Common management information service element (CMISE), 497
- Common object request broker architecture (CORBA), 497
- Completely connected network, 295
- Computer-aided design (CAD), 254
- Concatenated SONET streams, 120
- Concentrator, 445
- Conduction band (CB), 48
- Conflict resolution in a Clos network, 329
- Congestion, 388
- Congestion avoidance phase, 164
- Connection control separation, 518
- Connectionless communication, 434
- Connection-oriented communication, 433
- Connection-oriented service, 153
- Constant-bit-rate (CBR) services, 189
- Constrained shortest path first (CSPF), 513
- Control of digital crossbar switches, 314
- Control plane, 481, 490
- Converting, 446
- Copper wire, 2
- CORBA, 497
- Core, 35
- Core grooming, 445
- Core routers, 20, 23
- Corning's LEAF, 68
- Costs of Clos networks, 338
- Crossbar switch, 305
- Cross-connect system (DCS), 447
- Cross-phase modulation, 79
- Cross-phase modulation (XPM), 79
- Crosstalk, 288, 438
- CSPF, 513
- CSU, 227
- CWDM, 88, 91

- Data coding, 228
- Data communication network (DCN), 506
- Data encapsulation, 18
- Data link layer, 17, 138, 435
- Data networking ICs, 224
- Data payload, 19
- Data plane, 490
- Datagrams, 452
- DCC, 114
- DCF, 68, 69
- DCN, 506
- DCS, 447
- Decrement bits, 133
- Delayed acknowledgment, 166
- Deliberate congestion and backoff, 175
- Dense WDM (DWDM), 88, 91, 92, 94, 195, 208
- Depolarized light, 73
- Design flow, 256
- Design synthesis, 260
- Destination port number, 151
- Deterministic multiplexing, 442
- DFB, 42, 64
- DFB laser, 66
- DGD methods, 77
- Differential group delay, 74
- Digital cross-connect (DCC) system, 114, 450, 463
- Digital electronic crossbar switches, 310
- Digital integrated circuits, 221
- Digital signal processing (DSP), 221
- Digital subscriber line, 3
- Digital wrapper, 203
- Digital wrapper frame, 202
- Digital wrapper technology, 200
- Digiwrapper, 184
- Dijkstra's algorithm, 171
- Dijkstra's shortest-path algorithm, 173
- Direct modulation, 46, 47
- Discrete amplifiers, 60
- Dispersion and insertion loss of a multichannel, 71
- Dispersion compensation with fiber Bragg gratings, 70
- Dispersion management techniques, 66
- Dispersion parameter, 63
- Dispersion-compensating fiber (DCF), 68, 73
- Dispersion-shifted fiber (DSF), 67
- Dispersion-slope, 69
- Distance vector multicast routing protocol (DVMRP), 471
- Distributed feedback (DFB) lasers, 42
- Distributed Raman amplifier, 61
- Distributed switching fabrics, 297
- Distributed switching structures, 296
- Draining queues, 404, 405
- DRAM, 221
- DSF, 67
- DSL, 3
- DSL modems, 21
- DSP, 221
- Dual control pages, 349
- DVMRP, 471
- DWDM, 88, 91, 92, 94, 195, 208, 480, 500
- Dynamic random access memories (DRAMs), 221
- EAM, 48, 49, 54
- Ebus interface, 246
- EDFA, 55–58, 62, 72, 91, 95
- Edge, 330
- Edge-emitting laser diode, 41
- Edge routers, 23
- Effective length of a lossy fiber, 78
- Effective refractive index, 38
- EGP, 453, 480
- Egress stage, 319
- Egress vector, 306
- Egress-buffered self-select TDM switches, 357
- EIGRP, 453
- Electrical-to-optical (OEO), 95, 99, 440
- Electroabsorption modulated laser (EML), 54
- Electroabsorption modulators (EAMs), 48
- Electromagnetic interference (EMI), 34
- Electronic crossbar switches, 315
- Electronic dispersion compensation, 71, 73
- Electrooptic effect, 51
- Electrooptic modulation, 55
- Electrooptic modulator, 50
- Elementary streams (ESs), 443
- EMI, 34
- EML, 54
- End-to-end grooming, 446
- Energy-level diagram, 59
- Enhanced interior gateway routing protocol (EIGRP), 453
- E-NNI, 492
- EOM, 51, 54
- Equalization, 287, 289
- Erbium-doped fiber amplifier (EDFA), 55–58, 62, 72, 91, 95
- ESs (elementary streams), 443
- Ethernet (local area network) switch, 451
- Ethernet, 144, 195
- EtherType, 457

- External border gateway protocol (eBGP), 454
- External gateway protocol (EGP), 453
- External modulation, 46, 47
- External-network-to-network interfaces (E-NNIs), 492
- External-timing clock exchange, 131
- Extracting/inserting, 446
- Extraordinary index, 52

- Fabry-Perot (FP) laser, 42, 82
- Fast recovery, 166
- Fast retransmit, 165
- Fast retransmit algorithm, 165
- Fast-wave electrodes, 52
- Fat pipes, 177
- FCIP, 214
- FC over IP (FCIP), 213, 214
- FC over MPLS, 214
- FC over SONET, 211
- FC over WDM, 212
- FEC (forward error correction), 200, 229, 491, 494
- FEC (forwarding equivalence classes), 192, 193
- Fiber Bragg gratings, 73
- Fiber mode, 35
- Fiber to the curb, 34
- Fiber to the home, 34
- Fiber to the neighborhood, 34
- Fiber to the premise, 34
- Fiber transmission impairments, 62, 83
- Fiber channel (FC), 8
- Field-programmable gate arrays (FPGAs), 222
- Filling, 404
- First window, 38
- First-order PMD, 75
- First-order PMD coefficient, 75
- Flowchart, 256
- Form birefringence, 74
- Forward error correction (FEC), 200, 229, 491, 494
- Forwarding equivalence classes (FECs), 192, 193
- Four-fiber (two pair) SONET/SDH ring, 485
- Four-fiber bidirectional ring, 487
- Four-wave mixing (FWM), 80
- FPGA, 222
- Fractional PLLs, 275
- Frame, 384
- Frame relay (FR), 480
- Frame relay (FR) switch, 451
- Framers, 224, 228
- Framers and mappers (layer 2), 227
- Franz-Keldysh effect, 48, 49
- Free-running clock exchange, 131
- Frequency, 90
- Frequency detector, 278
- FTP Protocol, 143
- FTTC (fiber to the curb), 34
- FTTH (fiber to the home), 34
- FTTN (fiber to the neighborhood), 34
- FOTP (fiber to the premise), 34
- Function/scope, 433
- Functional design, 257
- FWM, 80

- GARP multicast registration protocol (GMRP), 471
- Gate array, 222
- GE, 184
- Generalized multi-protocol label switching (GMPLS), 501, 505, 506, 513, 516, 521, 523, 526
- Generic framing procedure (GFP), 184, 190, 496
- Geometric birefringence, 74
- GFP, 184, 190, 496
- GFP header, 191, 207
- Gigabit Ethernet (GE), 184
- Gigabit Ethernet over the Internet, 210
- Gimbal-type suspension mirror for three-dimensional switching, 98
- Global System for Mobile Communications (GSM), 5
- GMPLS, 501, 505, 506, 513, 516, 521, 523, 526
- GMPLS-based stack, 512
- GMRP, 471
- Graphs, 330
- Grooming, 435, 436, 437, 445, 446
- Grooming equipment, 462
- Group velocity dispersion, 63
- GSM, 5
- Guide, 35

- H pointers, 122, 123
- Half-wave voltage, 53
- Hard permanent circuits, 494
- Hardware, 140
- Head-of-line blocking and corruption of crossing traffic, 393
- HFC, 35
- High-refractive-index regions, 52
- Hogge-type detector, 279
- Hold range, 282
- Horizontal signal polarization mode, 461

- Hotspot loads, 387
- Hubs, 22
- Hub technology, 9
- Hybrid connections, 494
- Hybrid fiber-coax (HFC), 35

- ICMP, 140
- IGMP, 140
- IGP, 453, 480
- IGRP, 454
- III-V materials, 40
- Impact ionization, 45
- Increment bits, 133
- Information media, 433
- Information transfer, 436
- Information transmission, 435
- Information-handling, 433
- Information-handling protocols, 433
- Ingress, 306
- Ingress-buffered packet-cell switches, 410
- Ingress-buffered TDM switches, 355
- Ingress ports, classes, and egress (ICE) ports, 395
- Ingress stage, 318
- I-NNI, 492
- Integrated circuits (ICs), 220
- Integrated circuits for optical transceivers, 268
- Integrated services digital network (ISDN) switch, 450
- Interface, 231
- Interior border gateway protocol (IBGP), 454
- Interior gateway routing protocol (IGRP), 454
- Internal gateway protocol (IGP), 453, 454
- Internal-network-to-network interfaces (I-NNIs), 492
- Internet fiber channel protocol (iFCP), 214
- Internet protocol (IP), 140, 145
- Internet service providers (ISPs), 7
- Intersymbol interference, 288, 438
- I/O signaling schemes, 234
- IP, 140, 145
- IP addresses, 145
- IPE, 444
- IP encapsulator (IPE), 444
- IP header format, 146
- IP over ATM over SONET, 204
- IP over SONET, 204
- IP route calculations, 169
- IP router, 21
- IP routing mechanisms, 167
- IP switch, 452

- IPv6, 178, 179
- ISDN, 450
- ISPs, 7

- Jitter, 225
- Jitter generation, 285
- Jitter tolerance, 286
- Jitter transfer, 285
- JTAG, 221

- LA (limiting amplifier), 273
- Label edge routers (LERs), 192
- Labeled switch paths (LSPs), 514
- Label merging, 194
- Label stacking, 194
- Label swap routers (LSRs), 192
- Label switching, 468
- LAN, 6, 8
- Large-scale integration (LSI), 220
- Laser diodes (LDs), 39, 41
- Laser driver, 274
- Lasers, 42
- Last mile, 4
- Latency, 301, 421
- Lattice of queue structures, 395
- Layer 1, 17
- Layer 2, 17
- Layer 3, 17
- Layer 4 switch, 452
- Layout verification, 261
- LC oscillators, 276
- LD (laser diode), 39
- LDO, 221
- Leaky bucket mechanism, 405
- LED, 39, 41
- LER, 192, 193
- Light sources, 39
- Light-emitting diodes (LEDs), 39, 41
- Limiting amplifier (LA), 273
- Limits central memory designs, 353
- Linear electrooptic effect, 50
- Linearly polarized light, 73
- Linear-phase detector, 279, 280
- Linear SONET/SDH network, 484
- Line overhead (LOH), 117, 124
- Line, SONET, 115
- Line-timed clock exchange, 132
- Link management protocol (LMP), 506
- Link state packets (LSPs), 171
- Lithium niobate, 51
- Lithium niobate Mach-Zehnder modulator, 52
- LMP, 506
- Local area networks (LANs), 6

- Lock range, 282
- Logical queues, 390
- Logical scope, 433
- LOH, 117
- Long-period fiber grating, 58
- Long pipe, 177
- Loop-timed clock exchange, 132
- Low drop-out (LDO), 221
- LSI, 220
- LSP, 171, 514
- LSR, 192, 193

- Mach-Zehnder (MZ) interferometer, 52, 53
- MAN, 7, 9
- Managed bandwidth to core IP network connectivity, 517
- Management plane, 481
- Mappers, 224
- Master slice, 222
- Master-slave source synchronous serial interface, 241
- Master-slave timing mode, 132
- Material dispersion, 64
- Matrix switch, 450
- Maxigram, 384
- Maximum likelihood sequence estimation, 72
- Media, 140
- Media access controller (MAC), 198
- Media layer, 18
- MEF, 505
- Memory I/O interfaces, 243
- MEMS, 97, 309
- Mesh network topologies and restoration, 517
- Mesh topology, 10
- Metro Ethernet Forum (MEF), 505
- Metropolitan area networks (MANs), 7, 9
- Microelectronic mechanical systems (MEMSs), 97
- Microprocessor I/O interfaces, 245
- Microwave index, 52
- Middle stage, 318
- Minigram, 384
- Mixed-signal circuits, 221
- MLSE (maximum likelihood sequence estimation)-based detectors, 72
- MMF, 36, 37
- Modems, 21
- Modulation, 223
- Moving Picture Expert Group (MPEG), 442
- MPEG, 442
- MPLS, 184, 192, 193, 207, 452, 480

- Multicast, 426
- Multicast in Clos networks, 332
- Multicast in the blocking ingress-buffered architecture, 428
- Multicast in the nonblocking ingress-buffered architecture, 428
- Multicast in the request-grant architecture, 428
- Multicast service, 302
- Multimode fiber (MMF), 36, 37
- Multiple-branching multicast, 333
- Multiplexing, 27, 435, 436, 437, 440
- Multiplexing equipment, 462
- Multiplication layer, 45
- Multiprotocol label switches (MPLS), 184, 192, 193, 207, 452, 480
- Multiprotocol label switching (MPLS) switch, 452
- Multi-quantum-well electroabsorption modulator, 50
- Multistage crossbar switches, 318
- Multistage frame networks, 425
- Multistage memory switches, 377
- Multistage switch, 304
- MZ modulators, 53

- Naigle's algorithm, 167
- NE (network element), 431
- Near end crosstalk (NEXT), 288
- Negative stuffing, 133
- Network elements (NEs), 20, 431
- Network grooming, 445
- Networking equipment, 20
- Network interface controller (NIC), 139
- Network layer, 139, 435
- Network overly hierarchy, 19
- Network processor, 230
- Network topologies, 9
- Network topology comparison, 10
- NEXT, 288
- Next-hop determination, 385
- NIC, 139
- NNI, 513
- Noise, 438
- Nonassociated signaling, 525
- Nonblocking ingress-buffered frame switches, 412
- Nonlinear effects, 77
- Nonlinear phase modulation, 78
- Non-return-to-zero (NRZ), 129
- Nonzero dispersion-shifted fiber (NZDSF), 68
- Normal dispersion, 63
- Normal regime, 79

- NRZ, 233
- NZDSF, 67, 68
- OADM, 100
- OAM&P, 112, 114, 513
- OC (optical carrier), 113
- OC-192 interface, 239
- OEO conversion in WDM networks, 104
- OEO regeneration, 72, 73
- One-to-one mapping, 306
- OPA, 344, 366
- Open-path algorithm (OPA), 344
- Open shortest path first (OSPF), 170, 453, 454
- Open systems interconnection (OSI), 2, 16
- Open systems interconnection reference model (OSIRM), 28, 431, 480
- Operating principle of an LED, 40
- Operations, administration, maintenance, and provisioning (OAM&P), 112, 114, 513
- Optical add-drop multiplexer (OADM), 100, 101
- Optical amplification, 55, 83
- Optical carrier (OC), 113
- Optical channel data unit, 499
- Optical channel layer, 492
- Optical channel payload unit, 499
- Optical channel transport unit, 499
- Optical crossbar switches, 308
- Optical cross-connects (OXC), 96, 97, 480
- Optical-electrical-optical (OEO), 72
- Optical fiber, 4, 32
- Optical grooming, 447
- Optical internetworking forum standards, 234
- Optical links, 9
- Optical modulation, 46, 83
- Optical multiplex sections, 493
- Optical switch, 450
- Optical switching technologies, 97
- Optical transceiver, 267, 268
- Optical transceiver architectures, 267
- Optical transmission section, 493
- Optical transponder, 268
- Optical transport hierarchy (OTH), 492
- Optical transport network (OTN), 201, 203, 481, 488, 495, 496, 500, 501
- Ordinary index, 52
- OSIRM, 28, 431, 480
- OSPF, 171, 453, 454, 472
- OTH, 492
- OTN, 201, 203, 481, 488, 495, 496, 500, 501
- OTN ITU-T G.709 client mapping, 498
- OTN standards, 494
- OTN-related ITU-T standards, 495
- Overlap factor, 53
- OXC, 97, 480
- Packet mode communication, 434
- Packet over SONET (POS), 204, 228
- Packet processing, 230
- Packet processing devices (Layer 3), 230
- Packet switching, 11, 12, 472
- Packet transmission, 472
- Packing, 446
- Parallel interfaces, 233
- Parallel I/O, 232
- Partitioning, 424
- Path backup, 485
- Path overhead (POH), 117
- Path, SONET, 115
- Path switching, 485
- Path switching on a unidirectional ring, 485
- PCB, 287
- PCB backplane, 287
- PECL, 270, 271
- Permutation arbitration by wavefront computation, 416
- Permutation loads, 364
- PFD, 278, 279
- Phase detector, 278
- Phase-frequency detectors (PFDs), 278, 279
- Phase-locked loop (PLL), 275
- Phase noise characteristics, 282
- Phase velocity, 38
- Phonons, 41
- Photodetectors, 44
- Photonic cross-connects (PXC), 480
- PHY devices (layer 1), 225
- Physical and link layer (PLL), 235
- Physical connectivity, 17
- Physical layer, 17, 435
- Physical layer (PHY) devices, 225, 237
- PIN diode, 44
- Planck's constant, 40
- PLL, 235, 275, 282
- PMD, 72, 76, 77
- PMD devices (layer 1), 225
- Pockels effect, 50
- POH, 117
- Pointer interpolation, 251
- Pointer processing, 251
- Point-to-point topology, 9
- Polarization mode dispersion (PMD), 72, 75, 76
- Polarization mode dispersion compensation, 77
- Polarization modulator, 54

- Population inversion, 42
- POS, 204, 228
- Positive stuffing, 133
- Preemphasis, 287, 289
- Primitive logic gate, 316
- Principal polarization states model (PSP), 75
- Priority blocking, 396, 397, 398
- Propagation, 32, 35
- Propagation of light in a short-fiber, 74
- Protocol headers, 142
- Protocol layers, 17
- Provisioned circuits, 494
- Pseudo-emitter-coupled logic (PECL), 270, 271
- PSP, 75
- p-type/intrinsic/n-type (PIN) diodes, 44
- Pull-in range, 282
- Pull-out range, 282
- Pump laser, 56
- PXC, 480

- QCSE, 48
- QoS, 175, 179, 300, 489
- Quality-of-service (QoS), 175, 179, 300, 489
- Quantum confined stark effect (QCSE), 48, 49
- Quantum wells, 49
- Quasi-associated signaling, 525
- Queue locations, 400
- Queue structures, 389
- Queuing systems, 390

- Raman amplifier, 55, 59, 61, 62, 95
- Raman scattering, 59
- Random early detection, 405
- Random early drop (RED), 206
- Random jitter, 285
- Ray propagation, 36
- Read-only memory (ROM), 252
- Reamplification, 439
- Receiver-based flow control, 155, 156
- Receiver window, 153, 175
- RED, 206
- Refractive index, 36, 76
- Regeneration, 437, 438
- Regeneration equipment, 460
- Regenerators, 21
- Relaxation oscillators, 277
- Reliable flooding algorithm, 171, 172
- Remotely reconfigurable OADMs (ROADMs), 101
- Request-grant cell switches, 413
- Request-grant protocol, 415
- Reshaping, 439

- Resilient packet ring (RPR), 84, 196
- Retiming, 439
- Ring oscillators, 276
- Ring topology, 10
- ROADM, 101
- Round-robin mechanism, 406
- Route, 454
- Route change event, 454
- Route flap, 454
- Route mixture, 454
- Route packing, 454
- Router, 22, 23, 452, 455
- Router advertisement, 455
- Router architecture, 475
- Router discovery, 455
- Route reflector, 455
- Router internals, 474
- Routers discovery, 455
- Routing, 17, 298, 437, 438
- Routing equipment, 472
- Routing function, 452
- Routing information protocol (RIP), 453
- Routing layer, 17
- Routing table, 168
- RPR operation, 197
- RPR topology discovery, 199
- RPR, 184, 196

- SANs, 7, 8, 210, 211
- Satellite regenerator, 462
- Saturated unicast, 364
- SBS, 80
- Scrambling, 130
- SDH, 111, 127, 346
- Second window, 38
- Second-order PMD, 75
- Section overhead (SOH), 117, 124
- Section, SONET, 115
- Self-phase modulation (SPM), 72, 78
- SERDES, 225, 233, 237, 240, 250, 269
- Serial interfaces, 232
- Service-oriented architecture (SOA), 460
- Shortest route, 174
- Signal attenuation, 438
- Signal dispersion, 438
- Signal nonlinearities, 438
- Signal preemphasis, 289
- Signal reflections, 289
- Signaled circuits, 494
- Signal-spontaneous current noise, 58
- Simple network management protocol (SNMP), 497
- Simple optical cross-connects, 96
- Single-mode fiber (SMF), 36, 38, 67

- Single-stage fabrics, 339
- Single-stage switch, 303
- Sinusoidal jitter, 285
- Sliced request-grant switches, 425
- Sliced single-stage SNB TDM fabrics, 358
- Sliding window without selective
 - acknowledgments, 157
- Slow-wave electrodes, 54
- SMC, 131
- SMF, 36, 38, 67
- Snell's law, 35
- SNMP, 497
- SNR, 58
- SOA, 460
- SOC, 221
- SOH, 117
- Soliton propagation, 79
- SONET, 24, 111, 190, 195, 248, 346, 481, 500
- SONET ADM, 21, 128, 251
- SONET bandwidth rates, 113
- SONET byte stuffing, 133
- SONET clock distribution, 130
- SONET frame, 18
- SONET framer chip, 250
- SONET framing, 117
- SONET line, 115
- SONET minimum clock (SMC), 131
- SONET network, 116
- SONET OEO regenerator, 128
- SONET path, 115
- SONET reference model, 482
- SONET scrambling, 129
- SONET section, 115
- SONET serializers and deserializers
 - (SERDES devices), 225, 233, 237, 240, 250, 269
- SONET SPE, 126
- SONET streams, 120
- SONET STS multiplexing hierarchy, 119
- SONET terminal multiplexer, 129
- SONET transmission rates, 112
- SONET virtual tributaries, 125, 126
- Source port number, 151
- Space-time-space switching, 374
- SPE, 120
- Spectral width (linewidth), 39
- SPI, 236, 237
- SPM, 72
- Spontaneous-spontaneous current noise, 58
- SRAM, 221, 252
- SRS, 59, 61, 81
- Ssthresh, 164
- Static random access memories (SRAMs), 221
- Stimulated Brillouin scattering (SBS), 80
- Stimulated emission, 42
- Stimulated Raman scattering (SRS), 59, 61, 81
- Stimulated scattering, 80
- Stokes wave, 59, 81
- Stop-and-wait delays, 156
- Stop-and-wait scheme, 156
- Storage area networks (SANs), 7, 8, 210
- STP, 471
- Strictly nonblocking design, 349
- STS, 113
- STS-1 building block, 117
- STS-1 frame format, 118, 126
- STS-1 frame, virtual tributaries, 126
- Subpermutations, 367
- Support for priorities, 392
- Switched Ethernet, 470
- Switches, 22, 23, 96, 294
- Switching, 17, 27, 294, 436, 437, 438
- Switching architecture, 98
- Switching equipment, 464
- Switching function, 448
- Switching of cells and/or packets, 300
- Switching of physical circuits, 298
- Switching of time-division-multiplexed signals, 299
- Switching technology, 13
- Synchronous digital hierarchy (SDH), 111, 127
- Synchronous optical network (SONET), 24, 111, 190, 195, 248, 346, 481, 500
- Synchronous payload envelope (SPE), 118, 120
- Synchronous time-division multiplexing, 14
- Synchronous transport signal (STS), 113
- System packet interface (SPI), 236
- System-on-chip (SOC), 221
- TCP, 149, 157, 162, 164
- TCP byte stream concept, 150
- TCP connection round-trip effects, 177
- TCP flow control, 155
- TCP header format, 151
- TCP/IP protocol suite, 138, 140
- TCP receiver window, 159
- TCP sliding window, 158, 161
- TCP transmitter flow control modes, 163
- TCP windowed transmission, 157
- TDM, 14, 112, 298, 344, 345, 442
- Temporal alignment, 348
- Terminal multiplexers (TMs), 114
- Thin (low-bandwidth) pipes, 178
- Third window, 39

- Through-timing clock exchange, 131
- TIA, 226, 266
- Time-division multiplexing (TDM), 14, 112, 298, 345, 442
- Time-slice architecture, 247, 248, 249
- Time slot interchange (TSI), 465
- Time-space multistage TDM fabrics, 362
- Time to live (TTL), 148, 194
- TIR, 33
- TM, 114
- Token bucket policing, 404
- Top-bottom methodology, 260
- Total internal reflection (TIR), 33
- Traffic engineering of optical channels, 517
- Training loops, 284
- Transceiver, 269
- Transient chirp, 46
- Trans-impedance amplifier (TIA), 226, 266, 272
- Transmission channel technology, 433
- Transmission class, 433
- Transmission control protocol, 149, 157, 162, 164
- Transmission control protocol/Internet protocol (TCP/IP), 138, 140
- Transmission media, 2
- Transmission mode, 433
- Transmitter-based flow control, 155, 162
- Transparent support of Ethernet, 195
- Transponder, 268, 269, 462
- Transport, 17
- Transport layer, 139, 435
- Transport networks, 139
- Transport network survivability, 526
- Transport overhead, 118
- Transport streams (TS), 443
- TSI, 465
- TSI architecture, 468
- TS (transport streams), 443
- TTL, 148, 194
- Tunable lasers, 102
- Tunnel, 48
- Two-dimensional switching, 98
- Two-fiber SONET/SDH ring, 484
- Type of service (TOS) , 147

- UDP, 140
- UI (unit integrals), 285
- ULSI, 220
- Ultralarge-scale integration (ULSI), 220
- UNI, 513
- Unidirectional path-switched ring (UPSR), 485
- Unit integrals (UIs), 285

- Unshielded twisted pair (UTP), 2
- UPSR, 485
- User datagram protocol (UDP), 148, 444
- UTP, 2

- Valence band (VB), 48
- Variable-bit-rate (VBR) services, 189
- Varying port configurations, 350
- VB, 48
- VBR, 189
- VCI, 189
- VCO, 275
- VCSEL, 43, 82
- Vector, 306
- Velocity matching, 51
- VERILOG, 258
- Vertical signal polarization mode, 461
- Vertical-cavity surface-emitting lasers (VCSELs), 43, 82
- Very high speed integrated circuit (VHSIC) hardware description language (VHDL), 257
- Very large-scale integration (VLSI), 220
- VHDL, 258
- Video router switch, 451
- Virtual channel indicators (VCIs), 189
- Virtual local area network (Ethernet) switch, 451
- Virtual path indicators (VPIs), 189
- Virtual private networks (VPN), 24, 25, 195
- Virtual tributaries (VTs), 125
- VLSI, 220
- VLSI design methodology, 253
- Voice over IP (VoIP), 13
- Voice switch, 450
- VoIP switch (soft switch), 452
- Voltage-controlled oscillator (VCO), 275
- VPI, 189
- VPN, 24, 25, 195
- VT, 125

- WAN, 7, 183
- Water peak, 38
- Wavefront arbiter cell, 420
- Waveguide dispersion, 64
- Wavelength blocking problem, 103, 104
- Wavelength-conversion, 99
- Wavelength-division multiplexing (WDM), 13, 57, 87, 103
- WDM, 13, 57, 87, 103
- WDM bandwidth capacity, 89
- WDM grooming, 447
- WDM network protection, 105

- WDM network provisioning, 102
- WDM networks, 102
- WDM principle of operation, 89
- WDM regenerators, 95
- WDM terminal, 21
- Weighted round-robin mechanism, 406
- Wide area networks (WANs), 7, 183
- WiFi 802.11, 5
- Window size, 152
- Wireless communications, 5
- XPM, 80

