

# Index

- 3G cellular networks, 17
- 509 certificate, 145
- 802.11i, 144
- 802.15.5, 270
- 802.16 mesh networks, 229
- 802.16j, 280
- 802.1D bridging, 262
- 802.1X, 142
  - authentication, 156
- a control subframe, 278
- access categories (ACs), 53
- access point (AP), 248
- access routers (AR), 168
- accounting management, 165
- acknowledgement optimization, 128
- acknowledgements (ACKs), 125, 234
- active queue management (AQM), 234
- active scanning, 254
- ad hoc
  - networks, 2
  - on-demand distance vector (AODV), 87
  - routing, 1
  - traffic indication message (ATIM), 171
  - transport protocol (ATP), 129
- adaptive
  - antenna control, 226
  - detection rate control (ADTFRC), 130
  - modulation and coding, 17, 224
  - pacing, 127
  - rate control, 51
  - routing, 90
  - TCP protocol (ATCP), 129
- additional authentication data (AAD), 143
- additive-increase multiplicative-decrease (AIMD), 129
- address resolution protocol (ARP), 75
- adjacent channel rejection, 43
- aggregation, 34
- airtime cost, 100, 263
- amplify and forward scheme, 28
- amplitude and phase responses, 42
- announcement traffic indication message (ATIM), 260
  - window, 68
- antenna switching, 21
- AODV-ST, 107
- application layer, 2, 237
- arbitrarily placed infrastructure nodes, 199
- arbitrary inter-frame space(AIFS), 53
- arbitrary networks, 181
- asymptotic analysis, 180
- asymptotic capacity, 210, 219
- asynchronous power save (APS), 172
- asynchronous transfer mode (ATM), 57, 215
- authentication, 138
  - and key management (AKM), 152
- authenticator, 142
  - MP, 157
- automatic gain control (AGC), 33
- autonomic, 14
- background noise, 190
- backhaul access, 6
- backoff, 51
- BACnet (Building Automation and Control network), 2, 11
- bandwidth–delay product (BDP), 124
- base station (BS), 57
- basic service set (BSS), 68, 248
- beacon interval, 70, 261
- beacon period (BP), 272
- beaconless routing, 117
- beamforming, 21, 227
- Bellman–Ford, 109
- bidirectional traffic, 212
- binary convolutional code (BCC), 34
- bipartite subgraphs, 80
- bipartite topology, 78
- bit error rate (BER), 18, 79, 225
- blackouts, 124
- Bluetooth special interest group, 248
- bottleneck link capacity (BLC), 98
- broadband home networking, 1, 7
- broadcasting, 92
- Brownian motion model, 202
- brute-force attack, 138
- building automation, 1, 11

- call admission control, 282
- capacity and delay tradeoff, 202
- capacity bounds, 180
- capacity region, 238
- capacity-aware routing (CAR), 109
- care-of-address (CoA), 169
- carrier-to-interference ratio (CIR), 19
- cellular systems, 6
- centralized MAC, 49
- centralized scheduling, 279
- challenge–response, 140
- channel
  - assignment, 81
  - bandwidth, 38
  - coding, 17
  - fading, 173
  - hopping, 71
  - jamming, 138
  - sounding, 34, 43
  - state information (CSI), 19, 41, 228
  - switching, 29
  - time allocation (CTA), 172
- cipher block key chaining message authentication code (CBC-MAC), 143
- clean-slate protocol architecture, 241
- clear channel assessment (CCA), 44
- client meshing, 4
- client WMNs, 4
- closed-loop control system, 225
- clustered-OFDM, 162
- Code Division Multiple Access (CDMA), 13, 50
  - MAC, 63
- coded cooperation, 28
- coding rate, 233
- cognitive radios, 17, 31
- common channel framework (CCF), 258
- common management information protocol (CMIP), 165
- common part sublayer (CPS), 56
- community and neighborhood networking, 1, 8
- compatibility, 6
- configuration management, 165
- congestion control, 82, 233
  - signaling, 260
- connection admission control, 233
- connection-oriented, 123
- connectionless, 123
- constellation mapping, 35, 41
- constructive lower bound, 184
- contention access period (CAP), 62, 171
- contention free period (CFP), 62, 171
- contention period (CP), 171
- contention windows, 53
- controllable factors, 175
- controlled access CDMA (CA-CDMA), 64
- convex hull, 238
- cooperative communications, 27
- cooperative diversity, 27
- coordinated distributed scheduling, 279
- coordinated scheduling, 61
- counter-attack, 139
- counting to infinity, 256
- cross-layer
  - cooperation, 82
  - design, 83, 215
  - optimization, 20, 216
  - solution, 82
- cryptographic protocols, 139
- CSI matrices, 42
- CSMA/CA, 14, 52
- CTS, 64
- cumulative distribution function (CDF), 191
- cyclic redundancy check (CRC), 34
- cyclic shift diversity (CSD), 36
- data encryption standard (DES), 146
- data plane, 32
- data subframe, 278
- datagram congestion control protocol (DCCP), 125, 133
- decode and forward scheme, 28, 220
- deficit round robin (DRR), 62
- delivery traffic indication message (DTIM), 260
- destination sequence number (DSN), 256
- deterministic fluid model, 217
- device synchronized power save (DSPS), 172
- digital imaging, 267
- digital signal processing, 17
- digital signature, 147
- digital subscriber line (DSL), 8
- Dijkstra's algorithm, 109
- direct and indirect performance parameters, 93
- direct mesh routing, 170
- direct sequence
  - CDMA (DS-CDMA), 63
  - spread spectrum (DSSS), 63, 267
  - UWB (DS-UWB), 271
- directional
  - and smart antennas, 13
  - antennas, 4, 20
  - backoff, 52
  - communications, 20
- distance vector routing, 102
- distance-1 edge coloring (D1EC), 81
- distributed
  - code assignment, 63
  - joint channel and routing, 118
  - MAC, 49
  - mobility management, 166
  - reservation protocol (DRP), 272
  - scheduling, 56
  - system (DS), 248
- DS service (DSS), 251
- dynamic frequency selection (DFS), 82, 274
- dynamic host configuration protocol (DHCP), 277
- dynamic source routing (DSR), 87

- ease of use, 14
- eavesdropping, 138
- ECMA (European Computer Manufacturers' Association), 62, 272
- effective number of transmissions (ENT), 97
- embedded systems, 2
- emergency/disaster networking, 12
- encoder parser, 34
- encryption, 138
- end-to-end
  - delay, 80
  - QoS, 103
  - rate control, 233
  - transmission, 14, 131
- enhanced distributed channel access (EDCA), 53, 257
- enterprise networking, 1, 9
- equal gain combining, 22
- ergodic, 191
- error resilience, 17
- evolution capability, 242
- exact capacity, 212
- expected
  - busy time (EBT), 98
  - data rate (EDR), 99
  - transmission contention degree (TCD), 99
  - transmission count (ETX), 95
  - transmission on a path (ETOP), 96
  - transmission time (ETT), 97
- explicit congestion notification (ECN), 126
- explicit DRP, 273
- explicit link failure notification (ELFN), 124
- exposed node, 52
- extended distributed channel access (EDCA), 171
- extended service set (ESS), 251
- extensible authentication protocol (EAP), 142
  - MD5, 142
  - over LANs (EAPOL), 142
  - PSK, 142
  - transport layer security (EAP-TLS), 142
  - TTLS, 142
- fair end-to-end bandwidth allocation (FEBA), 61
- fast fail-over, 88
- fast handoff, 265
- fast route rediscovery, 169
- FAST TCP, 131
- fault management, 165
- fault tolerance, 6, 111
- feasible throughput, 181
- FEC
  - coding, 34
  - encoder, 35
- FH spread spectrum (FHSS), 63
- firmware, 51
- fixed frequency interleaving (FFI), 272
- fixed RS (FRS), 280
- Flash OFDM, 227
- foreign agent (FA), 166, 168
- forward link, 23
- four-way handshake, 145
- frame aggregation, 226
- frame delivery rate (FDR), 109
- frame-aggregation, 133
- frequency
  - agile radios, 31
  - agile/cognitive radios, 13
  - division duplex (FDD), 23
  - hopping CDMA (FH-CDMA), 63
  - planning, 31, 282
  - selective fading, 18
- full mesh, 268
- full-optimization design, 236
- general-purpose computer, 2
- geographic routing, 104, 115
- GPS, 116
- greedy algorithm, 116
- greenfield format, 32
- greenfield PLCP preamble, 36
- group transient key (GTK), 142
- guard interval (GI), 36
- HCF controlled channel access (HCCA), 53, 257
- heterogeneity, 125
- heterogeneous access technologies, 83
- heterogeneous QoS, 222
- hidden nodes, 52, 226
- hierarchical fair scheduling, 227
- hierarchical routing, 104, 114
- high rate (HR), 268
- high throughput (HT), 31
- home agent (HA), 166, 168
- hop count, 94
- hop delay, 206
- hop-by-hop control, 133
- hop-by-hop retransmission, 131
- horizontal decomposition, 218
- host-routing, 6
- HT greenfield short training field (HT-GF-STF), 33
- HT mixed format, 32
- hybrid
  - ARQ, 83
  - coordination function (HCF), 53
  - wireless mesh protocol (HWMP), 255
  - WMNs, 4
- IEEE
  - 802 standards committee, 245
  - 802.11, 1, 2
  - 802.11a, 17
  - 802.11e, 53
  - 802.11f, 167
  - 802.11i, 141
  - 802.11n, 13, 24
  - 802.11r, 167
  - 802.11s, 54, 248

- 802.15, 2
- 802.15.3, 62
- 802.16, 2
- 802.16e, 247
- imperfect MAC, 221
- imperfect scheduling, 241
- imple network management protocol (SNMP), 165
- implicit DRP, 273
- implicit feedback beamforming, 41
- independent and identically distributed (i.i.d.), 180
- independent basic service set (IBSS), 171
- information elements (IEs), 253
- information security, 138
- infrastructure meshing, 3, 4
- infrastructure support, 194
- infrastructure WMNs, 211
- infrastructure/backbone WMNs, 2, 4
- initialization vector (IV), 140
- integrated routing and MAC scheduling algorithm (IRMA), 108
- integrity check value (ICV), 141
- inter-arrival times, 206
- inter-cluster routing, 114
- inter-flow parameters, 93
- inter-path coupling, 91
- inter-system authentication, 164
- interference avoidance, 88
- interference nulling, 227
- interference-aware channel allocation, 177
- interference-aware resource usage (IRU), 98
- interfering neighbors, 186
- interleaver, 35
- internet backbone, 168
- internet congestion control, 235
- internet control message protocol (ICMP), 126
- Internet Engineering Task Force (IETF), 245
- internet engineering task force (IETF), 134
- internet service providers (ISPs), 1
- interoperability, 6
- interworking, 261
- intra-mesh congestion control, 259
- inverse discrete Fourier transform (IDFT), 36
- jitter, 14
  - joint channel allocation and routing, 230
  - joint channel assignment and routing, 117
  - joint optimization, 82
- K-connected topologies, 177
  - k-nearest-cell routing, 196
  - key confirmation key (KCK), 143
  - key encryption key (KEK), 143
  - key hierarchy, 143
- L2.5 routing, 119
  - Landau symbol, 180
  - layered protocol design, 216
  - licensed bands, 274
  - light client management routing (LCMR), 104
  - lightweight MP, 260
  - line-of-sight (LOS), 5, 274
  - link adaptation, 224
    - techniques, 17
  - link and neighbor management, 277
  - link capacity, 231
  - link quality, 91
    - and congestion aware (LQCA), 99
    - source routing (LQSR), 106
  - link state routing, 102
  - link-aware reliable transport protocol (LRTP), 132
  - link-centric capacity, 239
  - link-layer retransmission, 132
  - load and interference balanced routing algorithm (LIBRA), 108
  - load balancing, 89
    - routing, 230, 236
  - load-aware channel assignment, 231
  - local area network (LAN), 245
  - location services, 170
  - loosely coupled cross-layer design, 39, 222
  - loss differentiation algorithms (LDAs), 130
  - low rate (LR), 270
  - low-density parity check (LDPC) coding, 34
  - lower bound, 187
- man-in-the-middle, 138
  - management channel time allocations (MCTAs), 172
  - management information base (MIB), 99, 275
  - management plane, 32
  - master session key (MSK), 149
  - max-min algorithm, 132
  - maximum likelihood detection (MLD), 24, 25
  - maximum ratio combining (MRC), 22
  - medium access control (MAC), 49
    - layer congestion control, power management, 254
    - packet data unit (MPDU), 143
    - service data units (MSDU), 251
- mesh
  - access point (MAP), 251
  - backbone, 168
  - beacon collision avoidance (MBCA), 258
  - BS, 277
  - clients, 1, 2, 168
  - cluster, 277
  - connectivity, 6
  - deterministic access (MDA), 259
    - node, 265
    - opportunity (MDAOP), 259
  - domain, 168
  - four-way handshake, 158
  - gateway, 168
  - ID, 254
  - key distribution key (MKDK), 149
  - key distributor (MKD), 149

- key hierarchy, 157
- key holder security association, 157
- key transport pull protocol, 158
- key transport push protocol, 158
- modes, 275
- peer link establishment, 254
- point (MP), 251
- portal, 251
- PTK for key distribution (MPTK-KD), 150
- routers, 1, 2, 168
- security association (MSA), 149
- security capability information element (MSCIE), 150
- security configuration, 150
- SSs, 277
- mesh authenticator (MA), 149
- PMK (PMK-MA), 152
- mesh point portals (MPPs), 261
- message
  - forgery, 138
  - integrity, 138
  - integrity check (MIC), 139
  - replay, 138
- metropolitan area network (MAN), 10, 245
- Michael, 141
- minimum mean square error (MMSE), 23
- MKD domain (MKDD), 152
  - ID (MKDD-ID), 150
- mobile
  - backhaul, 10
  - delay, 206
  - IP, 166
  - mesh IP, 167
  - mesh networks, 10
  - multihop relay (MMR), 280
  - RS (MRS), 281
  - stations (MSs), 280
- mobile ad hoc networks (MANETs), 49, 245
- mobility, 7
  - management, 166
- modulation and coding scheme (MCS), 34
  - index, 38
- MSA four-way handshake, 154
- MSA handshake information element (MSAIE), 151
- multi-antenna communication, 20
- multi-antenna systems, 17
- multiband-OFDM (MB-OFDM), 224
- multicast routing, 122
- multichannel
  - hidden node, 66
  - MAC, 66
  - routing, 117
  - system, 29
  - topology formation, 254
  - unification protocol (MUP), 74
- Multichannel operation, 221
- multihop wireless network, 5
- multimedia, 267
- multipath mesh (MMESH) routing, 112
- multipath propagation, 18
- multipath routing, 111, 236
- multiple access interference (MAI), 64
- multiple input multiple output (MIMO), 17, 24, 221
  - systems, 13
- multipoint relays (MPRs), 257
- multipoint-to-multipoint communications, 6
- multiradio chipsets, 13
- multiradio LQSR (MR-LQSR) routing, 106
- multiradio/multichannel systems, 13
- multisystem security, 137
- multitier security, 137
- multitransceiver, 74
- negative ACK (NACK), 132
- network
  - access server (NAS), 149
  - allocation vector (NAV), 99
  - asymmetry, 124
  - capacity, 179
  - coding, 122
  - entry process, 59, 277
  - interface cards (NICs), 1
  - management, 283
  - security, 138
  - topology, 7, 87
  - utility maximization (NUM), 217
- network-wide parameters, 93
- next hop neighbor, 119
- node-centric capacity, 238
- nomadic RS (NRS), 281
- non-adjacent channel rejection, 43
- non-high-throughput (non-HT), 32
  - long training field (L-LTF), 32
  - short training field (L-STF), 32
  - signal (L-SIG), 32
- non-line-of-sight (NLOS), 5, 274
- non-MDA node, 265
- non-real-time traffic, 123
- NP-complete, 81
- NP-hard, 80
- null data packet (NDP), 43
- on-demand routing, 255
- open system authentication, 140
- open systems interconnection (OSI), 215
- operator objective functions, 218
- optimality principle, 88
- optimization decomposition, 216
- order optimal, 219
- orthogonal frequency division multiple access (OFDMA), 275
- orthogonal frequency division multiplexing (OFDM), 17, 50, 224, 227
- orthogonal rendezvous routing (ORR), 105
- out-of-order (OOO), 127
  - transmission, 182

- P2P communications, 12
- packet error rate (PER), 19
- packet loss rate (PLR), 98
- packet radio network (PRN), 176
- pairwise master key (PMK), 142, 149
- pairwise transient key (PTK), 142
- partial mesh, 268
- passive scanning, 254
- path capacity, 231
- path loss, 18
- pattern diversity, 22
- peer link
  - confirm, 154
  - management, 152
  - open, 154
  - setup, 154
- peer-to-peer (P2P) communications, 6
- per-flow parameters, 93
- per-hop packet pair delay (PPD), 95
- per-hop RTT, 94
- per-link parameters, 93
- per-node parameters, 93
- per-node throughput capacity, 201
- perfect scheduling, 241
- performance benchmark, 119
- performance management, 165
- personal area network (PAN), 245
- physical carrier sense, 52
- physical layer, 2, 18, 237
  - convergence procedure (PLCP), 32
  - management entity (PLME), 32
  - PLCP protocol data unit (PPDU), 32
  - service data unit (PSDU), 32
- physical medium dependent (PMD) sublayer, 32
- physical model, 182
- piconet synchronized power save (PSPS), 172
- pilot subcarriers, 38
- planar disk, 189
- PLCP preamble, 36
- point-to-multipoint (PMP), 56
  - mode, 274
- polarization diversity, 22
- port access entity (PAE), 145
- power control, 171
- power management, 171
- power-efficient routing, 88
- power-save mode, 260
- pre-shared key (PSK), 140, 149
- preamble field, 36
- primary channels, 81
- prioritized contention access (PCA), 62, 272
- privacy and key management (PKM), 146
- proactive tree-based routing, 255
- probabilistic routing, 196
- probe packets, 95
- programmable MAC, 13
- project authorization request (PAR), 251
- protocol interoperability, 242
- protocol model, 182
- protocol reference model, 32
- quality of service (QoS), 215, 282
  - access point (QAP), 54
  - routing, 232
  - station (QSTA), 54
- radar signals, 83
- radio aware optimized link state routing (RA-OLSR), 255, 257
- radio-metric AODV, 256
- radio-on-chip (RoC), 66
- rake receiver, 23
- random access based MAC, 229
- random access MAC protocol, 50
- random early detection (RED), 127
- random networks, 181
- random walk (RW) model, 202
- randomly placed infrastructure nodes, 197
- rate control, 132, 225
  - protocol (RCP), 129
- rate-adaptive framing, 225
- rational exchange, 147
- real-time protocol (RTP), 129
- real-time traffic, 123
- real-time transport protocol (RTCP), 129
- reconfigurable MAC, 85
- reconfigurable radios, 13, 31
- reduced interframe space (RIFS), 44
- regularly placed infrastructure nodes, 195
- relay queue, 206
- relay stations (RSs), 280
- relaying networks, 229
- relaying nodes, 191
- reliable multicast transport (RMT), 134
- remote authentication dial-in user service (RADIUS), 142
- request for comments (RFCs), 134
- reservation based MAC, 50
  - protocol, 229
- residual link capacity, 103
- resilient opportunistic mesh routing (ROMER), 112
- resource allocation, 232
- resource management, 282
- retransmission timeouts (RTO), 127
- reverse link, 23
- RF front end, 36
- RF technologies, 17
- RFID, 2
- Rivest Cipher 4 (RC4), 140
- robust security network (RSN), 145
  - association (RSNA), 145
- root announcement (RANN), 256
- round trip time (RTT), 124
  - measurement, 75
- route discovery, 106
- route error (RERR), 256
- route maintenance, 106

- route reply (RREP), 256
- route request (RREQ), 256
- routing
  - matrix, 217
  - metric, 87
  - path selection, 87
  - protocols, 87
  - strategy, 195
- RSN information element (RSNIE), 151
- RTS, 64
  
- scalability, 2, 13, 83, 91
- scalable routing, 104, 121
- scaling law, 212
- scrambler, 34
- secondary channels, 81
- secure
  - associations, 162
  - data forwarding, 164
  - MAC protocols, 139
  - mesh network infrastructure, 163
  - routing protocol, 139, 164
  - sockets layer (SSL), 163
- security, 14
  - attacks, 137
  - management, 165
  - monitoring, 139
  - surveillance, 12
- selection relay, 28
- self-configuration, 1
- self-forming, 5
- self-healing, 5
- self-organization, 1, 5
- service access point (SAP), 32
- service set identifier (SSID), 254
- service-specific convergence sublayer, 56
- shared-key authentication, 140
- short GI, 34
- short interframe space (SIFS), 44
- signal-to-interference-noise ratio (SINR), 79
- signal-to-noise ratio (SNR), 19, 225
- single carrier (SC), 274
- single channel MAC, 52
- singular value decomposition (SVD), 26
- site survey, 7
- slate protocol design, 220
- sliding window, 235
- small office home office (SOHO), 62
- smart antenna, 23
- softMAC, 51
- software radios, 13, 18, 31
- software retransmission, 55
- source-destination throughput, 189
- space diversity, 22
- space-time
  - block coding (STBC), 34, 36
  - coding (STC), 24, 25
  - receiver, 22
  - streams, 34
- spatial mapper, 36
- spatial multiplexing, 227
- spatial reuse efficiency, 20
- spectrum spatial-reuse, 173
- spreading factors, 20
- spreading-code selection, 63
- stateful transport protocol, 131
- stateless property, 116
- static networks, 204
- stationary, 191
- stations (STAs), 248
- steerable antenna, 20
- stochastic NUM, 217
- straight-line segment, 188
- stream control transmission protocol (SCTP), 125
- stream parser, 35
- strong connectivity, 197
- sub-network access protocol (SNAP)-encoded header, 262
- subcarrier, 36
  - allocation, 226
- subscriber station (SS), 57
- supplicant, 142
- supplicant MP, 157
- switch diversity, 22
- synchronization, 254
- synchronizing MP, 258
- system-on-chip (SoC), 66
  
- task group, 248
- TCP, 124, 133, 233
  - adaptive pacing (TCP-AP), 128
  - congestion control, 234
  - Detection of Out-of-Order and Response (TCP-DOOR), 127
  - feedback (TCP-F), 126
  - friendly, 130
  - semantics, 133
  - variant, 126
  - Vegas, 131, 234
- TDMA, 13, 50
  - over CSMA/CA, 55
- temporary key (TK), 143
- temporary key integrity protocol (TKIP), 141
- throughput capacity, 181
- tightly coupled cross-layer design, 39, 222
- time division duplex (TDD), 23
- time synchronization function (TSF), 55, 68
- time-frequency code (TFC), 272
- time-to-live (TTL), 256
- timescale separation, 243
- timing synchronization function (TSF), 258
- topology broadcast based on reverse-path forwarding (TBRPF), 87
- topology control, 80, 176
- topology discovery, 91, 92

- topology-aware MAC, 14
- traffic analysis, 138
- traffic shaping, 282
- traffic specifications (TSPEC), 54
- training symbols, 36
- transmission opportunity (TXOP), 54
- transmission rate, 10
- transmit diversity, 227
- transmit power, 233
- transmit spectrum mask, 44
- transport layer, 123, 237
- transport layer protocol, 232
- transport layer security (TLS), 163
- transport protocols, 123
- triangle inequality, 188
- trustworthy, 147
- two-hop neighbors, 264
- two-phase scheduling, 193
  
- ultra wideband (UWB), 17, 62, 224
  - forum, 247
- uncontrollable factors, 175
- uncoordinated distributed scheduling, 61
- unequal modulation, 38
- unicasting, 92
- unidirectional traffic, 212
- unified channel graph (UCG), 254
- unlicensed bands, 274
- unsynchronizing MP, 261
- upfront investment, 6
- upper bound, 182
- upstream node, 260
- User Datagram Protocol (UDP), 133, 233
  - IP, 216
- user objective functions, 218
- user utility function, 217
  
- vector antennas, 24
- vertical Bell Lab Layered Space-Time (V-BLAST), 25
  
- vertical decomposition, 218
- virtual carrier sense, 53
- virtual private networking (VPN), 161
- VoIP, 222
- Voronoi cells, 186
  
- weak connectivity, 197
- weighted cumulative ETT (WCETT), 97
- WiBro, 247
- WiMAX, 6, 247
- WiMedia, 1
  - Alliance, 246
  - UWB, 272
- window optimization, 127
- windowing, 36
- wired equivalent privacy (WEP), 1, 139, 140
- wireless
  - backhaul networks, 131
  - distribution system (WDS), 252
  - HUMAN, 274
  - infrastructure, 7
  - local area networks (WLANs), 7
  - mesh networking, 1
  - mesh networks (WMNs), 1
  - metropolitan area networks (wireless MAN), 56
  - network security, 137
  - personal area networks (WPANs), 17, 62
  - sensor networks, 2
- Wireless Fidelity (WiFi), 1
  - Alliance, 141, 245
  - protected access (WPA), 140, 141
- worldwide inter-operability for microwave access (WiMAX), 1
- WPA2, 143
  
- ZigBee, 6
  - cluster label (ZiCL) routing, 115