

Index

- Absolute overlap ratio, 420
Absorptivity, 466, 468
AC-to-DC rectification, 404
Admittance, 389
Ageing
 electrical, 444
 thermal, 443
Ageing of insulation, 442
Aho, T., 147
Air gap, 15, 159, 164, 297, 430
 length
 equivalent air-gap, 476
 length, 474, 476
 effective air-gap, 169
Air-gap diameter, 301
Air-gap flux, 16, 225
Air-gap flux density, 91, 282
Air-gap flux distribution, 145
Air-gap flux linkage, 360
Air-cooled machine, 295
AlNiCo magnet, 200, 201. *See also*
 permanent magnet
Amide-imide, 435
Amorphousness, 435
Ampère's law, 3, 5, 58, 153, 156,
 205, 256, 366, 367
Anisotropic, 6, 190, 202
Anisotropy, 204
Aplac (circuit analysis), 488
Apparent power, 281, 285,
 418
Aramid fibre, 434
Aramid paper, 431
Arkkio's method, 34
Armature current, 287, 308, 404
Armature reaction, 47, 145, 153, 166, 298,
 303, 358, 371, 409. *See also* armature
 current linkage
Armature yoke, 15
Arrhenius equation, 443
Asynchronous generator, 352
Asynchronous machine, 170, 177, 283, 358
Auringer, H., 351
Balancing connector, 140. *See also* equalizer
 bar
Barkhausen jump, 185. *See also* magnetic
 material
Barkhausen noise, 185. *See also* magnetic
 material
Base value, 40
Becker, K. M., 474
BH curve, 16, 159, 175, 186
Black body, 467
Bloch wall, 183
Boundary layer, 470
 concentration, 470
 thermal, 470, 472
 velocity, 470, 472
Braided conductor, 151
Breakdown strength, 444
Breakdown voltage, 429, 440
Breakthrough field strength, 440
Brush, 48, 128, 137, 394, 404, 409, 459
Brush rocker, 412
Brushless synchronous generator, 396
Capacitance, 357
 electric, 477
 of insulation, 443

- Capacitive load, 373
- Capacitor, 370, 451
- Carter factor, 160, 369
- Carter, F.W., 160
- Characteristic length of surface, 471
- Circulating current, 261
- Clearance in air, 429
- Coenergy, 29, 31, 416
- Coercive force, 5, 202
- Coercivity, 187, 189, 200
- Coil, 50, 370, 382
- Coil group, 50, 109
- Coil span, 54, 73, 229, 247, 405
 - average, 256
- Coil turn, 306
- Commutating pole, 146, 283, 405, 446
- Commutation, 411, 413
- Commutation period, 411
- Commutator, 394, 404, 405
- Commutator machine, 47, 122, 127, 193
- Comparative Tracking Index (CTI), 430
- Condition monitoring, 449
- Conductance
 - electric, 476
 - thermal, 476, 479
- Conduction, 462, 463
- Conductivity, 6, 255, 429
 - electric, 465
 - thermal, 463, 471, 477, 480
- Conductor height, 258, 262
 - critical, 265
 - reduced, 259, 264
- Conductor transposition, 266
- Conservation of charge, 2
- Contact heat transfer coefficient, 475
- Continuous running duty, 346
- Continuous-operation periodic duty, 347
 - with electric braking, 348
 - with related load/speed changes, 348
- Convection, 462, 470
 - heat transfer coefficient, 471
- Coolant, 487
 - flow rate, 495
- Cooling, 189, 282, 462
 - open-circuit, 492
- Cooling flow rate, 495
- Corona protection, 447
- Couette Reynolds number, 461
- Coulomb's condition, 9
- Coulomb's Virtual Work method, 32
- Counterrotating field, 362, 386, 387
- Creepage current, 430, 432, 444
- Creepage distance, 430, 444, 449
- Critical angular speed, 296
- Critical conductor height, 266
- Cross-linking agent, 436
- Crystallinity, 435
- Curie temperature, 204
- Current density, 1, 256, 271, 293, 308, 412, 465
 - armature linear, 145
 - linear, 316, 388
 - linear, 23, 143, 293, 326
- Current linkage, 5, 153, 158, 180, 209
 - armature, 47, 145, 409
 - asynchronous machine, 315
 - cage winding, 320
 - commutator armature, 144
 - commutator winding, 142
 - cosinusoidal distribution, 52
 - direct component, 144
 - harmonic stator, 366
 - pole winding, 312
 - quadrature component, 144
 - rotor bar, 325
 - salient-pole winding, 51
 - sinusoidal, 301
 - slot winding, 81
 - stator, 360
 - symmetrical three-phase, 359
 - three-phase winding, 58
- Current linkage harmonic, 315
- Current ripple, 425
- Dacron®, 431
- Damper bar, 362
- Damping, 361
- Davidson, R., 414
- DC link, 426
- DC machine, 15, 156, 283
- Demagnetization curve, 207
- Density, 464

- Depth of penetration, 258
- Dielectric loss, 450
- Dielectric loss factor, 450
- Dielectric strength, 429, 432, 440
- Diolen[®], 431
- Dip and bake method, 447
- Direct-on-line (DOL), 400
- Dirichlet's boundary condition, 11, 12, 21
- Displacement current, 5
- Dissipation power, 47, 194, 312
- Distribution factor, 66, 90
- Double-salient reluctance machine, 50, 157, 291, 413, 414
- Double-salient reluctance motor, 420
- Drain, 6
- Duty cycle, 281, 347
- Duty type, 346

- Eddy current, 3, 10, 147, 187, 275, 362
- Effective torque zone, 420
- Efficiency, 307, 312, 343, 421, 427
 - of totally enclosed four-pole induction motors, 352
- Efficiency class, 352
- Electric capacitance, 477
- Electric charge, 10, 477
- Electric charge density, 1
- Electric field density, 438
- Electrical stress, 440
- Electromotive force (emf), 16, 43, 63, 153, 250, 285, 302, 322, 377
 - stator, 376
- Emissivity, 468
 - relative, 467
- EN 10106, standard, 192
- Enclosure class, 281, 343, 346
- Energy conversion, 225
- Energy conversion loop, 418
- Energy conversion ratio, 419
- Energy density, 28, 185
- Energy product, 202, 204, 205
- Epoxy resin, 437, 448
- Equalizer bar, 140. *See also* balancing connector
- Equivalent air-gap length, 476
- Equivalent circuit, 363
 - of a three-phase asynchronous motor, 335
 - of a conductor, 274
 - of a slot, 275
 - of a synchronous machine, 363
 - of an asynchronous machine, 327
 - of an end winding, 486
 - of an insulation construction, 451
 - of capacitor motor main and auxiliary windings, 356
 - of transients, 364
 - thermal, 476
- Ester-imide, 435
- Euler's number, 326. *See also* Napier's constant
- Excitation, 394
 - brushless, 395

- Fanning friction coefficient, 472
- Faraday's induction law, 3, 63, 168, 230, 257, 303. *See also* induction law
- FEP fluoropolymer, 436
- Ferraris rotor, 147
- Ferrite magnet, 201. *See also* permanent magnet
- Ferromagnetic metal, 187
- Fibre insulator, 454
- Field
 - electric, 1, 3, 429
 - magnetic, 1, 47, 226
- Field diagram, 24, 161, 165
 - orthogonal, 18, 19, 20, 21, 164, 171, 427
- Field Effect Transistor (FET), 423
- Field strength, 309, 310, 311, 366
 - air-gap, 317
 - effective, 441
 - electric, 1, 10, 432, 438
 - magnetic, 1, 3, 153, 256, 286
 - tangential, 367
- Field winding current, 370, 394
- Finite Element Analysis (FEA), 365
- Flange mounting, 343
- Fluoropolymer, 436
- Flux
 - electric, 3
 - magnetic, 3, 154, 421

- Flux barrier, 401
- Flux density, 15, 163, 283, 294
 - air-gap, 302
 - air-gap magnetic, 51
 - apparent, 174
 - electric, 1, 6
 - magnetic, 1, 153, 159, 165, 275, 318, 360
 - remanence, 187
 - saturation, 187
- Flux density distribution, 63
 - sinusoidal, 301
- Flux diagram, 18, 158
- Flux guide, 401
- Flux leakage, 225, 361
 - air-gap, 229, 230
- Flux linkage, 4, 168
 - air-gap, 169, 225, 285, 303
- Flux tube, 17
- Fourier's law, 463
- Friction coefficient, 472
- Fundamental component
 - of stator current linkage, 367
- Fundamental harmonic
 - of linear current density, 316
- Fundamental wave, 315

- Galvanic contact, 431
- Gardiner, S., 474
- Gauss's law, 3, 7
- Generator
 - asynchronous machine, 351
- Generator logic, 43, 376, 382
- Geometrical factor, 474
- Gliding discharge voltage limit, 444
- Goss texture, 191

- Haataja, J., 352
- Haefely Trench Tettex partial discharge measurement unit, 452
- Hamata, V., 163
- Hard chopping, 425
- Harmonic factor, 389, 390
- Heat
 - capacity, 477
 - contact heat transfer coefficient, 475
 - diffusion, 457
 - flow, 483
 - flow density, 467, 472, 476
 - flow rate, 463
 - heat-flow-controlled temperature source, 488, 490, 491
 - quantity of heat, 476
 - specific heat capacity, 471, 477
 - transfer, 457
 - transfer area, 463
 - transfer coefficient, 468, 472, 474
 - transfer properties, 464
- Heck, C., 189
- Heikkilä, T., 399
- Heller, B., 163
- Hot pre-wedging, 448
- Hot-spot allowance, 442
- Huppunen, J., 147
- Hysteresis loop, 189

- IC class, 346
- IEC 600112, 430
- IEC 60034, 441
- IEC 60034-1, 315, 432
- IEC 60034-4, 383
- IEC 60034-5, 346
- IEC 60034-6, 346
- IEC 60034-7, 343
- IEC 60034-8, 343
- IEC 60050-411, 47
- IEC 60085, 432
- IEC code, 344
- Impedance, 366
 - AC, 271, 272
 - cage winding, 320
 - characteristic, 453
 - measuring, 451
 - negative-sequence, 353
 - phase, 321, 322
 - positive-sequence, 353
 - rated, 40
 - rotor, 320, 368
 - synchronous, 385
- Impregnating resin, 431, 439
- Impregnating varnish, 431, 436, 437

- Impulse voltage, 442
- Inception voltage, 440
- Indifference point, 24
- Inductance, 4, 168, 278. *See also* leakage inductance
 - air-gap, 230
 - direct-axis subtransient, 365
 - direct-axis synchronous, 360, 397
 - direct-axis transient, 364
 - leakage, 216, 227, 359
 - magnetizing, 154, 221, 252, 285, 387
 - mutual, 36, 217, 226
 - phase, 321
 - quadrature-axis subtransient, 365
 - saturating reluctance machine, 417
 - self-inductance, 36, 216, 226
 - skew, 252
 - stator, 359
 - stator magnetizing, 336
 - subtransient, 362
 - synchronous, 361
 - transient, 225, 363
 - winding, 226
- Inductance ratio, 400, 402
- Induction law, 3. *See also* Faraday's induction law
- Induction motor, 15, 288, 302
- Inductive load, 373
- Insulated-Gate Bipolar (IGB) transistor, 423
- Insulating film, 432
- Insulating foil, 433
- Insulating material, 429
- Insulating resin, 429
- Insulating strength, 429
- Insulating varnish, 439
- Insulation, 429, 457
 - conductor, 431, 435
 - groundwall, 431
 - lifetime, 458
 - phase coil, 434
 - phase-to-phase, 431
 - pole winding, 431
 - slot, 431, 434
- Insulation capacity, 449
- Insulation coordination, 430
- Insulation distance, 429
- Insulation resistance, 449
- Insulator, 429
- Intermittent periodic duty, 347
 - with electric braking, 347
 - with starting, 347
- IP class, 462
- Isotropic, 6, 202
- Kapton polyimide, 435
- Kapton[®], 431
- Kaye, J., 474
- Key fitting, 220
- Key-closed slot, 446
- Kirchhoff's 1st law, 321
- Küpfmüller, K., 259
- Kurronen, P., 399
- Law of energy conversion, 26
- Lawrenson, P.J., 291
- Leakage factor, 207, 232, 233, 389, 390
- Leakage flux, 225, 227, 256
 - end winding, 227
 - pole, 227
 - slot, 225, 227
 - tooth tip, 227
- Leakage inductance, 267, 322, 349. *See also* inductance
 - air-gap, 230
 - end winding, 230, 246
 - skew, 230
 - slot, 230, 234, 247
 - tooth tip, 230, 245
- Lenz's law, 276
- Levi, E., 249
- Lindström-Dahlander connection, 126
- Linear polymer, 436
- Liner
 - slot insulation, 445
- Lipo, T. A., 259, 460
- Litz wire, 266
- Load angle, 402, 403
- Load angle equation, 375

- Loadability, 426
 - electrical, 293
 - magnetic, 294
 - mechanical, 291
- Lorentz force, 1, 320, 405, 441
- Lorentz force equation, 318
- Lorentz law, 68
- Loss
 - additional, 458, 460
 - bearing, 460, 462
 - copper, 458
 - dielectric, 430, 432, 449, 451
 - eddy current, 193, 197, 261, 297
 - electromagnetic, 460
 - end winding, 426
 - friction, 313, 327, 328, 346, 461, 476, 488
 - hysteresis, 193, 194, 423
 - iron, 192, 294, 307, 311, 327, 401, 458, 476
 - mechanical, 458, 460
 - resistive, 255, 293, 308, 313, 327, 343, 354, 458, 476, 479, 486
 - surface, 199
 - ventilator, 462
 - windage, 313, 328, 461, 462, 476
- Loss angle, 451
- Magnetic circuit, 153, 226, 283, 312, 327, 358, 375, 404, 430
- Magnetic energy, 185, 194, 235
- Magnetic equipotential surface, 18
- Magnetic force, 28
- Magnetic material, 183
- Magnetic potential difference, 154, 305
- Magnetic voltage, 156, 250, 309, 311
- Magnetizing, 312
- Magnetizing current method, 34
- Magnetizing inductance, 349
 - direct, 359
 - quadrature, 359
- Magnetomotive force (mmf), 159
- Main dimension, 282, 302
- Mass density of fluid, 474
- Mass flow rate, 472
- Mass transfer coefficient, 471
- Matsch, L. D., 355
- Maxwell
 - displacement current, 5
 - equation, 1, 2
 - stress tensor, 33
- Maxwell, J. C., 5
- Mechanical strength
 - insulation, 431
- Mechanical stress, 291, 440
- Mica, 429, 431
- Mica insulator, 433
- Mica paper, 432
- Mica tape, 448
- Miller, T. J. E., 472
- Monomer, 436
- Moody diagram, 472
- Moody friction factor, 472
- Moody, L. F., 472
- Morgan, J. D., 355
- Motor logic, 43, 376, 379
- Motor supply cable, 453
- Mylar polyester, 434
- Mylar®, 431
- Napier's constant, 326. *See also* Euler's number
- NdFeB magnet, 399. *See also* permanent magnet
- Neodymium iron boron magnet, 397. *See also* NdFeB magnet, permanent magnet
- Neodymium magnet, 202. *See also* permanent magnet
- Nerg, J., 33
- Neumann's boundary condition, 11, 12
- Newton's law of cooling, 472
- Niemelä, M., 349
- No-load curve, 384
- Nomex®, 434
- Nonsalient pole machine, 15, 169, 358, 362
- Nonsalient pole synchronous machine, 159, 283, 308
- Normal system, 97
- Nusselt number, 471, 474
- Ohm's law, 255
- Open-circuit cooling, 488, 492

- Overexcitation, 370
- Overhang, 445

- Partial discharge, 429, 443, 447, 450
- Partial discharge measurement, 451, 452
- Partial discharge strength, 431
- Paschen curve, 429, 430
- Paschen law, 429
- Per unit value, 40
- Permanent magnet, 153, 183, 200, 285, 312, 358
- Permanent magnet excitation, 395
- Permanent magnet machine, 154, 395, 397
- Permanent magnet synchronous generator, 302
- Permanent magnet synchronous machine, 303
- Permanent magnet synchronous machine (PMSM), 358
- Permeability, 6, 191, 235, 256
- Permeance, 4, 18, 161, 166
 - magnetic, 38, 235
 - magnetic circuit, 336
 - mutual, 37
- Permeance factor, 235, 369, 392
 - slot, 237, 238
- Permeance harmonics, 193
- Permittivity, 6, 429
- Phase voltage, 360
- Phasor diagram, 372
 - current, 321
 - of a nonsalient pole synchronous generator, 378
 - of a nonsalient pole synchronous motor, 380
 - of a steady-state short-circuit nonsalient pole generator, 385
 - of a steady-state, salient-pole generator, 374
 - of a synchronous generator, 378
 - of a synchronous reluctance machine, 402
 - of currents in a conductor, 271
 - of subconductor currents, 279
- Phasor diagram of a capacitor
 - of a capacitor motor, 357
- Pitch factor, 66, 90, 322

- Poisson's ratio, 291
- Polarization, 10
- Polarization curve, 207
- Pole body, 15, 50, 164, 177
- Pole shoe, 15, 165, 199, 362, 380, 388, 404
- Pole-Amplitude-Modulation (PAM), 127
- Polyamide-imide, 435
- Polyester film, 431, 434
- Polyester resin, 431, 437
- Polyether-etherketone (PEEK), 436
- Polyethyleneterephthalate (PETP), 434
- Polyimide film, 431, 434
- Poly-phase induction machine, 155
- Position sensorless control, 425
- Power balance
 - of an induction motor, 458
- Power factor, 281, 283, 287, 302, 307, 350, 402
 - of totally enclosed induction motors, 351
 - synchronous reluctance machine, 403
- Poynting's vector, 369
- Prandtl number, 471
- Protective paint, 431
- PTFE fluoropolymer, 436
- Pull-out torque, 348

- Radial flux electrical machine, 473
- Radiation, 462, 466
 - electromagnetic, 466
 - heat transfer coefficient, 469
- Rao, K., 474
- Rated output power, 313
- Reactance, 41, 226
 - magnetizing, 42, 353, 361
- RECo magnet, 202. *See also* permanent magnet
- Reduced contactor height, 258
- Reduced system, 97
- Reflection factor, 454
- Reflectivity, 466
- Relative value, 41
- Reluctance, 4, 154, 304
- Reluctivity, 11
- Remanence, 352
- Remanence flux density, 154
- Resin Rich (RR) method, 448

- Resistance, 25, 255, 321, 322
 - AC, 259, 458
 - DC, 259, 333, 460
 - DC, field winding, 365
 - electric, 476
 - junction thermal resistance, 475
 - phase, 323
 - thermal, 477
 - thermal resistance of convection, 472
 - thermal resistance of radiation, 468
 - winding, 458
- Resistance factor, 259, 260, 264
- Resistivity, 188, 197, 269, 464
- Reynolds number, 471
 - critical, 471
 - tip, 462
- Richter, R., 199, 237, 238, 259, 370
- RMS value, 283, 285, 303
- Roebel bar, 151, 266, 267
- Rotating-field machine, 182
- Rotor bar, 334
- Rotor field winding current, 358
- Rotor stack, 475
- Rotor teeth, 181, 304
- Rotor yoke, 15, 154, 177, 181, 283, 311

- Saari, J., 461
- Saber* (circuit analysis), 488
- Sabersky, R., 474
- Saliency, 154, 387
- Salient-pole machine, 14, 358, 362
- Salient-pole synchronous machine, 156, 283, 359
- Salminen, P., 399
- Sankey diagram, 459
- Sastri, V., 474
- Saturation, 147, 179, 238, 304, 416, 427
- Saturation factor, 305
- Saturation magnetization, 185
- Saturation polarization, 185
- Schering bridge, 451
- Schuisky, W., 387, 389, 462
- Shaded-pole motor, 358
- Shearing stress, 441
- Short-time duty, 347
- Short-circuit ring, 220, 249, 322, 323, 358, 362, 461
- Short pitching, 73
- Silicone resin, 431
- Skewing, 220, 228, 339, 362
- Skewing factor, 66, 250, 322
- Skin effect, 3, 151, 225, 256, 266, 267, 271, 334
 - stator winding, 287
- Skin effect factor, 458
- Slip, 147, 193, 243, 322, 328, 386
 - fundamental, 368
- Slip ring, 48, 147, 394
- Slip-ring machine, 329
- Slot, 237, 334, 404, 479
- Slot angle, 53, 250
- Slot closer, 431
- Slot filling, 448
- Slot key, 445
- Slot number
 - cage winding, 340
- Slot pitch, 53, 158, 252, 285, 302, 377
 - rotor, 362
 - stator, 340
- Slot separator, 445
- Solid rotor, 295, 298
- Solid-rotor construction, 366
- Solution of a thermal equivalent circuit, 493
 - nodal point method, 493
- Solvent, 436
- Source, 6
- Source current, 10
- Space factor, 308
- Sparking, 444
- Specific heat capacity, 464
- Spice* (circuit analysis), 488
- Squirrel cage induction motor, 323, 475
- Squirrel cage rotor, 48
- Stack, 219. *See also* stator stack
- Stamping, 348
- Stator slot, 158, 164, 282, 447
- Stator slot insulation, 445
- Stator stack, 250, 256, 282, 447, 475
- Stator teeth, 181, 309

- Stator yoke, 154, 177, 181, 283, 309, 311, 489
- Stefan-Boltzmann constant, 467
- Stefan-Boltzmann equation, 467
- Stoke's theorem, 12
- Stoll, R., 259
- Stress tensor, 33
- Stroke angle, 420
- Subconductor, 259, 260, 261
- Surahammars Bruk, 192, 195
- Surge (impulse) wave, 453
- Surge comparison testing, 449
- Switched reluctance (SR) machine, 15
- Switched reluctance machine (SR machine), 414, 415
- Switching overvoltage, 441
- Symmetry condition, 99
- Synchronous inductance
direct-axis, 363. *See also* Inductance
quadrature-axis, 363. *See also*
Inductance
- Synchronous machine, 15, 358
permanent magnet, 358
separately excited, 358
- Synchronous reluctance machine, 154, 155
- Synchronous reluctance machine (SyRM), 358, 400
- Tangential stress, 23, 33, 283, 284, 301.
See also Maxwell
- $\tan\delta$ curve, 450
- $\tan\delta$ measurement, 442, 449, 451
- $\tan\delta$ measurement circuit, 451
- $\tan\delta$ value, 450
- Taylor number, 474
modified, 474
- Taylor vortex flow, 474. *See also*
Taylor-Couette flow
- Taylor-Couette flow, 474
- Teeth, 128, 486
- Teflon, 436
- Temperature gradient, 463
- Temperature index, 442
- Temperature rise, 291, 312, 320, 347, 442, 457, 481
- Temperature rise allowance, 442
- Tensile strength, 440
- Terminal voltage, 330, 352, 377
fundamental, 303
stator, 376
- Terylene®, 431
- Thermal class, 442, 458
- Thermal conductivity, 463
- Thermal equilibrium, 348
- Thermal equivalent circuit
of a winding, 479
of an electrical machine, 479
solution of, 493
- Thermal network, 488
of coolant flow, 490
- Thermal resistance, 282, 293, 431, 434, 442, 443, 465
of convection, 472
of junction, 475
of radiation, 468
per unit length, 477
- Thermal stress, 440, 443
- Thermoplastic, 431, 435
- Time constant, 365
- Time-harmonic field strength vector
amplitude, 367
- Tooth, 15, 173, 283
- Torque, 1, 30, 34, 50, 157, 284, 301, 312, 319, 476
asynchronous, 387
braking, 399
cogging, 399
drag, 461
electromagnetic, 329, 416
pull-out, 330, 399, 402
reluctance, 361, 376
SR machine, 415
starting, 147, 331, 386, 388, 391
synchronous, 338
- Torque coefficient, 461
- Torque production, 34, 147, 156, 171, 284, 303, 402. *See also* torque.
asynchronous machine, 315
- Torque ripple, 425
- Totally enclosed fan-cooled induction motor (TEFC), 491

- Track resistance, 430, 438
- Transmissivity, 466
- Trickle Impregnation, 447

- Underexcitation, 370

- V curve, 394
- Vacuum Pressure Impregnation (VPI), 440, 447
- Varnish
 - alkyd-based, 437
 - oil-based, 436
 - polyester, 437
 - polyester-based, 437
 - surface, 438
- Ventilating duct, 171, 172
- Virtual work, 25, 159
- Viscosity
 - dynamic, 461, 471
 - kinematic, 471
- Vogt, K., 259
- Voltage phasor diagram, 63, 80
- Voltage strength, 430, 431, 444, 449

- Weibull exponential distribution, 444
- Weiss domain, 183
- White body, 467
- Wiat, A., 296
- winding
 - random-wound, 446
- Winding
 - armature, 47, 127, 153, 273, 302, 309, 362, 396, 404, 405
 - base, 102, 182
 - cage, 148, 232, 308, 309, 321, 362, 369, 386
 - cage, asymmetric, 388
 - chorded. *See also* short-pitch winding
 - coil, 228
 - commutating, 47
 - commutating pole, 404, 410
 - commutator, 48, 122, 128, 129
 - compensating, 47, 145, 405, 409, 410
 - concentrated, 446
 - concentrated pole, 14
 - concentric, 54, 92
 - Dahlander, 127
 - damper, 150, 362, 366, 386
 - diamond, 54, 71, 73, 92. *See also* lap winding
 - double-layer, 98, 137, 239
 - double-layer fractional slot, 106
 - drum armature, 137
 - end, 228, 264, 486
 - excitation, 312
 - field, 14, 47, 153, 396, 404, 405, 446
 - fractional slot, 55, 72, 92, 93, 182, 393
 - frog-leg, 138
 - full-pitch, 66, 73, 74, 228, 338, 405
 - integral slot, 55, 72, 93, 182
 - integral slot stator, 340
 - lap, 129, 131, 132, 136. *See also* diamond winding
 - magnetizing, 15, 23, 47, 153, 170, 308, 343
 - phase, 48, 54, 285, 303, 306, 360
 - pole, 446
 - poly-phase, 84, 154, 301
 - poly-phase slot, 54
 - rotating-field, 47
 - rotor, 248
 - salient-pole, 48
 - short-pitch. *See also* chorded winding
 - short-pitched double-layer, 338
 - shunt, 404
 - single-layer, 98
 - single-layer fractional slot, 106
 - single-layer stator, 71
 - slot, 48, 179, 228, 255, 301, 308, 366
 - stator, 154, 232, 248, 353, 360, 366, 421, 486
 - two-plane, 53
 - wave, 137. *See also* commutator winding
- Winding current, 10, 226
- Winding factor, 4, 63, 77, 301, 302, 389
 - distribution, 61
 - of a salient-pole field winding, 366
- Wound rotor, 48

- Yoke, 404

- Zones of windings, 98