

# INDEX

- Aberfeldy bridge, 21
- American Concrete Institute (ACI),
  - design guides, 34, 128, 214
  - test methods, 121
- American Composites Manufacturers Association (ACMA), 37, 129
- Active bond length, 297
- Active strengthening system, 323
- Additives:
  - fire retardants, 68
  - low-shrink, 68
  - pigments, 68
  - release agents, 68
  - UV inhibitors, 68
- Adhesively bonded connection, 491
- Adhesively bonded strengthening system, 12, 70, 216
- Allowable Stress Design (ASD), 370
- Analysis example:
  - flexural and shear rigidity, 394
  - laminar theory, 94, 99
  - load-moment diagram, 336
  - micromechanics, 82
  - pultruded beam deflection, 399
  - timoshenko beam theory, 391
- Anchorage, 111, 245, 262, 297
- Angle of inclination, 187, 292
- Aramid fiber, 44
- ASTM test methods, 108, 118, 371
- Axial capacity, 325, 440
- Axial deformation:
  - columns, 439
  - tension members, 468
  - limits, 440, 468
- Axial load effect on shear strength, 308
  
- Balanced laminate, 93
- Balanced reinforcement ratio, 134, 146, 243
- Balloon frame, 486
- Bar spacing, 202
- Basalt fiber, 45
- Beam, 143, 227, 384
- Beam-column, 333, 436, 471
- Beam-to-column connection, 486, 492
- Bearing connection, 492, 497, 501
- Bend radius, 136, 201
- Bent bar, 133, 188
- Binder, 45
- Blast retrofit, 16
- Block shear failure, 499, 509, 511
- Bolt torque, 491, 492
- Bolted connection, 487, 496, 504
- Bond critical effective stress, 205
- Bond critical strengthening system, 218, 220, 293
- Bond dependent coefficient, 231
- Bond reduction coefficient, 297
- Bond related coefficient, 169
- Bond strength, 204
- Braced frame, 360, 485
- Bracing connection, 488
- Branson equation, 167, 272
- Bridge:
  - Aberfeldy, Scotland, 21
  - Dayton, Ohio, 8
  - Dickey Creek, Virginia, 21
  - highway, 23, 162
  - Kolding, Denmark, 22
  - Morristown, Vermont, 165
  - pedestrian, 21, 485
  - Point Bonita, California, 485
  - Storchen (Stork), Switzerland, 22, cover
  - Waupun, Wisconsin, 8
- Bridge Deck:
  - reinforcement, 6, 143
  - strengthening, 286
  - pultruded, 22
- Bridge parapet, 162
- Buckling of pultruded beam:
  - global lateral-torsional, 401
  - local in-plane: 403
    - approximate method, 411
    - box-shaped profile, 409
    - i-shaped profile, 407
  - local web shear, 413
  - local web transverse, 414

- Buckling of pultruded column:
  - global flexural (euler), 440
  - global torsional, 440
  - local in-plane, 443
    - approximate method, 447
    - box-shaped profile, 447
    - i-shaped profile, 445
  - local-global mode interaction, 450
- Building code, 2, 369
- Building:
  - eyecatcher, 21
  - Electromagnetic Interference (EMI), 18
  - cooling tower, 19, 490
- Cage, 130
- Catalyst, 66
- Centrifugal casting, 371
- Circular concrete column, 327
- Classical Lamination Theory (CLT), 89
- Clip angle connection, 487, 490, 503, 508
- Clipping connection, 490
- Codes, 34
- Coefficient of restraint, 407, 446
- Column, 227, 317, 324, 436
- Combined bending-tension, 477
- Compression molding, 490
- Compression reinforcement, 139
- Compression strengthening, 223
- Composite section, 167, 267
- Confined compressive strain, 334
- Confined compressive strength, 320, 325
- Confinement, 316
- Confining pressure, 323, 326
- Connection:
  - adhesively bonded, 491
  - beam-to-column, 486, 492
  - bearing, 492, 497, 501
  - bolt spacing recommendations, 500
  - bolted, 487, 496, 504
  - bracing, 488
  - clip angle, 504
  - clipping, 490
  - custom, 488
  - efficiency, 497
  - failure modes: 494
    - bearing, 499
    - block shear, 499
    - cleavage, 499
    - net-tension, 499
    - splitting, 499
  - frame, 317, 495, 503
  - lap joint, 499
  - multibolt, 502
  - prying action, 508
  - pultruded, 484
  - rotational stiffness, 495
  - seated, 504
  - semi-rigid, 494
  - shear, 488
  - single bolt, 499
  - slip-critical, 492, 497
  - staggered bolt, 506
  - stresses, 505
  - telescoping, 499
  - truss, 498
  - vector analysis method, 504
- Contact critical strengthening system, 220, 293, 323
- Continuous Filament Mat, 58, 360
- Continuous wrap, 294, 324
- Cooling tower, 19, 490
- Coordinate systems:
  - laminates, 83
  - pultruded profiles, 364
- Corrosive environment, 3, 137, 221, 368, 490
- Coupling agent, 43
- Cracked section, 166, 266
- Crack width:
  - calculation, 169
  - limits, 140
- Creep, 168, 368, 398
- Creep rupture, 43, 140, 170, 223
- Cross-ply laminate, 93
- Curing, 54, 68, 377
- Curing agent, 66
- Custom connection, 488
- Debonding, 229, 291, 297, 324
- Deflection: 166, 223, 271, 393, 474
  - instantaneous, 166, 397
  - limits, 151, 389
  - long-term, 168, 397
- Design basis, 133, 219, 359
- Design examples:
  - pultruded beam, 420
  - pultruded column, 455
  - pultruded connection, 513
  - reinforced beam (detailing), 208
  - reinforced beam (serviceability), 171
  - reinforced beam (shear), 191
  - reinforced beam (strength), 153
  - reinforced bridge deck (punching shear), 193
  - reinforced bridge deck (strength), 162
  - strengthen column (shear), 305
  - strengthened beam (serviceability), 273

- strengthened beam (shear), 298
- strengthened beam (strength), 247
- strengthened column (axial), 328
- Design guides, 34
- Design procedures:
  - pultruded beam, 419
  - pultruded column, 453
  - pultruded connection, 512
  - pultruded tension member, 470
  - reinforced beam (detailing), 207
  - reinforced beam (serviceability), 170
  - reinforced beam (shear), 190
  - reinforced beam (strength), 151
  - strengthened beam (shear), 298
  - strengthened beam (strength), 245
  - strengthened column (axial), 327
  - strengthened column (plastic hinge), 350
- Design properties, 135, 220, 367, 378
- Detailing, 198, 244, 292, 324, 501
- Development length, 205
- Die pressure, 59
- Ductility, 10, 145, 317, 346
- Ductility factor, 347, 350
- Durability, 22, 137
  
- Eccentrically loaded column, 333, 473
- Effective bearing area, 388
- Effective depth of shear strengthening, 291
- Effective strain limit, 296, 325
- E-glass fiber, 42
- Efficiency factor, 326
- Electromagnetic transparency, 18, 360, 490
- Engineering constants:
  - laminates, 87, 91, 92
  - pultruded profiles, 364
  - reinforcing bars, 135
  - strengthening systems, 221
- Environmental effects, 3, 137, 221, 368, 490
- Environmental strength reduction factor, 136, 220
- European Pultrusion Technology Association (EPTA), 37
- Epoxy, 48
- Experimental methods, 104
- Eyecatcher building, 21
  
- Fabric, 59, 65, 73, 216
- Factor of Safety, 370
- Failure criteria, 88, 94
- Failure modes:
  - pultruded connection, 499
  - pultruded profile, 401, 440
  - reinforced beam, 144
  - strengthened beam (strength), 232, 236
- Fastener, 490
- Fatigue, 44, 140, 170, 223
- Fiber: 41
  - anchor, 262
  - aramid, 44
  - area, 56, 63, 81, 223
  - basalt, 45
  - carbon: 43
    - fabric, 65
    - galvanic corrosion, 44
    - TEX, 63
    - tow, 63
    - tow sheet, 72
  - coupling agent, 43
  - direction:
    - circumferential, 320
    - hoop, 57, 320
    - longitudinal, 57
    - multi-axial, 60
    - off-axis, 60
    - on-axis, 60
    - random, 58
    - transverse, 57
  - glass: 42
    - continuous filament mat, 58, 360
    - creep rupture, 43, 133
    - e-glass, 42
    - fabric, 59
    - roving, 56
    - yield, 56
  - natural, 45
  - polypropylene, 45
  - sizing, 42, 44
  - system, 55, 72
  - test methods, 105
  - veil, 55, 65
- Filament winding, 75
- Filler, 67
- Fire retardant, 68
- Fire safety, 47, 219, 222, 368
- First ply failure (FPF), 94, 365
- Flexural rigidity, 393
- Frame: 317
  - balloon, 486
  - braced, 485
  - connection, 495, 503
  - cooling tower, 19
  - rigid, 19, 317, 495
  - simple, 487
  - stick-built, 19, 486
- FRP:
  - bolt, 492
  - concrete filled tube, 8
  - definition, 1, 46

FRP (*Continued*)

- dowel bar, 6
- grating, 4
- grid, 5
- luminaire, 25, 371
- nut, 492
- pile, 8
- pultruded profile:
  - codes and design guides, 18, 35, 362
  - coordinate systems, 363
  - design basis, 359
  - design examples, 420, 455, 513
  - design procedures, 419, 453, 470, 512
  - design properties, 364, 421, 455, 514
  - history, 18, 360
  - load factors, 380
  - manufacturers, 19, 361
  - properties, 31, 364
  - resistance factors, 380
  - safety factors, 359
  - shapes, 52, 361
  - test methods, 107, 116
- raw material, 40
- reinforcing bar:
  - codes and design guides, 4, 34, 128
  - design basis, 133
  - guaranteed properties, 135
  - history, 4, 129
  - limits on stresses, 140
  - load factors, 134
  - manufacturers, 141
  - manufacturing method, 54
  - properties, 28, 138
  - reinforcement ratio, 134
  - resistance factors, 134
  - test methods, 111
- stay-cable, 23
- stay-in-place formwork, 7, 160
- strengthening system:
  - codes and design guides, 14, 34, 216
  - design basis, 219
  - fabric, 13, 59, 65, 216, 318
  - guaranteed properties, 220
  - history, 10, 215, 317
  - limits on stresses, 223
  - load factors, 214
  - manufacturers, 15, 224
  - properties, 29, 218
  - reinforcement ratio, 243
  - resistance factors, 219
  - sheet, 13, 216, 292, 318
  - shell, 17
  - strap, 17, 292, 324
  - strip, 12, 216
    - test methods, 113
    - tow-sheet, 72
    - wrap, 12, 218, 291, 317, 335, 350
  - Tendon, 6
- FRPRCS conference series, 3, 129, 217
- Full-section modulus, 117, 421, 455
- Fully-cured material, 377
- Galvanic corrosion, 44
- Glass transition temperature, 46, 75, 132, 219, 377
- Guaranteed rupture strain, 135, 220
- Guaranteed tensile modulus, 135, 221
- Guaranteed tensile strength, 135, 220
- Gusset plate, 484, 491
- Hardener, 66
- Hand lay-up method, 11, 68, 216
- Heel of angle, 507
- Hooked bar, 206
- Hoop direction, 57, 320
- In-plane engineering constants, 87, 364
- Interaction equation for beam-columns, 475
- Interaction equation for bending-tension members, 478
- Interaction equation for block shear, 511
- Interaction equation for buckling mode coupling, 450
- Intermittent wrap, 294, 324
- International Institute for FRP in Construction (IIFC), 3, 37
- Jacket, 12, 215, 320
- Joint, 317
- Japan Society of Civil Engineers (JSCE) test methods, 122
- Lamina, 83, 106
- Laminate, 89, 107
- Lap joint, 499
- Lap splice, 207, 317, 347
- Lateral displacement, 316
- Limit States Design (LSD), 375
- Load factors, 134, 214, 380
- Load path, 485
- Long-term deflection, 168, 397
- Long-term stresses, 140, 170, 223
- Low shrink additive, 68
- Limits on stresses, 140, 223, 268, 323
- Load and Resistance Factor Design (LRFD), 133, 219, 375
- Luminaire, 25, 371

- Manufacturing methods, 51
  - centrifugal casting, 371
  - filament winding, 75
  - hand lay up: 68
    - fiber system, 73
    - pot life, 71
    - resin system, 73
    - wet-out, 71
  - pultrusion: 52
    - die pressure, 59
    - fiber system, 55
    - history, 53
    - pulling force, 54
    - resin system, 65
    - wet-out, 57
  - resin transfer molding, 76
- Masonry strengthening, 1, 23
- Material partial factor, 376
- Matrix, 78
- Mat, 58, 360
- Metal strengthening, 10, 23
- Micromechanics, 79
- Minimum reinforcement, 151, 189
- Minimum properties of pultruded materials, 366
- Modulus:
  - compressive, 87, 421, 455, 514
  - flexural, 92
  - full-section bending, 117, 421, 455
  - full-section shear, 117, 421, 455
  - in-plane shear, 117, 421, 455, 514
  - longitudinal, 87, 421, 455, 514
  - tensile, 87, 135, 221, 421, 455, 514
  - transverse, 87, 421, 455, 514
- Multiaxial laminate, 89
- Multibolt connection, 502
  
- Natural fibers, 45
- Near surface mounted (NSM) reinforcement, 11, 130, 215
- Nonlinear analysis, 94, 143, 240
  
- Off-axis lamina(te), 86
- On-axis lamina(te), 84
- Orthotropic lamina(te), 84, 93, 364
  
- Passive strengthening system, 323
- Performance based design, 371, 380
- Plastic hinge, 317, 349
- Plate flexural rigidity, 365
- Phenolic resin, 50
- Ply (plies), 83, 231, 364
- Pigment, 68
- Plastic, 46
  
- Polyester resin, 47
- Polymer resin: 45
  - curing, 54, 68
  - glass transition temperature, 46, 75, 132, 219, 377
  - phenolic, 50
  - polyurethane, 50
  - properties, 51
  - thermoplastic, 46, 50
  - thermosetting, 46
  - unsaturated polyester, 47
  - UV degradation, 47
  - vinylester, 49
- Polyurethane resin, 45
- Prying action, 508
- Pulling force, 54
- Pultruded connection, 484
- Punching shear, 189
  
- Quasi-isotropic laminate, 93
  
- Random mat, 58, 360
- Rectangular concrete column, 335
- Reliability index, 374
- Reinforced Concrete:
  - balanced reinforcement ratio, 134, 146
  - bar spacing, 202
  - bend radius, 136, 201
  - bond critical effective stress, 205
  - bond strength, 204
  - crack width calculation, 169
  - deflection, 166
  - design examples, 153, 171, 191, 208, 162, 193
  - design procedures, 151, 170, 190, 207
  - detailing, 198
  - development length, 205
  - failure modes, 144
  - flexural strength, 151
  - hooked bars, 206
  - lap splices, 207
  - long-term deflection, 170
  - minimum flexural reinforcement, 151
  - minimum shear reinforcement, 189
  - minimum thickness, 151
  - moment capacity, 143
  - neutral axis depth, 146
  - nonlinear analysis, 150
  - over-reinforced section, 147
  - punching shear, 189
  - reinforcement ratio, 146
  - serviceability, 170
  - shear stirrups, 187
  - shear strength, 185

- Reinforced Concrete (*Continued*)  
 surface deformations, 199  
 temperature and shrinkage, 140  
 under-reinforced section, 148
- Reinforcement ratio, 134, 243
- Release agent, 68
- Resin, 45, 65, 73
- Resin transfer molding, 76
- Resistance factors, 134, 219, 380
- Rigid frame, 317, 495
- Rotational stiffness, 495
- Roving, 56
- Saturant, 70
- Seismic retrofit, 14, 16, 317, 346
- Semi-rigid connection, 494
- Serviceability limit state, 393
- Shear connection, 488
- Shear deformation, 368, 388
- Shear strengthening schemes, 293
- Shear wall, 17, 290, 314
- Sign support structure, 371
- Single bolt connection, 499
- Sizing, 42
- Slab, 143, 193, 227
- Slip-critical connection, 492, 497
- Soft-eye, 6
- Specially orthotropic lamina(te), 84, 363
- Stick-built frame, 6, 19, 385, 485
- Stiffener:  
 bearing, 417  
 connection, 487  
 web, 416
- Stirrups, 187, 289
- Strength:  
 bearing, 364, 514  
 compressive, 88, 421, 455, 514  
 flexural, 514  
 in-plane shear, 88, 421, 455, 514  
 interlaminar shear, 364, 421, 455, 514  
 longitudinal, 88, 421, 455, 514  
 reduction factor, 219, 235, 293  
 short beam shear, 364, 421, 455, 514  
 tensile, 88, 135, 221, 421, 455, 514  
 through-the-thickness shear, 421, 455, 497, 514  
 transverse, 88, 421, 455, 514
- Strengthened Concrete:  
 active bond length, 297  
 active strengthening system, 323  
 anchorages, 262, 297  
 angle of inclination, 292  
 axial capacity, 325  
 axial load effect, 308  
 balanced Reinforcement ratio, 243  
 bar lap splice, 317, 350  
 bond critical system, 220, 293  
 circular concrete column, 327  
 confined compressive strain, 334  
 confined compressive strength, 320  
 confinement, 316  
 confining pressure, 323, 326  
 contact critical system, 220, 293, 323  
 continuous wrap, 294, 324  
 debonding, 229, 291, 297, 324  
 deflection, 223, 271  
 detailing, 245  
 drift, 316  
 ductility factor, 347  
 eccentrically loaded column, 333  
 effective depth of shear strengthening, 291  
 effective strain limit, 296, 325  
 failure modes, 236  
 fiber anchors, 262  
 fiber area calculation, 223  
 flexural strength, 245  
 intermittent wrap, 294  
 lateral displacement, 316, 350  
 limits on strengthening, 222, 298  
 load-moment diagram, 333  
 moment capacity, 235  
 neutral axis, 234  
 nonlinear analysis, 240  
 passive strengthening system, 323  
 plastic hinge confinement, 350  
 plastic hinge, 317, 349  
 rectangular concrete column, 335  
 reinforcement ratio, 243  
 serviceability, 273  
 shear capacity, 293  
 shear crack angle, 292  
 shear overstrength, 352  
 shear strengthening schemes, 293  
 sheet spacing, 292  
 sheet width, 292, 302  
 spiral column, 325  
 strengthening limits, 222  
 stress in FRP, 270  
 stress in steel, 269  
 substrate strain, 235  
 tied column, 325  
 truss analogy, 293  
 u-wrap, 262, 291
- Stress-strain relations, 84, 86, 89
- Structural Plastics Research Council (SPRC), 3, 18
- Structural reliability, 373
- Substrate strain, 235

- Surface deformations, 199
- Symmetric laminate, 90, 93
  
- Temperature effect, 368
- Test methods, 105, 108
- TEX, 63
- Thermoplastic polymer, 46, 50
- Thermosetting polymer, 46
- Thread, 492
- Timber strengthening, 1, 23
- Timoshenko beam theory, 388, 391
- Torsional constant, 402
- Tow, 63
- Tow-sheet, 72
- Transformed section analysis, 167, 250, 266
- Transverse shear rigidity, 394
- Truss, 360, 485
- Truss connections, 498
- Truss analogy, 293
  
- UV degradation, 47
  
- Unidirectional composite, 80, 84
- Unsaturated polyester resin, 47
- U-wrap, 262, 291
  
- Vector analysis method, 504
- Veil, 55, 65
- Vinylester resin, 49
- Viscoelastic modulus, 398
- Volume fraction, 78, 360
- Void content, 47, 78, 218
  
- Wall, 227, 290, 317, 486
- Warping constant, 402
- Web crushing, 414
- Web-flange junction, 368, 412, 494, 503
- Wet lay up, 11, 68
- Wet out, 57, 71
- Weight fraction, 78
- Wrap, 12, 218, 291, 317, 335, 350
  
- Yield, 56

