

Index

• Symbols and Numerics •

SECRET-DATA encryption, 93
? command, 78, 369
| (pipe), 353
+ (plus sign), 129
.0 file extension, 176
0.0.0.0/0 route, 236
.8 - (minus sign), 129
¹⁶ prefix, 238
1/8 route, 236
2/8 route, 236
5/8 route, 236
7/8 route, 236
23/8 route, 236
127/8 route, 236
3DES-CBC (Triple Data Encryption Standard-cipher Block Chaining), 291
802.1X protocol, 152–153

• A •

ABR (area border router), 118, 122
accept action, 134, 209, 228–230
access control list (ACL), 52, 58
access layer, 32
access permission, 20
access switching layer, 39–40
ACL (access control list), 52, 58
active alarm, 311
active configuration, 80
active route, 47
active state, 205
address block, 45
address family identifier (AFI), 121
Admin status, 337–338
admission control, 152–153
ADSL interface. *See* asymmetric digital subscriber line interface

ADSL-over-ATM interface, 187
Advanced Encryption Standard (AES), 291
Advanced Insight Solutions (AIS), 24–25
AES (Advanced Encryption Standard), 291
af (assured forwarding), 245–246
AFI (address family identifier), 121
age output field, 316
agent, 95
aggregate route, 238–240
aggregation layer, 38, 40
aggregation switch, 160
AH (Authentication Header) protocol, 289–290
AIS (Advanced Insight Solutions), 24–25
alarm, 311, 331–332
Alert severity level, 99
alert syslog severity, 172
ALG (Application Layer Gateway), 60
all keyword, 154
AND statement, 228
annotate command, 20
Any configuration option, 98
Any severity level, 98
any syslog facility, 171
any syslog severity, 171
any warning configuration, 98
application layer, 325
Application Layer Gateway (ALG), 60
Application-Specific Integrated Circuit (ASIC), 11
APS (Automatic Protection Switching), 350–351
archive log, 329
archiving configuration, 82–86
area
 IS-IS protocol, 121–122
 OSPF protocol, 118–119
area border router (ABR), 118, 122
area ID match condition, 226
area identifier, 121

- AS (autonomous system), 49, 117–118, 202, 317, 341–342
 - AS path match condition, 226
 - ASIC (Application-Specific Integrated Circuit), 11
 - assured forwarding (af), 245–246
 - asymmetric digital subscriber line (ADSL) interface
 - configuring, 187–192
 - overview, 181–182
 - Asynchronous Transfer Mode-over-ATM interface, 187
 - ATM-options hierarchy, 106
 - authentication, 61, 138–139, 168
 - authentication configuration option, 97
 - Authentication Header (AH) protocol, 289–290
 - authentication protocol, 192
 - authentication server, 92
 - authentication-profile-name statement, 153
 - authorization configuration option, 98
 - authorization error message, 98
 - authorization event, 175
 - authorization syslog facilities, 171
 - Automatic Protection Switching (APS), 350–351
 - automation script, 22–23
 - auto-negotiate setting, 189–191
 - autonomous network, 197
 - autonomous system (AS), 49, 117–118, 202, 317, 341–342
 - availability, 40
- **B** •
- BA classifier. *See* behavior aggregate classifier
 - backbone area, 118
 - bad route, 237
 - bandwidth
 - capping transmission rate, 257–258
 - overview, 255–256
 - reserving on LSPs, 280–284
 - strict-high scheduling, 257
 - bandwidth policy, 256
 - banner, 89–91
 - Basic Settings page, 142
 - BCD (binary-coded decimal), 121
 - be (best effort), 245
 - behavior aggregate (BA) classifier
 - aliases, 247
 - forwarding classes, 248–249
 - linking forwarding classes to, 250–252
 - linking to traffic, 252–253
 - massaging for core transit, 261–265
 - overview, 244
 - queues, 249–250
 - BER (bit error rate), 194–195
 - BERT tester, 194–195
 - best effort (be), 245
 - BFD (Bidirectional Forwarding Detection), 63
 - BGP. *See* Border Gateway Protocol
 - bgp command, 69
 - bgp neighbor neighbor-name command, 69
 - bgp-dead-peers script, 359–360
 - bidirectional communication, 278
 - Bidirectional Forwarding Detection (BFD), 63
 - bidirectional security association, 292
 - binary, 14
 - binary-coded decimal (BCD), 121
 - bit error rate (BER), 194–195
 - black holing, 48
 - block-all-else term, 132
 - book, JUNOS, 370
 - Border Gateway Protocol (BGP)
 - authenticating packets, 138–139
 - Autonomous Systems, 197–199
 - configuring, 199–203
 - dead-peers script, 359–360
 - default actions, 230
 - monitoring, 203–214
 - overview, 49
 - route reflectors, 214–220
 - verifying peering relationships, 342–343
 - branch router, 249
 - broadcast domain, 33, 145
 - broadcast message, 124
 - broadcast traffic, 145
 - bugs, 346, 348–349
 - business critical application, 250, 255
 - business rules, 347–348

• C •

- CA (certificate authority), 292
- candidate configuration, 21, 80
- capping transmission rate, 257–258
- carrier network, 272
- carrier-sense multiple access with
 - collection detection (CSMA/CD) protocol, 145
- centralized authentication, 94
- certificate authority (CA), 292
- certification, JUNOS, 370–371
- /cf/var/log/ log file directory, 174
- chain topology, 144
- Challenge Handshake Authentication Protocol (CHAP), 193–194
- challenge value, 193
- change-log configuration option, 98
- change-log notice message, 98
- change-log syslog facility, 171
- CHAP (Challenge Handshake Authentication Protocol), 193–194
- chassis configuration option, 97
- chassis statement, 73
- Chassis technology, 39–40
- chassisd process log file, 332–333
- CIDR (Classless Interdomain Routing), 116
- ciphertext, 290
- Cisco IOS software, 203
- Class of Service (CoS)
 - classifying inbound traffic, 243–253
 - controlling outbound traffic, 253–261
 - massaging BA classifiers for core transit, 261–265
 - overview, 35, 241–243
 - process log file, 332
 - queue, 311
- class selector (cs), 246
- classification stage, 242
- Classless Interdomain Routing (CIDR), 116
- class-of-service statement, 73
- clear bgp neighbor neighbor-name command, 69
- clear command, 69, 75
- clear log command, 177
- CLI. *See* command-line interface
- client, 95
- clock signal, 186
- clocking, 183
- cluster, 217
- cluster ID, 217, 219
- code point alias, 246–248
- collision domain, 145
- command, *see* names of specific commands
- command completion, 78–79
- command log, 329–330
- command-line interface (CLI)
 - archiving configurations, 82–86
 - command completion, 78–79
 - commit command, 21–22
 - commit confirmed command, 21–22
 - committing configurations, 80–82
 - configuration mode, 68–78
 - configuring routers, 86–88
 - help command, 78
 - keyboard sequences, 78–80
 - logging in to routers, 67–68
 - operational mode, 68–75
 - overview, 19–20
 - rollback command, 21–22
 - tools, 20
 - as troubleshooting tool, 326
- commit at command, 20
- Commit Check command, 21
- commit command, 21–22, 77, 80–81, 83–84, 88, 106, 157, 355
- commit complete command, 81
- commit confirmed command, 21–22, 81–82, 364
- commit synchronize command, 157
- commits log file, 331–332
- committing configuration, 80–82
- compatibility, 25–27
- /config directory, 83
- configuration
 - activating, 77
 - archiving, 82–86
 - changing, 350–351, 356–357
 - committing, 80–82
 - constraining, 350, 356
 - displaying, 77
 - returning to previous, 77
 - simplifying, 351, 357–359

Configuration and Diagnostic Automation Guide, 354

configuration configuration option, 97

configuration hierarchy, 77

configuration message log, 329–330

configuration mode, 69–78

configuration statement, 73

configure command, 72, 84, 364

conflict-log configuration option, 98

conflict-log syslog facility, 171

congestion, 258

connect state, 205

connecting switch, 143–144

console port, 68

constraint on packet forwarding, 279–286

constraint-based routing, 279

control plane, 8

conventions used in book, 2

convergence, 47–48

cooling, 40

copy command, 77

core file, 327, 336

core layer, 32, 40

core switch, 160

core transit, massaging BA classifiers for, 261–265

CoS. *See* Class of Service

cos-voice class, 251, 263

Critical severity level, 99

critical syslog severity, 172

cryptographic key, 61

cs (class selector), 246

CSC (Customer Support Center), 371

CSMA/CD (carrier-sense multiple access with collection detection) protocol, 145

Ctrl key, 79–80

current address, 311

Customer Support Center (CSC), 371

• D •

daemon, 13

daemon configuration option, 98

daemon syslog facility, 171

data communications equipment (DCE), 180

Data Encryption Standard (DES), 126

Data Encryption Standard-cipher Block Chaining (DES-CBC), 291

data link layer, 120, 325

data plane, 9

data terminal equipment (DTE), 180, 184

DCE (data communications equipment), 180

deactivate command, 20, 77

Debug severity level, 99

debug syslog severity, 171

debugging, 178, 352

DECNET Phase V Network Technology, 120

default action, 229–231

default gateway, 46

default route, 115

default security feature, 124–127

default VLAN, 143, 146–148

delete command, 77

DES (Data Encryption Standard), 126

DES-CBC (Data Encryption Standard-cipher Block Chaining), 291

destination port, 263–264

detail modifier, 315

development, JUNOS software, 14–17

Device Control daemon dec, 333

device flag, 309

DHCP (Dynamic Host Configuration Protocol), 46

diagnostic command, 308–318

diagnostic logic, custom, 351–352, 359–360

Differentiated Services Code Point (DSCP), 244–248, 264–265

digital certificate, 292

Digital Equipment Corporation DECNET Phase V Network Technology, 120

digital subscriber line (DSL) interface, 179

Dijkstra SPF calculation, 117

direct route, 314

disable command, 166–167, 276, 339

display xml modifier, 353

displaying running processes, 334–335

distance-vector algorithm, 48, 111

distribution, 160

documentation, 20

domain-name statement, 74

down arrow shortcut, 80

down device flag, 309

downloading new release, 29

downtime

human error, 63–64, 346–348

overview, 61, 345–346

planned, 62
 reducing with JUNOScript, 349–352
 software issues, 348–349
 unplanned, 62–63

DSCP (Differentiated Services Code Point), 244–248, 264–265

`dscp-classifier` statement, 252–253

DSL (digital subscriber line) interface, 179

DTE (data terminal equipment), 180, 184

dual route reflector, 220

Dynamic Host Configuration Protocol (DHCP), 46

dynamic IPsec tunnel, 299

dynamic routing protocol, 47, 110–111, 160

dynamic security association, 292–293

dynamic setup, 273

• E •

E1 interface, 180

EBGP (external BGP), 201, 210

ECN (Explicit Congestion Notification), 245

`edit chassis` configuration, 331–332

`edit` command, 76–77

`[edit protocols ospf]` hierarchy, 177

`[edit system]` hierarchy, 173

`[edit system syslog]` level, 177

EEOL (Extended End of Life), 29

ef (expedited forwarding), 245

EGP (Exterior Gateway Protocol), 48

egress queue, 313

egress router, 270, 274, 277, 280

EIGRP (Enhanced Interior Gateway Routing Protocol), 49

`else` statement, 354

Emergency severity level, 99

`emergency syslog` severity, 172

Encapsulating Security Payload (ESP) protocol, 289–291

encapsulation, 183

encryption, 125–126, 183, 290–291. *See also* secure tunnel

Encryption Services (ES), 294, 297

End of Engineering (EOE), 28

End of Life (EOL), 28

end of row (EOR), 39

endpoint, 188

engineering support, 28

Enhanced Interior Gateway Routing Protocol (EIGRP), 49

`Enter` command, 71

`Enter EZ Setup` option, 142

EOE (End of Engineering), 28

EOL (End of Life), 28

EOR (end of row), 39

ERO (explicit route object), 282

Error Correction Control daemon `eccd`, 333

Error severity level, 99

`error syslog` severities, 172

ES (Encryption Services), 294, 297

Esc key, 79–80

ESP (Encapsulating Security Payload) protocol, 289–291

Ethernet -options hierarchy, 106

`ethernet-switching` keyword, 146

event, 63, 95–99, 352

exact match type, 234–235

exact modifier, 318

`exit` command, 77, 130

expedited forwarding (ef), 245

Explicit Congestion Notification (ECN), 245

explicit route object (ERO), 282

`explicit-priority` configuration statement, 175–176

export policy, 208–209, 232

EX-series switch, 41, 106, 142, 152, 157

Extended End of Life (EEOL), 29

eXtensible Markup Language (XML), 27, 352–353

Extensible Stylesheet Language Transformation (XSLT), 353–354

Exterior Gateway Protocol (EGP), 48

external BGP (EBGP), 201, 210

• F •

failover, 12

family `ethernet-switching` command, 149, 159

family statement, 107, 159

Fast Ethernet interface, 85, 105, 165

Fast Ethernet -options hierarchy, 106

fast failover, 52
 Fast-Reroute (FRR), 52
 fe-0/0/2 Fast Ethernet interface, 114
 FEC (Forward Equivalency Class), 53
 FIB (Forwarding Information Base), 47
 file command, 75
 file copy operational mode command, 83, 84
 file list detail /config command, 364
 file list detail /var/db/config command, 364
 File Transfer Protocol (FTP), 60
 filter input statement, 263
 find-ospf term, 224
 firewall configuration option, 98
 firewall filter, 58–59, 61, 131, 135, 296–297, 343
 firewall policer, 256
 firewall statement, 73
 firewall syslog facility, 171
 Flexible PIC Concentrator (FPC), 86, 102
 flooding packet, 145
 Flow accounting, 24
 forum, JUNOS, 370
 Forward Equivalency Class (FEC), 53
 forwarding class, 245–252
 Forwarding Information Base (FIB), 47
 forwarding plane, 8–9
 forwarding table, 12, 221, 341
 forwarding-options statement, 73
 FPC (Flexible PIC Concentrator), 86, 102
 frame checksum, 340
 from statement, 226–227
 FRR (Fast-Reroute), 52
 FTP (File Transfer Protocol), 60
 ftp configuration option, 98
 ftp syslog facility, 171
 full mesh configuration, 202
 full-duplex operation, 145
 fxp0 management interface, 87, 104

• G •

gateway router, 38, 238, 282, 296
 Gbps (gigabits per second), 38
 ge-0/0/1 interface, 146, 148

ge-0/0/2 interface, 148
 ge-0/1/0 interface, 151
 ge-1/2/0 interface, 103
 ge-1/2/0.0 interface, 122
 Generic Routing Encapsulation (GRE), 51
 Gigabit Ethernet interface, 105, 142
 Gigabit Ethernet PIC, 102
 Gigabit Ethernet-options hierarchy, 106
 gigabits per second (Gbps), 38
 GMT (Greenwich Mean Time), 100
 Graceful Restart (GR) Protocol Extensions, 63
 Graceful Routing Engine Switchover (GRES), 40, 62, 157–158
 GRE (Generic Routing Encapsulation), 51
 Greenwich Mean Time (GMT), 100
 GRES (Graceful Routing Engine Switchover), 40, 62, 157–158

• H •

hacker, 123
 hardware
 routing, 54–55
 switching, 41–42
 troubleshooting, 331–334
 Hardware address, 311
 hashing algorithm, 125–126, 291
 Hashing Message Authentication Code (HMAC), 291
 Health monitor, 24
 Hello protocol packet, 138
 help command, 78
 help reference command, 78
 help resource, 369–371
 help syslog syslog_message command, 369
 help topic command_name command, 78, 369
 helper mode, 158
 hierarchical routing, 48
 high availability, 36, 61–64
 high-priority queue, 260–261
 HMAC (Hashing Message Authentication Code), 291
 hop popping, 277

hop-by-hop routing, 43
host, 44
hostname, 67, 305
hostname statement, 74
host-to-host monitoring, 303–306
human error, 63–64, 346–348

• I •

IANA (Internet Assigned Numbers Authority), 199
IBGP (internal BGP), 199–200, 210
ICMP packet, 307, 321, 344
icon used in book, 4
idle state, 205
IETF (Internet Engineering Task Force), 25, 120
if statement, 354
if-then construct, 225, 229
IGP. *See* Interior Gateway Protocol
IKE (Internet Key Exchange) protocol, 292–293
import policy, 208, 232
in profile queue, 260
inactive reason output field, 316
in-band management, 164–167
inbound traffic
 BA classifiers, 248–253
 configuring policies that advertise route, 208
 Differentiated Services Code Point, 244–248
 overview, 243–244
inet protocol, 103
inet.0 routing table, 112–113
inet.1 routing table, 112
inet.3 routing table, 112
inet6 protocol, 103
inet6.0 routing table, 112
info authorization event, 175
Info severity level, 99
info syslog severity, 172
ingress router, 270
input filter, 262
input policer, 242
input rate, 311
input-list statement, 263
insert command, 77, 224–225
integration, 26–27
interactive-command configuration option, 98
interactive-command syslog facility, 171
interconnecting switch
 redundancy, 157–159
 Virtual Chassis configuration, 154–157
interface
 choosing for remote management, 163–167
 configuring, 100–105, 183–195
 diagnostic commands, 308–313
 identifiers, 101
 limiting traffic on, 134–135
 matching to network needs, 106–107
 physical, 179–182
 properties of, 182–183
 putting to work, 105–107
 speed of, 38
 steps to connect, 166
 troubleshooting, 185, 337–340
interface address, 207, 298, 305
interface all configuration statement, 166
interface name match condition, 225
<interface>.<unit> tag, 150
interfaces command, 69, 73
Interior Gateway Protocol (IGP), 48–49, 111, 115–117, 137. *See also* Intermediate system to intermediate system protocol; Open Shortest Path First protocol
Intermediate system to intermediate system (IS-IS) protocol
 areas, 121–122
 automatic configuration of LDP on, 356–357
 configuring and monitoring, 122
 network entity title, 120–121
 overview, 49, 111
 security, 137–138
internal BGP (IBGP), 199–200, 210
internal router, 118

Internet Assigned Numbers Authority (IANA), 199

Internet Engineering Task Force (IETF), 25, 120

Internet Key Exchange (IKE) protocol, 292–293

Internet Protocol (IP), 141, 267, 288. *See also* IP address

Internetwork, 8

interoperability, 25–26

intrusion detection, 58

invoking JUNOScript, 355

IOS software, 203

IP (Internet Protocol), 141, 267, 288

IP address

- overview, 44–47
- routing policy, 50
- routing table, 47–49
- setting for router interface, 102–105

IP Security (IPSec) protocol, 61, 288, 296

IPSec tunnel, 289–299

IPSec tuple, 293

IPv4 address, 45

IPv6 address, 45

IS-IS protocol. *See* Intermediate system to intermediate system protocol

iso protocol, 103, 122

iso.0 routing table, 112

• J •

jinstall descriptor, 17

jitter, 35, 242, 322

J-Net Communities forum, 370

JNTCP (Juniper Network Technical Certification Program), 370–371

J-series router, 54, 249, 299

JTAC (Juniper Networks Technical Assistance Center), 24, 28, 371

Juniper Network Technical Certification Program (JNTCP), 370–371

Juniper Networks Education Services, 370

Juniper Networks router, 159, 165

Juniper Networks Technical Assistance Center (JTAC), 24, 28, 371

JUNOS software

- automated tools, 22–25
- command-line interface, 19–22
- compatibility, 25–27
- development of, 14–17
- functions, 10–12
- high availability, 61–64
- modular architecture, 13
- network operating system, 8–10
- overview, 7
- planes, 12
- security, 57–61
- upgrading, 27–29

JUNOScript

- changing configuration, 350–351, 356–357
- constraining configuration, 350, 356
- creating custom logic for operational commands, 351–352, 359–360
- invoking, 355
- minimizing downtime, 345–349
- overview, 352–353
- reacting to live events, 352
- simplifying configuration, 351, 357–359
- writing, 353–354

J-Web tool, 26

• K •

kernel, 12

kernel configuration option, 98

kernel syslog facilities, 171

keyboard sequence, 78–80

• L •

L2 (Layer 2), 33, 150

L3 (Layer 3), 34, 43–50

label, 271

Label Distribution Protocol (LDP)

- automatic configuration of, 356–357
- defined, 53
- enabling authentication for, 139

label operation, 271–272

label stacking, 272

label switching, 268–269

- label-switched path (LSP)
 - defined, 53
 - establishing, 273
 - overview, 269
 - reserving bandwidth on, 280–284
 - RSVP-Signaled, 274–279
 - verifying traffic using, 284–286
 - label-switching router (LSR), 53, 270–271
 - LAN, local-area network, 160
 - last flapped field, 311
 - latency, 318–322
 - layer, overview, 32
 - Layer 2 (L2), 33, 150
 - Layer 3 (L3), 34, 43–50
 - LCP (link control protocol), 192
 - LDP. *See* Label Distribution Protocol
 - left arrow shortcut, 80
 - Level 1 systems router, 122
 - Level 2 systems router, 122
 - limit-ssh-telnet filter, 131, 133
 - line card, 331, 333–334
 - link configuration option, 97
 - link control protocol (LCP), 192
 - Link Layer Discovery Protocol (LLDP), 34, 146
 - Link status, 337–338
 - link-state advertisement (LSA), 111, 117, 138
 - link-state algorithm, 48
 - link-state protocol, 111
 - link-state protocol data unit, 111, 120, 232
 - literature, JUNOS, 370
 - LLDP (Link Layer Discovery Protocol), 34, 146
 - 100 loopback interface, 103–104, 121, 133, 135, 137, 211
 - load command, 84
 - local change, 48
 - local preference, 210
 - local-area network (LAN)
 - overview, 33
 - segmenting, 145–154
 - using switches to connect to, 160
 - location independence, 40
 - logging. *See also* system log
 - tools for, 23–24
 - trace, 177–178
 - tracking events with, 97–99
 - logging out, 91, 130
 - logical interface, 107, 182–183, 189, 316
 - logical rule, 347–348
 - login, 67–68, 89–91, 126–128
 - longer match type, 234, 235
 - longest match, 46
 - loopback (100) interface, 103–104, 121, 133, 135, 137, 211
 - loopback address, 101, 203, 212–214, 304–305
 - loopback testing, 339
 - loose statement, 283
 - loss percentage field, 322
 - low-priority queue, 261
 - LSA (link-state advertisement), 111, 117, 138
 - LSP. *See* label-switched path
 - lsp-next-hop statement, 283
 - LSR (label-switching router), 53, 270–271
- M •
- MAC (Media Access Control), 33, 121, 141
 - Maintenance Menu, 142
 - maintenance release, 17
 - MAN (metropolitan area network), 33
 - Manage Access page, 143
 - Management Information Base (MIB), 26, 95
 - management interface, 104, 163, 165–166
 - Management Options page, 142
 - management process (MGD), 172, 352–353
 - management tool, 26
 - manager, 95
 - Martian address, 124–125, 235
 - mask, 45
 - Mastership priority column, 155
 - match action, 228–229, 236–237
 - match condition, 225–228
 - match type, 234–236
 - maximum transmission unit (MTU), 22, 343–344, 350, 356
 - MD5 (Message Digest 5) algorithm, 126, 139, 291
 - media, JUNOS, 370
 - Media Access Control (MAC), 33, 121, 141
 - medium-high priority queue, 260–261

medium-low priority queue, 260–261

Member ID: 0, Role: Master
message, 155

Member ID:1, Role Backup
message, 155

Message Digest 5 (MD5) algorithm,
126, 139, 291

messages file, 173, 174, 175, 330

metropolitan area network (MAN), 33

MF (multifield) classification, 244, 261

MGD (management process), 172, 352–353

mgmt switch management interface, 148

MIB (Management Information Base),
26, 95

mib2d string, 174

minus sign (-), 129

Modify action, 228

modular architecture, 13

monitoring
BGP protocol, 203–214
IS-IS protocol, 122
network, 24, 303–322
OSPF protocol, 119
router, 170–178
tools for, 23–24

MPLS. *See* Multi-Protocol Label Switching

mpls protocol, 103

mpls .0 routing table, 112

M-series routers, 55, 155

MTU (maximum transmission unit),
22, 343–344, 350, 356

multicast, 54

multifield (MF) classification, 244, 261

multihoming, 49

multiple match condition, 228

multiple mode authentication, 154

multiple push label operation, 272

Multi-Protocol Label Switching (MPLS)
authenticating signaling protocols, 139
constraints on packet forwarding,
279–286
label operations, 271–272
label switching, 268–269
labels, 271
label-switched path, 269, 273–279
label-switching router, 270–271
overview, 50–51, 267–268

reasons to use, 51–52
signaling protocols, 273–274
workings of, 52–53

MX-series Ethernet services router, 55

my-sample-policy routing policy, 223

• N •

NAC (Network Access Control), 36–37, 151

NAT (Network Address Translation), 46,
60–61, 101, 299–300

nc (network control), 246

NCP (network control protocol), 192

neighbor address match condition, 225

NET (network entity title), 120–121

NET selector (NSEL), 121

NETCONF (Network Configuration)
protocol, 27

Network Access Control (NAC), 36–37, 151

Network Address Translation (NAT), 46,
60–61, 101, 299–300

Network Configuration (NETCONF)
protocol, 27

network control (nc), 246

network control protocol (NCP), 192

network entity title (NET), 120–121

network layer, 325

Network Management System (NMS), 24, 95

network operating system (NOS), 7–10

network routing. *See* router/routing

Network Time Protocol (NTP), 100

network topology, 238–240, 268, 303

network-facing interface, 163

next-hop address, 111, 211–212, 314

next-hop-self policy, 220

next-policy action, 228–229

next-term action, 228–229

NMS (Network Management System), 24, 95

noncritical application, 250, 255

None severity level, 98

none syslog severity, 171

Nonstop Active Routing (NSR), 63

non-stop forwarding, 12

NOS (network operating system), 7–10

Notice severity level, 99

notice syslog severity, 172

not-so-stubby area (NSSA), 119

L (NET selector), 121
 (Nonstop Active Routing), 63
 A (not-so-stubby area), 119
 (Network Time Protocol), 100

O •

Object Identifier (OID), 95
 t, 45
 (Object Identifier), 95
 ommand, 355
 n development, 27
 n Shortest Path First (OSPF) protocol
 eas, 118–119
 omatic configuration of LDP on, 356–357
 nfiguring and monitoring, 119
 erview, 9, 49, 111, 117–118
 curity, 137–138
 rifying adjacencies, 341–342
 nConfirm state, 205
 nSent state, 205
 rating system (OS), 7
 ration script, 63
 rational mode, 68–75
 rational script, 355
 rator privilege class, 93
 ions hierarchy, 106
 onger match type, 234–235
 perating system), 7
 F. *See* Open Shortest Path First
 protocol
 log file, 177
 ound buffer, 258–259
 ound interface. 9, 298, 314

owner and test field, 321

• *p* •

packet, 8, 32
 packet forwarding, 9–10, 279–286
 Packet Forwarding Engine (PFE), 11–12
 packet loss priority (PLP), 245
 packet-switched networking, 267–272
 Partner Solution Development Platform
 (PSDP), 27
 password, 125–127
 path message, 274
 path statement, 282, 286
 pay-as-you-grow scalability, 40
 payload scrambling, 340
 penultimate hop popping (PHP), 271
 penultimate router, 270–271
 per-unit-classifier, 253
 PFE (Packet Forwarding Engine), 11–12
 pfe configuration option, 98
 pfe syslog facility, 171
 phone number, 371
 PHP (penultimate hop popping), 271
 physical interface, 179–182
 Physical Interface Card (PIC), 86, 100
 physical interface property, 182–183
 physical layer, 325
 physical security, 123–124
 PIC (Physical Interface Card), 86, 100
 ping command, 75, 213, 303–307, 326,
 331, 344
 ping, 205–207, 212–214
 pine (|), 72, 353

policy chain, 232–233
 policy-options statement, 73, 223
 pop label operation, 272
 port, 31, 151, 164, 339
 port density, 38
 port expansion, 39
 port number, 59
 positive voltage, 180
 POTS (plain old telephone service) splitter, 182
 Power over Ethernet (PoE), 35, 147
 PPP (point-to-point protocol), 192–194
 preemption, 157
 preference, route, 114–115, 314
 prefix, 46, 234
 prefix length, 234
 prefixlength-range match type, 234–235
 present device flag, 309
 presentation layer, 325
 preshared key, 292, 296
 primary statement, 283
 priority scheduling, 259–261
 private IP address, 44
 probe type field, 321
 propagation delay, 242
 protocol bundle, 296
 protocol match condition, 226
 protocols statement, 73
 provider network, 277
 PSDP (Partner Solution Development Platform), 27
 pseudo wire emulation, 53
 public command, 96
 public IP address, 44
 public key infrastructure (PKI), 292
 push label operation, 272

• Q •

Quality of Service (QoS). *See* Class of Service
 queue, 249–250
 queue starvation, 256
 quick mode, 293
 quit command, 77, 130

• R •

racking switch, 142
 RADIUS server, 93, 152
 random early detection (RED), 246
 rate-limit statement, 169
 rate-limiting traffic flow, 135
 RE (Routing Engine), 11, 135–137, 157
 read-only authorization, 96
 read-only privilege class, 93
 read-write authorization, 96
 real-time performance monitoring (RPM), 24, 319–322
 RED (random early detection), 246
 regression testing, 15
 regular area, 119
 reject command, 132, 228–229
 release numbering, JUNOS, 16–17
 release train, JUNOS, 15–16
 remote management, 170
 Remote Network Monitoring (RMON), 24
 remote router management

- accessing, 167–169
- choosing interface for, 163–164
- in-band management, 165–167
- monitoring, 170–178
- out-of-band management, 165

 remote syslog host, 329
 replace command, 77
 request command, 75
 request system snapshot command, 364
 rescue configuration, 20
 reserved address, 237
 Resource Reservation Protocol (RSVP), 139
 restart command, 75, 335
 RIB (Routing Information Base), 46
 right arrow shortcut, 80
 ring topology configuration, 143
 RIP (Routing Information Protocol), 115–117, 137
 RMON (Remote Network Monitoring), 24
 rmon-alarm configuration option, 97
 rollback command, 21–22, 77, 82–83, 364
 rollback rescue command, 20

- root login account, 126–127
 - root permission, 163
 - root user name, 67, 142, 169
 - round-trip time (RTT) field, 322
 - route aggregation, 238–240
 - route filter, 233–237
 - route flapping, 48, 111
 - route metric, 47, 225
 - route metric match condition, 230
 - route origin, 314
 - route preference, 114–115, 314
 - route preference match condition, 225
 - route prefix, 46, 234
 - route reflector, 214–220
 - route summary, 317–318
 - router ID, 219, 317
 - router interface card, 101
 - router/routing. *See also* interface
 - access, 124
 - banner at login, 89–91
 - configuring, 86–88
 - dynamic routing protocols, 110–111
 - event tracking, 95–99
 - hardware, 54–55
 - IS-IS protocol, 120–122
 - Layer 3, 43–50
 - logging out, 91
 - login, 67–68
 - managing remotely, 163–178
 - MPLS, 50–53
 - OSPF protocol, 117–119
 - overview, 109–110
 - RIP, 115–117
 - route preference, 114–115
 - routing table, 111–114
 - security, 128–135
 - SNMP Set commands, 124
 - time and time zone, 99–100
 - troubleshooting, 340–343
 - user account, 91–94
 - using switches as, 159–160
 - routing cluster, 218
 - routing configuration option, 97
 - Routing Engine (RE), 11, 135–137, 157
 - routing filter, 343
 - Routing Information Base (RIB), 46
 - routing information diagnostic command, 313–318
 - Routing Information Protocol (RIP), 115–117, 137
 - routing policy
 - applying, 231–232
 - configuring aggregate route, 238–240
 - constructing, 221–231
 - evaluating, 232–233
 - match conditions, 225–226
 - that advertise routes, 208–210
 - routing process (rpd), 113, 335
 - routing protocol, 49, 158, 221, 230
 - routing table, 46–49, 111–114, 208, 221, 231, 317
 - routing-options hierarchy, 282
 - routing-options statement, 73
 - rpd (routing process), 113, 335
 - RPM (real-time performance monitoring), 24, 319–322
 - RSVP (Resource Reservation Protocol), 139
 - RSVP-Signaled LSP, 274–279
 - RTT (round-trip time) field, 322
 - rule, 8, 347–348
 - running device flag, 309
- S •
- SA, 293–299
 - SaaS (Software as a Service), 38
 - scaling, 37–40
 - scheduler, 253
 - scheduler map, 253
 - scheduling, 254–261
 - scheduling/queueing delay, 242
 - SDH, 101, 106
 - SDK (software development kit), 27
 - second-rate traffic, 258
 - secret, 193
 - secret keyword, 152
 - ## SECRET-DATA encryption, 93
 - Secure Hash Algorithm 1 (SHA-1), 126, 291
 - Secure Shell (SSH), 124, 126–127, 131–133, 168–169

- secure tunnel
 - algorithms, 291
 - digital certificates, 292
 - hiding internal addresses from Internet, 299–300
 - IPSec protocols, 289–291
 - IPSec tunnel, 293–299
 - overview, 61, 287–289
 - presared keys, 292
 - security association, 292–293
- security
 - default features, 124–127
 - firewall filter, 58–59
 - Network Address Translation, 60–61
 - overview, 57–58
 - physical security, 123–124
 - router, 128–135
 - Routing Engine, 135–137
 - routing protocols, 137–139
 - secure VPN tunnels, 61
 - stateful firewall, 60
- security association (SA), 293–299
- security camera, 143
- security file, 174–175
- security parameter index (SPI), 292, 296
- segmenting LAN, 145–151
- serial cable, 180
- serial interface, 180–181, 184–187
- serial line protocol, 181
- serial link, 180
- serialization delay, 242
- service release, 17
- Service-Oriented Architecture (SOA), 38
- session layer, 325
- Session Resource Control (SRC), 26
- set command, 72, 76–77, 135
- set snmp community public authorization readonly command, 96
- set system announcement command, 90
- set system login message command, 90
- set unit 100... command, 150
- set unit 200... command, 150
- severity level, logging, 98–99
- severity syslog event, 175
- SHA-1 (Secure Hash Algorithm 1), 126, 291
- shared key, 290
- shared password, 193
- shortest-path first (SPF) algorithm, 111, 117, 120
- show | compare command, 21
- show bgp neighbor command, 203–205, 359, 366
- show bgp summary command, 360, 366
- show chassis alarms command, 331
- show chassis fpc pic-status command, 333
- show chassis hardware command, 363
- show chassis hardware detail command, 364
- show chassis hierarchy, 71
- show command, 69, 71, 75, 77, 82–83, 308, 316
- show configuration command, 227, 364
- show Ethernet-switching interfaces command, 366
- show interfaces brief command, 308–310
- show interfaces command, 69, 79, 308, 310–312, 331, 353, 365
- show interfaces detail command, 185–186, 309, 311–313, 365
- show interfaces detail interface-name command, 365
- show interfaces extensive command, 189, 195, 313, 350–351, 365
- show interfaces extensive interface-name command, 365
- show interfaces interface-name command, 365
- show interfaces terse command, 104, 338, 364
- show ipsec security-association command, 298
- show isis adjacency command, 122, 366
- show isis database command, 122
- show isis interface command, 122, 366
- show isis route command, 122

- show log command, 98
- show log messages command, 174, 367
- show mpls lsp extensive command, 278
- show ospf database command, 119
- show ospf interface command, 119, 366
- show ospf neighbor command, 119, 341, 366
- show ospf route command, 119
- show rip neighbor command, 116, 365
- show route command, 112, 209, 313–315, 365
- show route detail command, 313, 315–316
- show route exact command, 313, 318
- show route forwarding-table command, 340–341, 365
- show route inet.0 command, 365
- show route inet.6 command, 365
- show route protocol bgp command, 207, 210, 366
- show route protocol command, 365
- show route protocol isis command, 122
- show route protocol ospf command, 119
- show route summary command, 313, 316–318
- show rsvp interface command, 280–281
- show services nat pool command, 299
- show services rpm probe-results command, 321
- show spanning-tree bridge command, 366
- show spanning-tree interface command, 366
- show system cre-dumps command, 336
- show system processes command, 334–336
- show system uptime command, 367
- show system users command, 128
- show version command, 363
- show version detail command, 363
- show virtual-chassis status command, 366
- show vlans command, 147, 366
- signaling protocol, 273–274
- Simple Network Management Protocol (SNMP), 13, 26, 95–97
- single mode authentication, 153
- single-secure mode authentication, 154
- SLAX (Stylesheet Language Alternative Syntax), 353–354
- SMI (Structure of Management Information), 95
- SNMP (Simple Network Management Protocol), 13, 26, 95–97
- SNMP Set command, 124
- snmp statement, 73
- so- string, 356
- SOA (Service-Oriented Architecture), 38
- software, troubleshooting, 334–336
- Software as a Service (SaaS), 38
- software development, JUNOS, 14
- software development kit (SDK), 27
- software release numbering, JUNOS, 16–17
- software release train, JUNOS, 15–16
- SONAR, 306
- SONET interface, 106, 331–332, 350–351
- source address, 262–263
- source code, 14
- space, 40
- spacebar, 79
- Spanning Tree Protocol (STP), 33, 147
- SPF (shortest-path first) algorithm, 111, 117, 120
- SPI (security parameter index), 292, 296
- SRC (Session Resource Control), 26
- SSH (Secure Shell), 124, 126–127, 131–133, 168–169
- ssh command, 75
- start shell sh command, 175
- startup configuration option, 97
- stateful firewall, 59–60
- stateless firewall, 58
- statements configuration mode, 72
- static configuration, 159, 273
- static route, 47, 110, 208, 282

- status configuration mode command, 129
 - STP (Spanning Tree Protocol), 33, 147
 - strict keyword, 286
 - strict-high scheduling, 257
 - strong password, 125
 - Structure of Management Information (SMI), 95
 - stub area, 119
 - Stylesheet Language Alternative Syntax (SLAX), 353–354
 - subnet, 208, 214
 - subnet mask, 45
 - subnetwork, 45
 - subset, 146
 - super-user privilege class, 93
 - supplicant keyword, 153
 - support, JUNOS, 28–29, 371
 - swap label operation, 272
 - switching delay, 242
 - switch/switching
 - configuring, 142–143
 - connecting, 143–144
 - destinations, 32–33
 - hardware, 41–42
 - interconnecting, 154–159
 - Layer 3, 34
 - layers, 32
 - Network Access Control, 36–37
 - overview, 31–32, 141–142
 - plugging devices into, 143
 - racking, 142
 - scaling, 37–40
 - segmenting LANs, 145–154
 - unified communications, 35–36
 - using as routers, 159–160
 - symmetric-key hash function, 290
 - syntax checking, 20
 - syslog. *See* system log
 - syslog facility, 170
 - system command, 69
 - system event, 170
 - system identifier, 121
 - system issues, 346, 348–349
 - system log (syslog)
 - filtering events to different files, 174–175
 - hardware-related entries, 332–333
 - managing log files, 176–177
 - messages, 170–174, 170–176
 - overview, 24
 - preventing problems, 329–330
 - refining access to events, 175–176
 - software-related entries, 334
 - as troubleshooting tool, 326
 - turning on, 173
 - system redundancy, 12
 - system root-authentication statement, 88
 - system statement, 73–74
- ## ● T ●
- T1 interface, 106, 166, 180, 183–184
 - Tab key, 79
 - tag, 27
 - TCP traffic, 133, 139
 - technical publications, 369
 - telephone number, 371
 - Telnet, 59, 167–168
 - telnet command, 75
 - term, 222–225
 - terminating action, 229
 - text string, 101
 - then statement, 229, 354
 - through match type, 234, 235
 - time, setting, 99–100
 - time zone, 99–100
 - time-zone statement, 74
 - toolkit, troubleshooting, 326–327
 - top command, 77
 - top of rack (TOR), 39
 - to-router3 path, 283
 - ToS (Type of Service), 245
 - trace action, 228
 - trace file, 326
 - trace log, 24, 97, 177–178
 - traceoptions command, 24, 99, 177
 - traceroute command, 75, 284, 286, 306–308, 326
 - tracking
 - events, 95–99
 - interfaces, 104–105

- traffic, 123, 250, 255–257, 274–275. *See also*
 - inbound traffic; outbound traffic
 - traffic engineering, 51
 - traffic statistics, 312
 - training, JUNOS, 370
 - transit interface, 276–277
 - transit router, 270, 271, 289
 - transit traffic, 104
 - transmission rate, capping, 257–258
 - transparent bridging, 33
 - transport layer, 325
 - transport mode, 295
 - transport protocol, 59
 - transport session, 59
 - trap, 96
 - Triple Data Encryption Standard-cipher
 - Block Chaining (3DES-CBC), 291
 - troubleshooting
 - general tips, 323–324
 - hardware, 331–334
 - interface, 337–340
 - layers, 325–326
 - maximum transmission unit, 343–344
 - overview, 327–329
 - pinpointing problems, 330–331
 - preventing problems, 329–330
 - routing, 340–343
 - software, 334–336
 - toolkit for, 326–327
 - trunk port, 151
 - T-series core platforms, 55
 - tunnel, 289. *See also* secure tunnel
 - tunnel mode, 295
 - type external command, 200
 - Type of Service (ToS), 245
- U •
- UAC (Unified Access Control), 37
 - unauthorized privilege class, 93
 - undocumented feature, 346, 348–349
 - unicast traffic, 47, 49
 - unidirectional security association, 292
 - Unified Access Control (UAC), 37
 - unified communication. *See also* Class of Service
 - high availability, 36, 61–64
 - Power over Ethernet interface, 35, 147
 - unique numeric identifier, 296
 - unit, 103
 - unit 0 statement, 103
 - unit statement, 107
 - Universal Coordinated Time (UTC), 100, 173
 - up arrow shortcut, 80
 - up command, 77
 - upgrading JUNOS software, 27–29
 - upto match type, 234–235
 - user account, 91–94
 - user configuration option, 98
 - user syslog facility, 171
 - UTC (Universal Coordinated Time), 100, 173
- V •
- /var/log/ log file directory, 174, 176
 - VCEPs (Virtual Chassis Extender Ports), 143
 - vci statement, 188
 - VCP (Virtual Chassis port), 143, 154
 - video traffic, 250, 255
 - Virtual Chassis cable, 143
 - Virtual Chassis configuration, 143–144, 154–159
 - Virtual Chassis Extender Port (VCEP), 143
 - Virtual Chassis port (VCP), 143, 154
 - Virtual Local Area Network (VLAN), 33, 146–154, 160
 - virtual path identifier (VPI), 188
 - Virtual Private LAN Services (VPLS), 53
 - Virtual Private Network (VPN)
 - overview, 52
 - secure tunnel, 61
 - troubleshooting, 327–329, 330–344
 - virtualization, 52
 - VLAN (Virtual Local Area Network), 33, 146–154, 160
 - Voice over IP (VoIP), 35, 60, 143

voice traffic, 250, 255, 257, 274–275
VoIP (Voice over IP), 35, 60, 143
voltage, 180
VPI (virtual path identifier), 188
VPLS (Virtual Private LAN Services), 53
VPN. *See* Virtual Private Network

• W •

W3C (World Wide Web Consortium), 27
WAN (wide area network), 33
WAP (wireless access point), 143
Warning severity level, 99
warning syslog severity, 172
Web site
 books, 370
 certification, 371
 Configuration and Diagnostic Automation
 Guide, 354
 customer care, 371
 forums, 370
 IPSec tunnels, 95
 literature, 370
 media, 370

NETCONF API, 27
 new releases, 29
 products and services, 25, 41
 router MIBs, 95
 security, 58
 support, 371
 technical assistance, 371
 technical publications, 369
 training, 370
wide area network (WAN), 33
wildcard, 252
wireless access point (WAP), 143
workflow, troubleshooting, 328
World Wide Web Consortium (W3C), 27
writing JUNOScript, 353–354

• X •

XML (eXtensible Markup Language),
 27, 352–353
 <xsl:choose> element, 354
 <xsl:if> element, 354
XSLT (Extensible Stylesheet Language
 Transformation), 353–354