
Index

- Access to landslide sites, 45–46
- Active earth pressure, 139–140, 177
- Adits:
- drainage, 354–356
 - exploratory, 65–66
- Aging of sands, 56, 142
- All weather fill, 294
- Alternatives to remediation, 269–274
- Anchors, ground, 390–395, 548–555
- Anchor block retaining wall, 395–403
- Ancient landslide terrain reactivation, 22–24, 489–495, 507–513, 514–519
- Angle of repose test, 126–127
- Artesian pressures:
- cause of, 14, 203
 - landslide occurrence, 14–15, 501–506, 529–540
 - piezometer installation in, 88
 - stability calculations, 203–206
- At-rest earth pressure, 139–140
- Automatic Data Acquisition Systems, 88–89, 507–513
- Avoidance of landslides, 271
- Back analysis of landslides:
- principle, 173
 - velocity effect, 173–175
- Becker Penetration Test, 57–59
- Bin wall, 422–423
- Bioremediation, 307–313
- Bishop's Routine method, 193–196
- Bishop sand sampler, 64–65
- Blanket drains, 341–342
- Buttress:
- external, 278–281, 541–547, 556–562
 - infill, 281–283
 - replacement, 283–288
- Cantilever wall, concrete, 420–421
- Casagrande classification chart, 144–146
- Casing advancer, 49
- Causation of landslides:
- artesian pressure, 14–15, 501–506, 529–540
 - canals, 10
 - coastal (sea) erosion, 16
 - concentrated water sources, 15, 281–282
 - cut slopes, 13–14, 285–286, 507–513
 - debris flows, 20–22
 - delayed failure, 24–28, 165–167, 520–528, 541–547
 - earth dams, 13
 - earthquake-induced, 28–32, 489–495, 514–519
 - fills, 12–13, 287, 514–519, 529–540, 541–547, 556–562
 - irrigation, 10–11
 - rainfall, 8–9
 - river erosion, 15–16, 406, 496–500, 546–553
 - springs and seepage, 9–10, 297, 568–571
 - subaerial submarine, 16–20, 529–540
 - weathering, 11–12
- Cement grouting, 373–375
- Charts for stability analysis, 218
- Chemical grouting, 375–377
- Chunam plaster, 307
- Circular arc analysis, 193–197, 541–547
- Classification of landslides, 4–6

- Classification of sands, 121–123
- Clay-silt soils:
 - Casagrande classification chart, 144–146
 - consistency, 149
 - consolidation, coefficient of, 150–153
 - Cornforth classification chart, 146–148
 - drained strength, 154–156
 - fill, 293
 - gradation analysis, 143
 - permeability, coefficient of, 153
 - rate of consolidation, 151–154
 - residual strength, 159–162
 - time factor, 150–151
 - undrained strength, 156–159
- Clearcutting, 21–22
- Closely-sequenced construction, 265–267, 285
- Coefficient of consolidation c_v :
 - basics, 149–154
 - vs. cohesive index, 153
- Cohesion, 115
- Cohesion intercept, 115
- Cohesionless soils (sand, gravel):
 - aging of sand, 142
 - classification, 121–123
 - field behavior, 141–142
 - stability, 142
- Cohesive Index, 146–148, 153
- Compaction:
 - dynamic, 457–458
 - grouting, 455–457
 - vibro, 458–461
- Conceptual construction costs, 267–268
- Concrete block systems, 313–314
- Cone penetrometer, 59
- Consolidation of clay foundation, 359–360
- Construction costs, 267–268
- Contract bidding, 275–276
- Cornforth classification chart, 148
- Crib wall, 421–423
- Critical stability, 172
- Cut slopes, 13–14

- Debris flows, 20–22
- Deep soil mixing, 379–384, 464–466, 476
- Deep wells, 342–345
- Delayed failure, 24–28, 165–167, 520–528, 541–547
- Density limits of sand:
 - maximum, 125–126
 - minimum, 125
- Density of soils, 170–171
- Dewatering:
 - through consolidation, 359–360
 - site, 262–263, 315–316, 347–350, 505–506
- Differential erosion, 568–571

- Discrete shear zone:
 - measurement of, 473–474
 - significance of, 173
- Double wedge analysis:
 - method, 180–186
 - remedial analyses, 186, 190–193, 514–519, 520–528
- Dowel piles, 467–474
- Drains:
 - array of, 356–358
 - blanket, 341–342
 - french, 340–341
 - horizontal, 316–327
 - interior, 280
 - relief (wells), 350–353
 - surface, 358–359
 - trench, 327–340, 477, 563–567
 - tunnel, 492
 - vertical gravity, 353–354
 - wick (prefabricated), 360–362
- Drainage blanket, 341–342
- Drainage pipe, 236
- Drainage soils, 123
- Drained strength of sand:
 - estimate, 131–134
 - measurement, 127–131
 - selection for analysis, 134–135
- Drilling:
 - auger, 48
 - Becker, 57–59
 - hollow stem auger, 47–48
 - ODEX (downhole hammer), 49–50
 - overwater, 45–46
 - rotary, 46–47
 - shell and auger, 48
 - wireline casing advancer, 49
- Dynamic compaction, 457–458

- Earth pressures:
 - active, 139–140, 177, 386
 - behind retaining walls, 385–389
 - general, 385–387
 - passive, 386
 - at rest, 387
- Earthquake induced movements, 253–256, 495, 517–519
- Earthworks:
 - bidding contracts, 275–276
 - costs, 275
 - excavate and replace, 463–464
 - specifications for compacted fill, 292–294
- Effective stress analysis, 172, 529–540
- Effective stress principle, 101
- Ejector wells, 349–350
- Element wall, 395–403
- Engineering News-Record Construction Cost Index, 267

- Erosion:
- bowls, 281–282, 496–500
 - control products, 309–314
 - differential, 568–571
- Excavations, temporary, 141–142
- Excavation and replacement, 463–464
- Fabrics, 250
- Factor of safety, static:
- definition, 220
 - effect of velocity on, 173–175
 - relative to landslide size, 221
 - required, 221, 261–262
- Field vane test, 68–69
- Fills:
- clay, 154
 - failure due to, 12, 514–517
 - rock, 142, 264
 - sand, 142
- Filters:
- graded, 232–233, 263–264, 295–298, 496–500
 - permeability criterion, 232
 - pipng criterion, 232
 - reverse, 298–300
 - for silt and clay, 234–235
 - size segregation, 233
- Flow slides:
- debris, 20–22, 501–506
 - marine, 16–20, 529–540
- Foundation consolidation, 149–154
- Free-draining soils, 123
- French drains, 340–341
- Gabions:
- mattresses, 302–304
 - wall, 423
- Geological hazard mapping, 478–480
- Geological mapping, 43
- Geophysical explorations, 66–67
- Geotextile fabric, 249–250, 264
- Graben:
- nature of, 180, 527
 - width–depth relationship, 181
- Graded filters:
- general, 232–233, 263–264, 295–298, 496–500
 - relative density of, 57–59
- Gravity drains, vertical, 353–356
- Gravity retaining walls, 385–390, 420–423
- Ground anchors, 390–395, 548–555
- Ground movement during earthquake, 255–258
- Groundwater:
- flow in shear zone, 91
 - fluctuations seasonally, 91–94
 - lowering, 262–263
 - profile, 90–91
 - in stability analyses, 95
- Grouting:
- cement based, 373–375
 - chemical, 375–377
 - compaction, 455–457
 - curtain, 372–373
 - jet, 377–379, 477
- Grouted riprap, 301–302
- Hazard mapping of landslide risk, 478–486
- Height of slope measurement, 38–42
- Highly sensitive silt and clay, 34–35
- Hollow stem auger drilling, 47–48
- Horizontal drains, 316–327
- Inclinometers:
- casing backfill, 73–75
 - data plots, 77–81
 - errors, systematic, 78–81
 - grouted backfill, 73–75
 - inclined casings, 72, 548–555
 - in-place, 81–82, 508
 - reading, 75–77
 - sand backfill, 74–75
- Infinite slope analysis, 178–180
- Jet grouting, 377–379, 477
- Landslide:
- definition, 4
 - depth, 181
 - hazard maps, 478–480
 - size classification, 4
 - terms, 4
 - type classification, 4–6
 - velocity, 165–169, 173–175
- Liquefaction:
- analysis, 251–254
 - cyclic shear test, 117–118
 - definition, 251
 - improvement verification, 454, 456, 463
 - test apparatus, 116–118
- Liners, slope, 369–372
- Loess, 33–34
- Lowe and Karafiath strength envelope, 210–212
- Maintenance of landslides, 269–270
- Maps, landslide hazard, 478–480
- Marginal stabilization, 273–274, 514–519
- Masonry wall, 420
- Maximum density of sand, 125–126
- Mechanically-stabilized earth walls, 442–453
- Micropiles, 435–441

- Microtunnels, 354–355
- Minimum density of sand, 125
- Minimum intergranular density, 125
- Mohr diagram, 115–116
- Monitoring of survey hubs, 45, 489–495, 516–518, 520–522, 541–544
- Movement of ground during earthquakes, 255–258, 495, 517–518
- Nails, soil, 425–435, 507–509
- Neutral line concept, 218–219
- Non-circular stability analyses, 197–198
- Normally consolidated clay:
 - definition, 154
 - shear strength, 154
 - stability, 157, 162–163
- Null indicator, triaxial tests, 103

- Observation of landslides, 226–228, 270–271
- ODEX drilling, 49–50
- Original Profile analysis, 223–226, 410–411
- Osterberg piston sampler, 63
- Overburden drilling, 46–50
- Overconsolidated clay:
 - definition, 154
 - selection of design shear strength parameters, 164–165
 - shear movements, 165–169
 - shear strength, 154–162
 - stability, 163–165
- Overwater drilling, 45–46

- Pajari measurements, 325–326
- Partly consolidated soils, stability of, 199–203, 529–540
- Partly submerged slopes, stability of, 198–199
- Passive earth pressure, 139–140, 177
- Penetrometers:
 - cone, 59
 - pocket, 118–119
- Permeability:
 - vs. cohesive index, 153
 - field measurement, 96–99, 565
 - packer tests, 98–99
- Photographing a landslide, 42–43
- Piezometers:
 - fully grouted installation, 88
 - Halcrow buckets, 85
 - pneumatic type, 87
 - response time, 85
 - sensor position, 83
 - standpipe type, 84–85
 - vibrating wire type, 86–87, 508
- Piles:
 - resistance to sliding, 206–207
 - shear, 413–418, 467–474
- Pitcher sampler, 63–64
- Plane strain tests, 113–115, 128–131, 138
- Plasticity tests, 143–144
- Plastic liners, 369–372
- Pore pressure parameters A and B, 102
- Power auger drilling, 48
- Prefabricated vertical drains, 360–362, 505
- Preliminary site investigation, 37–43
- Principle of effective stress, 101
- Progressive failure, 164
- Pseudo-static stability analysis, 254–255

- Quick-clay, 34–35

- Rapid drawdown analysis, 207–214
- Regrading slopes, 276–278, 524–526
- Reinforced soil slopes, 453
- Relative cost of construction chart, 268
- Relative density:
 - gravel, 57–59
 - sand, 50–57, 124–127
- Relative dry density, 124
- Reliability analysis (Taylor Series method), 228–231
- Relief wells:
 - inclined, 352–353
 - vertical, 350–352
- Remedial costs, comparative, 268
- Remolded shear strength of clay, 158
- Residual shear strength of clay:
 - measurement, 110–113, 159–162, 557–558
 - velocity, effect of, 257–260
 - weathering, effect of, 556–562
- Residual strength of sand during earthquake, 253–254
- Retaining walls:
 - backfill, 389
 - bin, 422–423
 - concrete cantilever, 420–421
 - concrete crib, 421–422
 - concrete/masonry gravity, 420
 - earth pressures, 385–390
 - element, 395–403
 - gabion, 423
 - mechanically-stabilized earth, 442 – 453
 - micropile, 435–441
 - shear pile, 413–418, 507–513, 548–555
 - slurry trench, 418–420
 - soil nail, 425–435
 - soldier pile, 403–413
- Reverse filters, 298–300
- Reverse (antithetic) scarp, 181, 526
- Riprap:
 - construction, 300–301, 496–500, 541–547
 - design against stream erosion, 247–249
 - design against wave erosion, 237–247
 - grouted, 301–302
- Ring shear test:
 - apparatus, 111–112
 - residual strength measurement, 112–113
- Rockfall Hazard Rating System, 479–485, 568–571

- Rockfill:
 characteristics, 142, 263
 construction, 265
 properties, 142, 264
- Rock slopes, 33, 568–571
- Rotary drilling, 46–47
- Rubblized slip surface, 476–477
- Sample disturbance, 60
- Sampling equipment, 62–65
- Sand fill, 293–294
- Sand stability, 141–142
- Secondary cracks and scarps in landslides, 181–182
- Selective stabilization, 271–273, 548–555, 556–562
- Sensitivity of clay, 34–35
- Seismic refraction surveys, 66–67
- Shaft/drainage array, 356–358
- Shapes of landslides, 172–173
- Shear box test:
 apparatus, 109–110
 residual strength measurement, 110–111
- Shear key, 288–292, 556–562
- Shear piles, isolated, 467–474
- Shear pile wall, 413–418, 507–513, 548–555
- Shear zone, discrete, 23, 173, 473–474
- Shell and auger drilling, 48
- Shotcrete, 304–306
- Sinkhole repair, 299–300
- Site reconnaissance, 37
- Slope liners, 369–372
- Slope measurements, 38–42
- Slope regrading, 276–278
- Slurry trench construction:
 cutoff, 363–369
 wall, 418–420
- Soil mixing, deep, 379–384, 464–466, 476–477
- Soil nail wall, 425–435, 510
- Soldier pile wall, 403–413
- Spencer's method, 196–197
- Stability analysis:
 artesian conditions, 203–206
 Bishop's method, 193–197
 charts, 218
 circular arc, 193–196, 541–547
 double wedge, 180–193, 514–519, 520–528
 infinite slope, 178–180
 non-circular, 197–198
 pseudo-static, 254–255
 Spencer's method, 196–197
 three-dimensional, 214, 524
 triple wedge, 186–193
 unsaturated soils, 215–218
 vertical face, 175–176
- Standard Penetration Test (SPT), 50–59
- Stone columns (vibro-replacement), 461–463, 474–475
- Strain effect on granular strength, 130–131
- Subbottom profiling, 67
- Subgrade preparation, 292–293
- Submarine flow slides, 16–20, 529–540
- Surface water control, 358–359
- Surveys, ground, 43–45, 489–495, 516–518, 520–522, 541–544
- Temporary site dewatering, 262–263, 315–316, 347–350, 505–506,
- Temporary excavations, 142, 162–163, 175–176, 265–267
- Tension crack, 176
- Test pits, exploratory, 65–66
- Three-dimensional stability analyses, 214, 524
- Tiebacks, 388–393, 548–555
- Topography, 43–44
- Total stress analysis, 172, 529–540
- Trees, effect on stability, 308
- Trench drains, 327–340, 477, 563–567
- Trench safety, 65, 566–567
- Trenchfill revetment, 314
- Triaxial tests:
 apparatus, 102–104
 consolidation phase, 106–107
 permeability test, 107
 presaturation phase, 105–106
 shear phase, 108–109
 types of shear tests, 104–105
- Triple wedge analysis:
 method, 186–190
 remediation analyses, 190–193
- Tunnels:
 drainage, 354–356, 489–495
 micro, 354–355
- Undisturbed (relatively) sampling, 60–65
- Undrained strength of clays in triaxial tests, 109, 156–159
- Undrained strength of sands in triaxial tests, 135–138
- Unloading treatment, 276–278, 520–528
- Unsaturated soils, stability, 215–218
- Vane testing:
 Bjerrum correction, 69
 field, 68–69
 laboratory, 119–120
 torvane, 119
- Velocity of landslides:
 accelerating, 165–167
 constant, 167–168
 decelerating, 168–169
 effect on back analysis, 173–175
 effect on factor of safety calculations, 527–528
- Verification tests, ground treatment, 454, 456, 457, 463
- Vertical cut stability, 175–176

Vertical drains:

gravity, 353–354

prefabricated, 360–362

Vibro-compaction, 458–461

Vibro-replacement (stone columns), 461–463, 474–475

Walls, *see* Retaining Walls

Weathering, 11

Wellpoints, 345–349

Wells:

deep, 342–345

ejector, 349–350

inclined relief, 352–353

relief, 350–352

Wick drains, 360–362

Wireline drilling, 49