

Index

- μ TESLA, 136
- Abstract regions, 109, 112
- ACQUIRE, 98
- Aggregation, 92, 105
- Agilla, 108, 111
- ALOHA, 77, 88, 219
- Analysis, 60
- Antenna, 46
 - dipole, 49
 - isotropic, 344
 - loop, 49
 - monopole, 49
 - omnidirectional, 338
 - planar, 48
- API, *see* Application Programming Interface
- Application, 11
 - domain, 11
 - event detection, 12
 - monitoring, 12, 327
 - object classification, 12
 - object tracking, 12, 335
 - quality of service, 128, 219
- Application Programming Interface, 103, 104, 106, 193, 203, 343
- Asymmetric traffic, 91
- ATEMU, 62, 65
- Avrora, 62, 65
- B-MAC, 88
- Bertha, 120, 122
- Bluetooth, 22
 - security, 139
- Bootloader, 121, 203, 213
- Carrier Sense Multiple Access, 77, 79
- Cluster head, 80
- Collisions, 76
- Component, 56
- Component-based design, 56, 58
- Concurrency, 116
- Configuration, 55, 279, 328
- Connectivity, 53
- Contiki, 120, 122, 123
- CORMOS, 120, 122
- Cost, 17, 52
- Cougar, 107, 111
- Coverage, 53
- Cross-layer, 217
- CSMA, *see* Carrier Sense Multiple Access
- Data fusion, 105
- DCA, 82
- Deployment, 11, 52, 55, 279
 - Infrastructure, 280
- Design dimension, 51, 54
- Design flow, 54
- Design methodology, 56
- DFuse, 109, 112
- Directed diffusion, 94, 256
- DMAC, 84
- DSWare, 107, 111
- DVS, *see* Dynamic voltage scaling
- Dynamic source routing (DSR), 93
- Dynamic voltage scaling, 116
- Embedded system, 115
- Emstar, 58, 59
- Energy management, 116

- Energy-aware routing, 101
- Energy-efficient routing, 101
- Environmental monitoring, 222, 300–312
- Evaluation, 55, 60, 247
- Event-driven programming, 118

- Face Aware Routing (FAR), 96
- FACTS, 109, 112
- FAMA, 79
- Fault tolerance, 16
- FDMA, *see* Frequency Division Multiple Access
- Finite state machine, 120, 251
- Flooding, 97
- Frequency Division Multiple Access, 79
- FSM, *see* Finite state machine

- Gateway, 10, 193, 279, 280, 282, 344
- Global Positioning System, 10, 11, 200, 288, 334, 335, 343, 345
- Global sensor network, 110, 112
- GPS, *see* Global Positioning System
- GRAdient Broadcast (GRAB), 97
- GRATIS, 57, 59
- Greedy Perimeter Stateless Routing (GPSR), 95
- GSN, *see* Global Sensor Network

- H-MAS, 61, 64
- Headnode, 146
- Heterogeneity, 52
- Hidden-node problem, 77, 253

- Idle listening, 76
- IEEE 1451, 19
- IEEE 1451.5, 106
- IEEE 802.15.4, 22, 260, 261
 - Beacon Order (BO), 24
 - security, 136
 - Superframe Order (SO), 24
- Impala, 109, 112
- In-network processing, 105
- Information-directed routing, 99
- Interest, 196, 198

- J-Sim, 61, 64

- Kairos, 109, 112

- LEACH, 85
- Lifetime, 16, 108
- Localization, 222, 327, 334
- Localized max-min energy routing, 101

- MAC, *see* Medium Access Control
- MACA, 78
- Macroprogramming, 109
- MagnetOS, 108, 111
- MARE, 108, 111
- Maté, 107, 108, 111
- Medium Access Control, 75, 145
 - Contention-based, 77
 - Contention-free, 79
 - low duty-cycle, 82
 - multi channel, 80
 - quality of service, 130, 219
 - synchronized, 82
 - unsynchronized, 87
- Microcontroller Unit (MCU), 33
- Middleware, 103
 - application-driven, 106, 108, 110
 - database, 106, 107, 110
 - mobile agent, *see* Mobile agent
 - programming abstraction, 106
 - virtual machine, *see* Virtual machine
- MiLAN, 108, 112
- Minimum-cost forwarding, 99
- Mires, 109, 112
- MiWi, 28
- MMAC, 81
- Mobicast, 96
- Mobile agent, 106, 108–110
- Mobility, 52
- Model-driven design, 56, 58
- MOS, 121, 122

- NAMA, 85
- nano-RK, 121, 122
- nesC, 57, 59
- Network scan, 83, 151, 232

- Operating system, 103, 115, 203
 - event-based, 117, 118, 123

- microkernel, 115, 117
- monolithic, 115, 117
- multithreading, 117, 118, 203
- preemptive, 117, 118, 123, 203
- OS, *see* Operating System
- Overhead, 77
- Overhearing, 76

- PACT, 86
- PAMAS, 90
- Physical layer
 - quality of service, 131, 220
- Platform-based design, 57, 58
- Positioning, 334, 343
- POSIX, 121
- Proactive routing, 93
- Protocol stack, 103
- Protothreads, 110
- Prowler, 61, 64
- Pump-slowly, fetch-quickly (PSFQ), 129

- Q-MAC, 131
- QoS, *see* Quality of Service
- Quality of Service, 53, 105, 108, 125

- Reactive routing, 93
- Realtime, 17, 53, 116
- Received signal strength indicator, 286, 288, 335, 336, 340
- Receiver-decided forwarding, 93
- Reprogramming, 121, 203, 213
- Resource constraints, 11
- RETOS, 121, 122
- RF wake-up scheme, 87
- Robustness, 53
- Routing
 - cartesian, 95
 - cost field-based, 99
 - datacentric, 94
 - geographic, 95
 - location-based, 95
 - multipath Routing, 97
 - negotiation-based, 97
 - nodecentric, 93
 - quality of service, 129, 219
 - query-based, 98
- RSSI, *see* Received Signal Strength Indicator
- RTS/CTS procedure, 78

- S-MAC, 83, 256
- Scalability, 16
- SDL, *see* Specification and description language
- Security, 17, 133
 - active attacks, 134
 - architectures, 135
 - attacks, 133
 - centralized key distribution, 141
 - denial of service, 134
 - experiments, 290
 - key distribution, 140
 - node capturing, 134
 - passive attacks, 134
 - pre-distributed keys, 140
 - public-key cryptography, 140
 - random key pre-distributed, 141
 - routing attacks, 135
 - threats, 133
 - TinySec, 135
 - traffic analysis, 134
- Self-configuration, 224
- Sender-decided forwarding, 93
- senQ, 61, 64, 247
- SENS, 65
- SENSE, 61, 64
- SENSIM, 61, 64
- Sensor Protocols for Information via Negotiation (SPIN), 98
- SensorOS, 196, 203, 327, 331
 - bootloader, 213
 - lightweight kernel, 203, 211, 333
 - system call interface, 207
- SensorSim, 61, 64, 247
- Sensorware, 108, 111
- Sequential assignment routing (SAR), 130
- Service discovery, 195
- Simulation, 60, 61, 247, 329
- SINA, 107, 111
- Sink, 10, 91
- SMACS, 84
- SNAP, 62, 65

- SNEP, 136
- SOS, 120, 122
- Specification and description language, 247, 251, 329
- SpeckMAC, 88
- SPEED, 129
- SPINS, 136
- SQL, *see* Structured query language
- SRSA, 86
- STEM, 90
- Structured query language, 107, 111
- Subnode, 146
- Superframe, 315
- SWAN, 61, 64
- Synchronization inaccuracy, 219, 233, 311
- Synchroization inaccuracy, 230
- t-kernel*, 121, 122
- T-MAC, 84
- Task allocation, 104, 108, 109
- TCMote middleware, 107, 111
- TDMA, *see* Time Division Multiple Access
- Time Division Multiple Access, 79
- TinyDB, 107, 111
- TinyLIME, 107, 111
- TinyOS, 56, 57, 62, 120, 122
- TML, 110
- Topology, 53
- TOSSF, 62, 65
- TOSSIM, 57, 62, 65
- Tracking, 327
- Trajectory and Energy-Based Data Dissemination (TEDD), 96
- Trajectory-Based Forwarding (TBF), 95
- TRAMA, 85
- Transceiver
 - antenna, 46
- Transport
 - quality of service, 128
- Tuple space, 107, 108
- TUTWSN, 5, 256
 - API, 193, 260, 282, 344
 - API profile, 196
 - contention models, 234
 - gateway API, 194, 198
 - MAC, 259
 - node API, 196, 198
 - power consumption models, 240
 - radio energy models, 230
 - Routing, 183, 260
 - SensorOS, *see* SensorOS
 - throughput models, 238
 - user interface, 280, 282–283, 332, 341
- TUTWSN MAC, 145
 - channel access, 147
 - neighbor discovery, 152
 - slot allocation, 159
- Two-tier data dissemination (TTDD), 97
- Ubiquitous computing, 9
- Viptos, 57, 59
- Virtual machine, 106–108, 110
- VisualSense, 57, 61, 64
- VM, *see* Virtual machine
- Wake-up radio protocol, 89
- Wibree, 28
- Wireless Local Area Network, 4, 9, 69, 313
- Wireless Sensor Network, 4
 - characteristics, 9, 313
 - requirements, 16
- WiseMAC, 88
- WISENES, 247, 327, 329
 - design environment, 248, 328
 - framework, 249
- WLAN, *see* Wireless Local Area Network
- WMNet, 62, 65
- Worldsens, 58, 59
- WSN, *see* Wireless Sensor Network
- Z-MAC, 89
- Z-Wave, 28
- ZigBee, 14, 25, 256, 260, 261, 272
 - contention models, 235
 - power consumption models, 243
 - radio energy models, 232
 - security, 137
 - throughput models, 239