

Index

Note to the Reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

A

AAA (authentication, authorization, and accounting), 360, **363–364**, **367–368**
 accounting in, 365, **374–376**
 authentication in, 364, **368–370**
 authorization in, **364–365**, **370–373**
 defined, 388
 aaa accounting command command, 375
 aaa accounting connection command, 375
 aaa accounting exec command, 368–369, 375
 aaa accounting function command, 375–376
 aaa accounting network command, 375
 aaa accounting system command, 375
 aaa authentication command, 366
 aaa authentication enable command, 368–369
 aaa authentication login command, 368–369
 aaa authentication ppp user command, 367
 aaa authorization command, 366
 aaa authorization commands command, 373
 aaa authorization config-commands command, 373
 aaa authorization exec command, 373
 aaa authorization function command, 374
 aaa authorization network command, 373
 aaa authorization network tacacs+ command, 367
 aaa authorization reverse-access command, 373
 aaa new-model command, 368–369
 aarp option, 303

access control
 components in, **361–363**
 defined, 388
 access-list command, 239, 338, 340
 access lists
 DDR with, 179–180
 defined, 388
 access methods, 388
 access modes in routers, **365–367**
 access rates
 defined, 388
 in Frame Relay performance, 260
 access servers, 362
 configuring, 82
 for dedicated and interactive PPP, 83
 for local devices, 83–89, 84–85, 87, 90
 defined, 388
 accounting, 360
 configuring, **374–376**
 defined, 388
 ACK (acknowledgments), 388
 Active connection state in LMI, 258
 active number in WFQ, 298
 Address field
 in LAPD, **157–158**, 157
 in PPP, 80
 Address Extension field, 158
 address mapping, 388
 address masks, 388
 address resolution, 388
 Address Resolution Protocol (ARP), 389
 administrative distance, 388
 ADSL (Asymmetric Digital Subscriber Line), 9, **214–215**
 Advanced Connection Settings dialog box, 132, 132
 Advanced Encryption Standard (AES), 236

408 **Advanced options – authentication, authorization, and accounting (AAA)**

- Advanced options
 - for allowed network protocols, 133
 - for dial-up connection clients, 130–131
- Advanced Research Projects Agency (ARPA), 326
- AES (Advanced Encryption Standard), 236
- AHs (Authentication Headers), 236
- ALERTING messages, 164
- algorithms, 388
- Allowed Network Protocols section, 133
- alternate mark inversion (AMI), 388
- Always On/Dynamic ISDN (AO/DI), 152
- American Standard Code for Information Interchange (ASCII), 389
- AMI (alternate mark inversion), 388
- analog connections
 - cabling in, 26–27
 - defined, 388
 - with modems, 50
- analog dial-up, 389
- analog ports, 32
- analog transmissions, 389
- ANI (Automatic Number Identification), 153
- ANSI LMI version, 258
- AO/DI (Always On/Dynamic ISDN), 152
- apollo option, 303
- appletalk option, 303
- Application Layer, 389
- applications in WAN protocol selection, 20–21
- arap command, 365
- Architecture for Voice, Video, and Integrated Data (AVVID), 29
- ARP (Address Resolution Protocol), 389
- arp option, 304
- ARPA (Advanced Research Projects Agency), 326
- ASCII (American Standard Code for Information Interchange), 389
- Asymmetric Digital Subscriber Line (ADSL), 9, 214–215
- async dynamic address command, 85
- async mode dedicated command, 83
- async mode interactive command, 83
- async packet-mode connections, 366
- asynchronous connections, 50
 - cabling in, 26–27
 - configuring, 58–65
 - defined, 389
 - dial-up
 - characteristics of, 16–22
 - uses for, 4–5
 - exam essentials, 66–67
 - hands-on labs, 68–70
 - key terms, 67
 - modems for, 50–53, 51
 - configuring, 58–65
 - modulation standards for, 55–57
 - signaling and cabling, 53
 - review questions, 71–76
 - summary, 65–66
 - written lab, 68, 74
- asynchronous transmissions, 389
- AT (attention) commands, 59, 62–63
- ATM (Asynchronous Transfer Mode), 4
 - as encapsulation type, 14
 - uses for, 11
 - for VPNs, 240
- Authenticate-Request packets, 172–173, 172
- authentication, 360
 - configuring, 368–370
 - defined, 389
 - in ISDN, 171
 - CHAP, 173–175, 173, 175
 - PAP, 171–173, 172
 - in PPP, 91–93, 91–93
- authentication, authorization, and accounting (AAA), 360, 363–364, 367–368
 - accounting in, 365, 374–376
 - authentication in, 364, 368–370
 - authorization in, 364–365, 370–373
 - defined, 388

Authentication Headers (AHs), 236
 authorization, 360
 configuring, 370–373
 defined, 389
 autodiscovery function, 58
 automatic modem configuration, 58
 commands for, 59–61
 verifying and troubleshooting, 61–62
 Automatic Number Identification
 (ANI), 153
 autoselect command, 82
 auxiliary ports, 389
 availability in WAN protocol selection, 17
 AVVID (Architecture for Voice, Video,
 and Integrated Data), 29

B

B (bearer) channels
 defined, 389
 in ISDN, 150
 B8ZS (binary 8-zero substitution) code, 389
 backup delay command, 185
 backup interface bri0 command, 182
 backup load command, 190–191
 Backward Explicit Congestion Notification
 (BECN) bit
 defined, 390
 in Frame Relay, 261–262, 274
 bandwidth
 defined, 389
 in DSL, 214–215
 in WAN protocol selection, 17–18
 Bandwidth on Demand (BoD)
 configuring, 190–191
 defined, 390
 Basic Rate Interface (BRI), 5, 150–152, 151
 cabling in, 27
 defined, 390
 hands-on lab for, 200–203, 200
 packet-mode connections, 366

BASIC switch types, 152
 baud
 in asynchronous modem connections, 61
 defined, 389
 bearer (B) channels
 defined, 389
 in ISDN, 150
 Bearer Capability output, 165
 bearer services
 defined, 390
 in Frame Relay, 252
 BECN (Backward Explicit Congestion
 Notification) bit
 defined, 390
 in Frame Relay, 261–262, 274
 binary 8-zero substitution (B8ZS) code, 389
 binary numbering, 390
 bit stuffing, 79
 BoD (Bandwidth on Demand)
 configuring, 190–191
 defined, 390
 bonding, 33
 BRI (Basic Rate Interface), 5, 150–152, 151
 cabling in, 27
 defined, 390
 hands-on lab for, 200–203, 200
 packet-mode connections, 366
 BRIO B1 LED, 37, 37
 BRIO B2 LED, 37, 37
 Bridge-Group Virtual Interface (BVI), 220
 bridge option in queuing, 304
 broadcasts, 390
 brute force attacks
 CiscoSecure for, 363
 defined, 390
 bstun option, 304
 buffers, 390
 bursting in Frame Relay, 260–261, 261, 276
 BVI (Bridge-Group Virtual Interface), 220
 byte-count command, 305
 byte-count queues, 305–307

410 &C AT command – CHAP (Challenge Authentication Protocol)**C**

- &C AT command, 63
- C/R (Command/Response) field, 158
- cable modems, 10–11, 232–233, 233
 - characteristics of, 16–22
 - Cisco Cable Manager, 235
 - Cisco product line, 234–235
 - defined, 390
 - DOCSIS for, 233–234
 - exam essentials, 240–241
 - hands-on lab, 242–243, 248–249
 - key terms, 241
 - review questions, 244–247, 250
 - summary, 240–241
 - written lab, 242, 247
- cabling and assembling WANs, 26
 - company site equipment
 - identification, 28
 - internetworking and interface options, 26–28
 - verifying network installations, 35–39, 36–38
- CALL PROCEEDING messages, 164
- Call Reference Value (CRV)
 - information, 159
- call setup and teardown in ISDN, 163–166, 164
- callbacks, PPP, 93–97, 400
- Called Number Identification, 153
- Called Party Number output, 166
- Calling Line ID (CLID), 153
- Callref output, 165
- CAR (Committed Access Rate)
 - queuing, 310
- Carrier Detect (CD) signal
 - defined, 390
 - in DTE to DCE signaling, 54
- carrier operations (CO), 391
- catalyst switch configuration, 369–370
- CBWFQ (Class-Based Weighted Fair Queuing), 309
- CCM (Cisco Cable Manager), 235
- CD (Carrier Detect) signal
 - defined, 390
 - in DTE to DCE signaling, 54
- CDMA (code division multiple access), 12
- CDP (Cisco Discovery Protocol)
 - defined, 390
 - operation of, 105
- cdp option in queuing, 304
- cellular WAN connections, 11–13
- central office (CO), 391
- central sites, 29
 - Cisco 3600 platform, 29–30
 - Cisco 3700 platform, 30
 - Cisco 7000/7200/7500 platforms, 30
 - Cisco AS5x00 platform, 30
 - verifying, 35–37, 36
- CH1 LED, 38, 38
- CH1 RXD LED, 38, 38
- CH1 TXD LED, 38, 38
- CH2 LED, 38, 38
- CH2 RXD LED, 38, 38
- CH2 TXD LED, 38, 38
- Challenge Handshake Authentication Protocol (CHAP)
 - defined, 391
 - in ISDN, 173–175, 173, 175
 - in PPP, 81, 92–93
- challenges, 390
- channel-group command, 193
- Channel ID output, 166
- Channel Service Units (CSUs), 392
- Channel type parameter, 192
- channelized E-1
 - configuring, 194–195
 - defined, 390
- channelized T-1, 27
 - configuring, 192–194
 - defined, 391
- CHAP (Challenge Authentication Protocol)
 - defined, 391

- in ISDN, 173–175, 173, 175
- in PPP, 81, 92–93
- chap pap keyword, 92
- character-mode connections
 - commands for, 365–366
 - defined, 391
- checksums
 - defined, 391
 - FCS fields for, 82
- CIFS (Common Internet File System), 310
- CIR (Committed Information Rate)
 - defined, 391
 - in Frame Relay, 6–7, 260, 276–277
- circuit switching, 391
- Cisco Discovery Protocol (CDP)
 - defined, 390
 - operation of, 105
- Cisco IOS software, 391
- cisco option in Frame Relay, 259
- Cisco products, 23–24
 - 700 series, 32, 346–347
 - 766 routers, 38–39, 38
 - 800 series, 34
 - 1000 series, 35
 - 1600 platform, 31, 37, 37
 - 1700 platform, 31
 - 2500 platform, 31
 - 2600xM platform, 31
 - 3600 platform, 29–30
 - 3640 routers, 36–37, 36
 - 3700 platform, 30
 - 7000/7200/7500 platforms, 30
 - AS5x00 platform, 30
 - Cisco Cable Manager, 235
 - CiscoSecure, 362–363
 - fixed interface routers, 24–25
 - modular interface routers, 25
 - selection tools for, 25–26
- Cisco standard for LMI, 258
- CiscoSecure product, 362–363
- Class A networks, 391
- Class B networks, 391
- Class-Based Weighted Fair Queuing (CBWFQ), 309
- Class C networks, 391
- clear ip nat translation command, 343
- clear ip nat translation inside command, 343
- clear ip nat translation outside
 - command, 343
- Clear To Send (CTS) wire, 54
- clearing NAT translation entries, 343
- CLI (Command Line Interface), 391
- CLID (Calling Line ID), 153
- clients
 - in dial-up connections, 124
 - Dial-Up Networking for, 124–125, 125
 - Make New Connection Wizard for, 125–127, 125–127
 - properties for, 127–134, 128–130, 132, 134–135
 - in remote access, 361
- clock rate command, 273
- clocking
 - for asynchronous connections, 50–51
 - defined, 391
- CO (carrier operations), 391
- CO (central office), 391
- COAX (coaxial cable), 232, 233
- code division multiple access (CDMA), 12
- Code field, 173–175, 173
- Command accounting type, 374
- command command for character-mode connections, 365
- Command Line Interface (CLI), 391
- Command/Response (C/R) field, 158
- Committed Access Rate (CAR)
 - queuing, 310
- Committed Information Rate (CIR)
 - defined, 391
 - in Frame Relay, 6–7, 260, 276–277
- committed rate measurement interval, 260

412 Common Internet File System (CIFS) – Control field

- Common Internet File System (CIFS), 310
- company site equipment identification, 28
 - central sites, 29–30
 - remote branches, 31
 - telecommuter, 32
- compress command, 98
- Compressed Serial Line Internet Protocol (CSLIP), 129
- compressedtcp option, 304
- compression, 310–311, 311
 - in Cisco 700 platform, 33
 - considerations for, 313
 - defined, 391
 - exam essentials, 315–316
 - hands-on lab, 317–318, 317
 - key terms, 316
 - link, 312–313
 - in modulation, 56–57
 - payload, 312
 - PPP, 97–99
 - review questions, 319–324
 - status of, 314
 - summary, 314–315
 - TCP header, 311–312
 - written lab, 316, 322
- config-map-class command, 275
- configuring
 - AAA
 - accounting, 374–376
 - authentication, 368–370
 - authorization, 370–373
 - asynchronous modem connections, 58
 - automatic, 58–62
 - manual, 62–65
 - BoD, 190–191
 - channelized T1/E1, 192–195
 - DDR, 176–179
 - dial-up connection clients
 - Dial-Up Networking for, 124–125, 125
 - Make New Connection Wizard for, 125–127, 125–127
 - properties for, 127–134, 128–130, 132, 134–135
 - DSL, 218–220
 - dynamic addressing, 84–87, 84–85, 87
 - Frame Relay, 259
 - IPSec, 237–239
 - ISDN, 166–167
 - dialer interface, 169–171, 177
 - legacy interface, 167–169
 - multilink, 99–101, 99–101
 - NAT, 336–341
 - PAT, 345–347
 - queuing
 - custom, 302–307
 - priority, 299–300
 - Weighted Fair Queuing, 296
 - traffic shaping, 275–276
- conflict logging, 86
- congestion control in Frame Relay, 260–263, 261
- congestive-discard-threshold parameter, 296
- CONNECT messages, 164
- CONNECT ACKNOWLEDGE
 - messages, 164
- Connection accounting type, 374
- connection command, 365
- connection properties for dial-up clients, 127–128
 - General tab, 128, 128
 - Multilink tab, 134, 135
 - Scripting tab, 134, 134
 - Server Types tab, 128–133, 129–130
- connections, asynchronous. *See* asynchronous connections
- console ports, 392
- contention in DSL, 214–215
- Control field
 - in LAPD, 157, 158–159
 - in PPP, 80

convergence with modems, 52
 conversations in WFQ, 295–296
 costs in WAN protocol selection, 18–19
 CPE (Customer Premises Equipment), 256
 CPU cycles in compression, 313
 CPU utilization, 98
 CRC (cyclic redundancy check)
 defined, 392
 in LAPD, 160
 CRV (Call Reference Value)
 information, 159
 crypto IPsec transform-set command, 238
 crypto isakmp key command, 238
 crypto isakmp policy command, 237
 crypto map command, 238–239
 CSLIP (Compressed Serial Line Internet Protocol), 129
 CSUs (Channel Service Units), 392
 CTS (Clear To Send) wire, 54
 custom option in WFQ, 297
 custom queuing, 292, 301–302, 302
 configuring, 302–307
 defined, 392
 Customer Premises Equipment (CPE), 256
 cyclic redundancy check (CRC)
 defined, 392
 in LAPD, 160

D

D (data) channels
 defined, 392
 in ISDN, 150
 &D AT command, 63
 Data Communications Equipment (DCE)
 defined, 392
 with DTE connections, 51, 51, 54
 in Frame Relay, 253
 modems as, 50
 data compression. *See* compression
 Data Encryption Standard (DES), 237
 data exchange phase in PVCs, 255
 Data field in CHAP packets, 173, 173
 data link connection identifiers (DLCIs)
 defined, 393
 in Frame Relay, 255–258, 256–257
 mapping, 256–258, 257
 Data Link Layer, 392
 Data Over Cable Service Interface
 Specification (DOCSIS), 233–234
 Data Service Units (DSUs), 393
 Data Set Ready (DSR) circuits, 393
 Data Terminal Equipment (DTE)
 with DCE connections, 51, 51, 54
 defined, 393
 in Frame Relay, 253
 locking speed of, 135–136, 136
 routers as, 50
 data terminal ready (DTR) circuits
 defined, 393
 in DTE to DCE signaling, 54
 DCE (Data Communications Equipment)
 defined, 392
 with DTE connections, 51, 51, 54
 in Frame Relay, 253
 modems as, 50
 DDR (dial-on-demand routing), 175–176
 with access lists, 179–180
 configuring, 176–179
 defined, 392
 hands-on lab, 197–200, 198
 optional commands in, 179
 for verifying ISDN operations, 180
 DE (Discard Eligibility), 392
 DE (Discard Eligibility) bits
 defined, 392
 in Frame Relay bursting, 260
 debug dialer command, 180
 debug frame-relay lmi Command,
 269–270
 debug frame-relay packet command, 270

414 debug ip nat command – Discard Eligibility (DE)

- debug ip nat command, 342
- debug isdn q921 command, 160–162, 180
- debug isdn q931 command, 164–166, 180
- debug ppp authentication command, 101–102, 175
- debug ppp negotiation command, 102–106
- debug ppp packet command, 106–109
- decnet option, 304
- decnet_node option, 304
- decnet_router-l1 option, 304
- decnet_router-l2 option, 304
- dedicated PPP, 83
- default option
 - in custom queuing, 303
 - in PAT, 345
- default routes, 392
- delays
 - defined, 392
 - in NAT, 330
- Deleted connection state in LMI, 258
- demodulation, 393
- denial-of-service (DoS) attacks
 - dealing with, 363
 - defined, 393
- DES (Data Encryption Standard), 237
- destination addresses, 393
- DHCP (Dynamic Host Configuration Protocol), 84–87, 87
 - in Cisco 700 platform, 33
 - lease length in, 88–89, 90
 - operation of, 87–88
- dial backup, 181, 181
 - defined, 393
 - setting up, 181–183
 - testing, 183–190
- dial-on-demand routing (DDR), 175–176
 - with access lists, 179–180
 - configuring, 176–179
 - defined, 392
 - hands-on labs, 197–200, 198
 - optional commands in, 179
 - for verifying ISDN operations, 180
- Dial-up Connection Properties dialog box, 87, 87
- dial-up networking
 - configuring clients, 124
 - Dial-Up Networking for, 124–125, 125
 - Make New Connection Wizard for, 125–127, 125–127
 - properties for, 127–134, 128–130, 132, 134–135
 - uses for, 122–123
 - verifying, 137, 137
 - with Windows 95/98, 123
- Dial-Up Networking dialog box, 124–125, 125
- Dial-Up Networking Wizard, 125
- dialer-group command, 177, 179, 190
- dialer hold-queue command, 179, 190
- dialer idle-timeout command, 179
- dialer information, 177
- dialer interface in ISDN configuration, 169–171
- dialer-list command, 176–177, 179, 190
- dialer-list 1 protocol ip permit command, 171
- dialer load-threshold command, 179
- dialer map command, 96–97, 167–169, 177
- dialer pool-member command, 170–171
- dialer profiles, 185
- dialer string command, 169–170, 177
- Differentiated Services Code Point (DSCP), 309
- digital connections in DTE, 50
- Digital Subscriber Line. *See* DSL (Digital Subscriber Line)
- Digital Subscriber Line Access Multiplexer (DSLAM), 212
- directory numbers (DNs), 151
- Discard Eligibility (DE), 392

Discard Eligibility (DE) bits
 defined, 392
 in Frame Relay bursting, 260
 Discard Eligibility lists, 262
 DISCONNECT messages, 164, 166
 distributed compression process, 99
 DLCIs (data link connection identifiers)
 defined, 393
 in Frame Relay, 255–258, 256–257
 mapping, 256–258, 257
 dlsw option, 304
 DNs (directory numbers), 151
 DNS (Domain Name Server), 393
 DOCSIS (Data Over Cable Service
 Interface Specification), 233–234
 DoS (denial-of-service) attacks
 dealing with, 363
 defined, 393
 downstream traffic with cable modems, 10
 DSCP (Differentiated Services Code
 Point), 309
 DSL (Digital Subscriber Line), 7–10, 8,
 212–213, 213
 ADSL, 214–215
 characteristics of, 16–22
 configuring, 218–220
 defined, 393
 exam essentials, 222
 G.lite, 215–216
 hands-on lab, 223, 228
 HDSL, 216
 ISDN DSL, 216
 key terms, 223
 review questions, 224–227, 229
 routers for, 217–218
 SDSL, 216
 summary, 221–222
 troubleshooting, 220–221
 type summary, 217
 variations of, 213–214
 VDSL, 216
 written lab, 223, 228

DSLAM (Digital Subscriber Line Access
 Multiplexer), 212
 DSR (Data Set Ready) circuits, 393
 DSUs (Data Service Units), 393
 DTE (Data Terminal Equipment)
 with DCE connections, 51, 51, 54
 defined, 393
 in Frame Relay, 253
 locking speed of, 135–136, 136
 routers as, 50
 DTR (data terminal ready) circuits
 defined, 393
 in DTE to DCE signaling, 54
 dynamic addressing
 configuring, 84–87, 84–85, 87
 in PPP, 83–84
 Dynamic Host Configuration Protocol
 (DHCP), 84–87, 87
 in Cisco 700 platform, 33
 lease length in, 88–89, 90
 operation of, 87–88
 Dynamic Multiple Encapsulation, 192
 dynamic NAT, 329, 338–339
 dynamic-queues parameter, 296

E

E-1 services, 28
 capacity of, 153
 configuring, 194–195
 defined, 393
 e-mail, dial-up networking for, 122
 E protocols in ISDN, 156
 E reference points, 156
 Edit Extra Device dialog box, 134, 135
 egress in Frame Relay, 253
 802.11 standards, 11–12
 802.1q standard, 239
 EIR (Excess Information Rate), 274
 enable command, 365
 Enable Software Compression option, 131

416 Encapsulating Security Payload (ESP) – frame-relay class name command

Encapsulating Security Payload (ESP), 236
 encapsulation
 defined, 393
 WAN protocols. *See* WANs (wide area networks)
 encapsulation command, 170
 encapsulation frame-relay command, 259
 encapsulation ppp command, 91, 100
 encryption
 in compression, 313
 defined, 393
 end-to-end addresses in NAT, 330
 end-to-end reachability in PAT, 344
 Enhanced Terminal Access Controller
 Access Control System (TACACS+)
 protocol
 in authentication, 361
 configuration file, 371–373
 configuring, 379
 defined, 404
 error correction
 defined, 394
 in modulation, 57
 ESF (Extended Super Frame), 394
 ESP (Encapsulating Security Payload), 236
 ET (Exchange Termination), 155
 Ethernet, 32
 exam essentials
 asynchronous connections, 66–67
 cable modems, 240–241
 DSL, 222
 Frame Relay, 278
 ISDN, 195–196
 Microsoft Windows 95/98/2000/XP, 138–139
 NAT and PAT, 348–349
 PPP, 110–111
 queuing and compression, 315–316
 remote access, 39–40
 security, 377–378
 VPNs, 240–241
 Excess Information Rate (EIR), 274

Exchange Termination (ET), 155
 EXEC accounting type, 374
 exec command, 365
 extended IP access lists, 394
 Extended Super Frame (ESF), 394
 extended translation entries, 328
 EZ-ISDN switch types, 152

F

&F AT command, 63
 fair option, 297
 fair-queue command, 296–297
 fast paths, 342
 FCS (Frame Check Sequence) field, 82
 FECN (Forward Explicit Congestion Notification) bits
 defined, 394
 in Frame Relay, 261–262
 Fiber Optics Transmission Systems (FOTS), 151
 file synchronization, 122
 firewalls, 394
 fixed interface routers, 24–25
 Flag field
 in LAPD, 157, 157
 in PPP, 79
 Flash memory, 394
 flow control, 394
 flowcontrol command, 64
 Forward Explicit Congestion Notification (FECN) bits
 defined, 394
 in Frame Relay, 261–262
 FOTS (Fiber Optics Transmission Systems), 151
 fragments keyword, 304
 Frame Check Sequence (FCS) field, 82
 frame-relay adaptive-shaping becn command, 275
 frame-relay class name command, 276

frame-relay custom-queue-list number command, 275

frame-relay de-group command, 262–263

frame-relay de-list command, 262

frame-relay intf-type command, 272–273

frame-relay lmi type command, 272

frame-relay map command, 257–258

frame-relay priority-group number command, 275

Frame Relay protocol, 6, 16, 252–253

- cabling in, 28
- characteristics of, 16–22
- configuring, 259
- congestion control in, 260–263, 261
- defined, 394
- DLCIs in, 255–258, 256–257
- exam essentials, 278
- hands-on labs, 280, 280
 - subinterfaces, 280–281
 - traffic shaping, 282
- history of, 253
- key terms, 279
- LMI for, 258–259, 259
- performance of, 260–262, 261
- point-to-point and multipoint interfaces in, 263–266
- review questions, 283–286, 289–290
- summary, 277–278
- switching in, 270–273, 271, 394
- traffic shaping in, 274–277
- verifying, 266–270
- virtual circuits in, 253–255, 254
- for VPNs, 240
- written lab, 279–280, 287–288

frame-relay switching command, 273

frame-relay traffic-rate average command, 275

frame-relay traffic-shaping command, 276

Frame type parameter, 192

frames, 394

framing, 394

Framing parameter, 194

frequency, 394

front panel LEDs

- Cisco 766 routers, 38–39, 38
- Cisco 1600 routers, 37, 37
- Cisco 3640 routers, 36–37, 36

ftp option, 345

function groups in ISDN, 154–155, 154

G

G.lite, 215–216

General tab for dial-up clients, 128, 128

Generic Router Encapsulation (GRE), 239

global IP addresses in NAT, 328

Global System for Mobile Communications (GSM), 12

GND wire, 54

GRE (Generic Router Encapsulation), 239

group-async packet-mode connections, 366

group command, 237

Group of Four, 394

GSM (Global System for Mobile Communications), 12

gt keyword, 304

H

hands-on labs

- asynchronous connections, 68–70
- cable modems, 242–243, 248–249
- DSL, 223, 228
- Frame Relay, 280, 280
 - subinterfaces, 280–281
 - traffic shaping, 282
- ISDN, 197
 - DDR, 197–200, 198
 - PRI and BRI, 200–203, 200
 - NAT and PAT, 350–351

418 handshakes – Internet

- PPP, 112–113
 - queuing and compression, 317–318, 317
 - security, 379
 - VPNs, 242–243, 248–249
 - handshakes, 394
 - hash md command, 237
 - HCL (hardware compatibility list), 126
 - HDLC (High-Level Data Link Control)
 - characteristics of, 14
 - defined, 395
 - HDSL (high bit-rate DSL), 9, 216
 - helper addresses
 - defined, 395
 - IP, 86
 - HFC (Hybrid Fiber/COAX) devices, 232, 233
 - high bit-rate DSL (HDSL), 9, 216
 - High-Level Data Link Control (HDLC)
 - characteristics of, 14
 - defined, 395
 - host addresses, 395
 - hotelling installations, 89
 - http option, 345
 - Hybrid Fiber/COAX (HFC) devices, 232, 233
-
- I**
- I protocols in ISDN, 156
 - IARP (Inverse ARP)
 - defined, 395
 - for DLCI mapping, 258
 - ICMP (Internet Control Message Protocol), 395
 - IDASSN output, 162
 - IDCKRP output, 162
 - IDCKRQ output, 161, 163
 - Identifier field, 173–175, 173
 - idle phase in PVCs, 255
 - IDREM output, 162
 - IDREQ output, 162–163
 - IDSL (ISDN-based DSL), 9
 - ietf option, 259
 - IKE (Internet Key Exchange), 236
 - Inactive connection state in LMI, 258
 - INFOc output, 162
 - Information field
 - in LAPD, 157, 159–160
 - in PPP, 82
 - Information Transfer format, 158
 - ingress in Frame Relay, 253
 - inside global IP addresses in NAT, 328
 - configuring, 338–339
 - overloading, 333–334, 333
 - inside local IP addresses in NAT
 - translating, 332–333, 332
 - working with, 327
 - inside networks in NAT, 327
 - Integrated Routing and Bridging (IRB), 220
 - Integrated Services Digital Network. *See* ISDN (Integrated Services Digital Network)
 - interactive PPP, 83
 - interesting traffic in DDR, 176–177
 - interface addressing options for local devices, 83
 - DHCP lease length, 88–89, 90
 - DHCP operation, 87–88
 - dynamic addressing, 84–87, 84–85, 87
 - interface command, 265
 - interface async16 ppp authentication command, 367
 - interface cable-modem0 command, 239
 - interface dialer command, 185
 - interface Ethernet0 command, 238
 - interface option in custom queuing, 303
 - International Telecommunications Union-Telecommunication (ITU-T) group
 - defined, 396
 - for LMI, 258
 - Internet, 395

- Internet Control Message Protocol (ICMP), 395
- Internet Key Exchange (IKE), 236
- Internet Protocol (IP), 395
- internets, 395
- Internetwork Packet Exchange (IPX) protocol
 - in Cisco 700 platform, 33
 - defined, 396
- internetworking and interface options, **26**
 - asynchronous and analog connections, **26–27**
 - Frame Relay, **28**
 - ISDN, **27–28**
- internetworks, 395
- intruder detection
 - for brute force attacks, 363
 - defined, 395
- Inverse Address Resolution Protocol (Inverse ARP)
 - defined, 395
 - for DLCI mapping, 258
- IP (Internet Protocol), 395
- ip address command
 - in IPSec, 238
 - in ISDN, 170
- IP addresses, **85–87**
 - defined, 395
 - DHCP for, **84–87, 87**
 - lease length in, **88–89, 90**
 - operation of, **87–88**
 - limitations of, 326
 - NAT for. *See* NAT (Network Address Translation)
- IP Control Protocol (IPCP), 396
- ip dhcp database command, 86
- ip dhcp excluded-address low-address command, 86
- ip dhcp-server command, 86
- ip nat inside command, 337, 341
- ip nat inside source list command, 340
 - ip nat inside source static command, 337
- ip nat outside command, 337, 341
- ip nat outside source list command, 341
- ip nat pool command, **338–339**
 - ip nat pool insidepool command, 340
 - ip nat pool outsidepool command, 340
- ip option in queuing, 304
- IP routing in Cisco 700 platform, 33
- ip tcp header-compression command, 98, 312
- IP unnumbered options, 83
- IPCP (IP Control Protocol), 396
- IPSec, **235–236**
 - configuring, **237–239**
 - for VPNs, 240
- IPX (Internetwork Packet Exchange) protocol
 - in Cisco 700 platform, 33
 - defined, 396
- IPXCP (IPX Control Protocol), 396
- IRB (Integrated Routing and Bridging), 220
- ISDN (Integrated Services Digital Network), 5
 - authentication in, 171
 - CHAP, **173–175, 173, 175**
 - PAP, **171–173, 172**
 - Bandwidth on Demand, **190–191**
 - BRI, 5, **150–152, 151**
 - cabling in, 27
 - defined, 390
 - hands-on lab for, **200–203, 200**
 - packet-mode connections, 366
 - call setup and teardown in, **163–166, 164**
 - channelized T-1/E-1, **192–195**
 - characteristics of, **16–22**
 - configuring, **166–167**
 - dialer interface, **169–171, 177**
 - legacy interface, **167–169**

420 ISDN-based DSL (IDSL) – leased lines

DDR in. *See* DDR (dial-on-demand routing)
 defined, 396
 dial backup, 181, 181
 setting up, 181–183
 testing, 183–190
 exam essentials, 195–196
 function groups, 154–155, 154
 hands-on labs, 197
 DDR, 197–200, 198
 PRI and BRI, 200–203, 200
 key terms, 196
 LAPD frames in, 157–160, 157, 159
 Layer 2 negotiation in, 160–163
 line options for, 150–151
 Basic BRI, 151
 BRI, 151–152
 PRI, 153
 ordering, 166–167
 PRI, 5, 150, 153
 cabling in, 27–28
 configuring, 192–194
 defined, 400
 hands-on labs, 200–203, 200
 packet-mode connections, 366
 protocols for, 156–157
 reference points, 155–156, 155
 review questions, 204–207, 209–210
 summary, 195
 written lab, 197, 207–208
 ISDN-based DSL (IDSL), 9, 216
 isdn disconnect interface command, 180
 ISDN interface in Cisco 700 platform, 32
 ITU-T (International Telecommunications Union-Telecommunication) group
 defined, 396
 for LMI, 258

K

key terms
 asynchronous connections, 67

cable modems, 241
 DSL, 223
 Frame Relay, 279
 ISDN, 196
 Microsoft Windows 95/98/2000/XP, 139
 NAT and PAT, 349
 PPP, 111
 queuing and compression, 316
 remote access, 41
 security, 378
 VPNs, 241
 Keypad facility output, 166
 known values in modem connections, 62

L

L1 AT command, 63
 L2TP (Layer 2 Tunneling Protocol), 240
 LAN LED, 38, 38
 LAN activity LED, 37, 37
 LAN collision LED, 37, 37
 LAN RXD LED, 38, 38
 LAN TXD LED, 38, 38
 LAPB (Link Accessed Procedure, Balanced) protocol, 396
 LAPD (Link Access Procedure, Data) protocol
 defined, 396
 frames in, 157–160, 157, 159
 last mile, 13
 latency
 defined, 396
 in NAT, 330
 launching terminal windows, 136–137, 136
 Layer 2 negotiation, 160–163
 Layer 2 Tunneling Protocol (L2TP), 240
 LCP (Link Control Protocol)
 defined, 396
 in PPP, 79
 leased lines, 7
 cable modems, 10–11
 characteristics of, 16–22

- defined, 396
- Digital Subscriber Line, 7–10, 8
- leases in DHCP, 88–89, 90
- LEDs
 - Cisco 766 routers, 38–39, 38
 - Cisco 1600 routers, 37, 37
 - Cisco 3640 routers, 36–37, 36
- Legacy DDR Hub configuration, 175
- Legacy DDR Spoke configuration, 175
- legacy interface in ISDN configuration, 167–169
- Length information
 - in CHAP packets, 173, 173, 175
 - in LAPD, 159
- lifetime command, 238
- limit option, 305
- line command, 64–65
- LINE LED, 38, 38
- Linecode parameter
 - in E-1, 194
 - in PRI, 192
- Link Access Procedure, Data (LAPD)
 - protocol
 - defined, 396
 - frames in, 157–160, 157, 159
- Link Accessed Procedure, Balanced (LAPB)
 - protocol, 396
- link compression
 - defined, 396
 - working with, 312–313
- Link Control Protocol (LCP)
 - defined, 396
 - in PPP, 79
- list keyword, 304
- llc2 option, 304
- LLQ (low latency queuing), 309
- LMI (Local Management Interface)
 - defined, 396
 - for Frame Relay, 258–259, 259
- load-threshold command, 178
- local devices, interface addressing options
 - for, 83–89, 84–85, 87, 90

- local IP addresses in NAT, 327–328
- local loops, 396
- Local Management Interface (LMI)
 - defined, 396
 - for Frame Relay, 258–259, 259
- local significance in virtual circuits, 254
- Local Termination (LT), 155
- locking DTE speed, 135–136, 136
- log files for dial-up clients, 131–133
- Log On to Network option, 131
- login command
 - for asynchronous routers, 64
 - for character-mode connections, 365
- low latency queuing (LLQ), 309
- lowest-custom option, 303
- LT (Local Termination), 155
- lt keyword, 304
- LZW algorithm
 - for compression, 57
 - defined, 396

M

- MAC addresses, 396
- Make New Connection Wizard, 125–127, 125–127
- manageability in WAN protocol selection, 19–20
- management in Cisco 700 platform, 33
- Mandatory and Optional Information
 - Elements field, 160
- manual modem configuration, 62–65
- map-class frame-relay command, 275
- mapping
 - address, 388
 - DLCIs, 256–258, 257
 - in NAT, 329
- match address command, 238
- match-host parameter, 339
- max active number, 298
- max total number, 298

422 maximum rate – nasi command

- maximum rate, 397
 - maximum transmission units (MTUs), 397
 - media converters, 54
 - memory for compression, 313
 - Message field, 175
 - Message Type information, 160
 - Microsoft Point-to-Point Compression (MPPC), 98, 311
 - Microsoft Windows 95/98/2000/XP, 121
 - dial-up networking. *See* dial-up networking
 - exam essentials, 138–139
 - key terms, 139
 - launching terminal windows, 136–137, 136
 - locking DTE speed, 135–136, 136
 - review questions, 140–145
 - summary, 137–138
 - verifying dial-Up connections, 137, 137
 - written lab, 139, 143
 - MMP (Multichassis Multilink Protocol)
 - defined, 397
 - purpose of, 100, 101
 - MO AT command, 63
 - modem command, 64
 - modem autoconfigure discovery
 - command, 61
 - modem autoconfigure type command, 59–60
 - modem compression, 313
 - modem eliminators, 397
 - modem input command, 62
 - Modem Properties dialog box, 136, 136
 - modemcap database, 59, 397
 - modemcap edit command, 60–61
 - modems
 - for asynchronous communication, 50–53, 51
 - configuring, 58–65
 - modulation standards for, 55–57
 - signaling and cabling, 53
 - cable. *See* cable modems
 - defined, 397
 - modular interface routers, 25
 - modulation
 - defined, 397
 - standards for, 55–56
 - data compression, 56–57
 - error correction, 57
 - monitoring PAT, 347–348
 - MP (Multilink Protocol), 100
 - MP (Multilink Protocol) bonding
 - in Cisco 700 platform, 33
 - defined, 397
 - MPLS (Multi Protocol Label Switching)
 - for VPNs, 240
 - for WAN services, 22
 - MPP (Multilink Multipoint Protocol), 134
 - MPPC (Microsoft Point-to-Point Compression), 98, 311
 - MTUs (maximum transmission units), 397
 - Multi Protocol Label Switching (MPLS)
 - for VPNs, 240
 - for WAN services, 22
 - Multichassis Multilink Protocol (MMP)
 - defined, 397
 - purpose of, 100, 101
 - multilink in PPP, 99–101, 99–101
 - Multilink Multipoint Protocol (MPP), 134
 - Multilink Protocol (MP), 100
 - Multilink Protocol (MP) bonding
 - in Cisco 700 platform, 33
 - defined, 397
 - Multilink tab, 134, 135
 - multinational support, 33
 - multipoint interfaces, 263–266, 264
-
- N**
- NAK (negative acknowledgments), 397
 - Name field in CHAP packets, 174
 - nasi command, 365

NAT (Network Address Translation),
 326–327
 advantages of, 329
 clearing translation entries in, 343
 configuring, 336–341
 defined, 397
 disadvantages of, 330
 exam essentials, 348–349
 hands-on lab, 350–351
 IPSec with, 236
 key terms, 349
 operation of, 328–329, 328
 overlapping networks in, 335–336
 overloading inside global addresses in,
 333–334, 333
 review questions, 352–355, 357–358
 summary, 348
 TCP load distribution in, 334–335, 335
 terminology, 327–328
 traffic types in, 330–331
 translating inside local addresses in,
 332–333, 332
 troubleshooting, 342–343
 verifying, 341–342
 written lab, 349–350, 356

NBAR (Network-Based Application
 Recognition), 308

NCPs (Network Control Protocols), 79

negative acknowledgments (NAK), 397

Network accounting type, 374

Network Activity LED, 36, 36

Network Address Translation. *See* NAT
 (Network Address Translation)

network addresses, 397

Network-Based Application Recognition
 (NBAR), 308

Network Control Protocols (NCPs), 79

network installations, 35
 central site, 35–37, 36
 remote branch, 37, 37
 telecommuter, 38–39, 38

network interface cards (NICs), 398

Network Layer, 397

Network Termination type 1 (NT1)
 in BRI, 154
 defined, 398

Network Termination type 2 (NT2)
 in BRI, 155
 defined, 398

Next Level Communications systems, 8

NICs (network interface cards), 398

no async mode command, 83

no ip dhcp conflict logging command, 86

no ip forward-protocol command, 86

no modemcap edit command, 61

nonvolatile RAM (NVRAM), 398

NRN server type, 129

NT1 (Network Termination type 1)
 in BRI, 154
 defined, 398

NT1 LED, 38, 38

NT2 (Network Termination type 2)
 in BRI, 155
 defined, 398

NTT switch types, 152

NVRAM (nonvolatile RAM), 398

O

OAM (Operation, Administration, and
 Management) cells, 219

OC (Optical Carrier) protocols, 398

octets, 398

off option in PAT, 345

one-time challenge tokens
 defined, 398
 for passwords, 362

ones density signaling, 398

Operation, Administration, and
 Management (OAM) cells, 219

Optical Carrier (OC) protocols, 398

Options tab for terminal windows,
 136–137, 136

424 OSI Reference Model – Physical Layer

OSI Reference Model, 398
 out-of-band signaling, 398
 outside global IP addresses in NAT, 328
 outside local IP addresses in NAT, 328
 outside networks in NAT, 327
 outsourcing, 24, 34
 overlapping address translation,
 340–341
 overlapping networks in NAT operations,
 335–336
 overloading inside global addresses,
 333–334, 333
 oversubscription
 in DSL, 214–215
 in Frame Relay, 262

P

packet assembler/disassembler (PAD), 399
 Packet Internet groper (ping) tool
 defined, 399
 for ISDN, 180
 Packet Layer Protocol (PLP), 399
 packet-mode connections
 commands for, 366–367
 defined, 398
 Packet Switch Exchange (PSE), 400
 packet switches, 399
 packet switching, 399
 Packet-Switching Networks (PSNs), 400
 packet switching protocols, 252
 packets
 Authenticate-Request, 172–173, 172
 CHAP, 173–175, 173
 defined, 398
 PAP, 171–172
 PAD (packet assembler/disassembler), 399
 PAP (Password Authentication Protocol)
 defined, 399
 in ISDN, 171–173, 172
 in PPP, 81, 91–92, 91
 pap chap keyword, 92
 parity checking, 399
 passive parameter, 312
 Passwd-Length field, 172
 Password Authentication Protocol (PAP)
 defined, 399
 in ISDN, 171–173, 172
 in PPP, 81, 91–92, 91
 password command, 64
 Password field, 172
 PAT (Port Address Translation), 344
 in Cisco 700 platform, 33
 configuring, 345–347
 defined, 399
 disadvantages of, 344–345
 exam essentials, 348–349
 hands-on lab, 350–351
 key terms, 349
 monitoring, 347–348
 review questions, 352–355, 357–358
 summary, 348
 written lab, 349–350, 356
 patches, 124
 payload compression, 312, 399
 PC Card LEDs, 36, 36
 PCM (Pulse Code Modulation), 149
 PCMCIA LEDs, 36, 36
 pd output, 165
 PDNs (Public Data Networks), 399
 peer default ip address command, 86
 Peer-ID field, 172
 Peer-ID Length field, 172
 per-interface compression, 312
 per-virtual-circuit compression, 312
 performance of Frame Relay,
 260–262, 261
 Permanent Virtual Circuits (PVCs)
 defined, 400
 in Frame relay, 6–7, 255
 PH1 LED, 38, 38
 PH2 LED, 38, 38
 Physical Layer, 399

- physical-layer async command, 65
- ping (Packet Internet groper) tool
 - defined, 399
 - for ISDN, 180
- plain old telephone service (POTS)
 - defined, 400
 - operation of, 149
- PLP (Packet Layer Protocol), 399
- point-to-point interfaces, 263–266, 264
- Point-to-Point Protocol. *See* PPP (Point-to-Point Protocol)
- policies
 - queuing, 293, 293
 - security, 362
- Port Address Translation. *See* PAT (Port Address Translation)
- port density, 29
- port option, 345
- port types, 29
- ports in Cisco 700 platform, 32
- POTS (plain old telephone service)
 - defined, 400
 - operation of, 149
- PPP (Point-to-Point Protocol), 15, 78
 - architecture, 78–79, 79
 - Address field, 80
 - Control field, 80
 - Flag field, 79
 - Frame Check Sequence field, 82
 - Information field, 82
 - Protocol field, 80–81
 - callbacks, 93–97, 400
 - CHAP authentication in, 92–93, 92–93
 - compression, 97–99
 - configuring access servers, 82
 - for dedicated and interactive PPP, 83
 - for local devices, 83–89, 84–85, 87, 90
 - defined, 400
 - exam essentials, 110–111
 - hands-on labs, 112–113
 - key terms, 111
 - multilink in, 99–101, 99–101
 - review questions, 114–119
 - summary, 109–110
 - verifying and troubleshooting, 101
 - debug ppp authentication command, 101–102
 - debug ppp negotiation command, 102–106
 - debug ppp packet command, 106–109
 - written lab, 111–112, 117
- ppp authentication command, 91–92
- ppp callback accept command, 94
- ppp callback request command, 94
- ppp multilink command, 100, 179
- PPP server type, 129
- predictor option, 98
- Predictor technique
 - for compress, 98
 - defined, 400
 - for link compression, 312
- prefix-length command, 339
- Presentation Layer, 400
- PRI (Primary Rate Interface), 5, 150, 153
 - cabling in, 27–28
 - configuring, 192–194
 - defined, 400
 - hands-on lab, 200–203, 200
 - packet-mode connections, 366
- pri-group timeslots command, 192–194
- PRIMARY switch types, 153
- priorities
 - in priority queuing, 298, 298
 - in Weighted Fair Queuing, 295, 295, 297
- priority-group command, 299–300
- priority-list list-number default command, 299
- priority-list list-number interface interface-type command, 299

426 priority-list list-number protocol command – reliability

priority-list list-number protocol
 command, 299

priority-list list-number queue-limit
 command, 299

priority option, 297

priority queuing, 292
 configuring, 299–300
 defined, 400
 priorities in, 298, 298
 verifying, 301

process switching, 400

profiles, virtual, 376–377

propagation delay, 400

Protocol field, 80–81

Protocol Discriminator field, 159

protocols
 in custom queuing, 303
 defined, 400
 for ISDN, 156–157

PSE (Packet Switch Exchange), 400

PSNs (Packet-Switching Networks), 400

PSTNs (Public Switched Telephone
 Networks), 400

Public Data Networks (PDNs), 399

Pulse Code Modulation (PCM), 149

PVCs (Permanent Virtual Circuits)
 defined, 400
 in Frame relay, 6–7, 255

Q

Q protocols in ISDN, 156

&Q6 AT command, 63

QoS (quality of service)
 defined, 400
 in WAN protocol selection, 21

queue-list commands, 303, 306–307

queue option, 303, 305

queues, 401

queuing, 292–293
 Class-Based Weighted Fair Queuing, 309

Committed Access Rate, 310

custom queuing, 301–307, 302
 defined, 401
 exam essentials, 315–316
 in Frame Relay, 274
 hands-on lab, 317–318, 317
 key terms, 316
 low latency queuing, 309
 options, 294, 294
 policies for, 293, 293
 priority queuing, 298–301, 298
 review questions, 319–324
 summary, 314–315
 traffic prioritization in, 293
 Weighted Fair Queuing, 295–298, 295
 written lab, 316, 322

R

R reference points, 401

RADIUS (Remote Access Dial-In User
 Service) protocol
 in authentication, 361
 defined, 401

RAM (random access memory), 401

RARP (Reverse Address Resolution
 Protocol), 401

rate queues, 401

RD LED, 38, 38

read-only memory (ROM), 401

recompressed option, 98

Record a Log File for This Connection
 option, 131

reference points
 defined, 401
 ISDN, 155–156, 155

RELEASE messages, 164

RELEASE COMPLETE messages, 164

reliability
 defined, 401
 in WAN protocol selection, 21–22

- reloading, 401
- remote access, 2–3
 - cabling and assembling WANs, 26
 - company site equipment
 - identification, 28
 - internetworking and interface
 - options, 26–28
 - verifying network installations,
 - 35–39, 36–38
 - Cisco products, 23
 - fixed interface routers, 24–25
 - modular interface routers, 25
 - selection tools for, 25–26
 - defined, 401
 - exam essentials, 39–40
 - key terms, 41
 - review questions, 43–48
 - summary, 39
 - WANs in. *See* WANs (wide area networks)
 - written lab, 42, 46
- Remote Access Dial-In User Service (RADIUS) protocol
 - in authentication, 361
 - defined, 401
- remote branch equipment
 - platforms for, 31
 - verifying, 37, 37
- remote control, dial-up networking
 - for, 122
- Request To Send (RTS) signal
 - defined, 402
 - in DTE to DCE signaling, 54
- Requests for Comments (RFCs)
 - defined, 401
 - for PPP, 78–79
- Require Data Encryption option, 131
- Require Encrypted Password option, 131
- reservable-queues parameter, 296
- Resource accounting type, 374
- Reverse Address Resolution Protocol (RARP), 401
- reverse Telnet, 401
- review questions
 - asynchronous connections, 71–76
 - cable modems, 244–247, 250
 - DSL, 224–227, 229
 - Frame Relay, 283–286, 289–290
 - ISDN, 204–207, 209–210
 - Microsoft Windows 95/98/2000/XP,
 - 140–145
 - NAT and PAT, 352–355, 357–358
 - PPP, 114–119
 - queuing and compression, 319–324
 - remote access, 43–48
 - security, 380–383, 385–386
 - VPNs, 244–247, 250
- RFCs (Requests for Comments)
 - defined, 401
 - for PPP, 78–79
- RI (Ring Indication) wire, 54
- RIP (Routing Information Protocol), 34
- RJ connectors, 401
- robbed bit signaling, 401
- ROM (read-only memory), 401
- router access modes, 365
 - character-mode connections,
 - 365–366
 - packet-mode connections, 366–367
- routers
 - authentication configuration for, 369
 - defined, 401–402
 - for DSL, 217–218
 - in Frame Relay congestion control,
 - 262–263
- routing, 402
- Routing Information Protocol (RIP), 34
- RPS LED, 36, 36
- RRx output, 162
- RTS (Request To Send) signal, 402
 - defined, 402
 - in DTE to DCE signaling, 54
- RX output, 161, 165
- RXD wire, 54

428 S reference points – show frame-relay pvc command**S**

- S reference points
 - defined, 402
 - in ISDN, 156
- S/T interfaces, 156
- SABME output, 161
- SAPI (Service Access Point Identifier) field, 157–158
- sapi output, 161
- Scripting tab for dial-up clients, 134, 134 scripts, 402
- SDH (Synchronous Digital Hierarchy), 151
- SDSL (symmetric DSL), 9, 216
- secondary command, 169
- Secure Sockets Layer (SSL), 240
- security, 360
 - AAA, 360, 363–364, 367–368
 - accounting in, 365, 374–376
 - authentication in, 364, 368–370
 - authorization in, 364–365, 370–373
 - defined, 388
 - access control solutions, 361–363
 - exam essentials, 377–378
 - hands-on lab, 379
 - IPSec, 235–236
 - configuring, 237–239
 - for VPNs, 240
 - key terms, 378
 - review questions, 380–383, 385–386
 - router access modes, 365–367
 - summary, 377
 - terminology for, 360–361
 - virtual profiles for, 376–377
 - in WAN protocol selection, 22–23
 - written lab, 378–379, 384
- security policies, 362, 402
- security servers, 361–362, 402
- selection tools for Cisco products, 25–26
- Serial command, 169
- Serial Line Internet Protocol (SLIP)
 - defined, 402
 - purpose of, 15
- serial packet-mode connections, 366
- Server Types tab for dial-up clients, 128–133, 129–130
- servers
 - defined, 402
 - DHCP, 88
- Service Access Point Identifier (SAPI) field, 157–158
- service dhcp command, 87
- service packs, 124
- Service Profile Identifiers (SPIDs)
 - defined, 403
 - in ISDN, 151
- Session Layer, 402
- set authentication enable command, 370
- set authentication login command, 370
- set-based routers and switches, 402
- set ip pat on command, 345
- set ip pat porthandler command, 345
- set peer command, 238
- set tacacs attempts command, 369
- set tacacs directedrequest command, 370
- set tacacs key command, 370
- set tacacs server command, 369
- set tacacs timeout command, 370
- set transform-set command, 238
- SETUP messages, 164
- SETUP output, 165
- SF (Super Frame), 402
- show compress command, 314
- show config command, 370
- show dialer command, 180, 186
- show frame-relay lmi command, 269
- show frame-relay map command, 268–269
- show frame-relay pvc command, 267–268, 276

- show frame-relay route command, 272
- show interface command, 266–267
- show ip nat statistics command, 342
- show ip nat translation command, 341
- show ip nat translation verbose command, 342
- show ip pat command, 347–348
- show ip route command, 180
- show isdn active command, 180
- show isdn status command, 180, 182–183, 185
- show line command, 137
- show modemcap command, 59–60
- show process cpu command, 98
- show queue command, 297
- show queueing command, 297
- show queueing priority command, 301
- show running-config command, 276
- signaling, 53–55
- Simple Mail Transfer Protocol (SMTP), 403
- simple translation entries in NAT, 328
- site equipment identification, 28
 - central site, 29–30
 - remote branch, 31
 - telecommuter, 32
- sliding window method, 402
- SLIP (Serial Line Internet Protocol)
 - defined, 402
 - purpose of, 15
- SLIP server type, 130
- slow paths, 342
- small offices/home offices (SOHOs), 148–149, 403
- SMTP (Simple Mail Transfer Protocol), 403
- smtp option in PAT, 345
- snapshot routing, 34
- sniffers, 343
- SO=1 AT command, 63
- sockets, 403
- SOHOs (small offices/home offices), 148–149, 403
- SONET (Synchronous Optical Network)
 - standard
 - defined, 403
 - for fiber optics, 151
 - source list list-number interface
 - command, 339
 - speed command, 64
 - SPIDs (Service Profile Identifiers)
 - defined, 403
 - in ISDN, 151
 - split horizon
 - defined, 403
 - in Frame Relay, 264, 264
 - splitterless DSL, 215
 - splitters in DSL, 214–215
 - SSL (Secure Sockets Layer), 240
 - Stac option, 98
 - Stac technique
 - for compress, 98
 - defined, 403
 - for link compression, 312
 - standard IP access lists, 403
 - Stat-TDM (statistical time-division multiplexing), 255
 - static addressing options, 83
 - static NAT, 337
 - static routes, 403
 - static translation in NAT, 329
 - statistical multiplexing, 403
 - statistical time-division multiplexing (Stat-TDM), 255
 - stopbits command, 64
 - stun option, 303
 - subchannels, 403
 - subinterfaces
 - defined, 403
 - in Frame Relay, 264, 264
 - hands-on lab, 280–281
 - subnet addresses, 403

430 subnet masks – telecommuter equipment

- subnet masks, 403
 - subnetworks, 404
 - Super Frame (SF), 402
 - Supervisory format, 158–159
 - supported NAT traffic types, 330–331
 - SVCs (Switched Virtual Circuits)
 - defined, 404
 - in Frame relay, 7, 254–255
 - switch options
 - BRI, 152
 - PRI, 153
 - switches
 - defined, 404
 - in Frame Relay, 261–262, 270–273, 271
 - symmetric DSL (SDSL), 9, 216
 - Synchronous Digital Hierarchy (SDH), 151
 - Synchronous Optical Network (SONET)
 - standard
 - defined, 403
 - for fiber optics, 151
 - synchronous transmissions, 404
 - System accounting type, 374
 - System LED, 36, 36
 - System OK LED, 37, 37
 - System PWR LED, 37, 37
-
- T**
- T-1 circuits, 27, 153
 - configuring, 192–194
 - defined, 404
 - T-3 WANs, 404
 - T reference points
 - defined, 404
 - in ISDN, 156
 - TACACS+ (Enhanced Terminal Access Controller Access Control System) protocol
 - in authentication, 361
 - configuration file, 371–373
 - configuring, 379
 - defined, 404
 - tacacs-server host command, 368–369
 - tacacs-server key command, 368–369
 - TAs (Terminal Adapters)
 - in BRI, 155
 - defined, 405
 - TCP (Transmission Control Protocol)
 - defined, 404
 - in NAT, 329
 - TCP header compression
 - defined, 404
 - operation of, 311–312
 - TCP/IP (Transmission Control Protocol/Internet Protocol), 404
 - TCP/IP Properties dialog box, 85–86, 85
 - TCP/IP Settings dialog box, 84, 84
 - tcp keyword, 304
 - TCP load distribution
 - configuring, 338–339
 - in NAT, 334–335, 335
 - TDM (time division multiplexing)
 - defined, 404
 - in Frame Relay, 255
 - with modems, 52
 - in POTS, 149
 - TE (Terminal Equipment) devices, 404
 - TE1 (Terminal Equipment 1) devices
 - in BRI, 154
 - defined, 405
 - TE2 (Terminal Equipment 2) devices
 - in BRI, 154
 - defined, 405
 - TEI (Terminal Endpoint Identifier)
 - field, 158
 - telcos, 405
 - telecommuter equipment, 32
 - Cisco 700 series, 32
 - Cisco 800 series, 34
 - Cisco 1000 series, 35
 - verifying, 38–39, 38

- telephone service support, 34
 - telnet command, 180
 - telnet option, 345
 - Telnet protocol, 405
 - Terminal Access Controller Access Control System (TACACS+), protocol
 - in authentication, 361
 - configuration file, 371–373
 - configuring, 379
 - defined, 404
 - Terminal Adapters (TAs)
 - in BRI, 155
 - defined, 405
 - terminal emulation, 405
 - Terminal Endpoint Identifier (TEI) field, 158
 - Terminal Endpoints (TEs), 160
 - Terminal Equipment (TE) devices, 404
 - Terminal Equipment 1 (TE1) devices
 - in BRI, 154
 - defined, 405
 - Terminal Equipment 2 (TE2) devices
 - in BRI, 154
 - defined, 405
 - terminal windows, launching, 136–137, 136
 - TEs (Terminal Endpoints), 160
 - testing dial backups, 183–190
 - TFTP (Trivial File Transfer Protocol), 405
 - Thinnet networks
 - and cable modems, 148
 - defined, 405
 - time division multiplexing (TDM)
 - defined, 404
 - in Frame Relay, 255
 - with modems, 52
 - in POTS, 149
 - toll networks, 405
 - TOS (Type of Service), 309
 - trace command, 405
 - traffic prioritization, 293
 - traffic shaping in Frame Relay, 274–277
 - defined, 405
 - hands-on labs, 282
 - traffic types in NAT, 330–331
 - translating inside local addresses, 332–333, 332
 - Transmission Control Protocol (TCP)
 - defined, 404
 - in NAT, 329
 - Transmission Control Protocol/Internet Protocol (TCP/IP), 404
 - transport input command, 64
 - transport input all command, 62
 - Transport Layer, 405
 - Transport mode in IPSec, 236
 - Triple Data Encryption Standard (3DES), 236
 - Trivial File Transfer Protocol (TFTP), 405
 - troubleshooting, 342
 - asynchronous modem connections, 61–62
 - DSL, 220–221
 - NAT, 342–343
 - PPP, 101
 - debug ppp authentication command, 101–102
 - debug ppp negotiation command, 102–106
 - debug ppp packet command, 106–109
 - Tunnel mode in IPSec, 236
 - TX output, 161, 165
 - TXD wire, 54
 - Type of Service (TOS), 309
-
- ## U
- U reference points
 - defined, 405
 - in ISDN, 156

432 UAF output – VPNs (virtual private networks)

- UAF output, 162
 - UART (Universal Asynchronous Receiver/Transmitter) chips
 - characteristics of, 53
 - defined, 405
 - UBR (unspecified bit rate), 219
 - UDP (User Datagram Protocol), 405–406
 - udp keyword in queuing, 304
 - Universal Asynchronous Receiver Transmitter (UART) chips
 - characteristics of, 53
 - defined, 405
 - Unnumbered format in LAPD, 159
 - unnumbered frames, 406
 - unshielded twisted-pair (UTP) wiring, 406
 - unspecified bit rate (UBR), 219
 - unsupported NAT traffic types, 331
 - upstream traffic with cable modems, 10
 - User Datagram Protocol (UDP), 405–406
 - username command, 366
 - username name password command, 92–93, 174
 - UTP (unshielded twisted-pair) wiring, 406
-
- V**
- V reference points, 156
 - Value field, 174
 - Value-Size field, 174
 - variable-length subnet masks (VLSMs), 406
 - VCs (virtual circuits)
 - defined, 406
 - in Frame Relay, 253–255, 254
 - for VPNs, 239
 - VDSL (Very-High Data Rate DSL), 9, 216
 - verifying
 - asynchronous modem connections, 61–62
 - dial-up connections, 137, 137
 - Frame Relay, 266–270
 - ISDN operations, 180
 - NAT, 341–342
 - network installations, 35
 - central site, 35–37, 36
 - remote branch, 37, 37
 - telecommuter, 38–39, 38
 - PPP, 101
 - debug ppp authentication command, 101–102
 - debug ppp negotiation command, 102–106
 - debug ppp packet command, 106–109
 - priority queuing, 301
 - Weighted Fair Queuing, 297–298
 - Very-High Data Rate DSL (VDSL), 9, 216
 - virtual circuits (VCs)
 - defined, 406
 - in Frame Relay, 253–255, 254
 - for VPNs, 239
 - virtual dialer interfaces, 185
 - Virtual Path Identifiers (VPIs), 219
 - virtual private networks. *See* VPNs (virtual private networks)
 - virtual profiles, 376–377
 - VLSMs (variable-length subnet masks), 406
 - VN3 switch types
 - in BRI, 152
 - in PRI, 153
 - VPIs (Virtual Path Identifiers), 219
 - VPNs (virtual private networks), 235
 - defined, 406
 - for DSL, 219
 - encryption with, 53

exam essentials, 240–241
 hands-on lab, 242–243, 248–249
 IPSec for, 235–239
 key terms, 241
 review questions, 244–247, 250
 summary, 240–241
 technologies for, 239–240
 for WANs, 23
 written lab, 242, 247

W

WANs (wide area networks)

connection types in, 3
 asynchronous dial-Up, 4
 ATM, 11
 Frame Relay, 6
 ISDN, 5
 leased lines, 7–11, 8
 summary, 13
 wireless and cellular, 11–13
 X.25, 5
 defined, 406
 encapsulation protocols for, 14
 ATM, 14
 Frame Relay, 16
 HDLC, 14
 PPP, 15
 SLIP, 15
 X.25, 15–16
 protocol selection factors in, 16–17
 applications in use, 20–21
 availability, 17
 bandwidth, 17–18
 cost, 18–19
 manageability, 19–20
 quality of service, 21
 reliability, 21–22
 security, 22–23
 in remote access, 2

WFQ (Weighted Fair Queuing),
 292, 295
 configuring, 296
 conversations in, 295–296
 defined, 406
 priorities in, 295, 295
 verifying, 297–298
 WIC ACT LED, 37, 37
 WIC CD LED, 37, 37
 wide area networks. *See* WANs (wide area networks)
 wildcards, 406
 windowing, 406
 Windows for Workgroups server type, 130
 Windows NT server type, 130
 Windows operating systems. *See* Microsoft Windows 95/98/2000/XP
 wins option, 345
 wireless WAN connections, 11–13
 written labs
 asynchronous connections, 68, 74
 cable modems, 242, 247
 DSL, 223, 228
 Frame Relay, 279–280, 287–288
 ISDN, 197, 207–208
 Microsoft Windows 95/98/2000/XP, 139, 143
 NAT and PAT, 349–350, 356
 PPP, 111–112, 117
 queuing and compression, 316, 322
 remote access, 42, 46
 security, 378–379, 384
 VPNs, 242, 247

X

X.25 protocol, 5, 15–16
 characteristics of, 16–22
 defined, 406
 X.25 standard, 406